

MPE Calculation page

MPE Calculator	Garmin	Test Number	100224
MPE uses EIRP for calculation. EIRP is based on TX power added to the antenna gain in dBi.			
	dBi = dB gain compared to an isotropic radiator.		
	S = power density in mW/cm ²	Antenna Gain (dBi)	1
	Output Power	dBi to dBd	2.17
Tx Frequency (MHz)	2441	(Watts)	0.000330
		Antenna minus cable (dBi)	1.00
Cable Loss (dB)	0.0	(dBm)	-4.81
	Calculated ERP (mw)		Radiated (EIRP) dBm
	0.252		-3.810
	Calculated EIRP (mw)		Radiated (ERP) dBm
	0.416		-5.980
Occupational Limit	5.00000	mW/cm²	
General Public Limit	1.00000	mW/cm²	
<div style="border: 1px solid black; padding: 5px; width: fit-content;"> Power density (S) = EIRP ----- = mW/cm² 4 p r² [r (cm), EIRP (mW)] </div>			
FCC radio frequency radiation exposure limits per 1.1310			
Frequency (MHz)	Occupational Limit	Public Limit	
300-1,500	f/300	f/1500	
1,500-100,000	5	1	
FCC radio frequency radiation exposure limits per 1.1310			
Frequency (MHz)	Occupational Limit @ Tx Freq (mW/cm ²)	Public Limit @ Tx Freq (mW/cm ²)	
300-1,500	8.136666667	1.627333333	
1,500-100,000	5	1	
EIRP	Distance	Distance	S
milliwatts	cm	inches	mW/cm ²
0.416	50.00	19.69	0.00001
0.416	40.00	15.75	0.00002
0.416	30.00	11.81	0.00004
0.416	20.00	7.87	0.00008
0.416	10.00	3.94	0.00033
0.416	5.00	1.97	0.00132
0.416	4.00	1.57	0.00207
0.416	3.00	1.18	0.00368
0.416	2.00	0.79	0.00827
0.416	1.00	0.39	0.03310
0.416	0.50	0.20	0.13239
0.416	0.32	0.13	0.32321
0.416	0.20	0.08	0.82743
0.416	0.15	0.06	1.47098
0.416	0.10	0.04	3.30971
Frequency (MHz)	Occupational Limit minimum Distance (cm / in)	Public Limit minimum distance (cm / in)	
300-1,500	N/A	N/A	
1,500-10,000	0.1 / 0.04	0.2 / 0.08	