

Application Submittal Report For FCC And Industry Canada Grant Of Certification

FOR

Model: 01102458
2402 - 2480 MHz Transmitter

FCC ID: IPH-01787
IC: 1792A-01787

FOR

GARMIN INTERNATIONAL, INC.

1200 East 151st Street
Olathe, KS 66062

Test Report Number: 101118A

Authorized Signatory: *Scot D. Rogers*
Scot D. Rogers



NVLAP Lab Code 200087-0



ROGERS LABS, INC.

4405 West 259th Terrace
Louisburg, KS 66053
Phone / Fax (913) 837-3214

Engineering Test Report For Grant Of Certification Application Submittal

CFR47, Part 15C - Intentional Radiators Paragraph 15.249,
Industry Canada, RSS-210
Low Power Transmitter

For

Garmin International, Inc.

1200 East 151st Street
Olathe, KS 66062
Phone: (913) 397-8200
Mr. Van Ruggles
Director of Quality Assurance

Model: 01102458

Frequency 2402 - 2480 MHz
FCC ID#: IPH-01787
IC: 1792A-01787

Test Date: November 18, 2010

Certifying Engineer: 
Scot D. Rogers
Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Telephone: (913) 837-3214

This report shall not be reproduced except in full, without the written approval of the laboratory. This report must not be used by the client to claim product endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Garmin International, Inc.
Model: 01102458
Test #: 101118A SN: 3806879589b
Test to: FCC Parts 2 and 15.249, RSS-210
File: 01102458 TstRpt 101118A

FCC ID#: IPH-01787
IC: 1792A-01787
Date: December 3, 2010
Page 2 of 42



Table of Contents

TABLE OF CONTENTS..... 3

FORWARD 5

APPLICABLE STANDARDS & PROCEDURES 5

OPINION / INTERPRETATION OF RESULTS 5

APPLICATION FOR CERTIFICATION..... 6

STATEMENT OF MODIFICATIONS AND DEVIATIONS 6

EQUIPMENT TESTED..... 7

EQUIPMENT FUNCTION AND TESTING PROCEDURES 7

 AC Line Conducted Emission Test Procedure8

 Radiated Emission Test Procedure.....8

EQUIPMENT AND CABLE CONFIGURATIONS 8

 Configurations for the 01102458.....8

ENVIRONMENTAL CONDITIONS..... 10

UNITS OF MEASUREMENTS 10

TEST SITE LOCATIONS 10

LIST OF TEST EQUIPMENT 11

GENERAL EMISSIONS (UNINTENTIONAL RADIATORS) 12

 AC Line Conducted EMI Procedure12

 Figure One AC Line Conducted emissions of EUT line 1 (EUT AC Adapter).....13

 Figure Two AC Line Conducted emissions of EUT line 2 (EUT AC Adapter)13

 Figure Three AC Line Conducted emissions of EUT line 1 (EUT USB CPU)14

 Figure Four AC Line Conducted emissions of EUT line 2 (EUT USB CPU).....14

 Data AC Line Conducted Emissions15

Summary of Results for AC Line Conducted Emissions16

Radiated EMI17

 Figure Five Plot of General Radiated Emissions18

 Figure Six Plot of General Radiated Emissions.....18

 Figure Seven Plot of General Radiated Emissions19

 Figure Eight Plot of General Radiated Emissions19

 Figure Nine Plot of General Radiated Emissions20

 Figure Ten Plot of General Radiated Emissions.....20

 Figure Eleven Plot of General Radiated Emissions.....21

General Radiated Emissions Data from EUT21

Summary of Results for Radiated Emissions.....21



INTENTIONAL RADIATORS EMISSIONS 22

Antenna Requirements22

Restricted Bands of Operation.....22

 Radiated Emissions Data in Restricted Bands23

Summary of Results for Radiated Emissions in Restricted Bands23

Operation in the Band 2402 - 2480 MHz.....24

 Figure Twelve Plot of Occupied Bandwidth (Low channel)25

 Figure Thirteen Plot of Occupied Bandwidth (Middle channel)25

 Figure Fourteen Plot of Occupied Bandwidth (High channel)26

 Figure Fifteen Plot of Operation across frequency band26

 Figure Sixteen Plot of Lower Frequency Band Edge27

 Figure Seventeen Plot of Higher Frequency Band Edge27

Transmitter Emissions Data.....28

 Transmitter Antenna Port Conducted Emissions Data28

 Transmitter Radiated Emissions28

Summary of Results for Transmitter Radiated Emissions29

RECEIVER SPURIOUS EMISSIONS 29

 Figure Eighteen Receiver Temporary Antenna Port Conducted Emissions30

 Figure Nineteen Receiver Temporary Antenna Port Conducted Emissions30

 Figure Twenty Receiver Temporary Antenna Port Conducted Emissions31

 Figure Twenty-one Receiver Temporary Antenna Port Conducted Emissions31

 Figure Twenty-two Receiver Temporary Antenna Port Conducted Emissions32

 Figure Twenty-three Receiver Temporary Antenna Port Conducted Emissions32

 Figure Twenty-four Receiver Temporary Antenna Port Conducted Emissions33

 Figure Twenty-five Receiver Temporary Antenna Port Conducted Emissions.....33

Receiver Antenna Conducted Emissions Data (Sample 2 temporary antenna port)34

Receiver Radiated Emissions Data34

Summary of Results for Receiver Emissions35

ANNEX..... 36

Annex A Measurement Uncertainty Calculations.....37

Annex B Rogers Labs Test Equipment List.....39

Annex C Rogers Qualifications40

Annex D FCC Test Site Registration Letter41

Annex E Industry Canada Test Site Registration Letter.....42



Forward

The following information is submitted for consideration in obtaining Grant of Certification for a license exempt low power intentional radiator operating under CFR47 Paragraph 15.249 and Industry Canada Spectrum Management and Telecommunications Radio Standard Specification RSS-210, Issue 8.

Name of Applicant: Garmin International, Inc.
1200 East 151st Street
Olathe, KS 66062

Model: 01102458 Frequency Range: 2402 - 2480 MHz
FCC I.D.: IPH-01787 IC: 1792A-01787

Operating Power: Peak emission of 97.4 dB μ V/m and average emission of 74.8 dB μ V/m
(3 meter radiated measurement), 99% Occupied Bandwidth 937.5 kHz,
Receiver worst-case emission 32.3 dB μ V/m

Applicable Standards & Procedures

In accordance with the Federal Communications Code of Federal Regulations, dated October 1, 2009, Part 2, Subpart J, Paragraphs 2.907, 2.911, 2.913, 2.925, 2.926, 2.1031 through 2.1057, and applicable parts of paragraph 15, Part 15C Paragraph 15.249, and Industry Canada Spectrum Management and Telecommunications Radio Standard Specification RSS-210, Issue 8 the following information is submitted. Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in the ANSI 63.4-2009, RSS-210, and appropriate FCC documents DA00-1407 and DA00-705 and/or TIA/EIA 603-1.

Opinion / Interpretation of Results

Test Performed	Minimum Margin (dB)	Results
Antenna requirement per CFR 47 15.203	N/A	Complies
Restricted Bands Emissions as per CFR 47 15.205 and RSS-210 2.2	-17.3	Complies
AC Line Conducted Emissions as per CFR 47 15.207 and RSS-210 2.5	-9.0	Complies
Radiated Emissions as per CFR 47 15.209 and RSS-210 2.5	-22.3	Complies
Radiated Emissions per CFR 47 15.249 and RSS-210 A2.9	-19.2	Complies
Receivers emissions per CFR 47 15.111 and RSS-210 and RSS-GEN	-21.7	Complies



Application for Certification

- (1) Manufacturer: Garmin International, Inc.
1200 East 151st Street
Olathe, KS 66062
- (2) Identification: Model: 01102458
FCC I.D.: IPH-01787 IC: 1792A-01787
- (3) Instruction Book: Refer to Exhibit for Instruction Manual.
- (4) Description of Circuit Functions: Refer to Exhibit of Operational Description.
- (5) Block Diagram with Frequencies: Refer to Exhibit of Operational Description.
- (6) Report of Measurements: Report of measurements follows in this Report.
- (7) Photographs: Construction, Component Placement, etc.: Refer to Exhibit for photographs of equipment.
- (8) No Peripheral Equipment was Necessary.
- (9) Transition Provisions of 15.37 are not being requested.
- (10) Equipment is not a scanning receiver and this section is not applicable.
- (11) The equipment does not operate in the 59 – 64 GHz frequency band and this section is not applicable.
- (12) The equipment is not software defined and this section is not applicable.

Statement of Modifications and Deviations

No modifications to the EUT were required for the equipment to demonstrate compliance with CFR47 Part 15C, or RSS-210 Emissions Requirements. There were no deviations or modification to the specifications.



Equipment Tested

<u>Equipment</u>	<u>Model / PN</u>	<u>Serial Number</u>
01102458 (EUT)	011-02458-xx	3806879589b
AC Adapter	362-00072-00	N/A
USB Cable	320-00559-01	N/A
CLA	320-00239-50	N/A
GTM35	320-00422-60	N/A
FMI 10	320-00446-00	N/A
FMI 40	320-00493-90	N/A
Video Cable	320-00504-00	N/A

Equipment Function and Testing Procedures

The EUT is a GPS receiver and display unit offering reception and display of location, navigation, and other information for the user incorporating a low power transmitter with operation capability in the 2402-2480 MHz frequency band (CFR 47 15.249 and RSS-210). The GPS design offers use as a hand-held, transportation mount or portable configuration for use in navigational applications. The equipment offers communications to other 2402-2480 MHz compliant devices. Two samples were supplied for testing one production design and the other modified for testing purposes replacing integral antenna with RF connection port for this and other reports and documentation. This modification offered testing facility ability to connect to transmitter antenna port to test equipment for antenna port conducted emissions testing. The EUT was arranged as typical user equipment configurations for testing purposes. The transmitter offers no other interface connections than those in the configuration options shown below. The unit operates from internal battery or external power received from external power supply options as shown in the configuration diagrams below. Some configurations shown below are not applicable for this report and have been tested and documented in other relevant documentation. As requested by the manufacturer and required by regulations, the equipment was tested for emissions compliance using the available configurations with the worst-case data presented. Test results in this report relate only to the products described in this report.

AC Line Conducted Emission Test Procedure

Testing for the AC line-conducted emissions was performed as defined in sections 7.2.4 and 13 of ANSI C63.4. The test setup, including the EUT, was arranged in the test configurations as shown above during testing. The test configuration was placed on a 1 x 1.5-meter wooden bench, 0.8 meters high located in a screen room. The power lines of the system were isolated from the power source using a standard LISN with a 50- μ Hy choke. EMI was coupled to the spectrum analyzer through a 0.1 μ F capacitor internal to the LISN. The LISN was positioned on the floor beneath the wooden bench supporting the EUT. The power lines and cables were draped over the back edge of the table. Refer to photographs in exhibits for EUT placement used during testing.


Radiated Emission Test Procedure

Testing for the radiated emissions was performed as defined in sections 8.3 and 13.1 of ANSI C63.4. The EUT was arranged in the test configurations as shown above during testing. The test configuration was placed on a rotating 1 x 1.5-meter wooden platform 0.8 meters above the ground plane at a distance of 3 meters from the FSM antenna. EMI energy was maximized by equipment placement, raising and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before final data was taken using a spectrum analyzer. Refer to photographs in exhibits for EUT placement used during testing.


Equipment and Cable Configurations

Configurations for the 01102458


1. 01102458 Li-Ion battery charged by the AC wall brick power supply (GPN: 362-00072-00)




2. 01102458 connected to computer through USB cable (GPN: 320-00559-01)



3. 01102458 connected to car cigarette lighter power cable assembly (GPN: 320-00239-50)




4. 01102458 connected to GTM35 cable assembly (320-00422-60)




5. 01102458 connected to FMI-10 cable assembly (320-00446-00)




6. 01102458 connected to FMI-40 cable assembly (320-00493-90)




7. 01102458 connected to analog video cable assembly (320-00504-00)




8. 01102458 connected to car cigarette lighter power cable assembly (GPN: 320-00239-50) and analog video cable assembly (320-00504-00).




9. 01102458 connected to GTM35 cable assembly (320-00422-60) and analog video cable assembly (320-00504-00).



10. 01102458 connected to FMI-10 cable assembly (320-00446-00) and analog video cable assembly (320-00504-00).



11. 01102458 FMI-40 cable assembly (320-00493-90) and analog video cable assembly (320-00504-00).



Environmental Conditions

Ambient Temperature	22.4° C
Relative Humidity	26%
Atmospheric Pressure	1028.1 mb

Units of Measurements

Conducted EMI Data is in dB μ V; dB referenced to one microvolt.

Radiated EMI Data is in dB μ V/m; dB/m referenced to one microvolt per meter.

Test Site Locations

Conducted EMI The AC power line conducted emissions testing performed in a shielded screen room located at Rogers Labs, Inc., 4405 W. 259th Terrace, Louisburg, KS.

Radiated EMI The radiated emissions tests were performed at the 3 meters, Open Area Test Site (OATS) located at Rogers Labs, Inc., 4405 W. 259th Terrace, Louisburg, KS.



Site Approval Refer to Annex for FCC Site Registration Letter, # 90910, and Industry Canada Site Registration Letter, IC3041A-1.

List of Test Equipment

A Rohde & Schwarz ESU40 and/or Hewlett Packard 8591EM Spectrum Analyzer was used as the measuring device for the emissions testing of frequencies below 1 GHz. A Rohde & Schwarz ESU40 and/or Hewlett Packard 8562A Spectrum Analyzer was used as the measuring device for testing the emissions at frequencies above 1 GHz. The analyzer settings used are described in the following table. Refer to the appendix for a complete list of test equipment.

Analyzer Settings		
AC Line Conducted Emissions:		
RBW	AVG. BW	Detector Function
9 kHz	30 kHz	Peak/Quasi Peak
Radiated Emissions 30-1000 MHz		
RBW	AVG. BW	Detector Function
100 kHz	100 kHz	Peak
120 kHz	300 kHz	Peak/Quasi Peak
Radiated Emissions Above 1000 MHz		
RBW	Video BW	Detector Function
1 MHz	1 MHz	Peak / Average

<u>Equipment</u>	<u>Manufacturer</u>	<u>Model</u>	<u>Calibration Date</u>	<u>Due</u>
LISN	Comp. Design	FCC-LISN-2-MOD.CD	10/10	10/11
Antenna	ARA	BCD-235-B	10/10	10/11
Antenna	EMCO	3147	10/10	10/11
Antenna	EMCO	3143	5/10	5/11
Analyzer	HP	8591EM	5/10	5/11
Analyzer	HP	8562A	5/10	5/11
Analyzer	Rohde & Schwarz	ESU40	5/10	5/11

General Emissions (Unintentional Radiators)

AC Line Conducted EMI Procedure

The EUT was arranged in typical equipment configurations as offered by manufacturer. Testing was performed with the EUT placed on a 1 x 1.5-meter wooden bench 80 cm above the conducting ground plane, floor of a screen room. The bench was positioned 40 cm away from the wall of the screen room. The LISN was positioned on the floor of the screen room 80-cm from the rear of the EUT. Testing for the line-conducted emissions were the procedures of ANSI 63.4 paragraphs 13.1.3 and 7.2.4. The AC adapter for the EUT or CPU was connected to the LISN for line-conducted emissions testing. A second LISN was positioned on the floor of the screen room 80-cm from the rear of the supporting equipment of the EUT. All power cords except the EUT were then powered from the second LISN. EMI was coupled to the spectrum analyzer through a 0.1 μ F capacitor, internal to the LISN. Power line conducted emissions testing was carried out individually for each current carrying conductor of the EUT. The excess length of lead between the system and the LISN receptacle was folded back and forth to form a bundle not exceeding 40 cm in length. The screen room, conducting ground plane, analyzer, and LISN were bonded together to the protective earth ground. Preliminary testing was performed to identify the frequencies of each of the emissions, which demonstrated the highest amplitudes. The cables were repositioned to obtain maximum amplitude of measured EMI level. Once the worst-case configuration was identified, plots were made of the EMI from 0.15 MHz to 30 MHz then data was recorded with maximum conducted emissions levels. Refer to figures one and two showing plots of the worst-case AC Line conducted emissions of the AC Adapter while charging the EUT. Refer to figures three and four showing plots of the worst-case AC Line conducted emissions of the Laptop AC power adapter while communicating with the EUT.




Figure One AC Line Conducted emissions of EUT line 1 (EUT AC Adapter)




Figure Two AC Line Conducted emissions of EUT line 2 (EUT AC Adapter)




Figure Three AC Line Conducted emissions of EUT line 1 (EUT USB CPU)




Figure Four AC Line Conducted emissions of EUT line 2 (EUT USB CPU)



Data AC Line Conducted Emissions

Line 1 (EUT USB CPU)

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
1	210.000000000 kHz	48.35	Quasi Peak	-14.86
2	694.000000000 kHz	30.54	Average	-15.46
1	726.000000000 kHz	36.08	Quasi Peak	-19.92
1	846.000000000 kHz	39.85	Quasi Peak	-16.15
2	846.000000000 kHz	29.73	Average	-16.27
1	1.194000000 MHz	34.33	Quasi Peak	-21.67
1	1.274000000 MHz	41.10	Quasi Peak	14.04
2	1.274000000 MHz	28.22	Average	-17.78
2	1.858000000 MHz	33.09	Average	-12.91
1	1.862000000 MHz	46.95	Quasi Peak	-9.05
1	2.246000000 MHz	43.13	Quasi Peak	-12.87
2	2.254000000 MHz	33.00	Average	-13.00
1	2.834000000 MHz	37.73	Quasi Peak	-18.27
1	3.966000000 MHz	38.94	Quasi Peak	-17.06
2	3.970000000 MHz	32.46	Average	-13.54
1	4.978000000 MHz	36.46	Quasi Peak	-19.54

Line 2 (EUT USB CPU)

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
1	206.000000000 kHz	44.94	Quasi Peak	-18.43
2	698.000000000 kHz	25.51	Average	-20.49
2	894.000000000 kHz	31.59	Average	-14.41
1	1.222000000 MHz	37.28	Quasi Peak	-18.72
1	1.294000000 MHz	38.00	Quasi Peak	-18.00
2	1.478000000 MHz	32.78	Average	-13.22
1	1.790000000 MHz	40.87	Quasi Peak	-15.13
2	2.018000000 MHz	34.28	Average	-11.72
1	2.246000000 MHz	41.08	Quasi Peak	-14.92
2	2.334000000 MHz	32.05	Average	-13.95
1	2.830000000 MHz	37.58	Quasi Peak	-18.42
2	2.878000000 MHz	31.55	Average	-14.45

Other emissions present had amplitudes at least 20 dB below the limit.



Line 1 (EUT AC Adapter)

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
2	158.000000000 kHz	28.15	Average	-27.42
1	158.000000000 kHz	38.31	Quasi Peak	-27.25
2	10.316000000 MHz	27.75	Average	-22.25
2	10.596000000 MHz	27.08	Average	-22.92
2	13.392000000 MHz	24.42	Average	-25.58
1	13.928000000 MHz	35.63	Quasi Peak	-24.37
2	14.120000000 MHz	26.38	Average	-23.62
2	14.512000000 MHz	26.40	Average	-23.60
1	14.548000000 MHz	34.90	Quasi Peak	-25.10
1	15.236000000 MHz	35.17	Quasi Peak	-24.83
1	19.736000000 MHz	8.54	Quasi Peak	-51.46
1	20.536000000 MHz	13.52	Quasi Peak	-46.48

Line 2 (EUT AC Adapter)

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
2	158.000000000 kHz	31.86	Average	-23.71
1	158.000000000 kHz	37.17	Quasi Peak	-28.39
2	198.000000000 kHz	29.49	Average	-24.21
2	358.000000000 kHz	28.47	Average	-20.31
2	10.316000000 MHz	26.63	Average	-23.37
2	10.916000000 MHz	23.54	Average	-26.46
1	12.728000000 MHz	33.32	Quasi Peak	-26.68
1	13.400000000 MHz	36.10	Quasi Peak	-23.90
2	13.444000000 MHz	23.98	Average	-26.02
1	13.764000000 MHz	36.17	Quasi Peak	-23.83
1	14.116000000 MHz	34.81	Quasi Peak	-25.19
1	14.460000000 MHz	33.58	Quasi Peak	-26.42

Other emissions present had amplitudes at least 20 dB below the limit.

Summary of Results for AC Line Conducted Emissions

The EUT demonstrated compliance with the AC Line Conducted Emissions requirements of CFR 47 Part 15B, RSS-GEN, and other applicable standards. The EUT worst-case configuration demonstrated a minimum margin of 9.0 dB below the limit. Other emissions were present with amplitudes at least 20 dB below the limit and worst-case amplitudes recorded.



Radiated EMI

The EUT was arranged in typical equipment configurations and operated through all various modes. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. Plots were made of the radiated frequency spectrum from 30 MHz to 25,000 MHz for the preliminary testing. Refer to figures five through eleven showing plots of the radiated emissions spectrum taken in the screen room. Each radiated emission was then re-maximized at the OATS location before final radiated emissions measurements were performed. Final data was taken with the EUT located at the OATS at a distance of 3 meters between the EUT and the receiving antenna. The frequency spectrum from 30 MHz to 25,000 MHz was searched for radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Biconilog from 30 to 6,000 MHz, and/or Log Periodic from 200 MHz to 5 GHz, Double Ridge Horn or pyramidal horns and mixers from 4 GHz to 25 GHz, notch filters and appropriate amplifiers were utilized.




Figure Five Plot of General Radiated Emissions




Figure Six Plot of General Radiated Emissions




Figure Seven Plot of General Radiated Emissions




Figure Eight Plot of General Radiated Emissions




Figure Nine Plot of General Radiated Emissions




Figure Ten Plot of General Radiated Emissions




Figure Eleven Plot of General Radiated Emissions

General Radiated Emissions Data from EUT

Frequency in MHz	FSM Horz. (dBμV)	FSM Vert. (dBμV)	A.F. (dB/m)	Amp. Gain (dB)	RFS Horz. @ 3m (dBμV/m)	RFS Vert. @ 3m (dBμV/m)	Limit @ 3m (dBμV/m)
100.2	35.2	35.7	10.3	30	15.5	16.0	43.5
132.9	32.8	32.9	13.5	30	16.3	16.4	43.5
274.4	31.4	35.1	13.7	30	15.1	18.8	46.0
300.0	36.6	39.7	14.0	30	20.6	23.7	46.0
320.0	33.8	32.7	14.5	30	18.3	17.2	46.0
355.3	35.7	37.4	15.2	30	20.9	22.6	46.0
367.4	28.2	28.7	15.4	30	13.6	14.1	46.0

Other emissions present had amplitudes at least 20 dB below the limit.

Summary of Results for Radiated Emissions

The EUT demonstrated compliance with requirements of CFR47, and Industry Canada requirements. The EUT demonstrated a minimum margin of 22.3 dB below requirements. Other emissions were present with amplitudes at least 20 dB below the limit.



Intentional Radiators Emissions

As per CFR47 Part 15, Subpart C, paragraphs 15.203, 15.205, 15.209, 15.249 and RSS-210 the following information is submitted.

Antenna Requirements

The unit is produced with a permanently attached antenna and has no provision for user service, replacement, or antenna modification. The requirements of 15.203 are fulfilled and there are no deviations or exceptions to the specification.

Restricted Bands of Operation

Spurious emissions falling in the restricted frequency bands of operation were measured at a distance of three meters at the OATS. The EUT utilizes frequency, determining circuitry, which generates harmonics falling in the restricted bands. Emissions were checked at the OATS, using appropriate antennas or pyramidal horns, amplification stages, and a spectrum analyzer. No other significant emission was observed which fell into the restricted bands of operation.

Sample Calculation:

$$\text{RFS (dB}\mu\text{V/m @ 3m)} = \text{FSM (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} - \text{Amplifier Gain (dB)}$$

Radiated Emissions Data in Restricted Bands

Frequency in MHz	FSM Horz. (dBµV)	FSM Vert. (dBµV)	A.F. (dB/m)	Amp. Gain (dB)	RFS Horz. @ 3m (dBµV/m)	RFS Vert. @ 3m (dBµV/m)	Limit @ 3m (dBµV/m)
132.9	32.8	32.9	13.5	30.0	16.3	16.4	43.5
274.4	31.4	35.1	13.7	30.0	15.1	18.8	46.0
2390.0	17.3	17.3	30.6	25.0	22.9	22.9	54.0
2483.5	17.8	18.4	30.8	25.0	23.6	24.2	54.0
4804.0	18.8	22.1	38.4	25.0	32.2	35.5	54.0
4882.0	17.2	22.7	39.0	25.0	31.2	36.7	54.0
4960.0	18.1	18.2	38.6	25.0	31.7	31.8	54.0
7206.0	13.3	13.1	36.2	25.0	24.5	24.3	54.0
7323.0	14.1	12.3	36.5	25.0	25.6	23.8	54.0
7440.0	14.9	11.4	36.7	25.0	26.6	23.1	54.0
12010.0	8.8	8.7	40.0	25.0	23.8	23.7	54.0
12205.0	9.9	9.9	40.4	25.0	25.3	25.3	54.0
12400.0	10.1	9.1	40.7	25.0	25.8	24.8	54.0

Other emissions present had amplitudes at least 20 dB below the margin.

Summary of Results for Radiated Emissions in Restricted Bands

The EUT demonstrated compliance with requirements of CFR47 15C, and Industry Canada RSS-210 requirements. The EUT demonstrated a minimum margin of 17.3 dB below requirements. Peak and Quasi-peak amplitudes of frequencies below 1000 MHz were measured and average and peak amplitudes of frequencies above 1000 MHz were measured for demonstration of compliance with the regulations. No other significant emissions were found in the restricted frequency bands. Other emissions were present with amplitudes at least 20 dB below the FCC Limits.



Operation in the Band 2402 - 2480 MHz

The power output was measured on an Open Area Test Site at a 3 meters distance. The EUT was placed on a wooden turntable 0.8 meters above the ground plane at a distance of 3 meters from the FSM antenna. The peak and average amplitude of emissions above 1000 MHz including spurious emissions were measured using a spectrum analyzer/receiver. Data was then recorded from the analyzer display. Emissions radiated outside of the specified bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in 15.209 (and/or RSS-210), whichever is the lesser attenuation. The amplitude of each emission was maximized by varying the FSM antenna height, polarization, and by rotating the turntable. A Biconilog Antenna was used for measuring emissions from 30 to 6000 MHz, and/or Log Periodic Antenna for 200 to 5000 MHz, Double Ridge Horn or Pyramidal Horn Antennas from 4 GHz to 25 GHz. Emissions were measured in dB μ V/m @ 3 meters. Refer to figures twelve through seventeen showing the frequency and amplitude of emission displayed on the spectrum analyzer measured at the temporary test antenna port (performed on sample #2).




Figure Twelve Plot of Occupied Bandwidth (Low channel)




Figure Thirteen Plot of Occupied Bandwidth (Middle channel)




Figure Fourteen Plot of Occupied Bandwidth (High channel)




Figure Fifteen Plot of Operation across frequency band




Figure Sixteen Plot of Lower Frequency Band Edge




Figure Seventeen Plot of Higher Frequency Band Edge



Transmitter Emissions Data

Transmitter Antenna Port Conducted Emissions Data

Frequency MHz	Antenna Conducted Output Power dBm	Occupied Bandwidth kHz
2402.0	-5.01	929.49
2441.0	-5.31	929.48
2480.0	-4.60	937.50

Transmitter Radiated Emissions

Frequency	FSM Hor Peak	FSM Hor Ave	FSM Vert Peak	FSM Vert Ave	AF	Amp Gain	RFS @ 3 m Hor Peak	RFS @ 3 m Hor Ave	RFS @ 3 m Vert Peak	RFS @ 3 m Vert Ave	Ave Limit
2402.0	84.4	61.1	90.5	68.9	30.6	25	90.0	66.7	96.1	74.5	94.0
4804.0	34.9	18.8	44.3	22.1	38.4	25	48.3	32.2	57.7	35.5	54.0
7206.0	30.1	13.3	27.3	13.1	36.2	25	41.3	24.5	38.5	24.3	54.0
9608.0	27.2	15.6	28.1	15.6	38.1	25	40.3	28.7	41.2	28.7	54.0
12010.0	21.2	8.8	20.7	8.7	40.0	25	36.2	23.8	35.7	23.7	54.0
2441.0	83.6	61.0	91.5	68.1	30.9	25	89.5	66.9	97.4	74.0	94.0
4882.0	31.1	17.2	46.7	22.7	39.0	25	45.1	31.2	60.7	36.7	54.0
7323.0	33.1	14.1	26.3	12.3	36.5	25	44.6	25.6	37.8	23.8	54.0
9764.0	28.7	15.2	27.3	15.1	38.2	25	41.9	28.4	40.5	28.3	54.0
12205.0	21.5	9.9	22.1	9.9	40.4	25	36.9	25.3	37.5	25.3	54.0
2480.0	84.3	60.9	90.1	68.4	31.4	25	90.7	67.3	96.5	74.8	94.0
4960.0	35.3	18.1	35.7	18.2	38.6	25	48.9	31.7	49.3	31.8	54.0
7440.0	31.3	14.9	28.1	11.4	36.7	25	43.0	26.6	39.8	23.1	54.0
9920.0	36.5	16.3	27.3	15.1	38.4	25	49.9	29.7	40.7	28.5	54.0
12400.0	28.5	10.1	20.8	9.1	40.7	25	44.2	25.8	36.5	24.8	54.0

Other emissions were present with amplitudes at least 20 dB below limits.

Note: Levels measured @ 3-meter OATS site.

Summary of Results for Transmitter Radiated Emissions

The EUT demonstrated compliance with the requirements and specifications of CFR47 Part 15.249 and RSS-210 Intentional Radiators. The EUT demonstrated highest peak emission level of the fundamental of 97.4 dB μ V/m with a minimum margin of 3.4 dB, and average emission of 74.8 dB μ V/m with a minimum margin of 19.2 dB, as measured at 3 meters. The EUT demonstrated a minimum margin of 17.3 dB below limits for the harmonic emissions. There were no other measurable emissions greater than 20 dB below requirements than those recorded in this report. There are no deviations or exceptions to the requirements.

Receiver Spurious Emissions

Receivers which provide terminals for the connection of an external receiving antenna may be tested to demonstrate compliance with the provisions of CFR47 15.109 with the antenna terminals shielded and terminated with a termination equal to the impedance specified for the antenna, provided these receivers also comply with the following: With the receiver antenna terminal connected to a resistive termination equal to the impedance specified or employed for the antenna, the power at the antenna terminal at any frequency within the range of measurements specified in 15.33 shall not exceed 2.0 nanowatts. The EUT incorporates an integral antenna system in production equipment. A test sample was offered allowing connection to antenna port for testing purposes. The test antenna port was connected to a spectrum analyzer for testing the antenna-conducted emissions. Antenna port conduction testing was performed at temporary antenna test port connected to the spectrum analyzer through a short coaxial cable. The spectrum analyzer provided the 50-ohm load equivalent to the antenna. The frequency spectrum was investigated at the antenna port with the worst case data presented. Refer to figures eighteen through twenty-five showing the spectrum analyzer display of worst-case receiver antenna conduction emissions. Worst-case antenna port conducted emissions data presented. Worst-case (production design sample) receiver radiated emissions were tested at 3 meter OATS. Data presented below demonstrates compliance with regulations.




Figure Eighteen Receiver Temporary Antenna Port Conducted Emissions




Figure Nineteen Receiver Temporary Antenna Port Conducted Emissions




Figure Twenty Receiver Temporary Antenna Port Conducted Emissions




Figure Twenty-one Receiver Temporary Antenna Port Conducted Emissions




Figure Twenty-two Receiver Temporary Antenna Port Conducted Emissions




Figure Twenty-three Receiver Temporary Antenna Port Conducted Emissions




Figure Twenty-four Receiver Temporary Antenna Port Conducted Emissions




Figure Twenty-five Receiver Temporary Antenna Port Conducted Emissions



Receiver Antenna Conducted Emissions Data (Sample 2 temporary antenna port)

Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Margin (dB)
2402.0	-90.61	-57.0	-33.6
4804.0	-78.94	-57.0	-21.9
7206.0	-86.61	-57.0	-29.6
9608.0	-87.02	-57.0	-30.0
12010.0	-85.98	-57.0	-29.0
14412.0	-85.00	-57.0	-28.0
16814.0	-85.28	-57.0	-28.3
19216.0	-85.77	-57.0	-28.8
21618.0	-84.78	-57.0	-27.8

Other emissions present had amplitudes at least 20 dB below the limit.

Receiver Radiated Emissions Data

Emission Freq. (MHz)	FSM Horz. (dBµV)	FSM Vert. (dBµV)	Ant. Factor (dB)	Amp. Gain (dB)	RFS Horz. @ 3m (dBµV/m)	RFS Vert. @ 3m (dBµV/m)	Limit @ 3m (dBµV/m)
2402.0	17.8	17.3	30.6	25	23.4	22.9	54.0
4804.0	18.6	18.5	38.4	25	32.0	31.9	54.0
7206.0	11.9	12.1	36.0	25	22.9	23.1	54.0
9608.0	15.5	15.5	38.1	25	28.6	28.6	54.0
12010.0	16.8	9.9	40.0	25	31.8	24.9	54.0
14412.0	17.3	16.1	40.0	25	32.3	31.1	54.0

Other emissions were present with amplitudes at least 20 dB below limits.



Summary of Results for Receiver Emissions

The EUT demonstrated compliance with the antenna conducted emissions requirements of CFR 47 Part 15B and RSS-GEN with an antenna port conducted minimum margin of 21.9 dB below requirements (measured at test ant port). The EUT demonstrated compliance with the radiated emissions requirements of CFR 47 Part 15B and RSS-GEN with a minimum 21.7 dB margin below requirements. Other emissions were present with amplitudes at least 20 dB below the CFR 47 15 and RSS-GEN limits.



NVLAP Lab Code 200087-0

Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Rogers Labs Test Equipment List
- Annex C Rogers Qualifications
- Annex D FCC Test Site Registration Letter
- Annex E Industry Canada Test Site Registration Letter

Annex A Measurement Uncertainty Calculations

Radiated Emissions Measurement Uncertainty Calculation

Measurement of vertically polarized radiated field strength over the frequency range 30 MHz to 1 GHz on an open area test site at 3m and 10m includes following uncertainty:

Contribution	Probability Distribution	Uncertainty (dB)
Antenna factor calibration	normal (k = 2)	±0.58
Cable loss calibration	normal (k = 2)	±0.2
Receiver specification	rectangular	±1.0
Antenna directivity	rectangular	±0.1
Antenna factor variation with height	rectangular	±2.0
Antenna factor frequency interpolation	rectangular	±0.1
Measurement distance variation	rectangular	±0.2
Site Imperfections	rectangular	±1.5
Combined standard uncertainty $u_c(y)$ is		

$$U_c(y) = \pm \sqrt{\left[\frac{1.0}{2}\right]^2 + \left[\frac{0.2}{2}\right]^2 + \left[\frac{1.0^2 + 0.1^2 + 2.0^2 + 0.1^2 + 0.2^2 + 1.5^2}{3}\right]}$$

$$U_c(y) = \pm 1.6 \text{ dB}$$

It is probable that $u_c(y) / s(q_k) > 3$, where $s(q_k)$ is estimated standard deviation from a sample of n readings unless the repeatability of the EUT is particularly poor, and a coverage factor of $k = 2$ will ensure that the level of confidence will be approximately 95%, therefore:

$$s(q_k) = \sqrt{\frac{1}{(n-1)} \sum_{k=1}^n (q_k - \bar{q})^2}$$

$$U = 2 U_c(y) = 2 \times \pm 1.6 \text{ dB} = \pm 3.2 \text{ dB}$$

Notes:

- 1.1 Uncertainties for the antenna and cable were estimated, based on a normal probability distribution with $k = 2$.
- 1.2 The receiver uncertainty was obtained from the manufacturer's specification for which a rectangular distribution was assumed.
- 1.3 The antenna factor uncertainty does not take account of antenna directivity.
- 1.4 The antenna factor varies with height and since the height was not always the same in use as when the antenna was calibrated an additional uncertainty is added.
- 1.5 The uncertainty in the measurement distance is relatively small but has some effect on the received signal strength. The increase in measurement distance as the antenna height is increased is an inevitable consequence of the test method and is therefore not considered a contribution to uncertainty.
- 1.6 Site imperfections are difficult to quantify but may include the following contributions:
 - Unwanted reflections from adjacent objects.
 - Ground plane imperfections: reflection coefficient, flatness, and edge effects.
 - Losses or reflections from "transparent" cabins for the EUT or site coverings.
 - Earth currents in antenna cable (mainly effect Biconical antennas).



The specified limits for the difference between measured site attenuation and the theoretical value (± 4 dB) were not included in total since the measurement of site attenuation includes uncertainty contributions already allowed for in this budget, such as antenna factor.

Conducted Measurements Uncertainty Calculation

Measurement of conducted emissions over the frequency range 9 kHz to 30 MHz includes following uncertainty:

Contribution	Probability Distribution	Uncertainty (dB)
Receiver specification	rectangular	± 1.5
LISN coupling specification	rectangular	± 1.5
Cable and input attenuator calibration	normal (k=2)	± 0.5

Combined standard uncertainty $u_c(y)$ is

$$U_c(y) = \pm \sqrt{\left[\frac{0.5}{2}\right]^2 + \frac{1.5^2 + 1.5^2}{3}}$$

$$U_c(y) = \pm 1.2 \text{ dB}$$

As with radiated field strength uncertainty, it is probable that $u_c(y) / s(q_k) > 3$ and a coverage factor of $k = 2$ will suffice, therefore:

$$U = 2 U_c(y) = 2 \times \pm 1.2 \text{ dB} = \pm 2.4 \text{ dB}$$



Annex B Rogers Labs Test Equipment List

The test equipment used is maintained in calibration and good operating condition. Use of this calibrated equipment ensures measurements are traceable to national standards.

<u>Equipment</u>	<u>Date of last Calibration</u>
Oscilloscope Scope: Tektronix 2230	2/10
Wattmeter: Bird 43 with Load Bird 8085	2/10
Power Supplies: Sorensen SRL 20-25, SRL 40-25, DCR 150, DCR 140	2/10
H/V Power Supply: Fluke Model: 408B (SN: 573)	2/10
R.F. Generator: HP 606A	2/10
R.F. Generator: HP 8614A	2/10
R.F. Generator: HP 8640B	2/10
Spectrum Analyzer: Rohde & Schwarz ESU40	5/10
Spectrum Analyzer: HP 8562A, Mixers: 11517A, 11970A, 11970K, 11970U, 11970V, 11970W HP Adapters: 11518, 11519, 11520	5/10
Spectrum Analyzer: HP 8591EM	5/10
Frequency Counter: Leader LDC825	2/10
Antenna: EMCO Biconilog Model: 3143	5/10
Antenna: EMCO Log Periodic Model: 3147	10/10
Antenna: Antenna Research Biconical Model: BCD 235	10/10
Antenna: EMCO Dipole Set 3121C	2/10
Antenna: C.D. B-101	2/10
Antenna: Solar 9229-1 & 9230-1	2/10
Antenna: EMCO 6509	2/10
Audio Oscillator: H.P. 201CD	2/10
R.F. Power Amp 65W Model: 470-A-1010	2/10
R.F. Power Amp 50W M185- 10-501	2/10
R.F. Preamp CPPA-102	2/10
LISN 50 µHy/50 ohm/0.1 µf	10/10
LISN Compliance Eng. 240/20	2/10
LISN Fischer Custom Communications FCC-LISN-50-16-2-08	2/10
Peavey Power Amp Model: IPS 801	2/10
Power Amp A.R. Model: 10W 1010M7	2/10
Power Amp EIN Model: A301	2/10
ELGAR Model: 1751	2/10
ELGAR Model: TG 704A-3D	2/10
ESD Test Set 2010i	2/10
Fast Transient Burst Generator Model: EFT/B-101	2/10
Current Probe: Singer CP-105	2/10
Current Probe: Solar 9108-1N	2/10
Field Intensity Meter: EFM-018	2/10
KEYTEK Ecat Surge Generator	2/10
Shielded Room 5 M x 3 M x 3.0 M	



Annex C Rogers Qualifications

Scot D. Rogers, Engineer

Rogers Labs, Inc.

Mr. Rogers has approximately 17 years experience in the field of electronics. Work experience includes six years working in the automated controls industry and remaining years working with the design, development and testing of radio communications and electronic equipment.

Positions Held:

Systems Engineer: A/C Controls Mfg. Co., Inc. 6 Years

Electrical Engineer: Rogers Consulting Labs, Inc. 5 Years

Electrical Engineer: Rogers Labs, Inc. Current

Educational Background:

- 1) Bachelor of Science Degree in Electrical Engineering from Kansas State University
- 2) Bachelor of Science Degree in Business Administration Kansas State University
- 3) Several Specialized Training courses and seminars pertaining to Microprocessors and Software programming.



NVLAP Lab Code 200087-0

Annex D FCC Test Site Registration Letter

FEDERAL COMMUNICATIONS COMMISSION

**Laboratory Division
7435 Oakland Mills Road
Columbia, MD 21046**

May 18, 2010

Registration Number: 90910

Rogers Labs, Inc.
4405 West 259th Terrace,
Louisburg, KS 66053

Attention: Scot Rogers,

Re: Measurement facility located at Louisburg
~~3 & 10 meter site~~
Date of Renewal: May 18, 2010

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website www.fcc.gov under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,

Phyllis Farrish
Industry Analyst

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1


Garmin International, Inc.
Model: 01102458
Test #: 101118A SN: 3806879589b
Test to: FCC Parts 2 and 15.249, RSS-210
File: 01102458 TstRpt 101118A

FCC ID#: IPH-01787
IC: 1792A-01787
Date: December 3, 2010
Page 41 of 42



NVLAP Lab Code 200087-0

Annex E Industry Canada Test Site Registration Letter



May 26, 2010

OUR FILE: 46405-3041
Submission No: 140719

Rogers Labs Inc.
4405 West 259th Terrace
Louisburg, KY, 66053
USA

Attention: Mr. Scot D. Rogers

Dear Sir/Madame:

The Bureau has received your application for the renewal of a 3/10m OATS. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought (**3041A-1**). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please keep for your records the following information;

- Your primary code is: **3041**
- The company number associated to the site(s) located at the above address is: **3041A**

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2003 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2003 or later shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 metre OATS or 3 metre chamber). If the test facility is not accredited to ANSI C63.4-2003 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to exceed two years. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL;
http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h_tt00052e.html.

If you have any questions, you may contact the Bureau by e-mail at certification.bureau@ic.gc.ca Please reference our file and submission number above for all correspondence.

Yours sincerely,

Dalwinder Gill
For: Wireless Laboratory Manager
Certification and Engineering Bureau
3701 Carling Ave., Building 94
P.O. Box 11490, Station "H"
Ottawa, Ontario K2H 8S2
Email: dalwinder.gill@ic.gc.ca
Tel. No. (613) 998-8363
Fax. No. (613) 990-4752

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Garmin International, Inc.
Model: 01102458
Test #: 101118A SN: 3806879589b
Test to: FCC Parts 2 and 15.249, RSS-210
File: 01102458 TstRpt 101118A

FCC ID#: IPH-01787
IC: 1792A-01787
Date: December 3, 2010
Page 42 of 42