


**SPECIFICATION  
CONTROL  
DRAWING**

**REVISIONS**

REV.	DATE	DESCRIPTION	APPRVD.
1	2/27/12	EXPERIMENTAL RELEASE	-----
A	3/14/12	UPDATE LABEL	89128
B	4/5/12	ADD FREQ RANGE AND TYPE, UPDATE VOLTAGE	89878



**PROPOSED REV C**



**NOTES:**

1. MATERIAL: WHITE POLYESTER WITH PERMANENT ADHESIVE ON BACKSIDE. NOMENCLATURE, SERIAL AND MODEL NUMBER TO BE BLACK. ACRYLIC PERMANENT ADHESIVE ON BACK SIDE WITH PEEL OFF RELEASE LINER. TOTAL PACKAGE THICKNESS EXCLUDING RELEASE LINER IS 0.05-0.13mm.
2. 9 DIGIT SERIAL NUMBER TO BE PRINTED SEQUENTIALLY IN FIELDS AS SHOWN (2D, CODE 39 W/HUMAN READABLE OR HUMAN READABLE ONLY WHEN APPLICABLE). PRINT ADDITIONAL TAG (30 X 7.5) AS INDICATED (BARCODE 39 WITH HUMAN READABLE ONLY). ALL TAGS PRINTED WITH INDELIBLE BLACK INK. S/N RANGE FOR THIS ITEM: 2NM000000-2NM999999 AS INDICATED ON GARMIN PURCHASE ORDER.
3. MAIN TAG AND ADDITIONAL TAG ARE SUPPLIED ON ONE ROLL WITH EQUIVALENT SERIAL NO'S ADJACENT TO EACH OTHER. ALL TAGS ARE "KISS CUT" ON ROLL.
4. PARTS TO BE FABRICATED USING DIGITAL CORELDRAW FILE.
5. THIS PART SHALL NOT CONTAIN HAZARDOUS SUBSTANCES EXCEEDING LEVELS DEFINED BY EU DIRECTIVE 2002/95/EC (RoHS).
6. THIS PART SHALL COMPLY WITH GARMIN BANNED & RESTRICTED SUBSTANCES DOCUMENT GPN 001-00211-00.
7. DIMENSIONS: mm

<b>CONFIDENTIAL</b>		<b>GARMIN®</b>		<b>Garmin Ltd. or its subsidiaries c/o Garmin International, Inc. 1200 E. 151st Street Olathe, Kansas 66062 U.S.A.</b>	
This drawing and the specifications contained herein are the property of Garmin Ltd. or its subsidiaries and may not be reproduced or used in whole or in part as the basis for manufacture or sale of products without written permission.		TITLE <b>Lbl, S/N, Fuji, Radio, GPS, AutoOEM, NA</b>			
DATE		SIZE	DWG. NO.		REV.
DRAWN <b>BSC</b> 2/27/12		<b>A</b>	<b>161-02987-00</b>		<b>B</b>
CHKD. <b>BJK</b> 2/28/12					
PROJ. MGR. <b>DJB</b> 2/28/12		SCALE		SHT. 1 OF 1	
RELEASED BY <b>JIF</b> 2/29/12		<b>1X</b>			
TOLERANCE UNLESS NOTED OTHERWISE					
.XX +/- .010", .25 mm					
.XXX +/- .005", .13 mm					
HOLES +/- .003", .08 mm					
ANGLES +/- 0 DEG./30 MIN.					

Label placed on top of unit

