

FCC Test Report

FCC ID : IPH-02324
Equipment : Head Unit
Model No. : 884B
Brand Name : FUSION
Applicant : Garmin International
Address : 1200 E. 151st Street Olathe, KS 66062
Standard : 47 CFR FCC Part 15.247
Received Date : Feb. 02, 2016
Tested Date : Feb. 03 ~ Feb. 17, 2016

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	9
1.3	Test Setup Chart	9
1.4	The Equipment List	10
1.5	Test Standards	11
1.6	Measurement Uncertainty	11
2	TEST CONFIGURATION	12
2.1	Testing Condition	12
2.2	The Worst Test Modes and Channel Details	12
3	TRANSMITTER TEST RESULTS.....	13
3.1	6dB and Occupied Bandwidth	13
3.2	RF Output Power.....	16
3.3	Power Spectral Density	18
3.4	Unwanted Emissions into Restricted Frequency Bands	20
3.5	Emissions in Non-Restricted Frequency Bands.....	48
4	TEST LABORATORY INFORMATION	61

Release Record

Report No.	Version	Description	Issued Date
FR620201AC	Rev. 01	Initial issue	Mar. 11, 2016

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	Note	N/A
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 2390.00MHz 72.97 (Margin -1.03dB) - PK	Pass
15.247(b)(3)	Maximum Output Power	Max Power [dBm]: 22.26	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass
Note: The EUT consumes DC power from battery, therefore this test is not required.			

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	Data Rate / MCS
2400-2483.5	b	2412-2462	1-11 [11]	1	1-11 Mbps
2400-2483.5	g	2412-2462	1-11 [11]	1	6-54 Mbps
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	1	MCS 0-7
2400-2483.5	n (HT40)	2422-2452	3-9 [7]	1	MCS 0-7

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.
 Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.
 Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

1.1.2 Antenna Details

Ant. No.	Type	Gain (dBi)	Connector	Remark
1	Chip	2.5	NA	---

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	DC 12V
-------------------	--------

1.1.4 Accessories & Support Units

Accessories	
No.	Equipment
1	GPS antenna, 0.6m
2	USB cable, 0.3m shielded without core
3	28 pin cable, 0.2m
4	16 pin cable, 0.2m
5	10 pin cable, 0.2m
6	6 pin cable, 0.2m
7	mounting bracket
Support Units	
1	DC cable, 3.25m non-shielded without core
2	FM antenna, 4.95m non-shielded without core
3	Audio cable, 1.63m (x4) non-shielded without core
4	HDMI cable, 1.48m shielded with two cores
5	Micro SD card (Brand: ADATA ; Capacity: 8GB)

Note: Support units were provided by applicant.

1.1.5 Channel List

Frequency band (MHz)		2400~2483.5	
802.11 b / g / n HT20		802.11n HT40	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	3	2422
2	2417	4	2427
3	2422	5	2432
4	2427	6	2437
5	2432	7	2442
6	2437	8	2447
7	2442	9	2452
8	2447	---	---
9	2452	---	---
10	2457	---	---
11	2462	---	---

1.1.6 Test Tool and Duty Cycle

Test Tool	WIFI Test, V0.23		
Duty Cycle and Duty Factor	Mode	Duty cycle (%)	Duty factor (dB)
	11b	100.00%	0.00
	11g	96.57%	0.15
	HT20	93.81%	0.28
	HT40	87.31%	0.59


1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)	Power Set
11b	2412	24
11b	2437	24
11b	2462	22
11g	2412	24
11g	2437	24
11g	2462	21
HT20	2412	21
HT20	2437	24
HT20	2462	19
HT40	2422	18
HT40	2437	24
HT40	2452	19

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Signal cable / Length (m)
1	Battery	YUASA	115E41R	---	---

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	Radiated Emission				
Test Site	966 chamber 2 / (03CH02-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101499	Dec. 17, 2015	Dec. 16, 2016
Receiver	R&S	ESR3	101657	Jan. 12, 2016	Jan. 11, 2017
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-523	Nov. 09, 2015	Nov. 08, 2016
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1095	Oct. 07, 2015	Oct. 06, 2016
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 04, 2015	Nov. 03, 2016
Loop Antenna	R&S	HFH2-Z2	11900	Nov. 16, 2015	Nov. 15, 2016
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 10, 2015	Dec. 09, 2016
Preamplifier	Burgeon	BPA-530	100218	Nov. 03, 2015	Nov. 02, 2016
Preamplifier	Agilent	83017A	MY39501309	Sep. 22, 2015	Sep. 21, 2016
Preamplifier	EMC	EMC184045B	980192	Sep. 01, 2015	Aug. 31, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16140/4	Dec. 10, 2015	Dec. 09, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16018/4	Dec. 10, 2015	Dec. 09, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16015/4	Dec. 10, 2015	Dec. 09, 2016
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-003	Dec. 10, 2015	Dec. 09, 2016
LF cable 10M	EMCC	CFD400-E	CFD400-001	Dec. 10, 2015	Dec. 09, 2016
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Dec. 13, 2015	Dec. 12, 2016
Power Meter	Anritsu	ML2495A	1241002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor	Anritsu	MA2411B	1207366	Sep. 21, 2015	Sep. 20, 2016
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA

Note: Calibration Interval of instruments listed above is one year.

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2013

FCC KDB 558074 D01 DTS Meas Guidance v03r04

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.134 Hz
Conducted power	± 0.808 dB
Power density	± 0.463 dB
Conducted emission	± 2.670 dB
AC conducted emission	± 2.90 dB
Radiated emission ≤ 1 GHz	± 3.87 dB
Radiated emission > 1 GHz	± 5.60 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
Radiated Emissions	03CH02-WS	21°C / 65%	Aska Huang Warren Lee
RF Conducted	TH01-WS	21°C / 64%	Alex Huang

➤ FCC site registration No.: 657002

➤ IC site registration No.: 10807A-2

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate	Test Configuration
Radiated Emissions ≤1GHz	11g	2412	6 Mbps	---
Radiated Emissions >1GHz	11b	2412 / 2437 / 2462	1 Mbps	---
Maximum Output Power	11g	2412 / 2437 / 2462	6 Mbps	
6dB bandwidth	HT20	2412 / 2437 / 2462	MCS 0	
Power spectral density	HT40	2422 / 2437 / 2452	MCS 0	

3 Transmitter Test Results

3.1 6dB and Occupied Bandwidth

3.1.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.1.2 Test Procedures


6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth


1. Set resolution bandwidth (RBW) = 1 MHz, Video bandwidth = 3 MHz.
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.1.3 Test Setup




3.1.4 Test Result of 6dB and Occupied Bandwidth

Modulation Mode	N _{TX}	Freq. (MHz)	6dB Bandwidth (MHz)				Limit (kHz)
			Chain 0	Chain 1	Chain 2	Chain 3	
11b	1	2412	10.09	---	---	---	500
11b	1	2437	10.09	---	---	---	500
11b	1	2462	9.04	---	---	---	500
11g	1	2412	15.13	---	---	---	500
11g	1	2437	15.07	---	---	---	500
11g	1	2462	15.83	---	---	---	500
HT20	1	2412	15.48	---	---	---	500
HT20	1	2437	15.13	---	---	---	500
HT20	1	2462	15.71	---	---	---	500
HT40	1	2422	35.13	---	---	---	500
HT40	1	2437	35.13	---	---	---	500
HT40	1	2452	35.36	---	---	---	500



Modulation Mode	N _{TX}	Freq. (MHz)	99% Occupied Bandwidth (MHz)			
			Chain 0	Chain 1	Chain 2	Chain 3
11b	1	2412	18.57	---	---	---
11b	1	2437	17.70	---	---	---
11b	1	2462	13.18	---	---	---
11g	1	2412	18.60	---	---	---
11g	1	2437	19.29	---	---	---
11g	1	2462	17.05	---	---	---
HT20	1	2412	18.49	---	---	---
HT20	1	2437	19.74	---	---	---
HT20	1	2462	17.81	---	---	---
HT40	1	2422	36.68	---	---	---
HT40	1	2437	38.20	---	---	---
HT40	1	2452	36.70	---	---	---



3.2 RF Output Power

3.2.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.


- Antenna gain \leq 6dBi, no any corresponding reduction is in output power limit.
- Antenna gain $>$ 6dBi
 - Non Fixed, point to point operations.
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB
 - Fixed, point to point operations
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

3.2.2 Test Procedures

- Maximum Peak Conducted Output Power
 - Spectrum analyzer**
 1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
 2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
 3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.
 - Power meter**
 1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- Maximum Conducted Output Power (For reference only)
 - Power meter**
 1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.2.3 Test Setup



3.2.4 Test Result of Maximum Output Power

Modulation Mode	N _{TX}	Freq. (MHz)	Peak conducted Output Power (dBm)							Ant. Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3	Total Power (mW)	Total Power (dBm)	Limit (dBm)			
11b	1	2412	22.09	---	---	---	161.808	22.09	30.00	2.50	24.59	36.00
11b	1	2437	22.10	---	---	---	162.181	22.10	30.00	2.50	24.60	36.00
11b	1	2462	20.55	---	---	---	113.501	20.55	30.00	2.50	23.05	36.00
11g	1	2412	22.26	---	---	---	168.267	22.26	30.00	2.50	24.76	36.00
11g	1	2437	22.09	---	---	---	161.808	22.09	30.00	2.50	24.59	36.00
11g	1	2462	21.62	---	---	---	145.211	21.62	30.00	2.50	24.12	36.00
HT20	1	2412	22.26	---	---	---	168.267	22.26	30.00	2.50	24.76	36.00
HT20	1	2437	22.05	---	---	---	160.325	22.05	30.00	2.50	24.55	36.00
HT20	1	2462	21.71	---	---	---	148.252	21.71	30.00	2.50	24.21	36.00
HT40	1	2422	21.96	---	---	---	157.036	21.96	30.00	2.50	24.46	36.00
HT40	1	2437	22.00	---	---	---	158.489	22.00	30.00	2.50	24.50	36.00
HT40	1	2452	21.63	---	---	---	145.546	21.63	30.00	2.50	24.13	36.00

Modulation Mode	N _{TX}	Freq. (MHz)	Conducted (Average) Output Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3			
11b	1	2412	20.92	---	---	---	123.595	20.92	---
11b	1	2437	21.10	---	---	---	128.825	21.10	---
11b	1	2462	18.14	---	---	---	65.163	18.14	---
11g	1	2412	18.16	---	---	---	65.464	18.16	---
11g	1	2437	18.38	---	---	---	68.865	18.38	---
11g	1	2462	16.32	---	---	---	42.855	16.32	---
HT20	1	2412	17.69	---	---	---	58.749	17.69	---
HT20	1	2437	18.33	---	---	---	68.077	18.33	---
HT20	1	2462	14.88	---	---	---	30.761	14.88	---
HT40	1	2422	14.63	---	---	---	29.040	14.63	---
HT40	1	2437	18.33	---	---	---	68.077	18.33	---
HT40	1	2452	14.61	---	---	---	28.907	14.61	---

Note: Conducted average output power is for reference only.

3.3 Power Spectral Density


3.3.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.3.2 Test Procedures


- Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
 1. Set the RBW = 3kHz, VBW = 10kHz.
 2. Detector = Peak, Sweep time = auto couple.
 3. Trace mode = max hold, allow trace to fully stabilize.
 4. Use the peak marker function to determine the maximum amplitude level.
- Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
 1. Set the RBW = 100kHz, VBW = 300 kHz.
 2. Detector = RMS, Sweep time = auto couple.
 3. Perform the measurement over a single sweep.
 4. Use the peak marker function to determine the maximum amplitude level.

3.3.3 Test Setup



3.3.4 Test Result of Power Spectral Density

Modulation Mode	N _{TX}	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
11b	1	2412	-2.09	8.00
11b	1	2437	-2.95	8.00
11b	1	2462	-4.82	8.00
11g	1	2412	-6.79	8.00
11g	1	2437	-4.71	8.00
11g	1	2462	-8.38	8.00
HT20	1	2412	-6.84	8.00
HT20	1	2437	-7.55	8.00
HT20	1	2462	-10.47	8.00
HT40	1	2422	-13.62	8.00
HT40	1	2437	-10.92	8.00
HT40	1	2452	-12.87	8.00



3.4 Unwanted Emissions into Restricted Frequency Bands

3.4.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.4.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.4.3 Test Setup


Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



3.4.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	11g	Test Freq. (MHz)	2412						
Polarization	Horizontal								
									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	161.92	31.32	43.50	-12.18	43.08	-11.76	Peak	---	---
2	269.59	30.83	46.00	-15.17	42.85	-12.02	Peak	---	---
3	378.23	31.97	46.00	-14.03	41.22	-9.25	Peak	---	---
4	485.90	32.61	46.00	-13.39	39.41	-6.80	Peak	---	---
5	594.54	29.49	46.00	-16.51	34.18	-4.69	Peak	---	---
6	647.89	30.64	46.00	-15.36	34.65	-4.01	Peak	---	---
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m). Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.</p>									

Modulation	11g	Test Freq. (MHz)	2412
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	172.59	29.04	43.50	-14.46	41.35	-12.31	Peak	---	---
2	269.59	26.86	46.00	-19.14	38.88	-12.02	Peak	---	---
3	378.23	27.65	46.00	-18.35	36.90	-9.25	Peak	---	---
4	485.90	32.18	46.00	-13.82	38.98	-6.80	Peak	---	---
5	540.22	30.07	46.00	-15.93	35.88	-5.81	Peak	---	---
6	647.89	30.24	46.00	-15.76	34.25	-4.01	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.4.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11b

Modulation	11b	Test Freq. (MHz)	2412						
Polarization	Horizontal								
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	52.43	54.00	-1.57	55.49	-3.06	Average	141	43
2	2390.00	63.27	74.00	-10.73	66.33	-3.06	Peak	141	43
3	4824.00	36.22	54.00	-17.78	31.96	4.26	Average	320	241
4	4824.00	47.46	74.00	-26.54	43.20	4.26	Peak	320	241
5	12060.00	43.15	54.00	-10.85	29.30	13.85	Average	141	444
6	12060.00	56.26	74.00	-17.74	42.41	13.85	Peak	141	444
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	11b	Test Freq. (MHz)	2412
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	45.42	54.00	-8.58	48.48	-3.06	Average	133	4
2	2390.00	53.32	74.00	-20.68	56.38	-3.06	Peak	133	4
3	4824.00	35.16	54.00	-18.84	30.90	4.26	Average	129	160
4	4824.00	45.87	74.00	-28.13	41.61	4.26	Peak	129	160
5	12060.00	43.37	54.00	-10.63	29.52	13.85	Average	328	254
6	12060.00	56.44	74.00	-17.56	42.59	13.85	Peak	328	254

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2437
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	41.11	54.00	-12.89	44.17	-3.06	Average	102	45
2	2390.00	52.03	74.00	-21.97	55.09	-3.06	Peak	102	45
3	2483.50	50.67	54.00	-3.33	53.36	-2.69	Average	102	45
4	2483.50	57.44	74.00	-16.56	60.13	-2.69	Peak	102	45
5	4860.30	33.60	54.00	-20.40	29.25	4.35	Average	135	221
6	4860.30	46.66	74.00	-27.34	42.31	4.35	Peak	135	221
7	4874.00	32.93	54.00	-21.07	28.53	4.40	Average	124	357
8	4874.00	44.66	74.00	-29.34	40.26	4.40	Peak	124	357
9	7311.00	41.89	54.00	-12.11	32.68	9.21	Average	305	117
10	7311.00	52.67	74.00	-21.33	43.46	9.21	Peak	305	117

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2437
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	40.43	54.00	-13.57	43.49	-3.06	Average	162	66
2	2390.00	49.31	74.00	-24.69	52.37	-3.06	Peak	162	66
3	2483.50	45.79	54.00	-8.21	48.48	-2.69	Average	162	66
4	2483.50	53.62	74.00	-20.38	56.31	-2.69	Peak	162	66
5	4860.30	33.28	54.00	-20.72	28.93	4.35	Average	120	254
6	4860.30	46.56	74.00	-27.44	42.21	4.35	Peak	120	254
7	4874.00	38.54	54.00	-15.46	34.14	4.40	Average	320	196
8	4874.00	50.66	74.00	-23.34	46.26	4.40	Peak	320	196
9	7311.00	45.71	54.00	-8.29	36.50	9.21	Average	192	270
10	7311.00	55.73	74.00	-18.27	46.52	9.21	Peak	192	270

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2462
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	52.04	54.00	-1.96	54.73	-2.69	Average	100	47
2	2483.50	58.63	74.00	-15.37	61.32	-2.69	Peak	100	47
3	4924.00	39.63	54.00	-14.37	35.10	4.53	Average	177	350
4	4924.00	46.79	74.00	-27.21	42.26	4.53	Peak	177	350
5	7386.00	41.22	54.00	-12.78	31.83	9.39	Average	350	173
6	7386.00	51.66	74.00	-22.34	42.27	9.39	Peak	350	173

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2462
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	46.61	54.00	-7.39	49.30	-2.69	Average	197	117
2	2483.50	55.08	74.00	-18.92	57.77	-2.69	Peak	197	117
3	4924.00	40.27	54.00	-13.73	35.74	4.53	Average	196	161
4	4924.00	47.63	74.00	-26.37	43.10	4.53	Peak	196	161
5	7386.00	45.98	54.00	-8.02	36.59	9.39	Average	121	176
6	7386.00	54.64	74.00	-19.36	45.25	9.39	Peak	121	176

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.4.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11g

Modulation	11g	Test Freq. (MHz)	2412						
Polarization	Horizontal								
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	52.13	54.00	-1.87	55.19	-3.06	Average	186	281
2	2390.00	69.24	74.00	-4.76	72.30	-3.06	Peak	186	281
3	4824.00	34.52	54.00	-19.48	30.26	4.26	Average	231	140
4	4824.00	45.82	74.00	-28.18	41.56	4.26	Peak	231	140
5	12010.00	40.47	54.00	-13.53	26.60	13.87	Average	326	171
6	12010.00	54.08	74.00	-19.92	40.21	13.87	Peak	326	171
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	11g	Test Freq. (MHz)	2412
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	49.46	54.00	-4.54	52.52	-3.06	Average	221	216
2	2390.00	67.24	74.00	-6.76	70.30	-3.06	Peak	221	216
3	4824.00	34.46	54.00	-19.54	30.20	4.26	Average	288	170
4	4824.00	45.84	74.00	-28.16	41.58	4.26	Peak	288	170
5	12010.00	40.76	54.00	-13.24	26.89	13.87	Average	192	271
6	12010.00	53.76	74.00	-20.24	39.89	13.87	Peak	192	271

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2437
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	36.98	54.00	-17.02	40.04	-3.06	Average	100	48
2	2390.00	48.99	74.00	-25.01	52.05	-3.06	Peak	100	48
3	2483.50	38.07	54.00	-15.93	40.76	-2.69	Average	100	48
4	2483.50	49.10	74.00	-24.90	51.79	-2.69	Peak	100	48
5	4874.00	31.78	54.00	-22.22	27.38	4.40	Average	135	277
6	4874.00	43.65	74.00	-30.35	39.25	4.40	Peak	135	277
7	7311.00	36.10	54.00	-17.90	26.89	9.21	Average	241	133
8	7311.00	49.09	74.00	-24.91	39.88	9.21	Peak	241	133

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2437
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	35.35	54.00	-18.65	38.41	-3.06	Average	169	0
2	2390.00	47.07	74.00	-26.93	50.13	-3.06	Peak	169	0
3	2483.50	36.39	54.00	-17.61	39.08	-2.69	Average	169	0
4	2483.50	48.52	74.00	-25.48	51.21	-2.69	Peak	169	0
5	4874.00	31.25	54.00	-22.75	26.85	4.40	Average	282	157
6	4874.00	44.70	74.00	-29.30	40.30	4.40	Peak	282	157
7	7311.00	36.91	54.00	-17.09	27.70	9.21	Average	195	231
8	7311.00	49.48	74.00	-24.52	40.27	9.21	Peak	195	231

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2462
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	52.83	54.00	-1.17	55.52	-2.69	Average	100	47
2	2483.50	69.30	74.00	-4.70	71.99	-2.69	Peak	100	47
3	4924.00	34.83	54.00	-19.17	30.30	4.53	Average	248	302
4	4924.00	47.63	74.00	-26.37	43.10	4.53	Peak	248	302
5	7386.00	36.27	54.00	-17.73	26.88	9.39	Average	241	71
6	7386.00	47.97	74.00	-26.03	38.58	9.39	Peak	241	71

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2462
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	50.10	54.00	-3.90	52.79	-2.69	Average	256	57
2	2483.50	69.82	74.00	-4.18	72.51	-2.69	Peak	256	57
3	4924.00	34.81	54.00	-19.19	30.28	4.53	Average	218	174
4	4924.00	46.73	74.00	-27.27	42.20	4.53	Peak	218	174
5	7386.00	38.65	54.00	-15.35	29.26	9.39	Average	129	305
6	7386.00	48.33	74.00	-25.67	38.94	9.39	Peak	129	305

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.4.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20

Modulation	HT20	Test Freq. (MHz)	2412						
Polarization	Horizontal								
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	52.24	54.00	-1.76	55.30	-3.06	Average	100	47
2	2390.00	70.63	74.00	-3.37	73.69	-3.06	Peak	100	47
3	4824.00	34.55	54.00	-19.45	30.29	4.26	Average	338	271
4	4824.00	46.52	74.00	-27.48	42.26	4.26	Peak	338	271
5	12010.00	40.47	54.00	-13.53	26.60	13.87	Average	350	187
6	12010.00	52.12	74.00	-21.88	38.25	13.87	Peak	350	187

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2412
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	50.20	54.00	-3.80	53.26	-3.06	Average	221	216
2	2390.00	68.54	74.00	-5.46	71.60	-3.06	Peak	221	216
3	4824.00	34.44	54.00	-19.56	30.18	4.26	Average	269	178
4	4824.00	46.00	74.00	-28.00	41.74	4.26	Peak	269	178
5	12010.00	40.74	54.00	-13.26	26.87	13.87	Average	209	271
6	12010.00	53.94	74.00	-20.06	40.07	13.87	Peak	209	271

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.38	54.00	-15.62	41.44	-3.06	Average	100	49
2	2390.00	51.56	74.00	-22.44	54.62	-3.06	Peak	100	49
3	2483.50	38.68	54.00	-15.32	41.37	-2.69	Average	100	49
4	2483.50	51.65	74.00	-22.35	54.34	-2.69	Peak	100	49
5	4874.00	31.28	54.00	-22.72	26.88	4.40	Average	274	271
6	4874.00	43.30	74.00	-30.70	38.90	4.40	Peak	274	271
7	7311.00	38.47	54.00	-15.53	29.26	9.21	Average	174	142
8	7311.00	49.59	74.00	-24.41	40.38	9.21	Peak	174	142

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	36.32	54.00	-17.68	39.38	-3.06	Average	170	2
2	2390.00	47.49	74.00	-26.51	50.55	-3.06	Peak	170	2
3	2483.50	37.39	54.00	-16.61	40.08	-2.69	Average	170	2
4	2483.50	48.58	74.00	-25.42	51.27	-2.69	Peak	170	2
5	4874.00	30.88	54.00	-23.12	26.48	4.40	Average	218	160
6	4874.00	45.66	74.00	-28.34	41.26	4.40	Peak	218	160
7	7311.00	36.47	54.00	-17.53	27.26	9.21	Average	200	182
8	7311.00	50.89	74.00	-23.11	41.68	9.21	Peak	200	182

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	52.87	54.00	-1.13	55.56	-2.69	Average	100	47
2	2483.50	72.16	74.00	-1.84	74.85	-2.69	Peak	100	47
3	4924.00	33.43	54.00	-20.57	28.90	4.53	Average	267	187
4	4924.00	44.79	74.00	-29.21	40.26	4.53	Peak	267	187
5	7386.00	37.97	54.00	-16.03	28.58	9.39	Average	228	174
6	7386.00	48.38	74.00	-25.62	38.99	9.39	Peak	228	174

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	49.10	54.00	-4.90	51.79	-2.69	Average	256	57
2	2483.50	69.60	74.00	-4.40	72.29	-2.69	Peak	256	57
3	4924.00	34.63	54.00	-19.37	30.10	4.53	Average	209	138
4	4924.00	46.33	74.00	-27.67	41.80	4.53	Peak	209	138
5	7386.00	38.52	54.00	-15.48	29.13	9.39	Average	130	295
6	7386.00	48.18	74.00	-25.82	38.79	9.39	Peak	130	295

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.4.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT40

Modulation	HT40	Test Freq. (MHz)	2422						
Polarization	Horizontal								
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	48.52	54.00	-5.48	51.58	-3.06	Average	146	47
2	2390.00	72.97	74.00	-1.03	76.03	-3.06	Peak	146	47
3	4844.00	31.91	54.00	-22.09	27.59	4.32	Average	263	4
4	4844.00	45.22	74.00	-28.78	40.90	4.32	Peak	263	4
5	12110.00	41.08	54.00	-12.92	27.25	13.83	Average	347	189
6	12110.00	54.63	74.00	-19.37	40.80	13.83	Peak	347	189
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	HT40	Test Freq. (MHz)	2422
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	45.17	54.00	-8.83	48.23	-3.06	Average	195	113
2	2390.00	70.38	74.00	-3.62	73.44	-3.06	Peak	195	113
3	4844.00	31.21	54.00	-22.79	26.89	4.32	Average	293	106
4	4844.00	44.58	74.00	-29.42	40.26	4.32	Peak	293	106
5	12110.00	39.88	54.00	-14.12	26.05	13.83	Average	179	216
6	12110.00	54.08	74.00	-19.92	40.25	13.83	Peak	179	216

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	2437
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	48.48	54.00	-5.52	51.54	-3.06	Average	137	46
2	2390.00	64.42	74.00	-9.58	67.48	-3.06	Peak	137	46
3	2483.50	48.50	54.00	-5.50	51.19	-2.69	Average	137	46
4	2483.50	61.48	74.00	-12.52	64.17	-2.69	Peak	137	46
5	4874.00	31.28	54.00	-22.72	26.88	4.40	Average	168	238
6	4874.00	44.99	74.00	-29.01	40.59	4.40	Peak	168	238
7	7311.00	38.47	54.00	-15.53	29.26	9.21	Average	295	135
8	7311.00	48.79	74.00	-25.21	39.58	9.21	Peak	295	135

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	2437
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	45.93	54.00	-8.07	48.99	-3.06	Average	136	113
2	2390.00	61.21	74.00	-12.79	64.27	-3.06	Peak	136	113
3	2483.50	46.03	54.00	-7.97	48.72	-2.69	Average	136	113
4	2483.50	60.79	74.00	-13.21	63.48	-2.69	Peak	136	113
5	4874.00	33.99	54.00	-20.01	29.59	4.40	Average	209	328
6	4874.00	42.89	74.00	-31.11	38.49	4.40	Peak	209	328
7	7311.00	38.19	54.00	-15.81	28.98	9.21	Average	263	147
8	7311.00	49.47	74.00	-24.53	40.26	9.21	Peak	263	147

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	2452
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	52.65	54.00	-1.35	55.34	-2.69	Average	100	52
2	2483.50	72.52	74.00	-1.48	75.21	-2.69	Peak	100	52
3	4904.00	32.07	54.00	-21.93	27.59	4.48	Average	248	171
4	4904.00	43.46	74.00	-30.54	38.98	4.48	Peak	248	171
5	7356.00	37.91	54.00	-16.09	28.60	9.31	Average	326	219
6	7356.00	48.06	74.00	-25.94	38.75	9.31	Peak	326	219

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	2452
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	49.05	54.00	-4.95	51.74	-2.69	Average	159	71
2	2483.50	68.64	74.00	-5.36	71.33	-2.69	Peak	159	71
3	4904.00	31.74	54.00	-22.26	27.26	4.48	Average	157	174
4	4904.00	44.74	74.00	-29.26	40.26	4.48	Peak	157	174
5	7356.00	37.61	54.00	-16.39	28.30	9.31	Average	271	274
6	7356.00	47.59	74.00	-26.41	38.28	9.31	Peak	271	274

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.5 Emissions in Non-Restricted Frequency Bands

3.5.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz

3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

Emission level measurement


1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level


3.5.4 Test Setup




3.5.5 Unwanted Emissions into Non-Restricted Frequency Bands


802.11b










802.11g










802.11n HT20









802.11n HT40







4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan,
R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd
St., Kwei Shan Hsiang, Tao Yuan
Hsien 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan Hsiang, Tao Yuan
Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==