



**ROGERS LABS, INC.**

4405 West 259<sup>th</sup> Terrace  
Louisburg, KS 66053  
Phone / Fax (913) 837-3214

CFR47, PART 15C - Intentional Radiators  
CFR47 Paragraph 15.249 and  
Industry Canada RSS-GEN Issue 5 and RSS-210 Issue 10  
**Application For Grant of Certification**

**Model: A04158**

2402-2480 MHz (DXX)  
Low Power Digital Transmitter

**FCC ID: IPH-04158**

**IC: 1792A-04158**

**Garmin International, Inc.**

1200 East 151st Street  
Olathe, KS 66062

FCC Designation: US5305  
ISED Registration: 3041A-1

Test Report Number: 210307

Test Date: March 7, 2021

Authorized Signatory: *Scot D Rogers*  
Scot D. Rogers

This report shall not be reproduced except in full, without the written approval of the laboratory. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Rogers Labs, Inc.  
4405 West 259<sup>th</sup> Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214  
Revision 1

Garmin International, Inc.  
Model: A04158  
Test: 210307  
Test to: CFR47 15C, RSS-Gen RSS-247  
File: A04158 DXX TstRpt 210307

SN's: 3354564362 / 3354564378  
FCC ID: IPH-04158  
IC: 1792A-04158  
Date: June 17, 2021  
Page 1 of 57

## Table of Contents

<b>TABLE OF CONTENTS.....</b>	<b>2</b>
<b>REVISIONS.....</b>	<b>4</b>
<b>EXECUTIVE SUMMARY .....</b>	<b>5</b>
<b>OPINION / INTERPRETATION OF RESULTS .....</b>	<b>5</b>
<b>EQUIPMENT TESTED.....</b>	<b>6</b>
<b>Equipment Operational Modes.....</b>	<b>7</b>
<b>Equipment Function .....</b>	<b>8</b>
<b>Equipment Configuration.....</b>	<b>9</b>
<b>APPLICATION FOR CERTIFICATION.....</b>	<b>10</b>
<b>APPLICABLE STANDARDS.....</b>	<b>11</b>
<b>EQUIPMENT TESTING PROCEDURES .....</b>	<b>11</b>
<b>AC Line Conducted Emission Test Procedure .....</b>	<b>11</b>
<b>Radiated Emission Test Procedure.....</b>	<b>11</b>
<b>Antenna Port Conducted Emission Test Procedure.....</b>	<b>12</b>
Diagram 1 Test arrangement for Conducted emissions .....	13
Diagram 2 Test arrangement for radiated emissions of tabletop equipment.....	14
Diagram 3 Test arrangement for radiated emissions tested on Open Area Test Site (OATS) .....	15
Diagram 4 Test arrangement for Antenna Port Conducted emissions .....	16
<b>TEST SITE LOCATIONS .....</b>	<b>16</b>
<b>UNITS OF MEASUREMENTS .....</b>	<b>17</b>
<b>ENVIRONMENTAL CONDITIONS.....</b>	<b>17</b>
<b>STATEMENT OF MODIFICATIONS AND DEVIATIONS .....</b>	<b>17</b>
<b>INTENTIONAL RADIATORS.....</b>	<b>18</b>

**Antenna Requirements .....18**

**Restricted Bands of Operation.....18**

Table 1 Radiated Emissions in Restricted Frequency Bands Data Mode 1 BT BR.....19

Table 2 Radiated Emissions in Restricted Frequency Bands Data Mode 2 BT 2EDR .....20

Table 3 Radiated Emissions in Restricted Frequency Bands Data Mode 3 BT 3EDR .....21

Table 4 Radiated Emissions in Restricted Frequency Bands Data Mode 4 BT BLE .....22

**Summary of Results for Radiated Emissions in Restricted Bands .....22**

**AC Line Conducted EMI Procedure .....23**

Figure 1 AC Line Conducted emissions of EUT line 1 (EUT – AC Adapter) .....24

Figure 2 AC Line Conducted emissions of EUT line 2 (EUT – AC Adapter) .....24

Figure 3 AC Line Conducted emissions of EUT line 1 (EUT – Computer).....25

Figure 4 AC Line Conducted emissions of EUT line 2 (EUT – Computer).....25

Table 5 AC Line Conducted Emissions Data L1 (EUT – AC Adapter) .....26

Table 6 AC Line Conducted Emissions Data L2 ( EUT – AC Adapter) .....26

Table 7 AC Line Conducted Emissions Data L1 (EUT – Computer).....27

Table 8 AC Line Conducted Emissions Data L2 ( EUT – Computer).....27

**Summary of Results for AC Line Conducted Emissions Results.....28**

**General Radiated Emissions Procedure.....28**

Table 9 General Radiated Emissions Data .....29

**Summary of Results for General Radiated Emissions .....29**

**Operation in the Band 2400 – 2483.5 MHz .....30**

Figure 5 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 1 BT BR .....31

Figure 6 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 2 BT 2EDR.....32

Figure 7 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 3 BT 3EDR.....33

Figure 8 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 4 BT BLE .....34

Figure 9 Plot of Transmitter Emissions Low Band Edge Mode 1 BT BR.....35

Figure 10 Plot of Transmitter Emissions Low Band Edge Mode 2 BT 2EDR .....36

Figure 11 Plot of Transmitter Emissions Low Band Edge Mode 3 BT 3EDR .....37

Figure 12 Plot of Transmitter Emissions Low Band Edge Mode 4 BT BLE.....38

Figure 13 Plot of Transmitter Emissions High Band Edge Mode 1 BT BR .....39

Figure 14 Plot of Transmitter Emissions High Band Edge Mode 2 BT 2EDR .....40

Figure 15 Plot of Transmitter Emissions High Band Edge Mode 3 BR 2EDR .....41

Figure 16 Plot of Transmitter Emissions High Band Edge Mode 4 BT BLE .....42

Figure 17 Plot of Transmitter Emissions 99% Occupied Bandwidth Mode 1 BT BR.....43

Figure 18 Plot of Transmitter Emissions 99% Occupied Bandwidth Mode 2 BT 2EDR .....44

Figure 19 Plot of Transmitter Emissions 99% Occupied Bandwidth Mode 3 BT 3EDR .....45

Figure 20 Plot of Transmitter Emissions 99% Occupied Bandwidth Mode 4 BT BLE .....46

**Transmitter Emissions Data.....47**

Table 10 Transmitter Radiated Emissions Mode 1 BT BR .....47

Table 11 Transmitter Radiated Emissions Mode 2 BT 2EDR .....48

Table 12 Transmitter Radiated Emissions Mode 3 BT 3EDR .....49

Table 13 Transmitter Radiated Emissions Mode 4 BT BLE .....50

**Summary of Results for Transmitter Radiated Emissions of Intentional Radiator.....51**

**ANNEX..... 52**

**Annex A Measurement Uncertainty Calculations.....53**

**Annex B Test Equipment.....54**

**Annex C Rogers Qualifications .....56**

**Annex D Laboratory Certificate of Accreditation.....57**

## Revisions

Revision 1 Issued June 17, 2021

## Executive Summary

License Exempt Digital Transmission System Intentional Radiator operating under Code of Federal Regulations Title 47 (CFR47) Paragraph 15.249 and Industry Canada RSS-210 Issue 10 and RSS-GEN Issue 5, low power digital device transmitter operations in the 2400 – 2483.5 MHz frequency band.

Name of Applicant: Garmin International, Inc.  
1200 East 151st Street  
Olathe, KS 66062

M/N: A04158

FCC ID: IPH-04158 IC: 1792A-04158

Operating Frequency Range: 2402-2480 MHz

Operational communication modes

Mode	Peak Power (dB $\mu$ V/m@3m)	Average power (dB $\mu$ V/m@3m)	99% OBW (kHz)
Mode 1, BT BR (GFSK)	97.8	86.4	819
Mode 2, BT 2EDR ( $\pi/4$ -DQPSK)	97.1	83.0	1,160
Mode 3, BT 3EDR (8DPSK)	97.0	83.0	1,184
Mode 4, BT BLE (GMSK)	97.3	91.7	1,029

This report addresses EUT Operation as Low Power Device using transmitter modes 1, 2, 3, and 4

## Opinion / Interpretation of Results

Tests Performed	Margin (dB)	Results
Restricted Bands CFR47 15.205, RSS-210 4.1	-5.5	Complies
Emissions as per CFR47 15.207, RSS-GEN 8.8	-5.4	Complies
Radiated Emissions CFR47 15.209, RSS-GEN 8.9	-5.3	Complies
Harmonic Emissions per CFR47 15.249, RSS-210 B.10	-5.1	Complies

## Equipment Tested

Model: A04158

Garmin International, Inc.  
1200 East 151st Street  
Olathe, KS 66062

Garmin Corporation  
No.68, Zhangshu 2nd Rd.  
Xizhi Dist., New Taipei City 221, Taiwan, R.O.C.

<u>Equipment</u>	<u>Model / PN</u>	<u>Serial Number</u>
EUT	A04158	3354564362
EUT2	A04158	3354564378
USB cable	320-01461-0x	N/A
USB cable	320-01462-0x	N/A
USB cable	320-01545-00	N/A
AC Adapter	320-00096-0x	N/A
DC Power Cable (CLA)	013-00970-00	N/A
DC Power Cable (CLA)	013-00971-00	N/A
Pass-thru Cable	320-01487-00	N/A
DC Power Cable (GTM-xx)	320-00683-xx	N/A
DC Power Cable (FMI-75)	010-12375-00	N/A
DC Power Cable (BC-30)	320-00092-xx	N/A
DC Power Supply	BK 1745	209C13
Laptop Computer	Latitude 7480	EFSPSN2
USB Printer	Dell 0N5819	5D1SL61

Test results in this report relate only to the items tested. Worst-case configuration data recorded in this report.

Software: 1.07, Antennas: 2.4 GHz PIFA (0 dBi), 5 GHz PIFA (5 dBi)

### Equipment Operational Modes

Mode	Transmitter Operation
1	BT BR (GFSK)
2	BT 2EDR ( $\pi/4$ -DQPSK)
3	BT 3EDR (8DPSK)
4	BT BLE (GMSK)
5	802.11b
6	802.11g
7	802.11n
8	U-NII-1 802.11a
9	U-NII-1 802.11n
10	U-NII-1 802.11n40
11	U-NII-1 802.11ac80
12	U-NII-3 802.11a
13	U-NII-3 802.11n
14	U-NII-3 802.11n40
15	U-NII-3 802.11ac80

## ***Equipment Function***


The EUT is a GPS receiver and display unit providing GPS reception and graphical display of location, navigation, and other information for the user. The GPS design offers use as a hand-held, transportation mounted or portable configuration for use in navigational applications. The design incorporates transmitter circuitry operating in the 2402-2480, 5150-5250, and 5725-5850 MHz frequency bands. The design provides cabled interface capabilities as presented below and wireless communications with compatible equipment. The EUT operates from direct current power provided from internal battery system or external power. External power may be supplied from installation vehicle via DC power adapter, AC/DC power adapter, or compliant USB interface as documented in this and other relevant reports. The EUT was arranged as described by the manufacturer emulating typical user configurations for testing purposes. The EUT offers no other interface connections than those presented in configuration options below as described by the manufacturer. For testing purposes, the EUT received power from both internal and external power options and configurations. During testing, the test system was configured to operate in a manufacturer defined mode. As requested by the manufacturer the equipment was tested for emissions compliance using the available configurations with the worse-case data presented. Test results in this report relate only to the products described in this report.

## Equipment Configuration

- 1) EUT operating on internal battery




- 2) EUT connected to (and powered by) AC adapter through USB cable




- 3) EUT connected to Computer USB port through cable assembly (GPN: 320-01545-00)




- 4) EUT connected to DC Through USB cable (320-01461-x0, 320-01462-x0) powered from CLA (013-00970-00)



- 5) EUT connected to DC through USB cable (320-01461-x0, 320-01462-x0) powered from CLA (013-00971-00)



- 6) EUT connected to DC through ugh (320-01487-00) to (GTM-70; 320-00683-20, GTM-60; 320-00683-00)



- 7) EUT connected to DC through (320-01487-00) to FMI cable assembly (GPNS: 010-12375-00)



- 8) EUT connected to DC through (320-01487-00) to BC30 cable assembly (GPN: 320-00092-xx)



## Application for Certification

- (1) Manufacturer: Garmin International, Inc.  
1200 East 151st Street  
Olathe, KS 66062
- (2) Identification: M/N: A04158  
FCC ID: IPH-04158 IC: 1792A-04158
- (3) Instruction Book:  
Refer to Exhibit for Instruction Manual.
- (4) Description of Circuit Functions:  
Refer to Exhibit of Operational Description.
- (5) Block Diagram with Frequencies:  
Refer to Exhibit of Operational Description.
- (6) Report of Measurements:  
Report of measurements follows in this Report.
- (7) Photographs: Construction, Component Placement, etc.:  
Refer to Exhibit for photographs of equipment.
- (8) List of Peripheral Equipment Necessary for operation. The equipment operates from internal battery power or external direct current power provided from authorized sources. The EUT provides USB-C interface port for power and communications as presented in this filing.
- (9) Transition Provisions of CFR47 15.37 are not requested.
- (10) Not Applicable. The unit is not a scanning receiver.
- (11) Not Applicable. The EUT does not operate in the 59 – 64 GHz frequency band.
- (12) The equipment is not software defined and this section is not applicable.
- (13) Applications for certification of U-NII devices in the 5.15-5.35 GHz and the 5.47-5.85 GHz bands must include a high-level operational description of the security procedures that control the radio frequency operating parameters and ensure that unauthorized modifications cannot be made. This requirement is not applicable to his DTS device.
- (14) Contain at least one drawing or photograph showing the test set-up for each of the required types of tests applicable to the device for which certification is requested. These drawings or photographs must show enough detail to confirm other information contained in the test report. Any photographs used must be focused originals without glare or dark spots and must clearly show the test configuration used. This information is provided in this report and Test Setup Exhibits provided with the application filing.

## Applicable Standards

The following information is submitted in accordance with the eCFR (electronic Code of Federal Regulations Title 47) (CFR47), dated March 7, 2021: Part 2, Subpart J, Part 15C Paragraph 15.249, RSS-210 Issue 10, and RSS-GEN Issue 5. Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in ANSI C63.10-2013. This report documents compliance for the EUT operations as Low Power Transmitter.

## Equipment Testing Procedures

### ***AC Line Conducted Emission Test Procedure***

Testing for the AC line-conducted emissions were performed as required in CFR47 15C, RSS-210 Issue 10, RSS-GEN and specified in ANSI C63.10-2013. The test setup, including the EUT, was arranged in the test configurations as presented during testing. The test configuration was placed on a 1 x 1.5-meter bench, 0.8 meters high located in a screen room. The power lines of the system were isolated from the power source using a standard LISN with a 50- $\mu$ Hy choke. EMI was coupled to the spectrum analyzer through a 0.1  $\mu$ F capacitor internal to the LISN. The LISN was positioned on the floor beneath the wooden bench supporting the EUT. The power lines and cables were draped over the back edge of the table. Refer to diagram one showing typical test arrangement and photographs in the test setup exhibit for EUT placement used during testing.


### ***Radiated Emission Test Procedure***

Radiated emissions testing was performed as required in CFR47 15C, RSS-210 Issue 10, RSS-GEN and specified in ANSI C63.10-2013. The EUT was placed on a rotating 0.9 x 1.2-meter platform, elevated as required above the ground plane at a distance of 3 meters from the FSM antenna. EMI energy was maximized by equipment placement permitting orientation in three orthogonal axes, raising, and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken and recorded. The frequency spectrum from 9 kHz to 25,000 MHz was searched for emissions during preliminary investigation. Refer to diagrams two and three showing typical test setup. Refer to photographs in the test setup exhibit for specific EUT placement during testing.

## ***Antenna Port Conducted Emission Test Procedure***


The EUT was assembled as required for operation and placed on a benchtop. This configuration provided the ability to connect test equipment to the provided test antenna port. Antenna Port conducted emissions testing was performed as presented in this document and specified in ANSI C63.10-2013. Testing was completed on a laboratory bench in a shielded room. The active antenna port of the device was connected to appropriate attenuation and the spectrum analyzer. Refer to diagram four showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.

## Diagram 1 Test arrangement for Conducted emissions



1. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long see (see 6.2.3.1).
2. I/O cables that are not connected to an accessory shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m (see 6.2.2).
3. EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50  $\Omega$  loads. LISN can be placed on top of, or immediately beneath, reference ground plane (see 6.2.2 and 6.2.3).
  - 3.1 All other equipment powered from additional LISN(s).
  - 3.2 Multiple-outlet strip can be used for multiple power cords of non-EUT equipment.
  - 3.3 LISN at least 80 cm from nearest part of EUT chassis.
4. Non-EUT components of EUT system being tested.
5. Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop (see 6.2.3.1).
6. Edge of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane (see 6.2.2 for options).
7. Antenna may be integral or detachable. If detachable, the antenna shall be attached for this test.

**Diagram 2 Test arrangement for radiated emissions of tabletop equipment**



1—A LISN is optional for radiated measurements between 30 MHz and 1000 MHz but not allowed for measurements below 30 MHz and above 1000 MHz (see 6.3.1). If used, then connect EUT to one LISN. Unused LISN measuring port connectors shall be terminated in 50  $\Omega$  loads. The LISN may be placed on top of, or immediately beneath, the reference ground plane (see 6.2.2 and 6.2.3.2).


1.1—LISN spaced at least 80 cm from the nearest part of the EUT chassis.

2—Antenna can be integral or detachable, depending on the EUT (see 6.3.1).

3—Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long (see 6.3.1).


4—For emission measurements at or below 1 GHz, the table height shall be 80 cm. For emission measurements above 1 GHz, the table height shall be 1.5 m for measurements, except as otherwise specified (see 6.3.1 and 6.6.3.1).

**Diagram 3 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)**



AC Line Conducted Emissions (0.150 -30 MHz)		
RBW	AVG. BW	Detector Function
9 kHz	30 kHz	Peak / Quasi Peak
Emissions (30-1000 MHz)		
RBW	AVG. BW	Detector Function
120 kHz	300 kHz	Peak / Quasi Peak
Emissions (Above 1000 MHz)		
RBW	Video BW	Detector Function
100 kHz	100 kHz	Peak
1 MHz	1 MHz	Peak / Average

**Diagram 4 Test arrangement for Antenna Port Conducted emissions**



### Test Site Locations

Conducted EMI      AC line conducted emissions testing performed in a shielded screen room located at Rogers Labs, Inc., 4405 West 259<sup>th</sup> Terrace, Louisburg, KS

Antenna port      Antenna port conducted emissions testing was performed in a shielded screen room located at Rogers Labs, Inc., 4405 West 259<sup>th</sup> Terrace, Louisburg, KS

Radiated EMI      The radiated emissions tests were performed at the 3 meters, Open Area Test Site (OATS) located at Rogers Labs, Inc., 4405 West 259<sup>th</sup> Terrace, Louisburg, KS

Registered Site information:    FCC Site: US5305, ISED: 3041A, CAB Identifier: US0096

NVLAP Accreditation      Lab code 200087-0

## Units of Measurements

Conducted EMI            Data presented in dB $\mu$ V; dB referenced to one microvolt

Antenna port Conducted            Data is in dBm; dB referenced to one milliwatt

Radiated EMI            Data presented in dB $\mu$ V/m; dB referenced to one microvolt per meter

Note: Radiated limit may be expressed for measurement in dB $\mu$ V/m when the measurement is taken at a distance of 3 or 10 meters. Data taken for this report was taken at distance of 3 meters.

Sample calculation demonstrates corrected field strength reading for Open Area Test Site using the measurement reading and correcting for receive antenna factor, cable losses, and amplifier gains.

Sample Calculation:

RFS = Radiated Field Strength, FSM = Field Strength Measured

A.F. = Receive antenna factor, Losses = attenuators/cable losses, Gain = amplification gains

RFS (dB $\mu$ V/m @ 3m) = FSM (dB $\mu$ V) + A.F. (dB/m) + Losses (dB) - Gain (dB)

## Environmental Conditions

Ambient Temperature            22.8° C

Relative Humidity            38 %

Atmospheric Pressure            1030.2 mb

## Statement of Modifications and Deviations

No modifications to the EUT were required for the equipment to demonstrate compliance with the CFR47 Part 15C, Industry Canada RSS-210 Issue 10, and RSS-GEN Issue 5 emission requirements. There were no deviations to the specifications.

## Intentional Radiators

The following information is submitted supporting compliance with the requirements of CFR47, Subpart C, paragraph 15.249, Industry Canada RSS-210 Issue 10, and RSS-GEN Issue 5.

### ***Antenna Requirements***

The EUT incorporates integral Planer Inverted F Antenna (PIFA) system. Production equipment offers no provision for connection to alternate antenna system. The antenna connection point complies with the unique antenna connection requirements. There are no deviations or exceptions to the specification.

### ***Restricted Bands of Operation***

Spurious emissions falling in the restricted frequency bands of operation were measured at the OATS. The EUT utilizes frequency, determining circuitry, which generates harmonics falling in the restricted bands. Emissions were investigated at the OATS, using appropriate antennas or pyramidal horns, amplification stages, and a spectrum analyzer. Peak and average amplitudes of frequencies above 1000 MHz were compared to the required limits with worst-case data presented below. Test procedures of ANSI C63.10-2013 were used during testing. No other significant emission was observed which fell into the restricted bands of operation. Computed emission values consider the received radiated field strength, receive antenna correction factor, amplifier gain stage, and test system cable losses.

**Table 1 Radiated Emissions in Restricted Frequency Bands Data Mode 1 BT BR**

Frequency in MHz	Horizontal Peak (dB $\mu$ V/m)	Horizontal Average (dB $\mu$ V/m)	Vertical Peak (dB $\mu$ V/m)	Vertical Average (dB $\mu$ V/m)	Limit @ 3m (dB $\mu$ V/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	46.7	34.2	44.9	31.7	54.0	-19.8	-22.3
2483.5	46.9	32.5	45.6	32.0	54.0	-21.5	-22.0
4804.0	49.2	36.1	50.2	37.4	54.0	-17.9	-16.6
4882.0	54.3	41.5	50.1	37.4	54.0	-12.5	-16.6
4960.0	53.5	40.6	49.9	36.5	54.0	-13.4	-17.5
7206.0	54.2	41.6	54.8	41.7	54.0	-12.4	-12.3
7323.0	55.2	42.2	54.8	42.0	54.0	-11.8	-12.0
7440.0	55.5	42.4	54.9	42.2	54.0	-11.6	-11.8
12010.0	61.3	48.5	61.2	48.1	54.0	-5.5	-5.9
12205.0	60.2	47.2	59.7	47.1	54.0	-6.8	-6.9
12400.0	60.7	47.5	60.3	47.6	54.0	-6.5	-6.4

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

**Table 2 Radiated Emissions in Restricted Frequency Bands Data Mode 2 BT 2EDR**

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	44.3	31.7	45.3	31.7	54.0	-22.3	-22.3
2483.5	45.3	32.4	44.5	32.1	54.0	-21.6	-21.9
4804.0	52.7	38.1	50.0	36.6	54.0	-15.9	-17.4
4882.0	53.5	38.9	50.2	36.4	54.0	-15.1	-17.6
4960.0	52.9	38.1	49.8	36.2	54.0	-15.9	-17.8
7206.0	55.1	41.7	54.7	41.6	54.0	-12.3	-12.4
7323.0	55.5	42.1	54.8	42.0	54.0	-11.9	-12.0
7440.0	55.3	42.3	55.0	42.2	54.0	-11.7	-11.8
12010.0	60.8	48.1	61.5	48.5	54.0	-5.9	-5.5
12205.0	60.1	47.1	60.4	47.2	54.0	-6.9	-6.8
12400.0	60.4	47.6	60.4	47.6	54.0	-6.4	-6.4

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

**Table 3 Radiated Emissions in Restricted Frequency Bands Data Mode 3 BT 3EDR**

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	45.1	31.7	44.4	31.7	54.0	-22.3	-22.3
2483.5	45.3	32.4	45.4	32.1	54.0	-21.6	-21.9
4804.0	51.9	38.0	49.6	36.4	54.0	-16.0	-17.6
4882.0	53.1	38.8	50.1	36.4	54.0	-15.2	-17.6
4960.0	52.5	37.9	49.9	36.1	54.0	-16.1	-17.9
7206.0	54.9	41.7	54.5	41.6	54.0	-12.3	-12.4
7323.0	55.3	42.1	55.7	42.0	54.0	-11.9	-12.0
7440.0	54.8	42.3	54.8	42.2	54.0	-11.7	-11.8
12010.0	61.2	48.1	60.8	48.1	54.0	-5.9	-5.9
12205.0	60.3	46.9	60.2	47.1	54.0	-7.1	-6.9
12400.0	60.7	47.6	60.5	47.6	54.0	-6.4	-6.4

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

**Table 4 Radiated Emissions in Restricted Frequency Bands Data Mode 4 BT BLE**

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	44.5	31.8	44.3	31.7	54.0	-22.2	-22.3
2483.5	46.4	32.8	45.7	32.2	54.0	-21.2	-21.8
4804.0	52.4	40.7	50.1	36.5	54.0	-13.3	-17.5
4884.0	53.7	43.4	50.4	37.7	54.0	-10.6	-16.3
4960.0	53.4	42.0	50.3	37.4	54.0	-12.0	-16.6
7206.0	54.9	41.7	54.7	41.6	54.0	-12.3	-12.4
7326.0	55.3	42.3	54.8	42.1	54.0	-11.7	-11.9
7440.0	55.2	42.5	55.3	42.2	54.0	-11.5	-11.8
12010.0	61.3	48.1	61.0	48.1	54.0	-5.9	-5.9
12210.0	59.9	47.2	59.5	47.2	54.0	-6.8	-6.8
12400.0	60.8	47.6	60.7	47.6	54.0	-6.4	-6.4

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

**Summary of Results for Radiated Emissions in Restricted Bands**

The EUT demonstrated compliance with the radiated emissions requirements of CFR47 Part 15C and RSS-210 Issue 10 Intentional Radiator requirements. The EUT demonstrated a worst-case minimum margin of -5.5 dB below the emissions requirements in restricted frequency bands. Peak, Quasi-peak, and average amplitudes were checked for compliance with the regulations. Worst-case emissions are reported with other emissions found in the restricted frequency bands at least 20 dB below the requirements.

## **AC Line Conducted EMI Procedure**


The EUT was arranged in typical AC power equipment configurations for AC Line Conducted emissions testing. Testing was performed with the EUT placed on a 1 x 1.5-meter wooden bench 80 cm above the conducting ground plane, floor of a screen room. The bench was positioned 40 cm away from the wall of the screen room. The LISN was positioned on the floor of the screen room 80-cm from the rear of the EUT. Testing for the AC line-conducted emissions were the procedures of ANSI C63.10-2013 paragraph 6. The AC power adapter or CPU providing power to the EUT was connected to the LISN for AC line-conducted emissions testing. A second LISN was positioned on the floor of the screen room 80-cm from the rear of the supporting equipment of the EUT. All power cords except those providing power to the EUT were then powered from the second LISN. EMI was coupled to the spectrum analyzer through a 0.1  $\mu$ F capacitor, internal to the LISN. Power line conducted emissions testing was carried out individually for each current carrying conductor of the EUT. The excess length of lead between the system and the LISN receptacle was folded back and forth to form a bundle not exceeding 40 cm in length. The screen room, conducting ground plane, analyzer, and LISN were bonded together to the protective earth ground. Preliminary testing was performed to identify the frequencies of each of the emissions, which demonstrated the highest amplitudes. The cables were repositioned to obtain maximum amplitude of measured EMI level. Once the worst-case configuration was identified, plots were made of the EMI from 0.15 MHz to 30 MHz then data was recorded with maximum conducted emissions levels.

Refer to figures 1 and 2 for plots of the EUT – AC Power Adapter configuration #2 AC Line conducted emissions. Refer to figures 3 and 4 for plots of the EUT – USB Computer interface configuration #3 AC Line conducted emissions.

Trace 1 - QUASI PEAK

Trace 2 - AVERAGE

**Figure 1 AC Line Conducted emissions of EUT line 1 (EUT – AC Adapter)**



**Figure 2 AC Line Conducted emissions of EUT line 2 (EUT – AC Adapter)**




Figure 3 AC Line Conducted emissions of EUT line 1 (EUT – Computer)





Figure 4 AC Line Conducted emissions of EUT line 2 (EUT – Computer)



**Table 5 AC Line Conducted Emissions Data L1 (EUT – AC Adapter)**

Trace	Frequency	Level	Delta Limit
1	678.8 kHz	50.53 dB $\mu$ V	-5.47 dB $\mu$ V
2	685.5 kHz	39.69 dB $\mu$ V	-6.31 dB $\mu$ V
2	631.5 kHz	36.75 dB $\mu$ V	-9.25 dB $\mu$ V
1	636 kHz	44.07 dB $\mu$ V	-11.93 dB $\mu$ V
1	1.03 MHz	42.13 dB $\mu$ V	-13.87 dB $\mu$ V
2	1.315 MHz	31.8 dB $\mu$ V	-14.2 dB $\mu$ V
2	1.369 MHz	31.43 dB $\mu$ V	-14.57 dB $\mu$ V
2	739.5 kHz	31.43 dB $\mu$ V	-14.57 dB $\mu$ V
2	1.034 MHz	30.85 dB $\mu$ V	-15.15 dB $\mu$ V
1	1.226 MHz	40.71 dB $\mu$ V	-15.29 dB $\mu$ V
1	658.5 kHz	33.72 dB $\mu$ V	-22.28 dB $\mu$ V
1	150 kHz	36.79 dB $\mu$ V	-29.21 dB $\mu$ V

Other emissions present had amplitudes at least 20 dB below the limit.

**Table 6 AC Line Conducted Emissions Data L2 ( EUT – AC Adapter)**

Trace	Frequency	Level	Delta Limit
2	687.8 kHz	35.3 dB $\mu$ V	-10.7 dB $\mu$ V
1	690 kHz	44.95 dB $\mu$ V	-11.05 dB $\mu$ V
1	631.5 kHz	39.65 dB $\mu$ V	-16.35 dB $\mu$ V
2	1.318 MHz	28.46 dB $\mu$ V	-17.54 dB $\mu$ V
2	1.036 MHz	28.41 dB $\mu$ V	-17.59 dB $\mu$ V
2	1.385 MHz	28.16 dB $\mu$ V	-17.84 dB $\mu$ V
2	1.102 MHz	28.01 dB $\mu$ V	-17.99 dB $\mu$ V
2	636 kHz	27.49 dB $\mu$ V	-18.51 dB $\mu$ V
1	16.48 MHz	37.86 dB $\mu$ V	-22.14 dB $\mu$ V
1	18.93 MHz	35.53 dB $\mu$ V	-24.47 dB $\mu$ V
1	453.8 kHz	31.07 dB $\mu$ V	-25.74 dB $\mu$ V
1	152.3 kHz	34.45 dB $\mu$ V	-31.43 dB $\mu$ V

Other emissions present had amplitudes at least 20 dB below the limit.

**Table 7 AC Line Conducted Emissions Data L1 (EUT – Computer)**

Trace	Frequency	Level	Delta Limit
1	150 kHz	51.38 dB $\mu$ V	-14.62 dB $\mu$ V
1	465 kHz	39.37 dB $\mu$ V	-17.23 dB $\mu$ V
1	939.8 kHz	36.71 dB $\mu$ V	-19.29 dB $\mu$ V
2	16.46 MHz	29.74 dB $\mu$ V	-20.26 dB $\mu$ V
2	25.87 MHz	28.48 dB $\mu$ V	-21.52 dB $\mu$ V
2	21.17 MHz	27.72 dB $\mu$ V	-22.28 dB $\mu$ V
2	14.11 MHz	27.48 dB $\mu$ V	-22.52 dB $\mu$ V
2	204 kHz	30.91 dB $\mu$ V	-22.54 dB $\mu$ V
2	168 kHz	28.22 dB $\mu$ V	-26.84 dB $\mu$ V
1	2.175 MHz	27.74 dB $\mu$ V	-28.26 dB $\mu$ V
1	14.11 MHz	29.91 dB $\mu$ V	-30.09 dB $\mu$ V
1	6.774 MHz	21.28 dB $\mu$ V	-38.72 dB $\mu$ V

Other emissions present had amplitudes at least 20 dB below the limit.

**Table 8 AC Line Conducted Emissions Data L2 ( EUT – Computer)**

Trace	Frequency	Level	Delta Limit
1	489.8 kHz	40.35 dB $\mu$ V	-15.82 dB $\mu$ V
1	150 kHz	48.96 dB $\mu$ V	-17.04 dB $\mu$ V
1	948.8 kHz	37.09 dB $\mu$ V	-18.91 dB $\mu$ V
2	21.17 MHz	31.02 dB $\mu$ V	-18.98 dB $\mu$ V
1	251.3 kHz	42.25 dB $\mu$ V	-19.47 dB $\mu$ V
2	16.46 MHz	28.74 dB $\mu$ V	-21.26 dB $\mu$ V
1	1.532 MHz	33.24 dB $\mu$ V	-22.76 dB $\mu$ V
2	152.3 kHz	31.66 dB $\mu$ V	-24.22 dB $\mu$ V
2	25.87 MHz	24.18 dB $\mu$ V	-25.82 dB $\mu$ V
2	433.5 kHz	17.93 dB $\mu$ V	-29.26 dB $\mu$ V
1	5.678 MHz	25.26 dB $\mu$ V	-34.74 dB $\mu$ V
2	204 kHz	16.02 dB $\mu$ V	-37.43 dB $\mu$ V

Other emissions present had amplitudes at least 20 dB below the limit.

### **Summary of Results for AC Line Conducted Emissions Results**

The EUT demonstrated compliance with the AC Line Conducted Emissions requirements of CFR47 Part 15C and other applicable emissions requirements. The EUT – AC Adapter worst-case configuration demonstrated a minimum margin of -5.4 dB below the requirement. The EUT – computer worst-case configuration demonstrated a minimum margin of -14.6 dB below the requirement. Other emissions were present with amplitudes at least 20 dB below the limit and worst-case amplitudes recorded.

### **General Radiated Emissions Procedure**

The EUT was arranged in a typical equipment configuration and operated through all available mode during testing. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. Each radiated emission was then maximized at the OATS location before final radiated measurements were performed. Final data was taken with the EUT located on the OATS at 3 meters distance between the EUT and the receiving antenna. The frequency spectrum from 9 kHz to 25,000 MHz was searched for general radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Loop from 9 kHz to 30 MHz, Broadband Biconical from 30 to 200 MHz, Biconilog from 30 to 1000 MHz, Log Periodic from 200 MHz to 1 GHz and or double Ridge or pyramidal horns and mixers above 1 GHz, notch filters and appropriate amplifiers and external mixers were utilized.

**Table 9 General Radiated Emissions Data**

Frequency (MHz)	Horizontal Peak (dB $\mu$ V/m)	Horizontal Quasi-Peak (dB $\mu$ V/m)	Vertical Peak (dB $\mu$ V/m)	Vertical Quasi-Peak (dB $\mu$ V/m)	Limit @ 3m (dB $\mu$ V/m)	Horizontal Margin (dB)	Vertical Margin (dB)
55.3	37.7	31.7	39.2	24.1	40.0	-8.3	-15.9
55.9	35.4	29.4	38.4	34.7	40.0	-10.6	-5.3
62.0	40.1	32.0	40.0	34.4	40.0	-8.0	-5.6
67.6	39.2	26.3	39.2	33.2	40.0	-13.7	-6.8
70.5	42.0	34.6	39.2	23.6	40.0	-5.4	-16.4
72.3	40.3	32.7	39.0	33.0	40.0	-7.3	-7.0
94.3	34.1	30.3	37.2	33.2	40.0	-9.7	-6.8
108.0	27.2	21.1	29.3	24.9	40.0	-18.9	-15.1
130.3	39.1	27.0	39.3	34.6	40.0	-13.0	-5.4
135.0	40.0	28.8	32.2	28.4	40.0	-11.2	-11.6
205.3	30.8	26.1	20.0	16.5	40.0	-13.9	-23.5
205.3	31.2	25.7	28.7	24.3	40.0	-14.3	-15.7
216.0	33.1	26.8	29.8	25.8	40.0	-13.2	-14.2
240.0	39.5	34.3	33.4	30.2	47.0	-12.7	-16.8
720.0	37.0	32.5	33.6	28.4	47.0	-14.5	-18.6
960.0	36.3	33.6	35.0	30.9	47.0	-13.4	-16.1

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

**Summary of Results for General Radiated Emissions**


The EUT demonstrated compliance with the radiated emissions requirements of CFR47 Part 15C paragraph 15.209, RSS-210 Issue 10, and RSS-GEN Issue 5 Intentional Radiators. The EUT configuration demonstrated a minimum margin of -5.3 dB below the requirements. Other emissions were present with amplitudes at least 20 dB below the Limits.

### **Operation in the Band 2400 – 2483.5 MHz**

The transmitter output power; harmonic and general emissions were measured on an open area test site @ 3 meters. The EUT was placed on a turntable elevated as required above the ground plane and at a distance of 3 meters from the FSM antenna. The peak and quasi-peak amplitude of frequencies below 1000 MHz were measured using a spectrum analyzer. The peak and average amplitude of frequencies above 1000 MHz were measured using a spectrum analyzer. The amplitude of each emission was then recorded from the analyzer display. Emissions radiated outside of the specified bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits, whichever is the lesser attenuation. Antenna port emission plots were taken of transmitter performance for reference in this and other documentation using test sample #2. The amplitude of each radiated emission was measured on the OATS at a distance of 3 meters from the FSM antenna testing was performed on sample representative of production with integral antenna (sample #1) with worst-case data provided. The amplitude of each radiated emission was maximized by equipment orientation and placement on the turn table, raising and lowering the FSM (Field Strength Measuring) antenna, changing the FSM antenna polarization, and by rotating the turntable. A Loop antenna was used for measuring emissions from 0.009 to 30 MHz, Biconilog Antenna for 30 to 1000 MHz, Double-Ridge, and/or Pyramidal Horn Antennas from 1 GHz to 25 GHz. Emissions were measured in dB $\mu$ V/m @ 3 meters.


Plots were taken of transmitter performance (using sample #2) for reference in this and other documentation displaying compliance with the specifications.

**Figure 5 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 1 BT BR**




Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1		1	2.402 GHz	2.1 dBm		
M2		2	2.441 GHz	0.6 dBm		
M3		3	2.48 GHz	-0.4 dBm		

**Figure 6 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 2 BT 2EDR**




Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1		1	2.402 GHz	1 dBm		
M2		2	2.441 GHz	-0.5 dBm		
M3		3	2.48 GHz	-1.5 dBm		

**Figure 7 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 3 BT 3EDR**




Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1	1		2.402 GHz	1 dBm		
M2	2		2.441 GHz	-0.5 dBm		
M3	3		2.48 GHz	-1.6 dBm		

**Figure 8 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 4 BT BLE**




Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1		1	2.402 GHz	0.8 dBm		
M2		2	2.442 GHz	0.2 dBm		
M3		3	2.48 GHz	-0.6 dBm		

**Figure 9 Plot of Transmitter Emissions Low Band Edge Mode 1 BT BR**




Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1		1	2.4 GHz	-56.8 dBm		
D1	M1	1	1.85 MHz	58.7 dB		

**Figure 10 Plot of Transmitter Emissions Low Band Edge Mode 2 BT 2EDR**




Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1		1	2.4 GHz	-52.6 dBm		
D1	M1	1	2.25 MHz	53.4 dB		

**Figure 11 Plot of Transmitter Emissions Low Band Edge Mode 3 BT 3EDR**




Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1		1	2.4 GHz	-53 dBm		
D1	M1	1	2.25 MHz	53.8 dB		

**Figure 12 Plot of Transmitter Emissions Low Band Edge Mode 4 BT BLE**




Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1		1	2.4 GHz	-57.8 dBm		
D1	M1	1	2.15 MHz	57.8 dB		

**Figure 13 Plot of Transmitter Emissions High Band Edge Mode 1 BT BR**




Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1		1	2.56 GHz	-63.6 dBm		
D1	M1	1	-79.42 MHz	63 dB		

**Figure 14 Plot of Transmitter Emissions High Band Edge Mode 2 BT 2EDR**




Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1		1	2.484 GHz	-65.6 dBm		
D1	M1	1	-4.15 MHz	63 dB		

**Figure 15 Plot of Transmitter Emissions High Band Edge Mode 3 BR 2EDR**




Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1		1	2.484 GHz	-65.7 dBm		
D1	M1	1	-4.15 MHz	63.2 dB		

**Figure 16 Plot of Transmitter Emissions High Band Edge Mode 4 BT BLE**




Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1		1	2.56 GHz	-67.8 dBm		
D1	M1	1	-79.32 MHz	66.4 dB		

**Figure 17 Plot of Transmitter Emissions 99% Occupied Bandwidth Mode 1 BT BR**




Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1	1		2.441 GHz	-3.3 dBm	Occ Bw	819 kHz
T1	1		2.441 GHz	-22.5 dBm	Occ Bw Centroid	2.441 GHz
T2	1		2.441 GHz	-23 dBm	Occ Bw Freq Offset	-8.24 kHz

**Figure 18 Plot of Transmitter Emissions 99% Occupied Bandwidth Mode 2 BT 2EDR**




Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1	1	1	2.402 GHz	-2.7 dBm	Occ Bw	1.16 MHz
T1	1	1	2.401 GHz	-14.9 dBm	Occ Bw Centroid	2.402 GHz
T2	1	1	2.403 GHz	-14.3 dBm	Occ Bw Freq Offset	46.91 kHz

**Figure 19 Plot of Transmitter Emissions 99% Occupied Bandwidth Mode 3 BT 3EDR**



Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1	1	1	2.48 GHz	-5.3 dBm	Occ Bw	1.184 MHz
T1	1	1	2.479 GHz	-19.3 dBm	Occ Bw Centroid	2.48 GHz
T2	1	1	2.481 GHz	-17.1 dBm	Occ Bw Freq Offset	29.53 kHz

**Figure 20 Plot of Transmitter Emissions 99% Occupied Bandwidth Mode 4 BT BLE**



Type	Ref	Trace	X-Value	Y-Value	Function	Func Result
M1	1	1	2.402 GHz	-3.6 dBm	Occ Bw	1.029 MHz
T1	1	1	2.401 GHz	-17.8 dBm	Occ Bw Centroid	2.402 GHz
T2	1	1	2.403 GHz	-18.1 dBm	Occ Bw Freq Offset	10.66 kHz

**Transmitter Emissions Data**

**Table 10 Transmitter Radiated Emissions Mode 1 BT BR**

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2402.0	97.5	85.8	83.5	81.9	94.0	-8.2	-12.1
4804.0	49.2	36.1	50.2	37.4	54.0	-17.9	-16.6
7206.0	54.2	41.6	54.8	41.7	54.0	-12.4	-12.3
9608.0	58.2	45.2	59.2	45.4	54.0	-8.8	-8.6
12010.0	61.3	48.5	61.2	48.1	54.0	-5.5	-5.9
14412.0	61.3	48.3	61.7	48.5	54.0	-5.7	-5.5
16814.0	60.2	47.0	60.3	46.9	54.0	-7.0	-7.1
2441.0	97.8	86.3	92.6	81.0	94.0	-7.7	-13.0
4882.0	54.3	41.5	50.1	37.4	54.0	-12.5	-16.6
7323.0	55.2	42.2	54.8	42.0	54.0	-11.8	-12.0
9764.0	58.4	45.7	58.6	45.8	54.0	-8.3	-8.2
12205.0	60.2	47.2	59.7	47.1	54.0	-6.8	-6.9
14646.0	61.4	48.3	60.9	48.2	54.0	-5.7	-5.8
17087.0	59.6	46.6	59.4	46.6	54.0	-7.4	-7.4
2480.0	97.5	86.4	92.3	81.3	94.0	-7.6	-12.7
4960.0	53.5	40.6	49.9	36.5	54.0	-13.4	-17.5
7440.0	55.5	42.4	54.9	42.2	54.0	-11.6	-11.8
9920.0	58.2	45.4	58.5	45.4	54.0	-8.6	-8.6
12400.0	60.7	47.5	60.3	47.6	54.0	-6.5	-6.4
14880.0	61.9	48.9	61.7	48.9	54.0	-5.1	-5.1
17360.0	59.0	46.2	59.3	46.2	54.0	-7.8	-7.8

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Rogers Labs, Inc.  
 4405 West 259<sup>th</sup> Terrace  
 Louisburg, KS 66053  
 Phone/Fax: (913) 837-3214  
 Revision 1

Garmin International, Inc.  
 Model: A04158  
 Test: 210307  
 Test to: CFR47 15C, RSS-Gen RSS-247  
 File: A04158 DXX TstRpt 210307

SN's: 3354564362 / 3354564378  
 FCC ID: IPH-04158  
 IC: 1792A-04158  
 Date: June 17, 2021  
 Page 47 of 57

**Table 11 Transmitter Radiated Emissions Mode 2 BT 2EDR**

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2402.0	96.5	82.1	92.3	78.5	94.0	-11.9	-15.5
4804.0	52.7	38.1	50.0	36.6	54.0	-15.9	-17.4
7206.0	55.1	41.7	54.7	41.6	54.0	-12.3	-12.4
9608.0	59.0	45.4	59.7	46.2	54.0	-8.6	-7.8
12010.0	60.8	48.1	61.5	48.5	54.0	-5.9	-5.5
14412.0	61.3	48.5	61.4	48.5	54.0	-5.5	-5.5
16814.0	59.6	46.9	60.7	46.9	54.0	-7.1	-7.1
2441.0	97.1	83.0	91.9	78.2	94.0	-11.0	-15.8
4882.0	53.5	38.9	50.2	36.4	54.0	-15.1	-17.6
7323.0	55.5	42.1	54.8	42.0	54.0	-11.9	-12.0
9764.0	58.5	45.8	58.6	45.8	54.0	-8.2	-8.2
12205.0	60.1	47.1	60.4	47.2	54.0	-6.9	-6.8
14646.0	61.2	48.2	61.4	48.3	54.0	-5.8	-5.7
17087.0	59.2	46.5	60.3	46.5	54.0	-7.5	-7.5
2480.0	96.5	82.7	91.3	77.5	94.0	-11.3	-16.5
4960.0	52.9	38.1	49.8	36.2	54.0	-15.9	-17.8
7440.0	55.3	42.3	55.0	42.2	54.0	-11.7	-11.8
9920.0	58.3	45.5	58.9	45.5	54.0	-8.5	-8.5
12400.0	60.4	47.6	60.4	47.6	54.0	-6.4	-6.4
14880.0	62.1	48.9	62.3	48.9	54.0	-5.1	-5.1
17360.0	59.2	46.2	59.3	46.2	54.0	-7.8	-7.8

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

**Table 12 Transmitter Radiated Emissions Mode 3 BT 3EDR**

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2402.0	95.8	82.1	92.1	78.1	94.0	-11.9	-15.9
4804.0	51.9	38.0	49.6	36.4	54.0	-16.0	-17.6
7206.0	54.9	41.7	54.5	41.6	54.0	-12.3	-12.4
9608.0	58.7	45.4	58.6	45.4	54.0	-8.6	-8.6
12010.0	61.2	48.1	60.8	48.1	54.0	-5.9	-5.9
14412.0	61.3	48.5	61.6	48.5	54.0	-5.5	-5.5
16814.0	59.7	46.9	60.0	46.9	54.0	-7.1	-7.1
2441.0	97.0	83.0	92.2	77.8	94.0	-11.0	-16.2
4882.0	53.1	38.8	50.1	36.4	54.0	-15.2	-17.6
7323.0	55.3	42.1	55.7	42.0	54.0	-11.9	-12.0
9764.0	58.3	45.6	58.6	45.8	54.0	-8.4	-8.2
12205.0	60.3	46.9	60.2	47.1	54.0	-7.1	-6.9
14646.0	60.6	48.2	61.3	48.2	54.0	-5.8	-5.8
17087.0	59.1	46.5	59.4	46.5	54.0	-7.5	-7.5
2480.0	96.4	82.6	91.6	77.6	94.0	-11.4	-16.4
4960.0	52.5	37.9	49.9	36.1	54.0	-16.1	-17.9
7440.0	54.8	42.3	54.8	42.2	54.0	-11.7	-11.8
9920.0	58.7	45.5	59.0	45.5	54.0	-8.5	-8.5
12400.0	60.7	47.6	60.5	47.6	54.0	-6.4	-6.4
14880.0	61.7	48.9	61.6	48.9	54.0	-5.1	-5.1
17360.0	59.7	46.2	59.1	46.2	54.0	-7.8	-7.8

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

**Table 13 Transmitter Radiated Emissions Mode 4 BT BLE**

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2402.0	95.8	90.2	90.7	84.4	94.0	-3.8	-9.6
4804.0	52.4	40.7	50.1	36.5	54.0	-13.3	-17.5
7206.0	54.9	41.7	54.7	41.6	54.0	-12.3	-12.4
9608.0	57.9	45.4	58.4	45.3	54.0	-8.6	-8.7
12010.0	61.3	48.1	61.0	48.1	54.0	-5.9	-5.9
14412.0	61.7	48.5	61.1	48.5	54.0	-5.5	-5.5
16814.0	60.2	46.9	59.9	46.9	54.0	-7.1	-7.1
2442.0	97.3	91.7	92.3	86.6	94.0	-2.3	-7.4
4884.0	53.7	43.4	50.4	37.7	54.0	-10.6	-16.3
7326.0	55.3	42.3	54.8	42.1	54.0	-11.7	-11.9
9768.0	58.8	45.8	59.0	45.8	54.0	-8.2	-8.2
12210.0	59.9	47.2	59.5	47.2	54.0	-6.8	-6.8
14652.0	61.5	48.2	61.3	48.2	54.0	-5.8	-5.8
17094.0	59.1	46.5	60.6	46.5	54.0	-7.5	-7.5
2480.0	96.9	91.7	91.8	86.6	94.0	-2.3	-7.4
4960.0	53.4	42.0	50.3	37.4	54.0	-12.0	-16.6
7440.0	55.2	42.5	55.3	42.2	54.0	-11.5	-11.8
9920.0	58.8	45.5	58.3	45.5	54.0	-8.5	-8.5
12400.0	60.8	47.6	60.7	47.6	54.0	-6.4	-6.4
14880.0	62.0	48.9	62.2	48.9	54.0	-5.1	-5.1
17360.0	59.0	46.2	59.6	46.2	54.0	-7.8	-7.8

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

## ***Summary of Results for Transmitter Radiated Emissions of Intentional Radiator***

The EUT demonstrated compliance with the radiated emissions requirements of FCC CFR47 Part 15.249, Industry Canada RSS-210 Issue 10, and RSS-GEN Issue 5 Intentional Radiator regulations. The EUT worst-case test sample configuration demonstrated minimum average margin of -2.2 dB below the average emission limit for the fundamental. The EUT worst-case configuration demonstrated minimum radiated harmonic emission margin of -5.1 dB below the limit. No other radiated emissions were found in the restricted bands less than 20 dB below limits than those recorded in this report. Other emissions were present with amplitudes at least 20 dB below the limits.

## Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Test Equipment
- Annex C Rogers Qualifications
- Annex D Laboratory Certificate of Accreditation

## Annex A Measurement Uncertainty Calculations

The measurement uncertainty was calculated for all measurements listed in this test report according To CISPR 16-4. Result of measurement uncertainty calculations are recorded below. Component and process variability of production devices similar to those tested may result in additional deviations. The manufacturer has the sole responsibility of continued compliance.

Measurement	Expanded Measurement Uncertainty $U_{(lab)}$
3 Meter Horizontal 0.009-1000 MHz Measurements	4.16
3 Meter Vertical 0.009-1000 MHz Measurements	4.33
3 Meter Measurements 1-18 GHz	5.14
3 Meter Measurements 18-40 GHz	5.16
10 Meter Horizontal Measurements 0.009-1000 MHz	4.15
10 Meter Vertical Measurements 0.009-1000 MHz	4.32
AC Line Conducted	1.75
Antenna Port Conducted power	1.17
Frequency Stability	1.00E-11
Temperature	1.6°C
Humidity	3%

## Annex B Test Equipment

<u>Equipment</u>	<u>Manufacturer</u>	<u>Model (SN)</u>	<u>Band</u>	<u>Cal Date(m/d/y)</u>	<u>Due</u>
<input checked="" type="checkbox"/> LISN	FCC	FCC-LISN-50-25-10(1PA) (160611)	.15-30MHz	4/21/2020	4/21/2021
<input checked="" type="checkbox"/> LISN	Compliance Design	FCC-LISN-2.Mod.cd,(126)	.15-30MHz	10/14/2020	10/14/2021
<input checked="" type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(L10M)(303073)	9kHz-40 GHz	10/14/2020	10/14/2021
<input type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303069)	9kHz-40 GHz	10/14/2020	10/14/2021
<input checked="" type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303070)	9kHz-40 GHz	10/14/2020	10/14/2021
<input checked="" type="checkbox"/> Cable	Belden	RG-58 (L1-CAT3-11509)	9kHz-30 MHz	10/14/2020	10/14/2021
<input checked="" type="checkbox"/> Cable	Belden	RG-58 (L2-CAT3-11509)	9kHz-30 MHz	10/14/2020	10/14/2021
<input checked="" type="checkbox"/> Antenna	Com Power	AL-130 (121055)	.001-30 MHz	10/14/2020	10/14/2021
<input type="checkbox"/> Antenna:	EMCO	6509	.001-30 MHz	10/14/2020	10/14/2022
<input type="checkbox"/> Antenna	ARA	BCD-235-B (169)	20-350MHz	10/14/2020	10/14/2021
<input type="checkbox"/> Antenna:	Schwarzbeck Model	VHBB 9124 (9124-627)		4/21/2020	4/21/2021
<input checked="" type="checkbox"/> Antenna	Sunol	JB-6 (A100709)	30-1000 MHz	10/14/2020	10/14/2021
<input type="checkbox"/> Antenna	ETS-Lindgren	3147 (40582)	200-1000MHz	10/14/2020	10/14/2022
<input type="checkbox"/> Antenna:	Schwarzbeck Model:	VULP 9118 A (VULP 9118 A-534)		4/21/2020	4/21/2021
<input checked="" type="checkbox"/> Antenna	ETS-Lindgren	3117 (200389)	1-18 GHz	4/21/2020	4/21/2022
<input type="checkbox"/> Antenna	Com Power	AH-118 (10110)	1-18 GHz	10/14/2020	10/14/2022
<input checked="" type="checkbox"/> Antenna	Com Power	AH-840 (101046)	18-40 GHz	4/21/2020	4/21/2021
<input checked="" type="checkbox"/> Analyzer	Rohde & Schwarz	ESU40 (100108)	20Hz-40GHz	3/2/2021	3/2/2022
<input checked="" type="checkbox"/> Analyzer	Rohde & Schwarz	ESW44 (101534)	20Hz-44GHz	1/12/2021	1/12/2022
<input type="checkbox"/> Analyzer	Rohde & Schwarz	FS-Z60, 90, 140, and 220	40GHz-220GHz	12/22/2017	12/22/2027
<input checked="" type="checkbox"/> Amplifier	Com-Power	PA-010 (171003)	100Hz-30MHz	10/14/2020	10/14/2021
<input checked="" type="checkbox"/> Amplifier	Com-Power	CPPA-102 (01254)	1-1000 MHz	10/14/2020	10/14/2021
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-118A (551014)	0.5-18 GHz	10/14/2020	10/14/2021
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-840A (461328)	18-40 GHz	10/14/2020	10/14/2021
<input type="checkbox"/> Power Meter	Agilent	N1911A with N1921A	0.05-40 GHz	4/21/2020	4/21/2021
<input type="checkbox"/> Generator	Rohde & Schwarz	SMB100A6 (100150)	20Hz-6 GHz	4/21/2020	4/21/2021
<input type="checkbox"/> Generator	Rohde & Schwarz	SMBV100A6 (260771)	20Hz-6 GHz	4/21/2020	4/21/2021
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50722 (009).9G notch	30-18000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50114 (017)1.5G HPF	30-18000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50117 (063) 3G HPF	30-18000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50105 (059) 6G HPF	30-18000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> RF Filter	Micro-Tronics	BRM50702 (172) 2G notch	30-18000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50703 (G102) 5G notch	30-18000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50705 (024) 5G notch	30-18000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> Attenuator	Fairview	SA6NFN100W-40 (1625)	30-18000 MHz	4/21/2020	4/18/2021
<input checked="" type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1436)	30-6000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1445)	30-6000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1735)	30-6000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-6W2+ (1438)	30-6000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-6W2+ (1736)	30-6000 MHz	4/21/2020	4/21/2021
<input checked="" type="checkbox"/> Weather station	Davis	6312 (A81120N075)		11/4/2020	11/4/2021

Rogers Labs, Inc.  
 4405 West 259<sup>th</sup> Terrace  
 Louisburg, KS 66053  
 Phone/Fax: (913) 837-3214  
 Revision 1

Garmin International, Inc.  
 Model: A04158  
 Test: 210307  
 Test to: CFR47 15C, RSS-Gen RSS-247  
 File: A04158 DXX TstRpt 210307

SN's: 3354564362 / 3354564378  
 FCC ID: IPH-04158  
 IC: 1792A-04158  
 Date: June 17, 2021  
 Page 54 of 57

List of Test Equipment

Calibration

Date (m/d/y) Due

<input type="checkbox"/>	Frequency Counter: Leader LDC-825 (8060153)			4/21/2020	4/21/2021
<input type="checkbox"/>	LISN: Com-Power Model LI-220A			10/14/2020	10/14/2021
<input type="checkbox"/>	LISN: Com-Power Model LI-550C			10/14/2020	10/14/2021
<input type="checkbox"/>	ISN: Com-Power Model ISN T-8			4/21/2020	4/21/2021
<input type="checkbox"/>	LISN: Fischer Custom Communications Model: FCC-LISN-50-16-2-08			4/21/2020	4/21/2021
<input type="checkbox"/>	Cable Huber & Suhner Inc. Sucoflex102ea(1.5M)(303072)	9kHz-40 GHz		10/14/2020	10/14/2021
<input type="checkbox"/>	Cable Huber & Suhner Inc. Sucoflex102ea(L1M)(281183)	9kHz-40 GHz		10/14/2020	10/14/2021
<input type="checkbox"/>	Cable Huber & Suhner Inc. Sucoflex102ea(L4M)(281184)	9kHz-40 GHz		10/14/2020	10/14/2021
<input type="checkbox"/>	Cable Huber & Suhner Inc. Sucoflex102ea(L10M)(317546)	9kHz-40 GHz		10/14/2020	10/14/2021
<input type="checkbox"/>	Cable Time Microwave 4M-750HF290-750 (4M)	9kHz-24 GHz		10/14/2020	10/14/2021
<input type="checkbox"/>	RF Filter Micro-Tronics BRC17663 (001)	9.3-9.5 notch	30-1800 MHz	4/21/2020	4/21/2021
<input type="checkbox"/>	RF Filter Micro-Tronics BRC19565 (001)	9.2-9.6 notch	30-1800 MHz	10/16/2018	4/21/2021
<input type="checkbox"/>	Analyzer HP 8562A (3051A05950)	9kHz-125GHz		4/21/2020	4/21/2021
<input type="checkbox"/>	Analyzer HP External Mixers 11571, 11970	25GHz-110GHz		4/18/2015	4/18/2025
<input type="checkbox"/>	Analyzer HP 8591EM (3628A00871)			4/21/2020	4/21/2021
<input type="checkbox"/>	Wave Form Generator Keysight 33512B (MY57400128)			4/21/2020	4/21/2021
<input type="checkbox"/>	Antenna: Solar 9229-1 & 9230-1			2/22/2021	2/22/2022
<input type="checkbox"/>	CDN: Com-Power Model CDN325E			10/14/2020	10/14/2021
<input type="checkbox"/>	Injection Clamp Luthi Model EM101			10/14/2020	10/14/2021
<input type="checkbox"/>	Oscilloscope Scope: Tektronix MDO 4104			2/22/2021	2/22/2022
<input type="checkbox"/>	EMC Transient Generator HVT TR 3000			2/22/2021	2/22/2022
<input type="checkbox"/>	AC Power Source (Ametech, California Instruments)			2/22/2021	2/22/2022
<input type="checkbox"/>	Field Intensity Meter: EFM-018			2/22/2021	2/22/2022
<input type="checkbox"/>	ESD Simulator: MZ-15			2/22/2021	2/22/2022
<input type="checkbox"/>	R.F. Power Amp ACS 230-50W			not required	
<input type="checkbox"/>	R.F. Power Amp EIN Model: A301			not required	
<input type="checkbox"/>	R.F. Power Amp A.R. Model: 10W 1010M7			not required	
<input type="checkbox"/>	R.F. Power Amp A.R. Model: 50U1000			not required	
<input checked="" type="checkbox"/>	Shielded Room			not required	

## ***Annex C Rogers Qualifications***

***Scot D. Rogers, Engineer***

### **Rogers Labs, Inc.**

Mr. Rogers has approximately 35 years' experience in the field of electronics. Working experience includes six years working in the automated controls industry and 6 years working with the design, development and testing of radio communications and electronic equipment.

#### Positions Held:

Systems Engineer: A/C Controls Mfg. Co., Inc. 6 Years

Electrical Engineer: Rogers Consulting Labs, Inc. 5 Years

Electrical Engineer: Rogers Labs, Inc. Current

#### Educational Background:

Bachelor of Science Degree in Electrical Engineering from Kansas State University

Bachelor of Science Degree in Business Administration Kansas State University

Several Specialized Training courses and seminars pertaining to Microprocessors and Software programming

## Annex D Laboratory Certificate of Accreditation

United States Department of Commerce  
National Institute of Standards and Technology



### Certificate of Accreditation to ISO/IEC 17025:2017

NVLAP LAB CODE: 200087-0

**Rogers Labs, Inc.**  
Louisburg, KS

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,  
listed on the Scope of Accreditation, for:*

#### **Electromagnetic Compatibility & Telecommunications**

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.  
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality  
management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).*

2021-02-19 through 2022-03-31  
Effective Dates



  
For the National Voluntary Laboratory Accreditation Program

Rogers Labs, Inc.  
4405 West 259<sup>th</sup> Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214  
Revision 1

Garmin International, Inc.  
Model: A04158  
Test: 210307  
Test to: CFR47 15C, RSS-Gen RSS-247  
File: A04158 DXX TstRpt 210307

SN's: 3354564362 / 3354564378  
FCC ID: IPH-04158  
IC: 1792A-04158  
Date: June 17, 2021  
Page 57 of 57