

ROGERS LABS, INC.

4405 West 259th Terrace
Louisburg, KS 66053
Phone / Fax (913) 837-3214

47CFR, PART 15C - Intentional Radiators 47CFR Paragraph 15.247 and Industry Canada RSS-247 Issue 2 and RSS-GEN Issue 5 Application For Grant of Certification

Model: A04602

2402-2480 MHz (DTS)

Broadband Digital Transmission System

FCC ID: IPH-04602

IC: 1792A-04602

Garmin International, Inc.

1200 East 151st Street
Olathe, KS 66062

FCC Designation: US5305

ISED Registration: 3041A

Test Report Number: 220302

Test Date: June 5, 2022

Authorized Signatory: *Scot D Rogers*
Scot D. Rogers

This report shall not be reproduced except in full, without the written approval of the laboratory. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision r1

Garmin International, Inc.
Model: A04602
Test: 220302
Test to: 47CFR 15C, RSS-Gen RSS-247
File: A04602 DTS TstRpt 220302 r1 Page 1 of 86

SN's: 3402697514 / 34022697513
FCC ID: IPH-04602
IC: 1792A-04602
Date: June 21, 2022

Table of Contents

TABLE OF CONTENTS.....	2
REVISIONS.....	5
EXECUTIVE SUMMARY	6
OPINION / INTERPRETATION OF RESULTS	7
EQUIPMENT TESTED.....	9
Equipment Operational Modes.....	10
Equipment Function	11
Equipment Configuration.....	12
APPLICATION FOR CERTIFICATION.....	13
APPLICABLE STANDARDS & TEST PROCEDURES	14
TESTING PROCEDURES	14
AC Line Conducted Emission Test Procedure	14
Radiated Emission Test Procedure.....	14
Antenna Port Conducted Emission Test Procedure.....	15
Diagram 1 Test arrangement for Conducted emissions	16
Diagram 2 Test arrangement for radiated emissions of tabletop equipment.....	17
Diagram 3 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)	18
Diagram 4 Test arrangement for Antenna Port Conducted emissions	18
TEST SITE LOCATIONS	19
UNITS OF MEASUREMENTS	19
ENVIRONMENTAL CONDITIONS.....	20
STATEMENT OF MODIFICATIONS AND DEVIATIONS	20
INTENTIONAL RADIATORS.....	20

Antenna Requirements20

Restricted Bands of Operation.....20

Table 1 Radiated Emissions in Restricted Frequency Bands Data Mode 2 BT 2EDR21

Table 2 Radiated Emissions in Restricted Frequency Bands Data Mode 3 BT 3EDR22

Table 3 Radiated Emissions in Restricted Frequency Bands Data Mode 4 BT BLE23

Table 4 Harmonic Radiated Emissions in Restricted Bands Mode 5 802.11b24

Table 5 Harmonic Radiated Emissions in Restricted Bands Mode 6 802.11g25

Table 6 Harmonic Radiated Emissions in Restricted Bands Mode 7 802.11n26

Summary of Results for Radiated Emissions in Restricted Bands26

AC Line Conducted EMI Procedure27

Figure 1 AC Line Conducted emissions of EUT line 1 (EUT – AC Adapter)28

Figure 2 AC Line Conducted emissions of EUT line 2 (EUT – AC Adapter)29

Figure 3 AC Line Conducted emissions of EUT line 1 (EUT – Computer).....30

Figure 4 AC Line Conducted emissions of EUT line 2 (EUT – Computer).....31

Table 7 AC Line Conducted Emissions Data L1 (EUT – AC Adapter)32

Table 8 AC Line Conducted Emissions Data L2 (EUT – AC Adapter)32

Table 9 AC Line Conducted Emissions Data L1 (EUT – Computer).....33

Table 10 AC Line Conducted Emissions Data L2 (EUT – Computer).....33

Summary of Results for AC Line Conducted Emissions Results.....34

General Radiated Emissions Procedure.....34

Table 11 General Radiated Emissions Data.....35

Summary of Results for General Radiated Emissions35

Operation in the Band 2400 – 2483.5 MHz36

Figure 5 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 2 BT 2EDR.....37

Figure 6 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 3 BT 3EDR.....38

Figure 7 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 4 BT BLE39

Figure 8 Plot of Transmitter Operation in 2412-2462 MHz Mode 5 802.11b40

Figure 9 Plot of Transmitter Operation in 2412-2462 MHz Mode 6 802.11g41

Figure 10 Plot of Transmitter Operation in 2412-2462 MHz Mode 7 802.11n42

Figure 11 Plot of Transmitter Emissions Low Band Edge Mode 2 BT 2EDR43

Figure 12 Plot of Transmitter Emissions Low Band Edge Mode 3 BT 3EDR44

Figure 13 Plot of Transmitter Emissions Low Band Edge Mode 4 BT BLE.....45

Figure 14 Plot of Transmitter Emissions Low Band Edge Mode 5 802.11b46

Figure 15 Plot of Transmitter Emissions Low Band Edge Mode 6 802.11g47

Figure 16 Plot of Transmitter Emissions Low Band Edge Mode 7 802.11n48

Figure 17 Plot of Transmitter Emissions High Band Edge Mode 2 BT 2EDR49

Figure 18 Plot of Transmitter Emissions High Band Edge Mode 3 BR 3EDR50

Figure 19 Plot of Transmitter Emissions High Band Edge Mode 4 BT BLE51

Figure 20 Plot of Transmitter Emissions High Band Edge Mode 5 802.11b.....52

Figure 21 Plot of Transmitter Emissions High Band Edge Mode 6 802.11g.....53

Figure 22 Plot of Transmitter Emissions High Band Edge Mode 7 802.11n.....54

Figure 23 Plot of 6-dB Occupied Bandwidth Mode 2 BT 2EDR55

Figure 24 Plot of 99% Occupied Bandwidth Mode 2 BT 2EDR56

Figure 25 Plot of 6-dB Occupied Bandwidth Mode 3 BT 3EDR57

Figure 26 Plot of 99% Occupied Bandwidth Mode 3 BT 3EDR58

Figure 27 Plot of 6-dB Occupied Bandwidth Mode 4 BT BLE.....59

Figure 28 Plot of 99% Occupied Bandwidth Mode 4 BT BLE60

Figure 29 Plot of 6-dB Occupied Bandwidth Mode 5 802.11b61

Figure 30 Plot of 99% Occupied Bandwidth Mode 5 802.11b62

Figure 31 Plot of 6-dB Occupied Bandwidth Mode 6 802.11g63

Figure 32 Plot of 99% Occupied Bandwidth Mode 6 802.11g64

Figure 33 Plot of 6-dB Occupied Bandwidth Mode 7 802.11n65

Figure 34 Plot of 99% Occupied Bandwidth Mode 7 802.11n66

Figure 35 Plot of Transmitter Power Spectral Density Mode 2 BT 2EDR67

Figure 36 Plot of Transmitter Power Spectral Density Mode 3 BT 3EDR68

Figure 37 Plot of Transmitter Power Spectral Density Mode 4 BT BLE69

Figure 38 Plot of Transmitter Power Spectral Density Mode 5 802.11b70

Figure 39 Plot of Transmitter Power Spectral Density Mode 6 802.11g71

Figure 40 Plot of Transmitter Power Spectral Density Mode 7 802.11n72

Transmitter Emissions Data.....73

Table 12 Transmitter Radiated Emissions Mode 2 BT 2EDR73

Table 13 Transmitter Radiated Emissions Mode 3 BT 3EDR74

Table 14 Transmitter Radiated Emissions Mode 4 BT BLE75

Table 15 Transmitter Radiated Emissions Mode 5 802.11b76

Table 16 Transmitter Radiated Emissions Mode 6 802.11g77

Table 17 Transmitter Radiated Emissions Mode 7 802.11n78

Table 18 Transmitter Antenna Port Conducted Data modes 2, 3, and 479



NVLAP Lab Code 200087-0

Table 19 Transmitter Antenna Port Conducted Data modes 5, 6, and 7.....80

Summary of Results for Transmitter Radiated Emissions of Intentional Radiator.....80

ANNEX..... 81

Annex A Measurement Uncertainty Calculations.....82

Annex B Test Equipment.....83

Annex C Rogers Qualifications85

Annex D Laboratory Certificate of Accreditation.....86

Revisions

Revision r1 Issued June 21, 2022

Rogers Labs, Inc.
 4405 West 259th Terrace
 Louisburg, KS 66053
 Phone/Fax: (913) 837-3214
 Revision r1

Garmin International, Inc.
 Model: A04602
 Test: 220302
 Test to: 47CFR 15C, RSS-Gen RSS-247
 File: A04602 DTS TstRpt 220302 r1 Page 5 of 86

SN's: 3402697514 / 34022697513
 FCC ID: IPH-04602
 IC: 1792A-04602
 Date: June 21, 2022

Executive Summary

The following information is submitted for consideration in obtaining Grant of Certification for License Exempt Digital Transmission System Intentional Radiator operating under Code of Federal Regulations Title 47 (47CFR) Part 15C paragraph 15.247, Industry Canada RSS-247 Issue 2, and RSS-GEN Issue 5, operation in the 2400 – 2483.5 MHz band.

Name of Applicant: Garmin International, Inc.
 1200 East 151st Street
 Olathe, KS 66062

M/N: A04602 HVIN: A04602
 FCC ID: IPH-04602 IC: 1792A-04602
 Frequency Range: operation in the 2402-2480 MHz band

Operational communication modes two through seven

Mode	Power (Watts)	99% OBW (kHz)	6-dB OBW (kHz)
Mode 2, BT 2EDR ($\pi/4$ -DQPSK)	0.003	1,224.8	1,101.0
Mode 3, BT 3EDR (8DPSK)	0.003	1,231.5	1,105.8
Mode 4, BT BLE (GMSK)	0.004	2,221.3	1,810.9
Mode 5, 802.11b (CCK, DSSS)	0.062	11,737.5	8,628.5
Mode 6, 802.11g (OFDM)	0.052	17,085.0	16,308.1
Mode 7, 802.11n (MCS)	0.060	18,187.5	17,515.0

This report addresses EUT Operations as Digital Transmission System using transmitter modulations in modes 2 through 7. Note, the production device utilizes integral antenna systems with the 2.4 GHz and 5 GHz PIFA providing 0 dBi gain.

Opinion / Interpretation of Results

Tests Performed	Margin (dB)	Results
Emissions 15.205, RSS-GEN, RSS-247	-0.1	Complies
Emissions as per 47CFR 15.207, RSS-GEN 8.8	-12.3	Complies
Radiated Emissions 47 CFR 15.209, RSS-GEN 8.9	-1.5	Complies
Harmonic Emissions per 47CFR 15.247, RSS-247	-2.1	Complies
Power Spectral Density per 47CFR 15.247, RSS-247	-13.5	Complies

Tests performed include

47CFR

15.247 (a) (2) Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one-Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the *maximum conducted output power* is the highest total transmit power occurring in any mode.

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in

accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

RSS-247 Issue 2

5.2 Digital transmission systems

DTS's include systems that employ digital modulation techniques resulting in spectral characteristics similar to direct sequence systems. The following applies to the bands 902-928 MHz and 2400-2483.5 MHz

a)The minimum 6 dB bandwidth shall be 500 kHz.

b)The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

This power spectral density shall be determined in accordance with the provisions of section 5.4(d),(i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

5.4 Transmitter output power and equivalent isotropically radiated power (e.i.r.p.) requirements

d) For DTS's employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

5.5 Unwanted emissions

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB.

Attenuation below the general field strength limits specified in RSS-Gen is not required.



Equipment Tested

Model: A04602

Garmin International, Inc.
1200 East 151st Street
Olathe, KS 66062

<u>Equipment</u>	<u>Model / PN</u>	<u>Serial Number</u>
EUT	A04602	3402697514
EUT2	A04602	34022697513
USB cable (0.5-meter)	320-00541-0x	N/A
USB cable (1.7-meter)	320-01461-x0	N/A
USB cable (1.7-meter)	320-01462-x0	N/A
AC Adapter	320-00096-xx	N/A
CLA DC/DC Adapter (single)	013-00970-00	N/A
CLA DC/DC Adapter (Dual)	013-00791-00	N/A
USB-C to USB-mini (pass through)	320-01487-00	N/A
GTM-60	320-00683-00	N/A
GTM-70	320-00683-20	N/A
BC-20 (Camera)	A3EVNX01	N/A
BC-30	320-00922-xx	N/A
DC Power Supply	BK 1745	209C13
Laptop Computer	Latitude 7480	EFSPSN2
USB Printer	Dell 0N5819	5D1SL61

Test results in this report relate only to the items tested. Worst-case configuration data recorded in this report.

Software: 3.22, Antennas: 2.4 GHz PIFA (0 dBi), 5 GHz PIFA (0 dBi)

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision r1

Garmin International, Inc.
Model: A04602
Test: 220302
Test to: 47CFR 15C, RSS-Gen RSS-247
File: A04602 DTS TstRpt 220302 r1 Page 9 of 86

SN's: 3402697514 / 34022697513
FCC ID: IPH-04602
IC: 1792A-04602
Date: June 21, 2022

Equipment Operational Modes

Mode	Transmitter Operation
1	BT BR (GFSK)
2	BT 2EDR ($\pi/4$ -DQPSK)
3	BT 3EDR (8DPSK)
4	BT BLE (GMSK)
5	802.11b
6	802.11g
7	802.11n
8	U-NII-1 802.11a
9	U-NII-1 802.11n
10	U-NII-1 802.11n40
11	U-NII-1 802.11ac80
12	U-NII-3 802.11a
13	U-NII-3 802.11n
14	U-NII-3 802.11n40
15	U-NII-3 802.11ac80

Equipment Function

The EUT is a GPS receiver, graphical display, and user interface unit providing GPS reception, graphical display of location, navigation, and other information for the user. The design offers use as a hand-held, transportation mounted or portable configuration for use in navigational applications. The design incorporates transmitter circuitry operating in the 2402-2480, 5150-5250, and 5725-5850 MHz frequency bands. The typical use configuration has the EUT mounted in a transportation vehicle and powered from the direct current vehicle power through an interface cable. The design provides a Micro SD Card slot and USB-C interface port as presented below and wireless communications with compatible equipment. The EUT operates from direct current power provided from external power or internal rechargeable battery. External power may be supplied through the installation vehicles 12-volt power through Cigarette Lighter Adapter (CLA) and cable, AC/DC power adapter, or compliant USB interface as documented this report. The EUT was arranged as described by the manufacturer emulating typical user configurations for testing purposes. The EUT offers no other interface connections than those presented in the configuration options as described by the manufacturer and presented below. For testing purposes, the EUT received power from both internal and external power options and configurations. During testing, the test system was configured to operate in a manufacturer defined mode. The manufacturer provided test software for testing transmitter and equipment function. The software provided ability to operate the transmitter at 100% duty cycle for testing purposes. The testing mode of operation exceeds typical duty cycle operation of production equipment. As requested by the manufacturer the equipment was tested for emissions compliance using the available configurations with the worse-case data presented. Test results in this report relate only to the products described in this report.

Equipment Configuration

- 1) Unit operating off internal battery




- 2) Unit connected to (and powered by) AC adapter (320-00096-xx) through USB cable (GPN: 320-01545-00)




- 3) Unit connected to Computer USB port through cable assembly (GPN: GPN: 320-01545-00)



- 4) Unit connected to CLA (013-00970-00) through cable assembly (GPN: GPN: 320-01461-x0, 320-01462-x0)



- 5) Unit connected to CLA (013-00791-00) through cable assembly (GPN: GPN: 320-01461-x0, 320-01462-x0)



- 6) Unit connected to DC Power through Pass-Thru cable (320-01487-00) and (GTM-70; 320-00683-20, GTM-60; 320-00683-00)



- 7) Unit connected to DC Power through Pass-Thru cable (320-01487-00) and (BC-30)



Application for Certification

- (1) Manufacturer: Garmin International, Inc.
1200 East 151st Street
Olathe, KS 66062
- (2) Identification: HVIN: A04602
FCC ID: IPH-04602 IC: 1792A-04602
- (3) Instruction Book:
Refer to Exhibit for Instruction Manual.
- (4) Description of Circuit Functions:
Refer to Exhibit of Operational Description.
- (5) Block Diagram with Frequencies:
Refer to Exhibit of Operational Description.
- (6) Report of Measurements:
Report of measurements follows in this Report.
- (7) Photographs: Construction, Component Placement, etc.:
Refer to Exhibit for photographs of equipment.
- (8) List of Peripheral Equipment Necessary for operation. The equipment operates from internal battery power or external direct current power provided from authorized sources. The EUT provides Mini-USB interface port for power and communications as presented in this filing.
- (9) Transition Provisions of 47CFR 15.37 are not requested.
- (10) Not Applicable. The unit is not a scanning receiver.
- (11) Not Applicable. The EUT does not operate in the 59 – 64 GHz frequency band.
- (12) The equipment is not software defined and this section is not applicable.
- (13) Applications for certification of U-NII devices in the 5.15-5.35 GHz and the 5.47-5.85 GHz bands must include a high-level operational description of the security procedures that control the radio frequency operating parameters and ensure that unauthorized modifications cannot be made. This requirement is not applicable to his DTS device.
- (14) Contain at least one drawing or photograph showing the test set-up for each of the required types of tests applicable to the device for which certification is requested. These drawings or photographs must show enough detail to confirm other information contained in the test report. Any photographs used must be focused originals without glare or dark spots and must clearly show the test configuration used. This information is provided in this report and Test Setup Exhibits provided with the application filing.

Applicable Standards & Test Procedures

The following information is submitted in accordance with the eCFR Code of Federal Regulations Title 47 (47CFR), dated 2 Part 2, Subpart J, Part 15C Paragraph 15.247, Industry Canada RSS-247 Issue 2, and RSS-GEN Issue 5. Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in ANSI C63.10-2013. This report documents compliance for the EUT operations as Digital Transmission Systems operation.

Testing Procedures

AC Line Conducted Emission Test Procedure

Testing for the AC line-conducted emissions were performed as required in 47CFR 15C, RSS-247 Issue 2, RSS-GEN and specified in ANSI C63.10-2013. The test setup, including the EUT, was arranged in the test configurations as presented during testing. The test configuration was placed on a 1 x 1.5-meter bench, 0.8 meters high located in a screen room. The power lines of the system were isolated from the power source using a standard LISN with a 50- μ Hy choke. EMI was coupled to the spectrum analyzer through a 0.1 μ F capacitor internal to the LISN. The LISN was positioned on the floor beneath the wooden bench supporting the EUT. The power lines and cables were draped over the back edge of the table. Refer to diagram one showing typical test arrangement and photographs in exhibits for EUT placement used during testing.

Radiated Emission Test Procedure


Radiated emissions testing was performed as required in 47CFR 15C, RSS-247 Issue 2, RSS-GEN and specified in ANSI C63.10-2013. The EUT was placed on a rotating 0.9 x 1.2-meter platform, elevated as required above the ground plane at a distance of 3 meters from the FSM antenna. EMI energy was maximized by equipment placement permitting orientation in three orthogonal axes, raising, and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken and recorded. The frequency spectrum from 9 kHz to 25,000 MHz was searched for emissions during preliminary investigation. Refer to diagrams two and three showing typical test setup. Refer to photographs in the test setup exhibits for specific EUT placement during testing.



Antenna Port Conducted Emission Test Procedure


The EUT was assembled as required for operation and placed on a benchtop. This configuration provided the ability to connect test equipment to the provided test antenna port. Antenna Port conducted emissions testing was performed as presented in this document and specified in ANSI C63.10-2013. Testing was completed on a laboratory bench in a shielded room. The active antenna port of the device was connected to appropriate attenuation and the spectrum analyzer. Refer to diagram four showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.

Diagram 1 Test arrangement for Conducted emissions



1. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long see (see 6.2.3.1).
2. I/O cables that are not connected to an accessory shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m (see 6.2.2).
3. EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω loads. LISN can be placed on top of, or immediately beneath, reference ground plane (see 6.2.2 and 6.2.3).
 - 3.1 All other equipment powered from additional LISN(s).
 - 3.2 Multiple-outlet strip can be used for multiple power cords of non-EUT equipment.
 - 3.3 LISN at least 80 cm from nearest part of EUT chassis.
4. Non-EUT components of EUT system being tested.
5. Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop (see 6.2.3.1).
6. Edge of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane (see 6.2.2 for options).
7. Antenna may be integral or detachable. If detachable, the antenna shall be attached for this test.

Diagram 2 Test arrangement for radiated emissions of tabletop equipment



1—A LISN is optional for radiated measurements between 30 MHz and 1000 MHz but not allowed for measurements below 30 MHz and above 1000 MHz (see 6.3.1). If used, then connect EUT to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω loads. The LISN may be placed on top of, or immediately beneath, the reference ground plane (see 6.2.2 and 6.2.3.2).

1.1—LISN spaced at least 80 cm from the nearest part of the EUT chassis.

2—Antenna can be integral or detachable, depending on the EUT (see 6.3.1).

3—Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long (see 6.3.1).

4—For emission measurements at or below 1 GHz, the table height shall be 80 cm. For emission measurements above 1 GHz, the table height shall be 1.5 m for measurements, except as otherwise specified (see 6.3.1 and 6.6.3.1).

Diagram 3 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)





Diagram 4 Test arrangement for Antenna Port Conducted emissions



Test Site Locations

Conducted EMI	AC line conducted emissions testing performed in a shielded screen room located at Rogers Labs, Inc., 4405 West 259 th Terrace, Louisburg, KS
Antenna port	Antenna port conducted emissions testing was performed in a shielded screen room located at Rogers Labs, Inc., 4405 West 259 th Terrace, Louisburg, KS
Radiated EMI	The radiated emissions tests were performed at the 3 meters, Open Area Test Site (OATS) located at Rogers Labs, Inc., 4405 West 259 th Terrace, Louisburg, KS
Registered Site information: FCC Site: US5305, ISED: 3041A, CAB Identifier: US0096	
NVLAP Accreditation	Lab code 200087-0

Units of Measurements

Conducted EMI	Data presented in dB μ V; dB referenced to one microvolt
Antenna port Conducted	Data is in dBm; dB referenced to one milliwatt
Radiated EMI	Data presented in dB μ V/m; dB referenced to one microvolt per meter

Note: Radiated limit may be expressed for measurement in dB μ V/m when the measurement is taken at a distance of 3 or 10 meters. Data taken for this report was taken at distance of 3 meters. Sample calculation demonstrates corrected field strength reading for Open Area Test Site using the measurement reading and correcting for receive antenna factor, cable and test system losses, and amplifier gains.

Sample Calculation:

RFS = Radiated Field Strength, FSM = Field Strength Measured

A.F. = Receive antenna factor, Losses = attenuators/cable losses, Gain = amplification gains

$RFS (dB\mu V/m @ 3m) = FSM (dB\mu V) + A.F. (dB/m) + Losses (dB) - Gain (dB)$



Environmental Conditions

Ambient Temperature	22.9° C
Relative Humidity	42 %
Atmospheric Pressure	1010.5 mb

Statement of Modifications and Deviations

No modifications to the EUT were required for the unit to demonstrate compliance with 47CFR Part 15C, RSS-247 Issue 2, and RSS-GEN Issue 5 emission requirements. There were no deviations to the specifications.

Intentional Radiators

The following information is submitted in support demonstration of compliance with the requirements of 47CFR, Paragraph 15 Subpart C, paragraph 15.247, Industry Canada RSS-247 Issue 2, and RSS-GEN Issue 5.

Antenna Requirements

The EUT incorporates integral antenna system and offers no provision for connection to alternate antenna system. The antenna connection point complies with the unique antenna connection requirements. There are no deviations or exceptions to the specification.

Restricted Bands of Operation

Spurious emissions falling in the restricted frequency bands of operation were measured at the OATS. The EUT utilizes frequency, determining circuitry, which generates harmonics falling in the restricted bands. Emissions were investigated at the OATS, using appropriate antennas or pyramidal horns, amplification stages, and a spectrum analyzer. Peak and average amplitudes of frequencies above 1000 MHz were compared to the required limits with worst-case data presented below. Test procedures of ANSI C63.10-2013 were used during testing. No other significant emission was observed which fell into the restricted bands of operation. Computed emission values consider the received radiated field strength, receive antenna correction factor, amplifier gain stage, and test system cable losses.

Table 1 Radiated Emissions in Restricted Frequency Bands Data Mode 2 BT 2EDR

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	73.9	34.5	59.3	30.6	54.0	-19.5	-23.4
2483.5	73.9	37.0	67.0	35.1	54.0	-17.0	-18.9
4804.0	49.2	36.4	49.4	36.4	54.0	-17.6	-17.6
4882.0	50.1	36.8	49.4	36.7	54.0	-17.2	-17.3
4960.0	50.2	36.6	49.3	36.4	54.0	-17.4	-17.6
7206.0	53.1	40.4	53.2	40.7	54.0	-13.6	-13.3
7323.0	53.8	40.5	55.8	40.5	54.0	-13.5	-13.5
7440.0	52.9	40.5	53.2	40.5	54.0	-13.5	-13.5
12010.0	58.0	45.5	58.3	45.5	54.0	-8.5	-8.5
12205.0	61.2	47.4	60.7	47.5	54.0	-6.6	-6.5
12400.0	60.9	47.6	60.5	47.5	54.0	-6.4	-6.5

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 2 Radiated Emissions in Restricted Frequency Bands Data Mode 3 BT 3EDR

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	73.9	34.1	66.2	30.9	54.0	-19.9	-23.1
2483.5	73.9	35.0	65.0	31.8	54.0	-19.0	-22.2
4804.0	49.5	36.4	50.1	36.4	54.0	-17.6	-17.6
4882.0	49.7	36.7	49.4	36.7	54.0	-17.3	-17.3
4960.0	49.9	36.5	49.4	36.4	54.0	-17.5	-17.6
7206.0	53.1	40.4	53.1	40.4	54.0	-13.6	-13.6
7323.0	53.4	40.5	53.3	40.5	54.0	-13.5	-13.5
7440.0	53.3	40.4	53.8	40.4	54.0	-13.6	-13.6
12010.0	59.2	45.5	58.2	45.5	54.0	-8.5	-8.5
12205.0	60.5	47.5	61.0	47.4	54.0	-6.5	-6.6
12400.0	60.2	47.4	60.3	47.4	54.0	-6.6	-6.6

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 3 Radiated Emissions in Restricted Frequency Bands Data Mode 4 BT BLE

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	73.0	35.2	54.6	30.4	54.0	-18.8	-23.6
2483.5	73.9	37.4	65.6	36.6	54.0	-16.6	-17.4
4804.0	49.7	36.3	49.9	36.3	54.0	-17.7	-17.7
4880.0	50.2	36.7	49.6	36.7	54.0	-17.3	-17.3
4960.0	49.5	36.4	50.2	36.3	54.0	-17.6	-17.7
7206.0	52.6	40.3	53.1	40.3	54.0	-13.7	-13.7
7320.0	53.2	40.5	53.1	40.4	54.0	-13.5	-13.6
7440.0	53.0	40.4	52.9	40.4	54.0	-13.6	-13.6
12010.0	58.2	45.5	58.4	45.5	54.0	-8.5	-8.5
12200.0	60.1	47.5	60.2	47.5	54.0	-6.5	-6.5
12400.0	60.3	47.5	61.1	47.3	54.0	-6.5	-6.7

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 4 Harmonic Radiated Emissions in Restricted Bands Mode 5 802.11b

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	73.9	53.9	63.0	34.2	54.0	-0.1	-19.8
2483.5	73.9	53.9	71.5	35.6	54.0	-0.1	-18.4
4824.0	49.6	36.5	49.2	36.3	54.0	-17.5	-17.7
4874.0	49.8	36.6	49.4	36.6	54.0	-17.4	-17.4
4924.0	49.3	36.5	49.3	36.6	54.0	-17.5	-17.4
7236.0	52.9	40.2	53.9	40.5	54.0	-13.8	-13.5
7311.0	53.6	40.4	52.8	40.3	54.0	-13.6	-13.7
7386.0	53.5	40.3	53.3	40.3	54.0	-13.7	-13.7
12060.0	58.9	46.2	59.1	46.1	54.0	-7.8	-7.9
12185.0	59.8	46.9	60.0	46.9	54.0	-7.1	-7.1
12310.0	60.6	47.2	60.5	47.3	54.0	-6.8	-6.7

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 5 Harmonic Radiated Emissions in Restricted Bands Mode 6 802.11g

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	73.9	53.9	62.5	36.9	54.0	-0.1	-17.1
2483.5	73.9	53.9	69.1	39.7	54.0	-0.1	-14.3
4824.0	49.7	36.2	49.7	36.4	54.0	-17.8	-17.6
4874.0	50.0	36.6	50.1	36.6	54.0	-17.4	-17.4
4924.0	49.6	36.6	49.4	36.6	54.0	-17.4	-17.4
7236.0	53.4	40.3	53.8	40.3	54.0	-13.7	-13.7
7311.0	53.6	40.3	53.3	40.4	54.0	-13.7	-13.6
7386.0	54.3	40.4	53.7	40.4	54.0	-13.6	-13.6
12060.0	59.9	46.3	59.3	46.1	54.0	-7.7	-7.9
12185.0	59.7	46.9	59.9	47.0	54.0	-7.1	-7.0
12310.0	59.9	47.3	61.1	47.3	54.0	-6.7	-6.7

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 6 Harmonic Radiated Emissions in Restricted Bands Mode 7 802.11n

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	73.9	53.9	64.1	36.8	54.0	-0.1	-17.2
2483.5	73.9	53.9	73.9	40.1	54.0	-0.1	-13.9
4824.0	49.9	36.4	49.9	36.4	54.0	-17.6	-17.6
4874.0	49.8	36.7	49.9	36.7	54.0	-17.3	-17.3
4924.0	49.9	36.7	49.5	36.7	54.0	-17.3	-17.3
7236.0	53.9	40.4	53.6	40.3	54.0	-13.6	-13.7
7311.0	54.4	41.1	53.1	40.5	54.0	-12.9	-13.5
7386.0	53.6	40.5	53.6	40.5	54.0	-13.5	-13.5
12060.0	59.5	46.3	59.8	46.2	54.0	-7.7	-7.8
12185.0	60.0	46.9	59.8	46.9	54.0	-7.1	-7.1
12310.0	60.5	47.3	60.1	47.6	54.0	-6.7	-6.4

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for Radiated Emissions in Restricted Bands

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Paragraph 15, Subpart 15C, RSS-247 Issue 2, and RSS-GEN Issue 5 emission requirements. The EUT worst-case operations demonstrated a minimum radiated emission margin of -0.1 dB below the requirements in restricted frequency bands. Peak, Quasi-peak, and average amplitudes were checked for compliance with the regulations. Worst-case emissions are reported with other emissions found in the restricted frequency bands at least 20 dB below the requirements.

AC Line Conducted EMI Procedure

The EUT was arranged in typical equipment configurations operating from AC power adapter. Testing was performed with the EUT placed on a 1 x 1.5-meter wooden bench 80 cm above the conducting ground plane, floor of a screen room. The bench was positioned 40 cm away from the wall of the screen room. The LISN was positioned on the floor of the screen room 80-cm from the rear of the EUT. Testing for the AC line-conducted emissions were the procedures of ANSI C63.10-2013 paragraph 6. The AC power adapter or CPU providing power to the EUT was connected to the LISN for AC line-conducted emissions testing. A second LISN was positioned on the floor of the screen room 80-cm from the rear of the supporting equipment of the EUT. All power cords except those providing power to the EUT were then powered from the second LISN. EMI was coupled to the spectrum analyzer through a 0.1 μ F capacitor, internal to the LISN. Power line conducted emissions testing was carried out individually for each current carrying conductor of the EUT. The excess length of lead between the system and the LISN receptacle was folded back and forth to form a bundle not exceeding 40 cm in length. The screen room, conducting ground plane, analyzer, and LISN were bonded together to the protective earth ground. Preliminary testing was performed to identify the frequencies of each of the emissions, which demonstrated the highest amplitudes. The cables were repositioned to obtain maximum amplitude of measured EMI level. Once the worst-case configuration was identified, plots were made of the EMI from 0.15 MHz to 30 MHz then data was recorded with maximum conducted emissions levels.

Refer to figures one and two for plots of configuration #2, EUT – AC Power Adapter Line conducted emissions. Refer to figures three and four for plots of configuration #3, EUT – USB Computer interface AC Line conducted emissions.

Figure 1 AC Line Conducted emissions of EUT line 1 (EUT – AC Adapter)




Figure 2 AC Line Conducted emissions of EUT line 2 (EUT – AC Adapter)




Figure 3 AC Line Conducted emissions of EUT line 1 (EUT – Computer)




Figure 4 AC Line Conducted emissions of EUT line 2 (EUT – Computer)




Table 7 AC Line Conducted Emissions Data L1 (EUT – AC Adapter)

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
1	154.000000000 kHz	40.49	Quasi Peak	-25.29
2	158.000000000 kHz	26.42	Average	-29.15
1	650.000000000 kHz	40.48	Quasi Peak	-15.52
2	654.000000000 kHz	29.93	Average	-16.07
1	698.000000000 kHz	41.57	Quasi Peak	-14.43
2	706.000000000 kHz	31.36	Average	-14.64
2	1.406000000 MHz	26.47	Average	-19.53
1	14.371900000 MHz	34.53	Quasi Peak	-25.47
2	14.787900000 MHz	23.58	Average	-26.42
1	15.159900000 MHz	35.88	Quasi Peak	-24.12
2	15.287900000 MHz	23.58	Average	-26.42
1	16.131900000 MHz	33.01	Quasi Peak	-26.99

Other emissions present had amplitudes at least 20 dB below the limit.

Table 8 AC Line Conducted Emissions Data L2 (EUT – AC Adapter)

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
1	150.000000000 kHz	39.04	Quasi Peak	-26.96
1	186.000000000 kHz	35.44	Quasi Peak	-28.78
2	650.000000000 kHz	29.75	Average	-16.25
2	702.000000000 kHz	32.97	Average	-13.03
1	706.000000000 kHz	40.48	Quasi Peak	-15.52
1	1.110000000 MHz	33.53	Quasi Peak	-22.47
1	1.162000000 MHz	32.78	Quasi Peak	-23.22
2	1.306000000 MHz	24.86	Average	-21.14
1	1.310000000 MHz	33.89	Quasi Peak	-22.11
2	1.354000000 MHz	26.94	Average	-19.06
2	1.410000000 MHz	24.58	Average	-21.42
2	15.187900000 MHz	24.08	Average	-25.92

Other emissions present had amplitudes at least 20 dB below the limit.

Table 9 AC Line Conducted Emissions Data L1 (EUT – Computer)

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
1	154.000000000 kHz	50.10	Quasi Peak	-15.68
1	178.000000000 kHz	40.76	Quasi Peak	-23.82
1	194.000000000 kHz	37.16	Quasi Peak	-26.71
1	234.000000000 kHz	47.96	Quasi Peak	-14.34
2	250.000000000 kHz	36.95	Average	-14.81
2	286.000000000 kHz	34.92	Average	-15.72
1	286.000000000 kHz	47.51	Quasi Peak	-13.13
2	306.000000000 kHz	32.55	Average	-17.53
2	330.000000000 kHz	27.35	Average	-22.11
1	350.000000000 kHz	43.25	Quasi Peak	-15.71
2	18.807900000 MHz	26.07	Average	-23.93
2	19.435900000 MHz	28.35	Average	-21.65

Other emissions present had amplitudes at least 20 dB below the limit.

Table 10 AC Line Conducted Emissions Data L2 (EUT – Computer)

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
2	150.000000000 kHz	25.13	Average	-30.87
1	150.000000000 kHz	40.64	Quasi Peak	-25.36
2	246.000000000 kHz	36.66	Average	-15.23
1	254.000000000 kHz	46.08	Quasi Peak	-15.55
1	274.000000000 kHz	40.85	Quasi Peak	-20.15
1	298.000000000 kHz	42.80	Quasi Peak	-17.50
1	310.000000000 kHz	42.85	Quasi Peak	-17.12
2	334.000000000 kHz	28.39	Average	-20.96
2	350.000000000 kHz	32.43	Average	-16.53
2	366.000000000 kHz	33.16	Average	-15.43
2	378.000000000 kHz	35.51	Average	-12.82
1	394.000000000 kHz	40.56	Quasi Peak	-17.41

Other emissions present had amplitudes at least 20 dB below the limit.

Summary of Results for AC Line Conducted Emissions Results

The EUT demonstrated compliance with the AC Line Conducted Emissions requirements of 47CFR Part 15C and other applicable emissions requirements. The EUT-AC adapter configuration #2 worst-case configuration demonstrated a minimum margin of -13.0 dB below the requirement. The EUT-CPU configurations #3 worst-case configuration demonstrated a minimum margin of -12.2 dB below the requirement. Other emissions were present with amplitudes at least 20 dB below the limit and worst-case amplitudes recorded.

General Radiated Emissions Procedure

The EUT was arranged in a typical equipment configuration and operated through all available mode during testing. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. Each radiated emission was then maximized at the OATS location before final radiated measurements were performed. Final data was taken with the EUT located on the OATS at 3 meters distance between the EUT and the receiving antenna. The frequency spectrum from 9 kHz to 25,000 MHz was searched for general radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Loop from 9 kHz to 30 MHz, Broadband Biconical from 30 to 200 MHz, Biconilog from 30 to 1000 MHz, Log Periodic from 200 MHz to 1 GHz and or double Ridge or pyramidal horns and mixers above 1 GHz, notch filters and appropriate amplifiers and external mixers were utilized.

Table 11 General Radiated Emissions Data

Frequency (MHz)	Horizontal Peak (dBµV/m)	Horizontal Quasi-Peak (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Quasi-Peak (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
74.6	38.0	32.6	36.7	31.0	40.0	-7.4	-9.0
78.1	36.0	30.2	34.4	28.6	40.0	-9.8	-11.4
86.9	33.1	27.1	35.6	26.8	40.0	-12.9	-13.2
129.9	28.2	24.1	23.5	17.3	40.0	-15.9	-22.7
317.8	44.2	40.6	37.6	33.6	47.0	-6.4	-13.4
423.8	49.2	45.5	44.9	41.7	47.0	-1.5	-5.3
476.8	38.4	34.5	41.3	37.4	47.0	-12.5	-9.6

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for General Radiated Emissions

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Paragraph 15.209, RSS-247 Issue 2 and RSS-GEN Issue 5 emission requirements. The EUT demonstrated a minimum margin of -1.5 dB below the requirements. Other emissions were present with amplitudes at least 20 dB below the Limits.

Operation in the Band 2400 – 2483.5 MHz

Test procedures of ANSI C63.10-2013 paragraph 6, and KDB 558074 v05r02 were used during transmitter testing. Test sample #2 was provided for testing antenna port conducted emissions. This sample was modified by replacing the internal antenna with a 50-ohm antenna port connector and attenuator for testing purposes. The transmitter peak and average power was measured at the antenna port using a wideband RF power meter as described in ANSI C63.10-2013 and KDB 558074. Average power measured did not include any time intervals during which the transmitter was off or transmitting at a reduced power level. The Power Spectral Density (PSD) was measured as required in ANSI C63.10-2013 and KDB 558074. DTS Emission bandwidth was measured as required in ANSI C63.10-2013 and KDB 558074. The amplitude of each harmonic and general radiated emission was measured on the OATS at distance of 3 meters from the FSM antenna (radiated emission testing was performed on sample #1 representative of production equipment with integral antenna). The EUT was positioned on supporting turntable elevated as required above the ground plane, at a distance of 3 meters from the FSM antenna. Radiated emission investigations were performed from 9 kHz to 25,000 MHz. Each radiated emission was maximized by varying the FSM antenna height and polarization, and by rotating the turntable. The worst-case amplitude of each emission was then recorded from the analyzer display. The peak and quasi-peak amplitude of frequencies below 1000 MHz were measured using a spectrum analyzer. The peak and average amplitude of frequencies above 1000 MHz were measured using a spectrum analyzer. A Loop antenna was used for measuring emissions from 0.009 to 30 MHz, Biconilog Antenna for 30 to 1000 MHz, Double-Ridge, and/or Pyramidal Horn Antennas from 1 GHz to 25 GHz. Radiated Emissions were measured in dB μ V/m @ 3 meters. Plots were taken of transmitter performance (using sample #2) for reference in this and other documentation displaying compliance with the specifications.

Figure 5 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 2 BT 2EDR




Figure 6 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 3 BT 3EDR




Figure 7 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 4 BT BLE




Figure 8 Plot of Transmitter Operation in 2412-2462 MHz Mode 5 802.11b




Figure 9 Plot of Transmitter Operation in 2412-2462 MHz Mode 6 802.11g




Figure 10 Plot of Transmitter Operation in 2412-2462 MHz Mode 7 802.11n




Figure 11 Plot of Transmitter Emissions Low Band Edge Mode 2 BT 2EDR




Figure 12 Plot of Transmitter Emissions Low Band Edge Mode 3 BT 3EDR




Figure 13 Plot of Transmitter Emissions Low Band Edge Mode 4 BT BLE




Figure 14 Plot of Transmitter Emissions Low Band Edge Mode 5 802.11b




Figure 15 Plot of Transmitter Emissions Low Band Edge Mode 6 802.11g




Figure 16 Plot of Transmitter Emissions Low Band Edge Mode 7 802.11n




Figure 17 Plot of Transmitter Emissions High Band Edge Mode 2 BT 2EDR




Figure 18 Plot of Transmitter Emissions High Band Edge Mode 3 BR 3EDR




Figure 19 Plot of Transmitter Emissions High Band Edge Mode 4 BT BLE




Figure 20 Plot of Transmitter Emissions High Band Edge Mode 5 802.11b




Figure 21 Plot of Transmitter Emissions High Band Edge Mode 6 802.11g




Figure 22 Plot of Transmitter Emissions High Band Edge Mode 7 802.11n




Figure 23 Plot of 6-dB Occupied Bandwidth Mode 2 BT 2EDR




Figure 24 Plot of 99% Occupied Bandwidth Mode 2 BT 2EDR




Figure 25 Plot of 6-dB Occupied Bandwidth Mode 3 BT 3EDR




Figure 26 Plot of 99% Occupied Bandwidth Mode 3 BT 3EDR




Figure 27 Plot of 6-dB Occupied Bandwidth Mode 4 BT BLE




Figure 28 Plot of 99% Occupied Bandwidth Mode 4 BT BLE




Figure 29 Plot of 6-dB Occupied Bandwidth Mode 5 802.11b




Figure 30 Plot of 99% Occupied Bandwidth Mode 5 802.11b




Figure 31 Plot of 6-dB Occupied Bandwidth Mode 6 802.11g




Figure 32 Plot of 99% Occupied Bandwidth Mode 6 802.11g




Figure 33 Plot of 6-dB Occupied Bandwidth Mode 7 802.11n




Figure 34 Plot of 99% Occupied Bandwidth Mode 7 802.11n




Figure 35 Plot of Transmitter Power Spectral Density Mode 2 BT 2EDR




Figure 36 Plot of Transmitter Power Spectral Density Mode 3 BT 3EDR




Figure 37 Plot of Transmitter Power Spectral Density Mode 4 BT BLE




Figure 38 Plot of Transmitter Power Spectral Density Mode 5 802.11b




Figure 39 Plot of Transmitter Power Spectral Density Mode 6 802.11g





Figure 40 Plot of Transmitter Power Spectral Density Mode 7 802.11n



Transmitter Emissions Data

Table 12 Transmitter Radiated Emissions Mode 2 BT 2EDR

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2402.0	--	--	--	--	--	--	--
4804.0	49.2	36.4	49.4	36.4	54.0	-17.6	-17.6
7206.0	53.1	40.4	53.2	40.7	54.0	-13.6	-13.3
9608.0	56.7	43.7	56.6	43.8	54.0	-10.3	-10.2
12010.0	58.0	45.5	58.3	45.5	54.0	-8.5	-8.5
14412.0	60.1	47.4	59.9	47.3	54.0	-6.6	-6.7
16814.0	64.3	51.5	65.0	51.5	54.0	-2.5	-2.5
2441.0	--	--	--	--	--	--	--
4882.0	50.1	36.8	49.4	36.7	54.0	-17.2	-17.3
7323.0	53.8	40.5	55.8	40.5	54.0	-13.5	-13.5
9764.0	56.4	43.7	61.8	43.8	54.0	-10.3	-10.2
12205.0	61.2	47.4	60.7	47.5	54.0	-6.6	-6.5
14646.0	61.1	48.0	60.4	48.0	54.0	-6.0	-6.0
17087.0	64.3	51.1	65.1	51.1	54.0	-2.9	-2.9
2480.0	--	--	--	--	--	--	--
4960.0	50.2	36.6	49.3	36.4	54.0	-17.4	-17.6
7440.0	52.9	40.5	53.2	40.5	54.0	-13.5	-13.5
9920.0	56.3	43.6	56.4	43.6	54.0	-10.4	-10.4
12400.0	60.9	47.6	60.5	47.5	54.0	-6.4	-6.5
14880.0	60.9	47.6	60.4	47.6	54.0	-6.4	-6.4
17360.0	63.2	50.0	62.6	49.9	54.0	-4.0	-4.1

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 13 Transmitter Radiated Emissions Mode 3 BT 3EDR

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2402.0	--	--	--	--	--	--	--
4804.0	49.5	36.4	50.1	36.4	54.0	-17.6	-17.6
7206.0	53.1	40.4	53.1	40.4	54.0	-13.6	-13.6
9608.0	56.6	43.8	56.5	43.7	54.0	-10.2	-10.3
12010.0	59.2	45.5	58.2	45.5	54.0	-8.5	-8.5
14412.0	60.0	47.5	60.1	47.4	54.0	-6.5	-6.6
16814.0	65.4	51.8	64.5	51.8	54.0	-2.2	-2.2
2441.0	--	--	--	--	--	--	--
4882.0	49.7	36.7	49.4	36.7	54.0	-17.3	-17.3
7323.0	53.4	40.5	53.3	40.5	54.0	-13.5	-13.5
9764.0	57.0	43.8	56.6	43.9	54.0	-10.2	-10.1
12205.0	60.5	47.5	61.0	47.4	54.0	-6.5	-6.6
14646.0	61.1	48.1	61.0	48.2	54.0	-5.9	-5.8
17087.0	64.3	51.3	64.4	51.3	54.0	-2.7	-2.7
2480.0	--	--	--	--	--	--	--
4960.0	49.9	36.5	49.4	36.4	54.0	-17.5	-17.6
7440.0	53.3	40.4	53.8	40.4	54.0	-13.6	-13.6
9920.0	56.5	43.5	56.2	43.6	54.0	-10.5	-10.4
12400.0	60.2	47.4	60.3	47.4	54.0	-6.6	-6.6
14880.0	61.2	47.6	60.2	47.6	54.0	-6.4	-6.4
17360.0	63.4	50.0	62.8	50.0	54.0	-4.0	-4.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 14 Transmitter Radiated Emissions Mode 4 BT BLE

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2402.0	--	--	--	--	--	--	--
4804.0	49.7	36.3	49.9	36.3	54.0	-17.7	-17.7
7206.0	52.6	40.3	53.1	40.3	54.0	-13.7	-13.7
9608.0	56.3	43.7	55.8	43.8	54.0	-10.3	-10.2
12010.0	58.2	45.5	58.4	45.5	54.0	-8.5	-8.5
14412.0	60.0	47.4	60.0	47.4	54.0	-6.6	-6.6
16814.0	65.2	51.9	65.3	51.9	54.0	-2.1	-2.1
2440.0	--	--	--	--	--	--	--
4880.0	50.2	36.7	49.6	36.7	54.0	-17.3	-17.3
7320.0	53.2	40.5	53.1	40.4	54.0	-13.5	-13.6
9760.0	58.2	43.7	56.3	43.7	54.0	-10.3	-10.3
12200.0	60.1	47.5	60.2	47.5	54.0	-6.5	-6.5
14640.0	61.4	48.3	61.5	48.2	54.0	-5.7	-5.8
17080.0	64.5	51.2	63.8	51.1	54.0	-2.8	-2.9
2480.0	--	--	--	--	--	--	--
4960.0	49.5	36.4	50.2	36.3	54.0	-17.6	-17.7
7440.0	53.0	40.4	52.9	40.4	54.0	-13.6	-13.6
9920.0	56.4	43.6	56.2	43.5	54.0	-10.4	-10.5
12400.0	60.3	47.5	61.1	47.3	54.0	-6.5	-6.7
14880.0	61.3	47.7	60.5	47.7	54.0	-6.3	-6.3
17360.0	63.4	50.0	63.0	50.1	54.0	-4.0	-3.9

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 15 Transmitter Radiated Emissions Mode 5 802.11b

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2412.0	--	--	--	--	--	--	--
4824.0	49.6	36.5	49.2	36.3	54.0	-17.5	-17.7
7236.0	52.9	40.2	53.9	40.5	54.0	-13.8	-13.5
9648.0	57.0	44.1	57.4	44.2	54.0	-9.9	-9.8
12060.0	58.9	46.2	59.1	46.1	54.0	-7.8	-7.9
14472.0	60.2	47.3	60.3	47.4	54.0	-6.7	-6.6
16884.0	63.9	51.1	64.0	51.1	54.0	-2.9	-2.9
2437.0	--	--	--	--	--	--	--
4874.0	49.8	36.6	49.4	36.6	54.0	-17.4	-17.4
7311.0	53.6	40.4	52.8	40.3	54.0	-13.6	-13.7
9748.0	56.3	43.6	57.6	43.5	54.0	-10.4	-10.5
12185.0	59.8	46.9	60.0	46.9	54.0	-7.1	-7.1
14622.0	61.1	48.2	61.1	48.2	54.0	-5.8	-5.8
17059.0	64.6	51.6	64.0	51.5	54.0	-2.4	-2.5
2462.0	--	--	--	--	--	--	--
4924.0	49.3	36.5	49.3	36.6	54.0	-17.5	-17.4
7386.0	53.5	40.3	53.3	40.3	54.0	-13.7	-13.7
9848.0	57.2	44.4	57.5	44.3	54.0	-9.6	-9.7
12310.0	60.6	47.2	60.5	47.3	54.0	-6.8	-6.7
14772.0	60.9	48.3	61.3	48.4	54.0	-5.7	-5.6
17234.0	62.6	50.0	63.7	50.0	54.0	-4.0	-4.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 16 Transmitter Radiated Emissions Mode 6 802.11g

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2412.0	--	--	--	--	--	--	--
4824.0	49.7	36.2	49.7	36.4	54.0	-17.8	-17.6
7236.0	53.4	40.3	53.8	40.3	54.0	-13.7	-13.7
9648.0	57.1	44.2	57.5	44.2	54.0	-9.8	-9.8
12060.0	59.9	46.3	59.3	46.1	54.0	-7.7	-7.9
14472.0	60.7	47.4	60.1	47.4	54.0	-6.6	-6.6
16884.0	64.6	51.3	63.9	51.1	54.0	-2.7	-2.9
2437.0	--	--	--	--	--	--	--
4874.0	50.0	36.6	50.1	36.6	54.0	-17.4	-17.4
7311.0	53.6	40.3	53.3	40.4	54.0	-13.7	-13.6
9748.0	56.2	43.5	56.4	43.7	54.0	-10.5	-10.3
12185.0	59.7	46.9	59.9	47.0	54.0	-7.1	-7.0
14622.0	60.8	48.3	61.4	48.2	54.0	-5.7	-5.8
17059.0	64.8	51.6	64.7	51.6	54.0	-2.4	-2.4
2462.0	--	--	--	--	--	--	--
4924.0	49.6	36.6	49.4	36.6	54.0	-17.4	-17.4
7386.0	54.3	40.4	53.7	40.4	54.0	-13.6	-13.6
9848.0	57.4	44.4	57.4	44.5	54.0	-9.6	-9.5
12310.0	59.9	47.3	61.1	47.3	54.0	-6.7	-6.7
14772.0	61.0	48.3	60.9	48.4	54.0	-5.7	-5.6
17234.0	62.8	50.0	63.1	50.0	54.0	-4.0	-4.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 17 Transmitter Radiated Emissions Mode 7 802.11n

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2412.0	--	--	--	--	--	--	--
4824.0	49.9	36.4	49.9	36.4	54.0	-17.6	-17.6
7236.0	53.9	40.4	53.6	40.3	54.0	-13.6	-13.7
9648.0	57.8	44.2	57.7	44.2	54.0	-9.8	-9.8
12060.0	59.5	46.3	59.8	46.2	54.0	-7.7	-7.8
14472.0	60.2	47.4	59.9	47.4	54.0	-6.6	-6.6
16884.0	64.3	51.2	64.4	51.2	54.0	-2.8	-2.8
2437.0	--	--	--	--	--	--	--
4874.0	49.8	36.7	49.9	36.7	54.0	-17.3	-17.3
7311.0	54.4	41.1	53.1	40.5	54.0	-12.9	-13.5
9748.0	56.3	43.6	56.6	43.7	54.0	-10.4	-10.3
12185.0	60.0	46.9	59.8	46.9	54.0	-7.1	-7.1
14622.0	61.2	48.3	60.9	48.3	54.0	-5.7	-5.7
17059.0	64.6	51.6	64.2	51.5	54.0	-2.4	-2.5
2462.0	--	--	--	--	--	--	--
4924.0	49.9	36.7	49.5	36.7	54.0	-17.3	-17.3
7386.0	53.6	40.5	53.6	40.5	54.0	-13.5	-13.5
9848.0	57.1	44.5	57.3	44.4	54.0	-9.5	-9.6
12310.0	60.5	47.3	60.1	47.6	54.0	-6.7	-6.4
14772.0	61.4	47.4	61.4	48.6	54.0	-6.6	-5.4
17234.0	63.2	50.1	63.0	50.0	54.0	-3.9	-4.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 18 Transmitter Antenna Port Conducted Data modes 2, 3, and 4

Frequency MHz	Antenna Port Average Output Power (Watts)	99% Occupied Bandwidth (kHz)	6-dB Occupied Bandwidth (kHz)	Peak Power Spectral Density (dBm)
Mode 2 BT 2EDR				
2402	0.003	1,218.8	1,101.0	-11.9
2441	0.003	1,224.8	1,101.0	-11.3
2480	0.003	1,212.8	1,091.3	-12.3
Mode 3 BT 3EDR				
2402	0.003	1,227.8	1,092.1	-11.6
2440	0.003	1,231.5	1,094.7	-11.3
2480	0.003	1,231.5	1,105.8	-12.0
Mode 4 BT BLE				
2402	0.003	2,217.5	1,802.9	-11.2
2440	0.004	2,221.3	1,786.9	-10.6
2480	0.003	2,205.0	1,810.9	-12.0

Table 19 Transmitter Antenna Port Conducted Data modes 5, 6, and 7

Frequency MHz	Antenna Port Average Output Power (Watts)	99% Occupied Bandwidth (kHz)	6-dB Occupied Bandwidth (kHz)	Peak Power Spectral Density (dBm)
Mode 5 802.11b				
2412	0.062	11,557.5	8,628.5	-5.9
2437	0.057	11,403.5	8,317.3	-6.0
2462	0.059	11,737.5	8,413.5	-5.5
Mode 6 802.11g				
2412	0.024	16,860.0	16,308.1	-8.7
2437	0.052	17,085.0	16,250.0	-6.7
2462	0.025	16,815.0	16,317.3	-9.1
Mode 7 802.11n				
2412	0.023	18,097.5	17,515.0	-10.7
2437	0.060	18,187.5	17,505.0	-6.5
2462	0.023	17,850.0	16,490.3	-9.6

Summary of Results for Transmitter Radiated Emissions of Intentional Radiator

The EUT demonstrated compliance with the radiated and conducted emission requirements of 47CFR Subpart 15C Paragraph 15.247, RSS-247 Issue 2 and RSS-GEN Issue 5 emission requirements for Digital Transmission Systems. Highest average output power measured at the antenna port was 0.025 Watts. The highest peak power spectral density measured at the antenna port presented a minimum margin of -13.5 dB below the requirements. The EUT demonstrated a minimum margin of -2.1 dB below the harmonic emissions requirements. There were no other significantly measurable emissions in the restricted bands other than those recorded in this report. Other emissions were present with amplitudes at least 20 dB below the requirements. There were no other deviations or exceptions to the requirements.



Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Test Equipment
- Annex C Rogers Qualifications
- Annex D Rogers Labs Certificate of Accreditation

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision r1

Garmin International, Inc.
Model: A04602
Test: 220302
Test to: 47CFR 15C, RSS-Gen RSS-247
File: A04602 DTS TstRpt 220302 r1 Page 81 of 86

SN's: 3402697514 / 34022697513
FCC ID: IPH-04602
IC: 1792A-04602

Date: June 21, 2022

Annex A Measurement Uncertainty Calculations

The measurement uncertainty was calculated for all measurements listed in this test report according To CISPR 16-4. Result of measurement uncertainty calculations are recorded below. Component and process variability of production devices similar to those tested may result in additional deviations. The manufacturer has the sole responsibility of continued compliance.

Measurement	Expanded Measurement Uncertainty $U_{(lab)}$
3 Meter Horizontal 0.009-1000 MHz Measurements	4.16
3 Meter Vertical 0.009-1000 MHz Measurements	4.33
3 Meter Measurements 1-18 GHz	5.14
3 Meter Measurements 18-40 GHz	5.16
10 Meter Horizontal Measurements 0.009-1000 MHz	4.15
10 Meter Vertical Measurements 0.009-1000 MHz	4.32
AC Line Conducted	1.75
Antenna Port Conducted power	1.17
Frequency Stability	1.00E-11
Temperature	1.6°C
Humidity	3%

Annex B Test Equipment

<u>Equipment</u>	<u>Manufacturer</u>	<u>Model (SN)</u>	<u>Band</u>	<u>Cal Date(m/d/y)</u>	<u>Due</u>
<input checked="" type="checkbox"/> LISN	FCC	FCC-LISN-50-25-10(1PA) (160611)	.15-30MHz	3/29/2022	3/29/2023
<input checked="" type="checkbox"/> LISN: Fischer Custom Communications Model:		FCC-LISN-50-16-2-08		3/29/2022	3/29/2023
<input checked="" type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(L10M)(303073)	9kHz-40 GHz	10/14/2021	10/14/2022
<input type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303069)	9kHz-40 GHz	10/14/2021	10/14/2022
<input checked="" type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303070)	9kHz-40 GHz	10/14/2021	10/14/2022
<input checked="" type="checkbox"/> Cable	Belden	RG-58 (L1-CAT3-11509)	9kHz-30 MHz	10/14/2021	10/14/2022
<input type="checkbox"/> Cable	Belden	RG-58 (L2-CAT3-11509)	9kHz-30 MHz	10/14/2021	10/14/2022
<input checked="" type="checkbox"/> Antenna	Com Power	AL-130 (121055)	.001-30 MHz	10/14/2021	10/14/2022
<input type="checkbox"/> Antenna:	EMCO	6509	.001-30 MHz	10/14/2020	10/14/2022
<input type="checkbox"/> Antenna	ARA	BCD-235-B (169)	20-350MHz	10/14/2021	10/14/2022
<input type="checkbox"/> Antenna:	Schwarzbeck Model	VHBB 9124 (1468)	30-200MHz	10/14/2020	10/14/2022
<input checked="" type="checkbox"/> Antenna	Sunol	JB-6 (A100709)	30-1000 MHz	10/14/2021	10/14/2022
<input type="checkbox"/> Antenna	ETS-Lindgren	3147 (40582)	200-1000MHz	10/14/2020	10/14/2022
<input type="checkbox"/> Antenna:	Schwarzbeck Model:	VULP 9118 (A-534)	200-1000MHz	10/14/2020	10/14/2022
<input checked="" type="checkbox"/> Antenna	ETS-Lindgren	3117 (200389)	1-18 GHz	4/21/2020	4/21/2022
<input type="checkbox"/> Antenna	Com Power	AH-118 (10110)	1-18 GHz	10/14/2020	10/14/2022
<input checked="" type="checkbox"/> Antenna	Com Power	AH-840 (101046)	18-40 GHz	4/6/2021	4/6/2023
<input checked="" type="checkbox"/> Analyzer	Rohde & Schwarz	ESU40 (100108)	20Hz-40GHz	3/9/2022	3/9/2023
<input checked="" type="checkbox"/> Analyzer	Rohde & Schwarz	ESW44 (101534)	20Hz-44GHz	1/18/2022	1/18/2023
<input type="checkbox"/> Analyzer	Rohde & Schwarz	FS-Z60, 90, 140, and 220	40GHz-220GHz	12/22/2017	12/22/2027
<input checked="" type="checkbox"/> Amplifier	Com-Power	PA-010 (171003)	100Hz-30MHz	10/14/2021	10/14/2022
<input checked="" type="checkbox"/> Amplifier	Com-Power	CPPA-102 (01254)	1-1000 MHz	10/14/2021	10/14/2022
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-118A (551014)	0.5-18 GHz	10/14/2021	10/14/2022
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-840A (461328)	18-40 GHz	10/14/2021	10/14/2022
<input checked="" type="checkbox"/> Power Meter	Agilent	N1911A with N1921A	0.05-40 GHz	3/29/2022	3/29/2023
<input type="checkbox"/> Generator	Rohde & Schwarz	SMB100A6 (100150)	20Hz-6 GHz	3/29/2022	3/29/2023
<input type="checkbox"/> Generator	Rohde & Schwarz	SMBV100A6 (260771)	20Hz-6 GHz	3/29/2022	3/29/2023
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50722 (009).9G notch	30-18000 MHz	4/6/2021	4/6/2023
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50114 (017)1.5G HPF	30-18000 MHz	4/6/2021	4/6/2023
<input checked="" type="checkbox"/> RF Filter	Micro-Tronics	HPM50117 (063) 3G HPF	30-18000 MHz	4/6/2021	4/6/2023
<input checked="" type="checkbox"/> RF Filter	Micro-Tronics	HPM50105 (059) 6G HPF	30-18000 MHz	4/6/2021	4/6/2023
<input checked="" type="checkbox"/> RF Filter	Micro-Tronics	BRM50702 (172) 2G notch	30-18000 MHz	4/6/2021	4/6/2023
<input checked="" type="checkbox"/> RF Filter	Micro-Tronics	BRC50703 (G102) 5G notch	30-18000 MHz	4/6/2021	4/6/2023
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50705 (024) 5G notch	30-18000 MHz	4/6/2021	4/6/2023
<input type="checkbox"/> Attenuator	Fairview	SA6NFN100W-40 (1625)	30-18000 MHz	3/29/2022	3/29/2023
<input checked="" type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1436)	30-6000 MHz	3/29/2022	3/29/2023
<input checked="" type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1445)	30-6000 MHz	3/29/2022	3/29/2023
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1735)	30-6000 MHz	3/29/2022	3/29/2023
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-6W2+ (1438)	30-6000 MHz	3/29/2022	3/29/2023
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-6W2+ (1736)	30-6000 MHz	3/29/2022	3/29/2023
<input checked="" type="checkbox"/> Weather station	Davis	6312 (A81120N075)		11/4/2021	11/4/2022

Rogers Labs, Inc.
 4405 West 259th Terrace
 Louisburg, KS 66053
 Phone/Fax: (913) 837-3214
 Revision r1

Garmin International, Inc.
 Model: A04602
 Test: 220302
 Test to: 47CFR 15C, RSS-Gen RSS-247
 File: A04602 DTS TstRpt 220302 r1 Page 83 of 86

SN's: 3402697514 / 34022697513
 FCC ID: IPH-04602
 IC: 1792A-04602
 Date: June 21, 2022



List of Test Equipment

Calibration Date (m/d/y) Due

<input type="checkbox"/>	Antenna:	Schwarzbeck Model VHBB 9124 (01468)	10/14/2020	10/14/2022
<input type="checkbox"/>	Antenna:	Schwarzbeck Model: VULP 9118 A (VULP 9118 A-856)	10/14/2020	10/14/2022
<input type="checkbox"/>	Frequency Counter:	Leader LDC-825 (8060153)	3/29/2022	4/6/2023
<input type="checkbox"/>	ISN: Com-Power Model	ISN T-8	3/29/2022	3/29/2023
<input type="checkbox"/>	LISN	Compliance Design FCC-LISN-2.Mod.cd,(126) .15-30MHz	10/14/2021	10/14/2022
<input type="checkbox"/>	LISN: Com-Power Model	LI-220A	10/14/2020	10/14/2022
<input type="checkbox"/>	LISN: Com-Power Model	LI-550C	10/14/2020	10/14/2022
<input type="checkbox"/>	Cable	Huber & Suhner Inc. Sucoflex102ea(1.5M)(303072) 9kHz-40 GHz	10/14/2021	10/14/2022
<input type="checkbox"/>	Cable	Huber & Suhner Inc. Sucoflex102ea(L1M)(281183) 9kHz-40 GHz	10/14/2021	10/14/2022
<input type="checkbox"/>	Cable	Huber & Suhner Inc. Sucoflex102ea(L4M)(281184) 9kHz-40 GHz	10/14/2021	10/14/2022
<input type="checkbox"/>	Cable	Huber & Suhner Inc. Sucoflex102ea(L10M)(317546)9kHz-40 GHz	10/14/2021	10/14/2022
<input type="checkbox"/>	Cable	Time Microwave 4M-750HF290-750 (4M) 9kHz-24 GHz	10/14/2021	10/14/2022
<input type="checkbox"/>	RF Filter	Micro-Tronics BRC17663 (001) 9.3-9.5 notch 30-1800 MHz	4/6/2021	4/6/2023
<input type="checkbox"/>	RF Filter	Micro-Tronics BRC19565 (001) 9.2-9.6 notch 30-1800 MHz	10/14/2021	10/14/2023
<input type="checkbox"/>	Analyzer	HP 8562A (3051A05950) 9kHz-125GHz	3/29/2022	3/29/2023
<input type="checkbox"/>	Wave Form Generator	Keysight 33512B (MY57400128)	3/29/2022	3/29/2023
<input type="checkbox"/>	Antenna:	Solar 9229-1 & 9230-1	2/22/2022	2/22/2023
<input type="checkbox"/>	CDN: Com-Power Model	CDN325E	10/14/2021	10/14/2022
<input type="checkbox"/>	Injection Clamp	Luthi Model EM101	10/14/2021	10/14/2022
<input type="checkbox"/>	Oscilloscope Scope:	Tektronix MDO 4104	2/22/2022	2/22/2023
<input type="checkbox"/>	EMC Transient Generator	HVT TR 3000	2/22/2022	2/22/2023
<input type="checkbox"/>	AC Power Source (Ametech, California Instruments)		2/22/2022	2/22/2023
<input type="checkbox"/>	Field Intensity Meter:	EFM-018	2/22/2022	2/22/2023
<input type="checkbox"/>	ESD Simulator:	MZ-15	2/22/2022	2/22/2023
<input type="checkbox"/>	R.F. Power Amp	ACS 230-50W		not required
<input type="checkbox"/>	R.F. Power Amp	EIN Model: A301		not required
<input type="checkbox"/>	R.F. Power Amp	A.R. Model: 10W 1010M7		not required
<input type="checkbox"/>	R.F. Power Amp	A.R. Model: 50U1000		not required
<input type="checkbox"/>	Temperature Chamber			not required
<input checked="" type="checkbox"/>	Shielded Room			not required

Rogers Labs, Inc.
 4405 West 259th Terrace
 Louisburg, KS 66053
 Phone/Fax: (913) 837-3214
 Revision r1

Garmin International, Inc.
 Model: A04602
 Test: 220302
 Test to: 47CFR 15C, RSS-Gen RSS-247
 File: A04602 DTS TstRpt 220302 r1 Page 84 of 86

SN's: 3402697514 / 34022697513
 FCC ID: IPH-04602
 IC: 1792A-04602
 Date: June 21, 2022



Annex C Rogers Qualifications

Scot D. Rogers, Engineer

Rogers Labs, Inc.

Mr. Rogers has approximately 35 years’ experience in the field of electronics. Working experience includes six years working in the automated controls industry and 6 years working with the design, development and testing of radio communications and electronic equipment.

Positions Held:

Systems Engineer: A/C Controls Mfg. Co., Inc.

Electrical Engineer: Rogers Consulting Labs, Inc.

Electrical Engineer: Rogers Labs, Inc. Current

Educational Background:

Bachelor of Science Degree in Electrical Engineering from Kansas State University

Bachelor of Science Degree in Business Administration Kansas State University

Several Specialized Training courses and seminars pertaining to Microprocessors and Software programming

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision r1

Garmin International, Inc.
Model: A04602
Test: 220302
Test to: 47CFR 15C, RSS-Gen RSS-247
File: A04602 DTS TstRpt 220302 r1 Page 85 of 86

SN’s: 3402697514 / 34022697513

FCC ID: IPH-04602

IC: 1792A-04602

Date: June 21, 2022

Annex D Laboratory Certificate of Accreditation

United States Department of Commerce
National Institute of Standards and Technology



Certificate of Accreditation to ISO/IEC 17025:2017

NVLAP LAB CODE: 200087-0

Rogers Labs, Inc.
Louisburg, KS


*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:*

Electromagnetic Compatibility & Telecommunications

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality
management system (refer to joint ISO-ILAC-IAF Communiqué dated January 2009).*

2022-03-22 through 2023-03-31
Effective Dates




For the National Voluntary Laboratory Accreditation Program

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision r1

Garmin International, Inc.
Model: A04602
Test: 220302
Test to: 47CFR 15C, RSS-Gen RSS-247
File: A04602 DTS TstRpt 220302 r1 Page 86 of 86

SN's: 3402697514 / 34022697513
FCC ID: IPH-04602
IC: 1792A-04602

Date: June 21, 2022