

Measurement Report for Custom Band, BACK, NFC Type A

Exposure Conditions

|                                  |                |                        |            |
|----------------------------------|----------------|------------------------|------------|
| Band                             | Custom Band    | TSL Permittivity       | 52.8       |
| Frequency [MHz]   Channel Number | 13.600   13600 | TSL Conductivity [S/m] | 0.716      |
| Group   UID                      | CW   0--       | Phantom Section   TSL  | Flat   HSL |
| Conversion Factor                | 16.02          | Test Distance [mm]     | 0.00       |
| Communication Configuration      | CW             |                        |            |

Hardware Setup

|                          |                              |                  |                                      |
|--------------------------|------------------------------|------------------|--------------------------------------|
| Probe   Calibration Date | EX3DV4 - SN7710   2024-01-16 | Phantom          | ELI V8.0 (20deg probe tilt) - SN2081 |
| DAE   Calibration Date   | DAE4 Sn1715   2024-02-12     | TSL   Meas. Date | HBBL4-250V3   2024-Sep-16            |

Scans Setup

|                     |             |           |
|---------------------|-------------|-----------|
|                     | Area Scan   | Zoom Scan |
| Grid Extents [mm]   | 90.0 x 90.0 | x x       |
| Grid Steps [mm]     | 15.0 x 15.0 | x x       |
| Sensor Surface [mm] | 3.0         |           |
| Graded Grid         | N/A         |           |
| M2/M1 [%]           |             |           |
| Dist 3dB Peak [mm]  |             |           |

Measurement Results

|                  |           |           |
|------------------|-----------|-----------|
|                  | Area Scan | Zoom Scan |
| psSAR1g [W/Kg]   | 0         |           |
| psSAR10g [W/Kg]  | 0         |           |
| Power Drift [dB] | N/A       |           |

