



SAR EVALUATION REPORT

**FCC 47 CFR § 2.1093
IEEE Std 1528-2013**

For

Wearable Wireless Device

FCC ID: IPH-04896

Model Name: A04896

**Report Number: R15615920-S1
Issue Date: 2025-01-17**

Prepared for

Garmin International Inc.

1200 E 151st St

Olathe, KS 66062-3426, USA

Prepared by

UL LLC

12 LABORATORY DR

RTP, NC 27709, U.S.A.

TEL: (919) 549-1400



Revision History

Rev.	Date	Revisions	Revised By
V1	2024-12-11	Initial Issue	-
V2	2025-01-17	Updated maximum output power from 4.25 dBm to 8.35 dBm in §3.2 and §4	Sarah Kuhaneck

Table of Contents

1. Attestation of Test Results 4

2. Test Specification, Methods and Procedures..... 5


3. Device Under Test (DUT) Information 5

 3.1. DUT Description 5

 3.2. Wireless Technologies and Maximum Output Power 5

4. FCC Standalone SAR Test Exclusion Considerations..... 6

1. Attestation of Test Results

Applicant Name	Garmin International Inc.
FCC ID	IPH-04896
Model Name	A04896
Applicable Standards	Published RF exposure KDB procedures IEEE Std 1528-2013
Date Evaluated	2024-12-11
Test Results	Complaint
UL LLC tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report. This report contains data provided by the customer which can impact the validity of results. UL LLC is only responsible for the validity of results after the integration of the data provided by the customer. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise. This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the U.S. Government, or any agency of the U.S. government.	
Approved & Released By:	Prepared By:
	
Richard Jankovics Staff Engineer UL LLC	Lindsay Ryan Engineer UL LLC

2. Test Specification, Methods and Procedures

All calculations were made in accordance with FCC KDB 447498 D01 v06.

3. Device Under Test (DUT) Information

3.1. DUT Description

The DUT is a body-worn device with a BLE and ANT radio. The antenna to user separation distance was assumed to be 0 mm as this is the most conservative condition.

3.2. Wireless Technologies and Maximum Output Power

Wireless Technology	Frequency Band	Maximum Output Power		Antenna Gain dBi	E.I.R.P		E.R.P	
		dBm	mW		dBm	mW	dBm	mW
Bluetooth LE	2.450MHz	8.35	2.66	1.6	9.95	3.85	7.80	2.34
ANT	2.450MHz	8.35	2.66	1.6	9.95	3.85	7.80	2.34

Notes:

E.I.R.P = Maximum Output Power + Antenna Gain

E.R.P = E.I.R.P – 2.15

4. FCC Standalone SAR Test Exclusion Considerations

SAR Test Exclusion Calculations for WLAN

Antennas < 50mm to adjacent edges

Tx Interface	Frequency (MHz)	Output Power		Separation Distances (mm)		Calculated Threshold Value	
		dBm	mW	Back	Front	Back	Front
Bluetooth LE	2450	8.35	2.66	5	5	0.8 -EXEMPT-	0.8 -EXEMPT-
ANT	2450	8.35	2.66	5	5	0.8 -EXEMPT-	0.8 -EXEMPT-

Note(s):

According to KDB 447498, if the calculated threshold value is >3 for body-worn then SAR testing is required.