

TEST REPORT

Report Number: R15628768-E2

Applicant : Garmin International Inc.
1200 East 151St Street
Olathe, KS 66062-3426, USA

Model : A05201

FCC ID : IPH-05201

IC : 1792A-05201

EUT Description : Extremity Worn Digital Transceiver

Test Standard(s) : FCC 47 CFR PART 15 SUBPART C: 2025
RSS-210 ISSUE 11: 2024
RSS-GEN ISSUE 5 + A1 + A2: 2021

Date Of Issue:
2025-08-11

Prepared by:
UL LLC
12 Laboratory Dr.
Durham, NC 27713 U.S.A.
TEL: (919) 549-1400



REPORT REVISION HISTORY

Rev.	Issue Date	Revisions	Revised By
V1	2025-08-11	Initial Issue	Charles Moody

TABLE OF CONTENTS

REPORT REVISION HISTORY	2
TABLE OF CONTENTS	3
1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. SUMMARY OF TEST RESULTS	5
4. FACILITIES AND ACCREDITATION	6
5. DECISION RULES AND MEASUREMENT UNCERTAINTY	6
5.1. <i>METROLOGICAL TRACEABILITY</i>	6
5.2. <i>DECISION RULES</i>	6
5.3. <i>MEASUREMENT UNCERTAINTY</i>	7
5.4. <i>SAMPLE CALCULATION</i>	7
6. EQUIPMENT UNDER TEST	8
6.1. <i>DESCRIPTION OF EUT</i>	8
6.2. <i>MAXIMUM ELECTRIC FIELD STRENGTH</i>	8
6.3. <i>SOFTWARE AND FIRMWARE</i>	8
6.4. <i>WORST-CASE CONFIGURATION AND MODE</i>	8
6.5. <i>DESCRIPTION OF TEST SETUP</i>	9
7. TEST AND MEASUREMENT EQUIPMENT	10
8. 20dB and 99% BANDWIDTH	11
8.1. <i>Type F (Tag On)</i>	12
9. RADIATED EMISSION TEST RESULTS	13
9.1. <i>LIMITS AND PROCEDURE</i>	13
9.2. <i>FUNDAMENTAL AND SPURIOUS EMISSIONS (<30MHz)</i>	15
9.2.1. <i>TYPE F, TAG ON</i>	15
9.3. <i>TX SPURIOUS EMISSION 30 TO 1000 MHz</i>	20
9.3.1. <i>TYPE F, TAG ON</i>	20
10. FREQUENCY STABILITY	22
10.1. <i>Type F, Tag On</i>	22
11. SETUP PHOTOS	23
END OF TEST REPORT	23

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: Garmin International Inc.
1200 East 151st Street
Olathe, KS 66062-3426, USA

EUT DESCRIPTION: Extremity Worn Digital Transceiver

MODEL: A05201

SERIAL NUMBER: 604021458, 604021450, 604021458, 604021429

SAMPLE RECEIPT DATE: 2025-05-14, 2025-06-02

DATE TESTED: 2025-06-26 TO 2025-07-23

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C: 2025	
ISED RSS-210 Issue 11: 2024	Refer to Section 3
ISED RSS-GEN Issue 5 + A1 + A2: 2021	

UL LLC tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document.

Approved & Released
For UL LLC By:



Brian Kiewra
Project Engineer
Consumer, Medical and IT Segment
UL LLC

Prepared By:



Charles Moody
Lead Project Engineer
Consumer, Medical and IT Segment
UL LLC

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with:

- ANSI C63.10-2020
- FCC 47 CFR Part 2
- FCC 47 CFR Part 15C
- RSS-GEN Issue 5 + A1 + A2: 2021
- RSS-210 Issue 11:2024

3. SUMMARY OF TEST RESULTS

Requirement Description	Requirement Clause Number	Result	Remarks
Occupied Bandwidth	FCC §15.215 (c) RSS-Gen 6.7	Compliant	None
Fundamental Measurements.	FCC §15.225 (a-d) FCC §15.209 (d)		
Tx Spurious Emissions	IC RSS-210, Annex B.6 IC RSS-GEN, Section 8.9 (Transmitter)		
Frequency Stability	FCC §15.225 (e) RSS-210, Annex B.6		
AC Mains Line Conducted Emissions	FCC §15.207 IC RSS-GEN, Section 8.8	Not Performed	See Note 1

**NOTE 1: AC Mains testing not performed. As declared by the customer, EUT NFC doesn't function while in charging mode. Therefore, testing was not performed.

4. FACILITIES AND ACCREDITATION

UL LLC is accredited by A2LA, Certificate Number #0751.06, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address	ISED CABID	ISED Company Number	FCC Registration
<input type="checkbox"/>	Building: 12 Laboratory Dr Durham, NC 27713, U.S.A	US0067	2180C	825374
<input checked="" type="checkbox"/>	Building: 2800 Perimeter Park Dr. Suite B Morrisville, NC 27560, U.S.A		27265	

5. DECISION RULES AND MEASUREMENT UNCERTAINTY

5.1. METROLOGICAL TRACEABILITY

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, with a maximum time between calibrations of one year or the manufacturers' recommendation, whichever is less, and where applicable is traceable to recognized national standards.

5.2. DECISION RULES

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4:2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	U _{Lab}
Radio Frequency (Spectrum Analyzer)	141.16 Hz
Occupied Channel Bandwidth	1.22%
RF output power, conducted	1.3 dB (PK) 0.45 dB (AV)
Power Spectral Density, conducted	2.47 dB
Unwanted Emissions, conducted	1.94 dB
All emissions, radiated	6.01 dB
Conducted Emissions (0.150-30MHz) - LISN	3.40 dB
Temperature	0.57°C
Humidity	3.39%
DC Supply voltages	1.70%

Uncertainty figures are valid to a confidence level of 95%.

5.4. SAMPLE CALCULATION

RADIATED EMISSIONS

Where relevant, the following sample calculation is provided:

$$\text{Field Strength (dBuV/m)} = \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Preamp Gain (dB)}$$

$$36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} = 28.9 \text{ dBuV/m}$$

6. EQUIPMENT UNDER TEST

6.1. DESCRIPTION OF EUT

The EUT is an extremity worn digital transceiver with BT, BLE, ANT+, 802.11b/g/n 2.4GHz WLAN, NFC, and Global Navigation Satellite System (GNSS) receiver. This report covers the full testing of the NFC radio.

6.2. MAXIMUM ELECTRIC FIELD STRENGTH

The transmitter has a maximum peak radiated electric field strength at 30m as follows:

Fundamental Frequency (MHz)	E-Field (dBuV/m)
13.56	28.39

6.3. SOFTWARE AND FIRMWARE

EUT FW Version: 16.29

6.4. WORST-CASE CONFIGURATION AND MODE

The fundamental of the EUT was investigated under three orthogonal orientations X, Y, and Z. The Y orientation was determined to be the worst-case orientation. Therefore, all final radiated testing was performed with the EUT in the Y orientation.

In addition, Type A, B, AB, AF, and F with and without a tag were investigated to determine the worst case based on the highest power and spurious emissions. Type F with a tag was determined to be the worst case and therefore selected for all final tests.

The distance between the EUT and NFC reader was also investigated, and the worst-case condition occurs when the NFC reader and EUT are separated by 3cm; therefore, all final radiated testing was performed with the EUT and NFC reader separated by 3cm.

Note – Charging is not a mode of operation for NFC.

6.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Power Supply	Phihong	AQ27A-59CFA	n/a	n/a
Laptop	Lenovo	T14 Gen3	PF4FKVY8	n/a
NFC Reader	Synnix Technology Co.	CL-2100R	N/A	N/A

I/O CABLES

I/O Cable List						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	Proprietary	1	USB-C	Shielded	<3m	Program EUT

SETUP DIAGRAM

Please refer to R15628768-EP1 for setup diagrams

7. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:
 Test Equipment Used - Wireless Conducted Measurement Equipment

Equipment ID	Description	Manufacturer	Model Number	Last Cal.	Next Cal.
	Conducted Room 1				
90416	Spectrum Analyzer	Keysight Technologies	N9030A	2024-09-23	2025-09-23
207726	Temp/Humid Chamber	Thermotron	SM-32-8200	2025-01-15	2026-01-15
179892	Environmental Meter	Fisher Scientific	15-077-963	2024-08-12	2025-08-12
SOFTEMI	Antenna Port Software	UL	Version 2022.8.16	NA	NA
NA	NFC Probe Kit	EMCO	7405	NA	NA

Test Equipment Used - Radiated Disturbance Emissions Test Equipment (Morrisville – Chamber 4)

Equip. ID	Description	Manufacturer/Brand	Model Number	Last Cal.	Next Cal.
	0.009-30MHz				
135144	Active Loop Antenna	ETS-Lindgren	6502	2024-10-02	2025-10-02
	30-1000 MHz				
90628	Hybrid Broadband Antenna	Sunol Sciences Corp.	JB3	2024-01-02	2026-01-02
	Gain-Loss Chains				
207638	Gain-loss string: 0.009-30MHz	Various	Various	2025-06-13	2026-06-13
207639	Gain-loss string: 25-1000MHz	Various	Various	2025-06-13	2026-06-13
	Receiver & Software				
197954	Spectrum Analyzer	Rohde & Schwarz	ESW44	2025-04-21	2026-04-21
SOFTEMI	EMI Software	UL	Version 9.5 (18 Oct 2021)		
	Additional Equipment used				
241204	Environmental Meter	Fisher Scientific	15-077-963	2023-09-05	2025-09-05

8. 20dB and 99% BANDWIDTH

LIMITS

§15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1-5% of the 20dB bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS – TAG ON

Mode	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (MHz)
Type F	13.56	248.6	209.27

8.1. Type F (Tag On)



Note: Because the measured signal is CW or CW-like, adjusting the RBW per C63.10 would not be practical since the measured bandwidth will always follow the RBW.

9. RADIATED EMISSION TEST RESULTS

9.1. LIMITS AND PROCEDURE

LIMIT

FCC §15.225
 IC RSS-210, Annex B.6
 IC RSS-GEN, Section 8.9 (Transmitter)

- (a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/ meter at 30 meters.
- (b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110– 14.010 MHz and shall not exceed the general radiated emission limits in § 15.209 as follows:
 §15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

RSS-GEN, Section 8.9 and 8.10.

Frequency Range (MHz)	Field Strength Limit (uA/m) at 3 m	Field Strength Limit (dBuA/m) at 3 m
0.009-0.490	6.37/F(kHz) @ 300 m	-
0.490-1.705	63.7/F(kHz) @ 30 m	-
1.705 - 30	0.08 @ 30m	-
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz

or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

Formula for converting the filed strength from uV/m to dBuV/m is:

Limit (dBuV/m) = 20 log limit (uV/m)

In addition:

§15.209 (d) The emission limits shown the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

§15.209 (d) The provisions in §§ 15.225, measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

TEST PROCEDURE

ANSI C63.10 - 2020

The EUT is an intentional radiator that incorporates a digital device, the highest fundamental frequency generated or used in the device is 13.56 MHz; therefore, the frequency range was investigated from 9kHz to the 10th harmonic of the highest fundamental frequency, or 1000 MHz, whichever is greater.

Note: For all Below 30MHz test data, all measurements were made at a test distance of 3 m. The measured data was extrapolated from the test distance (3m) to the specification distance (300 m from 9-490 kHz and 30 m from 490 kHz – 30 MHz) to clearly show the relative levels of fundamental and spurious emissions and demonstrate compliance with the requirement that the level of any spurious emissions be below the level of the intentionally transmitted signal. The extrapolation factor for the limits were $40 * \log(\text{test distance} / \text{specification distance})$.


Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open area test site. Therefore, sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

RESULTS

9.2. FUNDAMENTAL AND SPURIOUS EMISSIONS (<30MHz)

9.2.1. TYPE F, TAG ON


FUNDAMENTAL



ANTENNA FACE ON

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	ANT (dB/m)	Gain/Loss (dB)	Dist. Corr. Factor (dB)	Corrected Reading dB(uVolts/meter)	Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Loop Angle
1	13.049	24.69	Pk	10.6	.4	-40	-4.31	29.5	-33.81	179	100	0 degs
2	13.3465	34.85	Pk	10.6	.4	-40	5.85	40.5	-34.65	179	100	0 degs
3	13.4725	39.76	Pk	10.6	.4	-40	10.76	50.5	-39.74	179	100	0 degs
4	13.56	57.39	Pk	10.6	.4	-40	28.39	84	-55.61	179	100	0 degs
5	13.644	40.58	Pk	10.6	.4	-40	11.58	50.5	-38.92	179	100	0 degs
6	13.7735	39.18	Pk	10.6	.4	-40	10.18	40.5	-30.32	179	100	0 degs
7	14.0675	26.63	Pk	10.6	.4	-40	-2.37	29.5	-31.87	179	100	0 degs


Pk - Peak detector



ANTENNA FACE OFF

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	ANT (dB/m)	Gain/Loss (dB)	Dist. Corr. Factor (dB)	Corrected Reading dB(uVolts/meter)	Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Loop Angle
1	13.0315	23.63	Pk	10.6	.4	-40	-5.37	29.5	-34.87	260	100	90 degs
2	13.3465	36.77	Pk	10.6	.4	-40	7.77	40.5	-32.73	260	100	90 degs
3	13.4725	38.68	Pk	10.6	.4	-40	9.68	50.5	-40.82	260	100	90 degs
4	13.56	56.49	Pk	10.6	.4	-40	27.49	84	-56.51	260	100	90 degs
5	13.644	39.78	Pk	10.6	.4	-40	10.78	50.5	-39.72	260	100	90 degs
6	13.77	38.91	Pk	10.6	.4	-40	9.91	40.5	-30.59	260	100	90 degs
7	14.071	26.92	Pk	10.6	.4	-40	-2.08	29.5	-31.58	260	100	90 degs


Pk - Peak detector



Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	ANT (dB/m)	Gain/Loss (dB)	Dist. Corr. Factor (dB)	Corrected Reading dB(uVolts/meter)	Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Loop Angle
1	13.007	19.92	Pk	10.6	.4	-40	-9.08	29.5	-38.58	168	100	Flat
2	13.3465	31.62	Pk	10.6	.4	-40	2.62	40.5	-37.88	168	100	Flat
3	13.4725	33.17	Pk	10.6	.4	-40	4.17	50.5	-46.33	168	100	Flat
4	13.56	50.93	Pk	10.6	.4	-40	21.93	84	-62.07	168	100	Flat
5	13.644	34.15	Pk	10.6	.4	-40	5.15	50.5	-45.35	168	100	Flat
6	13.7735	32.77	Pk	10.6	.4	-40	3.77	40.5	-36.73	168	100	Flat
7	14.0885	19.79	Pk	10.6	.4	-40	-9.21	29.5	-38.71	168	100	Flat

Pk - Peak detector

SPURIOUS EMISSION – E FIELD




<30MHz SPURIOUS EMISSIONS

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	ANT (dB/m)	Gain/Loss (dB)	Dist. Corr. Factor (dB)	Corrected Reading dB(uVolts/meter)	QP/AV Limit (dBuV/m)	PK Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Loop Angle
4	.02753	45.43	Pk	13.3	0	-80	-21.27	38.81	58.81	-60.08	0-360	90 degs
7	.02753	44.74	Pk	13.3	0	-80	-21.96	38.81	58.81	-60.77	0-360	Flat
1	.02867	45.38	Pk	13.2	0	-80	-21.42	38.46	58.46	-59.88	0-360	0 degs
5	.50686	35.74	Pk	11	.1	-40	6.84	33.51	-	-26.67	0-360	90 degs
8	.51108	34.99	Pk	11	.1	-40	6.09	33.43	-	-27.34	0-360	Flat
2	.61648	34.94	Pk	11	.1	-40	6.04	31.81	-	-25.77	0-360	0 degs
9	1.22358	28.46	Pk	11	.1	-40	-4.44	25.85	-	-26.29	0-360	Flat
3	1.26153	36.22	Pk	11	.1	-40	7.32	25.59	-	-18.27	0-360	0 degs
6	1.31634	28.89	Pk	11	.1	-40	-0.01	25.22	-	-25.23	0-360	90 degs

Pk - Peak detector

SPURIOUS EMISSION – H FIELD




Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	ANT (dB/m)	Gain/Loss (dB)	Dist. Corr. Factor (dB)	Corrected Reading dB(uAmps/meter)	QP/AV Limit (dBuA/m)	PK Limit (dBuA/m)	Margin (dB)	Azimuth (Degs)	Loop Angle
4	.02753	45.43	Pk	-38.2	0	-80	-72.77	-12.69	7.31	-60.08	0-360	90 degs
7	.02753	44.74	Pk	-38.2	0	-80	-73.46	-12.69	7.31	-60.77	0-360	Flat
1	.02867	45.38	Pk	-38.3	0	-80	-72.92	-13.04	6.96	-59.88	0-360	0 degs
5	.50686	35.74	Pk	-40.5	.1	-40	-44.66	-17.99	-	-26.67	0-360	90 degs
8	.51108	34.99	Pk	-40.5	.1	-40	-45.41	-18.07	-	-27.34	0-360	Flat
2	.61648	34.94	Pk	-40.5	.1	-40	-45.46	-19.69	-	-25.77	0-360	0 degs
9	1.22358	28.46	Pk	-40.5	.1	-40	-51.94	-25.65	-	-26.29	0-360	Flat
3	1.26153	36.22	Pk	-40.5	.1	-40	-44.18	-25.91	-	-18.27	0-360	0 degs
6	1.31634	28.89	Pk	-40.5	.1	-40	-51.51	-26.28	-	-25.23	0-360	90 degs


Pk - Peak detector

9.3. TX SPURIOUS EMISSION 30 TO 1000 MHz

9.3.1. TYPE F, TAG ON



HORIZONTAL



VERTICAL

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	90628 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	62.98	47.81	Pk	14	-31.4	30.41	40	-9.59	0-360	200	H
5	63.756	49.16	Pk	14.1	-31.4	31.86	40	-8.14	0-360	200	V
6	94.893	52.29	Pk	15.1	-30.5	36.89	43.52	-6.63	0-360	100	V
7	180.641	50.35	Pk	17.2	-30.5	37.05	43.52	-6.47	0-360	100	V
2	180.932	50.62	Pk	17.2	-30.5	37.32	43.52	-6.2	0-360	100	H
3	187.9009	47.04	Qp	17.2	-29.9	34.34	43.52	-9.18	338	145	H
4	542.354	42.07	Pk	24.2	-28.1	38.17	46.02	-7.85	0-360	200	H
8	542.3877	45.69	Qp	24.2	-28.1	41.79	46.02	-4.23	317	120	V

Pk - Peak detector
 Qp - Quasi-Peak detector

10. FREQUENCY STABILITY

LIMIT

§15.225 (e) The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency, over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

IC RSS-210, Annex B.6

Carrier frequency stability shall be maintained to $\pm 0.01\%$ (± 100 ppm).

TEST PROCEDURE

ANSI C63.10-2020 Clause 6.8

RESULTS

No non-compliance noted.

10.1. Type F, Tag On

		Limit: ± 100 ppm = 1.356 kHz								
		Frequency Deviation Measured with Time Elapse								
Power Supply	Envir. Temp	Startup	Delta	@ 2 mins	Delta	@ 5 mins	Delta	@ 10 mins	Delta	Limit
(Vdc)	(°C)	(MHz)	(ppm)	(MHz)	(ppm)	(MHz)	(ppm)	(MHz)	(ppm)	(ppm)
3.91	50	13.5595070	5.826	13.5595051	0.501	13.5595044	0.398	13.5595035	0.413	± 100
3.91	40	13.5595529	-28.024	13.5595201	-0.605	13.5595135	-0.273	13.5595115	-0.177	± 100
3.91	30	13.5595579	-31.711	13.5595508	-2.869	13.5595480	-2.817	13.5595353	-1.932	± 100
3.91	20	13.5595149	0.000	13.5595119	0.000	13.5595098	0.000	13.5595091	0.000	± 100
3.91	0	13.5595154	-0.369	13.5595181	-0.457	13.5595202	-0.767	13.5595400	-2.279	
3.91	10	13.5595113	2.655	13.5595133	-0.103	13.5595160	-0.457	13.5595182	-0.671	± 100
3.91	-10	13.5595374	-16.593	13.5595397	-2.050	13.5595423	-2.397	13.5595490	-2.942	± 100
3.91	-20	13.5595568	-30.900	13.5595600	-3.547	13.5595610	-3.776	13.5595628	-3.960	± 100
4.50	20	13.5595097	3.835	13.5595096	0.170	13.5595094	0.029	13.5595093	-0.015	± 100
3.35	20	13.55951328	1.191	13.55950932	0.190	13.55951133	-0.113	13.55951136	-0.167	± 100

Tested by: 104463/85502

Test date: 2025-07-23

NOTE: EUT was tested at 3.35 V for a low voltage condition as this is the lowest operating voltage of the EUT.

11. SETUP PHOTOS

Please refer to R15628768-EP1 for setup photos

END OF TEST REPORT