



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR
352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

RF Exposure Evaluation Report

APPLICANT	AUDIO-TECHNICA CORPORATION
	2-46-1 Nishi-Naruse Machida Tokyo 194-8666 JAPAN
FCC ID	JFZDSR9BT
IC	1752B-DSR9BT
MODEL NUMBER	ATH-DSR9BT
PRODUCT DESCRIPTION	Bluetooth In-Ear Headphones
STANDARD APPLIED	CFR 47 Part 2.1091
PREPARED BY	Cory Leverett

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

GENERAL REMARKS

Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

**Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669**



Authorized Signatory Name:

Cory Leverett

Engineering Project Manager

Date: 12/19/2016

RF Exposure Requirements

General information

Device type: Bluetooth In-Ear Headphones

KDB 447498 D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

100 MHz to 6 GHz at separation distance less than or equal to 50 mm

SAR Test Exclusion Calculator for Portable Devices

Insert values in yellow highlighted boxes to determine SAR Exclusion

Max Power **6.8** mW

Min Separ **5** mm

Frequency **2.48** GHz

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Answer 2.1 Must be less than or equal to 3.0 for SAR Exclusion

KDB 388624 D02 Permit But Ask List v15, Item II. A. 5.

PBA is required if:

General Population: The Answer is equal to or greater than 24 (8x threshold)

Controlled Use: The Answer is equal to or greater than 60 (20x threshold)

and, when published RF exposure KDB procedures are not established for SAR testing or

Please also note the following: [FCC KDB quote] These test exclusion conditions are based on source-based time-

Applicant: AUDIO-TECHNICA CORPORATION

FCC ID: JFZDSR9BT

Report: 2320AUT16RF EXP MPE RPT_Rev1