

TotTag 2

TT-2BLF

The TotTag is an active tag designed for monitoring newborn infants, and features 12 months of battery life. The tag transmits a periodic location beacon and contains a low frequency receiver for detecting signals from GuardRFID® Tag Exciters.



TotTags work with the GuardRFID AllGuard® software with TotGuard® support to provide real-time location services. The tag's built-in dual tamper detection capability allows the software to generate an alarm if the tag is tampered or removed from the infant, while minimizing false alarms caused by normal infant care. The AllGuard software can be configured to control doors to speed newborns to scheduled medical examinations or protect babies from suspicious activity.

The band is carefully designed with clinicians in mind. The tag and band system was tested to ensure ease-of-use for nurses and comfort of infants.

Product	TT-2BLF
Model Number	61-10012
Software Compatibility	AllGuard 9.1.0 or later
Sensors	Reflective and IR tamper detection
Transmit Frequency	433 MHz
Receive Frequency	125 KHz
Battery Life	12 months
Beacon Interval	Active / inside exciter field: 12 seconds Idle: 2 minutes
Compatible with Mother Tags	Yes
Dimensions	Ø 28 x 12.2 mm (1.1 x 0.48")
Weight	6.4 g
Waterproof	Yes, designed to IP66
Operating Temperature	-10°C to +50°C (-14° F to 122° F)
Humidity	0-100%
Regulatory	FCC, IC
Warranty	12 months

Final product that is delivered may appear different




FEATURES:

- Unique dual-tamper detection capability to minimize false alarms
- Separate Check Tag Tightness Warning and Tag Tamper Alarm to allow for a clear escalation path
- Small and light for comfort
- 12 month battery life
- Easy application and can be worn while infant is bathed
- Designed in consultation with labor and delivery nurses

TotTag 2

TT-2BLF



ACCESSORIES



61-14031 – TotTag 2 Mounting Band (pack of 100)

- Soft, hypoallergenic material to ensure infant comfort
- Latex free
- Multiple hook and loop fasteners to support a wide range of sizes
- Quick dry to allow infants to be bathed while wearing the band and tag
- 220mm x 25mm (8.6" x 1")

 FCC ID: JQ6-TT2
ISED ID: 2236B-TT2

FCC

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference; (2) This device must accept any interference received, including interference that may cause undesired operation.

ISED

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:
(1) This device may not cause interference;
(2) This device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'ISED Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

(1) l'appareil ne doit pas produire débrouillage, et (2) l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

RF Exposure Considerations

This module complies with FCC and ISED RF radiation exposure limits set forth for an uncontrolled environment. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. RF Exposure - At least 20 cm of separation distance between the module and the user's body must be maintained at all times.

Déclaration d'Exposition aux RF

Ce dispositif est conforme aux limites d'exposition aux radiofréquences (RF) établies par ISED Canada pour un environnement non contrôlé. Cet émetteur ne doit pas être installé ou utilisé en conjonction avec une autre antenne ou un autre émetteur. Pour assurer la conformité aux exigences d'exposition aux RF, une distance de séparation d'au moins 20 cm doit être maintenue en tout temps entre ce dispositif et le corps de l'utilisateur.



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +44 1440 714 850

Asia Pacific: +852 3160 9800 | Latin America: +52 (55) 9171-1108

For more global phone numbers click here

© 2025 HID Global Corporation/ASSA ABLOY AB. All rights reserved.

2025-02-04-idt-rfid-tottag-2-ds-en

PLT-08102

Part of ASSA ABLOY