

The FCC logo, consisting of the letters 'F' and 'C' in a stylized, bold, black font, with a circle around the 'C'.

Test Report

Product Name : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
Model No. : S88
FCC ID. : JVPS88

Applicant : BenQ Corporation

Address : 157 Shan-Ying Road, Gueishan, Taoyuan 333, Taiwan, R.O.C.

Date of Receipt : Nov. 22, 2005
Issued Date : Jan. 24, 2006
Report No. : 05BL144-RF-US-P06V01
Reference No. : KH-6343

The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Test Report Certification

Issued Date: Jan. 24, 2006

Report No.: 05BL144-RF-US-P06V01



Product Name : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
Applicant : BenQ Corporation
Address : 157 Shan-Ying Road, Gueishan, Taoyuan 333, Taiwan, R.O.C.
Manufacturer : 1.BenQ Corporation
2.BenQ China Co., Ltd.
Model No. : S88
FCC ID. : JVPS88
Rated Voltage : AC 120V/60Hz
Working Voltage : Battery 3.7V
Trade Name : BenQ-Siemens
Applicable Standard : FCC CFR Title 47 Part 15 Subpart C: 2005
CISPR 22: 2005
ANSI C63.4: 2003

Test Result : Complied

The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of QuietTek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented By : Gina Chen
(Gina Chen)



Tested By : Tom Hsieh
(Tom Hsieh)

Approved By : Gene Chang
(Gene Chang)



TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION	5
1.1. EUT Description.....	5
1.2. Operational Description.....	6
1.3. Tested System Details.....	7
1.4. Configuration of Tested System	7
1.5. EUT Exercise Software	7
1.6. Test Facility	8
2. CONDUCTED EMISSION	9
2.1. Test Equipment.....	9
2.2. Test Setup	9
2.3. Limits.....	9
2.4. Test Procedure	10
2.5. Uncertainty	10
2.6. Test Result of Conducted Emission.....	11
3. PEAK POWER OUTPUT	13
3.1. Test Equipment.....	13
3.2. Test Setup	13
3.3. Limit	13
3.4. Uncertainty	13
3.5. Test Result of Peak Power Output.....	14
4. RADIATED EMISSION	15
4.1. Test Equipment.....	15
4.2. Test Setup	15
4.3. Limits.....	16
4.4. Test Procedure	16
4.5. Uncertainty	16
4.6. Test Result of Radiated Emission.....	17
5. BAND EDGE	23
5.1. Test Equipment.....	23
5.2. Test Setup	23
5.3. Limit	24
5.4. Test Procedure	24
5.5. Uncertainty	24
5.6. Test Result of Band Edge	25
6. CHANNEL NUMBER.....	29
6.1. Test Equipment.....	29
6.2. Test Setup	29
6.3. Limit	29
6.4. Uncertainty	29
6.5. Test Result of Channel Number.....	30
7. CHANNEL SEPARATION.....	32
7.1. Test Equipment.....	32
7.2. Test Setup	32
7.3. Limit	32
7.4. Uncertainty	32
7.5. Test Result of Channel Separation.....	33
8. DWELL TIME	34
8.1. Test Equipment.....	34
8.2. Test Setup	34
8.3. Limit	34
8.4. Uncertainty	34
8.5. Test Result of Dwell Time.....	35

9.	OCCUPIED BANDWIDTH	37
9.1.	Test Equipment	37
9.2.	Test Setup	37
9.3.	Limits.....	37
9.4.	Uncertainty	37
9.5.	Test Result of Occupied Bandwidth	38
10.	EMI REDUCTION METHOD DURING COMPLIANCE TESTING	41
Attachment 1: EUT Test Photographs		
Attachment 2: EUT Detailed Photographs		

1. GENERAL INFORMATION

1.1. EUT Description

Product Name : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Trade Name : BenQ-Siemens
 FCC ID. : JVPS88
 Model No. : S88
 Frequency Range : 2402 - 2480MHz
 Antenna Gain : Refer to the table "Antenna List"
 Channel Number : 79
 Type of Modulation : FHSS
 Antenna Type : Chip Antenna
 Channel Control : Auto

Antenna List

No.	Manufacturer	Part No.	Peak Gain
1	ACX	AT3216 Series	0.5dBi

Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 00:	2402 MHz	Channel 20:	2422 MHz	Channel 40:	2442 MHz	Channel 60:	2462 MHz
Channel 01:	2403 MHz	Channel 21:	2423 MHz	Channel 41:	2443 MHz	Channel 61:	2463 MHz
Channel 02:	2404 MHz	Channel 22:	2424 MHz	Channel 42:	2444 MHz	Channel 62:	2464 MHz
Channel 03:	2405 MHz	Channel 23:	2425 MHz	Channel 43:	2445 MHz	Channel 63:	2465 MHz
Channel 04:	2406 MHz	Channel 24:	2426 MHz	Channel 44:	2446 MHz	Channel 64:	2466 MHz
Channel 05:	2407 MHz	Channel 25:	2427 MHz	Channel 45:	2447 MHz	Channel 65:	2467 MHz
Channel 06:	2408 MHz	Channel 26:	2428 MHz	Channel 46:	2448 MHz	Channel 66:	2468 MHz
Channel 07:	2409 MHz	Channel 27:	2429 MHz	Channel 47:	2449 MHz	Channel 67:	2469 MHz
Channel 08:	2410 MHz	Channel 28:	2430 MHz	Channel 48:	2450 MHz	Channel 68:	2470 MHz
Channel 09:	2411 MHz	Channel 29:	2431 MHz	Channel 49:	2451 MHz	Channel 69:	2471 MHz
Channel 10:	2412 MHz	Channel 30:	2432 MHz	Channel 50:	2452 MHz	Channel 70:	2472 MHz
Channel 11:	2413 MHz	Channel 31:	2433 MHz	Channel 51:	2453 MHz	Channel 71:	2473 MHz
Channel 12:	2414 MHz	Channel 32:	2434 MHz	Channel 52:	2454 MHz	Channel 72:	2474 MHz
Channel 13:	2415 MHz	Channel 33:	2435 MHz	Channel 53:	2455 MHz	Channel 73:	2475 MHz
Channel 14:	2416 MHz	Channel 34:	2436 MHz	Channel 54:	2456 MHz	Channel 74:	2476 MHz
Channel 15:	2417 MHz	Channel 35:	2437 MHz	Channel 55:	2457 MHz	Channel 75:	2477 MHz
Channel 16:	2418 MHz	Channel 36:	2438 MHz	Channel 56:	2458 MHz	Channel 76:	2478 MHz
Channel 17:	2419 MHz	Channel 37:	2439 MHz	Channel 57:	2459 MHz	Channel 77:	2479 MHz
Channel 18:	2420 MHz	Channel 38:	2440 MHz	Channel 58:	2460 MHz	Channel 78:	2480 MHz
Channel 19:	2421 MHz	Channel 39:	2441 MHz	Channel 59:	2461 MHz		

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. The transmitter is presented with a continuous data stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its 79 channels and over the minimum number of hopping channels (75 channels).

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Note:

1. This device is GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone including a 2.4GHz Bluetooth transceiver.
2. These tests are conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15 Subpart C Paragraph 15.247 for spread spectrum devices.
3. Regards to the frequency band operation; the lowest 、 middle and highest frequency of channel were selected to perform the test, then shown on this report.
4. This device is a composite device in accordance with Part 15 Subpart B regulations. The function for the receiver was measured and made a test report that the report number is 05BL144-RF-US-P01V01, certified under Declaration of Conformity.
5. QuieTek had verified among construction and function in typical operation, then shown in this test report.

1.2. Operational Description

The EUT is a GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone with 79 channels. This device provides wireless technology that revolutionizes personal connectivity. It is the solution for the seamless integration of Bluetooth technology into personal computer enabling short-range wireless connections between desktop/laptop computers, Bluetooth-enabled peripherals, and portable handheld devices.

Test Mode:	Mode 1: Transmitter
------------	---------------------


1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	FCC ID	Power Cord
(1) N/A	N/A	N/A	N/A	N/A	N/A

Signal Cable Type	Signal cable Description
A. N/A	N/A

1.4. Configuration of Tested System



1.5. EUT Exercise Software

- (1) Setup the EUT as shown in section 1.4.
- (2) Press “*#309#” into the test mode.
- (3) Setup the test channel and the test mode.
- (4) Start the continuous transmission.
- (5) Verify that the EUT works correctly.

1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

Site Description: June 22, 2001 File on
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046
Reference 31040/SIT1300F2



July 03, 2001 Accreditation on NVLAP
NVLAP Lab Code: 200533-0



Site Name: Quietek Corporation

Site Address: No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen,
Lin-Kou Shiang, Taipei,
Taiwan, R.O.C.
TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789
E-Mail : service@quietek.com



2. Conducted Emission


2.1. Test Equipment

The following test equipment are used during the conducted emission test:

Item	Instrument	Manufacturer	Type No./Serial No	Last Cal.	Remark
1	Test Receiver	R & S	ESCS 30/825442/17	May, 2005	
2	L.I.S.N.	R & S	ESH3-Z5/825016/6	May, 2005	EUT
3	L.I.S.N.	Kyoritsu	KNW-407/8-1420-3	May, 2005	Peripherals
4	Pulse Limiter	R & S	ESH3-Z2	May, 2005	
5	No.1 Shielded Room				

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

2.2. Test Setup



2.3. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dBuV) Limit		
Frequency MHz	Limits	
	QP	AV
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

Remarks: In the above table, the tighter limit applies at the band edges.

2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.

Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

2.5. Uncertainty

The measurement uncertainty is defined as ± 2.02 dB

2.6. Test Result of Conducted Emission

Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Conducted Emission Test
 Power Line : Line 1
 Test Mode : Mode 1: Transmitter (Channel 39)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBuV	dBuV	dB	dBuV
Quasi-Peak					
*0.177	0.202	48.240	48.442	-16.787	65.229
0.230	0.203	39.340	39.543	-24.172	63.714
0.290	0.204	35.420	35.624	-26.376	62.000
0.407	0.215	34.180	34.395	-24.262	58.657
5.689	0.432	40.020	40.451	-19.549	60.000
8.322	0.551	38.980	39.531	-20.469	60.000
Average					
0.177	0.202	32.350	32.552	-22.677	55.229
0.230	0.203	21.290	21.493	-32.222	53.714
0.290	0.204	26.970	27.174	-24.826	52.000
0.407	0.215	26.970	27.185	-21.472	48.657
*5.689	0.432	32.430	32.861	-17.139	50.000
8.322	0.551	30.400	30.951	-19.049	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. " * " means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Conducted Emission Test
 Power Line : Line 2
 Test Mode : Mode 1: Transmitter (Channel 39)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBuV	dBuV	dB	dBuV
Quasi-Peak					
0.170	0.202	38.110	38.312	-27.117	65.429
0.230	0.203	37.750	37.953	-25.762	63.714
0.291	0.204	36.980	37.184	-24.788	61.971
0.348	0.210	38.510	38.720	-21.623	60.343
3.459	0.335	39.410	39.745	-16.255	56.000
*5.330	0.391	43.770	44.161	-15.839	60.000
Average					
0.170	0.202	28.240	28.442	-26.987	55.429
0.230	0.203	29.000	29.203	-24.512	53.714
0.291	0.204	31.170	31.374	-20.598	51.971
0.348	0.210	30.640	30.850	-19.493	50.343
3.459	0.335	29.430	29.765	-16.235	46.000
*5.330	0.391	35.530	35.921	-14.079	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. " * " means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

3. Peak Power Output


3.1. Test Equipment

The following test equipments are used during the radiated emission tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	EMI Test Receiver	R & S	ESI 26 / 838786/004	May, 2005

Note: 1. All equipment upon which need to calibrated are with calibration period of 1 year.
2. Mark "X" test instruments are used to measure the final test results.

3.2. Test Setup



3.3. Limit

The maximum peak power shall be less 1Watt.




3.4. Uncertainty

The measurement uncertainty is defined as ± 1.27 dB

3.5. Test Result of Peak Power Output

Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Peak Power Output
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter

Channel No.	Frequency (MHz)	Measurement	Required Limit	Result
Channel 00	2402.00	-1.85dBm	1 Watt= 30 dBm	Pass
Channel 39	2441.00	-2.03dBm	1 Watt= 30 dBm	Pass
Channel 78	2480.00	-2.12dBm	1 Watt= 30 dBm	Pass



Note:

1. Receiver setting (Peak Detector): RBW: 1MHz; VBW: 1MHz; Span: 100MHz ◦

4. Radiated Emission


4.1. Test Equipment

The following test equipment are used during the radiated emission test:

Test Site	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☐ Site # 1	Test Receiver	R & S	ESVS 10 / 834468/003	May, 2005
	Spectrum Analyzer	Advantest	R3162/ 00803480	May, 2005
	Pre-Amplifier	Advantest	BB525C/ 3307A01812	May, 2005
	Bilog Antenna	SCHAFFNER	CBL6112B / 2697	Sep., 2005
☐ Site # 2	Test Receiver	R & S	ESCS 30 / 836858 / 022	May, 2005
	Spectrum Analyzer	Advantest	R3162 / 100803466	May, 2005
	Pre-Amplifier	Advantest	BB525C/3307A01814	May, 2005
	Bilog Antenna	SCHAFFNER	CBL6112B / 2705	May, 2005
	Horn Antenna	ETS	3115 / 0005-6160	Sep., 2005
	Pre-Amplifier	QTK	QTK-AMP-01/ 0001	May, 2005
☒ Site # 3	Test Receiver	R & S	ESI 26 / 838786 / 004	May, 2005
	Spectrum Analyzer	Advantest	R3162 / 100803480	May, 2005
	Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2005
	Bilog Antenna	SCHAFFNER	CBL6112B / 2697	May, 2005
	Horn Antenna	ETS	3115 / 0005-6160	July, 2005
	Pre-Amplifier	QTK	QTK-AMP-01 / 0001	July, 2005

Note: 1. All equipments that need to calibrate are with calibration period of 1 year.
2. Mark "X" test instruments are used to measure the final test results.

4.2. Test Setup



4.3. Limits

➤ General Radiated Emission Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209 Limits		
Frequency MHz	uV/m @3m	dBuV/m@3m
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Remarks: 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

4.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated measurement.

The additional latch filter below 1GHz was used to measure the level of harmonics radiated emission during field strength of harmonics measurement.

The bandwidth below 1GHz setting on the field strength meter (R&S Test Receiver ESCS 30)is 120 kHz, above 1GHz are 1 MHz.

The frequency range from 30MHz to 10th harmonics is checked.

4.5. Uncertainty

The measurement uncertainty above 1G is defined as ± 3.9 dB
under 1G is defined as ± 3.8 dB

4.6. Test Result of Radiated Emission

Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Harmonic Radiated Emission
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (Channel 00)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBuV	dBuV/m	dB	dBuV/m

Horizontal

Peak Detector:

4804.000	4.346	42.745	47.091	-26.879	73.970
7206.000	11.565	39.153	50.718	-23.252	73.970
9608.000	15.813	37.246	53.059	-20.911	73.970

Average Detector:

--

Vertical

Peak Detector:

4804.000	4.346	41.407	45.753	-28.217	73.970
7206.000	11.565	38.843	50.408	-23.562	73.970
9608.000	15.813	35.933	51.746	-22.224	73.970

Average Detector:

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Receiver setting (Peak Detector) : RBW:1MHz; VBW:1MHz; Span:100MHz °
3. Receiver setting (AVG Detector) : RBW:1MHz; VBW:30Hz; Span:20MHz °
4. Emission Level = Reading Level + Correct Factor.
5. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Harmonic Radiated Emission
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (Channel 39)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBuV	dBuV/m	dB	dBuV/m
Horizontal					
Peak Detector:					
4882.000	4.562	38.883	43.445	-30.525	73.970
7323.000	12.468	37.850	50.318	-23.652	73.970
9764.000	14.572	36.943	51.515	-22.455	73.970
Average Detector:					
--					
Vertical					
Peak Detector:					
4882.000	4.562	41.468	46.030	-27.940	73.970
7323.000	12.468	38.248	50.716	-23.254	73.970
9764.000	14.572	36.076	50.648	-23.322	73.970
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Receiver setting (Peak Detector) : RBW:1MHz; VBW:1MHz; Span:100MHz °
3. Receiver setting (AVG Detector) : RBW:1MHz; VBW:30Hz; Span:20MHz °
4. Emission Level = Reading Level + Correct Factor.
5. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Harmonic Radiated Emission
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (Channel 78)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBuV	dBuV/m	dB	dBuV/m
Horizontal					
Peak Detector:					
4960.000	4.804	40.871	45.674	-28.296	73.970
7440.000	12.912	37.876	50.788	-23.182	73.970
9920.000	14.271	36.437	50.708	-23.262	73.970
Average Detector:					
--					
Vertical					
Peak Detector:					
4960.000	4.804	43.234	48.037	-25.933	73.970
7440.000	12.912	38.366	51.278	-22.692	73.970
9920.000	14.271	36.764	51.035	-22.935	73.970
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Receiver setting (Peak Detector) : RBW:1MHz; VBW:1MHz; Span:100MHz °
3. Receiver setting (AVG Detector) : RBW:1MHz; VBW:30Hz; Span:20MHz °
4. Emission Level = Reading Level + Correct Factor..
5. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : General Radiated Emission
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (Channel 00)

Frequency	Correct	Reading	Measurement	Margin	Limit
	Factor	Level	Level		
MHz	dB	dBuV	dBuV/m	dB	dBuV/m
Horizontal					
105.180	12.655	15.030	27.685	-15.815	43.500
*207.100	9.777	21.100	30.877	-12.623	43.500
335.500	14.404	9.180	23.584	-22.416	46.000
340.100	14.639	8.420	23.059	-22.941	46.000
347.600	14.697	8.800	23.497	-22.503	46.000
380.100	15.603	8.100	23.704	-22.296	46.000
Vertical					
*42.100	12.264	16.670	28.934	-11.066	40.000
136.600	11.514	16.110	27.624	-15.876	43.500
206.100	10.020	17.400	27.420	-16.080	43.500
257.900	14.270	6.700	20.970	-25.030	46.000
371.900	16.662	7.800	24.462	-21.538	46.000
541.600	20.357	5.800	26.157	-19.843	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. “ * ” means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : General Radiated Emission
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (Channel 39)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dBuV	dBuV/m	dB	dBuV/m
Horizontal					
136.600	12.442	16.400	28.841	-14.659	43.500
141.500	11.996	13.700	25.696	-17.804	43.500
*209.400	9.804	20.500	30.304	-13.196	43.500
240.900	12.069	11.670	23.739	-22.261	46.000
294.300	13.915	15.400	29.315	-16.685	46.000
345.200	14.657	7.174	21.831	-24.169	46.000
Vertical					
141.600	11.211	13.790	25.001	-18.499	43.500
230.100	11.195	10.500	21.695	-24.305	46.000
240.990	12.465	1.290	13.755	-32.245	46.000
*294.300	13.808	15.360	29.168	-16.832	46.000
364.600	16.449	8.760	25.209	-20.791	46.000
381.600	16.688	6.090	22.778	-23.222	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. “ * ” means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : General Radiated Emission
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (Channel 78)

Frequency	Correct	Reading	Measurement	Margin	Limit
	Factor	Level	Level		
MHz	dB	dBuV	dBuV/m	dB	dBuV/m
Horizontal					
267.600	13.693	9.880	23.572	-22.428	46.000
*294.300	13.915	15.400	29.315	-16.685	46.000
310.100	13.734	14.800	28.533	-17.467	46.000
344.200	14.549	7.160	21.710	-24.290	46.000
364.500	15.766	8.870	24.635	-21.365	46.000
381.620	15.715	6.090	21.804	-24.196	46.000
Vertical					
136.600	11.514	10.980	22.494	-21.006	43.500
156.100	10.170	8.500	18.670	-24.830	43.500
177.800	9.648	9.800	19.448	-24.052	43.500
342.100	14.526	6.870	21.396	-24.604	46.000
*500.400	18.358	6.750	25.108	-20.892	46.000
515.100	18.691	6.700	25.392	-20.608	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. “ * ” means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

5. Band Edge

5.1. Test Equipment


The following test equipments are used during the band edge tests:

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X Spectrum Analyzer	Advantest	R3272 / 72421194	May, 2005
X Test Receiver	R & S	ESCS 30 / 825442/14	May, 2005
X Spectrum Analyzer	HP	E4407B / US39440758	May, 2005
X Pre-Amplifier	HP	8447D/3307A01812	May, 2005
X Bilog Antenna	Chase	CBL6112B / 12452	Sep., 2005
X Horn Antenna	EM	EM6917 / 103325	May, 2005

- Note:
1. All equipments that need to calibrate are with calibration period of 1 year.
 2. Mark "X" test instruments are used to measure the final test results.

5.2. Test Setup

RF Radiated Measurement:



5.3. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4:2003 on radiated measurement.

The bandwidth below 1GHz setting on the field strength meter (R&S Test Receiver ESCS 30)is 120 kHz, above 1GHz are 1 MHz.

5.5. Uncertainty

The measurement uncertainty above 1G is defined as ± 3.9 dB
under 1G is defined as ± 3.8 dB

5.6. Test Result of Band Edge

Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (Channel 01)


RF Radiated Measurement:

Channel No.	Frequency (MHz)	Required Limit (dBc)	Result
0	<2400	>20	Pass

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
00 (Peak)	2353.250	48.361	46.470	74.00	54.00	Pass
00 (Average)	--	--	--	74.00	54.00	Pass

Figure Channel 00: (Horizontal)



Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (Channel 01)


RF Radiated Measurement:

Channel No.	Frequency (MHz)	Required Limit (dBc)	Result
0	<2400	>20	Pass

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
00 (Peak)	2357.750	48.162	46.290	74.00	54.00	Pass
00(Average)	--	--	--	74.00	54.00	Pass

Figure Channel 00: (Vertical)




Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (Channel 78)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
78(Peak)	2495.750	47.852	46.490	74.00	54.00	Pass
78(Average)	--	--	--	74.00	54.00	Pass

Figure Channel 78: (Horizontal)




Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (Channel 78)

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
78(Peak)	2489.750	47.456	46.080	74.00	54.00	Pass
78(Average)	--	--	--	74.00	54.00	Pass

Figure Channel 78: (Vertical)



Note: The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

6. Channel Number


6.1. Test Equipment

The following test equipments are used during the radiated emission tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	EMI Test Receiver	R & S	ESI 26 / 838786/004	March, 2005

Note: 1. All equipment upon which need to calibrated are with calibration period of 1 year.
2. Mark "X" test instruments are used to measure the final test results.

6.2. Test Setup



6.3. Limit

Frequency hopping systems operating in the 2400-2483.5 MHz bands shall use at least 75 hopping frequencies.

6.4. Uncertainty


The measurement uncertainty is defined as $\pm 200\text{kHz}$

6.5. Test Result of Channel Number


Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Channel Number
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter

Frequency Range (MHz)	Measurement (Hopping Channel)	Required Limit (Hopping Channel)	Result
2402 ~ 2480	79	>75	Pass


2402-2411MHz




2412-2421MHz



2422-2431MHz




2432-2441MHz




Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Channel Number
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter


2442-2451MHz




2452-2461MHz



2462-2471MHz



2472-2481MHz



7. Channel Separation


7.1. Test Equipment

The following test equipments are used during the radiated emission tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	EMI Test Receiver	R & S	ESI 26 / 838786/004	May, 2005

Note: 1. All equipment upon which need to calibrated are with calibration period of 1 year.
2. Mark "X" test instruments are used to measure the final test results.

7.2. Test Setup



7.3. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

7.4. Uncertainty


The measurement uncertainty is defined as $\pm 150\text{Hz}$

7.5. Test Result of Channel Separation


Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Channel Separation
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter

Frequency (MHz)	Measurement Level (MHz)	Required Limit	Result
2402	1.00	>25 kHz or 2/3 * 20 dB BW	Pass
2441	1.00	>25 kHz or 2/3 * 20 dB BW	Pass
2480	1.00	>25 kHz or 2/3 * 20 dB BW	Pass


Channel 00 2402MHz



Channel 39 2441MHz



Channel 78 2480 MHz



8. Dwell Time


8.1. Test Equipment

The following test equipments are used during the radiated emission tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	EMI Test Receiver	R & S	ESI 26 / 838786/004	March, 2005

Note: 1. All equipment upon which need to calibrated are with calibration period of 1 year.
2. Mark "X" test instruments are used to measure the final test results.

8.2. Test Setup



8.3. Limit

The dwell time shall be the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.





8.4. Uncertainty

The measurement uncertainty is defined as $\pm 25\text{msec}$

8.5. Test Result of Dwell Time

Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Dwell Time
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (Channel 00,39,78 –DH5)

Channel (MHz)	Measurement Level (ms)	Required Limit (sec.)	Result
CH 00 2402	128.184	< 0.4	Pass
CH 39 2441	128.184	< 0.4	Pass
CH 78 2480	141.003	< 0.4	Pass



Note: Dwell time=time slot length * hop rate / number of hopping channels * period

Occupancy Time of Frequency Hopping System

Test Time Period: $0.4 \times 79 = 31.6\text{sec}$, Hopping Times Within 1sec: $40/50\text{msec} = 0.8 / \text{sec}$

A) 2402MHz The Maximum Occupancy Time Within 31.6sec: $(400 \mu \text{s} \times 800) / (79 \times 31.6) = 128.184\text{msec}$ °

B) 2441MHz The Maximum Occupancy Time Within 31.6sec: $(400 \mu \text{s} \times 800) / (79 \times 31.6) = 128.184\text{msec}$ °

C) 2480MHz The Maximum Occupancy Time Within 31.6sec: $(440 \mu \text{s} \times 800) / (79 \times 31.6) = 141.003\text{msec}$ °

Test Result: The Average Occupancy Time of Each Highest , Middle and Lowest Channel Is Less Than 0.4sec , And Corresponds to The Standard °

PS: (1) From Bluetooth Specification , It Hops 1600 Times in 1sec ° The Average Occupancy Time of Each 79 Channels is $1600/79$ Times , Therefore , We Calculate The Maximum Occupancy Time (worse cars) As Below:

A) 2402Mhz The Occupancy Time of Each Pulse is 0.4msec , The Maximum Occupancy Time within 31.6sec is $0.4\text{msec} \times 1640/79 \times 31.6 = 289.056\text{msec}$

B) 2441MHz The Occupancy Time of Each Pulse is 0.4msec , The Maximum Occupancy Time within 31.6sec is $0.4\text{msec} \times 1640/79 \times 31.6 = 289.056\text{msec}$

C) 2480MHz The Occupancy Time of Each Pulse is 0.4msec , The Maximum Occupancy Time within 31.6sec is $0.4\text{msec} \times 1640/79 \times 31.6 = 289.056\text{msec}$

Test Result: The Maximum Occupancy Time of Each Highest , Middle and Lowest Channel Is Less Than 0.4sec , And Corresponds to The Standard °

9. Occupied Bandwidth


9.1. Test Equipment

The following test equipments are used during the radiated emission tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	EMI Test Receiver	R & S	ESI 26 / 838786/004	May, 2005

Note: 1. All equipment upon which need to calibrated are with calibration period of 1 year.
2. Mark "X" test instruments are used to measure the final test results.

9.2. Test Setup



9.3. Limits

The minimum bandwidth shall be at least 500kHz.

9.4. Uncertainty


The measurement uncertainty is defined as ± 1.27 dB

9.5. Test Result of Occupied Bandwidth

Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2402MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
00	2402	350	>500	Pass


Figure Channel 00:



Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2441MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
39	2441	350	>500	Pass


Figure Channel 39:



Product : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (2480MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
78	2480	350	>500	Pass

Figure Channel 78:



10. EMI Reduction Method During Compliance Testing

No modification was made during testing.