



**849 NW State Road 45**  
**Newberry, FL 32669 USA**  
**Phone: 888.472.2424**  
**Fax: 352.472.2030**  
**Email: [info@timcoengr.com](mailto:info@timcoengr.com)**  
**Website: [www.timcoengr.com](http://www.timcoengr.com)**

## FCC PART 15

### SCANNING RECEIVER

<b>Applicant</b>	YAESU MUSEN CO., LTD.
<b>Address</b>	TENNOZU PARKSIDE BUILDING
	2-5-8 HIGASHI-SHINAGAWA, SHINAGAWA-KU, TOKYO 140-0002 JAPAN
<b>FCC ID:</b>	K6620523X50
<b>Model Number</b>	FTM-3200DR
<b>Product Description</b>	AMATEUR MOBILE RADIO -SCANNING RECEIVER 136-174 MHz
<b>Date Sample Received</b>	12/17/2015
<b>Date Tested</b>	01/07/2016
<b>Tested By</b>	Christian Pawlak
<b>Approved By</b>	Sid Sanders
<b>Test Results</b>	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

Report Number	Version Number	Description	Issue Date
2666AUT15TestReport.docx	Rev.1	Initial Issue	1/20/2016

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL  
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**

## TABLE OF CONTENTS

GENERAL REMARKS .....	3
REPORT SUMMARY PAGE.....	4
GENERAL INFORMATION .....	5
TEST PROCEDURE .....	6
RADIATED SPURIOUS EMISSIONS .....	7
TEST EQUIPMENT LIST.....	8

## GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

### Summary

The device under test does:

Fulfill the general approval requirements as identified in this test report  
 Not fulfill the general approval requirements as identified in this test report

### Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025: 2005 requirements.

I attest that the necessary measurements were made, under my supervision, at:

**Timco Engineering Inc.**  
**849 NW State Road 45**  
**Newberry, FL 32669**

### Authorized Signatory Name:



Christian Pawlak  
Engineering Project Manager

**Date:** 01/20/2016

[Table of Contents](#)

Applicant: YAESU MUSEN CO., LTD.  
FCC ID: K6620523X50  
MODEL #: FTM-3200DR  
Report: Y\YAESU\2666AUT15\2666AUT15TestReport.docx

## REPORT SUMMARY PAGE

### REPORT

Disclaimer	The test results only relate to the item tested.
Standards Applied Rule(s)	CFR 47 FCC Pt 15.109, Pt 15.107, ANSI C63.4: 2009
Related Report	NA

### ENVIRONMENT

Test Facility	<b>Timco Engineering, Inc. 849 NW State Road 45 Newberry, FL 32669 USA.</b>
Test Condition in the laboratory	Temperature: 24-26°C Relative humidity: 50-65%

### SETUP

Test Setup Diagram/ Description	The EUT was placed on the turntable per setup per ANSI C63.4: 2009. A test set up photo is provided for clarification.
Deviation from the standard/procedure	No deviation
Revision History of EUT	No modification

### RESULTS

15.109 Radiated Emissions	Pass
15.107 Powerline Conducted Emissions	Not Required
15.121(b) 38 dB Rejection Ratio	Not Required

### Table of Contents

Applicant: YAESU MUSEN CO., LTD.  
 FCC ID: K6620523X50  
 MODEL #: FTM-3200DR  
 Report: Y\YAESU\2666AUT15\2666AUT15TestReport.docx

## GENERAL INFORMATION

The test results relate only to the items tested.	
<b>EUT Description</b>	AMATEUR MOBILE RADIO -SCANNING RECEIVER
<b>FCC ID</b>	K6620523X50
<b>Model Number</b>	FTM-3200DR
<b>EUT Power Source</b>	<input type="checkbox"/> 110–120Vac/50– 60Hz <input checked="" type="checkbox"/> DC Power <input type="checkbox"/> Battery Operated Exclusively
<b>Test Item</b>	<input type="checkbox"/> Prototype <input type="checkbox"/> Pre-Production <input checked="" type="checkbox"/> Production
<b>Modifications to EUT</b>	None
<b>Test Standards</b>	FCC Part 15, Subpart B, ANSI C63.4-2009

[Table of Contents](#)

## TEST PROCEDURE

**General:** This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

**Radiation Interference:** The test procedure used was ANSI C63.4-2009 using a spectrum analyzer with a pre-selector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The video bandwidth was always greater than or equal to the RBW.

**Formula of Conversion Factors:** The field strength at 3 m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB $\mu$ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the spectrum analyzer Meter Reading.

**Example:**

Freq (MHz)	Meter Reading	+ ACF	+CL	= FS
33	20 dB $\mu$ V	+ 10.36 dB/m	+0.40 dB	=30.76 dB $\mu$ V/m @ 3m

**ANSI C63.4-2009 Section 10.1.7 Measurement Procedures:** The unit under test was placed on a table 80 cm high and with dimensions of 1 by 1.5 meters. The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1 to 4 meters. The antenna was placed in both the horizontal and vertical planes.

If power line conducted testing was required for this device, the situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSI C63.4-2009 with the EUT 40 cm from the vertical ground wall.

[Table of Contents](#)

## RADIATED SPURIOUS EMISSIONS

Rules Part No.: 15.109

### Requirements:

Frequency	Limits
30 – 88	40.0 dB $\mu$ V/m measured @ 3 meters
80 – 216	43.5 dB $\mu$ V/m measured @ 3 meters
216 – 960	46.0 dB $\mu$ V/m measured @ 3 meters
Above 960	54.0 dB $\mu$ V/m measured @ 3 meters

**Test Procedure:** The procedure used was ANSI C63.4-2009. The frequency was scanned from 30 MHz to 2 GHz. When an emission was found, the table was rotated to produce the maximum signal strength. The EUT was measured in three (3) orthogonal planes.

### Test Data:

Emission Frequency MHz	Meter Reading dB $\mu$ V	Antenna Polarity	Coax Loss dB	Correction Factor dB/m	Field Strength dB $\mu$ V/m	Margin dB
35.79	9.45	V	0.68	13.38	23.51	16.49
66.79	8.74	V	0.97	6.02	15.73	24.27
95.41	8.61	V	1.15	10.74	20.50	23.00
133.57	11.54	H	1.33	13.77	26.64	16.86
209.62	8.56	V	1.65	10.71	20.92	22.58
248.10	8.47	V	1.84	11.41	21.72	24.28
687.37	7.59	H	3.03	21.31	31.93	14.07

### Results Meet Requirements

[Table of Contents](#)

**TEST EQUIPMENT LIST**

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
Antenna: Biconnical Chamber	Eaton Chamber	94455-1	1057	11/18/15	11/18/17
Antenna: Log-Periodic Chamber	Electro-Metrics	LPA-25	1122	07/14/15	07/14/17
LISN	Electro-Metrics	ANS-25/2	2604	07/15/15	07/15/17
LISN (Primary)	Electro-Metrics	EM-7820	2682	05/08/15	05/08/17
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	01/05/16	03/01/16
Antenna: Double-Ridged Horn/ETS Horn 2	ETS-Lindgren	3117	00041534	02/25/15	02/25/17
EMI Test Receiver R & S ESIB 40 Screen Room	Rohde & Schwarz	ESIB 40	100274	08/12/14	08/12/16
Software: Field Strength Program	Timco	N/A	Version 4.0	12/12/99	12/12/99
EMI Test Receiver R & S ESU 40 Chamber	Rohde & Schwarz	ESU 40	100320	03/11/14	03/11/16

**\*EMI RECEIVER SOFTWARE VERSION**

The receiver firmware used was version 4.43 Service Pack 3

[Table of Contents](#)