



**M. Flom Associates, Inc. - Global Compliance Center**

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

---

T R A N S M I T T E R      C E R T I F I C A T I O N

of

FCC ID: K66VX-3200U-3

MODEL: VX-3200U-3

to

FEDERAL COMMUNICATIONS COMMISSION

Rule Part(s) 90, 90.210

DATE OF REPORT: December 23, 2002

ON THE BEHALF OF THE APPLICANT:

Vertex Standard Co., Ltd.

AT THE REQUEST OF:

P.O. UPS 12/10/2002

Vertex Standard USA Inc.  
10900 Walker Street  
Cypress, CA 90630

Attention of:

Mikio Maruya, Executive Vice President  
(800) 255-9237; FAX: (800) 477-9237  
(714) 827-7600; FAX: -8100  
m.maruya@vxstdusa.com

SUPERVISED BY:

  
Morton Flom, P. Eng.

THE APPLICANT HAS BEEN CAUTIONED AS TO THE FOLLOWING:

15.21 INFORMATION TO USER.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) SPECIAL ACCESSORIES.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

TABLE OF CONTENTS

<u>RULE</u>	<u>DESCRIPTION</u>	<u>PAGE</u>
	Test Report	1
2.1033(c)	General Information Required	2
2.1033(c)(14)	Rule Summary	7
	Standard Test Conditions and Engineering Practices	8
2.1046(a)	Carrier Output Power (Conducted)	9
2.1046(a)	ERP Carrier Power (Radiated)	11
2.1051	Unwanted Emissions (Transmitter Conducted)	12
2.1053(a)	Field Strength of Spurious Radiation	16
2.1049(c)(1)	Emission Masks (Occupied Bandwidth)	20
90.214	Transient Frequency Behavior	28
2.1047(a)	Audio Low Pass Filter (Voice Input)	34
2.1047(a)	Audio Frequency Response	37
2.1047(b)	Modulation Limiting	39
2.1055(a)(1)	Frequency Stability (Temperature Variation)	42
2.1055(b)(1)	Frequency Stability (Voltage Variation)	45
2.202(g)	Necessary Bandwidth and Emission Bandwidth	46

PAGE NO.

1 of 46.

*Required information per ISO/IEC Guide 25-1990, paragraph 13.2:*

a) TEST REPORT

b) Laboratory: M. Flom Associates, Inc.  
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107  
(Canada: IC 2044) Chandler, AZ 85225

c) Report Number: d02c0029

d) Client: Vertex Standard USA Inc.  
10900 Walker Street  
Cypress, CA 90630

e) Identification: VX-3200U-3  
EUT Description: FCC ID: K66VX-3200U-3  
UHF FM Mobile Transceiver

f) EUT Condition: Not required unless specified in individual tests.

g) Report Date: December 23, 2002  
EUT Received:

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with MFA internal quality manual.

m) Supervised by:

  
Morton Flom, P. Eng.

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

PAGE NO.

2 of 46.

LIST OF GENERAL INFORMATION REQUIRED FOR CERTIFICATIONIN ACCORDANCE WITH FCC RULES AND REGULATIONS,  
VOLUME II, PART 2 AND TO

90, 90.210

Sub-part 2.1033(c)(1): NAME AND ADDRESS OF APPLICANT:Vertex Standard Co., Ltd.  
4-8-8 Nakameguro, Meguro-Ku  
Tokyo 153-8644 JapanMANUFACTURER:Vertex Standard Co., Ltd.  
4-8-8 Nakameguro, Meguro-Ku  
Tokyo 153-8644 Japan(c)(2): FCC ID: K66VX-3200U-3MODEL NO: VX-3200U-3(c)(3): INSTRUCTION MANUAL(S):

PLEASE SEE ATTACHED EXHIBITS

(c)(4): TYPE OF EMISSION: 16K0F3E, 11K0F3E(c)(5): FREQUENCY RANGE, MHz: 480 to 512(c)(6): POWER RATING, Watts: 10 to 45  
\_\_\_\_ Switchable  Variable  N/A

FCC GRANT NOTE: BF - The output power is continuously variable from the value listed in this entry to 20%-25% of the value listed.

(c)(7): MAXIMUM POWER RATING, Watts: 300DUT RESULTS: Passes  Fails

PAGE NO.

3 of 46.

INFORMATION FOR PUSH-TO-TALK DEVICES

Type and number of antenna to be used for this device:  
(1), 0dBd

Maximum antenna gain for antenna indicated above:  
0 dBd

Can this device sustain continuous operation with respect to its hardware capabilities and allowable operating functions?  
No

Other hardware or operating restrictions that could limit a person's RF Exposure:

In Manual and Instructions to Installers and Users

Source-based time-averaging (see 2.1093 of rules) applicable to reduce the average output power:

No

If device has headset and belt-clip accessories that would allow body-worn operations, what is the minimum separation distance between the antenna and the user's body in this operating configuration?

N/A

Can device access wire-line services to make phone calls, either directly or through an operator?

No

Can specific operating instructions be given to users to eliminate any potential RF Exposure concerns for both front-of-the-face and body-worn operating configurations?

In Manual and Instructions to Installers and Users


Other applicable information the applicant may provide that can serve as effective means for ensuring RF Exposure compliance:

In Manual

PAGE NO.

4 of 46.

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Accreditation (A2LA) as shown in the scope below.



"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not be covered by this laboratory's A2LA accreditation.

PAGE NO.

5 of 46.

Subpart 2.1033 (continued)

(c)(8): VOLTAGES & CURRENTS IN ALL ELEMENTS IN FINAL R. F. STAGE,  
INCLUDING FINAL TRANSISTOR OR SOLID STATE DEVICE:

COLLECTOR CURRENT, A = per manual  
COLLECTOR VOLTAGE, Vdc = per manual  
SUPPLY VOLTAGE, Vdc = 13.6

(c)(9): TUNE-UP PROCEDURE:

PLEASE SEE ATTACHED EXHIBITS

(c)(10): CIRCUIT DIAGRAM/CIRCUIT DESCRIPTION:

Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

PLEASE SEE ATTACHED EXHIBITS

(c)(11): LABEL INFORMATION:

PLEASE SEE ATTACHED EXHIBITS

(c)(12): PHOTOGRAPHS:

PLEASE SEE ATTACHED EXHIBITS

(c)(13): DIGITAL MODULATION DESCRIPTION:

       ATTACHED EXHIBITS  
      x N/A

(c)(14): TEST AND MEASUREMENT DATA:

FOLLOWS

PAGE NO.

6 of 46.

PAGE INTENTIONALLY LEFT BLANK

PAGE NO.

7 of 46.

Sub-part

2.1033(c)(14):TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- \_\_\_\_ 21 - Domestic Public Fixed Radio Services
- \_\_\_\_ 22 - Public Mobile Services
- \_\_\_\_ 22 Subpart H - Cellular Radiotelephone Service
- \_\_\_\_ 22.901(d) - Alternative technologies and auxiliary services
- \_\_\_\_ 23 - International Fixed Public Radiocommunication services
- \_\_\_\_ 24 - Personal Communications Services
- \_\_\_\_ 74 Subpart H - Low Power Auxiliary Stations
- \_\_\_\_ 80 - Stations in the Maritime Services
- \_\_\_\_ 80 Subpart E - General Technical Standards
- \_\_\_\_ 80 Subpart F - Equipment Authorization for Compulsory Ships
- \_\_\_\_ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- \_\_\_\_ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- \_\_\_\_ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- \_\_\_\_ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- \_\_\_\_ 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
- \_\_\_\_ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- \_\_\_\_ 80 Subpart X - Voluntary Radio Installations
- \_\_\_\_ 87 - Aviation Services
- \_\_\_\_ x 90 - Private Land Mobile Radio Services
- \_\_\_\_ 94 - Private Operational-Fixed Microwave Service
- \_\_\_\_ 95 Subpart A - General Mobile Radio Service (GMRS)
- \_\_\_\_ 95 Subpart C - Radio Control (R/C) Radio Service
- \_\_\_\_ 95 Subpart D - Citizens Band (CB) Radio Service
- \_\_\_\_ 95 Subpart E - Family Radio Service
- \_\_\_\_ 95 Subpart F - Interactive Video and Data Service (IVDS)
- \_\_\_\_ 97 - Amateur Radio Service
- \_\_\_\_ 101 - Fixed Microwave Services

PAGE NO.

8 of 46.

STANDARD TEST CONDITIONS  
and  
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2000 Draft, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 9 of 46.  
NAME OF TEST: Carrier Output Power (Conducted)  
SPECIFICATION: 47 CFR 2.1046(a)  
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1  
TEST EQUIPMENT: As per attached page


MEASUREMENT PROCEDURE

1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.
2. Measurement accuracy is  $\pm 3\%$ .

MEASUREMENT RESULTS  
(Worst case)

FREQUENCY OF CARRIER, MHz = 496.1, 480.0, 512.0

POWER SETTING	R. F. POWER, WATTS
Low	10
High	45


PERFORMED BY:  Doug Noble, B.A.S. E.E.T.

PAGE NO.

10 of 46.

TRANSMITTER POWER CONDUCTED MEASUREMENTS

TEST 1: R. F. POWER OUTPUT  
 TEST 2: FREQUENCY STABILITY



Transmitter Power Conducted Measurements

Asset Description (as applicable)	s/n
(1) COAXIAL ATTENUATOR	
i00122 Narda 766-10	7802
i00123 Narda 766-10	7802A
i00069 Bird 8329 (30 dB)	1006
i00113 Sierra 661A-3D	1059
(2) POWER METERS	
i00014 HP 435A	1733A05836
i00039 HP 436A	2709A26776
i00020 HP 8901A POWER MODE	2105A01087
(3) FREQUENCY COUNTER	
i00042 HP 5383A	1628A00959
i00019 HP 5334B	2704A00347
i00020 HP 8901A FREQUENCY MODE	2105A01087

PAGE NO.

11 of 46.

NAME OF TEST:

ERP Carrier Power (Radiated)


SPECIFICATION:

TIA/EIA 603A (Substitution Method)

2.2.17.1 Definition: The average radiated power of a licensed device is the equivalent power required, when delivered to a half-wave dipole or horn antenna, to produce at a distant point the same average received power as produced by the licensed device.

2.2.17.2 Method of Measurement:

a) Connect the equipment as illustrated. Place the transmitter to be tested on the turntable in the standard test site.



b) Raise and lower the test antenna from 1m to 6 m with the transmitter facing the antenna and record the highest received signal in dB as LVL.

c) Repeat step b) for seven additional readings at 45° interval positions of the turntable.

d) Replace the transmitter under test with a half-wave or horn vertically polarized antenna. The center of the antenna should be at the same location as the transmitter under test. Connect the antenna to a signal generator with a known output power and record the path loss in dB or LOSS.

e) Calculate the average radiated output power from the readings in step c) and d) by the following:

$$\text{average radiated power} = 10 \log_{10} \sum 10(\text{LVL} - \text{LOSS})/10 \text{ (dBm)}$$

	480 MHz		496.1 MHz		512 MHz	
	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db
0°	47.4	1.3	47.9	1.3	45.7	0.8
45°	47.8	1.3	47.5	1.3	46.3	0.8
90°	47.8	1.3	47.5	1.3	44.1	0.8
135°	47.2	1.3	46.8	1.3	46.5	0.8
180°	46.7	1.3	46.8	1.3	46.7	0.8
225°	46.1	1.3	44.6	1.3	45.4	0.8
270°	46.0	1.3	45.8	1.3	44.1	0.8
315°	46.0	1.3	47.6	1.3	45.5	0.8

	480 MHz	496.1 MHz	512 MHz
Av. Radiated Power:	45.58 dbm	45.51 dbm	45.54 dbm

PAGE NO. 12 of 46.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

SPECIFICATION: 47 CFR 2.1051

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.13

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The emissions were measured for the worst case as follows:
  - (a): within a band of frequencies defined by the carrier frequency plus and minus one channel.
  - (b): from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.
2. The magnitude of spurious emissions that are attenuated more than 20 dB below the permissible value need not be specified.
3. MEASUREMENT RESULTS: ATTACHED FOR WORST CASE


FREQUENCY OF CARRIER, MHz = 496.1, 480.0, 512.0

SPECTRUM SEARCHED, GHz = 0 to  $10 \times F_c$

MAXIMUM RESPONSE, Hz = 2510

ALL OTHER EMISSIONS =  $\geq 20$  dB BELOW LIMIT

PERFORMED BY:


  
Doug Noble, B.A.S. E.E.T.

PAGE NO.

13 of 46.

TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)  
 TEST B. OUT-OF-BAND SPURIOUS



Asset Description (as applicable)	s/n
(1) <u>AUDIO OSCILLATOR/GENERATOR</u>	
i00010 HP 204D	1105A04683
i00017 HP 8903A	2216A01753
i00012 HP 3312A	1432A11250
(2) <u>COAXIAL ATTENUATOR</u>	
i00122 Narda 766-10	7802
i00123 Narda 766-10	7802A
i00069 Bird 8329 (30 dB)	1006
i00113 Sierra 661A-3D	1059
(3) <u>FILTERS; NOTCH, HP, LP, BP</u>	
i00126 Eagle TNF-1	100-250
i00125 Eagle TNF-1	50-60
i00124 Eagle TNF-1	250-850
(4) <u>SPECTRUM ANALYZER</u>	
i00048 HP 8566B	2511A01467
i00029 HP 8563E	3213A00104

PAGE NO.

14 of 46.

NAME OF TEST:

Unwanted Emissions (Transmitter Conducted)

LIMIT(S), dBc -(43+10xLOG P) = -53 (10 Watts)  
-(43+10xLOG P) = -59.5 (45 Watts)

g02c0163: 2002-Dec-17 Tue 11:43:00 STATE: 1:Low Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
480.000000	959.766500	-41.2	-81.4	-28.2
496.100000	992.113500	-42.4	-82.6	-29.4
512.000000	1024.091000	-41.2	-81.4	-28.2
480.000000	1439.821000	-40.3	-80.5	-27.3
496.100000	1488.171500	-41.8	-82	-28.8
512.000000	1536.034500	-41.8	-82	-28.8
480.000000	1920.076500	-39.5	-79.7	-26.5
496.100000	1984.571000	-40.4	-80.6	-27.4
512.000000	2047.898000	-39.9	-80.1	-26.9
480.000000	2400.031000	-39.6	-79.8	-26.6
496.100000	2480.693500	-40.6	-80.8	-27.6
512.000000	2559.981500	-42	-82.2	-29
480.000000	2879.897500	-43.1	-83.3	-30.1
496.100000	2976.590500	-42.9	-83.1	-29.9
512.000000	3071.906500	-42.5	-82.7	-29.5
480.000000	3360.210500	-42.8	-83	-29.8
496.100000	3472.843500	-42.9	-83.1	-29.9
512.000000	3584.019000	-42.4	-82.6	-29.4
480.000000	3840.099500	-43.4	-83.6	-30.4
496.100000	3969.026000	-42.4	-82.6	-29.4
512.000000	4096.239500	-43.1	-83.3	-30.1
480.000000	4319.760000	-41.4	-81.6	-28.4
496.100000	4465.120500	-41.9	-82.1	-28.9
512.000000	4608.210500	-42.6	-82.8	-29.6
480.000000	4800.181000	-43.3	-83.5	-30.3
496.100000	4960.805500	-41.1	-81.3	-28.1
512.000000	5120.233500	-42.5	-82.7	-29.5
480.000000	5280.059500	-43.2	-83.4	-30.2
496.100000	5457.016500	-42.2	-82.4	-29.2
512.000000	5631.987000	-43	-83.2	-30
480.000000	5759.835500	-43.3	-83.5	-30.3
496.100000	5953.222400	-37.2	-77.4	-24.2
512.000000	6143.988000	-37	-77.2	-24
480.000000	6239.922300	-36	-76.2	-23
496.100000	6449.226300	-37.2	-77.4	-24.2
512.000000	6656.112100	-37.1	-77.3	-24.1
480.000000	6720.197700	-36	-76.2	-23
496.100000	6945.427400	-35.3	-75.5	-22.3
512.000000	7168.003500	-36.7	-76.9	-23.7
480.000000	7199.812300	-36.8	-77	-23.8
496.100000	7441.433300	-37.4	-77.6	-24.4
512.000000	7680.016400	-35.4	-75.6	-22.4

PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO.

15 of 46.

NAME OF TEST:

Unwanted Emissions (Transmitter Conducted)

LIMIT(S), dBc -(43+10xLOG P) = -53 (10 Watts)  
 -(43+10xLOG P) = -59.5 (45 Watts)

g02c0162: 2002-Dec-17 Tue 11:40:00 STATE: 2:High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
480.000000	960.107500	-31.1	-77.5	-18.1
496.100000	992.097000	-32.5	-78.9	-19.5
512.000000	1024.100000	-31.5	-77.9	-18.5
480.000000	1439.861500	-31.7	-78.1	-18.7
496.100000	1488.418500	-31.7	-78.1	-18.7
512.000000	1536.114000	-32	-78.4	-19
480.000000	1920.137500	-30.5	-76.9	-17.5
496.100000	1984.453500	-29.2	-75.6	-16.2
512.000000	2048.188500	-30.2	-76.6	-17.2
480.000000	2399.878000	-30	-76.4	-17
496.100000	2480.507000	-29.8	-76.2	-16.8
512.000000	2559.802000	-32	-78.4	-19
480.000000	2880.006500	-32.7	-79.1	-19.7
496.100000	2976.767000	-32.5	-78.9	-19.5
512.000000	3072.056000	-32	-78.4	-19
480.000000	3359.756000	-34.2	-80.6	-21.2
496.100000	3472.482000	-34	-80.4	-21
512.000000	3583.888000	-33.3	-79.7	-20.3
480.000000	3839.846000	-32.8	-79.2	-19.8
496.100000	3968.938000	-33.7	-80.1	-20.7
512.000000	4095.812500	-33.4	-79.8	-20.4
480.000000	4320.068000	-33.7	-80.1	-20.7
496.100000	4464.768500	-32.9	-79.3	-19.9
512.000000	4607.937000	-33.2	-79.6	-20.2
480.000000	4799.916000	-32.8	-79.2	-19.8
496.100000	4960.894000	-32.7	-79.1	-19.7
512.000000	5120.121000	-32.4	-78.8	-19.4
480.000000	5279.844500	-31.7	-78.1	-18.7
496.100000	5457.273500	-32	-78.4	-19
512.000000	5631.969500	-33.5	-79.9	-20.5
480.000000	5760.184000	-32.8	-79.2	-19.8
496.100000	5953.334000	-26.2	-72.6	-13.2
512.000000	6143.786400	-27	-73.4	-14
480.000000	6239.878500	-26.4	-72.8	-13.4
496.100000	6449.530600	-26.9	-73.3	-13.9
512.000000	6655.856600	-26.6	-73	-13.6
480.000000	6720.018900	-25.5	-71.9	-12.5
496.100000	6945.349200	-26.2	-72.6	-13.2
512.000000	7168.211200	-26.7	-73.1	-13.7
480.000000	7200.200700	-27.7	-74.1	-14.7
496.100000	7441.693700	-26.8	-73.2	-13.8
512.000000	7680.058800	-27	-73.4	-14

PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO. 16 of 46.

NAME OF TEST: Field Strength of Spurious Radiation

SPECIFICATION: 47 CFR 2.1053(a)


GUIDE: ANSI/TIA/EIA-603-1992/2001, Paragraph 1.2.12 and Table 16, 47 CFR 22.917

MEASUREMENT PROCEDURE

1.2.12.1 Definition: Radiated spurious emissions are emissions from the equipment when transmitting into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.

1.2.12.2 Method of Measurement

- A) Connect the equipment as illustrated
- B) Adjust the spectrum analyzer for the following settings:
  - 1) Resolution Bandwidth 100 kHz (<1 GHZ), 1 MHZ (> 1GHz).
  - 2) Video Bandwidth  $\geq$  3 times Resolution Bandwidth, or 30 kHz (22.917)
  - 3) Sweep Speed  $\leq$  2000 Hz/second
  - 4) Detector Mode = Mean or Average Power
- C) Place the transmitter to be tested on the turntable in the standard test site. The transmitter is transmitting into a non-radiating load which is placed on the turntable. The RF cable to this load should be of minimum length.



PAGE NO.


17 of 46.

NAME OF TEST: Field Strength of Spurious Radiation (Cont.)

D) For each spurious measurement the test antenna should be adjusted to the correct length for the frequency involved. This length may be determined from a calibration ruler supplied with the equipment. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to  $\pm$  the test bandwidth (see section 1.3.4.4).

E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.

F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.



G) Reconnect the equipment as illustrated.

H) Keep the spectrum analyzer adjusted as in step B).

I) Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.

PAGE NO.

18 of 46.

NAME OF TEST: Field Strength of Spurious Radiation (Cont.)

J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.

K) Repeat step J) with both antennas vertically polarized for each spurious frequency.

L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.

M) The levels recorded in step L) are absolute levels of radiated spurious emissions in dBm. The radiated spurious emissions in dB can be calculated by the following:

Radiated spurious emissions dB =  
 $10\log_{10}(\text{TX power in watts}/0.001) - \text{the levels in step 1})$

NOTE: It is permissible that other antennas provided can be referenced to a dipole.

Test Equipment:

Asset	Description (as applicable)	s/n	Cycle	Last Cal
Per ANSI C63.4-1992/2000 Draft, 10.1.4				
<u>TRANSDUCER</u>				
i00088	EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Sep-02
i00065	EMCO 3301-B Active Monopole	2635	12 mo.	Sep-02
i00089	Aprel 2001 200MHz-1GHz	001500	12 mo.	Sep-02
i00103	EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Sep-02
<u>AMPLIFIER</u>				
i00028	HP 8449A	2749A00121	12 mo.	Mar-02
SPECTRUM ANALYZER				
i00029	HP 8563E	3213A00104	12 mo.	Jan-02
i00033	HP 85462A	3625A00357	12 mo.	Jan-02
i00048	HP 8566B	2511AD1467	6 mo.	Jul-02
<u>MICROPHONE, ANTENNA PORT, AND CABLING</u>				
Microphone	Yes/No	Y	Cable Length	1.0 Meters
Antenna Port Terminated	Yes/No	Y	Load	Y
All Ports Terminated by	Load	N/A	Antenna Gain	0 dBd
			Peripheral	No

PAGE NO.

19 of 46.

NAME OF TEST: Field Strength of Spurious Radiation

g02c0169: 2002-Dec-19 Thu 13:38:00

STATE: 2:High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	METER, dBuV	CF, dB	ERP, dBm	MARGIN, dB
496.100000	992.200000	31.07	2.26	-64	-51.1
496.100000	1488.292499	54.03	-1.68	-45	-32.1
496.100000	1984.393332	67.7	1.01	-28.7	-15.7
496.100000	2480.496665	67.37	2.65	-27.4	-14.4
496.100000	2976.608332	45.7	4.48	-47.2	-34.2
496.100000	3472.701665	59.7	6.16	-31.5	-18.5
496.100000	3968.805831	62.7	7.62	-27.1	-14.1
496.100000	4464.900831	44.7	7.17	-45.5	-32.5
496.100000	4961.008330	43.7	8.87	-44.8	-31.8

SUPERVISED BY:

  
 Doug Noble, B.A.S. E.E.T.

PAGE NO. 20 of 46.

NAME OF TEST: Emission Masks (Occupied Bandwidth)

SPECIFICATION: 47 CFR 2.1049(c)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11

TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for  $\pm 2.5/\pm 1.25$  kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

21 of 46.

NAME OF TEST: Emission Masks (Occupied Bandwidth)  
g02c0156: 2002-Dec-17 Tue 10:46:00  
STATE: 1:Low Power



POWER: LOW  
 MODULATION: NONE


PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO.

22 of 46.

NAME OF TEST: Emission Masks (Occupied Bandwidth)  
 g02c0157: 2002-Dec-17 Tue 10:48:00  
 STATE: 1:Low Power



POWER:  
 MODULATION:

LOW  
 VOICE: 2500 Hz SINE WAVE  
 MASK: B, VHF/UHF 25kHz,  
 w/LPF


PERFORMED BY:

  
 Doug Noble, B.A.S. E.E.T.

PAGE NO.

23 of 46.

NAME OF TEST: Emission Masks (Occupied Bandwidth)  
 g02c0160: 2002-Dec-17 Tue 10:54:00  
 STATE: 1:Low Power



POWER:  
 MODULATION:

LOW  
 VOICE: 2500 Hz SINE WAVE  
 MASK: D, VHF/UHF 12.5kHz BW


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

24 of 46.

NAME OF TEST: Emission Masks (Occupied Bandwidth)  
 g02c0155: 2002-Dec-17 Tue 10:44:00  
 STATE: 2:High Power



POWER: HIGH  
 MODULATION: NONE


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

25 of 46.

NAME OF TEST: Emission Masks (Occupied Bandwidth)  
 g02c0158: 2002-Dec-17 Tue 10:49:00  
 STATE: 2:High Power



POWER:  
 MODULATION:

HIGH  
 VOICE: 2500 Hz SINE WAVE  
 MASK: B, VHF/UHF 25kHz,  
 w/LPF

PERFORMED BY:




Doug Noble, B.A.S. E.E.T.

PAGE NO.

26 of 46.

NAME OF TEST: Emission Masks (Occupied Bandwidth)  
 g02c0159: 2002-Dec-17 Tue 10:52:00  
 STATE: 2:High Power



POWER:  
 MODULATION:

HIGH  
 VOICE: 2500 Hz SINE WAVE  
 MASK: D, VHF/UHF 12.5kHz BW


PERFORMED BY:

  
 Doug Noble, B.A.S. E.E.T.

PAGE NO.

27 of 46.

NAME OF TEST: Emission Masks (Occupied Bandwidth)  
 g02c0161: 2002-Dec-17 Tue 10:56:00  
 STATE: 2:High Power



POWER:  
 MODULATION:

HIGH  
 VOICE: 2500 Hz SINE WAVE  
 99 5 POWER BANDWIDTH

PERFORMED BY:

Doug Noble, B.A.S. E.E.T.



PAGE NO. 28 of 46.

NAME OF TEST: Transient Frequency Behavior

SPECIFICATION: 47 CFR 90.214

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.19

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was setup as shown on the attached page, following TIA/EIA-603 steps a, b, and c as a *guide*.

2. The transmitter was turned on.

3. Sufficient attenuation was provided so that the transmitter carrier level measured at the output of the combiner was 40 dB below the maximum input level of the test receiver. This level was recorded as step f.

4. The transmitter was turned off.

5. An RF signal generator (1) modulated with a 1 kHz tone at either 25, 12.5, or 6.25 kHz deviation, and set to the same frequency as the assigned transmitter frequency, (2) was adjusted to a level -20 dB below the level recorded for step f, as measured at the output of the combiner. This level was then fixed for the remainder of the test and is recorded at step h.

6. The oscilloscope was setup using TIA/EIA-603 steps j and k as a guide, and to either 10 ms/div (UHF) or 5 ms/div (VHF).


7. The 30 dB attenuator was removed, the transmitter was turned on, and the level of the carrier at the output of the combiner was recorded as step l.

8. The carrier on-time as referenced in TIA/EIA-603 steps m, n, and o was captured and plotted. The carrier off-time as referenced in TIA/EIA-603 steps p, q, r, and s was captured and plotted.


LEVELS MEASURED:

<u>step f</u> , dBm	=	-4.47
<u>step h</u> , dBm	=	-46.2
<u>step l</u> , dBm	=	4.4

PERFORMED BY:

  
Doug Noble, B.A.S. E.E.T.

## TRANSIENT FREQUENCY BEHAVIOR




Asset Description (as applicable)	s/n
(1) ATTENUATOR (Removed after 1st step) i00112 Philco 30 dB	989
(2) ATTENUATOR i00112 Philco 30 dB i00172 Bird 30 dB i00122 Narda 10 dB i00123 Narda 10 dB i00110 Kay Variable	989 989 7802 7802A 145-387
(3) COMBINER i00154 4 x 25 Ω COMBINER	154
(4) CRYSTAL DETECTOR i00159 HP 8470B	1822A10054
(5) RF SIGNAL GENERATOR i00018 HP 8656A i00031 HP 8656A i00067 HP 8920A	2228A03472 2402A06180 3345U01242
(6) MODULATION ANALYZER i00020 HP 8901A	2105A01087
(7) SCOPE i00030 HP 54502A	2927A00209

Transient Frequency Behavior

PAGE NO.

30 of 46.

NAME OF TEST: Transient Frequency Behavior  
 g02c0164: 2002-Dec-19 Thu 08:44:00  
 STATE: 2:High Power



```

Main      Timebase      Delay/Pos      Reference
        10.0 ms/div    40.0000 ms    Center
Channel 1  Sensitivity  Offset        Probe
          550 mV/div   0.00000 V    1.000 :1  dc
Trigger mode :
On Negative Edge Of
Trigger
Chan2 = -1.000 mV (noise reject
Holdoff = 40.000

```

POWER: HIGH  
 MODULATION: Ref Gen=25 kHz Deviation  
 DESCRIPTION: CARRIER ON TIME

PERFORMED BY:




Doug Noble, B.A.S. E.E.T.

PAGE NO.

31 of 46.

NAME OF TEST: Transient Frequency Behavior  
 g02c0165: 2002-Dec-19 Thu 08:45:00  
 STATE: 2:High Power



Main Timebase 10.0 ms/div Delay/Pos -30.0000 ms Reference Center  
 Channel 1 Sensitivity 550 mV/div Offset 0.00000 V Probe 1.000 :1 dc  
 Trigger mode : On Positive Edge Of Trigger Chan2 = -175.000 mV (noise reject) Holdoff = 40.000

POWER: HIGH  
 MODULATION: Ref Gen=25 kHz Deviation  
 DESCRIPTION: CARRIER OFF TIME


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

32 of 46.

NAME OF TEST: Transient Frequency Behavior  
 g02c0166: 2002-Dec-19 Thu 08:48:00  
 STATE: 2:High Power



Main Timebase 10.0 ms/div Delay/Pos 40.0000 ms Reference Center

Channel 1 Sensitivity 275 mV/div Offset 0.00000 V Probe 1.000 :1 dc

Trigger mode :  
 On Negative Edge Of  
 Trigger  
 Chan2 = -1.500 mV (noise reject)  
 Holdoff = 40.000

POWER:  
 MODULATION:  
 DESCRIPTION:

HIGH  
 Ref Gen=12.5 kHz Deviation  
 CARRIER ON TIME


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

33 of 46.

NAME OF TEST: Transient Frequency Behavior  
 g02c0167: 2002-Dec-19 Thu 08:49:00  
 STATE: 2:High Power



Main Timebase 10.0 ms/div Delay/Pos -30.0000 ms Reference Center

Channel 1 Sensitivity 275 mV/div Offset 0.00000 V Probe 1.000 :1 dc

Trigger mode :  
 On Positive Edge Of  
 Trigger  
 Chan2 = -175.000 mV (noise reject)  
 Holdoff = 40.000

POWER:  
 MODULATION:  
 DESCRIPTION:

HIGH  
 Ref Gen=12.5 kHz Deviation  
 CARRIER OFF TIME

PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO. 34 of 46.

NAME OF TEST: Audio Low Pass Filter (Voice Input)

SPECIFICATION: 47 CFR 2.1047(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.15

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE


1. The EUT and test equipment were set up such that the audio input was connected at the input to the modulation limiter, and the modulated stage.
2. The audio output was connected at the output to the modulated stage.
3. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

35 of 46.

TRANSMITTER TEST SET-UP

TEST A. MODULATION CAPABILITY/DISTORTION  
 TEST B. AUDIO FREQUENCY RESPONSE  
 TEST C. HUM AND NOISE LEVEL  
 TEST D. RESPONSE OF LOW PASS FILTER  
 TEST E. MODULATION LIMITING




Asset (as applicable)	Description	s/n
(1) <u>Audio Oscillator</u>		
i00010	HP 204D	1105A04683
i00017	HP 8903A	2216A01753
i00118	HP 33120A	US36002064
(2) <u>COAXIAL ATTENUATOR</u>		
i00122	NARDA 766-10	7802
i00123	NARDA 766-10	7802A
i00113	SIERRA 661A-3D	1059
i00069	BIRD 8329 (30 dB)	10066
(3) <u>MODULATION ANALYZER</u>		
i00020	HP 8901A	2105A01087
(4) <u>AUDIO ANALYZER</u>		
i00017	HP 8903A	2216A01753


PAGE NO.

36 of 46.

NAME OF TEST: Audio Low Pass Filter (Voice Input)  
g02c0026: 2002-Dec-11 Wed 15:50:00  
STATE: 0:General



PERFORMED BY:



Doug Noble, B.A.S. E.E.T.

PAGE NO. 37 of 46.

NAME OF TEST: Audio Frequency Response

SPECIFICATION: 47 CFR 2.1047(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.6

TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. The audio signal generator was connected to the audio input circuit/microphone of the EUT.
3. The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.
4. With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.
5. The response in dB relative to 1 kHz was then measured, using the HP 8901A Modulation Analyzer.
6. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

38 of 46.

NAME OF TEST: Audio Frequency Response  
 g02c0025: 2002-Dec-11 Wed 15:47:00  
 STATE: 0:General



Frequency of Maximum Audio Response, Hz = 2510

Additional points:

FREQUENCY, Hz	LEVEL, dB
300	-12.53
20000	-29.32
30000	-30.35
50000	-29.39

PERFORMED BY:

  
 Doug Noble, B.A.S. E.E.T.

PAGE NO. 39 of 46.

NAME OF TEST: Modulation Limiting

SPECIFICATION: 47 CFR 2.1047(b)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.3

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The signal generator was connected to the input of the EUT as for "Frequency Response of the Modulating Circuit."
2. The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.
3. The input level was varied from 30% modulation ( $\pm 1.5$  kHz deviation) to at least 20 dB higher than the saturation point.
4. Measurements were performed for both negative and positive modulation and the respective results were recorded.


5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.


40 of 46.

NAME OF TEST: Modulation Limiting  
 g02c0027: 2002-Dec-11 Wed 15:55:00  
 STATE: 0:General

Positive  
Peaks:



Negative  
Peaks:



PERFORMED BY:


  
 Doug Noble, B.A.S. E.E.T.

PAGE NO.


41 of 46.

NAME OF TEST: Modulation Limiting  
 g02c0028: 2002-Dec-11 Wed 16:12:00  
 STATE: 0:General

Positive  
Peaks:



Negative  
Peaks:



PERFORMED BY:

  
 Doug Noble, B.A.S. E.E.T.

PAGE NO. 42 of 46.

NAME OF TEST: Frequency Stability (Temperature Variation)

SPECIFICATION: 47 CFR 2.1055(a)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST CONDITIONS: As Indicated

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE


1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

43 of 46.

TRANSMITTER TEST SET-UP

TEST A. OPERATIONAL STABILITY  
 TEST B. CARRIER FREQUENCY STABILITY  
 TEST C. OPERATIONAL PERFORMANCE STABILITY  
 TEST D. HUMIDITY  
 TEST E. VIBRATION  
 TEST F. ENVIRONMENTAL TEMPERATURE  
 TEST G. FREQUENCY STABILITY: TEMPERATURE VARIATION  
 TEST H. FREQUENCY STABILITY: VOLTAGE VARIATION




Transmitter Test Set Up

Asset Description (as applicable)		s/n
(1) TEMPERATURE, HUMIDITY, VIBRATION		
i00027 Tenney Temp. Chamber		9083-765-234
i00 Weber Humidity Chamber		
i00 L.A.B. RVH 18-100		
(2) COAXIAL ATTENUATOR		
i00122 NARDA 766-10		7802
i00123 NARDA 766-10		7802A
i00113 SIERRA 661A-3D		1059
i00069 BIRD 8329 (30 dB)		10066
(3) R.F. POWER		
i00014 HP 435A POWER METER		1733A05839
i00039 HP 436A POWER METER		2709A26776
i00020 HP 8901A POWER MODE		2105A01087
(4) FREQUENCY COUNTER		
i00042 HP 5383A		1628A00959
i00019 HP 5334B		2704A00347
i00020 HP 8901A		2105A01087

PAGE NO.

44 of 46.

NAME OF TEST: Frequency Stability (Temperature Variation)  
g02c0045: 2002-Dec-16 Mon 14:04:57  
STATE: 0:General



PERFORMED BY:



Doug Noble, B.A.S. E.E.T.

PAGE NO. 45 of 46.

NAME OF TEST: Frequency Stability (Voltage Variation)

SPECIFICATION: 47 CFR 2.1055(d)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT was placed in a temperature chamber at  $25\pm5^{\circ}\text{C}$  and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

RESULTS: Frequency Stability (Voltage Variation)

g02c0154: 2002-Dec-11 Wed 16:46:36

STATE: 0:General

LIMIT, ppm	= 2.5
LIMIT, Hz	= 1240
BATTERY END POINT (Voltage)	= 10.8

% of STV	Voltage	Frequency, MHz	Change, Hz	Change, ppm
85	11.56	496.099990	-10	-0.02
100	13.6	496.100000	0	0.00
115	15.64	496.100020	20	0.04
79	10.8	496.100030	30	0.06

PERFORMED BY:

  
Doug Noble, B.A.S. E.E.T.

PAGE NO. 46 of 46.

NAME OF TEST: Necessary Bandwidth and Emission Bandwidth

SPECIFICATION: 47 CFR 2.202(g)

MODULATION = 16K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 3
MAXIMUM DEVIATION (D), kHz	= 5
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B <sub>N</sub> ), kHz	= (2xM)+(2xDxK)
	= 16.0

MODULATION = 11K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 3
MAXIMUM DEVIATION (D), kHz	= 2.5
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B <sub>N</sub> ), kHz	= (2xM)+(2xDxK)
	= 11.0

PERFORMED BY:



Doug Noble, B.A.S. E.E.T.

END OF TEST REPORT

TESTIMONIAL  
AND  
STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY THAT:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER:



Morton Flom, P. Eng.