

FCC ID: KR55WK49250

Date of issue: 2006-10-31



Test Report
acc. to the relevant standard
47 CFR Part 15 C – Intentional Radiators
Measurement Procedure:
ANSI C63.4 - 1992
relating to
Siemens AG
Siemens VDO Automotive
5WK4 9250

Measurement of Radio- Noise Emissions
from Low- Voltage Electrical and Electronic Equipment
Technical characteristics and test methods for radio equipment
in the frequency range 9 kHz to 40 GHz

FCC ID: KR55WK49250

Date of issue: 2006-10-31

Manufacturer's details	
Manufacturer	Siemens AG, Siemens VDO Automotive
Manufacturer's grantee code	KR5
Manufacturer's address	Siemens AG, Siemens VDO Automotive
	Siemensstrasse 12
	D-93005 Regensburg
	Germany
	Phone: +49 0941 790 6699
	Fax: +49 0941 790 136699
Relevant standard used	47 CFR Part 15C - Intentional Radiators
	ANSI C63.4-1992

Test report prepared by	
Technical engineer	Ralf Trepper
	m.dudde hochfrequenz-technik (laboratory)
	Rottland 5a
	51429 Bergisch Gladbach
	Germany
	Phone: +49 2207 96890
	Fax: +49 2207 968920
	E-mail: m.duddelabor@dudde.com

Equipment Under Test (EUT)	
Equipment category	Transmitter
Trade name	Siemens VDO
Type designation	5WK4 9250
Serial no.	none
Variants	none

FCC ID: KR55WK49250

Date of issue: 2006-10-31

0 Test result

CFR Section	Report Chapter	Requirements Headline	Test result OK		
15.203	10.1	Antenna requirement	pass	fail	na
15.231(b)	10.2	Field strength limits (fundamental)	pass	fail	na
15.205(b) 15.209	10.2	Radiated spurious emissions	pass	fail	na
15.231(a)	10.3	Periodic operation characteristics	pass	fail	na
15.231 (c)	10.4	20 dB bandwidth	pass	fail	na

Test requirements kept	yes	no
------------------------	-----	---------------

Signature
(Technical engineer)



.....
Ralf Trepper

Signature
(Manager)



.....
Manfred Dudde

FCC ID: KR55WK49250

Date of issue: 2006-10-31

List of contents	Page
0 Test result	3
1 Test laboratory	5
2 Introduction	5
3 Product	6
4 Test schedule	6
5 Product and measurement documentation.....	7
6 Observations and comments.....	7
7 Summary	7
8 Conclusions	8
9 Operation description.....	9
10.1 Antenna requirement	10
10.1.1 Regulation	10
10.1.2 Result	10
10.2 Radiated emissions	11
10.2.1 Regulation	11
10.2.2 Test equipment	12
10.2.2.1 Test procedures.....	12
10.2.3 Calculation of field strength limits.....	13
10.2.4 Calculation of average correction factor.....	13
10.2.5 Calculation of the field strengths	13
10.2.6 Results.....	14
10.3 Periodic operation characteristics	17
10.3.1 Periodic operation.....	17
10.3.1.1 Regulation	17
10.3.1.2 Result	17
10.3.2 Manually operated transmitter deactivation	17
10.3.2.1 Regulation	17
10.3.2.2 Result	17
10.3.3 Automatically operated transmitter deactivation	17
10.3.3.1 Regulation	17
10.3.3.2 Result	17
10.3.4 Prohibition of periodic transmission	18
10.3.4.1 Regulation	18
10.3.4.2 Result	18
10.3.5 Continuous transmission during an alarm condition.....	18
10.3.5.1 Regulation	18
10.3.5.2 Result	18
10.4 Bandwidth	19
10.4.1 Regulation	19
10.4.2 Calculation of the 20 dB bandwidth limit	19
10.4.3 Test equipment	19
10.4.4 Test procedure	19
10.4.5 Test result	20
11 Additional information to this test report	21

FCC ID: KR55WK49250

Date of issue: 2006-10-31

1 Test laboratory

Company name : m.dudde hochfrequenz-technik
Street : Rottland 5a
City : 51429 Bergisch Gladbach
Country : Germany
Laboratory : FCC Registration Number: 699717
This site has been fully described in a report submitted to the FCC, and renewed with letter dated July 12, 2005, Registration Number 699717.
Phone : +49-2207-9689-0
Fax : +49-2207-9689-20
E-Mail : manfred.dudde@t-online.de
Web : <http://www.dudde.com>

2 Introduction

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of m. dudde hochfrequenz - technik.

This report contains the result of tests performed by m. dudde hochfrequenz - technik for the purpose of a type approval. The order for carrying out these tests has been placed by:

Manufacturer

Company name : Siemens AG
Siemens VDO Automotive
Address : Siemensstrasse 12
Postcode : D-93055
City/town : Regensburg
Country : Germany
Telephone : +49 941 790 6699
Telefax : +49 941 790 136699
E-mail : dagmar.kolar@siemens.com
Date of order : 2006-10-09
References : Mrs. Kolar

FCC ID: KR55WK49250

Date of issue: 2006-10-31

3 Product

Samples of the following apparatus were submitted for testing:

Type of equipment	: Transmitter
Trademark	: Siemens VDO
Type designation	: 5WK4 9250
Hardware version	: 5WK4 9250
Serial number	: ---
Software release	: ---
Power used	: 3.00 VDC
Frequency used	: 433.670 MHz, 434.251 MHz
Generated or used frequencies	: 16.0 MHz / 433.670 MHz, 434.251 MHz
ITU emission class	: 25K F1D
FCC ID	: KR55WK49250

4 Test schedule

The tests were carried out in accordance with the specifications detailed in chapter 7 “Summary“ of this report at:

- **m. dudde hochfrequenz - technik, D-51429 Bergisch Gladbach**

The test sample was received on:

- **2006-09-06**

The tests were carried out in the following period of time:

- **2006-10-13 - 2006-10-16**

FCC ID: KR55WK49250

Date of issue: 2006-10-31

5 Product and measurement documentation

For issuing this report the following product documentation was used and the following annexes were created:

Description	Date	Identifications
External photographs of the Equipment Under Test	2006-10-30	Annex No. 1
Internal photographs of the Equipment Under Test	2006-10-30	Annex No. 2
Occupied bandwidth plot	2006-10-30	Annex No. 3
FCC ID label sample	2006-10-30	Annex No. 4
User Manual	2006-10-30	Annex No. 5
Test setup photos	2006-10-30	Annex No. 6
Block diagram	2006-10-30	Annex No. 7
Schematics	2006-10-30	Annex No. 8
Technical description	2006-10-30	Annex No. 9
Periodic operation characteristic	2006-10-30	Annex No. 10

The above mentioned documentation will be filed at m. dudde hochfrequenz - technik for a period of 10 years following the issue of this report.

6 Observations and comments

7 Summary

The product is intended for the use in the following areas of application:

**Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment
in the frequency range of 9 kHz to 40 GHz**

The samples were tested according to the following specification:

47 CFR Part 15 – Intentional Radiators, ANSI C63.4 - 1992

FCC ID: KR55WK49250

Date of issue: 2006-10-31

8 Conclusions

Samples of the apparatus were found to **CONFORM WITH** the specifications stated in chapter 7 "Summary" of this report.

In the opinion of m. dudde hochfrequenz - technik, the samples satisfied all applicable requirements relating to the network interface types specified in chapter 7 "Summary".

The results of the type tests as stated in this report are exclusively applicable to the product item as identified in this report. m. dudde hochfrequenz - technik does not accept any responsibility for the results stated in this report, with respect to the properties of product items not involved in these tests.

This report consists of a main module, modules with test results and annexes listed in chapter 5: "Product documentation". All pages have been numbered consecutively and bear the m. dudde hochfrequenz - technik logo, the report number and sub numbers.
The total number of pages in this report is **22**.

Tester:

Date : 2006-10-31

Name : Ralf Trepper

Signature : 

Technical responsibility for area of testing:

Date : 2006-10-31

Name : Manfred Dudde

Signature : 

FCC ID: KR55WK49250

Date of issue: 2006-10-31

9 Operation description

9.1 EUT details

See Annex no. 5 (User Manual)

9.2 EUT configuration

The **Transmitter 5WK4 9250** operated in the continuous transmitting mode after pressing a bottom.

To press the close or open bottom: the transmitter operated in CW mode

To press the tailgate bottom: the transmitter operated in modulation mode

9.3 EUT measurement description

The **Transmitter 5WK4 9250** was tested in a typical fashion. During preliminary emission tests the **Transmitter 5WK4 9250** was operated in the continuous transmitting mode for worst case emission mode investigation. Therefore, the final qualification testing was completed with **Transmitter 5WK4 9250** operated in continuous modes. All tests were performed with the applicant's typical voltage: 3.0 V DC

In order to establish the maximum radiation, firstly, there have been viewed all orthogonal adjustments of the test samples, secondly the test sample have been rotated at all adjustments around the own axis between 0° and 360°, and thirdly, the antenna polarization between horizontal and vertical had been varied.

FCC ID: KR55WK49250

Date of issue: 2006-10-31

10.1 Antenna requirement

10.1.1 Regulation

15.203 An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of Part 15C. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31 (d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

10.1.2 Result

The equipment meets the requirements	yes	no	n.a.
Further test results are attached	yes	no	page no:

n.a ^x See page no. 21

FCC ID: KR55WK49250

Date of issue: 2006-10-31

10.2 Radiated emissions

10.2.1 Regulation

Test requirement: FCC CFR47, Part 15C, Test procedure: ANSI C63.4:1992

Fundamental frequency (MHz)	Field strength of fundamental (µV/m)	Field strength of spurious emissions (µV/m)
40.66 - 40.70	2,250	225
70-130	1,250	125
130-174	1,250 to 3,750	125 to 375
174-260	3,750	375
260-470	3,750 to 12,500	375 to 1,250
Above 470	12,500	1,250

** Linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, µV/m at 3 meters = $56.81818(F) - 6136.3636$; for the band 260-470 MHz, µV/m at 3 meters = $41.6667(F) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

(1) The above field strength limits are specified at a distance of 3 meters. The tighter limits apply at the band edges.

(2) Intentional radiators operating under the provisions of this Section shall demonstrate compliance with the limits on the field strength of emissions, as shown in the above table, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector. The specific method of measurement employed shall be specified in the application for equipment authorization. If average emission measurements are employed, the provisions in Section 15.35 for averaging pulsed emissions and for limiting peak emissions apply. Further, compliance with the provisions of Section 15.205 shall be demonstrated using the measurement instrumentation specified in that section.

(3) The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in Section 15.209, whichever limit permits higher field strength.

Section 15.33 Frequency range of radiated measurements: (a) Unless otherwise noted in the specific rule section under which the equipment operates for an intentional radiator the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in this paragraph: (1). If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

FCC ID: KR55WK49250

Date of issue: 2006-10-31

10.2.2 Test equipment

Type	Manufacturer/ Model No.	Serial no.	Last calibration	Next calibration
Receiver (9 kHz –26.5 GHz)	Hewlett Packard Spectrum Analyzer 8593E (171)	3528U00990	2006/05	2008/05
Pre-amplifier (100kHz - 1.3GHz)	Hewlett Packard 8447 E (166a)	1726A00705	2006/03	2008/03
Bilog antenna (30- 1000 MHz)	CHASE CBL611A (167)	1517	2003/09	2009/09
Horn antenna (0,86-8,5 GHz)	Schwarzbeck BBHA 9120 A (284)	236	1998/01	2008/01

10.2.2.1 Test procedures

The EUT and this peripheral (when additional equipment exists) are placed on a turn table which is 0.8m above the ground. The turn table would be allowed to rotate 360 degrees to determine the position of the maximum emission level. The test distance between the EUT and the receiving antenna are 3m. To find the maximum emission, the polarization of the receiving antenna are changed in horizontal and vertical polarization, the position of the EUT was changed in different orthogonal determinations.

ANSI C63.4: 1992 Section 8 “Radiated Emissions Testing”

Radiated emissions test characteristics	
Frequency range	30 MHz - 4,000 MHz
Test distance	3 m*
Test instrumentation resolution bandwidth	120 kHz (30 MHz - 1,000 MHz)
	1 MHz (1000 MHz - 4,000 MHz)
Receive antenna scan height	1 m - 4 m
Receive antenna polarization	Vertical/horizontal

*According to Section 15.31 (f) (1): At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

FCC ID: KR55WK49250

Date of issue: 2006-10-31

10.2.3 Calculation of field strength limits

For example: Transmitter working on 315 MHz

Limit for average measurements $\rightarrow 41.6667 \cdot (315 \text{ MHz}) - 7083.3333 = 6041.677 \mu\text{V/m} = 75.6 \text{ dB}\mu\text{V/m} @ 3\text{m}$

Limit for peak measurements $\rightarrow$ Limit for average measurements + 20dB = 95.6dB $\mu\text{V/m} @ 3\text{m}$

10.2.4 Calculation of average correction factor

The average correction factor is computed by analyzing the "worst case" on time in any 100msec time period and using the formula: Corrections Factor + $20 \cdot \log$ (worst case on time/100msec). Analysis of the remote transmitter worst case on time in any 100msec time period is an on time of 50msec, therefore the correction factor is $20 \cdot \log (50/100) = -6 \text{ dB}$. The maximum correction factor to be applied is 20 dB per section 15.35 of the FCC rules.

10.2.5 Calculation of the field strengths

The field strength is calculated by the following calculation:

Corrected Level = Receiver Level + Correction Factor (without the use of a pre-amplifier)

Corrected Level = Receiver Level + Correction Factor – Pre-Amplifier (with the use of a pre-amplifier)

Receiver Level : Receiver reading without correction factors

Correction Factor : Antenna factor + cable loss

For example:

The receiver reading is 32.7 dB μV . The antenna factor for the measured frequency is +2.5 dB (1/m) and the cable factor for the measured frequency is 0.71 dB, giving a field strength of 35.91dB $\mu\text{V/m}$.

The 35.91dB $\mu\text{V/m}$ value can be mathematically converted to its corresponding level in $\mu\text{V/m}$.

Level in $\mu\text{V/m}$ = Common Antilogarithm $(35.91/20) = 39.8$

For test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f) (1) the field strength is calculated by adding additionally an extrapolation factor of 20 dB/decade (inverse linear distance for field strength measurements).

FCC ID: KR55WK49250

Date of issue: 2006-10-31

10.2.6 Results

Channel 1

TRANSMITTER SPURIOUS RADIATION (Section 15.231(b))										
f (MHz)	Bandwidth (kHz) / Type of detector	Noted receiver level dBμV	Test distance m	Correction factor dB	Distance extrapol. factor dB	Level corrected dBμV/m	Limit dBμV/m	Margin dBμV/m	Polarisation EUT / antenna	Antenna height cm
433.670	120, QPK	80.3	3	-2.2* ⁵	0	78.1	80.8	2.7	V / V	115
867.320	120, QPK	50.8	3	+6.0* ⁵	0	56.8	60.8	4.0	V / V	108
1301.010	100, AV	52.9	3	+1.6* ⁶	0	54.5	60.8	6.3	V / V	113
1734.680	100, AV	44.5	3	+2.5* ⁶	0	47.0	60.8	13.8	V / V	144
2168.350	100, AV	≤ 10	3	+4.8* ⁶	0	14.8	60.8	46.0	V / V	100 - 400
2602.020	100, AV	≤ 10	3	+8.7* ⁶	0	18.7	60.8	42.1	V / V	100 - 400
3035.690	100, AV	≤ 10	3	+9.6* ⁶	0	19.6	60.8	41.2	V / V	100 - 400
3469.360	100, AV	≤ 10	3	+11.0* ⁶	0	21.0	60.8	39.8	V / V	100 - 400
3903.030	100, AV	≤ 10	3	+9.9* ⁶	0	19.9	60.8	40.9	V / V	100 - 400
4336.700	100, AV	≤ 10	3	+10.0* ⁶	0	20.0	60.8	40.8	V / V	100 - 400
4770.370	100, AV	≤ 10	3	+9.9* ⁶	0	19.9	60.8	40.9	V / V	100 - 400
			3							
Measurement uncertainty			4 dB							

Bandwidth = the measuring receiver bandwidth

- Remark: *¹ noise floor noise level of the measuring instrument ≤ 3.5dBμV @ 3m distance (30 – 1,000 MHz)
 Remark: *² noise floor noise level of the measuring instrument ≤ 4.5dBμV @ 3m distance (1,000 – 2,000 MHz)
 Remark: *³ noise floor noise level of the measuring instrument ≤ 10dBμV @ 3m distance (2,000 – 5,500 MHz)
 Remark: *⁴ noise floor noise level of the measuring instrument ≤ 14dBμV @ 3m distance (5,500 – 14,500 MHz)
 Remark: *⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHz
 Remark: *⁶ for using a pre-amplifier in the range between 1.0 GHz and 18.0 GHz

The equipment meets the requirements	yes	no	n.a.
--------------------------------------	-----	----	------

Further test results are attached	yes	no	
-----------------------------------	-----	----	--

n.a.^x See page no. 21

FCC ID: KR55WK49250

Date of issue: 2006-10-31

Channel 2

TRANSMITTER SPURIOUS RADIATION (Section 15.231(b))										
f (MHz)	Bandwidth (kHz) / Type of detector	Noted receiver level dBμV	Test distance m	Correction factor dB	Distance extrapol. factor dB	Level corrected dBμV/m	Limit dBμV/m	Margin dBμV/m	Polarisation EUT / antenna	Antenna height cm
434.251	120, QPK	80.1	3	-2.2* ⁵	0	77.9	80.8	2.9	V / V	
868.502	120, QPK	50.8	3	+6.0* ⁵	0	56.8	60.8	4.0	V / V	
1302.753	100, AV	52.7	3	+1.6* ⁶	0	54.3	60.8	6.5	V / V	
1737.004	100, AV	45.2	3	+2.5* ⁶	0	47.7	60.8	13.1	V / V	
2171.255	100, AV	≤ 10	3	+4.8* ⁶	0	14.8	60.8	46.0	H,V / H,V	100 - 400
2605.506	100, AV	≤ 10	3	+8.7* ⁶	0	18.7	60.8	42.1	H,V / H,V	100 - 400
3039.757	100, AV	≤ 10	3	+9.6* ⁶	0	19.6	60.8	41.2	H,V / H,V	100 - 400
3474.008	100, AV	≤ 10	3	+11.0* ⁶	0	21.0	60.8	39.8	H,V / H,V	100 - 400
3908.259	100, AV	≤ 10	3	+9.9* ⁶	0	19.9	60.8	40.9	H,V / H,V	100 - 400
4342.510	100, AV	≤ 10	3	+10.0* ⁶	0	20.0	60.8	40.8	H,V / H,V	100 - 400
4776.761	100, AV	≤ 10	3	+9.9* ⁶	0	19.9	60.8	40.9	H,V / H,V	100 - 400
			3							
Measurement uncertainty			4 dB							

Bandwidth = the measuring receiver bandwidth

Remark: *¹ noise floor noise level of the measuring instrument ≤ 3.5dBμV @ 3m distance (30 – 1,000 MHz)
 Remark: *² noise floor noise level of the measuring instrument ≤ 4.5dBμV @ 3m distance (1,000 – 2,000 MHz)
 Remark: *³ noise floor noise level of the measuring instrument ≤ 10dBμV @ 3m distance (2,000 – 5,500 MHz)
 Remark: *⁴ noise floor noise level of the measuring instrument ≤ 14dBμV @ 3m distance (5,500 – 14,500 MHz)
 Remark: *⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHz
 Remark: *⁶ for using a pre-amplifier in the range between 1.0 GHz and 18.0 GHz

The equipment meets the requirements	yes	no	na
--------------------------------------	-----	----	----

Further test results are attached	yes	no	
-----------------------------------	-----	----	--

n.a ^x See page no. 21

FCC ID: KR55WK49250

Date of issue: 2006-10-31

TRANSMITTER SPURIOUS RADIATION ABOVE 30 MHz (Section 15.205, 15.209)

f (MHz)	Bandwidth (kHz) Type of detector	Noted receiver level dBμV	Test distance m	Correction factor dB	Distance extrapol. factor dB	AV Correction factor dB	Level corrected dBμV/m	Limit dBμV/m	Margin dBμV/m	Polaris. EUT / antenna	Antenna height cm
30.0000	100, AV	≤ 3.5	3	-2.60* ⁵	0	0	0.90	40.00	39.10	H,V/H,V	100-400
88.0000	100, AV	≤ 3.5	3	-10.80* ⁵	0	0	-7.30	40.00	47.30	H,V/H,V	100-400
216.0000	100, AV	≤ 3.5	3	-10.30* ⁵	0	0	-6.80	43.50	50.30	H,V/H,V	100-400
960.0000	100, AV	≤ 3.5	3	8.50* ⁵	0	0	12.00	43.50	31.50	H,V/H,V	100-400
1700.0000	1000, AV	≤ 4.5	3	3.80* ⁶	0	0	8.30	54.00	45.70	H,V/H,V	100-400
2250.0000	1000, AV	≤ 10	3	8.00* ⁶	0	0	18.00	54.00	36.00	H,V/H,V	100-400
4000.0000	1000, AV	≤ 10	3	8.40* ⁶	0	0	18.40	54.00	35.60	H,V/H,V	100-400
5000.0000	1000, AV	≤ 10	3	9.10* ⁶	0	0	19.40	54.00	34.60	H,V/H,V	100-400
7500.0000	1000, AV	≤ 14	3	12.9* ⁶	0	0	26.90	54.00	27.10	H,V/H,V	100-400
8300.0000	1000, AV	≤ 14	3	14.80* ⁶	0	0	28.80	54.00	25.20	H,V/H,V	100-400
9400.0000	1000, AV	≤ 14	3	16.00* ⁶	0	0	30.00	54.00	24.00	H,V/H,V	100-400
11000.0000	1000, AV	≤ 14	3	18.25* ⁶	0	0	32.25	54.00	21.75	H,V/H,V	100-400
Measurement uncertainty			4 dB								

Bandwidth = the measuring receiver bandwidth

- Remark: *¹ noise floor noise level of the measuring instrument ≤ 3.5dBμV @ 3m distance (30 – 1,000 MHz)
 Remark: *² noise floor noise level of the measuring instrument ≤ 4.5dBμV @ 3m distance (1,000 – 2,000 MHz)
 Remark: *³ noise floor noise level of the measuring instrument ≤ 10dBμV @ 3m distance (2,000 – 5,500 MHz)
 Remark: *⁴ noise floor noise level of the measuring instrument ≤ 14dBμV @ 3m distance (5,500 – 14,500 MHz)
 Remark: *⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHz
 Remark: *⁶ for using a pre-amplifier in the range between 1.0 GHz and 18.0 GHz

The equipment meets the requirements	yes	no	n.a.
--------------------------------------	-----	----	------

Further test results are attached	yes	no	page no:
-----------------------------------	-----	----	----------

n.a ^x See page no. 21

FCC ID: KR55WK49250

Date of issue: 2006-10-31

10.3 Periodic operation characteristics

10.3.1 Periodic operation

10.3.1.1 Regulation

15.231 (a) The provisions of this Section are restricted to periodic operation within the band 40.66 40.70 MHz and above 70 MHz. Except as shown in paragraph (e) of this Section, the intentional radiator is restricted to the transmission of a control signal such as those used with alarm systems, door openers, remote switches, etc. Radio control of toys is not permitted. Continuous transmissions, such as voice or video, and data transmissions are not permitted. The prohibition against data transmissions does not preclude the use of recognition codes. Those codes are used to identify the sensor that is activated or to identify the particular component as being part of the system.

10.3.1.2 Result

The equipment meets the requirements	yes	no	n.a.
Further test results are attached	yes	no	Annex no: 10

10.3.2 Manually operated transmitter deactivation

10.3.2.1 Regulation

15.231 (a1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released

10.3.2.2 Result

The equipment meets the requirements	yes	no	n.a.
Further test results are attached	yes	no	Annex no: 10

10.3.3 Automatically operated transmitter deactivation

10.3.3.1 Regulation

15.231 (a2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.

10.3.3.2 Result

The equipment meets the requirements	yes	no	n.a.
Further test results are attached	yes	no	page no:

FCC ID: KR55WK49250

Date of issue: 2006-10-31

10.3.4 Prohibition of periodic transmission

10.3.4.1 Regulation

15.231 (a3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions to determine system integrity of transmitters used in security or safety applications are allowed if the periodic rate of transmission does not exceed one transmission of not more than one second duration per hour for each transmitter.

10.3.4.2 Result

The equipment meets the requirements	yes	no	n.a.
Further test results are attached	yes	no	page no:

10.3.5 Continuous transmission during an alarm condition

10.3.5.1 Regulation

15.231 (a4) Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.

10.3.5.2 Result

The equipment meets the requirements	yes	no	n.a.
Further test results are attached	yes	no	page no:

FCC ID: KR55WK49250

Date of issue: 2006-10-31

10.4 Bandwidth

10.4.1 Regulation

15.231 (c) The bandwidth of the emission shall be no wider than 0.25% of the centre frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the centre frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

10.4.2 Calculation of the 20 dB bandwidth limit

The 20 dB bandwidth limit = $0.0025 * 315 \text{ MHz} = 0.7875 \text{ MHz} = 787.5 \text{ kHz}$

10.4.3 Test equipment

Type	Manufacturer/ Model no.	Serial no.	Last calibration	Next calibration
Receiver (30MHz - 1GHz)	Hewlett Packard Spectrum Analyzer (171) 8593 E	3528U00990	05/2006	05/2008
Test fixture	Dudde			

10.4.4 Test procedure

ANSI C63.4-1992 Section 13.1.7 Occupied bandwidth measurements. The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at either the fundamental frequency or first-order modulation products in all typical modes of operation, including the unmodulated carrier, even if atypical. Once the reference level is established, the equipment is conditioned with typical modulating signals to produce worst-case (i.e., the widest) bandwidth. In order to measure the modulated signal properly, a resolution bandwidth that is small compared to the bandwidth required by the procuring or regulatory agency shall be used on the measuring instrument. However, the 6 dB resolution bandwidth of the measuring instrument shall be set to a value greater than 5% of the bandwidth requirements.

FCC ID: KR55WK49250

Date of issue: 2006-10-31

10.4.5 Test result

The measured 20 dB bandwidth is:25.0 kHz

The equipment meets the requirements	yes	no	na
Further test results are attached	yes	no	Annex no: 3

FCC ID: KR55WK49250

Date of issue: 2006-10-31

11 Additional information to this test report

Remarks

- | | |
|-------------------|---|
| n.a. ¹ | Not applicable, because the antenna is part of the PCB |
| n.a. ² | Not applicable, because the EUT is directly battery powered |

FCC ID: KR55WK49250

Date of issue: 2006-10-31

End of test report