

EUT: 5WK50128  
FCC ID: KR55WK50128

Date of issue: 2009-02-09



**Test Report**  
acc. to the relevant standard  
**47 CFR Part 15 C – Intentional Radiators**  
**Measurement Procedure:**  
**ANSI C63.4-2003**  
relating to  
**Continental Automotive GmbH**  
**5WK50128**

**Methods of Measurement of Radio-  
Noise Emissions from Low-Voltage  
Electrical and Electronic Equipment  
in the Range 9 kHz to 40 GHz**



**EUT: 5WK50128**  
**FCC ID: KR55WK50128**

**Date of issue: 2009-02-09**

<b>Manufacturer's details</b>	
Manufacturer	<b>Continental Automotive GmbH</b>
Manufacturer's grantee code	<b>KR5</b>
Manufacturer's address	<b>Continental Automotive GmbH</b> Siemensstrasse 12 D-93005 Regensburg Germany Phone: +49 0941 790 6699 Fax: +49 0941 790 136699 <a href="mailto:dagmar.kolar@continental-corporation.com">dagmar.kolar@continental-corporation.com</a>
Relevant standard used	47 CFR Part 15C - Intentional Radiators ANSI C63.4-2003

<b>Test report prepared by</b>	
Technical engineer	Ralf Trepper m.dudde hochfrequenz-technik (laboratory) Rottland 5a 51429 Bergisch Gladbach Germany Phone: +49 (0) 2207 96 89-0 Fax: +49 (0) 2207 96 89-20 E-mail: <a href="mailto:m.duddelabor@dudde.com">m.duddelabor@dudde.com</a>

<b>Equipment Under Test (EUT)</b>	
Equipment category	Inductive system (Vehicle immobilizing system)
Trade name	Continental
Type designation	5WK50128
Serial no.	---
Variants	---
	---
	---
	---
	---

EUT: 5WK50128  
 FCC ID: KR55WK50128

Date of issue: 2009-02-09

## 1. Test result summary

CFR Section	Report Chapter	Requirements Headline	Test result		
15.203	11.1	Antenna requirement	Pass	Fail	Not
15.205	11.2	Restricted bands of operation	Pass	Fail	Not
15.209	11.3	Radiated emission limits, general requirements	Pass	Fail	Not
15.209	11.4	Field strength of the fundamental	Pass	Fail	Not
15.209	11.5	Field strength of spurious emissions	Pass	Fail	Not

The equipment meets the requirements	Yes	No
--------------------------------------	-----	----

Signature  
 Technician .....  
  
 Ralf Trepper

Signature  
 Manager .....  
  
 Manfried Dudde

**EUT: 5WK50128**  
**FCC ID: KR55WK50128****Date of issue: 2009-02-09****Table of contents**

1. Test result summary .....	3
2. Test laboratory .....	5
3. Introduction.....	5
4. Product.....	6
5. Test schedule.....	6
6. Product and measurement documentation .....	7
7. Observations and comments .....	7
8. Summary.....	7
9. Conclusions.....	8
10. Operational description .....	9
11.1 Antenna requirement.....	10
11.1.1 Regulation.....	10
11.1.2 Result .....	10
11.2 Restricted bands of operation.....	11
11.2.1 Regulation.....	11
11.2.2 Result .....	13
11.3 Radiated emission limits, general requirements.....	14
11.3.1 Regulation.....	14
11.3.2 Test equipment.....	15
11.3.3 Test procedure.....	16
11.3.4 Calculation of the field strength.....	17
11.3.5 Test result.....	18
11.4 Field strength of fundamental .....	20
11.4.1 Regulation.....	20
11.4.2 Test results .....	20
11.5 Field strength of spurious emissions.....	21
11.5.1 Regulation.....	21
11.5.2 Test results .....	21
12. Additional information to the test report.....	22

**EUT: 5WK50128**  
**FCC ID: KR55WK50128****Date of issue: 2009-02-09**

## 2. Test laboratory

Company name : m.dudde hochfrequenz-technik  
Street : Rottland 5a  
City : 51429 Bergisch Gladbach  
Country : Germany  
Laboratory : FCC Registration Number: 699717  
This site has been fully described in a report submitted to the FCC, and renewed with letter dated July 12, 2005, Registration Number 699717.  
Phone : +49-2207-9689-0  
Fax : +49-2207-9689-20  
E-Mail : [manfred.dudde@t-online.de](mailto:manfred.dudde@t-online.de)  
Web : <http://www.dudde.com>

## 3. Introduction

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of m. dudde hochfrequenz - technik.

This report contains the result of tests performed by m. dudde hochfrequenz - technik for the purpose of a type approval. The order for carrying out these tests has been placed by:

### Manufacturer

Company name : Continental Automotive GmbH  
Address : Siemensstrasse 12  
Postcode : D-93055  
City/town : Regensburg  
Country : Germany  
Telephone : +49 941 790 6699  
Telefax : +49 941 790 136699  
E-mail : [dagmar.kolar@continental-corporation.com](mailto:dagmar.kolar@continental-corporation.com)  
Date of order : 2008-11-27  
References : Mrs. Kolar

**EUT: 5WK50128**  
**FCC ID: KR55WK50128****Date of issue: 2009-02-09**

## 4. Product

Samples of the following apparatus were submitted for testing:

Type of equipment	:	Transmitter (Inductive system)
Trademark	:	Continental
Type designation	:	5WK50128
Hardware version	:	5WK50128
Serial number	:	---
Software release	:	---
Power used	:	12.0 V DC (Car battery)
Frequency used	:	125 kHz
Generated or used frequencies	:	125 kHz / 8 MHz (Crystal oscillator)
<b>FCC ID</b>	:	<b>KR55WK50128</b>

## 5. Test schedule

The tests were carried out in accordance with the specifications detailed in chapter 8 "Summary" of this report at:

**- m. dudde hochfrequenz - technik, D-51429 Bergisch Gladbach**

The test sample was received on:

**- 2008-11-27**

The tests were carried out in the following period of time:

**- 2009-01-20 - 2009-02-06**

**EUT: 5WK50128**  
**FCC ID: KR55WK50128****Date of issue: 2009-02-09**

## 6. Product and measurement documentation

For issuing this report the following product documentation was used and the following annexes were created:

Description	Date	Identifications
External photographs of the Equipment Under Test		Annex no. 1
Internal photographs of the Equipment Under Test		Annex no. 2
Occupied bandwidth plot		Annex no. 3
FCC ID label sample		Annex no. 4
Functional description		Annex no. 5
Test setup photos		Annex no. 6
Block diagram		Annex no. 7
Schematics		Annex no. 8a
Parts list		Annex no. 8b
Operational description		Annex no. 9

The above mentioned documentation will be filed at m. dudde hochfrequenz - technik for a period of 10 years following the issue of this test report.

## 7. Observations and comments

## 8. Summary

The product is intended for the use in the following areas of application:

**Radio-Noise Emissions from Low- Voltage Electrical and Electronic Equipment  
in the frequency range of 9 kHz to 40 GHz**

The samples were tested according to the following specification:

**47 CFR Part 15 – Intentional Radiators, ANSI C63.4-2003**

EUT: 5WK50128  
FCC ID: KR55WK50128

Date of issue: 2009-02-09

## 9. Conclusions

Samples of the apparatus were found to **CONFORM WITH** the specifications stated in chapter 8 "Summary" of this report.

In the opinion of m. dudde hochfrequenz - technik, the samples satisfied all applicable requirements relating to the network interface types specified in chapter 8.

The results of the type tests as stated in this report are exclusively applicable to the product item as identified in this report. m. dudde hochfrequenz - technik does not accept any responsibility for the results stated in this report, with respect to the properties of product items not involved in these tests.

This report consists of a main module, modules with test results and annexes listed in chapter 6. All pages have been numbered consecutively and bear the m. dudde hochfrequenz - technik logo, the report number and sub-numbers.

The total number of pages in this report is **23**.

### Technical inspector:

Date : 2009-02-09


Name : Ralf Trepper

Signature : 

### Technical responsibility for area of testing:

Date : 2009-02-09

Name : Manfried Dudde

Signature : 

EUT: **5WK50128**  
FCC ID: **KR55WK50128**

Date of issue: 2009-02-09

## 10. Operational description

### 10.1 EUT details

Inductive System, Vehicle Immobilizer

### 10.2 EUT configuration

See Annex no. 5 (Functional description)

### 10.3 EUT measurement description

The inductive Transmitter **5WK50128** was tested in a typical fashion. During primary emission tests there had been examined all orthogonal adjustments of the EUT. In the final measurement there was chosen the adjustment in which there had been established before the highest level.

EUT: 5WK50128  
FCC ID: KR55WK50128

Date of issue: 2009-02-09

## 11.1 Antenna requirement

### 11.1.1 Regulation

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

### 11.1.2 Result

The equipment meets the requirements	Yes	No	N.t.
Further test results are attached	Yes	No	Annex No.5

n.a.\* See page no. 22

EUT: 5WK50128  
 FCC ID: KR55WK50128

Date of issue: 2009-02-09

## 11.2 Restricted bands of operation

### 11.2.1 Regulation

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
<b>0.090 - 0.110</b>	<b>16.42 - 16.423</b>	<b>399.9 - 410</b>	<b>4.5 - 5.15</b>
<sup>1</sup> <b>0.495 - 0.505</b>	<b>16.69475 - 16.69525</b>	<b>608 - 614</b>	<b>5.35 - 5.46</b>
<b>2.1735 - 2.1905</b>	<b>16.80425 - 16.80475</b>	<b>960 - 1240</b>	<b>7.25 - 7.75</b>
<b>4.125 - 4.128</b>	<b>25.5 - 25.67</b>	<b>1300 - 1427</b>	<b>8.025 - 8.5</b>
<b>4.17725 - 4.17775</b>	<b>37.5 - 38.25</b>	<b>1435 - 1626.5</b>	<b>9.0 - 9.2</b>
<b>4.20725 - 4.20775</b>	<b>73 - 74.6</b>	<b>1645.5 - 1646.5</b>	<b>9.3 - 9.5</b>
<b>6.215 - 6.218</b>	<b>74.8 - 75.2</b>	<b>1660 - 1710</b>	<b>10.6 - 12.7</b>
<b>6.26775 - 6.26825</b>	<b>108 - 121.94</b>	<b>1718.8 - 1722.2</b>	<b>13.25 - 13.4</b>
<b>6.31175 - 6.31225</b>	<b>123 - 138</b>	<b>2200 - 2300</b>	<b>14.47 - 14.5</b>
<b>8.291 - 8.294</b>	<b>149.9 - 150.05</b>	<b>2310 - 2390</b>	<b>15.35 - 16.2</b>
<b>8.362 - 8.366</b>	<b>156.52475 - 156.52525</b>	<b>2483.5 - 2500</b>	<b>17.7 - 21.4</b>
<b>8.37625 - 8.38675</b>	<b>156.7 - 156.9</b>	<b>2690 - 2900</b>	<b>22.01 - 23.12</b>
<b>8.41425 - 8.41475</b>	<b>162.0125 - 167.17</b>	<b>3260 - 3267</b>	<b>23.6 - 24.0</b>
<b>12.29 - 12.293</b>	<b>167.72 - 173.2</b>	<b>3332 - 3339</b>	<b>31.2 - 31.8</b>
<b>12.51975 - 12.52025</b>	<b>240 - 285</b>	<b>3345.8 - 3358</b>	<b>36.43 - 36.5</b>
<b>12.57675 - 12.57725</b>	<b>322 - 335.4</b>	<b>3600 - 4400</b>	<b>(<sup>2</sup>)</b>
<b>13.36 - 13.41</b>			

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

(c) Except as provided in paragraphs (d) and (e), regardless of the field strength limits specified elsewhere in this Subpart, the provisions of this Section apply to emissions from any intentional radiator.

**EUT: 5WK50128**  
**FCC ID: KR55WK50128****Date of issue: 2009-02-09**

(d) The following devices are exempt from the requirements of this Section:

- (1) Swept frequency field disturbance sensors operating between 1.705 and 37 MHz provided their emissions only sweep through the bands listed in paragraph (a), the sweep is never stopped with the fundamental emission within the bands listed in paragraph (a), and the fundamental emission is outside of the bands listed in paragraph (a) more than 99% of the time the device is actively transmitting, without compensation for duty cycle.
- (2) Transmitters used to detect buried electronic markers at 101.4 kHz which are employed by telephone companies.
- (3) Cable locating equipment operated pursuant to Section 15.213.
- (4) Any equipment operated under the provisions of § 15.253, § 15.255 or § 15.257 of this part.
- (5) Biomedical telemetry devices operating under the provisions of Section 15.242 of this part are not subject to the restricted band 608-614 MHz but are subject to compliance within the other restricted bands.
- (6) Transmitters operating under the provisions of Subpart D or F of this part.
- (7) Devices operated pursuant to § 15.225 are exempt from complying with this section for the 13.36-13.41 MHz band only.
- (8) Devices operated in the 24.075-24.175 GHz band under § 15.245 are exempt from complying with the requirements of this section for the 48.15-48.35 GHz and 72.225-72.525 GHz bands only, and shall not exceed the limits specified in § 15.245(b).
- (9) Devices operated in the 24.0-24.25 GHz band under § 15.249 are exempt from complying with the requirements of this section for the 48.0-48.5 GHz and 72.0-72.75 GHz bands only, and shall not exceed the limits specified in § 15.249(a).

(e) Harmonic emissions appearing in the restricted bands above 17.7 GHz from field disturbance sensors operating under the provisions of Section 15.245 shall not exceed the limits specified in Section 15.245(b).

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

(c) Except as provided in paragraphs (d) and (e), regardless of the field strength limits specified elsewhere in this Subpart, the provisions of this Section apply to emissions from any intentional radiator. (d) The following devices are exempt from the requirements of this Section:

- (1) Swept frequency field disturbance sensors operating between 1.705 and 37 MHz provided their emissions only sweep through the bands listed in paragraph (a), the sweep is never stopped with the fundamental emission within the bands listed in paragraph (a), and the fundamental emission is outside of the bands listed in paragraph (a) more than 99% of the time the device is actively transmitting, without compensation for duty cycle.

**EUT: 5WK50128**  
**FCC ID: KR55WK50128****Date of issue: 2009-02-09**

(2) Transmitters used to detect buried electronic markers at 101.4 kHz which are employed by telephone companies.

(3) Cable locating equipment operated pursuant to Section 15.213.

(4) Any equipment operated under the provisions of § 15.253, § 15.255 or § 15.257 of this part.

(5) Biomedical telemetry devices operating under the provisions of Section 15.242 of this part are not subject to the restricted band 608-614 MHz but are subject to compliance within the other restricted bands.

(6) Transmitters operating under the provisions of Subpart D or F of this part.

(7) Devices operated pursuant to § 15.225 are exempt from complying with this section for the 13.36-13.41 MHz band only.

(8) Devices operated in the 24.075-24.175 GHz band under § 15.245 are exempt from complying with the requirements of this section for the 48.15-48.35 GHz and 72.225-72.525 GHz bands only, and shall not exceed the limits specified in § 15.245(b).

(9) Devices operated in the 24.0-24.25 GHz band under § 15.249 are exempt from complying with the requirements of this section for the 48.0-48.5 GHz and 72.0-72.75 GHz bands only, and shall not exceed the limits specified in § 15.249(a).

(e) Harmonic emissions appearing in the restricted bands above 17.7 GHz from field disturbance sensors operating under the provisions of Section 15.245 shall not exceed the limits specified in Section 15.245(b).

### 11.2.2 Result

The equipment meets the requirements	Yes	No	Not
Further test results are attached	Yes	No	

EUT: 5WK50128  
 FCC ID: KR55WK50128

Date of issue: 2009-02-09

## 11.3 Radiated emission limits, general requirements

### 11.3.1 Regulation

(a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

(b) In the emission table above, the tighter limit applies at the band edges.

(c) The level of any unwanted emissions from an intentional radiator operating under these general provisions shall not exceed the level of the fundamental emission. For intentional radiators which operate under the provisions of other sections within this part and which are required to reduce their unwanted emissions to the limits specified in this table, the limits in this table are based on the frequency of the unwanted emission and not the fundamental frequency. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.

(d) The emission limits shown in the above table are based on measurements employing a CISPR quasi peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

(e) The provisions in §§ 15.31, 15.33, and 15.35 for measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

(f) In accordance with Section 15.33(a), in some cases the emissions from an intentional radiator must be measured to beyond the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator because of the incorporation of a digital device. If measurements above the tenth harmonic are so required, the radiated emissions above the tenth harmonic shall comply with the general radiated emission limits applicable to the incorporated digital device, as shown in Section 15.109 and as based on the frequency of the emission being measured, or, except for emissions contained in the restricted frequency bands shown in Section 15.205, the limit on spurious emissions specified for the intentional radiator, whichever is the higher limit. Emissions which must be measured above the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator and which fall within the restricted bands shall comply with the general radiated emission limits in Section 15.109 that are applicable to the incorporated digital device.

EUT: 5WK50128  
 FCC ID: KR55WK50128

Date of issue: 2009-02-09

### 11.3.2 Test equipment

Type	Manufacturer/ Model no.	Serial no.	Last calibration	Next calibration
Receiver (9 kHz –18.0 GHz)	Rohde & Schwarz Spectrum Analyzer FSL 18 (171a)	100.117	2008/10	2010/10
Pre-amplifier (100kHz - 1.3GHz)	Hewlett Packard 8447 E (166a)	1726A00705	2008/02	2010/02
Pre-amplifier (1GHz - 18GHz)	Narda --- (345)	---	2008/02	2010/02
Magnetic loop antenna (9 kHz - 30 MHz)	Schwarzbeck FMZB 1516 (23)	---	2008/09	2010/09
Bilog antenna (30- 1000 MHz)	Schwarzbeck VULP 9168 (406)	---	2007/02	2013/02
Horn antenna (0.86-8.5 GHz)	Schwarzbeck BBHA 9120 A (284)	236	2008/01	2013/01
Horn antenna (2.0-14.0 GHz)	Schwarzbeck BBHA 9120 C (169)	305	2008/01	2013/01
RF- cable	Kabelmetal 18m [N]	K1	2008/01	2009/01
RF- cable	Aircell 0.5m [BNC]	K40	2008/01	2009/01
RF- cable	Aircell 1m [BNC/N]	K56	2008/01	2009/01
RF- cable	Sucoflex 106 Suhner 6,4m [N]	K74	2008/01	2009/01
RF- cable	Sucoflex 106 Suhner 6,4m [N]	K75	2008/01	2009/01

**EUT: 5WK50128**  
**FCC ID: KR55WK50128**

**Date of issue: 2009-02-09**

### 11.3.3 Test procedure

The EUT and this peripheral (when additional equipment exists) are placed on a turn table which is 0.8 m above the ground. The turn table would be allowed to rotate 360 degrees to determine the position of the maximum emission level. The test distance between the EUT and the receiving antenna are 3m. To find the maximum emission, the polarization of the receiving antenna is changed in horizontal and vertical polarization; the position of the EUT was changed in different orthogonal determinations.

ANSI C63.4: 2003 Section 8 “Radiated Emissions Testing”

Measurement procedures for electric field radiated emissions above 1 GHz are covered in Clause 8 of ANSI C63.4-2003. The C63.4-2003 measurement procedure consists of both an exploratory test and a final measurement. The exploratory test is critical to determine the frequency of all significant emissions. For each mode of operation required to be tested, the frequency spectrum is monitored. Variations in antenna height, antenna orientation, antenna polarization, EUT azimuth, and cable or wire placement is explored to produce the emission that has the highest amplitude relative to the limit.

The final measurements are made based on the findings in the exploratory testing. When making exploratory and final measurements it is necessary to maximize the measured radiated emission. Subclause 8.3.1.2 of C63.4-2003 states that the measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” We consider the “cone of radiation” to be the 3 dB beamwidth of the measurement antenna.

While the “bore-sighting” technique is not explicitly mentioned in C63.4-2003, it is a useful technique for measurements using a directional antenna, such as a double-ridged waveguide antenna. Several precautions must be observed, including: knowledge of the beamwidth of the antenna and the resulting illumination area relative to the size of the EUT, estimation for source of the emission and general location within larger EUTS, measuring system sensitivity, etc.

C63.4-2003 requires that the measurement antenna is kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. That means that if the directional radiation pattern of the EUT results in a maximum emission at an upwards angle from the EUT, when a directional antenna is used to make the measurement it will be necessary for it to be pointed towards the source of the emission within the EUT. This can be done by either pointing the antenna at an angle towards the source of the emission, or by rotating the EUT, in both height and polarization, to maximize the measured emission. The emission must be kept within the illumination area of the 3 dB beamwidth of the antenna so that the maximum emission from the EUT is measured.

**EUT: 5WK50128**  
**FCC ID: KR55WK50128**

**Date of issue: 2009-02-09**

<b>Radiated emissions test characteristics</b>	
Frequency range	30 MHz - 4,000 MHz
Test distance	10m, 3 m*
Test instrumentation resolution bandwidth	9 kHz (20 kHz – 30 MHz) 120 kHz (30 MHz - 1,000 MHz) 1 MHz (1000 MHz - 12,000 MHz)
Receive antenna height	1 m (20 kHz – 30 MHz)
Receive antenna polarization	0° - 90° (20 kHz – 30 MHz)
Receive antenna scan height	1 m - 4 m (30 MHz - 12,000 MHz)
Receive antenna polarization	vertical/horizontal (30 MHz - 12,000 MHz)

\* According to Section 15.31 (f) (1): At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

#### 11.3.4 Calculation of the field strength

The field strength is calculated by the following calculation:

Corrected Level = Receiver Level + Correction Factor (without the use of a pre-amplifier)

Corrected Level = Receiver Level + Correction Factor – Pre-amplifier (with the use of a pre-amplifier)

Receiver Level : Receiver reading without correction factors  
 Correction Factor : Antenna factor + cable loss

For example:

The receiver reading is 32.7 dB $\mu$ V. The antenna factor for the measured frequency is +2.5 dB (1/m) and the cable factor for the measured frequency is 0.71 dB, giving a field strength of 35.91dB $\mu$ V/m.

The 35.91dB $\mu$ V/m value can be mathematically converted to its corresponding level in  $\mu$ V/m.

Level in  $\mu$ V/m = Common Antilogarithm (35.91/20) = 39.8

For test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f) (1) the field strength is calculated by adding additionally an extrapolation factor of 20 dB/decade (inverse linear distance for field strength measurements).

**EUT: 5WK50128**  
**FCC ID: KR55WK50128**

**Date of issue: 2009-02-09**

### 11.3.5 Test result

For all emission other than harmonic spurious emissions (e.g. oscillator frequencies, crystals, microcontroller)

TRANSMITTER SPURIOUS RADIATION BELOW 30 MHz (Section 15.205, 15.209)									
f (MHz)	Bandwidth (kHz) Type of detector	Noted receiver level dB $\mu$ V	Test distance m	Correction factor dB	Distance extrapol. factor dB	Level corrected dB $\mu$ V/m	Limit dB $\mu$ V/m	Margin dB $\mu$ V/m	Polarisation EUT / antenna orientation
0.1200	PK/0.2kHz	< 4.0	10	20.2	-59.1	-34.90	Pk46.0- @ 300	80.90	V, H/0-360°
	AV/0.2kHz	< 4.0	10	20.2	-59.1	-34.90	AV26.0 @ 300	80.90	V, H/0-360°
0.5000	AV/0.2kHz	< 4.0	10	20.2	-19.1	5.10	AV33.6 @ 30	28.5	V, H/0-360°
1.5000	AV/0.2kHz	< 4.0	10	20.2	-19.1	5.10	AV24.1 @ 30	19.00	V, H/0-360°
3.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
5.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
8.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
10.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
20.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
30.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
Measurement uncertainty			4 dB						

Remark: \*<sup>1</sup> Noise level of the measuring instrument  $\leq 4.0\text{dB}\mu\text{V}$  @ 10m distance (0.009 MHz –30 MHz)

Remark: \* Peak Limit according to Section 15.35 (b).

The equipment meets the requirements	Yes	No	N.t.
--------------------------------------	-----	----	------

Further test results are attached	Yes	No
-----------------------------------	-----	----

n.a<sup>x</sup> see page no. 22

**EUT: 5WK50128**  
**FCC ID: KR55WK50128**

**Date of issue: 2009-02-09**

For all emission other than harmonic spurious emissions (e.g. oscillator frequencies, crystals, microcontroller)

<b>TRANSMITTER SPURIOUS RADIATION ABOVE 30 MHz (Section 15.205, 15.209)</b>										
<b>f (MHz)</b>	<b>Bandwidth (kHz)</b>	<b>Noted receiver level dB<math>\mu</math>V</b>	<b>Test distance m</b>	<b>Correction factor dB</b>	<b>Distance extrapol. factor dB</b>	<b>AV Correction factor dB</b>	<b>Level corrected dB<math>\mu</math>V/m</b>	<b>Limit dB<math>\mu</math>V/m</b>	<b>Margin dB<math>\mu</math>V/m</b>	<b>Polaris. EUT / antenna cm</b>
30.0000	100, AV	≤ 6.5	3	-2.6 <sup>5</sup>	0	0	3.9	40.00	36.1	H,V/H,V
88.0000	100, AV	≤ 6.5	3	-10.8 <sup>5</sup>	0	0	-4.3	40.00	44.3	H,V/H,V
216.0000	100, AV	≤ 6.5	3	-10.3 <sup>5</sup>	0	0	-3.8	43.50	47.3	H,V/H,V
960.0000	100, AV	≤ 6.5	3	8.5 <sup>5</sup>	0	0	15.0	43.50	28.5	H,V/H,V
1700.0000	1000, AV	≤ 10	3	3.8 <sup>5</sup>	0	0	13.8	54.00	40.2	H,V/H,V
2250.0000	1000, AV	≤ 10	3	8.0 <sup>5</sup>	0	0	18.00	54.00	36.00	H,V/H,V
4000.0000	1000, AV	≤ 10	3	8.4 <sup>6</sup>	0	0	18.40	54.00	35.60	H,V/H,V
5000.0000	1000, AV	≤ 10	3	9.1 <sup>6</sup>	0	0	19.40	54.00	34.60	H,V/H,V
7500.0000	1000, AV	≤ 14	3	12.9 <sup>6</sup>	0	0	26.90	54.00	27.10	H,V/H,V
8300.0000	1000, AV	≤ 14	3	14.8 <sup>6</sup>	0	0	28.80	54.00	25.20	H,V/H,V
9400.0000	1000, AV	≤ 14	3	16.0 <sup>6</sup>	0	0	30.00	54.00	24.00	H,V/H,V
11000.0000	1000, AV	≤ 14	3	18.3 <sup>6</sup>	0	0	32.25	54.00	21.75	H,V/H,V
Measurement uncertainty			4 dB							

Bandwidth = the measuring receiver bandwidth

Remark: <sup>\*1</sup> noise floor noise level of the measuring instrument ≤ 4.0 dB $\mu$ V @ 10m distance (0.009 – 30 MHz)

Remark: <sup>\*2</sup> noise floor noise level of the measuring instrument ≤ 6.5 dB $\mu$ V @ 3m distance (30 – 1,000 MHz)

Remark: <sup>\*3</sup> noise floor noise level of the measuring instrument ≤ 10 dB $\mu$ V @ 3m distance (1,000 – 2,000 MHz)

Remark: <sup>\*4</sup> noise floor noise level of the measuring instrument ≤ 17 dB $\mu$ V @ 3m distance (2,000 – 5,500 MHz)

Remark: <sup>\*5</sup> for using a pre-amplifier in the range between 100 kHz and 1,000 MHz

Remark: <sup>\*6</sup> for using a pre-amplifier in the range between 1.0 GHz and 18.0 GHz

The equipment meets the requirements	<b>Yes</b>	<b>No</b>	<b>N.t.</b>
--------------------------------------	------------	-----------	-------------

Further test results are attached	<b>Yes</b>	<b>No</b>	
-----------------------------------	------------	-----------	--

n.a<sup>x</sup> see page no. 22

EUT: 5WK50128  
 FCC ID: KR55WK50128

Date of issue: 2009-02-09

## 11.4 Field strength of fundamental

### 11.4.1 Regulation

The field strength limit of the fundamental frequency 125 kHz is 25.6 microvolts/meter at 300 meters.  
 See also 11.3 Radiated emission limits, general requirements

### 11.4.2 Test results

INTENTIONAL RADIATOR SPURIOUS RADIATION (Section 15.209(a))									
f (MHz)	Bandwidth (kHz), Type of detector	Noted receiver level dB $\mu$ V	Test distance m	Correction factor dB	Distance extrapol. factor dB	Level corrected dB $\mu$ V/m	Limit dB $\mu$ V/m	Margin dB $\mu$ V/m	Polarisation EUT / antenna orientation
0.125	QPK/0.2kHz	42.0	10	20.2	-59.1	3.1	25.6 @ 300	22.5	H 0° / 0°
0.125	QPK/0.2kHz	41.5	10	20.2	-59.1	2.6	25.6 @ 300	23.0	H 90° / 90°
0.125	QPK/0.2kHz	41.5	10	20.2	-59.1	2.6	25.6 @ 300	23.0	V 0° / 0°
0.125	QPK/0.2kHz	42.0	10	20.2	-59.1	3.1	25.6 @ 300	22.5	V 90° / 90°
Measurement uncertainty			4 dB						

Remark: \*<sup>1</sup> noise floor noise level of the measuring instrument  $\leq 4.0 \text{ dB}\mu\text{V}$  @ 10m distance (0.009 – 30 MHz)

Remark: \*<sup>2</sup> noise floor noise level of the measuring instrument  $\leq 6.5 \text{ dB}\mu\text{V}$  @ 3m distance (30 – 1,000 MHz)

Remark: \*<sup>3</sup> noise floor noise level of the measuring instrument  $\leq 10 \text{ dB}\mu\text{V}$  @ 3m distance (1,000 – 2,000 MHz)

Remark: \*<sup>4</sup> noise floor noise level of the measuring instrument  $\leq 17 \text{ dB}\mu\text{V}$  @ 3m distance (2,000 – 5,500 MHz)

Remark: \*<sup>5</sup> for using a pre-amplifier in the range between 100 kHz and 1,000 MHz

The equipment meets the requirements	yes	no	n.a.
--------------------------------------	-----	----	------

Further test results are attached	yes	no	page no:
-----------------------------------	-----	----	----------

n.a.<sup>x</sup> see page no. 22

EUT: 5WK50128  
 FCC ID: KR55WK50128

Date of issue: 2009-02-09

## 11.5 Field strength of spurious emissions

### 11.5.1 Regulation

See 11.3 Radiated emission limits, general requirements

### 11.5.2 Test results

INTENTIONAL RADIATOR SPURIOUS RADIATION (Section 15.209(a))									
f (MHz)	Bandwidth (kHz), Type of detector	Noted receiver level <b>dB<math>\mu</math>V</b>	Test distance <b>m</b>	Correction factor <b>dB</b>	Distance extrapol. factor <b>dB</b>	Level corrected <b>dB<math>\mu</math>V/m</b>	Limit <b>dB<math>\mu</math>V/m</b>	Margin <b>dB<math>\mu</math>V/m</b>	Polarisation EUT / antenna orientation
0.250	QPK/0.2kHz	< 4.0	10	20.2	-59.1	< -34.9	19.6 @ 300	<b>54.5</b>	V, H/0-360°
0.375	QPK/0.2kHz	15.5	10	20.2	-59.1	-23.4	16.1 @ 300	<b>39.5</b>	H 0° / 0°
0.500	QPK/9kHz	< 4.0	10	20.2	-19.1	< 5.1	33.6 @ 30	<b>28.5</b>	V, H/0-360°
0.625	QPK/9kHz	< 4.0	10	20.2	-19.1	< 5.1	31.7 @ 30	<b>26.6</b>	V, H/0-360°
0.750	QPK/9kHz	< 4.0	10	20.2	-19.1	< 5.1	30.1 @ 30	<b>25.0</b>	V, H/0-360°
0.875	QPK/9kHz	< 4.0	10	20.2	-19.1	< 5.1	28.7 @ 30	<b>23.6</b>	V, H/0-360°
1.000	QPK/9kHz	< 4.0	10	20.2	-19.1	< 5.1	27.6 @ 30	<b>22.5</b>	V, H/0-360°
1.125	QPK/9kHz	< 4.0	10	20.2	-19.1	< 5.1	26.6 @ 30	<b>21.5</b>	V, H/0-360°
1.250	QPK/9kHz	< 4.0	10	20.2	-19.1	< 5.1	25.6 @ 30	<b>20.5</b>	V, H/0-360°
Measurement uncertainty			4 dB						

Remark: \*<sup>1</sup> noise floor noise level of the measuring instrument  $\leq 4.0 \text{ dB}\mu\text{V}$  @ 10m distance (0.009 – 30 MHz)

Remark: \*<sup>2</sup> noise floor noise level of the measuring instrument  $\leq 6.5 \text{ dB}\mu\text{V}$  @ 3m distance (30 – 1,000 MHz)

Remark: \*<sup>3</sup> noise floor noise level of the measuring instrument  $\leq 10 \text{ dB}\mu\text{V}$  @ 3m distance (1,000 – 2,000 MHz)

Remark: \*<sup>4</sup> noise floor noise level of the measuring instrument  $\leq 17 \text{ dB}\mu\text{V}$  @ 3m distance (2,000 – 5,500 MHz)

Remark: \*<sup>5</sup> for using a pre-amplifier in the range between 100 kHz and 1,000 MHz

The equipment meets the requirements	<b>yes</b>	<b>no</b>	<b>n.a.</b>
--------------------------------------	------------	-----------	-------------

Further test results are attached	<b>yes</b>	<b>no</b>	page no:
-----------------------------------	------------	-----------	----------

n.a<sup>x</sup> see page no. 22

EUT: 5WK50128  
FCC ID: KR55WK50128

Date of issue: 2009-02-09

## 12. Additional information to the test report

### Remarks

N.t.<sup>1</sup> Not tested, because the antenna is part of the PCB

N.t.<sup>2</sup> Not tested, because the EUT is directly battery powered

N.t.<sup>3</sup> Not tested, because not applicable for this type of equipment

---

**EUT: 5WK50128**  
**FCC ID: KR55WK50128**

**Date of issue: 2009-02-09**

**End of test report**