

FCC ID: KR582035100
IC ID: 7812D-82035100

EMI - TEST REPORT

- FCC Part 15.249, RSS210 -

| | | |
|-------------------|----------------|------------------------------------|
| Test Report No. : | T36248-07-00HU | 09. December 2014 Date of issue |
|-------------------|----------------|------------------------------------|

Type / Model Name : A2C82035100

Product Description : Transceiver for remote vehicle access

Applicant : Continental Automotive GmbH

Address : Siemensstr. 12

93055 Regensburg, Germany

Manufacturer : Continental Guadalajara México, S.A. de C.V.

Address : Camino a la Tijera No.3

45640 Tlajomulco de Zúñiga, Jalisco, Mexico

Licence holder : Continental Automotive GmbH

Address : Siemensstr. 12

93055 Regensburg, Germany

Test Result according to the
standards listed in clause 1 test
standards:

POSITIVE



DAkkS
Deutsche
Akkreditierungsstelle
D-PL-12030-01-01
D-PL-12030-01-02

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test results
without the written permission of the test laboratory.

FCC ID: KR582035100
IC ID: 7812D-82035100

Contents

| | |
|--|-----------|
| 1 TEST STANDARDS | 3 |
| 2 SUMMARY | 4 |
| 2.1 Test result summary | 4 |
| 2.2 GENERAL REMARKS: | 5 |
| 2.3 FINAL ASSESSMENT: | 6 |
| 3 EQUIPMENT UNDER TEST | 7 |
| 3.1 Photo documentation of the EUT – Please see attachment A | 7 |
| 3.2 Power supply system utilised | 7 |
| 3.3 Short description of the equipment under test (EUT) | 7 |
| 4 TEST ENVIRONMENT | 8 |
| 4.1 Address of the test laboratory | 8 |
| 4.2 Statement regarding the usage of logos in test reports | 8 |
| 4.3 Environmental conditions | 8 |
| 4.4 Statement of the measurement uncertainty | 8 |
| 4.5 Measurement protocol for FCC and IC | 9 |
| 5 TEST CONDITIONS AND RESULTS | 11 |
| 5.1 Conducted emissions | 11 |
| 5.2 Radiated emission of the fundamental wave | 12 |
| 5.4 Spurious emissions radiated | 15 |
| 5.5 20 dB bandwidth | 22 |
| 5.6 Bandwidth of momentary signals | 26 |
| 5.7 Antenna application | 29 |
| 5.8 Receiver radiated emissions | 30 |
| 6 USED TEST EQUIPMENT AND ACCESSORIES | 35 |

FCC ID: KR582035100

IC ID: 7812D-82035100

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Rules and Regulations Part 15, Subpart A - General (October, 2014)

| FCC Rules and Regulations Part 15, Subpart A - General (October, 2014) | |
|---|---|
| Part 15, Subpart A, Section 15.31 | Measurement standards |
| Part 15, Subpart A, Section 15.33 | Frequency range of radiated measurements |
| Part 15, Subpart A, Section 15.35 | Measurement detector functions and bandwidths |
| FCC Rules and Regulations Part 15, Subpart C - Intentional Radiators (October, 2014) | |
| Part 15, Subpart C, Section 15.203 | Antenna requirement |
| Part 15, Subpart C, Section 15.204 | External radio frequency power amplifiers and antenna modifications |
| Part 15, Subpart C, Section 15.205 | Restricted bands of operation |
| Part 15, Subpart C, Section 15.207 | Conducted limits |
| Part 15, Subpart C, Section 15.209 | Radiated emission limits, general requirements |
| Part 15, Subpart C, Section 15.249 | Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz, 5725 - 5875 MHz, and 24.0 - 24.25 GHz |
| ANSI C63.4: 2009 | Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz. |
| CISPR 16-4-2: 2003 | Uncertainty in EMC measurement |
| CISPR 22: 2005 EN 55022: 2006 | Information technology equipment |

FCC ID: KR582035100
IC ID: 7812D-82035100

2 SUMMARY

2.1 Test result summary

The A2C82035100 is a transceiver for remote vehicle access:

Operating in the 902 MHz – 928 MHz band:

| FCC Rule Part | RSS Rule Part | Description | Result |
|-----------------|------------------|-----------------------------------|----------------|
| 15.207(a) | RSS Gen, 8.8 (3) | AC power line conducted emissions | not applicable |
| 15.215(c) | RSS Gen, 4.6.3 | -20 dBc EBW | not applicable |
| 15.249(a) | RSS-210, A8.4(4) | Field strength of fundamental | passed |
| 15.249(d) | RSS-210, A8.5 | Out-of-band emission, radiated | passed |
| 15.205(a) | RSS-Gen, 8.10 | Emissions in restricted bands | passed |
| 15.35(c) | RSS-Gen, 6.10 | Pulsed operation | not applicable |
| 15.107 | RSS Gen, 8.8 (3) | AC power line conducted emissions | not applicable |
| | RSS-Gen, 6.11 | Transmitter frequency stability | not applicable |
| | RSS-Gen, 6.6 | 99 % Bandwidth | passed |
| OET Bulletin 65 | RSS102, 3.2 | Co-location, Co-transmission | not applicable |

The mentioned RSS Rule Parts in the above table are related to:

RSS Gen, Issue 4, November 2014

RSS 210, Issue 8, December 2010

RSS 102, Issue 4, March 2010

FCC ID: KR582035100
IC ID: 7812D-82035100

2.2 GENERAL REMARKS:

All radiated tests have been performed on samples which are in original state in a test mode function with three different examples of the same car roof antenna:

- No. 1: 39150-TZ3A-A231-M1
- No. 2: 39150-TZ3A-X021-M1
- No. 3: 39150-TZ3A-A040-M1

and long range antenna:

- Bracket type 1: A2C93257900
- Bracket type 2: A2C93258000

The difference between the long range antennas are the plastic mounting bracket. The PCB and all other parts from the antenna are identicall. For detailed information about the antenna type please refer to the manufacturer documents.

All other test has been performed conducted with a special antenna connector to SMA.

For technical differences between the three antennas please refer to the manufacturer documents.

The EuT has an external antenna and is powered by a vehicle battery.

Declaration of manufacturer:

- Operation modes:
- DSSS transmissions shall comply with the US regulation as defined in FCC part 15.247
 - o LR CH1: 925.99955 MHz
 - o LR CH2: 926.00045 MHz
 - Rx mode:
 - 924.000 MHz
- FSK transmissions shall comply with the US regulation as defined in FCC part 15.249
 - o SR CH1: 926.225 MHz
 - o SR CH2: 925.400 MHz
 - Rx mode:
 - 924.600 MHz
 - 923.625 MHz

The radiated tests with the long range antenna without mounting bracket and the duty cycle test were performed on 13. October 2014 and 01. December 2014.

All other tests were performed from 13. January 2014 to 15. January 2014.

FCC ID: KR582035100
IC ID: 7812D-82035100

2.3 FINAL ASSESSMENT:

The equipment under test **fulfills** the EMI requirements cited in clause 1 test standards.

Date of receipt of test sample : acc. to storage records

Testing commenced on : 13. January 2014

Testing concluded on : 01. December 2014

Checked by: Tested by:

Klaus Gegenfurtner
Teamleader radio

Markus Huber

FCC ID: KR582035100
IC ID: 7812D-82035100

3 EQUIPMENT UNDER TEST

3.1 Photo documentation of the EUT – Please see attachment A

3.2 Power supply system utilised

Power supply voltage : 12.0 V / DC (Vehicle regulated)

3.3 Short description of the equipment under test (EUT)

The EuT is a transceiver module for remote vehicle access.

Number of tested samples: 1
Serial number: Prototype

EUT operation mode:

The equipment under test was operated during the measurement under the following conditions:

- Continuous modulated Tx mode at SR1 926.255 MHz, SR2 925.400 MHz

- Rx mode at SR1 924.600 MHz, SR2 923.625 MHz

-

EUT configuration:

The following peripheral devices and interface cables were connected during the measurements:

- Car roof antenna, 39150-TZ3A-A231-M1 Model : Supplied by customer Continental
- Car roof antenna, 39150-TZ3A-X021-M1 Model : Supplied by customer Continental
- Car roof antenna, 39150-TZ3A-A040-M1 Model : Supplied by customer Continental
- Car battery 12 V / DC Model : Supplied by mikes-testingpartners gmbh
- Long range antenna, A2C93257900 Model : Supplied by customer Continental
- Long range antenna, A2C93258000 Model : Supplied by customer Continental
 - Customer specific cables
 - Unscreened power cables

FCC ID: KR582035100
IC ID: 7812D-82035100

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

CSA Group Bayern GmbH
Ohmstrasse 1-4
94342 STRASSKIRCHEN
GERMANY

4.2 Statement regarding the usage of logos in test reports

The accreditation and notification body logos displayed in this test report are only valid for standards listed in the accreditation or notification scope of CSA Group Bayern GmbH.

4.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35 ° C

Humidity: 30-60 %

Atmospheric pressure: 86-106 kPa

4.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. It is noted that the expanded measurement uncertainty corresponds to the measurement results from the standard measurement uncertainty multiplied by the coverage factor $k = 2$. The true value is located in the corresponding interval with a probability of 95 %. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16-4-2 / 11.2003 „Uncertainties, statistics and limit modelling – Uncertainty in EMC measurements“ and is documented in the quality system acc. to DIN EN ISO/IEC 17025. For all measurements shown in this report, the measurement uncertainty of the test laboratory, CSA Group Bayern GmbH, is below the measurement uncertainty as defined by CISPR. Therefore, no special measures must be taken into consideration with regard to the limits according to CISPR. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

FCC ID: KR582035100
IC ID: 7812D-82035100

4.5 Measurement protocol for FCC and IC

4.5.1 General information

4.5.1.1 Test methodology

Conducted and radiated disturbance testing is performed according to the procedures set out by the International Special Committee on Radio Interference (CISPR) Publication 22, European Standard EN 55022 as shown under section 1 of this report.

The Open Area test site is a listed Open Site under the Canadian Test-Sites File-No:

IC 3009A-1

In compliance with RSS 210 testing for RSS compliance may be achieved by following the procedures set out in ANSI C63.4 and applying the CISPR 22 limits.

4.5.1.2 Justification

The equipment under test (EUT) is configured in a typical user arrangement in accordance with the manufacturer's instructions. A cable is connected to each available port and either terminated with a peripheral using the appropriate impedance characteristic or left unterminated. Where appropriate, cables are manually manipulated with respect to each other thus obtaining maximum disturbances from the unit.

4.5.1.3 Details of test procedures

The test methods used comply with CISPR Publication 22, EN 55022 - "Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement" and with ANSI C63.4 - "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". In compliance with 47 CFR Part 15 Subpart A, Section 15.38 testing for FCC compliance may be achieved by following the procedures set out in ANSI C63.4 and applying the CISPR 22 limits.

4.5.1.4 Conducted emission

The final level, expressed in dB μ V, is arrived at by taking the reading directly from the EMI receiver. This level is compared directly to the FCC limit or to the CISPR limit.

To convert between dB μ V and μ V, the following conversion formula apply:

$$\begin{aligned} \text{dB}\mu\text{V} &= 20 \cdot \log(\mu\text{V}) \\ \mu\text{V} &= 10^{(\text{dB}\mu\text{V}/20)} \end{aligned}$$

Conducted emissions on the 50 Hz and/or 60 Hz power interface of the EUT are measured in the frequency range of 150 kHz to 30 MHz. The measurements are performed using a receiver, which has CISPR characteristic bandwidth and quasi-peak detection and a Line Impedance Stabilization Network (LISN) with 50 Ω / 50 μ H (CISPR 16) characteristics. Table top equipment is placed on a non-conducting table 80 centimetres above the floor and is positioned 40 centimetres from the vertical ground plane (wall) of the screen room. If the minimum limit margin of a peak mode measurement appears to be less than 20 dB, the emissions are remeasured using a tuned receiver with quasi-peak and average detection and recorded on the data sheets.

**FCC ID: KR582035100
IC ID: 7812D-82035100**

4.5.1.5 Radiated emission (electrical field 30 MHz - 1 GHz)

Spurious emission from the EUT is measured in the frequency range of 30 MHz to 1000 MHz using a tuned receiver and appropriate broadband linearly polarised antennas. Measurements between 30 MHz and 1000 MHz are made with 120 kHz/6 dB bandwidth and quasi-peak detection. Table top equipment is placed on a 1.0 X 1.5 m non-conducting table 80 centimetres above the ground plane. Floor standing equipment is placed directly on the turntable/ground plane. The setup of the equipment under test is established in accordance with ANSI C63.4. The interface cables that are closer than 40 cm to the ground plane are bundled in the center in a serpentine fashion so that they are at least 40 cm from the ground plane. Cables to simulators/testers (if used in this test) are routed through the center of the table and to a screened room located outside the test area. The antenna is positioned 3, 10 or 30 m horizontally from the EUT and is repeated vertically. To locate maximum emissions from the test sample the antenna is varied in height from 1 to 4 m and the EUT is rotated 360 degrees.

The final level in dB μ V/m is calculated by add on the reading value from the EMI receiver (level dB μ V) the correction factor. The FCC or CISPR limit is subtracted from this result in order to provide the limit margin listed in the measurement protocol.

The resolution bandwidth setting:

30 MHz – 1000 MHz: RBW: 120 kHz

Example:

| Frequency (MHz) | Reading level (dB μ V) | + | Correction Factor (dB/m) | = | Level (dB μ V/m) | - | CISPR Limit (dB μ V/m) | = | Delta (dB) |
|--------------------|-------------------------------|---|-----------------------------|---|-------------------------|---|-------------------------------|---|---------------|
| 719.0 | 75.0 | + | 32.6 | = | 107.6 | - | 110.0 | = | -2.4 |

4.5.2 Radiated emission (electrical field 1 GHz - 40 GHz)

Description of measurement

Radiated emissions from the EUT are measured in the frequency range 1 GHz up to the maximum frequency as specified in 47 CFR Part 15, Subpart A, Section 15.33, using a spectrum analyser and appropriate linearly polarized antennas. Table top equipment is placed on a 1.0 X 1.5 metre non-conducting table 80 centimetres above the ground plane. Floor standing equipment is placed directly on the turntable/ground plane. The setup of the equipment under test is following set out in ANSI C63.4. The interface cables that are closer than 40 centimetres to the ground plane are bundled in the center in a serpentine fashion so they are at least 40 centimetres from the ground plane. Cables to simulators/testers (if used in this test) are routed through the center of the table and to a screened room located outside the test area. Measurements are made in both the horizontal and vertical polarization planes in a fully anechoic room using a spectrum analyser set to max peak detector function and a resolution 1 MHz and video bandwidth 3 MHz for peak and 10 Hz for average measurement. The conditions determined as worst case will then be used for the final measurements. When the EUT is larger than the beam width of the measuring antenna it will be moved over the surface for the four sides of the equipment. Where appropriate, the test distance may be reduced in order to detect emissions under better uncertainty and are calculated at the specified test distance.

FCC ID: KR582035100

IC ID: 7812D-82035100

5 TEST CONDITIONS AND RESULTS

5.1 Conducted emissions

For test instruments and accessories used see section 6 Part A 4.

5.1.1 Description of the test location

Test location: NONE

5.1.2 Photo documentation of the test set-up

5.1.3 Applicable standard

According to FCC Part 15, Section 15.207(a):

Except as shown in paragraphs (b) and (c) of this Section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the given limits.

5.1.4 Description of Measurement

The measurements are performed following the procedures set out in ANSI C63.4 described under item 4.4.3. If the minimum limit margin appears to be less than 20 dB with a peak mode measurement, the emissions are remeasured using a tuned receiver with quasi-peak and average detection and recorded on the data sheets.

5.1.5 Test result

Limit according to FCC Part 15, Section 15.207(a):

| Frequency of Emission (MHz) | Conducted Limit (dB μ V) | |
|--------------------------------|------------------------------|------------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56 * | 56 to 46 * |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

* Decreases with the logarithm of the frequency

Remarks: The measurement is not applicable.

The EuT has no AC mains connections.

The EuT is separated powered by a 12.0 V / DC vehicle battery.

FCC ID: KR582035100
IC ID: 7812D-82035100

5.2 Radiated emission of the fundamental wave

For test instruments and accessories used see section 6 Part **CPR 2**.

5.2.1 Description of the test location

Test location: OATS 1


Test distance: 3 m

5.2.2 Photo documentation of the test set-up

Roof antenna:



Long range antenna:



FCC ID: KR582035100
IC ID: 7812D-82035100

5.2.1 Applicable standard

According to FCC Part 15C, Section 15.249(a):

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the effective limits.

5.2.2 Description of Measurement

The radiated power of the fundamental wave from the EUT is measured in the frequency range of 30 to 1000 MHz using a tuned receiver and appropriate broadband linearly polarized antennas. Measurements between 30 MHz and 1000 MHz are made with 120 kHz/6 dB bandwidth and quasi-peak detection. Table top equipment is placed on a 1.0 X 1.5 meter non-conducting table 80 centimetres above the ground plane. Floor standing equipment is placed directly on the turntable/ground plane. The setup of the Equipment under test will be in accordance to ANSI C63.4-2003.

The Interface cables that are closer than 40 centimetres to the ground plane are bundled in the center in a serpentine fashion so they are at least 40 centimetres from the ground plane. Cables to simulators/testers (if used in this test) are routed through the center of the table and to a screen room located outside the test area. The antenna was positioned 3, 10 or 30 meters horizontally from the EuT. To locate maximum emissions from the test sample the antenna is varied in height from 1 to 4 meters, measurement scans are made with both horizontal and vertical antenna polarization's and the EuT are rotated 360 degrees.

The final level, expressed in dB μ V/m, is arrived by taking the reading from the EMI receiver (Level dB μ V) and adding the correction factors and cable loss factor (Factor dB) to it. This is done automatically in the EMI receiver, where the correction factors are stored. This result then has the FCC or CISPR limit subtracted from it to provide the Delta which gives the tabular data as shown in the data sheets at page.

The resolution bandwidth during the measurement is as follows:

30 MHz – 1000 MHz: ResBW: 120 kHz

**FCC ID: KR582035100
IC ID: 7812D-82035100**

5.2.3 Test result

- Car roof antenna 39150-TZ63A-A231-M1

| Frequency [MHz] | L: QP [dB μ V] | L: AV [dB μ V] | Bandwidth [kHz] | Correct. [dB] | L: QP [dB μ V/m] | L: AV [dB μ V/m] | Limit [dB μ V/m] | Delta [dB] |
|--------------------|-----------------------|-----------------------|--------------------|------------------|-------------------------|-------------------------|-------------------------|---------------|
| 925.400 | 49.7 | | 120 | 29.2 | 78.9 | | 94.0 | -15.1 |
| 926.225 | 49.5 | | 120 | 29.2 | 78.7 | | 94.0 | -15.3 |

- Car roof antenna 39150-TZ3A-X022-M1

| Frequency [MHz] | L: QP [dB μ V] | L: AV [dB μ V] | Bandwidth [kHz] | Correct. [dB] | L: QP [dB μ V/m] | L: AV [dB μ V/m] | Limit [dB μ V/m] | Delta [dB] |
|--------------------|-----------------------|-----------------------|--------------------|------------------|-------------------------|-------------------------|-------------------------|---------------|
| 925.400 | 51.1 | | 120 | 29.2 | 80.3 | | 94.0 | -13.7 |
| 926.225 | 52.7 | | 120 | 29.2 | 81.9 | | 94.0 | -12.1 |

- Car roof antenna 39150-TZ3A-A041-M1

| Frequency [MHz] | L: QP [dB μ V] | L: AV [dB μ V] | Bandwidth [kHz] | Correct. [dB] | L: QP [dB μ V/m] | L: AV [dB μ V/m] | Limit [dB μ V/m] | Delta [dB] |
|--------------------|-----------------------|-----------------------|--------------------|------------------|-------------------------|-------------------------|-------------------------|---------------|
| 925.400 | 52.1 | | 120 | 29.2 | 81.3 | | 94.0 | -12.7 |
| 926.225 | 52.1 | | 120 | 29.2 | 81.3 | | 94.0 | -12.7 |

- Long range antenna without mounting bracket

| Frequency [MHz] | L: QP [dB μ V] | L: AV [dB μ V] | Bandwidth [kHz] | Correct. [dB] | L: QP [dB μ V/m] | L: AV [dB μ V/m] | Limit [dB μ V/m] | Delta [dB] |
|--------------------|-----------------------|-----------------------|--------------------|------------------|-------------------------|-------------------------|-------------------------|---------------|
| 925.400 | 60.4 | | 120 | 28.6 | 89.0 | | 94.0 | -5.0 |
| 926.225 | 61.6 | | 120 | 28.6 | 90.2 | | 94.0 | -3.8 |

Average-Limit according to FCC Part 15C, Section 15.249(a):

| Frequency (MHz) | Field strength of fundamental | |
|--------------------|-------------------------------|----------------|
| | (mV/m) | dB(μ V/m) |
| 902 - 928 | 50 | 94 |
| 2400 - 2483.5 | 50 | 94 |
| 5725-5875 | 50 | 94 |
| 24000 - 24250 | 250 | 108 |

Peak-Limit according to FCC Part 15C, Section 15.249(e):

However the peak fieldstrength shall not exceed the maximum permitted average limit by more than 20 dB.

The requirements are **FULFILLED**.

Remarks: _____

FCC ID: KR582035100
IC ID: 7812D-82035100

5.4 Spurious emissions radiated


For test instruments and accessories used see section 6 Part **SER1, SER 2, SER 3**.

5.4.1 Description of the test location


Test location: OATS 1
Test location: Anechoic chamber 2
Test distance: 3 m

5.4.2 Photo documentation of the test set-up

Car roof antenna:





FCC ID: KR582035100
IC ID: 7812D-82035100



Long range antenna without mounting bracket:



FCC ID: KR582035100
IC ID: 7812D-82035100



**FCC ID: KR582035100
IC ID: 7812D-82035100**

5.4.3 Applicable standard

According to FCC Part 15C, Section 15.249 (d):

Emission radiated outside of the specified frequency bands, except harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated limit in FCC Part 15C, Section 15.209, whichever is the lesser attenuation.

5.4.4 Description of Measurement

The radiated emissions from the EUT are measured in the frequency range of 9 kHz to 1000 MHz using a tuned receiver and appropriate broadband linearly polarized antennas. The setup of the EUT will be in accordance to ANSI C63.4. In the frequency range above 1 GHz a spectrum analyser is used with appropriate linear polarized antennas. If the emission level in peak mode complies with the average limit then testing will be stopped and peak values of the EUT will be reported, otherwise, the emission will be measured in average mode again and reported. During the test, the EUT was set into continuous transmitting mode modulated.

Instrument settings:

| | | |
|--------------------|------|---------|
| 9 kHz – 150 kHz | RBW: | 200 Hz |
| 150 kHz - 30 MHz | RBW: | 9 kHz |
| 30 MHz – 1000 MHz: | RBW: | 120 kHz |
| 1000 MHz – 40 GHz | RBW: | 1 MHz |

5.4.5 Test result f < 1 GHz

| Frequency [kHz] | L: QP [dB μ V] | L: AV [dB μ V] | Bandwidth [kHz] | Correct. [dB] | L: QP [dB μ V/m] | L: AV [dB μ V/m] | Limit [dB μ V/m] | Delta [dB] |
|--------------------|-----------------------|-----------------------|--------------------|------------------|-------------------------|-------------------------|-------------------------|---------------|
| 536.8 | 24.1 | 19.7 | 9.0 | 20 | 44.1 | 39.7 | 73.0 | -33.3 |
| 1073.6 | 23.4 | 18.0 | 9.0 | 20 | 43.4 | 38.0 | 67.0 | -29.0 |
| 1342.0 | 21.6 | 15.9 | 9.0 | 20 | 41.6 | 35.9 | 65.0 | -29.1 |

| Frequency [MHz] | L: QP [dB μ V] | Correct. [dB] | L: QP [dB μ V/m] | Limit [dB μ V/m] | Delta [dB] |
|--------------------|-----------------------|------------------|-------------------------|-------------------------|---------------|
| 73.50 | 2.8 | 12.0 | 14.8 | 40.0 | -22.9 |
| 162.20 | 6.9 | 14.6 | 21.5 | 43.5 | -21.3 |

In both frequency ranges, regardless of the antenna type, only ambient noises could be detected.

FCC ID: KR582035100
IC ID: 7812D-82035100

5.4.6 Test result f > 1 GHz

Car roof antenna 39150-TZ3A-X022-M1

Frequency SR1 926.225 MHz:

| Frequency (MHz) | L: PK (dB μ V) | L: AV (dB μ V) | Bandwidth (kHz) | Correct. (dB) | Duty Cycle Correct. factor (dB) | Corrected PK level dB(μ V/m) | Effective limit dB(μ V/m) | Delta (dB) |
|-----------------|--------------------|--------------------|-----------------|---------------|---------------------------------|-----------------------------------|--------------------------------|------------|
| 1852.45 | 60.43 | -- | 1000 | -15.9 | -- | 44.5 | 54.0 | -9.5 |
| 2778.68 | 54.34 | -- | 1000 | -12.9 | -- | 41.4 | 54.0 | -12.6 |

Frequency SR2 925.400 MHz:

| Frequency (MHz) | L: PK (dB μ V) | L: AV (dB μ V) | Bandwidth (kHz) | Correct. (dB) | Duty Cycle Correct. factor (dB) | Corrected PK level dB(μ V/m) | Effective limit dB(μ V/m) | Delta (dB) |
|-----------------|--------------------|--------------------|-----------------|---------------|---------------------------------|-----------------------------------|--------------------------------|------------|
| 1850.80 | 59.34 | -- | 1000 | -15.9 | -- | 43.4 | 54.0 | -10.6 |
| 2776.20 | 57.87 | -- | 1000 | -12.9 | -- | 45.0 | 54.0 | -9.0 |

⇒ Measurement was performed in both SR frequency ranges with the worst case antenna with the highest antenna gain.

Long range antenna without mounting bracket:

Frequency SR1 926.225 MHz:

| Frequency (MHz) | L: PK (dB μ V) | L: AV (dB μ V) | Bandwidth (kHz) | Correct. (dB) | Duty Cycle Correct. factor (dB) | Corrected PK level dB(μ V/m) | Effective limit dB(μ V/m) | Delta (dB) |
|-----------------|--------------------|--------------------|-----------------|---------------|---------------------------------|-----------------------------------|--------------------------------|------------|
| 1852.45 | 58.8 | -- | 1000 | -16.3 | -- | 42.5 | 54.0 | -11.5 |
| 2778.68 | 53.1 | -- | 1000 | -12.6 | -- | 40.5 | 54.0 | -13.5 |

Frequency SR2 925.400 MHz:

| Frequency (MHz) | L: PK (dB μ V) | L: AV (dB μ V) | Bandwidth (kHz) | Correct. (dB) | Duty Cycle Correct. factor (dB) | Corrected PK level dB(μ V/m) | Effective limit dB(μ V/m) | Delta (dB) |
|-----------------|--------------------|--------------------|-----------------|---------------|---------------------------------|-----------------------------------|--------------------------------|------------|
| 1850.80 | 57.6 | -- | 1000 | -15.9 | -- | 41.7 | 54.0 | -12.3 |
| 2776.20 | 54.4 | -- | 1000 | -12.6 | -- | 41.8 | 54.0 | -12.2 |

FCC ID: KR582035100
IC ID: 7812D-82035100

Limit according to FCC Part 15C, Section 15.209:

| Frequency (MHz) | 15.209 Limits dB(μ V/m) | Measurement distance (m) |
|--------------------|---------------------------------|-----------------------------|
| 0.009 - -0.49 | 2400/f(kHz) | 300 |
| 0.49 - 1.705 | 24000/f(kHz) | 30 |
| 1.705 - 30.0 | 30 | 30 |
| 30-88 | 40 | 3 |
| 88-216 | 43.5 | 3 |
| 216-960 | 46 | 3 |
| Above 960 | 54 | 3 |

Average limit according to FCC Part 15C, Section 15.249(a):

| Fundamental frequency (MHz) | Field strength of harmonics | |
|--------------------------------|-----------------------------|----------------|
| | (μ V/m) | dB(μ V/m) |
| 902 - 928 | 500 | 54 |
| 2400 - 2483.5 | 500 | 54 |
| 5725-5875 | 500 | 54 |
| 24000 - 24250 | 2500 | 68 |

Peak-Limit according to FCC Subpart 15.249(a), Subpart 15.249(e)

| Frequency (MHz) | Fieldstrength of harmonics | |
|--------------------|----------------------------|-----------------|
| | (μ V/m) | dB (μ V/m) |
| 902-928 | 5000 | 74 |
| 2400-2483.5 | 5000 | 74 |
| 5725-5875 | 5000 | 74 |

Average-Limit according to FCC Subpart 15.249(d) for spurious emissions outside of the specified frequency band:

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

| Frequency [MHz] | 50dB below of the fundamental [$\text{dB}\mu\text{V/m}$] | 15.209 Limits [$\text{dB}\mu\text{V/m}$] | General Radiated Limits [$\text{dB}\mu\text{V/m}$] |
|--------------------|---|---|---|
| 30-88 | 44 | 40 | 44 |
| 88-216 | 44 | 43.5 | 44 |
| 216-960 | 44 | 46 | 46 |
| Above 960 | 44 | 54 | 54 |

FCC ID: KR582035100
IC ID: 7812D-82035100

Restricted bands of operation:

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209

| MHz | MHz | GHz |
|-----------------------|-----------------|---------------|
| 25.5 – 25.67 | 960 – 1240 | 4.5 – 5.15 |
| 37.5 – 38.25 | 1300 – 1427 | 5.35 – 5.46 |
| 73 – 74.6 | 1435 – 1626.5 | 7.25 – 7.75 |
| 74.8 – 75.2 | 1645.5 – 1646.5 | 8.025 – 8.5 |
| 108 – 121.94 | 1660 – 1710 | 9.0 – 9.2 |
| 123 – 138 | 1718.8 – 1722.2 | 9.3 – 9.5 |
| 149.9 – 150.05 | 2200 – 2300 | 10.6 – 12.7 |
| 156.52475 – 156.52525 | 2310 – 2390 | 13.25 – 13.4 |
| 156.7 – 156.9 | 2483.5 – 2500 | 14.47 – 14.5 |
| 162.0125 – 167.17 | 2655 – 2900 | 15.35 – 16.2 |
| 167.72 – 173.2 | 3260 – 3267 | 17.7 – 21.4 |
| 240 – 285 | 3332 – 3339 | 22.01 – 23.12 |
| 322 – 335.4 | 3345.8 – 3358 | 23.6 – 24.0 |
| 399.9 – 410 | 3600 – 4400 | 31.2 – 31.8 |
| 608 – 614 | | 36.43 – 36.5 |

The requirements are **FULFILLED**.

Remarks: The measurement was performed up to the 10th harmonic (10.0 GHz).

FCC ID: KR582035100
IC ID: 7812D-82035100


5.5 20 dB bandwidth

For test instruments and accessories used see section 6 Part **MB**.

5.5.1 Description of the test location

Test location: AREA4

5.5.2 Photo documentation of the test set-up



5.5.3 Applicable standard

According to FCC Part 15, Section 15.215(c):

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in Section 15.217 through Section 15.257, must be designed to ensure that the 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section under which the equipment is operated.

5.5.4 Description of Measurement

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio of -20 dB. The reference level is the level of the highest signal amplitude observed from the transmitter at the fundamental frequency. Alternative is the x-dB-down function of the analyser used. The EBW is then directly shown in the marker display. The measurement is performed with normal modulation and a transfer rate means the worst case.

FCC ID: KR582035100
IC ID: 7812D-82035100

5.5.5 Test result

| Fundamental [MHz] | 20dB Bandwidth F1 [MHz] | 20dB Bandwidth F2 [MHz] | Measured Bandwidth [MHz] | LIMIT Fundamental f*0,0050 [MHz] |
|----------------------|----------------------------------|----------------------------------|--------------------------------|---|
| 926.225 | 926.180 | 926.265 | 0.085 | 4.63 |
| 925.400 | 925.355 | 925.439 | 0.084 | 4.63 |
| | | | | |

Limit according to FCC Part 15C Section 15.215(c):

| Frequency (MHz) | 20 dB BW limit dependent of the carrier (%) |
|--------------------|--|
| 70 – 900 | 0.25 |
| above 900 | 0.50 |

The bandwidth of the emission shall be no wider than 0.50% of the centre frequency for devices operating above 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.


The requirements are **FULFILLED**.

Remarks: For detailed test result please refer to following test protocols.

FCC ID: KR582035100
IC ID: 7812D-82035100


5.5.6 Test protocols

SR1, 926.225 MHz:



FCC ID: KR582035100
IC ID: 7812D-82035100

SR2, 925.400 MHz:



**FCC ID: KR582035100
IC ID: 7812D-82035100**


5.6 Bandwidth of momentary signals

For test instruments and accessories used see section 6 Part **MB**.

5.6.1 Description of the test location

Test location: Anechoic chamber 2

5.6.2 Photo documentation of the test set-up



5.6.3 Test result

| Fundamental frequency (MHz) | 99% bandwidth f_1 (MHz) | 99% bandwidth f_2 (MHz) | Measured bandwidth (MHz) | Limit (MHz) |
|-----------------------------|---------------------------|---------------------------|--------------------------|-------------|
| 926.225 | 926.1848 | 926.2586 | 0.0738 | 4.63 |
| 925.400 | 925.3604 | 925.4330 | 0.0726 | 4.63 |

Limit according to RSS 210, Annex 1, section A1.1.3:

The 99% bandwidth shall be no wider than 0.50% of the center frequency for devices operating above 900 MHz.

The requirements are **FULFILLED**.

Remarks: For detailed results, please see the test protocol below.

The Rhode & Schwarz analyzer which we used for this measurement calculates automatically

the 99 % emission bandwidth.

**FCC ID: KR582035100
IC ID: 7812D-82035100**


5.6.4 Test protocol

Emission bandwidth

RSS 210 Annex 1, section A1.1.3


The 99 % emission bandwidth was automatically calculated by the used Rhode & Schwarz analyzer.

SR1, 926.225 MHz:



FCC ID: KR582035100
IC ID: 7812D-82035100

SR2, 925.400 MHz:



FCC ID: KR582035100
IC ID: 7812D-82035100

5.7 Antenna application

5.7.1 Applicable standard

According to FCC Part 15C, Section 15.203(a):

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

5.7.2 Result

The EUT use an antenna which will be mounted on a roof of a vehicle or in a instrument panel of a vehicle. There are three different examples of the same antenna types of the car roof antennas and two different types of the long range antennas.

No other antenna than that furnished by the responsible party or external power amplifier can be applied by a customer.

The antenna of the EUT meets the requirement of FCC Part 15C, Section 15.203 and 15.204.

FCC ID: KR582035100
IC ID: 7812D-82035100

5.8 Receiver radiated emissions

For test instruments and accessories used see section 6 Part **SER1**, **SER2** and **SER3**.


5.8.1 Description of the test location

Test location: OATS 1
Test location: Anechoic chamber 2


Test distance: 3 m

5.8.2 Photo documentation of the test set-up

Car roof antenna:





FCC ID: KR582035100
IC ID: 7812D-82035100



Long range antenna without mounting bracket:



FCC ID: KR582035100
IC ID: 7812D-82035100



**FCC ID: KR582035100
IC ID: 7812D-82035100**

5.8.3 Applicable standard

According to FCC Part 15C, Section 15.109(a):

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 m shall not exceed the given limit.

5.8.4 Description of Measurement

The radiated emissions from the EUT are measured in the frequency range of 9 kHz to 1000 MHz using a tuned receiver and appropriate broadband linearly polarized antennas. In the frequency range above 1 GHz a spectrum analyser is used with appropriate linear polarized antennas. The setup of the EUT will be in accordance to ANSI C63.4. If the emission level in peak mode complies with the average limit then testing will be stopped and peak values of the EUT will be reported, otherwise, the emission will be measured in average mode again and reported. During the test, the EUT was set into continuous transmitting mode, modulated.

Instrument settings:

| | | |
|--------------------|------------|---------|
| 9 kHz – 150 kHz | RBW: | 200 Hz |
| 150 kHz - 30 MHz | RBW: | 9 kHz |
| 30 MHz – 1000 MHz: | RBW: | 120 kHz |
| 1000 MHz – 40 GHz | RBW = VBW: | 1 MHz |

5.8.5 Test result f < 1 GHz

| Frequency [kHz] | L: QP [dB μ V] | L: AV [dB μ V] | Bandwidth [kHz] | Correct. [dB] | L: QP [dB μ V/m] | L: AV [dB μ V/m] | Limit [dB μ V/m] | Delta [dB] |
|--------------------|-----------------------|-----------------------|--------------------|------------------|-------------------------|-------------------------|-------------------------|---------------|
| 536.8 | 24.1 | 19.7 | 9.0 | 20 | 44.1 | 39.7 | 73.0 | -33.3 |
| 1073.6 | 23.4 | 18.0 | 9.0 | 20 | 43.4 | 38.0 | 67.0 | -29.0 |
| 1342.0 | 21.6 | 15.9 | 9.0 | 20 | 41.6 | 35.9 | 65.0 | -29.1 |

| Frequency [MHz] | L: QP [dB μ V] | Correct. [dB] | L: QP [dB μ V/m] | Limit [dB μ V/m] | Delta [dB] |
|--------------------|-----------------------|------------------|-------------------------|-------------------------|---------------|
| 33.78 | 3.7 | 13.4 | 17.1 | 40.0 | -22.9 |
| 118.54 | 9.3 | 12.9 | 22.2 | 43.5 | -21.3 |
| 517.43 | 4.8 | 21.9 | 26.7 | 46.0 | -19.3 |

In both frequency ranges, regardless of the antenna type, only ambient noises could be detected.

**FCC ID: KR582035100
IC ID: 7812D-82035100**

5.8.6 Test result f > 1 GHz

Rx mode

| Frequency (GHz) | L: PK (dB μ V) | L: AV (dB μ V) | Bandwidth (kHz) | Correct. (dB) | L: PK dB(μ V/m) | L: AV dB(μ V/m) | Limit AV dB(μ V/m) | Delta (dB) |
|-----------------|--------------------|--------------------|-----------------|---------------|----------------------|----------------------|-------------------------|------------|
| 3761.0 | 26.2 | | 1000 | 3.3 | 29.5 | | 54.0 | -24.5 |
| 8536.0 | 23.2 | | 1000 | 7.5 | 30.7 | | 54.0 | -23.3 |
| | | | | | | | | |

In the frequency range from 1 GHz up to 10 GHz only ambient noises could be detected.

In the frequency ranges, regardless of the antenna type, only ambient noises could be detected.

Limit according to FCC Part 15 Subpart 15.209(a)

| Frequency (MHz) | Field strength of spurious emissions | | Measurement distance (meters) |
|-----------------|--------------------------------------|-----------------|-------------------------------|
| | (μ V/m) | dB (μ V/m) | |
| 0.009-0.490 | 2400/F(kHz) | -- | 300 |
| 0.490-1.705 | 24000/F (kHz) | -- | 30 |
| 1.705-30.0 | 30 | 29.5 | 30 |

Limit according to FCC part, Section 15.109(a):

| Frequency (MHz) | Limit (μ V/m) | Limit dB(μ V/m) |
|-----------------|--------------------|----------------------|
| 30 - 88 | 100 | 40 |
| 88 - 216 | 150 | 43.5 |
| 216 - 960 | 200 | 46 |
| Above 960 | 500 | 54 |

The requirements are **FULFILLED**.

Remarks: The measurement was performed up to the 10th harmonic (10 GHz).

FCC ID: KR582035100
IC ID: 7812D-82035100

6 USED TEST EQUIPMENT AND ACCESSORIES

All test instruments used are calibrated and verified regularly. The calibration history is available on request.

| Test ID | Model Type | Equipment No. | Next Calib. | Last Calib. | Next Verif. | Last Verif. |
|----------------|------------------------|----------------------|--------------------|--------------------|--------------------|--------------------|
| CPR 2 | ESVS 30 | 02-02/03-05-006 | 03/07/2015 | 03/07/2014 | | |
| | VULB 9168 | 02-02/24-05-005 | 08/04/2015 | 08/04/2014 | 04/03/2015 | 04/09/2014 |
| | S10162-B | 02-02/50-05-031 | | | | |
| | NW-2000-NB | 02-02/50-05-113 | | | | |
| | KK-EF393/U-16N-21N20 m | 02-02/50-12-018 | | | | |
| MB | FSP 30 | 02-02/11-05-001 | 20/10/2015 | 20/10/2014 | | |
| | METRA HIT World | 02-02/32-10-001 | 21/08/2015 | 21/08/2014 | | |
| | VLP-1405 PRO | 02-02/50-10-014 | | | | |
| SER 1 | FMZB 1516 | 01-02/24-01-018 | | | 13/02/2015 | 13/02/2014 |
| | ESR 7 | 02-02/03-13-001 | 03/06/2015 | 03/06/2014 | | |
| | S10162-B | 02-02/50-05-031 | | | | |
| | KK-EF393-21N-16 | 02-02/50-05-033 | | | | |
| | NW-2000-NB | 02-02/50-05-113 | | | | |
| SER 2 | ESVS 30 | 02-02/03-05-006 | 03/07/2015 | 03/07/2014 | | |
| | VULB 9168 | 02-02/24-05-005 | 08/04/2015 | 08/04/2014 | 04/03/2015 | 04/09/2014 |
| | S10162-B | 02-02/50-05-031 | | | | |
| | NW-2000-NB | 02-02/50-05-113 | | | | |
| | KK-EF393/U-16N-21N20 m | 02-02/50-12-018 | | | | |
| SER 3 | FSP 30 | 02-02/11-05-001 | 20/10/2015 | 20/10/2014 | | |
| | AFS5-12001800-18-10P-6 | 02-02/17-06-002 | | | | |
| | AFS4-01000400-10-10P-4 | 02-02/17-13-002 | | | | |
| | AMF-4F-04001200-15-10P | 02-02/17-13-003 | | | | |
| | 3117 | 02-02/24-05-009 | 07/05/2015 | 07/05/2014 | | |
| | Sucoflex N-2000-SMA | 02-02/50-05-075 | | | | |
| | SF104/11N/11N/1500MM | 02-02/50-13-015 | | | | |