

FCC LISTED, REGISTRATION
NUMBER: 720267

Informe de ensayo nº:
Test report No:

IC LISTED REGISTRATION
NUMBER IC 4621A-1

NIE: 46341RRF.003

Test report

USA FCC Part 15.231, 15.209

CANADA RSS-210, RSS-Gen

Radio Frequency Devices. Periodic operation in the band 40.66-40.70 MHz and above 70 MHz.

Licence-Exempt Radio Apparatus (All Frequency Bands): Category I Equipment.
General Requirements and Information for the Certification of Radio Apparatus.

Identificación del objeto ensayado..... Identification of item tested	Radio frequency transmitter used in vehicle locking/unlocking systems
Marca Trademark	Continental
Modelo y/o referencia tipo Model and /or type reference	TXN1
Other identification of the product	FCC ID: KR5TXN1 IC: 7812D-TXN1
Final HW version	---
Final SW version	---
Características Features	Immobilizer transponder functionality, Remote keyless functionality, Passive key functionality
Fabricante Manufacturer	Continental Automotive GmbH Siemensstr. 12, 93055 Regensburg, Germany.
Método de ensayo solicitado, norma..... Test method requested, standard	USA FCC Part 15.231 10-1-14 Edition: Periodic operation in the band 40.66-40.70 MHz and above 70 MHz. USA FCC Part 15.209 10-1-14 Edition: Radiated emission limits; general requirements. CANADA RSS-210 Issue 8 (December 2010). CANADA RSS-Gen Issue 4 (November 2014). ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Resultado..... Summary	IN COMPLIANCE
Aprobado por (nombre / cargo y firma) Approved by (name / position & signature)	A. Llamas / RF Lab. Manager
Fecha de realización Date of issue	2015-12-14
Formato de informe No. Report template No	FDT08_17

Index

Competences and guarantees.....	3
General conditions.....	3
Uncertainty	3
Usage of samples.....	3
Test sample description	4
Identification of the client	4
Testing period.....	4
Environmental conditions.....	5
Remarks and comments.....	6
Testing verdicts	7
Appendix A – Test result.....	8

Competences and guarantees

AT4 wireless is a laboratory with a measurement facility in compliance with the requirements of Section 2.948 of the FCC rules and has been added to the list of facilities whose measurements data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Registration Number: 720267.

AT4 wireless is a laboratory with a measurement site in compliance with the requirements of RSS 212, Issue 1 (Provisional) and has been added to the list of filed sites of the Canadian Certification and Engineering Bureau. Reference File Number: IC 4621A-1.

In order to assure the traceability to other national and international laboratories, AT4 wireless has a calibration and maintenance program for its measurement equipment.

AT4 wireless guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at AT4 wireless at the time of performance of the test.

AT4 wireless is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of AT4 wireless.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of AT4 wireless.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of AT4 wireless and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the AT4 wireless internal document PODT000.

Usage of samples

Samples undergoing test have been selected by: **the client**

Sample M/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
46341B/009	Remote control car key with antenna connector	TXN1	---	2015-11-24

1. Sample M/01 has undergone following test(s) in appendix A:
Section 15.231 Subclause (c) / RSS-210 A1.1.3: 20 dB Emission Bandwidth and Occupied Bandwidth.

Sample M/02 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
46341B/002	Remote control car key with integral antenna	TXN1	---	2015-11-17

1. Sample M/02 has undergone following test(s) in appendix A:
Section 15.231 Subclause (b) / 15.209.: Field strength and Emission limitations radiated (Transmitter).

Sample M/03 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
46341B/001	Remote control car key with integral antenna	TXN1	---	2015-11-17

1. Sample M/03 has undergone following test(s) in appendix A:
Section 15.231 Subclause (a) (1) / RSS-210 A1.1.1: Transmitter deactivation.

Test sample description

The test sample consists of a radio frequency transmitter used for vehicle access.

Features:

- Remote control function by user activation (button press). The commands are transmitted with radio frequency (433,92 MHz).
- Alternatively, passive key operation, where no user action on the key side is required. In this case, the trigger is delivered by the vehicle via a low frequency (125 kHz) data telegram.
- Immobilizer function: In this mode, the key is operating as an immobilizer transponder, the communication is done via a "contactless interface" depending on a magnetic coupling at 125 kHz. The key is the passive side of the link and there is no 125 kHz transmission from it involved.

Identification of the client

Continental Automotive GmbH
Siemensstr. 12, 93055 Regensburg, Germany.

Testing period

The performed test started on 2015-11-24 and finished on 2015-11-25.

The tests have been performed at AT4 wireless.

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 1 Ω

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 1 Ω
Normal site attenuation (NSA)	< ±4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz)
Field homogeneity	More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz).

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 35 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 1 Ω

Remarks and comments

1: Used instrumentation:

Conducted Measurements

		Last Cal. date	Cal. due date
1.	Spectrum Analyzer Agilent E4440A	2014/05	2016/05
2.	DC power supply R&S NGPE 40/40	2014/11	2017/11

Radiated Measurements

		Last Cal. date	Cal. due date
1.	Semianechoic Absorber Lined Chamber ETS FACT3 200STP	N.A.	N.A.
2.	BiconicalLog antenna ETS LINDGREN 3142E	2014/03	2017/03
3.	Multi Device Controller EMCO 2090	N.A.	N.A.
4.	Double-ridge Guide Horn antenna 1-18 GHz SCHWARZBECK BBHA 9120 D	2013/11	2016/11
5.	EMI Test Receiver R&S ESU 40	2014/02	2016/02
6.	EMI Test Receiver R&S ESU 26	2015/11	2017/11
7.	RF pre-amplifier 10 MHz-6 GHz SCHWARZBECK BBV9743	2015/03	2016/03
8.	RF pre-amplifier 1-18 GHz Bonn Elektronik BLMA 0118-3A	2015/05	2016/05

Testing verdicts

Not applicable	N/A
Pass	P
Fail	F
Not measured	N/M

FCC PART 15 PARAGRAPH / RSS-210		VERDICT			
		NA	P	F	NM
Section 15.231 Subclause (a) (1) / RSS-210 A1.1.1.	Transmitter deactivation		P		
Section 15.231 Subclause (c) / RSS-210 A1.1.3.	Bandwidth		P		
Section 15.231 Subclause (b) / 15.209 / RSS-210 A1.1.2.	Field strength and Emission limitations radiated (Transmitter)		P		

Appendix A – Test result

INDEX

TEST CONDITIONS.....	10
Section 15.231 Subclause (a) (1) / RSS-210 A1.1.1. Transmitter deactivation.	12
Section 15.231 Subclause (c) / RSS-210 A1.1.3. Bandwidth	13
Occupied Bandwidth.....	14
Section 15.231 Subclause (b)/15.209 / RSS-210 A1.1.2.. Field strength and Emission limitations radiated (Transmitter)	15

TEST CONDITIONS

Power supply (V):

$$V_{\text{nominal}} = 3.0 \text{ Vdc}$$

Type of power supply = Lithium battery cell

Type of antenna = Integral antenna

TEST FREQUENCIES:

The equipment transmits at the nominal frequency of 433.92 MHz.

CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is directly connected to the spectrum analyzer.



RADIATED MEASUREMENTS

The equipment under test was scanned for spurious emissions in the frequency range 30 to 5000 MHz.


All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-5 GHz (1 GHz-18 GHz Double ridge horn antenna).

For radiated emissions in the range 1 GHz-5 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance. The sample is prepared so that transmits continuously when the batteries are connected


The equipment under test was set up on a non-conductive (wooden) platform one meter above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

Radiated measurements setup $f < 1$ GHz



Radiated measurements setup $f > 1$ GHz



Section 15.231 Subclause (a) (1) / RSS-210 A1.1.1. Transmitter deactivation.


SPECIFICATION

A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

RESULTS

The equipment can only operate in manual mode.

The transmission is activated by pressing a button and ceases after releasing it in less than 5 seconds (see next plot).



Verdict: Pass

Section 15.231 Subclause (c) / RSS-210 A1.1.3. Bandwidth

SPECIFICATION


FCC 15.231: The bandwidth of the emission shall be no wider than 0.25 % of the centre frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

RESULTS (see next plots)

Nominal centre frequency = 433.92 MHz

Limit of spectrum bandwidth = 0.25 % of 433.92 MHz = 1084.80 kHz

Measured 20 dB Bandwidth (kHz)	200.0
Measurement uncertainty (kHz)	<±2.96




Verdict: PASS

SPECIFICATION

RESULTS (see next plots).

Limit of spectrum bandwidth = 0.25 % of 433.92 MHz = 1084.80 kHz

99% bandwidth (kHz)	199.273
-26 dBc bandwidth (kHz)	276.632
Measurement uncertainty (kHz)	<±1.50



Section 15.231 Subclause (b)/15.209 / RSS-210 A1.1.2. Field strength and Emission limitations radiated (Transmitter)

SPECIFICATION

The field strength of emissions from intentional radiators shall not exceed the following:

Fundamental frequency (MHz)	Field strength of fundamental ($\mu\text{V/m}$)	Field strength of spurious emissions ($\mu\text{V/m}$)
40.66 – 40.70	2,250	225
70 – 130	1,250	125
130 - 174	1,250 to 3,750 **	125 to 375 **
174 - 260	3,750	375
260 - 470	3,750 to 12,500 **	375 to 1,250 **
Above 470	12,500	1,250

** : Linear Interpolations. The maximum permitted unwanted emission level is 20dB below the maximum permitted fundamental level.

Spurious emissions shall be attenuated to the limits shown in the above table or to the general limits shown in Section 15.209/RSS-Gen, whichever limit permits a higher field strength.


For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RESULTS:

The field strength is calculated by adding correction factor to the measured level from the spectrum analyser. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

The transmission is pulsed so the average values of transmitter fundamental and spurious emissions are calculated from the measured peak values using the duty cycle correction factor δ as indicated in standard ANSI C63.10-2013.

Computation of duty-cycle correction factor



Pulse train period: 84.68 ms
Number of pulses within 100 ms: 2
Pulse duration: 8.408 ms

Duty-cycle correction factor calculation.

Sub-pulse	Duration (ms)	Number of pulses	Sub-pulse "On Time" (ms)
1	8.408	2	16.816
		TOTAL ON TIME:	16.816

Duty cycle correction factor $\delta = 16.816 / 100 = 0.1682$

$\delta = 20 \log (0.1682) = -15.48 \text{ dB}$

Frequency range 30 MHz-1000 MHz (see next plots)

Frequency (MHz)	Polarization	Detector	Emission Level (µV/m)	Limits (µV/m) 15.231 (b) / 15.209
433.92 (Fundamental)	V	Peak	13,381.35	109,972.5 / ---
867.789	V	Peak	29.41	10,997.25 / 2000

Calculation for average level

Spurious frequency (MHz)	Emission Level (dBµV/m) Peak	Duty-cycle correction factor δ (dB)	Corrected Emission Level (dBµV/m) Average	Limits (µV/m) 15.231 (b) / 15.209
433.92 (Fundamental)	82.53	-15.48	67.05	10,997.25 (80.82 dBµV/m) / ---
867.789	29.37	-15.48	13.89	1,099.725 (60.82 dBµV/m) / 200 (46.02 dBµV/m)

Measurement uncertainty (dB): ± 3.88 dB.

Frequency range 1 GHz-5 GHz (see next plots)

All peaks are more than 20 dB below the limit.

Highest spurious levels.

Frequency (GHz)	Polarization	Detector	Emission Level (µV/m)	Limits (µV/m) 15.231 (b) / 15.209
4.3396	V	Peak	202.07	10,997.25 / 5,000
4.7732	V	Peak	332.66	10,997.25 / 5,000


Calculation for average level

Spurious frequency (GHz)	Emission Level (dBµV/m) Peak	Duty-cycle correction factor δ (dB)	Corrected Emission Level (dBµV/m) Average	Limits (µV/m) 15.231 (b) / 15.209
4.3396	46.11	-15.48	30.63	1,099.725 (60.82 dBµV/m) / 500 (54 dBµV/m)
4.7732	50.44	-15.48	34.96	1,099.725 (60.82 dBµV/m) / 500 (54 dBµV/m)

Measurement uncertainty (dB): ± 4.69 dB.

Verdict: PASS.

FREQUENCY RANGE 30 MHz-1000 MHz



Note: The carrier frequency (fundamental) was attenuated using a notch filter.

SWT 45 ms

```
* Att 0 dB
```

