

-SPEC TABLE

LAMP WATT (W)	20 W	23 W	26 W	32 W
INPUT VOLT (V)	110 V 50 / 60 Hz			
INPUT CURRENT (A)	0.18 A	0.20 A	0.21 A	0.22 A
LUMINOUS FLUX(Lm)	1200	1500	1750	2250
COLOR TEMPERATURE (k)	6500 K / 3000 K			
LENGTH (m/m)	126	130	137	142
DIAMETER ()	50			
WEIGHT(G)	75	80	85	90
SOK	E26 / B22D			

- Warning

- Do not cover the paper and towel on the lamp.
- Do not put down flammable object beside of the lamp.
- Do not use dimmable lighting fixture.
- Do not contact with A.C.
- Turn off the switch during setting, separating and cleaning.
- Do not use making waterdrop.
- Do not hold too strong, schretch and crash.
- Do not touch upon turning off or turning on.
- Assemble the lamp with socket completely.

-Caution is use

- Do not separate and retrofit.
- Do not apply with enclosed fixture.
- Frequent on/off switch caused short lifetime.
- Do not use over 40 .

-Guarantee

- Lifetime : 10 times of incandescent lamp.
- Energy saving : 80 % than incandescent lamp.
- Replacement if any defects when buying.

FCC NOTICE

THIS PRODUCT MAY CAUSE INTERFERENCE TO RADIO EQUIPMENT AND SHOULD NOT BE
INSTALLED NEAR MARITIME SAFETY COMMUNICATIONS EQUIPMENT OR OTHER
CRITICAL NAVIGATION OR COMMUNICATION EQUIPMENT OPERATING BETWEEN .45-30
MHZ.