

TEST REPORT

Report No.: 18111043HKG-003

Lionel L.L.C.

Application For Certification
(Class II Permissive Change)

FCC ID: LIV-RTPGRXV2

Transceiver

Prepared and Checked by:

Signed On File

Lee Yee Yat, Adrian
Assistant Engineer

Approved by:

Wong Kwok Yeung, Kenneth
Senior Lead Engineer
Date: January 16, 2019

TEST REPORT

GENERAL INFORMATION

Grantee:	Lionel L.L.C.
Grantee Address:	6301 Performance Drive, Concord, North Carolina 28027, United States
Contact Person:	James Rohde
Tel:	586-421-9022
Fax:	704-455-8940
e-mail:	jrohde@lionel.com
Manufacturer:	Goldlok Holdings (GuangDong) Co., Ltd.
Manufacturer Address:	No. 168, Dongpian Tangbianli, Tangbian Village, Chiwei Street, Puning City, Guang Dong Province, China
Brand Name:	Lionel
Model:	711792
Additional Model:	711960
Type of EUT:	Transceiver
Description of EUT:	Hogwarts Express Ready To Play Train Set
Serial Number:	N/A
FCC ID:	LIV-RTPGRXV2
Date of Sample Submitted:	November 23, 2018
Date of Test:	November 23, 2018 to November 27, 2018
Report No.:	18111043HKG-003
Report Date:	January 16, 2019
Environmental Conditions:	Temperature: +10 to 40°C Humidity: 10 to 90%
Conclusion:	Test was conducted by client submitted sample. The submitted sample as received complied with the 47 CFR Part 15 Certification.

TEST REPORT**SUMMARY OF TEST RESULT**

Test Specification	Reference	Results
Radiated Emission	15.249, 15.209	Pass
Radiated Emission on the Bandedge		
Radiated Emission in Restricted Bands	15.205	Pass

The equipment under test is found to be complying with the following standards:

FCC Part 15, October 1, 2017 Edition

Note:

1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

TEST REPORT**TABLE OF CONTENTS**

1.0	GENERAL DESCRIPTION	5
1.1	Product Description	5
1.2	Purpose of Change	5
1.3	Test Methodology	5
1.4	Test Facility	5
2.0	SYSTEM TEST CONFIGURATION	6
2.1	Justification	6
2.2	EUT Exercising Software	6
2.3	Special Accessories	6
2.4	Measurement Uncertainty	6
2.5	Support Equipment List and Description	6
3.0	EMISSION RESULTS	7
3.1	Field Strength Calculation	7
3.2	Radiated Emission Configuration Photograph	8
3.3	Radiated Emission Data	8
4.0	EQUIPMENT PHOTOGRAPHS	12
5.0	PRODUCT LABELLING	12
6.0	TECHNICAL SPECIFICATIONS	12
7.0	INSTRUCTION MANUAL	12
8.0	MISCELLANEOUS INFORMATION	13
8.1	Radiated Emission on the Bandedge	13
8.2	Emissions Test Procedures	13
9.0	EQUIPMENT LIST	16

TEST REPORT

1.0 GENERAL DESCRIPTION

1.1 Product Description

The Equipment Under Test (EUT) is a 2.4GHz Transceiver (Train) for a Train Set. The EUT is powered by 6 x 1.5V C batteries. The 2.4GHz module is operating at the frequencies (2413; 2435; 2436; 2438; 2439; 2440; 2441; 2442; 2443; 2444; 2445; 2468; 2469; 2470; and 2471) MHz. After switching on the EUT, the corresponding Transceiver (Controller) can control the EUT (Train) moving forward and backward.

The Model: 711960 is the same as the Model: 711792 in hardware aspect as declared by client. The models are different in model number and package only as declared by client.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Purpose of Change

The purpose of change is saved with filename: product change.pdf

1.3 Test Methodology

Radiated emission measurements was performed according to the procedures in ANSI C63.10 (2013). All radiated measurements were performed in an 3m Chamber. Preliminary scans were performed in the 3m Chamber only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

1.4 Test Facility

The 3m Chamber used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

TEST REPORT

2.0 SYSTEM TEST CONFIGURATION

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The device was powered by new DC 9.0V (6 x 1.5V "C" Batteries).

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance - Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

2.5 Support Equipment List and Description

N/A.

TEST REPORT

3.0 EMISSION RESULTS

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where FS = Field Strength in $\text{dB}\mu\text{V}/\text{m}$

RA = Receiver Amplitude (including preamplifier) in $\text{dB}\mu\text{V}$

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where FS = Field Strength in $\text{dB}\mu\text{V}/\text{m}$

RR = RA - AG - AV in $\text{dB}\mu\text{V}$

LF = CF + AF in dB

Assume a receiver reading of 52.0 $\text{dB}\mu\text{V}$ is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 $\text{dB}\mu\text{V}/\text{m}$. This value in $\text{dB}\mu\text{V}/\text{m}$ was converted to its corresponding level in $\mu\text{V}/\text{m}$.

$$RA = 52.0 \text{ dB}\mu\text{V}/\text{m}$$

$$AF = 7.4 \text{ dB}$$

$$RR = 18.0 \text{ dB}\mu\text{V}$$

$$CF = 1.6 \text{ dB}$$

$$LF = 9.0 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$AV = 5.0 \text{ dB}$$

$$FS = RR + LF$$

$$FS = 18 + 9 = 27 \text{ dB}\mu\text{V}/\text{m}$$

$$\text{Level in } \mu\text{V}/\text{m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V}/\text{m})/20] = 22.4 \mu\text{V}/\text{m}$$

TEST REPORT**3.2 Radiated Emission Configuration Photograph**

The worst case in radiated emission was found at 2483.5 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 4.9 dB

TEST REPORT

RADIATED EMISSIONS

Model: 711792

Date of Test: November 27, 2018

Worst-Case Operating Mode: Transmitting

Table 1
Pursuant to FCC Part 15 Section 15.249 Requirement

Lowest Channel

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	2413.000	61.8	33	29.4	58.2	94.0	-35.8
H	2400.000	52.2	33	29.4	48.6	54.0	-5.4
H	4826.000	28.4	33	34.9	30.3	54.0	-23.7
H	7239.000	27.7	33	37.9	32.6	54.0	-21.4
V	9652.000	28.8	33	40.4	36.2	54.0	-17.8
V	12065.000	27.3	33	40.5	34.8	54.0	-19.2
V	14478.000	28.3	33	40.0	35.3	54.0	-18.7

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	2413.000	95.0	33	29.4	91.4	114.0	-22.6
H	2400.000	68.7	33	29.4	65.1	74.0	-8.9
H	4826.000	46.7	33	34.9	48.6	74.0	-25.4
H	7239.000	46.4	33	37.9	51.3	74.0	-22.7
V	9652.000	46.4	33	40.4	53.8	74.0	-20.2
V	12065.000	44.7	33	40.5	52.2	74.0	-21.8
V	14478.000	45.9	33	40.0	52.9	74.0	-21.1

NOTES:

1. Peak Detector Data unless otherwise stated.
2. Average detector is used according to ANSI C63.10.
3. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
4. Negative sign in the column shows value below limit.
5. Horn antenna is used for the emission over 1000MHz.
6. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.

TEST REPORT

Model: 711792

Date of Test: November 27, 2018

Worst-Case Operating Mode: Transmitting

Table 2
Pursuant to FCC Part 15 Section 15.249 Requirement

Middle Channel

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	2443.000	61.4	33	29.4	57.8	94.0	-36.2
H	4886.000	28.5	33	34.9	30.4	54.0	-23.6
H	7329.000	27.9	33	37.9	32.8	54.0	-21.2
H	9772.000	28.7	33	40.4	36.1	54.0	-17.9
V	12215.000	27.3	33	40.5	34.8	54.0	-19.2
V	14658.000	29.7	33	38.4	35.1	54.0	-18.9

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	2443.000	94.6	33	29.4	91.0	114.0	-23.0
H	4886.000	46.7	33	34.9	48.6	74.0	-25.4
H	7329.000	46.6	33	37.9	51.5	74.0	-22.5
H	9772.000	46.2	33	40.4	53.6	74.0	-20.4
V	12215.000	44.8	33	40.5	52.3	74.0	-21.7
V	14658.000	47.4	33	38.4	52.8	74.0	-21.2

NOTES:

1. Peak Detector Data unless otherwise stated.
2. Average detector is used according to ANSI C63.10.
3. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
4. Negative sign in the column shows value below limit.
5. Horn antenna is used for the emission over 1000MHz.
6. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.

TEST REPORT

Model: 711792

Date of Test: November 27, 2018

Worst-Case Operating Mode: Transmitting

Table 3
Pursuant to FCC Part 15 Section 15.249 Requirement

Highest Channel

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	2471.000	61.7	33	29.4	58.1	94.0	-35.9
H	2483.500	52.7	33	29.4	49.1	54.0	-4.9
H	4942.000	28.7	33	34.9	30.6	54.0	-23.4
H	7413.000	28.0	33	37.9	32.9	54.0	-21.1
H	9884.000	28.6	33	40.4	36.0	54.0	-18.0
V	12355.000	27.1	33	40.5	34.6	54.0	-19.4
V	14826.000	30.1	33	38.4	35.5	54.0	-18.5

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	2471.000	94.9	33	29.4	91.3	114.0	-22.7
H	2483.500	68.3	33	29.4	64.7	74.0	-9.3
H	4942.000	46.9	33	34.9	48.8	74.0	-25.2
H	7413.000	46.7	33	37.9	51.6	74.0	-22.4
H	9884.000	46.3	33	40.4	53.7	74.0	-20.3
V	12355.000	44.6	33	40.5	52.1	74.0	-21.9
V	14826.000	47.7	33	38.4	53.1	74.0	-20.9

NOTES: 1. Peak Detector Data unless otherwise stated.

2. Average detector is used according to ANSI C63.10.
3. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
4. Negative sign in the column shows value below limit.
5. Horn antenna is used for the emission over 1000MHz.
6. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.

TEST REPORT

4.0 EQUIPMENT PHOTOGRAPHS

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

5.0 PRODUCT LABELLING

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

6.0 TECHNICAL SPECIFICATIONS

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

7.0 INSTRUCTION MANUAL

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

TEST REPORT**8.0 MISCELLANEOUS INFORMATION**

The miscellaneous information includes details of the test procedure and measured bandwidth.

8.1 Radiated Emission on the Bandedge

The test data of bandedge emissions were shown on the above radiated emissions table 1 & table 3 respectively.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

8.2 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately 0.8m in height above the ground plane for emission measurement at or below 1GHz and 1.5m in height above the ground plane for emission measurement above 1GHz. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

TEST REPORT

8.2 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.10 (2013).


The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 3 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.


TEST REPORT

8.2.1 Radiated Emission Test Setup

The figure below shows the test setup, which is utilized to make these measurements.



Test setup of radiated emissions up to 1GHz



Test setup of radiated emissions above 1GHz

TEST REPORT

9.0 EQUIPMENT LIST

1) Radiated Emissions Test

Equipment	EMI Test Receiver	Log Periodic Antenna	Biconical Antenna
Registration No.	EW-2666	EW-0447	EW-0571
Manufacturer	ROHDESCHWARZ	EMCO	EMCO
Model No.	ESCI7	3146	3104C
Calibration Date	August 28, 2018	January 17, 2018	February 27, 2018
Calibration Due Date	August 28, 2019	July 17, 2019	August 27, 2019

Equipment	Log Periodic Antenna	Biconical Antenna	BiConiLog Antenna
Registration No.	EW-1042	EW-2512	EW-3061
Manufacturer	EMCO	EMCO	EMCO
Model No.	3148	3104C	3142E
Calibration Date	June 19, 2017	August 06, 2018	November 02, 2017
Calibration Due Date	December 19, 2018	February 06, 2020	May 02, 2019

Equipment	12m Double Shield RF Cable	12 metre RF Cable 40GHz	Double Ridged Guide Antenna
Registration No.	EW-1852	EW-2774	EW-1133
Manufacturer	RADIALL	GREATBILLION	EMCO
Model No.	N(m)-RG142 - N(m)	SMA m-m ra 12m 40G outdoor	3115
Calibration Date	January 19, 2018	January 19, 2018	November 29, 2018
Calibration Due Date	January 19, 2019	January 19, 2019	November 29, 2020

Equipment	Notch Filter (cutoff frequency 2.4GHz to 2.5GHz)	RF Pre-amplifier 3 pcs (9kHz to 40GHz)	Solid State Low Noise Preamplifier Assembly (1 - 18)GHz
Registration No.	EW-2213	EW-3006	EW-3229
Manufacturer	MICROTRONICS	SCHWARZBECK	BONN ELEKTRO
Model No.	BRM50701-02	BBV 9718	BLMA 0118-5G
Calibration Date	May 24, 2018	April 26, 2018	January 30, 2018
Calibration Due Date	May 24, 2019	April 26, 2019	January 30, 2019

Equipment	Spectrum Analyzer
Registration No.	EW-3016
Manufacturer	ROHDESCHWARZ
Model No.	FSV40
Calibration Date	October 16, 2018
Calibration Due Date	October 16, 2019

2) Bandedge Measurement

Equipment	Spectrum Analyzer
Registration No.	EW-2425
Manufacturer	R&S
Model No.	FSP3
Calibration Date	August 17, 2018
Calibration Due Date	August 17, 2019