

# FCC TEST REPORT

**REPORT NO.:** F90042501

**MODEL NO.:** N0902

**RECEIVED:** April 25, 2001

**TESTED:** May 5, 2001

**APPLICANT:** NPG Display LTD., Taiwan Branch

**ADDRESS:** 2FL-1, No. 8, Tunhua N. Rd., Taipei,  
Taiwan, R.O.C.

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** 47 14th Lin, Chiapau Tsun, Linko, Taipei,  
Taiwan, R.O.C.

This test report consists of 23 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by NVLAP or any U.S. government agencies. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



0528



Lab Code: 200102-0

## Table of Contents

1	CERTIFICATION.....	3
2	SUMMARY OF TEST RESULTS.....	4
3	GENERAL INFORMATION .....	5
3.1	GENERAL DESCRIPTION OF EUT .....	5
3.2	DESCRIPTION OF TEST MODES .....	5
3.3	DESCRIPTION OF SUPPORT UNITS.....	6
4	EMISSION TEST .....	7
4.1	CONDUCTED EMISSION MEASUREMENT .....	7
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	7
4.1.2	TEST INSTRUMENTS .....	7
4.1.3	TEST PROCEDURE .....	8
4.1.4	DEVIATION FROM TEST STANDARD .....	8
4.1.5	TEST SETUP .....	8
4.1.6	EUT OPERATING CONDITIONS.....	9
4.1.7	TEST RESULTS (A) .....	10
4.1.8	TEST RESULTS (B) .....	12
4.2	RADIATED EMISSION MEASUREMENT .....	14
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT .....	14
4.2.2	TEST INSTRUMENTS .....	15
4.2.3	TEST PROCEDURE .....	15
4.2.4	DEVIATION FROM TEST STANDARD .....	16
4.2.5	TEST SETUP .....	16
4.2.6	EUT OPERATING CONDITIONS.....	16
4.2.7	TEST RESULTS (A) .....	17
4.2.8	TEST RESULTS (B) .....	19
5	PHOTOGRAPHS OF THE TEST CONFIGURATION .....	21
6	APPENDIX - INFORMATION ON THE TESTING LABORATORIES.....	23

## 1 CERTIFICATION

**PRODUCT:** 19" CRT COLOR MONITOR  
**BRAND NAME:** NEC  
**MODEL NO:** N0902  
**TEST ITEM:** ENGINEERING SAMPLE  
**APPLICANT:** NPG Display LTD., Taiwan Branch  
**STANDARDS:** FCC Part 15, Subpart B, Class B  
CISPR 22: 1997, Class B  
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility on May 5, 2001. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

**TESTED BY:** Bill Chang, **DATE:** 5/17/2001  
( Bill Chang )

**CHECKED BY:** Yemmy Soong, **DATE:** 5/17/2001  
( Yemmy Soong )

**APPROVED BY:** Paul Yang, **DATE:** 5/17/2001  
( Paul Yang, Manager )

## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

Standard	Test Type	Result	Remarks
FCC Part 15, Subpart B, CISPR 22: 1997, Class B	Conducted Test	PASS	Meets Class B Limit Minimum passing margin is -2.9 dB at 22.800 MHz
	Radiated Test	PASS	Meets Class B Limit Minimum passing margin is -3.1 dB at 57.29 MHz

**NOTE:** For conducted emission test, the test limit used is according to FCC Part 15.107. In this part, conducted emission test for telecom port is not mentioned and therefore this item is not tested.

### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	19" CRT COLOR MONITOR
<b>MODEL NO.</b>	N0902
<b>POWER SUPPLY</b>	Switching Power Cord: Non-shielded, 3 pin, AC (1.8m)
<b>DATA CABLE</b>	Shielded (1.8m) with a ferrite core

**NOTE:** The EUT is a 19" CRT color monitor with resolution up to 1600x1200.

The EUT has two types of CRT: SAMSUNG and MITSUBISHI. Both were tested separately and their data are recorded in this report.

For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

#### 3.2 DESCRIPTION OF TEST MODES

The EUT was pre-tested under the following resolution & horizontal synchronization speed mode:

- 1600x1200 mode (85Hz/106kHz),
- 1280x1024 mode (85Hz/91kHz),
- 640x480 mode (60Hz/31kHz)

The worst emission levels were found under **1600x1200 (85Hz/106kHz)**. Therefore for the final test, the EUT was tested with the following modes:

**MODE 1 – SAMSUNG CRT**

**MODE 2 – MITSUBISHI CRT**

### 3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	PERSONAL COMPUTER	NTI	PI I-450T	P201140	FCC DoC APPROVED
2	PRINTER	HP	2225C+	3208S05355	DSI6XU2225
3	MODEM	ACEEX	1414	980020502	IFAXDM1414
4	PS/2 KEYBOARD	FORWARD	FDA-104GA	FDKB8110124	F4ZDA-104G
5	MOUSE	LOGITECH	M-S43	LZE000703132	DZL211106
6	COLOR VGA CARD	CARDEX	CD-GX2A44T	GHF11905	ICUVGA-GW710

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core.
3	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.
4	1.5 m foil shielded wire, terminated with PS/2 connector via metallic frame, w/o core.
5	1.8 m foil shielded wire, terminated with PS2 connector via drain wire, w/o core.
6	NA

**NOTE:** All power cords of the above support units are non shielded (1.8m).

## 4 EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

**NOTES:** (1) The lower limit shall apply at the transition frequencies.

(2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

(3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS30	834115/016	Feb. 21, 2002
ROHDE & SCHWARZ Artificial Mains Network (For EUT)	ESH2-Z5	892107/003	July 11, 2001
ROHDE & SCHWARZ 4-wire ISN	ENY41	838119/028	Dec. 12, 2001
ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/018	Dec. 3, 2001
EMCO L.I.S.N. (For peripherals)	3825/2	9504-2359	July 11, 2001
Software	Cond-V2e	NA	NA
RF cable (JYEBAO)	RG-58A/U	Cable-C03.01	July 11, 2001
Terminator (For EMCO LISN)	NA	E1-01-300	Feb. 20, 2002
Terminator (For EMCO LISN)	NA	E1-01-301	Feb. 20, 2002
Shielded Room	Site 3	ADT-C03	NA
VCCI Site Registration No.	Site 3	C-274	NA

**NOTE:** 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


### 4.1.3 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported.

### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

### 4.1.5 TEST SETUP



**Note: 1. Support units were connected to second LISN.**

**2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes**

For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.





#### **4.1.6 EUT OPERATING CONDITIONS**


- a. Turn on the power of all equipment.
- b. PC runs a test program to enable all functions.
- c. PC reads and writes messages from FDD and HDD.
- d. PC sends "H" messages to monitor (EUT) and monitor displays "H" patterns on screen.
- e. PC sends "H" messages to modem.
- f. PC sends "H" messages to printer, and the printer prints them on paper.
- g. Repeat steps c-g.

#### 4.1.7 TEST RESULTS (A)

EUT	19" CRT COLOR MONITOR	MODEL NO.	N0902
MODE	1	6dB BANDWIDTH	10 kHz
INPUT POWER	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 55 % RH, 1050 hPa	TESTED BY: BILL CHANG	

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.197	0.20	46.24	-	46.44	-	63.74	53.74	-17.30	-
2	0.233	0.20	45.44	-	45.64	-	62.35	52.35	-16.71	-
3	0.955	0.29	29.53	-	29.82	-	56.00	46.00	-26.18	-
4	2.651	0.33	31.05	-	31.38	-	56.00	46.00	-24.62	-
5	8.067	0.54	32.40	-	32.94	-	60.00	50.00	-27.06	-
6	18.985	0.94	46.54	-	47.48	-	60.00	50.00	-12.52	-
7	22.800	1.11	49.56	45.99	50.67	47.10	60.00	50.00	-9.33	-2.90


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



<b>EUT</b>	19" CRT COLOR MONITOR	<b>MODEL NO.</b>	N0902
<b>MODE</b>	1	<b>6dB BANDWIDTH</b>	10 kHz
<b>INPUT POWER</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 55 % RH, 1050 hPa	<b>TESTED BY: BILL CHANG</b>	

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.159	0.16	51.92	-	52.08	-	65.54	55.54	-13.46	-
2	0.171	0.17	46.98	-	47.15	-	64.89	54.89	-17.74	-
3	0.289	0.20	40.22	-	40.42	-	60.55	50.55	-20.13	-
4	2.440	0.32	37.17	-	37.49	-	56.00	46.00	-18.51	-
5	4.774	0.41	34.60	-	35.01	-	56.00	46.00	-20.99	-
6	18.983	0.66	46.48	-	47.14	-	60.00	50.00	-12.86	-
7	23.013	0.76	49.48	46.02	50.24	46.78	60.00	50.00	-9.76	-3.22

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.




#### 4.1.8 TEST RESULTS (B)

<b>EUT</b>	19" CRT COLOR MONITOR	<b>MODEL NO.</b>	N0902
<b>MODE</b>	2	<b>6dB BANDWIDTH</b>	10 kHz
<b>INPUT POWER</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 55 % RH, 1050 hPa	<b>TESTED BY: BILL CHANG</b>	

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.176	0.18	41.82	-	42.00	-	64.67	54.67	-22.68	-
2	0.237	0.20	34.42	-	34.62	-	62.19	52.19	-27.57	-
3	0.548	0.22	39.65	-	39.87	-	56.00	46.00	-16.13	-
4	2.600	0.33	22.78	-	23.11	-	56.00	46.00	-32.89	-
5	5.872	0.46	23.38	-	23.84	-	60.00	50.00	-36.16	-
6	11.939	0.64	39.35	-	39.99	-	60.00	50.00	-20.01	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



<b>EUT</b>	19" CRT COLOR MONITOR	<b>MODEL NO.</b>	N0902
<b>MODE</b>	2	<b>6dB BANDWIDTH</b>	10 kHz
<b>INPUT POWER</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 55 % RH, 1050 hPa	<b>TESTED BY: BILL CHANG</b>	

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.150	0.15	55.97	48.88	56.12	49.03	66.00	56.00	-9.88	-6.97
2	0.193	0.19	48.22	-	48.41	-	63.91	53.91	-15.49	-
3	0.240	0.20	34.91	-	35.11	-	62.10	52.10	-26.99	-
4	0.550	0.22	39.93	-	40.15	-	56.00	46.00	-15.85	-
5	2.446	0.32	6.50	-	6.82	-	56.00	46.00	-49.18	-
6	9.304	0.49	2.96	-	3.45	-	60.00	50.00	-56.55	-
7	11.896	0.50	14.95	-	15.45	-	60.00	50.00	-44.55	-

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT FOR FREQUENCY BELOW 1000 MHz

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 10m)
	dBuV/m	dBuV/m
30 – 230	40	30
230 - 1000	47	37

### LIMIT OF RADIATED EMISSION OF FCC PART 15, SUBPART B FOR FREQUENCY ABOVE 1000 MHz

FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80.0	60.0	74.0	54.0

- Note:** (1) The lower limit shall apply at the transition frequencies.  
 (2) Emission level (dBuV/m) = 20 log Emission level (uV/m).  
 (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

## 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
HP Spectrum Analyzer	8590L	3544A00941	Nov. 29, 2001
HP Pre-Amplifier	8447D	2944A08312	Sept. 15, 2001
* HP Preamplifier	8449B	3008A01201	Dec. 13, 2001
* HP Preamplifier	8449B	3008A01292	Aug. 21, 2001
* R&S Receiver	ESVS10	844594/010	Oct. 2, 2001
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 23, 2001
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Jan. 25, 2002
* CHASE BILOG Antenna	CBL6111A	1500	Aug. 31, 2001
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	July 9, 2001
* EMCO Horn Antenna	3115	9312-4192	April 15, 2002
* EMCO Turn Table	1060-04	1196	NA
* EMCO Tower	1051	1264	NA
* Software	AS61D	NA	NA
* ANRITSU RF Switches	MP59B	M06089	Aug. 31, 2001
* TIMES RF cable	LMR-600	CABLE-ST1-01	Aug. 31, 2001
Open Field Test Site	Site 1	ADT-R01	Aug. 25, 2001
VCCI Site Registration No.	Site 1	R-236	NA

**NOTE:** 1. The measurement uncertainty is less than +/- 3.0dB, which is calculated as per the NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

3. "\*" = These equipment are used for the final measurement.

## 4.2.3 TEST PROCEDURE


- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10-meter open field site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi- peak method or average method as specified and then reported In Data sheet peak mode and QP mode.
- g. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the interference antenna and the detect function was set to Peak or Average.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.



## 4.2.7 TEST RESULTS (A)

<b>EUT</b>	19" CRT COLOR MONITOR	<b>MODEL NO.</b>	N0902
<b>MODE</b>	1	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>INPUT POWER</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Quasi-Peak, 120kHz
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 55 % RH, 1050 hPa	<b>TESTED BY: BILL CHANG</b>	

### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 10 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)
1	133.43	21.3 QP	30.00	-8.70	4.00H	211	8.94	11.19	1.13	0.00	-12.32
2	171.53	21.9 QP	30.00	-8.10	4.00H	60	12.01	8.62	1.31	0.00	-9.94
3	190.69	23.9 QP	30.00	-6.10	4.00H	245	14.36	8.19	1.37	0.00	-9.56
4	209.64	22.6 QP	30.00	-7.40	4.00H	304	12.38	8.82	1.43	0.00	-10.24
5	419.53	28.0 QP	37.00	-9.00	3.12H	74	9.71	16.04	2.25	0.00	-18.29
6	496.53	28.7 QP	37.00	-8.30	2.86H	347	8.83	17.29	2.58	0.00	-19.87
7	541.68	27.8 QP	37.00	-9.20	2.86H	356	5.73	19.32	2.75	0.00	-22.07
8	669.98	28.9 QP	37.00	-8.10	3.20H	208	5.41	20.33	3.16	0.00	-23.49

### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 10 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)
1	57.29	26.5 QP	30.00	-3.50	1.42V	148	19.58	6.21	0.74	0.00	-6.95
2	133.37	25.2 QP	30.00	-4.80	1.00V	54	12.90	11.19	1.13	0.00	-12.32
3	171.50	24.7 QP	30.00	-5.30	1.00V	219	14.74	8.62	1.31	0.00	-9.94
4	190.69	24.5 QP	30.00	-5.50	1.00V	169	14.97	8.19	1.37	0.00	-9.56
5	228.88	23.4 QP	30.00	-6.60	1.00V	124	11.85	10.02	1.52	0.00	-11.54
6	343.66	30.5 QP	37.00	-6.50	2.92V	78	14.89	13.62	1.97	0.00	-15.59
7	400.94	27.7 QP	37.00	-9.30	3.11V	295	9.67	15.85	2.18	0.00	-18.03
8	515.47	26.2 QP	37.00	-10.80	1.05V	148	5.46	18.08	2.65	0.00	-20.73

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
  2. Correction Factor(dB/m) = Pre-Amplifier Factor (dB) - Antenna Factor (dB/m) - Cable Factor (dB)
  3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
  4. The other emission levels were very low against the limit.
  5. Margin value = Emission level – Limit value.



<b>EUT</b>	19" CRT COLOR MONITOR	<b>MODEL NO.</b>	N0902
<b>MODE</b>	1	<b>FREQUENCY RANGE</b>	1000-2000 MHz
<b>INPUT POWER</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak, 1MHz Average, 1MHz
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 55 % RH, 1050 hPa	<b>TESTED BY: BILL CHANG</b>	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)
1	1031.90	31.9 Av	54.00	-22.10	1.30H	345	2.87	24.96	4.04	0.00	-29.00
2	1256.40	30.1 Av	54.00	-23.90	1.58H	239	0.26	25.41	4.43	0.00	-29.84
3	1004.30	44.9 pk	74.00	-29.10	1.50H	62	15.91	24.90	4.06	0.00	-28.96
4	1031.90	51.5 pk	74.00	-22.50	1.37H	221	22.45	24.96	4.04	0.00	-29.00
5	1256.40	50.7 pk	74.00	-23.30	1.48H	201	20.85	25.42	4.44	0.00	-29.86

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)
1	1061.00	32.6 Av	54.00	-21.40	1.89V	185	3.51	25.02	4.03	0.00	-29.05
2	1061.00	50.5 pk	74.00	-23.50	1.74V	352	21.45	25.02	4.03	0.00	-29.05
3	1258.30	45.8 pk	74.00	-28.20	1.95V	285	15.94	25.42	4.44	0.00	-29.86
4	1497.70	44.7 pk	74.00	-29.30	1.95V	174	13.91	25.90	4.90	0.00	-30.80

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
  2. Correction Factor(dB/m) = Pre-Amplifier Factor (dB) - Antenna Factor (dB/m) - Cable Factor (dB)
  3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
  4. The other emission levels were very low against the limit.
  5. Margin value = Emission level – Limit value.

## 4.2.8 TEST RESULTS (B)

<b>EUT</b>	19" CRT COLOR MONITOR	<b>MODEL NO.</b>	N0902
<b>MODE</b>	2	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>INPUT POWER</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Quasi-Peak, 120kHz
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 55 % RH, 1050 hPa	<b>TESTED BY: BILL CHANG</b>	

### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 10 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)
1	57.77	22.4 QP	30.00	-7.60	3.46H	323	15.47	6.21	0.74	0.00	-6.95
2	152.46	21.7 QP	30.00	-8.30	4.00H	201	10.34	10.15	1.21	0.00	-11.36
3	171.50	24.9 QP	30.00	-5.10	4.00H	77	14.91	8.62	1.31	0.00	-9.94
4	190.59	25.2 QP	30.00	-4.80	4.00H	259	15.67	8.19	1.37	0.00	-9.56
5	209.75	25.4 QP	30.00	-4.60	4.00H	279	15.19	8.82	1.43	0.00	-10.25
6	228.90	21.4 QP	30.00	-8.60	4.00H	93	9.90	10.02	1.52	0.00	-11.54
7	285.96	30.4 QP	37.00	-6.60	4.00H	74	16.37	12.26	1.77	0.00	-14.04
8	362.18	30.6 QP	37.00	-6.40	1.77H	54	14.24	14.31	2.04	0.00	-16.36
9	457.70	33.0 QP	37.00	-4.00	1.52H	190	14.15	16.47	2.38	0.00	-18.86
10	629.08	32.9 QP	37.00	-4.10	3.64H	94	10.32	19.59	2.98	0.00	-22.58
11	648.05	31.7 QP	37.00	-5.30	3.68H	92	8.71	19.90	3.05	0.00	-22.97
12	666.08	32.2 QP	37.00	-4.80	3.61H	83	8.83	20.23	3.14	0.00	-23.38

### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 10 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)
1	57.29	26.9 QP	30.00	-3.10	1.00V	350	19.95	6.21	0.74	0.00	-6.95
2	85.90	21.3 QP	30.00	-8.70	1.00V	356	13.22	7.19	0.92	0.00	-8.11
3	114.42	26.2 QP	30.00	-3.80	1.00V	292	14.72	10.41	1.07	0.00	-11.48
4	133.50	23.5 QP	30.00	-6.50	1.00V	214	11.20	11.19	1.13	0.00	-12.32
5	152.67	21.3 QP	30.00	-8.70	1.00V	97	10.17	9.87	1.23	0.00	-11.10
6	400.93	27.9 QP	37.00	-9.10	1.00V	85	9.84	15.85	2.18	0.00	-18.03
7	649.50	28.0 QP	37.00	-9.00	2.45V	212	5.04	19.90	3.05	0.00	-22.96
8	667.30	31.2 QP	37.00	-5.80	2.27V	176	7.81	20.28	3.15	0.00	-23.43

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
  2. Correction Factor(dB/m) = Pre-Amplifier Factor (dB) - Antenna Factor (dB/m) - Cable Factor (dB)
  3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
  4. The other emission levels were very low against the limit.
  5. Margin value = Emission level – Limit value.

<b>EUT</b>	19" CRT COLOR MONITOR	<b>MODEL NO.</b>	N0902
<b>MODE</b>	2	<b>FREQUENCY RANGE</b>	1000-2000 MHz
<b>INPUT POWER</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak, 1MHz Average, 1MHz
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 55 % RH, 1050 hPa	<b>TESTED BY: BILL CHANG</b>	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)
1	1052.60	30.7 Av	54.00	-23.30	3.80H	337	1.67	25.00	4.03	0.00	-29.03
2	1156.50	33.8 Av	54.00	-20.20	1.30H	42	4.40	25.21	4.19	0.00	-29.40
3	1004.00	47.9 pk	74.00	-26.10	1.12H	189	18.93	24.90	4.06	0.00	-28.96
4	1052.60	52.3 pk	74.00	-21.70	2.05H	270	23.31	25.00	4.03	0.00	-29.03
5	1156.50	52.4 pk	74.00	-21.60	2.26H	172	22.95	25.22	4.20	0.00	-29.42

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB/m)
1	1057.70	33.2 Av	54.00	-20.80	2.12V	182	4.17	25.01	4.03	0.00	-29.04
2	1095.50	31.7 Av	54.00	-22.30	1.49V	334	2.52	25.09	4.05	0.00	-29.14
3	1004.10	41.7 pk	74.00	-32.30	2.17V	82	12.74	24.90	4.06	0.00	-28.96
4	1054.70	49.9 pk	74.00	-24.10	1.39V	155	20.84	25.00	4.03	0.00	-29.03
5	1095.50	48.1 pk	74.00	-25.90	1.71V	149	18.97	25.10	4.05	0.00	-29.15
6	1193.10	44.6 pk	74.00	-29.40	2.25V	129	15.09	25.28	4.28	0.00	-29.56

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
  2. Correction Factor(dB/m) = Pre-Amplifier Factor (dB) - Antenna Factor (dB/m) - Cable Factor (dB)
  3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
  4. The other emission levels were very low against the limit.
  5. Margin value = Emission level – Limit value.

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

### CONDUCTED EMISSION TEST



## RADIATED EMISSION TEST





## 6 APPENDIX - INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

<b>USA</b>	FCC, NVLAP
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>New Zealand</b>	MoC
<b>Norway</b>	NEMKO, DNV
<b>U.K.</b>	INCHCAPE
<b>R.O.C.</b>	BSMI

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: [www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml).  
If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC Lab:**  
Tel: 886-2-26052180  
Fax: 886-2-26052943

**Hsin Chu EMC Lab:**  
Tel: 886-35-935343  
Fax: 886-35-935342

**Lin Kou Safety Lab:**  
Tel: 886-2-26093195  
Fax: 886-2-26093184

**Design Center:**  
Tel: 886-2-26093195  
Fax: 886-2-26093184

**Email:** [service@mail.adt.com.tw](mailto:service@mail.adt.com.tw)  
**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.