



## FCC 47 CFR PART 15 SUBPART C

### TEST REPORT

For

Computer

Model:

**TREK-550, TREK-550XXXXXXXXXXXXXX (where “X” may be any alphanumeric character , “-” or blank)**

Trade Name: ADVANTECH

*Issued to*

**Advantech Co. Ltd.**  
**No.1, Alley 20, Lane 26, Rueiguang Road, Neihu District,**  
**Taipei 114, Taiwan, R.O.C.**

*Issued by*

**Compliance Certification Services Inc.**  
**No.11, Wugong 6th Rd., Wugu Dist.,**  
**New Taipei City 24891, Taiwan. (R.O.C.)**  
**<http://www.ccsrf.com>**  
**[service@ccsrf.com](mailto:service@ccsrf.com)**  
**Issued Date: June 24, 2013**



---

**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



**Revision History**

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	June 24, 2013	Initial Issue	ALL	Gina Lo



## TABLE OF CONTENTS

<b>1. TEST RESULT CERTIFICATION.....</b>	<b>4</b>
<b>2. EUT DESCRIPTION .....</b>	<b>5</b>
<b>3. TEST METHODOLOGY .....</b>	<b>6</b>
3.1 EUT CONFIGURATION .....	6
3.2 EUT EXERCISE.....	6
3.3 GENERAL TEST PROCEDURES.....	6
3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....	7
3.5 DESCRIPTION OF TEST MODES .....	8
<b>4. INSTRUMENT CALIBRATION.....</b>	<b>9</b>
4.1 MEASURING INSTRUMENT CALIBRATION.....	9
4.2 MEASUREMENT EQUIPMENT USED.....	9
4.3 MEASUREMENT UNCERTAINTY .....	10
<b>5. FACILITIES AND ACCREDITATIONS .....</b>	<b>11</b>
5.1 FACILITIES .....	11
5.2 EQUIPMENT.....	11
5.3 TABLE OF ACCREDITATIONS AND LISTINGS.....	12
<b>6. SETUP OF EQUIPMENT UNDER TEST .....</b>	<b>13</b>
6.1 SETUP CONFIGURATION OF EUT.....	13
6.2 SUPPORT EQUIPMENT .....	13
<b>7. FCC PART 15.247 REQUIREMENTS.....</b>	<b>14</b>
7.1 6DB BANDWIDTH.....	14
7.2 PEAK POWER.....	28
7.3 AVERAGE POWER .....	30
7.4 BAND EDGES MEASUREMENT .....	32
7.5 PEAK POWER SPECTRAL DENSITY.....	58
7.6 SPURIOUS EMISSIONS.....	72
7.7 RADIATED EMISSIONS .....	72
7.8 POWERLINE CONDUCTED EMISSIONS.....	95
<b>APPENDIX I PHOTOGRAPHS OF TEST SETUP.....</b>	<b>96</b>
<b>APPENDIX 1 - PHOTOGRAPHS OF EUT</b>	



## 1. TEST RESULT CERTIFICATION

**Applicant:** Advantech Co. Ltd.  
No.1, Alley 20, Lane 26, Rueiguang Road, Neihu District,  
Taipei 114, Taiwan, R.O.C.

**Equipment Under Test:** Computer

**Trade Name:** ADVANTECH

**Model:** TREK-550, TREK-550XXXXXXXXXXXXXX (where "X" may be any alphanumeric character, "-" or blank)

**Date of Test:** June 11, 2013

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

### We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2009 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

*Approved by:*

---

Miller Lee  
Section Manager  
Compliance Certification Services Inc.

*Reviewed by:*

---

Gina Lo  
Section Manager  
Compliance Certification Services Inc.



## 2. EUT DESCRIPTION

<b>Product</b>	Computer
<b>Trade Name</b>	ADVANTECH
<b>Model Number</b>	TREK-550, TREK-550XXXXXXXXXXXXXX (where "X" may be any alphanumeric character , "-" or blank)
<b>Model Discrepancy</b>	All the specification and layout are identical except they come with different model numbers for marketing purpose. The suffix of "XXXXXXXXXXXXXX" (X= any alphanumeric character , "-" or blank) on model number is just for marketing purpose only.
<b>Received Date</b>	May 7, 2013
<b>Power Adapter</b>	DC 12V
<b>Frequency Range</b>	2412 ~ 2462 MHz
<b>Transmit Power</b>	IEEE 802.11b mode: 20.28 dBm IEEE 802.11g mode: 24.39 dBm IEEE 802.11n HT 20 MHz mode: 24.07 dBm IEEE 802.11n HT 40 MHz mode: 24.41 dBm
<b>Modulation Technique</b>	IEEE 802.11b mode: DSSS (1, 2, 5.5 and 11 Mbps) IEEE 802.11g mode: OFDM (6, 9, 12, 18, 24, 36, 48 and 54 Mbps) IEEE 802.11n HT 20 MHz mode: OFDM (6.5, 13, 19.5, 26, 39, 52, 58.5, 65.0Mbps) IEEE 802.11n HT 40 MHz mode: OFDM (13.5, 27, 40.5, 54, 81, 108, 121.5, 135Mbps)
<b>Number of Channels</b>	IEEE 802.11b/g mode: 11 Channels IEEE 802.11n HT 20 MHz mode: 11 Channels IEEE 802.11n HT 40 MHz mode: 7 Channels
<b>Antenna Specification</b>	Loop Antenna / Gain: 2.1dBi

**Remark:**

1. *The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.*
2. *This submittal(s) (test report) is intended for FCC ID: **M82-TREK550A2** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.*



### **3. TEST METHODOLOGY**

The tests documented in this report were performed in accordance with ANSI C63.4: 2009 and FCC CFR 47 Part 15.207, 15.209, 15.247, KDB558074.

#### **3.1 EUT CONFIGURATION**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### **3.2 EUT EXERCISE**

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

#### **3.3 GENERAL TEST PROCEDURES**

##### **Conducted Emissions**

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

##### **Radiated Emissions**

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4.

**3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS**

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

<b>MHz</b>	<b>MHz</b>	<b>MHz</b>	<b>GHz</b>
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41	322 - 335.4		

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



### **3.5 DESCRIPTION OF TEST MODES**

The EUT (model: TREK-550) had been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting mode was programmed.

The worst case data rate is determined as the data rate with highest output power.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only.

#### **IEEE 802.11b mode:**

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 1Mbps data rate were chosen for full testing.

#### **IEEE 802.11g mode:**

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate were chosen for full testing.

#### **IEEE 802.11n HT 20 MHz mode:**

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6.5Mbps data rate were chosen for full testing.

#### **IEEE 802.11n HT 40 MHz mode:**

Channel Low (2422MHz), Channel Mid (2437MHz) and Channel High (2452MHz) with 13.5Mbps data rate were chosen for full testing.



## 4. INSTRUMENT CALIBRATION

### 4.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

### 4.2 MEASUREMENT EQUIPMENT USED

#### Equipment Used for Emissions Measurement

*Remark: Each piece of equipment is scheduled for calibration once a year.*

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360131	03/27/2014
Power Meter	Anritsu	ML2495A	1012009	06/04/2014
Power Sensor	Anritsu	MA2411A	0917072	06/04/2014

3M Chamber Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510268	11/06/2013
EMI Test Receiver	R&S	ESCI	100064	02/28/2014
Pre-Amplifier	Mini-Circuits	ZFL-1000LN	SF350700823	01/12/2014
Pre-Amplifier	MITEQ	AFS44-00102650-42-10P-44	1415367	11/19/2013
Bilog Antenna	Sunol Sciences	JB3	A030105	10/02/2013
Horn Antenna	EMCO	3117	00055165	02/13/2014
Horn Antenna	EMCO	3116	2487	10/10/2013
Loop Antenna	EMCO	6502	8905/2356	06/12/2014
Turn Table	CCS	CC-T-1F	N/A	N.C.R
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R
Site NSA	CCS	N/A	N/A	12/22/2013
Test S/W	EZ-EMC (CCS-3A1RE)			



### 4.3 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
3M Semi Anechoic Chamber / 30M~200M	+/- 4.0138
3M Semi Anechoic Chamber / 200M~1000M	+/- 3.9483
3M Semi Anechoic Chamber / 1G~8G	+/- 2.5975
3M Semi Anechoic Chamber / 8G~18G	+/- 2.6112
3M Semi Anechoic Chamber / 18G~26G	+/- 2.7389
3M Semi Anechoic Chamber / 26G~40G	+/- 2.9683

**Remark:** This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .



## 5. FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

- No.199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.  
Tel: 886-2-2217-0894 / Fax: 886-2-2217-1029
- No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)  
Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045
- No.81-1, Lane 210, Bade 2nd Rd., Lujhu Township, Taoyuan County 33841, TAIWAN, R.O.C.  
Tel: 886-3-324-0332 / Fax: 886-3-324-5235

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

### 5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."



### 5.3 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3M Semi Anechoic Chamber (FCC MRA: TW1039) to perform FCC Part 15 measurements	 FCC MRA: TW1039
Taiwan	TAF	LP0002, RTTE01, FCC Method-47 CFR Part 15 Subpart C, D, E, RSS-210, RSS-310 IDA TS SRD, AS/NZS 4268, AS/NZS 4771, TS 12.1 & 12.2, ETSI EN 300 440-1, ETSI EN 300 440-2, ETSI EN 300 328, ETSI EN 300 220-1, ETSI EN 300 220-2, ETSI EN 301 893, ETSI EN 301 489-1/3/7/17 FCC OET Bulletin 65 + Supplement C, EN 50360, EN 50361, EN 50371, RSS 102, EN 50383, EN 50385, EN 50392, IEC 62209, CNS 14958-1, CNS 14959 FCC Method -47 CFR Part 15 Subpart B IEC / EN 61000-3-2, IEC / EN 61000-3-3, IEC / EN 61000-4-2/3/4/5/6/8/11	 Testing Laboratory 1309
Canada	Industry Canada	3M Semi Anechoic Chamber (IC 2324G-1 / IC 2324G-2) to perform	 IC 2324G-1 IC 2324G-2

\* No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.



## **6. SETUP OF EQUIPMENT UNDER TEST**

### **6.1 SETUP CONFIGURATION OF EUT**

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

### **6.2 SUPPORT EQUIPMENT**

No	Equipment	Brand	Model	Series No.	FCC ID	Data Cable	Power Cord
1.	USB Keyboard	Logitech	Y-SJ14C	867247-0121	FCC DoC	Shielded, 1.8m	N/A
2.	USB Mouse	DELL	MO56UO	408031121	FCC DoC	Shielded, 1.8m	N/A
3.	Power Supply	ABM	8301HD	D011531	FCC DoC	N/A	Shielded, 1.5m

***Remark:***

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.*
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.*




## 7. FCC PART 15.247 REQUIREMENTS

### 7.1 6DB BANDWIDTH

#### **LIMIT**

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

#### **Test Configuration**



#### **TEST PROCEDURE**

The transmitter output is connected to the spectrum analyzer. Set the RBW=100kHz the emission bandwidth,  $VBW \geq 3 \times RBW$ , Detector = Peak, Trace mode = max hold, Sweep = auto couple. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

#### **TEST RESULTS**

*No non-compliance noted*

**Test Data****Test mode: IEEE 802.11b mode**

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (kHz)	Result
Low	2412	10.5	>500	PASS
Mid	2437	10.5		PASS
High	2462	10.5		PASS

**Test mode: IEEE 802.11g mode**

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (kHz)	Result
Low	2412	16	>500	PASS
Mid	2437	16.25		PASS
High	2462	16.25		PASS

**Test mode: IEEE 802.11n HT 20 MHz mode**

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (kHz)	Result
Low	2412	17	>500	PASS
Mid	2437	17		PASS
High	2462	17		PASS


**Test mode: IEEE 802.11n HT 40 MHz mode**

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (kHz)	Result
Low	2422	33.8333	>500	PASS
Mid	2437	33.8333		PASS
High	2452	33.8333		PASS



IEEE 802.11b mode

6dB Bandwidth (CH Low)




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2406.6667	0.34	2.79	-2.45
2	2411.4167	8.79	2.79	6.00
3	2417.1667	1.30	2.79	-1.49

No.	△Frequency(MHz)	△Level(dB)
1	mk3-mk1	10.5



### 6dB Bandwidth (CH Mid)




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2431.6667	-0.01	2.43	-2.44
2	2436.4167	8.43	2.43	6.00
3	2442.1667	0.82	2.43	-1.61

No.		△Frequency(MHz)	△Level(dB)
1	mk3-mk1	10.5	0.83




**6dB Bandwidth (CH High)**



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2456.6667	-0.22	2.08	-2.30
2	2461.4167	8.08	2.08	6.00
3	2467.1667	0.29	2.08	-1.79

No.	△Frequency(MHz)	△Level(dB)
1	mk3-mk1	10.5


**IEEE 802.11g mode****6dB Bandwidth (CH Low)**

No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2403.9167	2.64	3.30	-0.66
2	2409.8333	9.30	3.30	6.00
3	2419.9167	3.29	3.30	-0.01

No.		△Frequency(MHz)	△Level(dB)
1	mk3-mk1	16	0.65




### 6dB Bandwidth (CH Mid)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2428.8333	2.07	2.42	-0.35
2	2441.0833	8.42	2.42	6.00
3	2445.0833	2.21	2.42	-0.21

No.		△Frequency(MHz)	△Level(dB)
1	mk3-mk1	16.25	0.14

**6dB Bandwidth (CH High)**


No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2453.8333	-0.03	0.13	-0.16
2	2466.0833	6.13	0.13	6.00
3	2470.0833	-0.20	0.13	-0.33

No.		$\Delta$ Frequency(MHz)	$\Delta$ Level(dB)
1	mk3-mk1	16.25	-0.17




**IEEE 802.11n HT 20 MHz mode**

**6dB Bandwidth (CH Low)**



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2403.4167	0.65	1.30	-0.65
2	2411.1667	7.30	1.30	6.00
3	2420.4167	1.15	1.30	-0.15

No.	△Frequency(MHz)	△Level(dB)
1	mk3-mk1	17


**6dB Bandwidth (CH Mid)**

No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2428.4167	1.79	2.39	-0.60
2	2436.1667	8.39	2.39	6.00
3	2445.4167	2.07	2.39	-0.32

No.		△Frequency(MHz)	△Level(dB)
1	mk3-mk1	17	0.28



**6dB Bandwidth (CH High)**




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2453.4167	1.39	1.88	-0.49
2	2461.1667	7.88	1.88	6.00
3	2470.4167	1.14	1.88	-0.74

No.		△Frequency(MHz)	△Level(dB)
1	mk3-mk1	17	-0.25




**IEEE 802.11n HT 40 MHz mode**

**6dB Bandwidth (CH Low)**




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2405.0000	-4.44	-4.31	-0.13
2	2419.8333	1.69	-4.31	6.00
3	2438.8333	-4.92	-4.31	-0.61

No.		△Frequency(MHz)	△Level(dB)
1	mk3-mk1	33.8333	-0.48

**6dB Bandwidth (CH Mid)**

No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2419.9167	1.53	1.63	-0.10
2	2434.7500	7.63	1.63	6.00
3	2453.7500	1.49	1.63	-0.14

No.	△Frequency(MHz)	△Level(dB)
1	mk3-mk1	33.8333

**6dB Bandwidth (CH High)**

No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2434.9167	-3.01	-2.97	-0.04
2	2449.7500	3.03	-2.97	6.00
3	2468.7500	-3.22	-2.97	-0.25

No.	△Frequency(MHz)	△Level(dB)
1	mk3-mk1	33.8333




## 7.2 PEAK POWER

### LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### Test Configuration



### TEST PROCEDURE

The transmitter output is connected to the Power Meter. The Power Meter is set to the peak power detection.

### TEST RESULTS

*No non-compliance noted*

**Test Data****Test mode: IEEE 802.11b mode**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	20.28	0.1067	1.00	PASS
Mid	2437	19.86	0.0968		PASS
High	2462	19.64	0.0920		PASS

**Test mode: IEEE 802.11g mode**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	24.39	0.2748	1.00	PASS
Mid	2437	24.37	0.2735		PASS
High	2462	22.55	0.1799		PASS

**Test mode: IEEE 802.11n HT 20 MHz mode**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	23.03	0.2009	1.00	PASS
Mid	2437	24.07	0.2553		PASS
High	2462	22.66	0.1845		PASS

**Test mode: IEEE 802.11n HT 40 MHz mode**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2422	18.93	0.0782	1.00	PASS
Mid	2437	24.41	0.2761		PASS
High	2452	20.46	0.1112		PASS




## 7.3 AVERAGE POWER

### LIMIT

None; for reporting purposes only.

### Test Configuration



### TEST PROCEDURE

The transmitter output is connected to the Power Meter. The Power Meter is set to the avg power detection.



## **TEST RESULTS**

*No non-compliance noted*

### **Test Data**

#### **Test mode: IEEE 802.11b mode**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2412	17.81	0.0604
Mid	2437	17.39	0.0548
High	2462	17.16	0.0520

#### **Test mode: IEEE 802.11g mode**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2412	16.68	0.0466
Mid	2437	16.74	0.0472
High	2462	14.48	0.0281

#### **Test mode: IEEE 802.11n HT 20 MHz mode**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2412	15.08	0.0322
Mid	2437	16.42	0.0439
High	2462	15.02	0.0318

#### **Test mode: IEEE 802.11n HT 40 MHz mode**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2422	10.09	0.0102
Mid	2437	16.37	0.0434
High	2452	11.57	0.0144


## 7.4 BAND EDGES MEASUREMENT

### LIMIT


According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

### Test Configuration

#### For Radiated



#### For Conducted





## **TEST PROCEDURE**

### **For Radiated**

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=1MHz / VBW=3MHz / Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz / VBW= 300Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.



### **For Conducted**



Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.



The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

## **TEST RESULTS**

Refer to attach spectrum analyzer data chart.

**Band Edges (IEEE 802.11b mode / CH Low)****Detector mode: Peak****Polarity: Vertical****Detector mode: Average****Polarity: Vertical**


**Detector mode: Peak****Polarity: Horizontal****Detector mode: Average****Polarity: Horizontal**

**Band Edges (IEEE 802.11b mode / CH High)****Detector mode: Peak****Polarity: Vertical****Detector mode: Average****Polarity: Vertical**




**Detector mode: Peak**



**Polarity: Horizontal**





**Detector mode: Average**

**Polarity: Horizontal**



**Band Edges (IEEE 802.11g mode / CH Low)****Detector mode: Peak****Polarity: Vertical****Detector mode: Average****Polarity: Vertical**


**Detector mode: Peak****Polarity: Horizontal****Detector mode: Average****Polarity: Horizontal**



**Band Edges (IEEE 802.11g mode / CH High)**


**Detector mode: Peak**



**Polarity: Vertical**



**Detector mode: Average**

**Polarity: Vertical**




**Detector mode: Peak****Polarity: Horizontal****Detector mode: Average****Polarity: Horizontal**



**Band Edges (IEEE 802.11n HT 20 MHz mode / CH Low)**


**Detector mode: Peak**



**Polarity: Vertical**



**Detector mode: Average**

**Polarity: Vertical**




**Detector mode: Peak****Polarity: Horizontal****Detector mode: Average****Polarity: Horizontal**



**Band Edges (IEEE 802.11n HT 20 MHz mode / CH High)**


**Detector mode: Peak**



**Polarity: Vertical**







**Detector mode: Average**



**Polarity: Vertical**





**Detector mode: Peak****Polarity: Horizontal****Detector mode: Average****Polarity: Horizontal**

**Band Edges (IEEE 802.11n HT 40 MHz mode / CH Low)****Detector mode: Peak****Polarity: Vertical****Detector mode: Average****Polarity: Vertical**

**Detector mode: Peak****Polarity: Horizontal****Detector mode: Average****Polarity: Horizontal**


**Band Edges (IEEE 802.11n HT 40 MHz mode / CH High)****Detector mode: Peak****Polarity: Vertical****Detector mode: Average****Polarity: Vertical**

**Detector mode: Peak****Polarity: Horizontal****Detector mode: Average****Polarity: Horizontal**



## Test Plot


### Conducted Band Edges (IEEE 802.11b mode / CH Low)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2396.8750	-30.47	-13.09	-17.38
2	2412.8750	6.91	-13.09	20.00




Conducted Band Edges (IEEE 802.11b mode / CH High)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2459.8750	6.08	-13.92	20.00
2	2484.3750	-52.52	-13.92	-38.60




Conducted Band Edges (IEEE 802.11g mode / CH Low)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2400.0000	-28.16	-16.67	-11.49
2	2409.7500	3.33	-16.67	20.00




Conducted Band Edges (IEEE 802.11g mode / CH High)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2459.1250	1.02	-18.98	20.00
2	2483.5000	-41.66	-18.98	-22.68




Conducted Band Edges (IEEE 802.11n HT 20 MHz mode / CH Low)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2400.0000	-30.55	-17.41	-13.14
2	2409.1250	2.59	-17.41	20.00




Conducted Band Edges (IEEE 802.11n HT 20 MHz mode / CH High)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2459.0000	3.24	-16.76	20.00
2	2483.5000	-36.57	-16.76	-19.81




Conducted Band Edges (IEEE 802.11n HT 40 MHz mode / CH Low)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2397.7500	-36.99	-26.05	-10.94
2	2420.3750	-6.05	-26.05	20.00



Conducted Band Edges (IEEE 802.11n HT 40 MHz mode / CH High)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2455.3750	-4.21	-24.21	20.00
2	2483.5000	-38.74	-24.21	-14.53




## 7.5 PEAK POWER SPECTRAL DENSITY

### LIMIT

1. According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
2. According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

### Test Configuration



## TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. Set the RBW = 100 kHz, VBW  $\geq$  300 kHz, span to 1.5 times the DTS bandwidth, Detector = peak, Trace mode = max hold, Sweep = auto couple. Use the peak marker function to determine the maximum amplitude level within the RBW. If measured value exceeds limit, reduce RBW (no less than 3 kHz).



## TEST RESULTS

*No non-compliance noted*

### Test Data

#### **Test mode: IEEE 802.11b mode**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-5.11	8.00	PASS
Mid	2437	-5.49		PASS
High	2462	-5.95		PASS

#### **Test mode: IEEE 802.11g mode**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-4.35	8.00	PASS
Mid	2437	-4.63		PASS
High	2462	-6.87		PASS

#### **Test mode: IEEE 802.11n HT 20 MHz mode**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-4.02	8.00	PASS
Mid	2437	-3.01		PASS
High	2462	-3.67		PASS

#### **Test mode: IEEE 802.11n HT 40 MHz mode**


Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2422	-12.39	8.00	PASS
Mid	2437	-6.50		PASS
High	2452	-11.05		PASS



## Test Plot

IEEE 802.11b mode


PPSD (CH Low)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2412.7250	-5.11	8.00	-13.11




**PPSD (CH Mid)**



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2437.7250	-5.49	8.00	-13.49



**PPSD (CH High)**




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2462.7250	-5.95	8.00	-13.95



**IEEE 802.11g mode**


**PPSD (CH Low)**



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2414.7333	-4.35	8.00	-12.35




**PPSD (CH Mid)**



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2438.5000	-4.63	8.00	-12.63



**PPSD (CH High)**




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2464.4333	-6.87	8.00	-14.87



**IEEE 802.11n HT 20 MHz mode**


**PPSD (CH Low)**



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2409.8000	-4.02	8.00	-12.02




**PPSD (CH Mid)**



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2434.8000	-3.01	8.00	-11.01



**PPSD (CH High)**




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2459.8000	-3.67	8.00	-11.67



**IEEE 802.11n HT 40 MHz mode**


**PPSD (CH Low)**



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2425.3333	-12.39	8.00	-20.39




**PPSD (CH Mid)**



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2433.5333	-6.50	8.00	-14.50



**PPSD (CH High)**



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2448.5333	-11.05	8.00	-19.05



## 7.6 SPURIOUS EMISSIONS

## 7.7 RADIATED EMISSIONS

### LIMIT



- According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu$ V/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

*Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.*


- In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength ( $\mu$ V/m at 3-meter)	Field Strength (dB $\mu$ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

**Test Configuration****9kHz ~ 30MHz****30MHz ~ 1GHz**



**Above 1 GHz**





## **TEST PROCEDURE**

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:

Below 1GHz:

RBW=100kHz / VBW=300kHz / Sweep=AUTO

Above 1GHz:

(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO

(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO

7. Repeat above procedures until the measurements for all frequencies are complete.



## TEST RESULTS

### Below 1GHz

**Operation Mode:** Normal Link

**Test Date:** June 11, 2013

**Temperature:** 27°C

**Tested by:** Rex Huang

**Humidity:** 53% RH

**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
84.9666	73.24	-34.03	39.21	40.00	-0.79	QP	V
117.3000	66.77	-28.72	38.05	43.50	-5.45	peak	V
367.8833	63.95	-26.19	37.76	46.00	-8.24	peak	V
620.0833	60.78	-21.77	39.01	46.00	-6.99	peak	V
797.9167	58.17	-19.06	39.11	46.00	-6.89	peak	V
959.5833	60.39	-16.75	43.64	46.00	-2.36	QP	V
72.0333	70.68	-33.47	37.21	40.00	-2.79	QP	H
117.3000	67.07	-28.72	38.35	43.50	-5.15	peak	H
293.5167	66.43	-27.83	38.60	46.00	-7.40	peak	H
738.1000	60.45	-19.73	40.72	46.00	-5.28	peak	H
911.0833	57.87	-17.25	40.62	46.00	-5.38	peak	H
959.5833	62.07	-16.75	45.32	46.00	-0.68	QP	H

**Remark:**

1. *No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz)*
2. *Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.*
3. *Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.*
4. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
5. *Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).*

**Above 1 GHz****Operation Mode:** TX / IEEE 802.11b / CH Low**Test Date:** June 11, 2013**Temperature:** 27°C**Tested by:** Rex Huang**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1606.667	56.95	-5.33	51.62	74.00	-22.38	peak	V
2123.333	54.20	-1.19	53.01	74.00	-20.99	peak	V
2123.333	44.41	-1.19	43.22	54.00	-10.78	AVG	V
2253.333	57.50	-0.94	56.56	74.00	-17.44	peak	V
2253.333	47.22	-0.94	46.28	54.00	-7.72	AVG	V
2330.000	58.84	-0.74	58.10	74.00	-15.90	peak	V
2330.000	46.83	-0.74	46.09	54.00	-7.91	AVG	V
2370.000	57.77	-0.60	57.17	74.00	-16.83	peak	V
2370.000	46.59	-0.60	45.99	54.00	-8.01	AVG	V
4825.000	46.31	6.12	52.43	74.00	-21.57	peak	V
4825.000	46.49	6.12	52.61	54.00	-1.39	AVG	V
<hr/>							
1323.333	58.65	-6.67	51.98	74.00	-22.02	peak	H
1556.667	58.55	-5.83	52.72	74.00	-21.28	peak	H
1556.667	47.82	-5.83	41.99	54.00	-12.01	AVG	H
4825.000	45.41	6.12	51.53	74.00	-22.47	peak	H
N/A							

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX / IEEE 802.11b / CH Mid**Test Date:** June 11, 2013**Temperature:** 27°C**Tested by:** Rex Huang**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1326.667	62.00	-6.67	55.33	74.00	-18.67	peak	V
1326.667	52.59	-6.67	45.92	54.00	-8.08	AVG	V
1533.333	58.36	-6.06	52.30	74.00	-21.70	peak	V
1533.333	48.05	-6.06	41.99	54.00	-12.01	AVG	V
2123.333	53.99	-1.19	52.80	74.00	-21.20	peak	V
2123.333	42.87	-1.19	41.68	54.00	-12.32	AVG	V
2213.333	54.43	-1.02	53.41	74.00	-20.59	peak	V
2213.333	43.97	-1.02	42.95	54.00	-11.05	AVG	V
2306.667	57.38	-0.83	56.55	74.00	-17.45	peak	V
2306.667	47.41	-0.83	46.58	54.00	-7.42	AVG	V
2353.333	57.50	-0.66	56.84	74.00	-17.16	peak	V
2353.333	47.55	-0.66	46.89	54.00	-7.11	AVG	V
4875.000	44.93	6.24	51.17	74.00	-22.83	peak	V
1356.667	56.97	-6.62	50.35	74.00	-23.65	peak	H
1533.333	57.48	-6.06	51.42	74.00	-22.58	peak	H
4875.000	44.26	6.24	50.50	74.00	-23.50	peak	H

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX / IEEE 802.11b / CH High**Test Date:** June 11, 2013**Temperature:** 27°C**Tested by:** Rex Huang**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1640.000	58.23	-5.00	53.23	74.00	-20.77	peak	V
1640.000	48.22	-5.00	43.22	54.00	-10.78	AVG	V
2130.000	54.70	-1.18	53.52	74.00	-20.48	peak	V
2130.000	45.71	-1.18	44.53	54.00	-9.47	AVG	V
2213.333	55.25	-1.02	54.23	74.00	-19.77	peak	V
2213.333	45.98	-1.02	44.96	54.00	-9.04	AVG	V
2256.667	56.39	-0.93	55.46	74.00	-18.54	peak	V
2256.667	46.13	-0.93	45.20	54.00	-8.80	AVG	V
2320.000	58.12	-0.78	57.34	74.00	-16.66	peak	V
2320.000	47.06	-0.78	46.28	54.00	-7.72	AVG	V
2380.000	57.21	-0.56	56.65	74.00	-17.35	peak	V
2380.000	46.99	-0.56	46.43	54.00	-7.57	AVG	V
4925.000	43.96	6.37	50.33	74.00	-23.67	peak	V
<hr/>							
1323.333	58.48	-6.67	51.81	74.00	-22.19	peak	H
1560.000	58.41	-5.79	52.62	74.00	-21.38	peak	H
1560.000	48.67	-5.79	42.88	54.00	-11.12	AVG	H
4925.000	43.28	6.37	49.65	74.00	-24.35	peak	H
N/A							

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX / IEEE 802.11g / CH Low**Test Date:** June 11, 2013**Temperature:** 27°C**Tested by:** Rex Huang**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1063.333	63.03	-7.09	55.94	74.00	-18.06	peak	V
1063.333	51.28	-7.09	44.19	54.00	-9.81	AVG	V
1206.667	59.28	-6.86	52.42	74.00	-21.58	peak	V
1206.667	48.76	-6.86	41.90	54.00	-12.10	AVG	V
1330.000	64.37	-6.66	57.71	74.00	-16.29	peak	V
1330.000	51.88	-6.66	45.22	54.00	-8.78	AVG	V
1600.000	57.84	-5.40	52.44	74.00	-21.56	peak	V
1600.000	46.05	-5.40	40.65	54.00	-13.35	AVG	V
1860.000	56.67	-2.82	53.85	74.00	-20.15	peak	V
1860.000	45.94	-2.82	43.12	54.00	-10.88	AVG	V
2123.333	54.77	-1.19	53.58	74.00	-20.42	peak	V
2123.333	44.24	-1.19	43.05	54.00	-10.95	AVG	V
2350.000	59.09	-0.67	58.42	74.00	-15.58	peak	V
2350.000	49.01	-0.67	48.34	54.00	-5.66	AVG	V
4825.000	48.60	6.12	54.72	74.00	-19.28	peak	V
4825.000	46.19	6.12	52.31	54.00	-1.69	AVG	V
1063.333	58.34	-7.09	51.25	74.00	-22.75	peak	H
1326.667	60.12	-6.67	53.45	74.00	-20.55	peak	H
1326.667	49.51	-6.67	42.84	54.00	-11.16	AVG	H
1356.667	62.75	-6.62	56.13	74.00	-17.87	peak	H
1356.667	51.21	-6.62	44.59	54.00	-9.41	AVG	H
1860.000	57.89	-2.82	55.07	74.00	-18.93	peak	H
1860.000	47.05	-2.82	44.23	54.00	-9.77	AVG	H
4825.000	48.72	6.12	54.84	74.00	-19.16	peak	H
4825.000	46.81	6.12	52.93	54.00	-1.07	AVG	H



**Remark:**

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

**Operation Mode:** TX / IEEE 802.11g / CH Mid**Test Date:** June 11, 2013**Temperature:** 27°C**Tested by:** Rex Huang**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1063.333	63.18	-7.09	56.09	74.00	-17.91	peak	V
1063.333	50.27	-7.09	43.18	54.00	-10.82	AVG	V
1200.000	62.86	-6.87	55.99	74.00	-18.01	peak	V
1200.000	50.93	-6.87	44.06	54.00	-9.94	AVG	V
1330.000	63.20	-6.66	56.54	74.00	-17.46	peak	V
1330.000	52.56	-6.66	45.90	54.00	-8.10	AVG	V
1866.667	55.78	-2.75	53.03	74.00	-20.97	peak	V
1866.667	45.77	-2.75	43.02	54.00	-10.98	AVG	V
2123.333	55.14	-1.19	53.95	74.00	-20.05	peak	V
2123.333	43.69	-1.19	42.50	54.00	-11.50	AVG	V
2353.333	58.75	-0.66	58.09	74.00	-15.91	peak	V
2353.333	48.79	-0.66	48.13	54.00	-5.87	AVG	V
2376.667	59.04	-0.57	58.47	74.00	-15.53	peak	V
2376.667	48.80	-0.57	48.23	54.00	-5.77	AVG	V
4875.000	46.10	6.24	52.34	74.00	-21.66	peak	V
4875.000	45.51	6.24	51.75	54.00	-2.25	AVG	V
1063.333	58.17	-7.09	51.08	74.00	-22.92	peak	H
1353.333	60.71	-6.62	54.09	74.00	-19.91	peak	H
1353.333	50.19	-6.62	43.57	54.00	-10.43	AVG	H
1863.333	57.78	-2.79	54.99	74.00	-19.01	peak	H
1863.333	46.89	-2.79	44.10	54.00	-9.90	AVG	H
4875.000	47.20	6.24	53.44	74.00	-20.56	peak	H
4875.000	46.15	6.24	52.39	54.00	-1.61	AVG	H



**Remark:**

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

**Operation Mode:** TX / IEEE 802.11g / CH High**Test Date:** June 11, 2013**Temperature:** 27°C**Tested by:** Rex Huang**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1063.333	62.75	-7.09	55.66	74.00	-18.34	peak	V
1063.333	50.98	-7.09	43.89	54.00	-10.11	AVG	V
1326.667	63.03	-6.67	56.36	74.00	-17.64	peak	V
1326.667	50.24	-6.67	43.57	54.00	-10.43	AVG	V
1860.000	56.49	-2.82	53.67	74.00	-20.33	peak	V
1860.000	45.91	-2.82	43.09	54.00	-10.91	AVG	V
2126.667	55.19	-1.19	54.00	74.00	-20.00	peak	V
2126.667	44.79	-1.19	43.60	54.00	-10.40	AVG	V
2323.333	55.64	-0.77	54.87	74.00	-19.13	peak	V
2323.333	44.93	-0.77	44.16	54.00	-9.84	AVG	V
2383.333	57.07	-0.55	56.52	74.00	-17.48	peak	V
2383.333	47.35	-0.55	46.80	54.00	-7.20	AVG	V
4925.000	43.12	6.37	49.49	74.00	-24.51	peak	V
<hr/>							
1326.667	59.75	-6.67	53.08	74.00	-20.92	peak	H
1326.667	49.24	-6.67	42.57	54.00	-11.43	AVG	H
1356.667	61.99	-6.62	55.37	74.00	-18.63	peak	H
1356.667	51.54	-6.62	44.92	54.00	-9.08	AVG	H
1860.000	58.24	-2.82	55.42	74.00	-18.58	peak	H
1860.000	46.08	-2.82	43.26	54.00	-10.74	AVG	H
4925.000	44.11	6.37	50.48	74.00	-23.52	peak	H

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX / IEEE 802.11n HT 20 MHz mode / CH Low**Test Date:** June 11, 2013**Temperature:** 27°C**Tested by:** Rex Huang**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1066.667	62.39	-7.08	55.31	74.00	-18.69	peak	V
1066.667	51.35	-7.08	44.27	54.00	-9.73	AVG	V
1330.000	63.42	-6.66	56.76	74.00	-17.24	peak	V
1330.000	50.65	-6.66	43.99	54.00	-10.01	AVG	V
1856.667	56.59	-2.85	53.74	74.00	-20.26	peak	V
1856.667	43.94	-2.85	41.09	54.00	-12.91	AVG	V
2133.333	55.16	-1.17	53.99	74.00	-20.01	peak	V
2133.333	44.67	-1.17	43.50	54.00	-10.50	AVG	V
2260.000	55.63	-0.93	54.70	74.00	-19.30	peak	V
2260.000	43.80	-0.93	42.87	54.00	-11.13	AVG	V
2326.667	58.81	-0.75	58.06	74.00	-15.94	peak	V
2326.667	48.71	-0.75	47.96	54.00	-6.04	AVG	V
2350.000	59.71	-0.67	59.04	74.00	-14.96	peak	V
2350.000	49.92	-0.67	49.25	54.00	-4.75	AVG	V
4825.000	46.54	6.12	52.66	74.00	-21.34	peak	V
4825.000	45.18	6.12	51.30	54.00	-2.70	AVG	V
1326.667	59.55	-6.67	52.88	74.00	-21.12	peak	H
1326.667	48.47	-6.67	41.80	54.00	-12.20	AVG	H
1356.667	60.10	-6.62	53.48	74.00	-20.52	peak	H
1356.667	49.91	-6.62	43.29	54.00	-10.71	AVG	H
1866.667	57.52	-2.75	54.77	74.00	-19.23	peak	H
1866.667	46.35	-2.75	43.60	54.00	-10.40	AVG	H
4825.000	45.85	6.12	51.97	74.00	-22.03	peak	H



**Remark:**

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

**Operation Mode:** TX / IEEE 802.11n HT 20 MHz mode / CH Mid**Test Date:** June 11, 2013**Temperature:** 27°C**Tested by:** Rex Huang**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1063.333	65.49	-7.09	58.40	74.00	-15.60	peak	V
1063.333	53.89	-7.09	46.80	54.00	-7.20	AVG	V
1120.000	60.41	-7.00	53.41	74.00	-20.59	peak	V
1120.000	49.38	-7.00	42.38	54.00	-11.62	AVG	V
1330.000	62.72	-6.66	56.06	74.00	-17.94	peak	V
1330.000	51.86	-6.66	45.20	54.00	-8.80	AVG	V
1860.000	55.57	-2.82	52.75	74.00	-21.25	peak	V
1860.000	44.79	-2.82	41.97	54.00	-12.03	AVG	V
2133.333	55.30	-1.17	54.13	74.00	-19.87	peak	V
2133.333	45.49	-1.17	44.32	54.00	-9.68	AVG	V
2356.667	61.48	-0.65	60.83	74.00	-13.17	peak	V
2356.667	50.02	-0.65	49.37	54.00	-4.63	AVG	V
4875.000	47.41	6.24	53.65	74.00	-20.35	peak	V
4875.000	46.53	6.24	52.77	54.00	-1.23	AVG	V
1063.333	61.53	-7.09	54.44	74.00	-19.56	peak	H
1063.333	50.24	-7.09	43.15	54.00	-10.85	AVG	H
1326.667	60.58	-6.67	53.91	74.00	-20.09	peak	H
1326.667	49.64	-6.67	42.97	54.00	-11.03	AVG	H
1356.667	60.39	-6.62	53.77	74.00	-20.23	peak	H
1356.667	49.29	-6.62	42.67	54.00	-11.33	AVG	H
1860.000	55.35	-2.82	52.53	74.00	-21.47	peak	H
1860.000	45.72	-2.82	42.90	54.00	-11.10	AVG	H
4875.000	47.09	6.24	53.33	74.00	-20.67	peak	H
4875.000	44.26	6.24	50.50	54.00	-3.50	AVG	H



**Remark:**

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

**Operation Mode:** TX / IEEE 802.11n HT 20 MHz mode / CH High    **Test Date:** June 11, 2013**Temperature:** 27°C**Tested by:** Rex Huang**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1060.000	64.06	-7.09	56.97	74.00	-17.03	peak	V
1060.000	52.89	-7.09	45.80	54.00	-8.20	AVG	V
1200.000	59.11	-6.87	52.24	74.00	-21.76	peak	V
1200.000	48.74	-6.87	41.87	54.00	-12.13	AVG	V
1326.667	63.84	-6.67	57.17	74.00	-16.83	peak	V
1326.667	51.89	-6.67	45.22	54.00	-8.78	AVG	V
1560.000	58.14	-5.79	52.35	74.00	-21.65	peak	V
1560.000	47.14	-5.79	41.35	54.00	-12.65	AVG	V
1860.000	55.10	-2.82	52.28	74.00	-21.72	peak	V
1860.000	44.70	-2.82	41.88	54.00	-12.12	AVG	V
2130.000	56.10	-1.18	54.92	74.00	-19.08	peak	V
2130.000	45.40	-1.18	44.22	54.00	-9.78	AVG	V
2303.333	59.12	-0.84	58.28	74.00	-15.72	peak	V
2303.333	47.56	-0.84	46.72	54.00	-7.28	AVG	V
2390.000	60.87	-0.53	60.34	74.00	-13.66	peak	V
2390.000	49.46	-0.53	48.93	54.00	-5.07	AVG	V
4958.333	45.36	6.45	51.81	74.00	-22.19	peak	V
1326.667	60.01	-6.67	53.34	74.00	-20.66	peak	H
1326.667	49.47	-6.67	42.80	54.00	-11.20	AVG	H
1353.333	62.04	-6.62	55.42	74.00	-18.58	peak	H
1353.333	50.83	-6.62	44.21	54.00	-9.79	AVG	H
1860.000	55.59	-2.82	52.77	74.00	-21.23	peak	H
1860.000	44.72	-2.82	41.90	54.00	-12.10	AVG	H
4925.000	44.64	6.37	51.01	74.00	-22.99	peak	H



**Remark:**

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*

**Operation Mode:** TX / IEEE 802.11n HT 40 MHz mode / CH Low**Test Date:** June 11, 2013**Temperature:** 27°C**Tested by:** Rex Huang**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1060.000	64.36	-7.09	57.27	74.00	-16.73	peak	V
1060.000	52.39	-7.09	45.30	54.00	-8.70	AVG	V
1120.000	59.67	-7.00	52.67	74.00	-21.33	peak	V
1120.000	48.26	-7.00	41.26	54.00	-12.74	AVG	V
1333.333	61.80	-6.66	55.14	74.00	-18.86	peak	V
1333.333	51.86	-6.66	45.20	54.00	-8.80	AVG	V
1600.000	57.63	-5.40	52.23	74.00	-21.77	peak	V
1600.000	47.37	-5.40	41.97	54.00	-12.03	AVG	V
1860.000	58.48	-2.82	55.66	74.00	-18.34	peak	V
1860.000	47.15	-2.82	44.33	54.00	-9.67	AVG	V
2130.000	54.96	-1.18	53.78	74.00	-20.22	peak	V
2130.000	44.43	-1.18	43.25	54.00	-10.75	AVG	V
2263.333	56.45	-0.92	55.53	74.00	-18.47	peak	V
2263.333	45.55	-0.92	44.63	54.00	-9.37	AVG	V
2320.000	58.71	-0.78	57.93	74.00	-16.07	peak	V
2320.000	47.05	-0.78	46.27	54.00	-7.73	AVG	V
1323.333	60.75	-6.67	54.08	74.00	-19.92	peak	H
1323.333	50.45	-6.67	43.78	54.00	-10.22	AVG	H
1356.667	59.53	-6.62	52.91	74.00	-21.09	peak	H
1356.667	48.12	-6.62	41.50	54.00	-12.50	AVG	H
1860.000	55.39	-2.82	52.57	74.00	-21.43	peak	H
1860.000	44.72	-2.82	41.90	54.00	-12.10	AVG	H
2130.000	53.23	-1.18	52.05	74.00	-21.95	peak	H
2130.000	42.40	-1.18	41.22	54.00	-12.78	AVG	H



**Remark:**

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.*
3. *Average test would be performed if the peak result were greater than the average limit or as required by the applicant.*
4. *Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
5. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
6. *Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).*



**Operation Mode:** TX / IEEE 802.11n HT 40 MHz mode / CH Mid

**Test Date:** June 11, 2013

**Temperature:** 27°C

**Tested by:** Rex Huang

**Humidity:** 53 % RH

**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1063.333	63.01	-7.09	55.92	74.00	-18.08	peak	V
1063.333	52.27	-7.09	45.18	54.00	-8.82	AVG	V
1326.667	62.41	-6.67	55.74	74.00	-18.26	peak	V
1326.667	52.02	-6.67	45.35	54.00	-8.65	AVG	V
1596.667	59.52	-5.43	54.09	74.00	-19.91	peak	V
1596.667	49.64	-5.43	44.21	54.00	-9.79	AVG	V
1863.333	55.57	-2.79	52.78	74.00	-21.22	peak	V
1863.333	44.69	-2.79	41.90	54.00	-12.10	AVG	V
2126.667	54.33	-1.19	53.14	74.00	-20.86	peak	V
2126.667	43.37	-1.19	42.18	54.00	-11.82	AVG	V
2343.333	58.23	-0.69	57.54	74.00	-16.46	peak	V
2343.333	46.96	-0.69	46.27	54.00	-7.73	AVG	V
1326.667	61.26	-6.67	54.59	74.00	-19.41	peak	H
1326.667	51.23	-6.67	44.56	54.00	-9.44	AVG	H
1356.667	60.00	-6.62	53.38	74.00	-20.62	peak	H
1356.667	50.42	-6.62	43.80	54.00	-10.20	AVG	H
1866.667	56.60	-2.75	53.85	74.00	-20.15	peak	H
1866.667	45.68	-2.75	42.93	54.00	-11.07	AVG	H

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



**Operation Mode:** TX / IEEE 802.11n HT 40 MHz mode / CH High

**Test Date:** June 11, 2013

**Temperature:** 27°C

**Tested by:** Rex Huang

**Humidity:** 53 % RH

**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1060.000	62.16	-7.09	55.07	74.00	-18.93	peak	V
1060.000	51.45	-7.09	44.36	54.00	-9.64	AVG	V
1196.667	60.77	-6.88	53.89	74.00	-20.11	peak	V
1196.667	48.99	-6.88	42.11	54.00	-11.89	AVG	V
1333.333	64.70	-6.66	58.04	74.00	-15.96	peak	V
1333.333	53.53	-6.66	46.87	54.00	-7.13	AVG	V
1533.333	59.05	-6.06	52.99	74.00	-21.01	peak	V
1533.333	47.73	-6.06	41.67	54.00	-12.33	AVG	V
1863.333	55.85	-2.79	53.06	74.00	-20.94	peak	V
1863.333	44.88	-2.79	42.09	54.00	-11.91	AVG	V
2130.000	54.26	-1.18	53.08	74.00	-20.92	peak	V
2130.000	44.33	-1.18	43.15	54.00	-10.85	AVG	V
2370.000	58.46	-0.60	57.86	74.00	-16.14	peak	V
2370.000	49.10	-0.60	48.50	54.00	-5.50	AVG	V
1326.667	60.05	-6.67	53.38	74.00	-20.62	peak	H
1326.667	49.20	-6.67	42.53	54.00	-11.47	AVG	H
1353.333	61.05	-6.62	54.43	74.00	-19.57	peak	H
1353.333	50.82	-6.62	44.20	54.00	-9.80	AVG	H
1860.000	56.42	-2.82	53.60	74.00	-20.40	peak	H
1860.000	46.64	-2.82	43.82	54.00	-10.18	AVG	H

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



## 7.8 POWERLINE CONDUCTED EMISSIONS

### LIMIT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

\* Decreases with the logarithm of the frequency.

### Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

## TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

## TEST RESULTS

*Not applicable, because EUT does not connect to AC Main Source direct.*