

4.7.5 Test Results

Below 1GHz

WCDMA:

Mode	TX channel 1413	Frequency Range	Below 1000 MHz
------	-----------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	91.93	34.80	-57.11	-1.04	-58.16	-13	-45.16
2	237.94	35.80	-59.56	3.84	-55.72	-13	-42.72
3	287.8	33.84	-61.63	3.78	-57.84	-13	-44.84
4	345.45	34.04	-63.65	3.61	-60.04	-13	-47.04
5	470.7	36.75	-60.43	2.84	-57.59	-13	-44.59
6	737.34	31.03	-65.34	1.02	-64.31	-13	-51.31
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	68.46	31.33	-56.30	-4.91	-61.21	-13	-48.21
2	94.06	33.29	-58.51	-1.00	-59.52	-13	-46.52
3	128.94	27.94	-63.41	-1.23	-64.65	-13	-51.65
4	238.82	31.88	-63.48	3.82	-59.66	-13	-46.66
5	510.22	33.87	-61.52	2.81	-58.71	-13	-45.71
6	608.86	34.34	-60.35	1.78	-58.57	-13	-45.57

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 4: 1.4MHz

Mode	TX channel 20175	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.41	33.07	-58.84	-1.04	-59.89	-13	-46.89
2	127.92	33.99	-61.37	3.84	-57.53	-13	-44.53
3	277.53	32.04	-63.43	3.78	-59.64	-13	-46.64
4	345.64	30.36	-67.33	3.61	-63.72	-13	-50.72
5	520.06	34.20	-62.98	2.84	-60.14	-13	-47.14
6	736.58	30.12	-66.25	1.02	-65.22	-13	-52.22

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	66.73	30.94	-56.69	-4.91	-61.60	-13	-48.60
2	194.33	33.56	-58.24	-1.00	-59.25	-13	-46.25
3	215.91	34.92	-56.43	-1.23	-57.67	-13	-44.67
4	238.34	29.84	-65.52	3.82	-61.70	-13	-48.70
5	423.26	35.64	-59.75	2.81	-56.94	-13	-43.94
6	557.24	38.49	-56.20	1.78	-54.42	-13	-41.42

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 4: 3MHz

Mode	TX channel 20175	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.88	33.78	-58.13	-1.04	-59.18	-13	-46.18
2	126.68	34.90	-60.46	3.84	-56.62	-13	-43.62
3	277.78	33.06	-62.41	3.78	-58.62	-13	-45.62
4	346.7	30.48	-67.21	3.61	-63.60	-13	-50.60
5	520.36	34.66	-62.52	2.84	-59.68	-13	-46.68
6	735.38	28.98	-67.39	1.02	-66.36	-13	-53.36

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	65.84	30.68	-56.95	-4.91	-61.86	-13	-48.86
2	194.54	33.68	-58.12	-1.00	-59.13	-13	-46.13
3	216.25	35.76	-55.59	-1.23	-56.83	-13	-43.83
4	238.94	30.01	-65.35	3.82	-61.53	-13	-48.53
5	423.56	36.03	-59.36	2.81	-56.55	-13	-43.55
6	556.63	38.21	-56.48	1.78	-54.70	-13	-41.70

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 4: 5MHz

Mode	TX channel 20175	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	75.31	33.83	-58.08	-1.04	-59.13	-13	-46.13
2	128.04	34.62	-60.74	3.84	-56.90	-13	-43.90
3	279.05	31.74	-63.73	3.78	-59.94	-13	-46.94
4	346.68	31.57	-66.12	3.61	-62.51	-13	-49.51
5	521.43	33.88	-63.30	2.84	-60.46	-13	-47.46
6	736.02	29.20	-67.17	1.02	-66.14	-13	-53.14

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.5	31.30	-56.33	-4.91	-61.24	-13	-48.24
2	194	33.18	-58.62	-1.00	-59.63	-13	-46.63
3	215.6	35.06	-56.29	-1.23	-57.53	-13	-44.53
4	237.73	29.89	-65.47	3.82	-61.65	-13	-48.65
5	423.08	35.14	-60.25	2.81	-57.44	-13	-44.44
6	556.35	38.17	-56.52	1.78	-54.74	-13	-41.74

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 4: 10MHz

Mode	TX channel 20175	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	75.66	33.87	-58.04	-1.04	-59.09	-13	-46.09
2	128.11	34.37	-60.99	3.84	-57.15	-13	-44.15
3	277.53	32.11	-63.36	3.78	-59.57	-13	-46.57
4	346.73	31.77	-65.92	3.61	-62.31	-13	-49.31
5	521.04	34.10	-63.08	2.84	-60.24	-13	-47.24
6	735.91	29.61	-66.76	1.02	-65.73	-13	-52.73

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	66.04	31.76	-55.87	-4.91	-60.78	-13	-47.78
2	194.96	33.70	-58.10	-1.00	-59.11	-13	-46.11
3	216.9	34.88	-56.47	-1.23	-57.71	-13	-44.71
4	238.35	30.64	-64.72	3.82	-60.90	-13	-47.90
5	423.37	35.88	-59.51	2.81	-56.70	-13	-43.70
6	556.32	39.03	-55.66	1.78	-53.88	-13	-40.88

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 4: 15MHz

Mode	TX channel 20175	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.96	32.48	-59.43	-1.04	-60.48	-13	-47.48
2	126.83	35.29	-60.07	3.84	-56.23	-13	-43.23
3	277.88	32.98	-62.49	3.78	-58.70	-13	-45.70
4	346.57	30.77	-66.92	3.61	-63.31	-13	-50.31
5	521.92	34.54	-62.64	2.84	-59.80	-13	-46.80
6	736.06	29.69	-66.68	1.02	-65.65	-13	-52.65

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.43	31.52	-56.11	-4.91	-61.02	-13	-48.02
2	194.14	34.08	-57.72	-1.00	-58.73	-13	-45.73
3	215.57	35.60	-55.75	-1.23	-56.99	-13	-43.99
4	238.97	30.44	-64.92	3.82	-61.10	-13	-48.10
5	423.54	35.58	-59.81	2.81	-57.00	-13	-44.00
6	557.87	38.06	-56.63	1.78	-54.85	-13	-41.85

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 4: 20MHz

Mode	TX channel 20175	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	75.32	33.67	-58.24	-1.04	-59.29	-13	-46.29
2	128.26	34.80	-60.56	3.84	-56.72	-13	-43.72
3	278.45	31.83	-63.64	3.78	-59.85	-13	-46.85
4	346.12	31.54	-66.15	3.61	-62.54	-13	-49.54
5	521.21	34.54	-62.64	2.84	-59.80	-13	-46.80
6	736.87	29.09	-67.28	1.02	-66.25	-13	-53.25

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	68.43	30.60	-57.03	-4.91	-61.94	-13	-48.94
2	92.9	33.83	-57.97	-1.00	-58.98	-13	-45.98
3	128.5	36.08	-55.27	-1.23	-56.51	-13	-43.51
4	238.01	31.25	-64.11	3.82	-60.29	-13	-47.29
5	509.23	36.03	-59.36	2.81	-56.55	-13	-43.55
6	609.29	38.55	-56.14	1.78	-54.36	-13	-41.36

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 7: 5MHz

Mode	TX channel 21100	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.38	33.33	-58.58	-1.04	-59.63	-25	-34.63
2	128.5	34.41	-60.95	3.84	-57.11	-25	-32.11
3	278.89	32.77	-62.70	3.78	-58.91	-25	-33.91
4	346.12	30.66	-67.03	3.61	-63.42	-25	-38.42
5	521.18	33.69	-63.49	2.84	-60.65	-25	-35.65
6	736.59	30.22	-66.15	1.02	-65.12	-25	-40.12

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	65.94	31.66	-55.97	-4.91	-60.88	-25	-35.88
2	194.69	33.14	-58.66	-1.00	-59.67	-25	-34.67
3	215.28	34.80	-56.55	-1.23	-57.79	-25	-32.79
4	237.77	31.06	-64.30	3.82	-60.48	-25	-35.48
5	423.97	34.91	-60.48	2.81	-57.67	-25	-32.67
6	556.47	38.43	-56.26	1.78	-54.48	-25	-29.48

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 7: 10MHz

Mode	TX channel 21100	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	77.12	33.52	-58.39	-1.04	-59.44	-25	-34.44
2	127.14	35.00	-60.36	3.84	-56.52	-25	-31.52
3	277.54	32.84	-62.63	3.78	-58.84	-25	-33.84
4	346.29	31.71	-65.98	3.61	-62.37	-25	-37.37
5	521.58	34.46	-62.72	2.84	-59.88	-25	-34.88
6	736.75	29.14	-67.23	1.02	-66.20	-25	-41.20

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	66.16	31.88	-55.75	-4.91	-60.66	-25	-35.66
2	193.42	34.22	-57.58	-1.00	-58.59	-25	-33.59
3	216.87	35.15	-56.20	-1.23	-57.44	-25	-32.44
4	238.29	30.79	-64.57	3.82	-60.75	-25	-35.75
5	423.69	35.84	-59.55	2.81	-56.74	-25	-31.74
6	556.89	37.80	-56.89	1.78	-55.11	-25	-30.11

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 7: 15MHz

Mode	TX channel 21100	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.2	33.08	-58.83	-1.04	-59.88	-25	-34.88
2	128.44	33.97	-61.39	3.84	-57.55	-25	-32.55
3	278.79	33.01	-62.46	3.78	-58.67	-25	-33.67
4	346.34	31.59	-66.10	3.61	-62.49	-25	-37.49
5	520.88	34.66	-62.52	2.84	-59.68	-25	-34.68
6	736.25	29.90	-66.47	1.02	-65.44	-25	-40.44

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.04	30.03	-57.60	-4.91	-62.51	-25	-37.51
2	194.83	33.02	-58.78	-1.00	-59.79	-25	-34.79
3	214.97	27.58	-63.77	-1.23	-65.01	-25	-40.01
4	238.84	31.61	-63.75	3.82	-59.93	-25	-34.93
5	423.11	33.12	-62.27	2.81	-59.46	-25	-34.46
6	558.22	33.61	-61.08	1.78	-59.30	-25	-34.30

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 7: 20MHz

Mode	TX channel 21100	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	75.64	33.34	-58.57	-1.04	-59.62	-25	-34.62
2	127.14	35.21	-60.15	3.84	-56.31	-25	-31.31
3	277.41	32.72	-62.75	3.78	-58.96	-25	-33.96
4	346.18	30.78	-66.91	3.61	-63.30	-25	-38.30
5	521.01	33.99	-63.19	2.84	-60.35	-25	-35.35
6	736.07	30.22	-66.15	1.02	-65.12	-25	-40.12

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.39	30.44	-57.19	-4.91	-62.10	-25	-37.10
2	193.54	34.15	-57.65	-1.00	-58.66	-25	-33.66
3	216.62	34.88	-56.47	-1.23	-57.71	-25	-32.71
4	238.51	29.93	-65.43	3.82	-61.61	-25	-36.61
5	422.99	35.78	-59.61	2.81	-56.80	-25	-31.80
6	556.71	38.24	-56.45	1.78	-54.67	-25	-29.67

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 12: 1.4MHz

Mode	TX channel 23095	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	84.96	35.91	-56.00	-1.04	-57.05	-13	-44.05
2	137.75	36.07	-59.29	3.84	-55.45	-13	-42.45
3	289.23	34.45	-61.02	3.78	-57.23	-13	-44.23
4	344.89	34.07	-63.62	3.61	-60.01	-13	-47.01
5	471.22	36.16	-61.02	2.84	-58.18	-13	-45.18
6	736.44	31.07	-65.30	1.02	-64.27	-13	-51.27

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.82	30.22	-57.41	-4.91	-62.32	-13	-49.32
2	93.28	33.76	-58.04	-1.00	-59.05	-13	-46.05
3	129.26	26.79	-64.56	-1.23	-65.80	-13	-52.80
4	238.34	30.87	-64.49	3.82	-60.67	-13	-47.67
5	509.58	33.12	-62.27	2.81	-59.46	-13	-46.46
6	609.57	33.87	-60.82	1.78	-59.04	-13	-46.04

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 12: 3MHz

Mode	TX channel 23095	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	84.68	34.88	-57.03	-1.04	-58.08	-13	-45.08
2	137.46	35.80	-59.56	3.84	-55.72	-13	-42.72
3	289	34.13	-61.34	3.78	-57.55	-13	-44.55
4	346.5	32.77	-64.92	3.61	-61.31	-13	-48.31
5	470.38	35.07	-62.11	2.84	-59.27	-13	-46.27
6	737.4	30.24	-66.13	1.02	-65.10	-13	-52.10

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.48	30.92	-56.71	-4.91	-61.62	-13	-48.62
2	92.7	32.83	-58.97	-1.00	-59.98	-13	-46.98
3	129.99	26.85	-64.50	-1.23	-65.74	-13	-52.74
4	239.26	32.15	-63.21	3.82	-59.39	-13	-46.39
5	509.73	33.44	-61.95	2.81	-59.14	-13	-46.14
6	609.97	32.86	-61.83	1.78	-60.05	-13	-47.05

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 12: 5MHz

Mode	TX channel 23095	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	84.34	35.58	-56.33	-1.04	-57.38	-13	-44.38
2	136.79	35.36	-60.00	3.84	-56.16	-13	-43.16
3	289.14	33.30	-62.17	3.78	-58.38	-13	-45.38
4	345.82	33.47	-64.22	3.61	-60.61	-13	-47.61
5	469.97	36.08	-61.10	2.84	-58.26	-13	-45.26
6	736.32	30.87	-65.50	1.02	-64.47	-13	-51.47

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	66.91	30.64	-56.99	-4.91	-61.90	-13	-48.90
2	94.22	33.67	-58.13	-1.00	-59.14	-13	-46.14
3	129.57	27.41	-63.94	-1.23	-65.18	-13	-52.18
4	237.69	30.81	-64.55	3.82	-60.73	-13	-47.73
5	509.72	33.52	-61.87	2.81	-59.06	-13	-46.06
6	608.6	32.77	-61.92	1.78	-60.14	-13	-47.14

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 12: 10MHz

Mode	TX channel 23095	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	85.78	34.42	-57.49	-1.04	-58.54	-13	-45.54
2	137	35.48	-59.88	3.84	-56.04	-13	-43.04
3	288.86	33.33	-62.14	3.78	-58.35	-13	-45.35
4	345	32.70	-64.99	3.61	-61.38	-13	-48.38
5	469.78	34.67	-62.51	2.84	-59.67	-13	-46.67
6	736.12	30.07	-66.30	1.02	-65.27	-13	-52.27

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.49	30.81	-56.82	-4.91	-61.73	-13	-48.73
2	93.16	33.73	-58.07	-1.00	-59.08	-13	-46.08
3	129.88	26.86	-64.49	-1.23	-65.73	-13	-52.73
4	239.02	31.61	-63.75	3.82	-59.93	-13	-46.93
5	510.02	33.30	-62.09	2.81	-59.28	-13	-46.28
6	610.16	33.38	-61.31	1.78	-59.53	-13	-46.53

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 13: 5MHz

Mode	TX channel 23230	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	77.03	33.30	-58.61	-1.04	-59.66	-13	-46.66
2	128.33	34.19	-61.17	3.84	-57.33	-13	-44.33
3	278.41	33.24	-62.23	3.78	-58.44	-13	-45.44
4	345.69	30.90	-66.79	3.61	-63.18	-13	-50.18
5	520.68	33.36	-63.82	2.84	-60.98	-13	-47.98
6	736.44	28.76	-67.61	1.02	-66.58	-13	-53.58

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.08	31.70	-55.93	-4.91	-60.84	-13	-47.84
2	92.56	33.86	-57.94	-1.00	-58.95	-13	-45.95
3	129.81	35.10	-56.25	-1.23	-57.49	-13	-44.49
4	237.59	30.11	-65.25	3.82	-61.43	-13	-48.43
5	509.38	35.97	-59.42	2.81	-56.61	-13	-43.61
6	608.99	38.89	-55.80	1.78	-54.02	-13	-41.02

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 13: 10MHz

Mode	TX channel 23230	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	75.79	33.90	-58.01	-1.04	-59.06	-13	-46.06
2	128.49	35.45	-59.91	3.84	-56.07	-13	-43.07
3	278.13	33.18	-62.29	3.78	-58.50	-13	-45.50
4	345.69	31.78	-65.91	3.61	-62.30	-13	-49.30
5	521.18	34.95	-62.23	2.84	-59.39	-13	-46.39
6	736.29	30.29	-66.08	1.02	-65.05	-13	-52.05

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.79	31.10	-56.53	-4.91	-61.44	-13	-48.44
2	92.26	33.87	-57.93	-1.00	-58.94	-13	-45.94
3	127.64	35.27	-56.08	-1.23	-57.32	-13	-44.32
4	238.21	31.21	-64.15	3.82	-60.33	-13	-47.33
5	508.38	34.79	-60.60	2.81	-57.79	-13	-44.79
6	609.14	38.50	-56.19	1.78	-54.41	-13	-41.41

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 17: 5MHz

Mode	TX channel 23790	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.67	33.64	-58.27	-1.04	-59.32	-13	-46.32
2	127.46	34.37	-60.99	3.84	-57.15	-13	-44.15
3	279.36	32.94	-62.53	3.78	-58.74	-13	-45.74
4	345.78	30.53	-67.16	3.61	-63.55	-13	-50.55
5	520.46	34.17	-63.01	2.84	-60.17	-13	-47.17
6	736.48	29.37	-67.00	1.02	-65.97	-13	-52.97

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.78	30.60	-57.03	-4.91	-61.94	-13	-48.94
2	92.66	34.47	-57.33	-1.00	-58.34	-13	-45.34
3	128.34	34.87	-56.48	-1.23	-57.72	-13	-44.72
4	238.31	29.82	-65.54	3.82	-61.72	-13	-48.72
5	507.56	35.08	-60.31	2.81	-57.50	-13	-44.50
6	609.72	38.30	-56.39	1.78	-54.61	-13	-41.61

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 17: 10MHz

Mode	TX channel 23790	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	75.98	33.77	-58.14	-1.04	-59.19	-13	-46.19
2	128.66	34.55	-60.81	3.84	-56.97	-13	-43.97
3	278.3	32.30	-63.17	3.78	-59.38	-13	-46.38
4	345.92	31.42	-66.27	3.61	-62.66	-13	-49.66
5	521.21	34.28	-62.90	2.84	-60.06	-13	-47.06
6	737.24	29.60	-66.77	1.02	-65.74	-13	-52.74

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.37	30.52	-57.11	-4.91	-62.02	-13	-49.02
2	93.1	33.99	-57.81	-1.00	-58.82	-13	-45.82
3	127.06	34.80	-56.55	-1.23	-57.79	-13	-44.79
4	237.66	30.34	-65.02	3.82	-61.20	-13	-48.20
5	508.76	34.94	-60.45	2.81	-57.64	-13	-44.64
6	608.49	38.95	-55.74	1.78	-53.96	-13	-40.96

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 30: 5MHz

Mode	TX channel 27710	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	75.51	32.95	-58.96	-1.04	-60.01	-40	-20.01
2	128.42	34.36	-61.00	3.84	-57.16	-40	-17.16
3	277.72	32.64	-62.83	3.78	-59.04	-40	-19.04
4	344.75	30.84	-66.85	3.61	-63.24	-40	-23.24
5	521.78	33.99	-63.19	2.84	-60.35	-40	-20.35
6	736.68	28.60	-67.77	1.02	-66.74	-40	-27.28

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	68.32	30.62	-57.01	-4.91	-61.92	-40	-21.92
2	92.56	34.24	-57.56	-1.00	-58.57	-40	-18.57
3	130.05	35.03	-56.32	-1.23	-57.56	-40	-17.56
4	238.37	31.09	-64.27	3.82	-60.45	-40	-20.45
5	510.11	36.10	-59.29	2.81	-56.48	-40	-16.48
6	609.51	37.75	-56.94	1.78	-55.16	-40	-15.16

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 30: 10MHz

Mode	TX channel 27710	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.85	33.86	-58.05	-1.04	-59.10	-40	-19.10
2	127.39	35.17	-60.19	3.84	-56.35	-40	-16.35
3	279.17	33.51	-61.96	3.78	-58.17	-40	-18.17
4	345.82	31.94	-65.75	3.61	-62.14	-40	-22.14
5	520.04	34.77	-62.41	2.84	-59.57	-40	-19.57
6	735.56	28.83	-67.54	1.02	-66.51	-40	-26.51

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.37	30.83	-56.80	-4.91	-61.71	-40	-21.71
2	93.06	33.52	-58.28	-1.00	-59.29	-40	-19.29
3	130.55	35.81	-55.54	-1.23	-56.78	-40	-16.78
4	237.95	30.18	-65.18	3.82	-61.36	-40	-21.36
5	510.77	36.16	-59.23	2.81	-56.42	-40	-16.42
6	610.34	39.10	-55.59	1.78	-53.81	-40	-13.81

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 38: 5MHz

Mode	TX channel 38000	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	75.41	33.64	-58.27	-1.04	-59.32	-25	-34.32
2	128.25	34.48	-60.88	3.84	-57.04	-25	-32.04
3	279.16	32.44	-63.03	3.78	-59.24	-25	-34.24
4	345.1	31.00	-66.69	3.61	-63.08	-25	-38.08
5	521.21	33.87	-63.31	2.84	-60.47	-25	-35.47
6	735.57	29.04	-67.33	1.02	-66.30	-25	-41.30

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.19	30.88	-56.75	-4.91	-61.66	-25	-36.66
2	193.36	33.68	-58.12	-1.00	-59.13	-25	-34.13
3	216.12	34.80	-56.55	-1.23	-57.79	-25	-32.79
4	238.55	29.98	-65.38	3.82	-61.56	-25	-36.56
5	423.26	35.96	-59.43	2.81	-56.62	-25	-31.62
6	556.25	38.84	-55.85	1.78	-54.07	-25	-29.07

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 38: 10MHz

Mode	TX channel 38000	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.05	33.86	-58.05	-1.04	-59.10	-25	-34.10
2	127.87	34.01	-61.35	3.84	-57.51	-25	-32.51
3	277.83	32.89	-62.58	3.78	-58.79	-25	-33.79
4	346.67	30.36	-67.33	3.61	-63.72	-25	-38.72
5	520.11	34.02	-63.16	2.84	-60.32	-25	-35.32
6	735.47	28.95	-67.42	1.02	-66.39	-25	-41.39

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.7	31.19	-56.44	-4.91	-61.35	-25	-36.35
2	195.04	33.98	-57.82	-1.00	-58.83	-25	-33.83
3	216.22	34.84	-56.51	-1.23	-57.75	-25	-32.75
4	238.21	29.87	-65.49	3.82	-61.67	-25	-36.67
5	423.78	35.17	-60.22	2.81	-57.41	-25	-32.41
6	557.05	39.11	-55.58	1.78	-53.80	-25	-28.80

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 38: 15MHz

Mode	TX channel 38000	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	75.52	33.65	-58.26	-1.04	-59.31	-25	-34.31
2	128.63	34.57	-60.79	3.84	-56.95	-25	-31.95
3	277.41	31.73	-63.74	3.78	-59.95	-25	-34.95
4	345.54	30.84	-66.85	3.61	-63.24	-25	-38.24
5	521.75	33.82	-63.36	2.84	-60.52	-25	-35.52
6	736.99	29.27	-67.10	1.02	-66.07	-25	-41.07

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	66.26	31.57	-56.06	-4.91	-60.97	-25	-35.97
2	194.43	34.37	-57.43	-1.00	-58.44	-25	-33.44
3	216.72	36.14	-55.21	-1.23	-56.45	-25	-31.45
4	238.13	29.83	-65.53	3.82	-61.71	-25	-36.71
5	424.22	34.96	-60.43	2.81	-57.62	-25	-32.62
6	557.78	37.81	-56.88	1.78	-55.10	-25	-30.10

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 38: 20MHz

Mode	TX channel 38000	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.66	33.86	-58.05	-1.04	-59.10	-25	-34.10
2	127.83	34.33	-61.03	3.84	-57.19	-25	-32.19
3	277.52	32.94	-62.53	3.78	-58.74	-25	-33.74
4	345.66	30.48	-67.21	3.61	-63.60	-25	-38.60
5	521.89	34.01	-63.17	2.84	-60.33	-25	-35.33
6	735.97	29.88	-66.49	1.02	-65.46	-25	-40.46

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	66.9	30.67	-56.96	-4.91	-61.87	-25	-36.87
2	194.07	33.88	-57.92	-1.00	-58.93	-25	-33.93
3	216.69	36.13	-55.22	-1.23	-56.46	-25	-31.46
4	238.32	31.14	-64.22	3.82	-60.40	-25	-35.40
5	422.32	35.44	-59.95	2.81	-57.14	-25	-32.14
6	558.15	37.85	-56.84	1.78	-55.06	-25	-30.06

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 41: 5MHz

Mode	TX channel 40620	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	86.02	34.65	-57.26	-1.04	-58.31	-25	-33.31
2	138.11	35.37	-59.99	3.84	-56.15	-25	-31.15
3	288.23	32.38	-63.09	3.78	-59.30	-25	-34.30
4	345.26	31.79	-65.90	3.61	-62.29	-25	-37.29
5	470.44	35.42	-61.76	2.84	-58.92	-25	-33.92
6	736.96	30.01	-66.36	1.02	-65.33	-25	-40.33

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.69	31.90	-55.73	-4.91	-60.64	-25	-35.64
2	194.55	34.50	-57.30	-1.00	-58.31	-25	-33.31
3	216.27	36.15	-55.20	-1.23	-56.44	-25	-31.44
4	238.61	31.29	-64.07	3.82	-60.25	-25	-35.25
5	422.69	36.19	-59.20	2.81	-56.39	-25	-31.39
6	556.29	39.12	-55.57	1.78	-53.79	-25	-28.79

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 41: 10MHz

Mode	TX channel 40620	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.22	33.82	-58.09	-1.04	-59.14	-25	-34.14
2	127.68	34.13	-61.23	3.84	-57.39	-25	-32.39
3	278.35	33.09	-62.38	3.78	-58.59	-25	-33.59
4	345.66	30.43	-67.26	3.61	-63.65	-25	-38.65
5	521.1	34.03	-63.15	2.84	-60.31	-25	-35.31
6	736.78	29.43	-66.94	1.02	-65.91	-25	-40.91

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	66.95	32.22	-55.41	-4.91	-60.32	-25	-35.32
2	195.37	34.57	-57.23	-1.00	-58.24	-25	-33.24
3	215.5	37.26	-54.09	-1.23	-55.33	-25	-30.33
4	239.17	31.23	-64.13	3.82	-60.31	-25	-35.31
5	422.43	36.05	-59.34	2.81	-56.53	-25	-31.53
6	555.32	39.16	-55.53	1.78	-53.75	-25	-28.75

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 41: 15MHz

Mode	TX channel 40620	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	75.6	32.94	-58.97	-1.04	-60.02	-25	-35.02
2	127.23	34.13	-61.23	3.84	-57.39	-25	-32.39
3	279.28	32.69	-62.78	3.78	-58.99	-25	-33.99
4	345.18	30.99	-66.70	3.61	-63.09	-25	-38.09
5	520.1	33.64	-63.54	2.84	-60.70	-25	-35.70
6	736.43	29.67	-66.70	1.02	-65.67	-25	-40.67

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.31	32.01	-55.62	-4.91	-60.53	-25	-35.53
2	194.79	34.02	-57.78	-1.00	-58.79	-25	-33.79
3	215.93	36.83	-54.52	-1.23	-55.76	-25	-30.76
4	238.64	31.60	-63.76	3.82	-59.94	-25	-34.94
5	422.27	35.82	-59.57	2.81	-56.76	-25	-31.76
6	556.85	38.71	-55.98	1.78	-54.20	-25	-29.20

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 41: 20MHz

Mode	TX channel 40620	Frequency Range	Below 1000 MHz
------	------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	75.57	33.79	-58.12	-1.04	-59.17	-25	-34.17
2	128.57	35.08	-60.28	3.84	-56.44	-25	-31.44
3	279.36	31.83	-63.64	3.78	-59.85	-25	-34.85
4	346.61	31.46	-66.23	3.61	-62.62	-25	-37.62
5	520.43	33.48	-63.70	2.84	-60.86	-25	-35.86
6	735.77	29.93	-66.44	1.02	-65.41	-25	-40.41

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	68.57	31.48	-56.15	-4.91	-61.06	-25	-36.06
2	194.47	33.79	-58.01	-1.00	-59.02	-25	-34.02
3	216.47	36.52	-54.83	-1.23	-56.07	-25	-31.07
4	238.68	30.31	-65.05	3.82	-61.23	-25	-36.23
5	421.99	36.11	-59.28	2.81	-56.47	-25	-31.47
6	555.8	38.19	-56.50	1.78	-54.72	-25	-29.72

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 66: 1.4MHz

Mode	TX channel 132322	Frequency Range	Below 1000 MHz
------	-------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.49	33.69	-58.22	-1.04	-59.27	-13	-46.27
2	126.94	35.13	-60.23	3.84	-56.39	-13	-43.39
3	277.71	32.08	-63.39	3.78	-59.60	-13	-46.60
4	345.72	30.38	-67.31	3.61	-63.70	-13	-50.70
5	520.63	34.09	-63.09	2.84	-60.25	-13	-47.25
6	737.35	30.08	-66.29	1.02	-65.26	-13	-52.26

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.07	31.06	-56.57	-4.91	-61.48	-13	-48.48
2	195.08	34.94	-56.86	-1.00	-57.87	-13	-44.87
3	217.23	37.15	-54.20	-1.23	-55.44	-13	-42.44
4	238.48	31.12	-64.24	3.82	-60.42	-13	-47.42
5	423.06	35.14	-60.25	2.81	-57.44	-13	-44.44
6	556.93	38.62	-56.07	1.78	-54.29	-13	-41.29

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 66: 3MHz

Mode	TX channel 132322	Frequency Range	Below 1000 MHz
------	-------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.6	33.88	-58.03	-1.04	-59.08	-13	-46.08
2	127.13	34.04	-61.32	3.84	-57.48	-13	-44.48
3	278.42	31.98	-63.49	3.78	-59.70	-13	-46.70
4	345.49	31.51	-66.18	3.61	-62.57	-13	-49.57
5	521.71	33.77	-63.41	2.84	-60.57	-13	-47.57
6	736.51	28.96	-67.41	1.02	-66.38	-13	-53.38

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.67	31.89	-55.74	-4.91	-60.65	-13	-47.65
2	194.84	34.67	-57.13	-1.00	-58.14	-13	-45.14
3	216.95	37.56	-53.79	-1.23	-55.03	-13	-42.03
4	239.01	30.26	-65.10	3.82	-61.28	-13	-48.28
5	422.24	35.52	-59.87	2.81	-57.06	-13	-44.06
6	555.41	38.22	-56.47	1.78	-54.69	-13	-41.69

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 66: 5MHz

Mode	TX channel 132322	Frequency Range	Below 1000 MHz
------	-------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.4	32.71	-59.20	-1.04	-60.25	-13	-47.25
2	127.25	34.34	-61.02	3.84	-57.18	-13	-44.18
3	278.61	33.17	-62.30	3.78	-58.51	-13	-45.51
4	346.26	30.45	-67.24	3.61	-63.63	-13	-50.63
5	521.71	33.91	-63.27	2.84	-60.43	-13	-47.43
6	737.09	30.27	-66.10	1.02	-65.07	-13	-52.07

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.78	31.78	-55.85	-4.91	-60.76	-13	-47.76
2	194.1	34.83	-56.97	-1.00	-57.98	-13	-44.98
3	215.31	36.17	-55.18	-1.23	-56.42	-13	-43.42
4	238.32	30.98	-64.38	3.82	-60.56	-13	-47.56
5	422.75	35.97	-59.42	2.81	-56.61	-13	-43.61
6	555.99	39.27	-55.42	1.78	-53.64	-13	-40.64

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 66: 10MHz

Mode	TX channel 132322	Frequency Range	Below 1000 MHz
------	-------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.88	32.93	-58.98	-1.04	-60.03	-13	-47.03
2	127.01	34.78	-60.58	3.84	-56.74	-13	-43.74
3	278.62	33.02	-62.45	3.78	-58.66	-13	-45.66
4	346.51	30.83	-66.86	3.61	-63.25	-13	-50.25
5	521.17	34.62	-62.56	2.84	-59.72	-13	-46.72
6	736.64	29.69	-66.68	1.02	-65.65	-13	-52.65

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	68.47	31.21	-56.42	-4.91	-61.33	-13	-48.33
2	193.72	34.09	-57.71	-1.00	-58.72	-13	-45.72
3	215.78	36.50	-54.85	-1.23	-56.09	-13	-43.09
4	239.36	31.19	-64.17	3.82	-60.35	-13	-47.35
5	421.77	35.31	-60.08	2.81	-57.27	-13	-44.27
6	556.14	39.09	-55.60	1.78	-53.82	-13	-40.82

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 66: 15MHz

Mode	TX channel 132322	Frequency Range	Below 1000 MHz
------	-------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.39	33.30	-58.61	-1.04	-59.66	-13	-46.66
2	127.95	35.09	-60.27	3.84	-56.43	-13	-43.43
3	277.71	32.89	-62.58	3.78	-58.79	-13	-45.79
4	345.02	31.01	-66.68	3.61	-63.07	-13	-50.07
5	520.17	34.29	-62.89	2.84	-60.05	-13	-47.05
6	735.96	29.37	-67.00	1.02	-65.97	-13	-52.97

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	68.08	30.83	-56.80	-4.91	-61.71	-13	-48.71
2	195.47	35.05	-56.75	-1.00	-57.76	-13	-44.76
3	216.34	36.82	-54.53	-1.23	-55.77	-13	-42.77
4	238.68	30.70	-64.66	3.82	-60.84	-13	-47.84
5	423.04	35.92	-59.47	2.81	-56.66	-13	-43.66
6	557.16	38.34	-56.35	1.78	-54.57	-13	-41.57

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 66: 20MHz

Mode	TX channel 132322	Frequency Range	Below 1000 MHz
------	-------------------	-----------------	----------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	76.23	33.23	-58.68	-1.04	-59.73	-13	-46.73
2	127.68	35.10	-60.26	3.84	-56.42	-13	-43.42
3	278.36	33.00	-62.47	3.78	-58.68	-13	-45.68
4	345.74	31.27	-66.42	3.61	-62.81	-13	-49.81
5	520.92	33.83	-63.35	2.84	-60.51	-13	-47.51
6	736.36	29.78	-66.59	1.02	-65.56	-13	-52.56

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	67.49	32.30	-55.33	-4.91	-60.24	-13	-47.24
2	193.65	35.20	-56.60	-1.00	-57.61	-13	-44.61
3	215.89	37.59	-53.76	-1.23	-55.00	-13	-42.00
4	238.66	31.61	-63.75	3.82	-59.93	-13	-46.93
5	423.27	36.57	-58.82	2.81	-56.01	-13	-43.01
6	557.07	39.32	-55.37	1.78	-53.59	-13	-40.59

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

ABOVE 1GHz

WCDMA:

Mode	TX channel 1413	Frequency Range	Above 1000MHz
------	-----------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3465.2	36.21	-67.94	7.68	-60.26	-13	-47.26
2	5197.8	39.86	-64.88	7.02	-57.86	-13	-44.86
3	6930.4	45.80	-56.82	4.53	-52.29	-13	-39.29
4	8663	47.41	-54.46	4.21	-50.26	-13	-37.26
5	10395.6	48.64	-52.85	3.48	-49.37	-13	-36.37
6	12128.2	48.3	-52.31	4.06	-48.24	-13	-35.24
7	13860.8	48.65	-48.70	3.70	-45.00	-13	-32.00
8	15593.4	48.91	-48.44	3.70	-44.74	-13	-31.74
9	17326	47.57	-49.78	3.70	-46.08	-13	-33.08

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3465.2	34.3	-70.04	7.87	-62.17	-13	-49.17
2	5197.8	37.76	-67.29	7.33	-59.96	-13	-46.96
3	6930.4	45.41	-57.71	5.03	-52.68	-13	-39.68
4	8663	48.36	-53.65	4.34	-49.31	-13	-36.31
5	10395.6	48.68	-51.58	2.24	-49.33	-13	-36.33
6	12128.2	47.67	-53.13	4.26	-48.87	-13	-35.87
7	13860.8	49.39	-46.28	2.03	-44.26	-13	-31.26
8	15593.4	49.34	-48.01	3.70	-44.31	-13	-31.31
9	17326	47.17	-50.18	3.70	-46.48	-13	-33.48

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 4: 1.4MHz

Mode	TX channel 20175	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3465	46.09	-57.07	7.80	-49.27	-13	-36.27
2	5197.5	41.80	-62.73	7.05	-55.67	-13	-42.67
3	6930	35.76	-66.56	5.10	-61.45	-13	-48.45
4	8662.5	38.27	-64.44	4.23	-60.21	-13	-47.21
5	10395	39.52	-62.48	3.67	-58.81	-13	-45.81
6	12127.5	41.61	-59.87	4.38	-55.49	-13	-42.49
7	13860	41.99	-61.68	5.71	-55.96	-13	-42.96
8	15592.5	44.32	-53.03	3.70	-49.33	-13	-36.33
9	17325	47.44	-49.91	3.70	-46.21	-13	-33.21

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3465	41.88	-61.28	7.80	-53.48	-13	-40.48
2	5197.5	41.76	-62.77	7.05	-55.71	-13	-42.71
3	6930	36.73	-65.59	5.10	-60.48	-13	-47.48
4	8662.5	38.39	-64.32	4.23	-60.09	-13	-47.09
5	10395	38.65	-63.35	3.67	-59.68	-13	-46.68
6	12127.5	39.02	-62.46	4.38	-58.08	-13	-45.08
7	13860	42.17	-57.48	2.47	-55.02	-13	-42.02
8	15592.5	44.07	-53.28	3.70	-49.58	-13	-36.58
9	17325	45.7	-51.65	3.70	-47.95	-13	-34.95

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 4: 3MHz

Mode	TX channel 20175	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3465	47.43	-55.73	7.80	-47.93	-13	-34.93
2	5197.5	43.21	-61.32	7.05	-54.26	-13	-41.26
3	6930	36.21	-66.11	5.10	-61.00	-13	-48.00
4	8662.5	37.9	-64.81	4.23	-60.58	-13	-47.58
5	10395	39.17	-62.83	3.67	-59.16	-13	-46.16
6	12127.5	43.48	-58.00	4.38	-53.62	-13	-40.62
7	13860	42.83	-60.84	5.71	-55.12	-13	-42.12
8	15592.5	45.55	-51.80	3.70	-48.10	-13	-35.10
9	17325	46.89	-50.46	3.70	-46.76	-13	-33.76

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3465	42.15	-61.01	7.80	-53.21	-13	-40.21
2	5197.5	42	-62.53	7.05	-55.47	-13	-42.47
3	6930	36.65	-65.67	5.10	-60.56	-13	-47.56
4	8662.5	39.23	-63.48	4.23	-59.25	-13	-46.25
5	10395	39.1	-62.90	3.67	-59.23	-13	-46.23
6	12127.5	39.14	-62.34	4.38	-57.96	-13	-44.96
7	13860	41.61	-58.04	2.47	-55.58	-13	-42.58
8	15592.5	43.34	-54.01	3.70	-50.31	-13	-37.31
9	17325	45.97	-51.38	3.70	-47.68	-13	-34.68

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 4: 5MHz

Mode	TX channel 20175	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3465	46.10	-57.06	7.80	-49.26	-13	-36.26
2	5197.5	43.07	-61.46	7.05	-54.40	-13	-41.40
3	6930	35.70	-66.62	5.10	-61.51	-13	-48.51
4	8662.5	36.8	-65.91	4.23	-61.68	-13	-48.68
5	10395	38.93	-63.07	3.67	-59.40	-13	-46.40
6	12127.5	43.3	-58.18	4.38	-53.80	-13	-40.80
7	13860	43.21	-60.46	5.71	-54.74	-13	-41.74
8	15592.5	45.64	-51.71	3.70	-48.01	-13	-35.01
9	17325	46.72	-50.63	3.70	-46.93	-13	-33.93

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3465	41.48	-61.68	7.80	-53.88	-13	-40.88
2	5197.5	40.96	-63.57	7.05	-56.51	-13	-43.51
3	6930	36.98	-65.34	5.10	-60.23	-13	-47.23
4	8662.5	39.28	-63.43	4.23	-59.20	-13	-46.20
5	10395	39.11	-62.89	3.67	-59.22	-13	-46.22
6	12127.5	38.55	-62.93	4.38	-58.55	-13	-45.55
7	13860	42.2	-57.45	2.47	-54.99	-13	-41.99
8	15592.5	42.84	-54.51	3.70	-50.81	-13	-37.81
9	17325	45.96	-51.39	3.70	-47.69	-13	-34.69

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 4: 10MHz

Mode	TX channel 20175	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3465	46.93	-56.23	7.80	-48.43	-13	-35.43
2	5197.5	42.39	-62.14	7.05	-55.08	-13	-42.08
3	6930	35.93	-66.39	5.10	-61.28	-13	-48.28
4	8662.5	37.73	-64.98	4.23	-60.75	-13	-47.75
5	10395	39.51	-62.49	3.67	-58.82	-13	-45.82
6	12127.5	43.38	-58.10	4.38	-53.72	-13	-40.72
7	13860	42.14	-61.53	5.71	-55.81	-13	-42.81
8	15592.5	43.92	-53.43	3.70	-49.73	-13	-36.73
9	17325	47.39	-49.96	3.70	-46.26	-13	-33.26
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3465	41.77	-61.39	7.80	-53.59	-13	-40.59
2	5197.5	40.6	-63.93	7.05	-56.87	-13	-43.87
3	6930	36.72	-65.60	5.10	-60.49	-13	-47.49
4	8662.5	38.32	-64.39	4.23	-60.16	-13	-47.16
5	10395	38.7	-63.30	3.67	-59.63	-13	-46.63
6	12127.5	38.76	-62.72	4.38	-58.34	-13	-45.34
7	13860	40.84	-58.81	2.47	-56.35	-13	-43.35
8	15592.5	43.18	-54.17	3.70	-50.47	-13	-37.47
9	17325	46.78	-50.57	3.70	-46.87	-13	-33.87

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 4: 15MHz

Mode	TX channel 20175	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3465	46.83	-56.33	7.80	-48.53	-13	-35.53
2	5197.5	42.68	-61.85	7.05	-54.79	-13	-41.79
3	6930	35.75	-66.57	5.10	-61.46	-13	-48.46
4	8662.5	37.03	-65.68	4.23	-61.45	-13	-48.45
5	10395	39.36	-62.64	3.67	-58.97	-13	-45.97
6	12127.5	41.93	-59.55	4.38	-55.17	-13	-42.17
7	13860	41.46	-62.21	5.71	-56.49	-13	-43.49
8	15592.5	44.61	-52.74	3.70	-49.04	-13	-36.04
9	17325	47.91	-49.44	3.70	-45.74	-13	-32.74

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3465	41.92	-61.24	7.80	-53.44	-13	-40.44
2	5197.5	41.6	-62.93	7.05	-55.87	-13	-42.87
3	6930	37.38	-64.94	5.10	-59.83	-13	-46.83
4	8662.5	38.8	-63.91	4.23	-59.68	-13	-46.68
5	10395	38.09	-63.91	3.67	-60.24	-13	-47.24
6	12127.5	38.48	-63.00	4.38	-58.62	-13	-45.62
7	13860	40.77	-58.88	2.47	-56.42	-13	-43.42
8	15592.5	44.37	-52.98	3.70	-49.28	-13	-36.28
9	17325	46.27	-51.08	3.70	-47.38	-13	-34.38

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 4: 20MHz

Mode	TX channel 20175	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3465	45.57	-57.59	7.80	-49.79	-13	-36.79
2	5197.5	41.76	-62.77	7.05	-55.71	-13	-42.71
3	6930	36.34	-65.98	5.10	-60.87	-13	-47.87
4	8662.5	37.91	-64.80	4.23	-60.57	-13	-47.57
5	10395	39.42	-62.58	3.67	-58.91	-13	-45.91
6	12127.5	43.15	-58.33	4.38	-53.95	-13	-40.95
7	13860	42.37	-61.30	5.71	-55.58	-13	-42.58
8	15592.5	44.76	-52.59	3.70	-48.89	-13	-35.89
9	17325	47.09	-50.26	3.70	-46.56	-13	-33.56

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3465	40.41	-62.75	7.80	-54.95	-13	-41.95
2	5197.5	40.49	-64.04	7.05	-56.98	-13	-43.98
3	6930	37.3	-65.02	5.10	-59.91	-13	-46.91
4	8662.5	38.56	-64.15	4.23	-59.92	-13	-46.92
5	10395	38.39	-63.61	3.67	-59.94	-13	-46.94
6	12127.5	38.32	-63.16	4.38	-58.78	-13	-45.78
7	13860	40.72	-58.93	2.47	-56.47	-13	-43.47
8	15592.5	43.31	-54.04	3.70	-50.34	-13	-37.34
9	17325	46.32	-51.03	3.70	-47.33	-13	-34.33

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 7: 5MHz

Mode	TX channel 21100	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5070	46.61	-57.73	7.02	-50.70	-25	-25.70
2	7605	43.14	-59.48	4.46	-55.02	-25	-30.02
3	10140	36.33	-65.39	3.91	-61.48	-25	-36.48
4	12675	37.57	-63.76	4.38	-59.39	-25	-34.39
5	15210	39.07	-58.28	3.70	-54.58	-25	-29.58
6	17745	42.45	-54.90	3.70	-51.20	-25	-26.20

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5070	41.85	-62.49	7.02	-55.46	-25	-30.46
2	7605	40.23	-62.39	4.46	-57.93	-25	-32.93
3	10140	36.46	-65.26	3.91	-61.35	-25	-36.35
4	12675	39.48	-61.85	4.38	-57.48	-25	-32.48
5	15210	38.7	-58.65	3.70	-54.95	-25	-29.95
6	17745	39.63	-57.72	3.70	-54.02	-25	-29.02

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 7: 10MHz

Mode	TX channel 21100	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5070	47.42	-56.92	7.02	-49.89	-25	-24.89
2	7605	41.86	-60.76	4.46	-56.30	-25	-31.30
3	10140	35.38	-66.34	3.91	-62.43	-25	-37.43
4	12675	37.56	-63.77	4.38	-59.40	-25	-34.40
5	15210	39.11	-58.24	3.70	-54.54	-25	-29.54
6	17745	43.2	-54.15	3.70	-50.45	-25	-25.45

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5070	41.41	-62.93	7.02	-55.90	-25	-30.90
2	7605	41.88	-60.74	4.46	-56.28	-25	-31.28
3	10140	37.83	-63.89	3.91	-59.98	-25	-34.98
4	12675	38.05	-63.28	4.38	-58.91	-25	-33.91
5	15210	39.58	-57.77	3.70	-54.07	-25	-29.07
6	17745	37.93	-59.42	3.70	-55.72	-25	-30.72

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 7: 15MHz

Mode	TX channel 21100	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5070	46.94	-57.40	7.02	-50.37	-25	-25.37
2	7605	42.87	-59.75	4.46	-55.29	-25	-30.29
3	10140	35.72	-66.00	3.91	-62.09	-25	-37.09
4	12675	38.49	-62.84	4.38	-58.47	-25	-33.47
5	15210	39.13	-58.22	3.70	-54.52	-25	-29.52
6	17745	42.26	-55.09	3.70	-51.39	-25	-26.39

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5070	41.7	-62.64	7.02	-55.61	-25	-30.61
2	7605	41.11	-61.51	4.46	-57.05	-25	-32.05
3	10140	37.52	-64.20	3.91	-60.29	-25	-35.29
4	12675	37.6	-63.73	4.38	-59.36	-25	-34.36
5	15210	39.32	-58.03	3.70	-54.33	-25	-29.33
6	17745	37.9	-59.45	3.70	-55.75	-25	-30.75

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 7:20MHz

Mode	TX channel 21100	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5070	45.62	-58.72	7.02	-51.69	-25	-26.69
2	7605	42.74	-59.88	4.46	-55.42	-25	-30.42
3	10140	36.38	-65.34	3.91	-61.43	-25	-36.43
4	12675	37.96	-63.37	4.38	-59.00	-25	-34.00
5	15210	40.13	-57.22	3.70	-53.52	-25	-28.52
6	17745	42.82	-54.53	3.70	-50.83	-25	-25.83

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5070	40.45	-63.89	7.02	-56.86	-25	-31.86
2	7605	41.19	-61.43	4.46	-56.97	-25	-31.97
3	10140	37.82	-63.90	3.91	-59.99	-25	-34.99
4	12675	38.22	-63.11	4.38	-58.74	-25	-33.74
5	15210	39.13	-58.22	3.70	-54.52	-25	-29.52
6	17745	38.98	-58.37	3.70	-54.67	-25	-29.67

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 12: 1.4MHz

Mode	TX channel 23095	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1415	47.51	-56.21	5.58	-50.63	-13	-37.63
2	2122.5	42.86	-57.51	6.84	-50.68	-13	-37.68
3	2830	36.19	-64.99	6.97	-58.02	-13	-45.02
4	3537.5	38.04	-65.30	7.82	-57.47	-13	-44.47
5	4245	39.17	-65.23	7.04	-58.19	-13	-45.19
6	4952.5	41.91	-62.35	7.04	-55.31	-13	-42.31
7	5660	41.87	-61.80	5.71	-56.08	-13	-43.08
8	6367.5	45.56	-58.58	6.15	-52.43	-13	-39.43
9	7075	47.06	-54.64	4.83	-49.81	-13	-36.81
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1415	40.72	-63.00	5.58	-57.42	-13	-44.42
2	2122.5	41.22	-59.15	6.84	-52.32	-13	-39.32
3	2830	36.48	-64.70	6.97	-57.73	-13	-44.73
4	3537.5	38.80	-64.54	7.82	-56.71	-13	-43.71
5	4245	39.29	-65.11	7.04	-58.07	-13	-45.07
6	4952.5	38.39	-65.87	7.04	-58.83	-13	-45.83
7	5660	40.79	-63.92	7.01	-56.91	-13	-43.91
8	6367.5	43.28	-60.86	6.15	-54.71	-13	-41.71
9	7075	47.12	-54.58	4.83	-49.75	-13	-36.75

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 12: 3MHz

Mode	TX channel 23095	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1415	45.82	-57.90	5.58	-52.32	-13	-39.32
2	2122.5	42.52	-57.85	6.84	-51.02	-13	-38.02
3	2830	35.37	-65.81	6.97	-58.84	-13	-45.84
4	3537.5	37.85	-65.49	7.82	-57.66	-13	-44.66
5	4245	38.69	-65.71	7.04	-58.67	-13	-45.67
6	4952.5	43.07	-61.19	7.04	-54.15	-13	-41.15
7	5660	42.82	-60.85	5.71	-55.13	-13	-42.13
8	6367.5	45.21	-58.93	6.15	-52.78	-13	-39.78
9	7075	46.62	-55.08	4.83	-50.25	-13	-37.25

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1415	41.90	-61.82	5.58	-56.24	-13	-43.24
2	2122.5	40.73	-59.64	6.84	-52.81	-13	-39.81
3	2830	37.62	-63.56	6.97	-56.59	-13	-43.59
4	3537.5	38.49	-64.85	7.82	-57.02	-13	-44.02
5	4245	39.54	-64.86	7.04	-57.82	-13	-44.82
6	4952.5	39.76	-64.50	7.04	-57.46	-13	-44.46
7	5660	41.04	-63.67	7.01	-56.66	-13	-43.66
8	6367.5	43.17	-60.97	6.15	-54.82	-13	-41.82
9	7075	46.07	-55.63	4.83	-50.80	-13	-37.80

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 12: 5MHz

Mode	TX channel 23095	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1415	46.32	-57.40	5.58	-51.82	-13	-38.82
2	2122.5	43.11	-57.26	6.84	-50.43	-13	-37.43
3	2830	35.82	-65.36	6.97	-58.39	-13	-45.39
4	3537.5	37.55	-65.79	7.82	-57.96	-13	-44.96
5	4245	39.11	-65.29	7.04	-58.25	-13	-45.25
6	4952.5	42.75	-61.51	7.04	-54.47	-13	-41.47
7	5660	41.53	-62.14	5.71	-56.42	-13	-43.42
8	6367.5	45.49	-58.65	6.15	-52.50	-13	-39.50
9	7075	47.43	-54.27	4.83	-49.44	-13	-36.44

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1415	41.86	-61.86	5.58	-56.28	-13	-43.28
2	2122.5	42.13	-58.24	6.84	-51.41	-13	-38.41
3	2830	37.54	-63.64	6.97	-56.67	-13	-43.67
4	3537.5	38.48	-64.86	7.82	-57.03	-13	-44.03
5	4245	39.47	-64.93	7.04	-57.89	-13	-44.89
6	4952.5	37.98	-66.28	7.04	-59.24	-13	-46.24
7	5660	42.29	-62.42	7.01	-55.41	-13	-42.41
8	6367.5	42.99	-61.15	6.15	-55.00	-13	-42.00
9	7075	46.46	-55.24	4.83	-50.41	-13	-37.41

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 12: 10MHz

Mode	TX channel 23095	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1415	45.69	-58.03	5.58	-52.45	-13	-39.45
2	2122.5	43.06	-57.31	6.84	-50.48	-13	-37.48
3	2830	35.80	-65.38	6.97	-58.41	-13	-45.41
4	3537.5	38.63	-64.71	7.82	-56.88	-13	-43.88
5	4245	39.27	-65.13	7.04	-58.09	-13	-45.09
6	4952.5	41.73	-62.53	7.04	-55.49	-13	-42.49
7	5660	43.01	-60.66	5.71	-54.94	-13	-41.94
8	6367.5	45.31	-58.83	6.15	-52.68	-13	-39.68
9	7075	47.62	-54.08	4.83	-49.25	-13	-36.25

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1415	41.42	-62.30	5.58	-56.72	-13	-43.72
2	2122.5	40.99	-59.38	6.84	-52.55	-13	-39.55
3	2830	36.78	-64.40	6.97	-57.43	-13	-44.43
4	3537.5	37.63	-65.71	7.82	-57.88	-13	-44.88
5	4245	38.07	-66.33	7.04	-59.29	-13	-46.29
6	4952.5	38.41	-65.85	7.04	-58.81	-13	-45.81
7	5660	42.32	-62.39	7.01	-55.38	-13	-42.38
8	6367.5	42.73	-61.41	6.15	-55.26	-13	-42.26
9	7075	46.20	-55.50	4.83	-50.67	-13	-37.67

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 13: 5MHz

Mode	TX channel 23230	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1564	46.62	-56.55	6.11	-50.44	-13	-37.44
2	2346	43.18	-56.05	6.73	-49.32	-13	-36.32
3	3128	35.42	-67.33	7.32	-60.01	-13	-47.01
4	3910	38.66	-66.04	7.58	-58.46	-13	-45.46
5	4692	38.64	-65.77	7.19	-58.58	-13	-45.58
6	5474	41.88	-63.06	7.11	-55.95	-13	-42.95
7	6256	42.82	-60.85	5.71	-55.13	-13	-42.13
8	7038	44.7	-57.37	4.94	-52.43	-13	-39.43
9	7820	47.81	-54.81	4.27	-50.54	-13	-37.54

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1564	40.66	-62.51	6.11	-56.40	-13	-43.40
2	2346	40.71	-58.52	6.73	-51.79	-13	-38.79
3	3128	37.31	-65.44	7.32	-58.12	-13	-45.12
4	3910	38.23	-66.47	7.58	-58.89	-13	-45.89
5	4692	39.33	-65.08	7.19	-57.89	-13	-44.89
6	5474	39.81	-65.13	7.11	-58.02	-13	-45.02
7	6256	42.65	-61.49	6.34	-55.15	-13	-42.15
8	7038	43.09	-58.98	4.94	-54.04	-13	-41.04
9	7820	46.4	-56.22	4.27	-51.95	-13	-38.95

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 13: 10MHz

Mode	TX channel 23230	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1564	46.64	-56.53	6.11	-50.42	-13	-37.42
2	2346	43.49	-55.74	6.73	-49.01	-13	-36.01
3	3128	35.43	-67.32	7.32	-60.00	-13	-47.00
4	3910	36.78	-67.92	7.58	-60.34	-13	-47.34
5	4692	39.94	-64.47	7.19	-57.28	-13	-44.28
6	5474	42.14	-62.80	7.11	-55.69	-13	-42.69
7	6256	42.88	-60.79	5.71	-55.07	-13	-42.07
8	7038	44.34	-57.73	4.94	-52.79	-13	-39.79
9	7820	46.25	-56.37	4.27	-52.10	-13	-39.10

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1564	40.74	-62.43	6.11	-56.32	-13	-43.32
2	2346	41.46	-57.77	6.73	-51.04	-13	-38.04
3	3128	37.65	-65.10	7.32	-57.78	-13	-44.78
4	3910	37.96	-66.74	7.58	-59.16	-13	-46.16
5	4692	38.69	-65.72	7.19	-58.53	-13	-45.53
6	5474	39.32	-65.62	7.11	-58.51	-13	-45.51
7	6256	42.09	-62.05	6.34	-55.71	-13	-42.71
8	7038	42.81	-59.26	4.94	-54.32	-13	-41.32
9	7820	45.95	-56.67	4.27	-52.40	-13	-39.40

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 17: 5MHz

Mode	TX channel 23790	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1420	45.89	-57.82	5.61	-52.21	-13	-39.21
2	2130	43.35	-56.98	6.83	-50.15	-13	-37.15
3	2840	37.02	-64.24	6.98	-57.26	-13	-44.26
4	3550	37.69	-65.69	7.82	-57.88	-13	-44.88
5	4260	39.91	-64.47	7.03	-57.44	-13	-44.44
6	4970	41.57	-62.68	7.03	-55.65	-13	-42.65
7	5680	42.93	-60.74	5.71	-55.02	-13	-42.02
8	6390	44.07	-60.07	6.11	-53.96	-13	-40.96
9	7100	47.25	-54.35	4.78	-49.57	-13	-36.57

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1420	41.45	-62.26	5.61	-56.65	-13	-43.65
2	2130	41.43	-58.90	6.83	-52.07	-13	-39.07
3	2840	36.62	-64.64	6.98	-57.66	-13	-44.66
4	3550	38.37	-65.01	7.82	-57.20	-13	-44.20
5	4260	38.49	-65.89	7.03	-58.86	-13	-45.86
6	4970	39.21	-65.04	7.03	-58.01	-13	-45.01
7	5680	42.28	-62.40	6.99	-55.40	-13	-42.40
8	6390	43.98	-60.16	6.11	-54.05	-13	-41.05
9	7100	46.09	-55.51	4.78	-50.73	-13	-37.73

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 17: 10MHz

Mode	TX channel 23790	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1413	46.47	-57.25	5.57	-51.68	-13	-38.68
2	2119.5	42.74	-57.65	6.84	-50.81	-13	-37.81
3	2826	36.56	-64.59	6.96	-57.62	-13	-44.62
4	3532.5	37.13	-66.19	7.83	-58.36	-13	-45.36
5	4239	38.58	-65.83	7.04	-58.79	-13	-45.79
6	4945.5	42.24	-62.02	7.04	-54.98	-13	-41.98
7	5652	42.66	-61.01	5.71	-55.29	-13	-42.29
8	6358.5	45.29	-58.85	6.17	-52.68	-13	-39.68
9	7065	46.84	-54.90	4.85	-50.06	-13	-37.06

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	1413	41.42	-62.30	5.57	-56.73	-13	-43.73
2	2119.5	41.59	-58.80	6.84	-51.96	-13	-38.96
3	2826	37.57	-63.58	6.96	-56.61	-13	-43.61
4	3532.5	39.14	-64.18	7.83	-56.35	-13	-43.35
5	4239	38.38	-66.03	7.04	-58.99	-13	-45.99
6	4945.5	39.71	-64.55	7.04	-57.51	-13	-44.51
7	5652	41.8	-62.92	7.01	-55.91	-13	-42.91
8	6358.5	43.34	-60.80	6.17	-54.63	-13	-41.63
9	7065	45.47	-56.27	4.85	-51.43	-13	-38.43

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 30: 5MHz

Mode	TX channel 27710	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5070	44.30	-60.04	7.02	-53.01	-40	-13.01
2	7605	47.90	-54.72	4.46	-50.26	-40	-10.26
3	10140	44.70	-57.02	3.91	-53.11	-40	-13.11
4	12675	36.4	-64.93	4.38	-60.56	-40	-20.56
5	15210	38.56	-58.79	3.70	-55.09	-40	-15.09
6	17745	39.51	-57.84	3.70	-54.14	-40	-14.14

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5070	43.2	-61.14	7.02	-54.11	-40	-14.11
2	7605	45.3	-57.32	4.46	-52.86	-40	-12.86
3	10140	44.2	-57.52	3.91	-53.61	-40	-13.61
4	12675	35.1	-66.23	4.38	-61.86	-40	-21.86
5	15210	37.21	-60.14	3.70	-56.44	-40	-16.44
6	17745	38.94	-58.41	3.70	-54.71	-40	-14.71

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 30: 10MHz

Mode	TX channel 27710	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5070	44.95	-59.39	7.02	-52.36	-40	-12.36
2	7605	47.15	-55.47	4.46	-51.01	-40	-11.01
3	10140	44.88	-56.84	3.91	-52.93	-40	-12.93
4	12675	37.11	-64.22	4.38	-59.85	-40	-19.85
5	15210	39.17	-58.18	3.70	-54.48	-40	-14.48
6	17745	40.32	-57.03	3.70	-53.33	-40	-13.33

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5070	43.23	-61.11	7.02	-54.08	-40	-14.08
2	7605	44.87	-57.75	4.46	-53.29	-40	-13.29
3	10140	43.93	-57.79	3.91	-53.88	-40	-13.88
4	12675	34.27	-67.06	4.38	-62.69	-40	-22.69
5	15210	38.08	-59.27	3.70	-55.57	-40	-15.57
6	17745	38.71	-58.64	3.70	-54.94	-40	-14.94

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 38: 5MHz

Mode	TX channel 38000	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5190	46.58	-57.94	7.05	-50.88	-25	-25.88
2	7785	41.85	-60.77	4.30	-56.47	-25	-31.47
3	10380	35.74	-66.25	3.68	-62.56	-25	-37.56
4	12975	38.36	-62.51	4.44	-58.07	-25	-33.07
5	15570	38.59	-58.76	3.70	-55.06	-25	-30.06

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5190	42.07	-62.45	7.05	-55.39	-25	-30.39
2	7785	41.47	-61.15	4.30	-56.85	-25	-31.85
3	10380	37.41	-64.58	3.68	-60.89	-25	-35.89
4	12975	38.07	-62.80	4.44	-58.36	-25	-33.36
5	15570	38.84	-58.51	3.70	-54.81	-25	-29.81

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 38: 10MHz

Mode	TX channel 38000	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5190	47.50	-57.02	7.05	-49.96	-25	-24.96
2	7785	43.20	-59.42	4.30	-55.12	-25	-30.12
3	10380	35.37	-66.62	3.68	-62.93	-25	-37.93
4	12975	38.59	-62.28	4.44	-57.84	-25	-32.84
5	15570	38.73	-58.62	3.70	-54.92	-25	-29.92

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5190	41.09	-63.43	7.05	-56.37	-25	-31.37
2	7785	40.38	-62.24	4.30	-57.94	-25	-32.94
3	10380	37.85	-64.14	3.68	-60.45	-25	-35.45
4	12975	38.73	-62.14	4.44	-57.70	-25	-32.70
5	15570	39.53	-57.82	3.70	-54.12	-25	-29.12

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 38: 15MHz

Mode	TX channel 38000	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5190	46.79	-57.73	7.05	-50.67	-25	-25.67
2	7785	42.96	-59.66	4.30	-55.36	-25	-30.36
3	10380	36.18	-65.81	3.68	-62.12	-25	-37.12
4	12975	38.06	-62.81	4.44	-58.37	-25	-33.37
5	15570	39.05	-58.30	3.70	-54.60	-25	-29.60

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5190	41.07	-63.45	7.05	-56.39	-25	-31.39
2	7785	40.28	-62.34	4.30	-58.04	-25	-33.04
3	10380	37.39	-64.60	3.68	-60.91	-25	-35.91
4	12975	37.75	-63.12	4.44	-58.68	-25	-33.68
5	15570	38.67	-58.68	3.70	-54.98	-25	-29.98

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 38: 20MHz

Mode	TX channel 38000	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5190	45.59	-58.93	7.05	-51.87	-25	-26.87
2	7785	43.25	-59.37	4.30	-55.07	-25	-30.07
3	10380	37.28	-64.71	3.68	-61.02	-25	-36.02
4	12975	37.81	-63.06	4.44	-58.62	-25	-33.62
5	15570	39.98	-57.37	3.70	-53.67	-25	-28.67

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5190	42.04	-62.48	7.05	-55.42	-25	-30.42
2	7785	41.54	-61.08	4.30	-56.78	-25	-31.78
3	10380	37.15	-64.84	3.68	-61.15	-25	-36.15
4	12975	38.65	-62.22	4.44	-57.78	-25	-32.78
5	15570	39.52	-57.83	3.70	-54.13	-25	-29.13

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 41: 5MHz

Mode	TX channel 40620	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5186	46.43	-58.08	7.05	-51.03	-25	-26.03
2	7779	43.08	-59.54	4.31	-55.23	-25	-30.23
3	10372	36.52	-65.46	3.69	-61.77	-25	-36.77
4	12965	38.71	-62.17	4.44	-57.74	-25	-32.74
5	15558	39.83	-57.52	3.70	-53.82	-25	-28.82

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5186	41.26	-63.25	7.05	-56.20	-25	-31.20
2	7779	42.17	-60.45	4.31	-56.14	-25	-31.14
3	10372	36.67	-65.31	3.69	-61.62	-25	-36.62
4	12965	39.01	-61.87	4.44	-57.44	-25	-32.44
5	15558	38.3	-59.05	3.70	-55.35	-25	-30.35

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 41: 10MHz

Mode	TX channel 40620	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5186	45.98	-58.53	7.05	-51.48	-25	-26.48
2	7779	43.11	-59.51	4.31	-55.20	-25	-30.20
3	10372	35.84	-66.14	3.69	-62.45	-25	-37.45
4	12965	37.45	-63.43	4.44	-59.00	-25	-34.00
5	15558	39.95	-57.40	3.70	-53.70	-25	-28.70

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5186	41.18	-63.33	7.05	-56.28	-25	-31.28
2	7779	41.03	-61.59	4.31	-57.28	-25	-32.28
3	10372	37.57	-64.41	3.69	-60.72	-25	-35.72
4	12965	38	-62.88	4.44	-58.45	-25	-33.45
5	15558	38.12	-59.23	3.70	-55.53	-25	-30.53

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 41: 15MHz

Mode	TX channel 40620	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5186	46.77	-57.74	7.05	-50.69	-25	-25.69
2	7779	43.53	-59.09	4.31	-54.78	-25	-29.78
3	10372	36.10	-65.88	3.69	-62.19	-25	-37.19
4	12965	37.82	-63.06	4.44	-58.63	-25	-33.63
5	15558	40.16	-57.19	3.70	-53.49	-25	-28.49

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5186	40.97	-63.54	7.05	-56.49	-25	-31.49
2	7779	40.99	-61.63	4.31	-57.32	-25	-32.32
3	10372	36.49	-65.49	3.69	-61.80	-25	-36.80
4	12965	38.32	-62.56	4.44	-58.13	-25	-33.13
5	15558	38.16	-59.19	3.70	-55.49	-25	-30.49

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 41: 20MHz

Mode	TX channel 40620	Frequency Range	Above 1000MHz
------	------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5186	45.67	-58.84	7.05	-51.79	-25	-30.75
2	7779	43.52	-59.10	4.31	-54.79	-25	-32.80
3	10372	35.76	-66.22	3.69	-62.53	-25	-37.06
4	12965	37.95	-62.93	4.44	-58.50	-25	-32.37
5	15558	39.49	-57.86	3.70	-54.16	-25	-29.01

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	5186	41.71	-62.80	7.05	-55.75	-25	-26.79
2	7779	40.51	-62.11	4.31	-57.80	-25	-29.79
3	10372	36.23	-65.75	3.69	-62.06	-25	-37.53
4	12965	39.08	-61.80	4.44	-57.37	-25	-33.50
5	15558	39.64	-57.71	3.70	-54.01	-25	-29.16

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 66: 1.4MHz

Mode	TX channel 132322	Frequency Range	Above 1000MHz
------	-------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3490	47.21	-55.95	7.85	-48.10	-13	-35.10
2	5235	43.07	-61.51	7.06	-54.45	-13	-41.45
3	6980	35.37	-66.73	5.01	-61.73	-13	-48.73
4	8725	38.22	-64.52	4.24	-60.28	-13	-47.28
5	10470	39.98	-62.11	3.60	-58.51	-13	-45.51
6	12215	43.49	-58.02	4.37	-53.65	-13	-40.65
7	13960	41.87	-61.80	5.71	-56.08	-13	-43.08
8	15705	44.51	-52.84	3.70	-49.14	-13	-36.14
9	17450	47.74	-49.61	3.70	-45.91	-13	-32.91

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3490	42.23	-60.93	7.85	-53.08	-13	-40.08
2	5235	41.42	-63.16	7.06	-56.10	-13	-43.10
3	6980	36.45	-65.65	5.01	-60.65	-13	-47.65
4	8725	37.99	-64.75	4.24	-60.51	-13	-47.51
5	10470	38.87	-63.22	3.60	-59.62	-13	-46.62
6	12215	38.69	-62.82	4.37	-58.45	-13	-45.45
7	13960	42.04	-57.48	2.25	-55.24	-13	-42.24
8	15705	43.8	-53.55	3.70	-49.85	-13	-36.85
9	17450	46.21	-51.14	3.70	-47.44	-13	-34.44

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 66: 3MHz

Mode	TX channel 132322	Frequency Range	Above 1000MHz
------	-------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3490	46.55	-56.61	7.85	-48.76	-13	-35.76
2	5235	42.71	-61.87	7.06	-54.81	-13	-41.81
3	6980	36.29	-65.81	5.01	-60.81	-13	-47.81
4	8725	37.78	-64.96	4.24	-60.72	-13	-47.72
5	10470	39.25	-62.84	3.60	-59.24	-13	-46.24
6	12215	42.52	-58.99	4.37	-54.62	-13	-41.62
7	13960	42.43	-61.24	5.71	-55.52	-13	-42.52
8	15705	44.72	-52.63	3.70	-48.93	-13	-35.93
9	17450	47.06	-50.29	3.70	-46.59	-13	-33.59

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3490	41.29	-61.87	7.85	-54.02	-13	-41.02
2	5235	41.17	-63.41	7.06	-56.35	-13	-43.35
3	6980	36.92	-65.18	5.01	-60.18	-13	-47.18
4	8725	38.55	-64.19	4.24	-59.95	-13	-46.95
5	10470	38.95	-63.14	3.60	-59.54	-13	-46.54
6	12215	38.86	-62.65	4.37	-58.28	-13	-45.28
7	13960	41.65	-57.87	2.25	-55.63	-13	-42.63
8	15705	43.53	-53.82	3.70	-50.12	-13	-37.12
9	17450	46.32	-51.03	3.70	-47.33	-13	-34.33

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 66: 5MHz

Mode	TX channel 132322	Frequency Range	Above 1000MHz
------	-------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3490	46.23	-56.93	7.85	-49.08	-13	-36.08
2	5235	42.30	-62.28	7.06	-55.22	-13	-42.22
3	6980	36.44	-65.66	5.01	-60.66	-13	-47.66
4	8725	38.04	-64.70	4.24	-60.46	-13	-47.46
5	10470	38.39	-63.70	3.60	-60.10	-13	-47.10
6	12215	43	-58.51	4.37	-54.14	-13	-41.14
7	13960	42.81	-60.86	5.71	-55.14	-13	-42.14
8	15705	44.87	-52.48	3.70	-48.78	-13	-35.78
9	17450	46.08	-51.27	3.70	-47.57	-13	-34.57

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3490	41.43	-61.73	7.85	-53.88	-13	-40.88
2	5235	40.9	-63.68	7.06	-56.62	-13	-43.62
3	6980	36.61	-65.49	5.01	-60.49	-13	-47.49
4	8725	38.29	-64.45	4.24	-60.21	-13	-47.21
5	10470	39.36	-62.73	3.60	-59.13	-13	-46.13
6	12215	39.74	-61.77	4.37	-57.40	-13	-44.40
7	13960	42.18	-57.34	2.25	-55.10	-13	-42.10
8	15705	44.23	-53.12	3.70	-49.42	-13	-36.42
9	17450	45.85	-51.50	3.70	-47.80	-13	-34.80

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 66: 10MHz

Mode	TX channel 132322	Frequency Range	Above 1000MHz
------	-------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3490	45.72	-57.44	7.85	-49.59	-13	-36.59
2	5235	42.99	-61.59	7.06	-54.53	-13	-41.53
3	6980	35.42	-66.68	5.01	-61.68	-13	-48.68
4	8725	37.82	-64.92	4.24	-60.68	-13	-47.68
5	10470	40.1	-61.99	3.60	-58.39	-13	-45.39
6	12215	42.75	-58.76	4.37	-54.39	-13	-41.39
7	13960	42.5	-61.17	5.71	-55.45	-13	-42.45
8	15705	44.15	-53.20	3.70	-49.50	-13	-36.50
9	17450	46.35	-51.00	3.70	-47.30	-13	-34.30

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3490	42.17	-60.99	7.85	-53.14	-13	-40.14
2	5235	40.6	-63.98	7.06	-56.92	-13	-43.92
3	6980	36.79	-65.31	5.01	-60.31	-13	-47.31
4	8725	38.02	-64.72	4.24	-60.48	-13	-47.48
5	10470	38.28	-63.81	3.60	-60.21	-13	-47.21
6	12215	39.47	-62.04	4.37	-57.67	-13	-44.67
7	13960	42.45	-57.07	2.25	-54.83	-13	-41.83
8	15705	43.44	-53.91	3.70	-50.21	-13	-37.21
9	17450	46.54	-50.81	3.70	-47.11	-13	-34.11

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 66: 15MHz

Mode	TX channel 132322	Frequency Range	Above 1000MHz
------	-------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3490	47.32	-55.84	7.85	-47.99	-13	-34.99
2	5235	42.60	-61.98	7.06	-54.92	-13	-41.92
3	6980	35.79	-66.31	5.01	-61.31	-13	-48.31
4	8725	37.5	-65.24	4.24	-61.00	-13	-48.00
5	10470	39.39	-62.70	3.60	-59.10	-13	-46.10
6	12215	43.22	-58.29	4.37	-53.92	-13	-40.92
7	13960	42.07	-61.60	5.71	-55.88	-13	-42.88
8	15705	44.55	-52.80	3.70	-49.10	-13	-36.10
9	17450	47.89	-49.46	3.70	-45.76	-13	-32.76

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3490	40.81	-62.35	7.85	-54.50	-13	-41.50
2	5235	41.7	-62.88	7.06	-55.82	-13	-42.82
3	6980	36.61	-65.49	5.01	-60.49	-13	-47.49
4	8725	39.36	-63.38	4.24	-59.14	-13	-46.14
5	10470	39.54	-62.55	3.60	-58.95	-13	-45.95
6	12215	39.32	-62.19	4.37	-57.82	-13	-44.82
7	13960	42.51	-57.01	2.25	-54.77	-13	-41.77
8	15705	43.59	-53.76	3.70	-50.06	-13	-37.06
9	17450	46.99	-50.36	3.70	-46.66	-13	-33.66

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

LTE Band 66: 20MHz

Mode	TX channel 132322	Frequency Range	Above 1000MHz
------	-------------------	-----------------	---------------

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3490	47.20	-55.96	7.85	-48.11	-13	-35.11
2	5235	43.39	-61.19	7.06	-54.13	-13	-41.13
3	6980	36.70	-65.40	5.01	-60.40	-13	-47.40
4	8725	37.21	-65.53	4.24	-61.29	-13	-48.29
5	10470	38.91	-63.18	3.60	-59.58	-13	-46.58
6	12215	42.28	-59.23	4.37	-54.86	-13	-41.86
7	13960	43.34	-60.33	5.71	-54.61	-13	-41.61
8	15705	45.51	-51.84	3.70	-48.14	-13	-35.14
9	17450	48.03	-49.32	3.70	-45.62	-13	-32.62

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	Emission Value (dBm)	Limit (dBm)	Margin (dB)
1	3490	40.71	-62.45	7.85	-54.60	-13	-41.60
2	5235	41.79	-62.79	7.06	-55.73	-13	-42.73
3	6980	36.56	-65.54	5.01	-60.54	-13	-47.54
4	8725	39.09	-63.65	4.24	-59.41	-13	-46.41
5	10470	38.8	-63.29	3.60	-59.69	-13	-46.69
6	12215	37.92	-63.59	4.37	-59.22	-13	-46.22
7	13960	41.86	-57.66	2.25	-55.42	-13	-42.42
8	15705	42.58	-54.77	3.70	-51.07	-13	-38.07
9	17450	45.69	-51.66	3.70	-47.96	-13	-34.96

Remarks:

1. Emission Value (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---