

FCC SAR Test Report (Class II Permissive Change)

Product Name : INTEL DUAL BAND WIRELESS-AC 7265

Model No. : 7265NGW

Applicant : ASUSTeK COMPUTER INC.

Address : 4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan

Date of Receipt : 2015/09/26

Issued Date : 2015/11/11

Report No. : 15A0003R-SAUSP02V00-B

Report Version : V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of QuieTek Corporation.

Test Report

Issued Date: 2015/11/11

Report No.: 15A0003R-SAUSP02V00-B



Product Name : INTEL DUAL BAND WIRELESS-AC 7265
Applicant : ASUSTeK COMPUTER INC.
Address : 4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan
Manufacturer : Intel Mobile Communications
Model No. : 7265NGW
Trade Name : INTEL
FCC ID : MSQ7265NG
Applicable Standard : FCC Oet65 Supplement C June 2001
IEEE Std. 1528-2013
47CFR § 2.1093
Measurement : KDB 447498 D01 v05r02
procedures : KDB 248227 D01 v01r02
KDB 616217 D04 V01r01
KDB 865664 D01 V01r01
Test Result : Max. SAR Measurement (1g)
802.11b/g/n(2.4GHz): **1.18** W/kg
802.11a/n/ac(5 GHz): **1.20** W/kg
Application Type : Certification

The above equipment has been tested by QuieTek-a DEKRA, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report.

Documented By : Anny Chou
(Adm. Specialist / Anny Chou)

Tested By : wenLee
(Senior Engineer / Wen Lee)

Approved By : [Signature]
(Director / Vincent Lin)

TABLE OF CONTENTS

Description	Page
1. General Information.....	4
1.1EUT Description	4
1.2Antenna List.....	5
1.3SAR Test Exclusion Calculation.....	6
1.4Test Environment	9
2. SAR Measurement System	10
2.1 DASY5 System Description	10
2.1.1 Applications	11
2.1.2 Area Scans.....	11
2.1.3 Zoom Scan (Cube Scan Averaging).....	11
2.1.4 Uncertainty of Inter-/Extrapolation and Averaging	11
2.2 DASY5 E-Field Probe	12
2.2.1 Isotropic E-Field Probe Specification	12
2.3 Boundary Detection Unit and Probe Mounting Device	13
2.4 DATA Acquisition Electronics (DAE) and Measurement Server	13
2.5 Robot.....	14
2.6 Light Beam Unit.....	14
2.7 Device Holder	15
2.8 SAM Twin Phantom	15
3. Tissue Simulating Liquid	16
3.1 The composition of the tissue simulating liquid	16
3.2 Tissue Calibration Result	16
3.3 Tissue Dielectric Parameters for Head and Body Phantoms	19
4. SAR Measurement Procedure	20
4.1 SAR System Check.....	20
4.1.1 Dipoles	20
4.1.2 System Check Result	20
4.2 SAR Measurement Procedure	22
5. SAR Exposure Limits	23
6. Test Equipment List.....	24
7. Measurement Uncertainty	25
8. Conducted Power Measurement (Including tolerance allowed for production unit)	27
8.1 PAD Mode.....	27
8.2 Notebook Mode	30
9.Test Results	33
9.1 SAR Test Results Summary	33
9.2 Simultaneous Transmission	37
9.2.1 Simultaneous transmission of MIMO in 802.11 Wi-Fi configurations.....	37
9.2.2 simultaneous transmission of Wi-Fi and other wireless technologies	39
10. SAR measurement variability.....	40
Appendix.....	41
Appendix A. SAR System Check Data	
Appendix B. SAR measurement Data	
Appendix C. Test Setup Photographs & EUT Photographs	
Appendix D. Probe Calibration Data	
Appendix E. Dipole Calibration Data	

1. General Information

1.1 EUT Description

Product Name	INTEL DUAL BAND WIRELESS-AC 7265				
Trade Name	INTEL				
Model No.	7265NGW				
FCC ID	MSQ7265NG				
TX Frequency	802.11b/g/n-20MHz:2412MHz~2462MHz 802.11n-40MHz: 2422MHz~2452MHz 802.11a/n-20:5180-5320MHz,5500-5720MHz, 5745-5825MHz 802.11n-40/MHz: 5190-5310MHz, 5510-5670MHz, 5755-5795MHz 802.11ac-20MHz: 5720MHz, 802.11ac-40MHz: 5710MHz 802.11ac-80MHz: 5210-5290MHz, 5530-5690MHz, 5775MHz BT : 2402 – 2480MHz				
Channel separation	802.11b/g/n-20MHz: 5 MHz, 802.11a/n-20/ac-20MHz: 20MHz 802.11n-40/ac-40MHz: 40MHz, 802.11ac-80MHz: 80MHz BT : 1MHz , BLE : 2MHz				
Number of Channels	802.11b/g/n-20MHz: 11, n-40MHz: 7 802.11a/n-20MHz: 24; 802.11n-40MHz:11 802.11ac-20MHz: 1, 802.11ac-40MHz: 1,802.11ac-80MHz: 5 BT : 79 , BLE : 40				
Data Rate	802.11b: 1-11Mbps, 802.11a/g: 6-54Mbps, 802.11n: up to 300Mbps 802.11ac-80MHz: up to 866.7Mbps BT : 3Mbps , BLE : 1Mbps				
Type of Modulation	DSSS/OFDM/BPSK/QPSK/16QAM/64QAM/256QAM FHSS: GFSK(1Mbps) / π /4DQPSK(2Mbps) / 8DPSK(3Mbps)				
Antenna Type	PIFA				
Device Category	Portable				
RF Exposure Environment	Uncontrolled				
Summary of test result –Reported 1g SAR (W/Kg)					
Test configuration	DTS(WLAN-Main)	DTS(WLAN-Aux)	U-NII(WLAN-Main)	U-NII(WLAN-Aux)	DTS(BT)
Body-Standalone	1.18	1.18	1.19	1.20	0.18
Body-Simultaneous	1.36		1.38		1.38

* Note: (1) This is to request a Class II permissive change for FCC ID: MSQ7265NG, originally granted on 12/15/2015.

The major change filed under this application is:

Change #1: Additional Chassis added, Host device: ASUSTeK, model TP301U, Q303U notebook/tablet.

All models are listed as below

Brand	Model	Difference
ASUS	TP301U (Main test model)	All models are electrically identical, different model names are for marketing purpose.
	Q303U	

#2: When in PAD mode, Reduce the Output Power through firmware
(only reduce Wi-Fi Power, Bluetooth power haven't changes).

#3: Addition two new antennas, the antenna type is the same, the antenna gain is lower than the original application.

1.2 Antenna List

Mode	No.	Manufacturer	Part No.	Peak Gain
PAD	1	LUXSHARE	LA05RF867-1H(Main) LA05RF868-1H (Aux)	-3.1dBi in 2.4GHz -3.3dBi For 5.15~5.25GHz -3.3dBi For 5.25~5.35GHz -3.3dBi For 5.47~5.725GHz- -0.8dBi For 5.725~5.850GHz
	2	Hong Lin	260-26076 (Main) 260-26077 (Aux)	-3.1dBi in 2.4GHz -3.3dBi For 5.15~5.25GHz -3.3dBi For 5.25~5.35GHz -3.1dBi For 5.47~5.725GHz -0.8dBi For 5.725~5.850GHz
Notebook	1	LUXSHARE	LA05RF867-1H(Main) LA05RF868-1H (Aux)	-0.9dBi in 2.4GHz -4.3dBi For 5.15~5.25GHz -4.3dBi For 5.25~5.35GHz -3.7dBi For 5.47~5.725GHz -3.4dBi For 5.725~5.850GHz
	2	Hong Lin	260-26076 (Main) 260-26077 (Aux)	-0.9dBi in 2.4GHz -4.3dBi For 5.15~5.25GHz -4.3dBi For 5.25~5.35GHz -3.6dBi For 5.47~5.725GHz -3.6dBi For 5.725~5.850GHz

Note : (1) Hong Lin antenna was tested and recorded in this report.

(2) There are the same only difference in Manufacturer.

1.3 SAR Test Exclusion Calculation

According to KDB Publication 447498 D01, section 4.3.1, per the calculations of item 1 (Power(mW)/separation (mm)*sqrt(f(GHz)≤3.0), SAR is required as shown in the table below where calculated values are greater than 3.0 :

PAD Mode SAR exclusion calculations for WiFi-SISO and Bluetooth for antenna < 50mm from the user :

Antenna	Tx	Frequency (MHz)	Output Power		Separation distances (mm)					Calculated Threshold Value (≤ 3.0 SAR is not required)				
			dBm	mW	Back	Right	Left	Top	Bottom	Back	Right	Left	Top	Bottom
Main	WiFi	2437	15.00	32	5	227	66	225	3.5	9.9	>50mm	>50mm	>50mm	9.9
Main	WiFi	5180	10.50	11	5	227	66	225	3.5	5.1	>50mm	>50mm	>50mm	5.1
Main	WiFi	5260	12.00	16	5	227	66	225	3.5	7.3	>50mm	>50mm	>50mm	7.3
Main	WiFi	5500	9.50	9	5	227	66	225	3.5	4.2	>50mm	>50mm	>50mm	4.2
Main	WiFi	5745	9.50	9	5	227	66	225	3.5	4.2	>50mm	>50mm	>50mm	4.2
Main	BT	2480	6.00	4	5	227	66	225	3.5	1.3	>50mm	>50mm	>50mm	1.3

PAD Mode SAR exclusion calculations for WiFi-SISO and Bluetooth for antenna > 50mm from the user :

Antenna	Tx	Frequency (MHz)	Output Power		Separation distances (mm)					Calculated Threshold Value (SAR test exclusion power,mW)				
			dBm	mW	Back	Right	Left	Top	Bottom	Back	Right	Left	Top	Bottom
Main	WiFi	2462	15.00	32	5	227	66	225	3.5	<50mm	1865.6	255.6	1845.6	<50mm
Main	WiFi	5240	10.50	11	5	227	66	225	3.5	<50mm	1835.5	225.5	1815.5	<50mm
Main	WiFi	5320	12.00	16	5	227	66	225	3.5	<50mm	1835.0	225.0	1815.0	<50mm
Main	WiFi	5500	9.50	9	5	227	66	225	3.5	<50mm	1834.0	224.0	1814.0	<50mm
Main	WiFi	5660	9.50	9	5	227	66	225	3.5	<50mm	1833.0	223.0	1813.0	<50mm
Main	BT	2480	6.00	4	5	227	66	225	3.5	<50mm	1865.3	255.3	1845.3	<50mm

PAD Mode SAR exclusion calculations for WiFi-SISO and Bluetooth for antenna < 50mm from the user:

Antenna	Tx	Frequency (MHz)	Output Power		Separation distances (mm)					Calculated Threshold Value (≤ 3.0 SAR is not required)				
			dBm	mW	Back	Right	Left	Top	Bottom	Back	Right	Left	Top	Bottom
Aux	WiFi	2462	15.00	32	5	66	227	225	3.5	9.9	>50mm	>50mm	>50mm	9.9
Aux	WiFi	5240	11.50	14	5	66	227	225	3.5	6.5	>50mm	>50mm	>50mm	6.5
Aux	WiFi	5320	12.50	18	5	66	227	225	3.5	8.2	>50mm	>50mm	>50mm	8.2
Aux	WiFi	5580	11.50	14	5	66	227	225	3.5	6.7	>50mm	>50mm	>50mm	6.7
Aux	WiFi	5825	10.00	10	5	66	227	225	3.5	4.8	>50mm	>50mm	>50mm	4.8
Aux	BT	2480	6.00	4	5	66	227	225	3.5	1.3	>50mm	>50mm	>50mm	1.3

PAD Mode SAR exclusion calculations for WiFi-SISO and Bluetooth for antenna > 50mm from the user:

Antenna	Tx	Frequency (MHz)	Output Power		Separation distances (mm)					Calculated Threshold Value (SAR test exclusion power,mW)				
			dBm	mW	Back	Right	Left	Top	Bottom	Back	Right	Left	Top	Bottom
Aux	WiFi	2462	15.00	32	5	66	227	225	3.5	<50mm	255.6	1865.6	1845.6	<50mm
Aux	WiFi	5240	11.50	14	5	66	227	225	3.5	<50mm	225.5	1835.5	1815.5	<50mm
Aux	WiFi	5320	12.50	18	5	66	227	225	3.5	<50mm	225.0	1835.0	1815.0	<50mm
Aux	WiFi	5580	11.50	14	5	66	227	225	3.5	<50mm	223.5	1833.5	1813.5	<50mm
Aux	WiFi	5825	10.00	10	5	66	227	225	3.5	<50mm	222.2	1832.2	1812.2	<50mm
Aux	BT	2480	6.00	4	5	66	227	225	3.5	<50mm	255.3	1865.3	1845.3	<50mm

Notebook Mode SAR exclusion calculations for WiFi-SISO and Bluetooth:

Antenna	Tx	Frequency (MHz)	Output Power		Separation distances (mm)					Calculated Threshold Value (≤ 3.0 SAR is not required)				
			dBm	mW	Back	Right	Left	Top	Bottom	Back	Right	Left	Top	Bottom
Main/Aux	WiFi	2437	15.00	32	--	--	--	--	3	--	--	--	--	9.9
Main/Aux	WiFi	5240	13.50	18	--	--	--	--	3	--	--	--	--	10.2
Main/Aux	WiFi	5320	13.50	13	--	--	--	--	3	--	--	--	--	10.3
Main/Aux	WiFi	5660	13.50	20	--	--	--	--	3	--	--	--	--	10.7
Main/Aux	WiFi	5825	13.50	13	--	--	--	--	3	--	--	--	--	10.8
Main/Aux	BT	2441	6.00	4	--	--	--	--	3	--	--	--	--	1.3

Note : .According to KDB Publication 616217 D04, section 4.2,

1. The required minimum test separation distance for incorporating transmitters and antennas into laptop, notebook and netbook computer displays is determined with the display screen opened at an angle of 90° to the keyboard compartment.

2. When antennas are incorporated in the keyboard section of a laptop computer, SAR is required for the bottom surface of the keyboard

1.4 Test Environment

Ambient conditions in the laboratory:

Test Date: Oct. 27, 2015

Items	Required	Actual
Temperature (°C)	18-25	24.1± 2
Humidity (%RH)	30-70	55

Test Date: Oct. 30, 2015

Items	Required	Actual
Temperature (°C)	18-25	22.5± 2
Humidity (%RH)	30-70	50

Site Description:


Accredited by TAF
Accredited Number: 3023
Effective through: December 12, 2017

Site Name: Quietek Corporation

Site Address: No.5-22, Ruishukeng, Linkou Dist.,
New Taipei City 24451,
Taiwan, R.O.C.
TEL: 886-2-8601-3788 / FAX: 886-2-8601-3789
E-Mail: service@quietek.com

2. SAR Measurement System

2.1 DASY5 System Description



The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

2.1.1 Applications

Predefined procedures and evaluations for automated compliance testing with all worldwide standards, e.g., IEEE 1528, OET 65, IEC 62209-1, IEC 62209-2, EN 50360, EN 50383 and others.

2.1.2 Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 10mm² step integral, with 1mm interpolation used to locate the peak SAR area used for zoom scan assessments.

When an Area Scan has measured all reachable points, it computes the field maxima found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE 1528-2013, EN 50361 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan).

2.1.3 Zoom Scan (Cube Scan Averaging)

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. A density of 1000 kg/m³ is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1 g cube is 10mm, with the side length of the 10 g cube 21,5mm.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 5x5x7 (8mmx8mmx5mm) providing a volume of 32mm in the X & Y axis, and 30mm in the Z axis.

2.1.4 Uncertainty of Inter-/Extrapolation and Averaging

In order to evaluate the uncertainty of the interpolation, extrapolation and averaged SAR calculation algorithms of the Postprocessor, DASY5 allows the generation of measurement grids which are artificially predefined by analytically based test functions. Therefore, the grids of area scans and zoom scans can be filled with uncertainty test data, according to the SAR benchmark functions of IEEE 1528. The three analytical functions shown in equations as below are used to describe the possible range of the expected SAR distributions for the tested handsets. The field gradients are covered by the spatially flat

distribution f_1 , the spatially steep distribution f_3 and f_2 accounts for H-field cancellation on the phantom/tissue surface.

$$f_1(x, y, z) = Ae^{-\frac{z}{2a}} \cos^2 \left(\frac{\pi}{2} \frac{\sqrt{x'^2 + y'^2}}{5a} \right)$$

$$f_2(x, y, z) = Ae^{-\frac{z}{a}} \frac{a^2}{a^2 + x'^2} \left(3 - e^{-\frac{2z}{a}} \right) \cos^2 \left(\frac{\pi}{2} \frac{y'}{3a} \right)$$

$$f_3(x, y, z) = A \frac{a^2}{\frac{a^2}{4} + x'^2 + y'^2} \left(e^{-\frac{2z}{a}} + \frac{a^2}{2(a + 2z)^2} \right)$$

2.2 DASY5 E-Field Probe

The SAR measurement is conducted with the dosimetric probe manufactured by SPEAG. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

SPEAG conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528, EN 62209-1, IEC 62209, etc.) under ISO 17025. The calibration data are in Appendix D.

2.2.1 Isotropic E-Field Probe Specification

Model	Ex3DV4	
Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.	

2.3 Boundary Detection Unit and Probe Mounting Device

The DASY probes use a precise connector and an additional holder for the probe, consisting of a plastic tube and a flexible silicon ring to center the probe. The connector at the DAE is flexibly mounted and held in the default position with magnets and springs. Two switching systems in the connector mount detect frontal and lateral probe collisions and trigger the necessary software response.



2.4 DATA Acquisition Electronics (DAE) and Measurement Server

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit.

Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE4 is 200M Ohm; the inputs are symmetrical and floating. Common mode rejection is above 80dB.



The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz intel ULV Celeron, 128MB chipdisk and 128MB RAM. The necessary circuits for communication with the DAE electronics box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY5 I/O board, which is directly connected to the PC/104 bus of the CPU board.



2.5 Robot

The DASY5 system uses the high precision robots TX90 XL type out of the newer series from Stäubli SA (France). For the 6-axis controller DASY5 system, the CS8C robot controller version from Stäubli is used.

The XL robot series have many features that are important for our application:

- High precision (repeatability 0.02 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)
- 6-axis controller



2.6 Light Beam Unit

The light beam switch allows automatic "tooling" of the probe. During the process, the actual position of the probe tip with respect to the robot arm is measured, as well as the probe length and the horizontal probe offset. The software then corrects all movements, such that the robot coordinates are valid for the probe tip.

The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe, the same position will be reached with another aligned probe within 0.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position.



2.7 Device Holder

The DASY5 device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR).

Thus the device needs no repositioning when changing the angles.

The DASY5 device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon_r = 3$ and loss tangent $\delta = 0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



2.8 SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm). It has three measurement areas:

- Left head
- Right head
- Flat phantom



The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

3. Tissue Simulating Liquid

3.1 The composition of the tissue simulating liquid

INGREDIENT (% Weight)	2450MHz Head	2450MHz Body	5200MHz Body	5800MHz Body
Water	46.7	73.2	76	75.68
Salt	0.00	0.04	0.00	0.43
Sugar	0.00	0.00	0.00	0.00
HEC	0.00	0.00	0.00	0.00
Preventol	0.00	0.00	0.00	0.00
DGBE	53.3	26.7	4.44	4.42
Triton X-100	46.7	--	28.99	--

3.2 Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using APREL Dielectric Probe Kit and Agilent E5071C Vector Network Analyzer.

Body Tissue Simulate Measurement				
Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]
		ϵ_r	σ [s/m]	
2450 MHz	Reference result ± 5% window	52.7 50.065 to 55.335	1.95 1.8525 to 2.0475	N/A
	27-Oct-15	52.03	1.97	22.8
2412 MHz	Low channel	52.38	1.92	22.8
2437 MHz	Mid channel	52.15	1.95	22.8
2462 MHz	High channel	51.88	1.98	22.8

Body Tissue Simulate Measurement

Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]
		ϵ_r	σ [s/m]	
5200MHz	Reference result ± 5% window	49 46.55 to 51.45	5.3 5.03 to 5.56	N/A
	30-Oct-15	48.41	5.40	21.8
5180 MHz	Low channel	48.46	5.38	21.8
5240 MHz	Mid channel	48.28	5.44	21.8
5280 MHz	High channel	48.16	5.48	21.8

Body Tissue Simulate Measurement

Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]
		ϵ_r	σ [s/m]	
5300MHz	Reference result ± 5% window	48.9 46.45 to 51.34	5.42 5.15 to 5.69	N/A
	30-Oct-15	48.11	5.50	21.8
5320 MHz	High channel	47.98	5.52	21.8

Body Tissue Simulate Measurement

Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]
		ϵ_r	σ [s/m]	
5600MHz	Reference result ± 5% window	48.5 46.07 to 50.92	5.77 5.48 to 6.06	N/A
	30-Oct-15	47.33	5.84	21.8
5500 MHz	Low channel	47.76	5.64	21.8
5580 MHz	Mid channel	47.38	5.80	21.8
5660 MHz	High channel	47.11	5.96	21.8

Body Tissue Simulate Measurement				
Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]
		ϵ_r	σ [S/m]	
5800MHz	Reference result ± 5% window	48.2 45.79 to 50.61	6 5.7 to 6.3	N/A
	30-Oct-15	46.35	6.23	21.8
5745 MHz	Low channel	46.75	6.12	21.8
5825 MHz	High channel	46.18	6.29	21.8

3.3 Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.


Target Frequency	Head		Body	
(MHz)	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

(ϵ_r = relative permittivity, σ = conductivity and $\rho = 1000 \text{ kg/m}^3$)

4. SAR Measurement Procedure

4.1 SAR System Check

4.1.1 Dipoles



The dipoles used is based on the IEEE-1528 standard, and is complied with mechanical and electrical specifications in line with the requirements of both IEEE and FCC Supplement C. the table below provides details for the mechanical and electrical specifications for the dipoles.

Frequency	L (mm)	h (mm)	d (mm)
2450MHz	53.5	30.4	3.6
5200M~5800MHz	20.6	45.4	3.6

4.1.2 System Check Result

System Performance Check at 2450MHz				
Dipole Kit: D2450V2				
Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Tissue Temp. [°C]
2450 MHz	Reference result ± 10% window	50.4 45.36 to 55.44	23.44 21.1 to 25.78	N/A
	27-Oct-15	55.2	25.44	22.8
Note: (1) The power level is used 250mW (2) All SAR values are normalized to 1W forward power. (3) The reference result is from Appendix E.				

System Performance Check at 5200MHz

Dipole Kit: D5GHzV2

Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Tissue Temp. [°C]
5200 MHz	Reference result ± 10% window	74.3 66.87 to 81.73	20.8 18.72 to 22.88	N/A
	30-Oct-15	80	22.1	21.8

Note: (1) The power level is used 100mW
 (2) All SAR values are normalized to 1W forward power.
 (3) The reference result is from Appendix E.

System Performance Check at 5300MHz

Dipole Kit: D5GHzV2

Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Tissue Temp. [°C]
5300 MHz	Reference result ± 10% window	74.4 66.96 to 81.84	20.8 18.72 to 22.88	N/A
	30-Oct-15	79.2	21.3	21.8

Note: (1) The power level is used 100mW
 (4) All SAR values are normalized to 1W forward power.
 (5) The reference result is from Appendix E.

System Performance Check at 5600MHz

Dipole Kit: D5GHzV2

Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Tissue Temp. [°C]
5600 MHz	Reference result ± 10% window	79.1 71.19 to 87.01	21.9 19.71 to 24.09	N/A
	30-Oct-15	85.8	23.1	21.8

Note: (1) The power level is used 100mW
 (6) All SAR values are normalized to 1W forward power.
 (7) The reference result is from Appendix E.

System Performance Check at 5800MHz				
Dipole Kit: D5GHzV2				
Frequency [MHz]	Description	SAR [w/kg] 1g	SAR [w/kg] 10g	Tissue Temp. [°C]
5800 MHz	Reference result ± 10% window	77.2 69.48 to 84.92	21.4 19.26 to 23.54	N/A
	30-Oct-15	81.4	22.1	21.8
Note: (1) The power level is used 100mW (2) All SAR values are normalized to 1W forward power. (3) The reference result is from Appendix E.				

4.2 SAR Measurement Procedure

The Dasy5 calculates SAR using the following equation,

$$SAR = \frac{\sigma |E|^2}{\rho}$$

σ : represents the simulated tissue conductivity

ρ : represents the tissue density

The EUT is set to transmit at the required power in line with product specification, at each frequency relating to the LOW, MID, and HIGH channel settings.

Pre-scans are made on the device to establish the location for the transmitting antenna, using a large area scan in either air or tissue simulation fluid.

The EUT is placed against the Universal Phantom where the maximum area scan dimensions are larger than the physical size of the resonating antenna. When the scan size is not large enough to cover the peak SAR distribution, it is modified by either extending the area scan size in both the X and Y directions, or the device is shifted within the predefined area.

The area scan is then run to establish the peak SAR location (interpolated resolution set at 1mm²) which is then used to orient the center of the zoom scan. The zoom scan is then executed and the 1g and 10g averages are derived from the zoom scan volume (interpolated resolution set at 1mm³).

5. SAR Exposure Limits

SAR assessments have been made in line with the requirements of IEEE-1528, FCC Supplement C, and comply with ANSI/IEEE C95.1-1992 “Uncontrolled Environments” limits. These limits apply to a location which is deemed as “Uncontrolled Environment” which can be described as a situation where the general public may be exposed to an RF source with no prior knowledge or control over their exposure.

Limits for General Population/Uncontrolled Exposure (W/kg)

Type Exposure	Uncontrolled Environment Limit
Spatial Peak SAR (1g cube tissue for brain or body)	1.60 W/kg
Spatial Average SAR (whole body)	0.08 W/kg
Spatial Peak SAR (10g for hands, feet, ankles and wrist)	4.00 W/kg

6. Test Equipment List

Instrument	Manufacturer	Model No.	Serial No.	Last Calibration	Next Calibration
Stäubli Robot TX60L	Stäubli	TX60L	F09/5BL1A1/A06	2009/05/18	only once
Controller	Speag	CS8c	N/A	2009/05/18	only once
Aprel Reference Dipole 2450MHz	Aprel	D2450V2	930	2014/11/19	2016/11/18
Speag Reference Dipole 5GHz	Speag	D5GHzV2	1041	2015/05/22	2017/05/21
SAM Twin Phantom	Speag	QD000 P40 CA	Tp 1515	N/A	N/A
Device Holder	Speag	N/A	N/A	N/A	N/A
Data Acquisition Electronic	Speag	DAE4	1425	2014/11/13	2015/11/12
E-Field Probe	Speag	EX3DV4	3979	2014/11/21	2015/11/20
SAR Software	Speag	DASY52	V52.8 (8)	N/A	N/A
Aprel Dipole Spaccer	Aprel	ALS-DS-U	QTK-295	N/A	N/A
Power Amplifier	Mini-Circuit	ZHL-42	D051404-20	N/A	N/A
Directional Coupler	Agilent	778D-012	50550	N/A	N/A
Universal Radio Communication Tester	R&S	CMU200	104846	2015/06/11	2016/06/09
Vector Network	Agilent	E5071C	MY46108013	2015/03/30	2016/03/28
Signal Generator	Anritsu	MG3694A	041902	2015/08/14	2016/08/12
Power Meter	Anritsu	ML2487A	6K00001447	2015/09/17	2016/09/16
Wide Bandwidth Sensor	Anritsu	MA2411B	1339194	2015/09/17	2016/09/16

7. Measurement Uncertainty

DASY5 Uncertainty(According to IEEE 1528-2013) Measurement uncertainty for 30 MHz to 3 GHz								
Error Description	Uncert. value	Prob. Dist.	Div.	(ci) 1g	(ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(vi) V _{eff}
Measurement System								
Probe Calibration	±6%	N	1	1	1	±6.0%	±6.0%	∞
Axial Isotropy	±4.7%	R	$\sqrt{3}$	0.7	0.7	±1.9%	±1.9%	∞
Hemispherical Isotropy	±9.6%	R	$\sqrt{3}$	0.7	0.7	±3.9%	±3.9%	∞
Boundary Effects	±1.0%	R	$\sqrt{3}$	1	1	±0.6%	±0.6%	∞
Linearity	±4.7%	R	$\sqrt{3}$	1	1	±2.7%	±2.7%	∞
System Detection Limits	±1.0%	R	$\sqrt{3}$	1	1	±0.6%	±0.6%	∞
Modulation Response	±2.4%	R	$\sqrt{3}$	1	1	±1.4%	±1.4%	∞
Readout Electronics	±0.3%	N	1	1	1	±0.3%	±0.3%	∞
Response Time	±0.8%	R	$\sqrt{3}$	1	1	±0.5%	±0.5%	∞
Integration Time	±2.6%	R	$\sqrt{3}$	1	1	±1.5%	±1.5%	∞
RF Ambient Noise	±3.0%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%	∞
RF Ambient Reflections	±3.0%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%	∞
Probe Positioner	±0.4%	R	$\sqrt{3}$	1	1	±0.2%	±0.2%	∞
Probe Positioning	±2.9%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%	∞
Max. SAR Eval.	±4.0%	R	$\sqrt{3}$	1	1	±1.2%	±1.2%	∞
Test Sample Related								
Device Positioning	±2.9%	N	1	1	1	±2.9%	±2.9%	145
Device Holder	±3.6%	N	1	1	1	±3.6%	±3.6%	5
Power Drift	±5.0%	R	$\sqrt{3}$	1	1	±2.9%	±2.9%	∞
Power Scaling	±0%	R	$\sqrt{3}$	1	1	±0.0%	±0.0%	
Phantom and Setup								
Phantom Uncertainty	±6.1%	R	$\sqrt{3}$	1	1	±3.5%	±3.5%	∞
SAR correction	±1.9%	R	$\sqrt{3}$	1	0.84	±1.1%	±0.9%	∞
Liquid Conductivity (meas.)	±2.5%	R	$\sqrt{3}$	0.78	0.71	±1.1%	±1.0%	∞
Liquid Permittivity (meas.)	±2.5%	R	$\sqrt{3}$	0.26	0.26	±0.3%	±0.4%	∞
Temp. unc. - Conductivity	±3.4%	R	$\sqrt{3}$	0.78	0.71	±1.5%	±1.4%	∞
Temp. unc. - Permittivity	±0.4%	R	$\sqrt{3}$	0.23	0.26	±0.1%	±0.1%	∞
Combined Std. Uncertainty						±11.2%	±11.1%	361
Expanded STD Uncertainty						±22.3%	±22.2%	

DASY5 Uncertainty(According to IEEE 1528-2013) Measurement uncertainty for 3GHz to 6 GHz								
Error Description	Uncert. value	Prob. Dist.	Div.	(ci) 1g	(ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(vi) V _{eff}
Measurement System								
Probe Calibration	±6.55%	N	1	1	1	±6.55%	±6.55%	∞
Axial Isotropy	±4.7%	R	$\sqrt{3}$	0.7	0.7	±1.9%	±1.9%	∞
Hemispherical Isotropy	±9.6%	R	$\sqrt{3}$	0.7	0.7	±3.9%	±3.9%	∞
Boundary Effects	±2.0%	R	$\sqrt{3}$	1	1	±1.2%	±1.2%	∞
Linearity	±4.7%	R	$\sqrt{3}$	1	1	±2.7%	±2.7%	∞
System Detection Limits	±1.0%	R	$\sqrt{3}$	1	1	±0.6%	±0.6%	∞
Modulation Response	±2.4%	R	$\sqrt{3}$	1	1	±1.4%	±1.4%	∞
Readout Electronics	±0.3%	N	1	1	1	±0.3%	±0.3%	∞
Response Time	±0.8%	R	$\sqrt{3}$	1	1	±0.5%	±0.5%	∞
Integration Time	±2.6%	R	$\sqrt{3}$	1	1	±1.5%	±1.5%	∞
RF Ambient Noise	±3.0%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%	∞
RF Ambient Reflections	±3.0%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%	∞
Probe Positioner	±0.8%	R	$\sqrt{3}$	1	1	±0.5%	±0.5%	∞
Probe Positioning	±6.7%	R	$\sqrt{3}$	1	1	±3.9%	±3.9%	∞
Post-processing	±4.0%	R	$\sqrt{3}$	1	1	±2.3%	±2.3%	∞
Test Sample Related								
Device Positioning	±2.9%	N	1	1	1	±2.9%	±2.9%	145
Device Holder	±3.6%	N	1	1	1	±3.6%	±3.6%	5
Power Drift	±5.0%	R	$\sqrt{3}$	1	1	±2.9%	±2.9%	∞
Power Scaling	±0%	R	$\sqrt{3}$	1	1	±0.0%	±0.0%	
Phantom and Setup								
Phantom Uncertainty	±6.6%	R	$\sqrt{3}$	1	1	±3.8%	±3.8%	∞
SAR correction	±1.9%	R	$\sqrt{3}$	1	1	±1.1%	±0.9%	∞
Liquid Conductivity (meas.)	±2.5%	R	$\sqrt{3}$	1	0.84	±1.1%	±1.0%	∞
Liquid Permittivity (meas.)	±2.5%	R	$\sqrt{3}$	0.26	0.26	±0.3%	±0.4%	∞
Temp. unc. - Conductivity	±3.4%	R	$\sqrt{3}$	0.78	0.71	±1.5%	±1.4%	∞
Temp. unc. - Permittivity	±0.4%	R	$\sqrt{3}$	0.23	0.26	±0.1%	±0.1%	∞
Combined Std. Uncertainty						±12.3%	±12.2%	748
Expanded STD Uncertainty						±24.6%	±24.5%	

8. Conducted Power Measurement (Including tolerance allowed for production unit)

8.1 PAD Mode

SISO-Main(TX1)																	
DSSS/OFDM mode specified maximum output power at an antenna port	Mode	BW	15.247			U-NII-1			U-NII-2A			U-NII-2C			U-NII-3		
			CH	Target	Power	CH	Target	Power	CH	Target	Power	CH	Target	Power	CH	Target	Power
	b	20	1	15	14.6												
			6	15	14.94												
			11	15	14.88												
	g	20	1	14	13.82												
			6	15	14.64												
			11	12.5	12.38												
	a	20				36	8.5	8.35	52	11.5	10.99	100	9.5	9.31	132	9.5	9.17
						40	9	8.97	56	11.5	10.69	112	9	8.85	149	9	8.68
						44	10	9.61	60	12	11.69	116	9	8.83	165	8	7.67
						48	10.5	10.41	64	12	11.79	128	9	8.69			
DSSS/OFDM mode specified maximum output power at an antenna port	n(HT)	20	1	14	13.71	36	8.5	8.03	52	11.5	11.41	100	9.5	9.32	132	9.5	9.5
			6	15	14.55	40	9	9	56	11.5	11.49	112	9	8.68	149	9	8.74
			11	12.5	12.29	44	10	9.73	60	12	11.98	116	9	9	165	8	8
						48	10.5	9.81	64	12	12	128	9	8.63			
		40	3	13.5	13.23	38	8.5	8.46	54	11	10.83	102	9	9	134	9	8.88
			6	15	14.86	46	10	9.61	62	11.5	11.44	110	8.5	8.5	142	8.5	8.5
			9	12.5	12.46							118	8.5	8.5	151	8.5	8.5
												126	8.5	8.46	159	7.5	7.5
	ac(VHT)	20													144	9	9
		40													142	8.5	8.5
		80				42	8.5	8.36	58	11	10.77	106	8.5	8.46	138	8.5	8.36
												122	8.5	8.41	155	7.5	7.5

SISO-Aux(TX2)																	
DSSS/OFDM mode specified maximum output power at an antenna port	Mode	BW	15.247			U-NII-1			U-NII-2A			U-NII-2C			U-NII-3		
			CH	Target	Power	CH	Target	Power	CH	Target	Power	CH	Target	Power	CH	Target	Power
	b	20	1	13.5	13.5												
			6	14	13.74												
			11	15	15												
	g	20	1	13.5	13.16												
			6	14	14												
			11	12.5	12.37												
	a	20				36	11	10.99	52	12	11.81	100	10	10	132	9.5	9.5
						40	11	11	56	12	11.71	112	11.5	11.14	149	8	8
						44	11.5	11.45	60	12	12	116	11.5	11.5	165	10	9.98
						48	11.5	11.41	64	12.5	12.33	128	10	10			
	n(HT)	20	1	13.5	13.13	36	11	10.91	52	12	11.72	100	10	10	132	9.5	9.49
			6	14	14	40	11	10.86	56	12	11.64	112	11.5	11.13	149	8	8
			11	12.5	12.31	44	11.5	11.34	60	12	11.98	116	11.5	11.48	165	10	9.79
						48	11.5	11.31	64	12.5	12.22	128	10	9.51			
		40	3	13.5	13.28	38	10.5	10.03	54	11.5	11.13	102	9.5	9.43	134	9	9
			6	14	13.71	46	11	10.83	62	12	11.82	110	11	11	142	8	8
			9	11.5	11.31							118	11	10.92	151	7.5	7.49
												126	9.5	9.46	159	9.5	9.25
ac(VHT)	20													144	8	8	
	40													142	8	8	
	80				42	10.5	10.16	58	11.5	11.43	106	9.5	8.75	138	8	7.55	
												122	9.5	9.11	155	7.5	7.39

MIMO-802.11n																			
Mode	BW	Ant	15.247 (2.4GHz)			U-NII-1 (5150~5250MHz)			U-NII-2A (5250~5350MHz)			U-NII-2C (5470~5725MHz)			U-NII-3 (5725~5850MHz)				
			CH	Target	Power	CH	Target	Power	CH	Target	Power	CH	Target	Power	CH	Target	Power		
DSSS/OFDM mode specified maximum output power at an antenna port	MIMO-n(HT)	20	Tx1	1	12	11.62	36	8.5	8.47	52	11.5	11.5	100	9.5	9.37	132	9.5	8.34	
				6	14	13.81	40	9	8.48	56	11.5	11.33	112	9	9	149	8	7.05	
				11	12	11.96	44	10	9.55	60	12	11.89	116	9	8.82	165	8	7.44	
							48	10.5	9.55	64	12	12	128	9	8.71				
			Tx2	1	12	12	36	8.5	8.5	52	11.5	11.14	100	9.5	8.17	132	9.5	9.5	
				6	14	13.63	40	9	8.92	56	11.5	10.56	112	9	8.48	149	8	8	
				11	12	12	44	10	9.73	60	12	11.59	116	9	8.42	165	8	8	
							48	10.5	9.74	64	12	11.06	128	9	8.83				
			TX1+TX2	1	15	14.82	36	11.5	11.5	52	14.5	14.33	100	12.5	11.82	132	12.5	11.97	
				6	17	16.73	40	12	11.72	56	14.5	13.97	112	12	11.76	149	11	10.56	
				11	15	14.99	44	13	12.65	60	15	14.75	116	12	11.63	165	11	10.74	
							48	13.5	12.66	64	15	14.57	128	12	11.78				
		40	Tx1	3	9.5	9.48	38	8.5	7.96	54	11	10.36	102	9	9	134	9	8.68	
				6	13.5	13.16	46	10	9.99	62	11.5	11.15	110	8.5	8.5	142	8	7.38	
				9	9.5	9.5							118	8.5	8.5	151	7.5	6.98	
													126	8.5	8.5	159	7.5	6.87	
			Tx2	3	9.5	9.5	38	8.5	8.5	54	11	10.59	102	9	8.46	134	9	9	
				6	13.5	12.83	46	10	9.99	62	11.5	10.75	110	8.5	8.28	142	8	8	
				9	9.5	9.01							118	8.5	8.25	151	7.5	7.49	
													126	8.5	8.13	159	7.5	7.5	
			TX1+TX2	3	12.5	12.5	38	11.5	11.25	54	14	13.49	102	12	11.75	134	12	11.85	
				6	16.5	16.01	46	13	13	62	14.5	13.96	110	11.5	11.4	142	11	10.71	
				9	12.5	12.27							118	11.5	11.39	151	10.5	10.25	
													126	11.5	11.33	159	10.5	10.21	
		MIMO-ac(HT)	20	Tx1													144	8	7.06
				Tx2													144	8	7.93
				TX1+TX2													144	11	10.51
Tx1															142	8	7.38		
Tx2															142	8	8		
TX1+TX2															142	11	10.71		
40	Tx1					42	8.5	8.38	58	11	11	106	8.5	8.5	138	8	6.76		
												122	8.5	8.23	155	7.5	6.41		
	Tx2					42	8.5	8.5	58	11	10.09	106	8.5	7.33	138	8	7.47		
												122	8.5	8.17	155	7.5	7.38		
	TX1+TX2					42	11.5	11.45	58	14	13.58	106	11.5	10.96	138	11	10.14		
												122	11.5	11.21	155	10.5	9.93		

8.2 Notebook Mode

SISO-Main(TX1)																	
DSSS/OFDM mode specified maximum output power at an antenna port	Mode	BW	15.247			U-NII-1			U-NII-2A			U-NII-2C			U-NII-3		
			CH	Target	Power	CH	Target	Power	CH	Target	Power	CH	Target	Power	CH	Target	Power
	b	20	1	15	14.6												
			6	15	14.94												
			11	15	14.88												
	g	20	1	14	13.82												
			6	15	14.64												
			11	12.5	12.38												
	a	20				36	13.5	13.48	52	13.5	13.41	100	13.5	13.41	132	13.5	13.05
						40	13.5	13.5	56	13.5	13.06	112	13.5	13.26	149	13.5	13.17
						44	13.5	13.15	60	13.5	13.5	116	13.5	13.21	165	13.5	13.37
						48	13.5	13.28	64	13.5	13.22	128	13.5	13.06			
	n(HT)	20	1	14	13.71	36	13.5	13.42	52	13.5	13.07	100	13.5	13.08	132	13.5	13.11
			6	15	14.55	40	13.5	13.56	56	13.5	13.16	112	13.5	13.38	149	13.5	13.13
			11	12.5	12.29	44	13.5	13.26	60	13.5	13.24	116	13.5	13.31	165	13.5	13.42
						48	13.5	13.41	64	13.5	13.31	128	13.5	13.13			
		40	3	13.5	13.23	38	12	11.87	54	13.5	13.22	102	13.5	13.16	134	13.5	13.29
			6	15	14.86	46	13.5	13.5	62	13.5	13.38	110	13.5	13.5	142	13.5	13.44
			9	12.5	12.46							118	13.5	13.45	151	13.5	13.38
												126	13.5	13.34	159	13.5	13.22
	ac(VHT)	20													144	13.5	13.44
		40													142	13.5	13.44
		80				42	13.5	13.19	58	13.5	13.17	106	13.5	13.33	138	13.5	13.21
												122	13.5	13.31	155	13.5	13.21

SISO-Aux(TX2)																	
DSSS/OFDM mode specified maximum output power at an antenna port	Mode	BW	15.247			U-NII-1			U-NII-2A			U-NII-2C			U-NII-3		
			CH	Target	Power	CH	Target	Power	CH	Target	Power	CH	Target	Power	CH	Target	Power
	b	20	1	15	15												
			6	15	14.68												
			11	15	15												
	g	20	1	14.5	14.04												
			6	15	15												
			11	12.5	12.37												
	a	20				36	13.5	13.48	52	13.5	13.35	100	13.5	13.33	132	13.5	13.41
						40	13.5	13.49	56	13.5	13.28	112	13.5	13.5	149	13.5	13.43
						44	13.5	13.48	60	13.5	13.62	116	13.5	13.5	165	13.5	13.34
						48	13.5	13.42	64	13.5	13.47	128	13.5	13.45			
	n(HT)	20	1	14.5	14.36	36	13.5	13.43	52	13.5	13.24	100	13.5	13.3	132	13.5	13.32
			6	15	14.9	40	13.5	13.38	56	13.5	13.21	112	13.5	13.13	149	13.5	13.22
			11	12.5	12.31	44	13.5	13.38	60	13.5	13.08	116	13.5	13.43	165	13.5	13.22
					Avg	48	13.5	13.34	64	13.5	13.41	128	13.5	13.34			
		40	3	13.5	13.28	38	13.5	13.48	54	13.5	13.25	102	13.5	13.33	134	13.5	13.11
			6	15	14.67	46	13.5	13.39	62	13.5	13.41	110	13.5	13.22	142	13.5	13.44
			9	11.5	11.31							118	13.5	13.13	151	13.5	13.44
												126	13.5	13.5	159	13.5	13.41
	ac(VHT)	20													144	13.5	13.5
		40													142	13.5	13.44
		80				42	13.5	13.42	58	13.5	13.49	106	13.5	13.34	138	13.5	13.48
												122	13.5	13.09	155	13.5	13.19

MIMO-(TX1+TX2)																	
DSSS/OFDM mode specified maximum output power at an antenna port	Mode	BW	15.247			U-NII-1			U-NII-2A			U-NII-2C			U-NII-3		
			CH	Target	Power	CH	Target	Power	CH	Target	Power	CH	Target	Power	CH	Target	Power
	b	20															
	g	20															
	n(HT)	20	1	17	16.19	36	16.5	16.19	52	16.5	16.38	100	16.5	16.29	132	16.5	16.43
			6	18	17.68	40	16.5	16.28	56	16.5	16.11	112	16.5	16.37	149	16.5	16.41
			11	15.5	15.33	44	16.5	16.22	60	16.5	16.18	116	16.5	16.35	165	16.5	16.48
						48	16.5	16.47	64	16.5	16.24	128	16.5	16.43			
		40	3	16.5	16.34	38	16.5	16.31	54	16.5	16.43	102	16.5	16.34	134	16.5	16.33
			6	18	17.89	46	16.5	16.34	62	16.5	16.41	110	16.5	16.38	142	16.5	16.19
			9	15	14.88							118	16.5	16.27	151	16.5	16.33
												126	16.5	16.48	159	16.5	16.39
	ac(HT)	20													144	16.5	16.32
		40													142	16.5	16.48
		80				42	16.5	16.11	58	16.5	16.37	106	16.5	16.34	138	16.5	16.28
												122	16.5	16.28	155	16.5	16.39

9. Test Results

9.1 SAR Test Results Summary

SAR MEASUREMENT								
Ambient Temperature (°C) : 24.1 ±2					Relative Humidity (%): 55			
Liquid Temperature (°C) : 22.8 ±2					Depth of Liquid (cm):>15			
Test Mode: 802.11b - 2450 MHz –Main								
Test Position Body	Antenna Position	Frequency		Conducted Power (dBm)		SAR 1g (W/kg)		Limit (W/kg)
		Channel	MHz	Measurement	Tune-up Limit	Measurement	Tune-up Scaled	
Bottom	Fixed	6	2437	14.94	14	0.690	0.700	1.6
Back	Fixed	1	2412	14.6	15	0.908	0.996	1.6
Back	Fixed	6	2437	14.94	14	0.927	0.940	1.6
Back	Fixed	11	2462	14.88	15	1.020	1.049	1.6
Bottom (NB Mode)	Fixed	6	2437	14.94	14	0.504	0.511	1.6
Test Mode: 802.11b - 2450 MHz –Aux								
Bottom	Fixed	11	2462	15	15	0.879	0.879	1.6
Back	Fixed	1	2412	13.5	13.5	1.080	1.080	1.6
Back	Fixed	6	2437	13.74	14	1.110	1.178	1.6
Back	Fixed	11	2462	15	15	1.160	1.160	1.6
Bottom (NB Mode)	Fixed	6	2437	14.68	15	0.414	0.446	1.6
Test Mode: BT-1M								
Bottom	Fixed	39	2441	5.69	6	0.171	0.184	1.6
Note : 1. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required. 2. When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.								

SAR Measurement								
Ambient Temperature (°C) : 22.5 ±2				Relative Humidity (%): 50				
Liquid Temperature (°C) : 21.8 ±2				Depth of Liquid (cm):>15				
Test Mode: 802.11a - 5 GHz –Main								
Test Position Body	Antenna Position	Frequency		Conducted Power (dBm)		SAR 1g (W/kg)		Limit (W/kg)
		Channel	MHz	Measurement	Tune-up Limit	Measurement	Tune-up Scaled	
Bottom (NB Mode)	Fixed	60	5300	13.5	13.5	0.595	0.595	1.6
Bottom	Fixed	36	5180	8.35	8.5	1.040	1.077	1.6
Bottom	Fixed	40	5200	8.97	9	1.020	1.027	1.6
Bottom	Fixed	44	5220	9.61	10	0.981	1.073	1.6
Bottom	Fixed	48	5240	10.41	10.5	0.974	0.994	1.6
Bottom	Fixed	52	5260	10.99	11.5	0.966	1.086	1.6
Bottom	Fixed	56	5280	10.69	11.5	0.888	1.070	1.6
Bottom	Fixed	60	5300	11.69	12	1.060	1.138	1.6
Bottom	Fixed	64	5320	11.79	12	0.932	0.978	1.6
Bottom	Fixed	100	5500	9.31	9.5	0.897	0.937	1.6
Bottom	Fixed	112	5560	8.85	9	0.900	0.932	1.6
Bottom	Fixed	116	5580	8.83	9	0.879	0.914	1.6
Bottom	Fixed	128	5640	8.69	9	0.861	0.925	1.6
Bottom	Fixed	132	5660	9.17	9.5	1.090	1.176	1.6
Bottom	Fixed	149	5745	8.68	9	1.030	1.109	1.6
Bottom	Fixed	165	5825	7.67	8	1.060	1.144	1.6
Back	Fixed	36	5180	8.35	8.5	1.110	1.149	1.6
Back	Fixed	40	5200	8.97	9	1.160	1.168	1.6
Back	Fixed	44	5220	9.61	10	1.030	1.127	1.6
Back	Fixed	48	5240	10.41	10.5	1.140	1.164	1.6
Back	Fixed	52	5260	10.99	11.5	1.060	1.192	1.6
Back	Fixed	56	5280	10.69	11.5	0.989	1.192	1.6
Back	Fixed	60	5300	11.69	12	1.110	1.192	1.6
Back	Fixed	64	5320	11.79	12	1.060	1.113	1.6
Back	Fixed	100	5500	9.31	9.5	1.140	1.191	1.6
Back	Fixed	112	5560	8.85	9	1.140	1.180	1.6
Back	Fixed	116	5580	8.83	9	1.070	1.113	1.6
Back	Fixed	128	5640	8.69	9	1.100	1.181	1.6

Back	Fixed	132	5660	9.17	9.5	1.030	1.111	1.6
Back	Fixed	149	5745	8.68	9	0.977	1.052	1.6
Back	Fixed	165	5825	7.67	8	1.090	1.176	1.6
Test Mode: 802.11a - 5 GHz –Aux								
Bottom (NB Mode)	Fixed	60	5300	13.5	13.5	0.717	0.717	1.6
Bottom	Fixed	36	5180	10.99	11	1.090	1.093	1.6
Bottom	Fixed	40	5200	11	11	0.993	0.993	1.6
Bottom	Fixed	44	5220	11.45	11.5	1.040	1.052	1.6
Bottom	Fixed	48	5240	11.41	11.5	0.974	0.994	1.6
Bottom	Fixed	52	5260	11.81	12	0.975	1.019	1.6
Bottom	Fixed	56	5280	11.71	12	0.923	0.987	1.6
Bottom	Fixed	60	5300	12.41	12.5	1.050	1.072	1.6
Bottom	Fixed	64	5320	12.33	12.5	1.060	1.102	1.6
Bottom	Fixed	100	5500	10	10	0.914	0.914	1.6
Bottom	Fixed	112	5560	11.14	11.5	0.878	0.954	1.6
Bottom	Fixed	116	5580	11.5	11.5	0.995	0.995	1.6
Bottom	Fixed	128	5640	10	10	0.908	0.908	1.6
Bottom	Fixed	132	5660	9.5	9.5	0.922	0.922	1.6
Bottom	Fixed	149	5745	8	8	0.836	0.836	1.6
Bottom	Fixed	165	5825	9.98	10	0.879	0.883	1.6
Back	Fixed	36	5180	10.99	11	1.140	1.143	1.6
Back	Fixed	40	5200	11	11	1.150	1.150	1.6
Back	Fixed	44	5220	11.45	11.5	1.140	1.153	1.6
Back	Fixed	48	5240	11.41	11.5	1.150	1.174	1.6
Back	Fixed	52	5260	11.81	12	1.130	1.181	1.6
Back	Fixed	56	5280	11.71	12	1.120	1.197	1.6
Back	Fixed	60	5300	12.41	12.5	1.150	1.174	1.6
Back	Fixed	64	5320	12.33	12.5	1.150	1.196	1.6
Back	Fixed	100	5500	10	10	1.140	1.140	1.6
Back	Fixed	112	5560	11.14	11.5	1.080	1.173	1.6
Back	Fixed	116	5580	11.5	11.5	1.130	1.130	1.6
Back	Fixed	128	5640	10	10	1.140	1.140	1.6
Back	Fixed	132	5660	9.5	9.5	1.150	1.150	1.6
Back	Fixed	149	5745	8	8	1.150	1.150	1.6
Back	Fixed	165	5825	9.98	10	1.080	1.085	1.6

Note : 1. When multiple transmission modes (802.11 n) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected

2. When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required in that exposure configuration.

9.2 Simultaneous Transmission


9.2.1 Simultaneous transmission of MIMO in 802.11 Wi-Fi configurations

Frequency (GHz)	Test Position (Body)	WLAN Main SAR (W/Kg)	WLAN Aux SAR W/Kg)	Simultaneous Transmission (W/Kg)	Antenna pair in mm	Peak location separation ratio
2.4	Bottom	0.700	0.879	1.579	N/A	N/A
2.4	Back	1.049	1.178	2.227	157.7* ²	0.021
2.4	Bottom (NB Mode)	0.511	0.446	0.957	N/A	N/A
5	Bottom	1.176	1.102	2.278	165* ³	0.021
5	Back	1.192	1.197	2.389	176* ⁴	0.021
5	Bottom (NB Mode)	0.595	0.717	1.312	N/A	N/A

Note : (1) The sum of value is less than 1.6W/Kg or the ratio is determined by $(SAR1 + SAR2)^{1.5}/R_i$, rounded to two decimal digits, and must be ≤ 0.04 for all antenna pairs in the configuration to qualify for SAR test exclusion.


(*2)

Maxima and position w.r.t. Grid Reference Point associated 1g averages	
Zoom Scan (5x5x7) (C:\Users\Administrator\Desktop\ASUS TP301\15A0003R ASUS TP301\802.11b_11-Back...	
Max. 1 at (0.48, 8.40, -0.15) cm	1.02 W/kg
Zoom Scan (5x5x7) (C:\Users\Administrator\Desktop\ASUS TP301\15A0003R ASUS TP301\802.11b_11-Back...	
Max. 2 at (0.88, -7.36, -0.17) cm	1.16 W/kg
Distances and Separation Ratios	
Max. 1 - Max. 2	Distance [cm]: 15.77




(*3)

Maxima and position w.r.t. Grid Reference Point associated 1g averages	
Zoom Scan (6x6x12) (C:\Users\Administrator\Desktop\ASUS TP301\15A0003R ASUS TP301\802.11a_132-Bo...	
Max. 1 at (-0.05, -7.85, 0.02) cm	1.09 W/kg
Zoom Scan (6x6x12) (C:\Users\Administrator\Desktop\ASUS TP301\15A0003R ASUS TP301\802.11a_36-Bot...	
Max. 2 at (0.15, 8.65, 0.01) cm	1.09 W/kg
Distances and Separation Ratios	
Max. 1 - Max. 2	Distance [cm]: 16.50



(*4)

Maxima and position w.r.t. Grid Reference Point associated 1g averages	
Zoom Scan (6x6x12) (C:\Users\Administrator\Desktop\ASUS TP301\15A0003R ASUS TP301\802.11a_40-Bac...	
Max. 1 at (0.15, 8.75, 0.03) cm	1.16 W/kg
Zoom Scan (6x6x12) (C:\Users\Administrator\Desktop\ASUS TP301\15A0003R ASUS TP301\802.11a_132-Ba...	
Max. 2 at (0.55, -8.85, 0.03) cm	1.15 W/kg
Distances and Separation Ratios	
Max. 1 - Max. 2	Distance [cm]: 17.60



9.2.2 simultaneous transmission of Wi-Fi and other wireless technologies

According the KDB 447498 D01 Section 4.3.2, the standalone SAR must be estimated according to the following to determine simultaneous transmission SAR test exclusion

$$(max. power of channel, mW)/(min. test separation distance, mm)] \cdot [\sqrt{f(GHz)}/7.5]$$

Mode	Frequency	Max. power (mW)	Test separation distance ,(mm)	Estimated SAR (W/Kg)
N/A	N/A	N/A	N/A	N/A

Note : A test separation distance of 5 mm must be applied to determine test exclusion according to the SAR Test Exclusion Threshold requirements

When the sum of SAR is larger than the limit, The ratio is determined by $(SAR1 + SAR2)^{1.5/R_i}$, rounded to two decimal digits, and must be ≤ 0.04 for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion . The estimation result as below :

For DTS Band :

Mode	WLAN SAR (W/Kg)	BT SAR (W/Kg)	Simultaneous Transmission (W/Kg)	Antenna pair in mm	Peak location separation ratio
Back	1.178	0.184	1.362	N/A	N/A

The sum of value is less than 1.6W/Kg, thus simultaneous SAR testing is not needed.

For NII Band :

Mode	WLAN SAR (W/Kg)	BT SAR (W/Kg)	Simultaneous Transmission (W/Kg)	Antenna pair in mm	Peak location separation ratio
Back	1.197	0.184	1.378	N/A	N/A

The sum of value is less than 1.6W/Kg, thus simultaneous SAR testing is not needed.

10. SAR measurement variability

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Frequency		SAR 1g (W/kg)						
Channel	MHz	Original	First Repeated		Second Repeated		Third Repeated	
			Value	Ratio	Value	Ratio	Value	Ratio
11	2462	1.178	1.070	1.10	N/A	N/A	N/A	N/A
40	5200	1.150	1.110	1.04	N/A	N/A	N/A	N/A

Appendix

Appendix A. SAR System Check Data

Appendix B. SAR measurement Data

Appendix C. Test Setup Photographs & EUT Photographs

Appendix D. Probe Calibration Data

Appendix E. Dipole Calibration Data

Appendix A. SAR System Check Data

Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/27

System Performance Check_2450MHz-Body

DUT: Dipole 2450 MHz; Type: D2450V2

Communication System: UID 0, CW; Frequency: 2450 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.97$ S/m; $\epsilon_r = 52.03$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 24.1, Liquid Temperature (°C) : 22.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 11/21/2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM left tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/2450MHz Body/Area Scan (9x9x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 16.1 W/kg

Configuration/2450MHz Body/Zoom Scan (7x7x7) (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 90.33 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 31.4 W/kg

SAR(1 g) = 13.8 W/kg; SAR(10 g) = 6.36 W/kg

Maximum value of SAR (measured) = 15.9 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

System Performance Check_5200MHz-Body

DUT: Dipole 5GHz; Type: D5GHzV2

Communication System: UID 0, CW; Frequency: 5200 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5200$ MHz; $\sigma = 5.4$ S/m; $\epsilon_r = 48.41$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/5200MHz-Body/Area Scan (8x8x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 10.9 W/kg


Configuration/5200MHz-Body/Zoom Scan (7x7x12mm), dist=1.4mm (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 68.39 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 29.6 W/kg

SAR(1 g) = 8 W/kg; SAR(10 g) = 2.21 W/kg

Maximum value of SAR (measured) = 18.6 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

System Performance Check_5300MHz-Body

DUT: Dipole 5GHz; Type: D5GHzV2

Communication System: UID 0, CW; Frequency: 5300 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5300$ MHz; $\sigma = 5.5$ S/m; $\epsilon_r = 48.11$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/5300MHz-Body/Area Scan (8x8x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 14.9 W/kg


Configuration/5300MHz-Body/Zoom Scan (7x7x12mm), dist=1.4mm (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 67.53 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 31.8 W/kg

SAR(1 g) = 7.92 W/kg; SAR(10 g) = 2.13 W/kg

Maximum value of SAR (measured) = 18.8 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

System Performance Check_5600MHz-Body

DUT: Dipole 5GHz; Type: D5GHzV2

Communication System: UID 0, CW; Frequency: 5600 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5600$ MHz; $\sigma = 5.84$ S/m; $\epsilon_r = 47.33$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/5600MHz-Body/Area Scan (8x8x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 14.3 W/kg


Configuration/5600MHz-Body/Zoom Scan (7x7x12mm), dist=1.4mm (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 69.17 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 35.9 W/kg

SAR(1 g) = 8.58 W/kg; SAR(10 g) = 2.31 W/kg

Maximum value of SAR (measured) = 21.5 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

System Performance Check_5800MHz-Body

DUT: Dipole 5GHz; Type: D5GHzV2

Communication System: UID 0, CW; Frequency: 5800 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5800$ MHz; $\sigma = 6.23$ S/m; $\epsilon_r = 46.35$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.18, 4.18, 4.18); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/5800MHz-Body/Area Scan (8x8x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 13.0 W/kg


Configuration/5800MHz-Body/Zoom Scan (7x7x12mm), dist=1.4mm (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 65.79 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 37.4 W/kg

SAR(1 g) = 8.14 W/kg; SAR(10 g) = 2.21 W/kg

Maximum value of SAR (measured) = 21.0 W/kg



Appendix B. SAR measurement Data

Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/27

802.11b_6-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 2.4G; Frequency: 2437 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.95$ S/m; $\epsilon_r = 52.15$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 24.1, Liquid Temperature (°C) : 22.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 11/21/2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM left tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x21x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 0.682 W/kg

Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.528 V/m; Power Drift = 0.17 dB
Peak SAR (extrapolated) = 1.70 W/kg
SAR(1 g) = 0.690 W/kg; SAR(10 g) = 0.287 W/kg
Maximum value of SAR (measured) = 0.977 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/27

802.11b_1-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 2.4G; Frequency: 2412 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.92$ S/m; $\epsilon_r = 52.38$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 24.1, Liquid Temperature (°C) : 22.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 11/21/2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM left tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x11x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 1.50 W/kg

Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.919 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 2.59 W/kg
SAR(1 g) = 0.908 W/kg; SAR(10 g) = 0.337 W/kg
Maximum value of SAR (measured) = 1.48 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/27

802.11b_6-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 2.4G; Frequency: 2437 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.95$ S/m; $\epsilon_r = 52.15$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 24.1, Liquid Temperature (°C) : 22.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 11/21/2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM left tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x21x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 1.57 W/kg


Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.069 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 2.72 W/kg

SAR(1 g) = 0.927 W/kg; SAR(10 g) = 0.344 W/kg

Maximum value of SAR (measured) = 1.55 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/27

802.11b_11-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 2.4G; Frequency: 2462 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 2462$ MHz; $\sigma = 1.98$ S/m; $\epsilon_r = 51.88$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 24.1, Liquid Temperature (°C) : 22.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 11/21/2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM left tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x11x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 1.69 W/kg


Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.104 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 3.22 W/kg

SAR(1 g) = 1.02 W/kg; SAR(10 g) = 0.372 W/kg

Maximum value of SAR (measured) = 1.71 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/27

802.11b_6-Bottom(NB Mode) Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 2.4G; Frequency: 2437 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.95$ S/m; $\epsilon_r = 52.15$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 24.1, Liquid Temperature (°C) : 22.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 11/21/2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM left tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x21x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 0.610 W/kg


Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.778 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 1.14 W/kg

SAR(1 g) = 0.504 W/kg; SAR(10 g) = 0.255 W/kg

Maximum value of SAR (measured) = 0.605 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/27

802.11b_11-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 2.4G; Frequency: 2462 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 2462$ MHz; $\sigma = 1.98$ S/m; $\epsilon_r = 51.88$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 24.1, Liquid Temperature (°C) : 22.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 11/21/2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM left tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x21x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 1.19 W/kg

Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.179 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 2.06 W/kg
SAR(1 g) = 0.879 W/kg; SAR(10 g) = 0.338 W/kg
Maximum value of SAR (measured) = 1.25 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/27

802.11b_1-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 2.4G; Frequency: 2412 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.92$ S/m; $\epsilon_r = 52.38$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 24.1, Liquid Temperature (°C) : 22.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 11/21/2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM left tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x11x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 1.63 W/kg


Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.998 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 3.14 W/kg

SAR(1 g) = 1.08 W/kg; SAR(10 g) = 0.413 W/kg

Maximum value of SAR (measured) = 1.77 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/27

802.11b_6-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 2.4G; Frequency: 2437 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.95$ S/m; $\epsilon_r = 52.15$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 24.1, Liquid Temperature (°C) : 22.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 11/21/2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM left tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x11x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 1.64 W/kg

Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.876 V/m; Power Drift = -0.11 dB
Peak SAR (extrapolated) = 3.52 W/kg
SAR(1 g) = 1.11 W/kg; SAR(10 g) = 0.418 W/kg
Maximum value of SAR (measured) = 1.69 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/27

802.11b_11-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 2.4G; Frequency: 2462 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 2462$ MHz; $\sigma = 1.98$ S/m; $\epsilon_r = 51.88$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 24.1, Liquid Temperature (°C) : 22.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 11/21/2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM left tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x21x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 1.93 W/kg


Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.332 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 3.47 W/kg

SAR(1 g) = 1.16 W/kg; SAR(10 g) = 0.414 W/kg

Maximum value of SAR (measured) = 1.89 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/27

802.11b_6-Bottom(NB Mode) Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 2.4G; Frequency: 2437 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.95$ S/m; $\epsilon_r = 52.15$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 24.1, Liquid Temperature (°C) : 22.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 11/21/2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM left tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x21x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 0.498 W/kg


Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.392 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.414 W/kg; SAR(10 g) = 0.206 W/kg

Maximum value of SAR (measured) = 0.539 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/27

BT_39-Back

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, BT 1M&3M&BLE; Frequency: 2441 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 2441$ MHz; $\sigma = 1.96$ S/m; $\epsilon_r = 52.11$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 24.1, Liquid Temperature (°C) : 22.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 11/21/2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM left tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x21x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 0.243 W/kg


Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.152 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.451 W/kg


SAR(1 g) = 0.171 W/kg; SAR(10 g) = 0.084 W/kg

Maximum value of SAR (measured) = 0.235 W/kg



802.11b EUT Back (Aux) Z-Axis plot

Channel: 11



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_60-Bottom(NB Mode) Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5300 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5300$ MHz; $\sigma = 5.5$ S/m; $\epsilon_r = 48.11$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x25x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 0.856 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 9.173 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 0.997 W/kg
SAR(1 g) = 0.595 W/kg; SAR(10 g) = 0.485 W/kg
Maximum value of SAR (measured) = 0.925 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_36-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5180 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5180$ MHz; $\sigma = 5.38$ S/m; $\epsilon_r = 48.46$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.15 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.505 V/m; Power Drift = -0.11 dB
Peak SAR (extrapolated) = 3.90 W/kg
SAR(1 g) = 1.04 W/kg; SAR(10 g) = 0.343 W/kg
Maximum value of SAR (measured) = 1.97 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_40-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5200 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5200$ MHz; $\sigma = 5.4$ S/m; $\epsilon_r = 48.41$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.10 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.206 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 3.90 W/kg
SAR(1 g) = 1.02 W/kg; SAR(10 g) = 0.339 W/kg
Maximum value of SAR (measured) = 1.93 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_44-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5220 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5220$ MHz; $\sigma = 5.42$ S/m; $\epsilon_r = 48.35$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.06 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.425 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 3.50 W/kg
SAR(1 g) = 0.981 W/kg; SAR(10 g) = 0.328 W/kg
Maximum value of SAR (measured) = 1.91 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_48-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5240 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5240$ MHz; $\sigma = 5.44$ S/m; $\epsilon_r = 48.28$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.97 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.502 V/m; Power Drift = -0.15 dB
Peak SAR (extrapolated) = 3.69 W/kg
SAR(1 g) = 0.974 W/kg; SAR(10 g) = 0.327 W/kg
Maximum value of SAR (measured) = 1.86 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_52-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5260 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5260$ MHz; $\sigma = 5.46$ S/m; $\epsilon_r = 48.21$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.95 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.417 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 3.66 W/kg
SAR(1 g) = 0.966 W/kg; SAR(10 g) = 0.328 W/kg
Maximum value of SAR (measured) = 1.84 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_56-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5280 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5280$ MHz; $\sigma = 5.48$ S/m; $\epsilon_r = 48.16$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.77 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.576 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 3.31 W/kg
SAR(1 g) = 0.888 W/kg; SAR(10 g) = 0.337 W/kg
Maximum value of SAR (measured) = 1.65 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_60-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5300 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5300$ MHz; $\sigma = 5.5$ S/m; $\epsilon_r = 48.11$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x25x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.84 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 8.598 V/m; Power Drift = -0.18 dB
Peak SAR (extrapolated) = 3.99 W/kg
SAR(1 g) = 1.06 W/kg; SAR(10 g) = 0.531 W/kg
Maximum value of SAR (measured) = 2.10 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_64-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5320 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5320$ MHz; $\sigma = 5.52$ S/m; $\epsilon_r = 47.98$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.87 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.463 V/m; Power Drift = -0.18 dB
Peak SAR (extrapolated) = 3.48 W/kg
SAR(1 g) = 0.932 W/kg; SAR(10 g) = 0.338 W/kg
Maximum value of SAR (measured) = 1.76 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_100-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5500 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5500$ MHz; $\sigma = 5.64$ S/m; $\epsilon_r = 47.76$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.04, 4.04, 4.04); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.77 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.587 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 3.40 W/kg
SAR(1 g) = 0.897 W/kg; SAR(10 g) = 0.373 W/kg
Maximum value of SAR (measured) = 1.63 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_112-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5560 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5560$ MHz; $\sigma = 5.76$ S/m; $\epsilon_r = 47.45$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.68 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.893 V/m; Power Drift = 0.16 dB
Peak SAR (extrapolated) = 2.95 W/kg
SAR(1 g) = 0.900 W/kg; SAR(10 g) = 0.425 W/kg
Maximum value of SAR (measured) = 1.57 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_116-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5580 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5580$ MHz; $\sigma = 5.8$ S/m; $\epsilon_r = 47.38$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.65 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 6.557 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 3.41 W/kg
SAR(1 g) = 0.879 W/kg; SAR(10 g) = 0.410 W/kg
Maximum value of SAR (measured) = 1.48 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_128-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5640 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5640$ MHz; $\sigma = 5.92$ S/m; $\epsilon_r = 47.18$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.03 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 6.311 V/m; Power Drift = -0.18 dB
Peak SAR (extrapolated) = 3.37 W/kg
SAR(1 g) = 0.861 W/kg; SAR(10 g) = 0.397 W/kg
Maximum value of SAR (measured) = 1.51 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_132-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5660 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5660$ MHz; $\sigma = 5.96$ S/m; $\epsilon_r = 47.11$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.17 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 6.451 V/m; Power Drift = 0.15 dB
Peak SAR (extrapolated) = 3.63 W/kg
SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.621 W/kg
Maximum value of SAR (measured) = 1.94 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_149-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5745 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5745$ MHz; $\sigma = 6.12$ S/m; $\epsilon_r = 46.75$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.18, 4.18, 4.18); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.23 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 8.862 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 4.24 W/kg
SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.599 W/kg
Maximum value of SAR (measured) = 1.59 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_165-Bottom Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5825 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5825$ MHz; $\sigma = 6.29$ S/m; $\epsilon_r = 46.18$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.18, 4.18, 4.18); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.27 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 8.944 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 4.99 W/kg
SAR(1 g) = 1.06 W/kg; SAR(10 g) = 0.612 W/kg
Maximum value of SAR (measured) = 1.86 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_36-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5180 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5180$ MHz; $\sigma = 5.38$ S/m; $\epsilon_r = 48.46$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.54 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.474 V/m; Power Drift = 0.11 dB
Peak SAR (extrapolated) = 6.37 W/kg
SAR(1 g) = 1.11 W/kg; SAR(10 g) = 0.412 W/kg
Maximum value of SAR (measured) = 2.96 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_40-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5200 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5200$ MHz; $\sigma = 5.4$ S/m; $\epsilon_r = 48.41$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.04 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 6.751 V/m; Power Drift = 0.16 dB
Peak SAR (extrapolated) = 5.01 W/kg
SAR(1 g) = 1.16 W/kg; SAR(10 g) = 0.465 W/kg
Maximum value of SAR (measured) = 2.91 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_44-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5220 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5220$ MHz; $\sigma = 5.42$ S/m; $\epsilon_r = 48.35$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.79 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.917 V/m; Power Drift = -0.19 dB
Peak SAR (extrapolated) = 4.61 W/kg
SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.361 W/kg
Maximum value of SAR (measured) = 2.41 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_48-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5240 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5240$ MHz; $\sigma = 5.44$ S/m; $\epsilon_r = 48.28$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.45 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 4.690 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 5.78 W/kg
SAR(1 g) = 1.14 W/kg; SAR(10 g) = 0.364 W/kg
Maximum value of SAR (measured) = 2.75 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_52-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5260 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5260$ MHz; $\sigma = 5.46$ S/m; $\epsilon_r = 48.21$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.97 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.879 V/m; Power Drift = -0.15 dB
Peak SAR (extrapolated) = 5.02 W/kg
SAR(1 g) = 1.06 W/kg; SAR(10 g) = 0.377 W/kg
Maximum value of SAR (measured) = 2.67 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_56-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5280 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5280$ MHz; $\sigma = 5.48$ S/m; $\epsilon_r = 48.16$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.81 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 6.022 V/m; Power Drift = -0.18 dB
Peak SAR (extrapolated) = 4.30 W/kg
SAR(1 g) = 0.989 W/kg; SAR(10 g) = 0.369 W/kg
Maximum value of SAR (measured) = 2.50 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_60-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5300 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5300$ MHz; $\sigma = 5.5$ S/m; $\epsilon_r = 48.11$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x25x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.95 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 7.618 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 4.75 W/kg
SAR(1 g) = 1.11 W/kg; SAR(10 g) = 0.400 W/kg
Maximum value of SAR (measured) = 2.92 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_64-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5320 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5320$ MHz; $\sigma = 5.52$ S/m; $\epsilon_r = 47.98$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.68 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.719 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 4.20 W/kg
SAR(1 g) = 1.06 W/kg; SAR(10 g) = 0.358 W/kg
Maximum value of SAR (measured) = 2.25 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_100-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5500 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5500$ MHz; $\sigma = 5.64$ S/m; $\epsilon_r = 47.76$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.04, 4.04, 4.04); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.00 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 4.750 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 6.94 W/kg
SAR(1 g) = 1.14 W/kg; SAR(10 g) = 0.339 W/kg
Maximum value of SAR (measured) = 2.60 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_112-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5560 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5560$ MHz; $\sigma = 5.76$ S/m; $\epsilon_r = 47.45$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.93 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 6.518 V/m; Power Drift = -0.19 dB
Peak SAR (extrapolated) = 5.88 W/kg
SAR(1 g) = 1.14 W/kg; SAR(10 g) = 0.416 W/kg
Maximum value of SAR (measured) = 2.79 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_116-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5580 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5580$ MHz; $\sigma = 5.8$ S/m; $\epsilon_r = 47.38$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.89 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 6.306 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 4.89 W/kg
SAR(1 g) = 1.07 W/kg; SAR(10 g) = 0.393 W/kg
Maximum value of SAR (measured) = 2.76 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_128-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5640 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5640$ MHz; $\sigma = 5.92$ S/m; $\epsilon_r = 47.18$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.65 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 6.587 V/m; Power Drift = -0.11 dB
Peak SAR (extrapolated) = 5.21 W/kg
SAR(1 g) = 1.1 W/kg; SAR(10 g) = 0.394 W/kg
Maximum value of SAR (measured) = 2.49 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_132-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5660 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5660$ MHz; $\sigma = 5.96$ S/m; $\epsilon_r = 47.11$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.75 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.900 V/m; Power Drift = -0.18 dB
Peak SAR (extrapolated) = 5.70 W/kg
SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.361 W/kg
Maximum value of SAR (measured) = 2.46 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_149-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5745 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5745$ MHz; $\sigma = 6.12$ S/m; $\epsilon_r = 46.75$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.18, 4.18, 4.18); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.64 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.724 V/m; Power Drift = -0.11 dB
Peak SAR (extrapolated) = 5.53 W/kg
SAR(1 g) = 0.977 W/kg; SAR(10 g) = 0.339 W/kg
Maximum value of SAR (measured) = 2.33 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_165-Back Main

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5825 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5825$ MHz; $\sigma = 6.29$ S/m; $\epsilon_r = 46.18$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.18, 4.18, 4.18); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.09 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 6.447 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 8.81 W/kg
SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.403 W/kg
Maximum value of SAR (measured) = 3.00 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_60-Bottom(NB Mode) Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5300 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5300$ MHz; $\sigma = 5.5$ S/m; $\epsilon_r = 48.11$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x25x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 1.25 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:


dx=5mm, dy=5mm, dz=2mm

Reference Value = 6.803 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 1.87 W/kg

SAR(1 g) = 0.717 W/kg; SAR(10 g) = 0.428 W/kg

Maximum value of SAR (measured) = 1.29 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_36-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5180 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5180$ MHz; $\sigma = 5.38$ S/m; $\epsilon_r = 48.46$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.59 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.372 V/m; Power Drift = -0.15 dB
Peak SAR (extrapolated) = 4.20 W/kg
SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.371 W/kg
Maximum value of SAR (measured) = 2.21 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_40-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5200 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5200$ MHz; $\sigma = 5.4$ S/m; $\epsilon_r = 48.41$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.78 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.130 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 3.53 W/kg
SAR(1 g) = 0.993 W/kg; SAR(10 g) = 0.329 W/kg
Maximum value of SAR (measured) = 2.09 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_44-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5220 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5220$ MHz; $\sigma = 5.42$ S/m; $\epsilon_r = 48.35$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.88 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.484 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 3.94 W/kg
SAR(1 g) = 1.04 W/kg; SAR(10 g) = 0.342 W/kg
Maximum value of SAR (measured) = 2.17 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_48-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5240 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5240$ MHz; $\sigma = 5.44$ S/m; $\epsilon_r = 48.28$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.72 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.400 V/m; Power Drift = -0.15 dB
Peak SAR (extrapolated) = 3.65 W/kg
SAR(1 g) = 0.974 W/kg; SAR(10 g) = 0.323 W/kg
Maximum value of SAR (measured) = 2.09 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_52-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5260 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5260$ MHz; $\sigma = 5.46$ S/m; $\epsilon_r = 48.21$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.71 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.276 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 3.67 W/kg
SAR(1 g) = 0.975 W/kg; SAR(10 g) = 0.328 W/kg
Maximum value of SAR (measured) = 2.07 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_56-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5280 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5280$ MHz; $\sigma = 5.48$ S/m; $\epsilon_r = 48.16$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.61 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.463 V/m; Power Drift = -0.15 dB
Peak SAR (extrapolated) = 3.59 W/kg
SAR(1 g) = 0.923 W/kg; SAR(10 g) = 0.324 W/kg
Maximum value of SAR (measured) = 1.92 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_60-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5300 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5300$ MHz; $\sigma = 5.5$ S/m; $\epsilon_r = 48.11$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.93 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.278 V/m; Power Drift = -0.15 dB
Peak SAR (extrapolated) = 3.90 W/kg
SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.349 W/kg
Maximum value of SAR (measured) = 2.32 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_64-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5320 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5320$ MHz; $\sigma = 5.52$ S/m; $\epsilon_r = 47.98$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x25x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.97 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 7.669 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 4.24 W/kg
SAR(1 g) = 1.06 W/kg; SAR(10 g) = 0.518 W/kg
Maximum value of SAR (measured) = 2.17 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_100-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5500 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5500$ MHz; $\sigma = 5.64$ S/m; $\epsilon_r = 47.76$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.04, 4.04, 4.04); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.67 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.530 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 3.61 W/kg
SAR(1 g) = 0.914 W/kg; SAR(10 g) = 0.325 W/kg
Maximum value of SAR (measured) = 1.95 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_112-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5560 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5560$ MHz; $\sigma = 5.76$ S/m; $\epsilon_r = 47.45$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.60 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.783 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 3.45 W/kg
SAR(1 g) = 0.878 W/kg; SAR(10 g) = 0.322 W/kg
Maximum value of SAR (measured) = 1.87 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_116-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5580 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5580$ MHz; $\sigma = 5.8$ S/m; $\epsilon_r = 47.38$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.85 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.671 V/m; Power Drift = -0.15 dB
Peak SAR (extrapolated) = 4.13 W/kg
SAR(1 g) = 0.995 W/kg; SAR(10 g) = 0.349 W/kg
Maximum value of SAR (measured) = 2.17 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_128-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5640 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5640$ MHz; $\sigma = 5.92$ S/m; $\epsilon_r = 47.18$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.63 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.680 V/m; Power Drift = -0.19 dB
Peak SAR (extrapolated) = 3.72 W/kg
SAR(1 g) = 0.908 W/kg; SAR(10 g) = 0.339 W/kg
Maximum value of SAR (measured) = 1.92 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_132-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5660 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5660$ MHz; $\sigma = 5.96$ S/m; $\epsilon_r = 47.11$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.69 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.878 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 3.80 W/kg
SAR(1 g) = 0.922 W/kg; SAR(10 g) = 0.345 W/kg
Maximum value of SAR (measured) = 2.00 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_149-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5745 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5745$ MHz; $\sigma = 6.12$ S/m; $\epsilon_r = 46.75$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.18, 4.18, 4.18); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.56 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.444 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 3.73 W/kg
SAR(1 g) = 0.836 W/kg; SAR(10 g) = 0.311 W/kg
Maximum value of SAR (measured) = 1.81 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_165-Bottom Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5825 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5825$ MHz; $\sigma = 6.29$ S/m; $\epsilon_r = 46.18$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.18, 4.18, 4.18); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x10x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 1.42 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.449 V/m; Power Drift = -0.18 dB
Peak SAR (extrapolated) = 3.48 W/kg
SAR(1 g) = 0.879 W/kg; SAR(10 g) = 0.312 W/kg
Maximum value of SAR (measured) = 1.58 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_36-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5180 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5180$ MHz; $\sigma = 5.38$ S/m; $\epsilon_r = 48.46$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.43 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 4.361 V/m; Power Drift = 0.16 dB
Peak SAR (extrapolated) = 6.35 W/kg
SAR(1 g) = 1.14 W/kg; SAR(10 g) = 0.341 W/kg
Maximum value of SAR (measured) = 3.15 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_40-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5200 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5200$ MHz; $\sigma = 5.4$ S/m; $\epsilon_r = 48.41$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.28 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 8.451 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 5.81 W/kg
SAR(1 g) = 1.15 W/kg; SAR(10 g) = 0.516 W/kg
Maximum value of SAR (measured) = 3.15 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_44-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5220 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5220$ MHz; $\sigma = 5.42$ S/m; $\epsilon_r = 48.35$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.53 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 4.481 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 6.51 W/kg
SAR(1 g) = 1.14 W/kg; SAR(10 g) = 0.354 W/kg
Maximum value of SAR (measured) = 3.01 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_48-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5240 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5240$ MHz; $\sigma = 5.44$ S/m; $\epsilon_r = 48.28$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.20 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 8.057 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 5.72 W/kg
SAR(1 g) = 1.15 W/kg; SAR(10 g) = 0.519 W/kg
Maximum value of SAR (measured) = 3.03 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_52-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5260 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5260$ MHz; $\sigma = 5.46$ S/m; $\epsilon_r = 48.21$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.73 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 4.635 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 5.67 W/kg
SAR(1 g) = 1.13 W/kg; SAR(10 g) = 0.324 W/kg
Maximum value of SAR (measured) = 2.64 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_56-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5260 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5260$ MHz; $\sigma = 5.46$ S/m; $\epsilon_r = 48.21$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.11 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 7.998 V/m; Power Drift = 0.16 dB
Peak SAR (extrapolated) = 5.59 W/kg
SAR(1 g) = 1.12 W/kg; SAR(10 g) = 0.523 W/kg
Maximum value of SAR (measured) = 3.02 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_60-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5300 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5300$ MHz; $\sigma = 5.5$ S/m; $\epsilon_r = 48.11$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.52 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 4.251 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 6.24 W/kg
SAR(1 g) = 1.15 W/kg; SAR(10 g) = 0.334 W/kg
Maximum value of SAR (measured) = 2.89 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_64-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5320 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5320$ MHz; $\sigma = 5.52$ S/m; $\epsilon_r = 47.98$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.42, 4.42, 4.42); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x25x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.07 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 8.415 V/m; Power Drift = -0.11 dB
Peak SAR (extrapolated) = 5.80 W/kg
SAR(1 g) = 1.15 W/kg; SAR(10 g) = 0.506 W/kg
Maximum value of SAR (measured) = 2.53 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_100-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5500 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5500$ MHz; $\sigma = 5.64$ S/m; $\epsilon_r = 47.76$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.04, 4.04, 4.04); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 3.00 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 4.674 V/m; Power Drift = 0.18 dB
Peak SAR (extrapolated) = 6.54 W/kg
SAR(1 g) = 1.14 W/kg; SAR(10 g) = 0.344 W/kg
Maximum value of SAR (measured) = 2.78 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_112-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5560 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5560$ MHz; $\sigma = 5.76$ S/m; $\epsilon_r = 47.45$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.71 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 4.898 V/m; Power Drift = 0.17 dB
Peak SAR (extrapolated) = 7.04 W/kg
SAR(1 g) = 1.08 W/kg; SAR(10 g) = 0.325 W/kg
Maximum value of SAR (measured) = 2.52 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_116-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5580 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5580$ MHz; $\sigma = 5.8$ S/m; $\epsilon_r = 47.38$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 3.25 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 4.697 V/m; Power Drift = 0.18 dB
Peak SAR (extrapolated) = 7.51 W/kg
SAR(1 g) = 1.13 W/kg; SAR(10 g) = 0.353 W/kg
Maximum value of SAR (measured) = 2.90 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_128-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5640 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5640$ MHz; $\sigma = 5.92$ S/m; $\epsilon_r = 47.18$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.51 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.385 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 8.19 W/kg
SAR(1 g) = 1.14 W/kg; SAR(10 g) = 0.339 W/kg
Maximum value of SAR (measured) = 2.98 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_132-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5660 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5660$ MHz; $\sigma = 5.96$ S/m; $\epsilon_r = 47.11$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.01, 4.01, 4.01); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 3.12 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 7.254 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 9.10 W/kg
SAR(1 g) = 1.15 W/kg; SAR(10 g) = 0.341 W/kg
Maximum value of SAR (measured) = 3.01 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_149-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5745 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5745$ MHz; $\sigma = 6.12$ S/m; $\epsilon_r = 46.75$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.18, 4.18, 4.18); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 3.18 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 4.822 V/m; Power Drift = 0.17 dB
Peak SAR (extrapolated) = 8.32 W/kg
SAR(1 g) = 1.15 W/kg; SAR(10 g) = 0.327 W/kg
Maximum value of SAR (measured) = 2.82 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_165-Back Aux

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5825 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5825$ MHz; $\sigma = 6.29$ S/m; $\epsilon_r = 46.18$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.18, 4.18, 4.18); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)


Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.85 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 5.262 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 7.48 W/kg
SAR(1 g) = 1.08 W/kg; SAR(10 g) = 0.349 W/kg
Maximum value of SAR (measured) = 2.56 W/kg



802.11a EUT Back (Main), Z-Axis plot

Channel: 40



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/27

802.11b_11-Back Aux-Vetify

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 2.4G; Frequency: 2462 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 2462$ MHz; $\sigma = 1.98$ S/m; $\epsilon_r = 51.88$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 24.1, Liquid Temperature (°C) : 22.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(7.08, 7.08, 7.08); Calibrated: 11/21/2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM left tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (6x11x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 1.03 W/kg

Configuration/Body/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.868 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 3.10 W/kg
SAR(1 g) = 1.07 W/kg; SAR(10 g) = 0.398 W/kg
Maximum value of SAR (measured) = 1.64 W/kg



Test Laboratory: QuieTek-a DEKRA

Date/Time: 2015/10/30

802.11a_40-Back Main-Verify

DUT: Notebook PC; Type: TP301U, Q303U

Communication System: UID 0, WLAN 5G; Frequency: 5200 MHz;

Communication System PAR: 0 dB

Medium parameters used: $f = 5200$ MHz; $\sigma = 5.4$ S/m; $\epsilon_r = 48.41$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature (°C) : 22.5, Liquid Temperature (°C) : 21.8


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3979; ConvF(4.6, 4.6, 4.6); Calibrated: 11/21/2014;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1425; Calibrated: 2014/11/13
- Phantom: SAM right tablet; Type: SAM
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 2.40 W/kg

Configuration/Body/Zoom Scan (6x6x12) (6x6x12)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=2mm
Reference Value = 4.659 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 5.66 W/kg
SAR(1 g) = 1.11 W/kg; SAR(10 g) = 0.346 W/kg
Maximum value of SAR (measured) = 2.70 W/kg



Appendix D. Probe Calibration Data

Object: EX3DV4- SN: 3979



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **Quietek-TW (Auden)**

Certificate No: **EX3-3979_Nov14**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3979**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6**
Calibration procedure for dosimetric E-field probes

Calibration date: **November 21, 2014**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	03-Apr-14 (No. 217-01911)	Apr-15
Power sensor E4412A	MY41498087	03-Apr-14 (No. 217-01911)	Apr-15
Reference 3 dB Attenuator	SN: S5054 (3c)	03-Apr-14 (No. 217-01915)	Apr-15
Reference 20 dB Attenuator	SN: S5277 (20x)	03-Apr-14 (No. 217-01919)	Apr-15
Reference 30 dB Attenuator	SN: S5129 (30b)	03-Apr-14 (No. 217-01920)	Apr-15
Reference Probe ES3DV2	SN: 3013	30-Dec-13 (No. ES3-3013_Dec13)	Dec-14
DAE4	SN: 660	13-Dec-13 (No. DAE4-660_Dec13)	Dec-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-16
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-14)	In house check: Oct-15

	Name	Function	Signature
Calibrated by:	Jeton Kastrati	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
Issued: November 24, 2014			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E^2 -field uncertainty inside TSL (see below *ConvF*).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Probe EX3DV4

SN:3979

Manufactured: November 5, 2013
Calibrated: November 21, 2014

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3979

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.48	0.50	0.48	$\pm 10.1 \%$
DCP (mV) ^B	99.8	99.9	100.5	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	193.1	$\pm 3.8 \%$
		Y	0.0	0.0	1.0		190.4	
		Z	0.0	0.0	1.0		184.4	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3979

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth (mm) ^G	Unct. (k=2)
750	41.9	0.89	9.94	9.94	9.94	0.64	0.70	± 12.0 %
835	41.5	0.90	9.50	9.50	9.50	0.27	1.16	± 12.0 %
900	41.5	0.97	9.29	9.29	9.29	0.26	1.19	± 12.0 %
1450	40.5	1.20	8.36	8.36	8.36	0.80	0.58	± 12.0 %
1640	40.3	1.29	8.08	8.08	8.08	0.68	0.78	± 12.0 %
1750	40.1	1.37	8.02	8.02	8.02	0.71	0.73	± 12.0 %
1810	40.0	1.40	7.81	7.81	7.81	0.67	0.74	± 12.0 %
1900	40.0	1.40	7.76	7.76	7.76	0.56	0.83	± 12.0 %
2000	40.0	1.40	7.78	7.78	7.78	0.62	0.76	± 12.0 %
2300	39.5	1.67	7.38	7.38	7.38	0.44	0.87	± 12.0 %
2450	39.2	1.80	7.09	7.09	7.09	0.43	0.88	± 12.0 %
2600	39.0	1.96	6.90	6.90	6.90	0.42	0.97	± 12.0 %
3500	37.9	2.91	7.19	7.19	7.19	0.77	0.66	± 13.1 %
5200	36.0	4.66	4.88	4.88	4.88	0.35	1.80	± 13.1 %
5300	35.9	4.76	4.69	4.69	4.69	0.35	1.80	± 13.1 %
5500	35.6	4.96	4.57	4.57	4.57	0.40	1.80	± 13.1 %
5600	35.5	5.07	4.45	4.45	4.45	0.40	1.80	± 13.1 %
5800	35.3	5.27	4.40	4.40	4.40	0.40	1.80	± 13.1 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3979

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	55.5	0.96	9.79	9.79	9.79	0.44	0.85	± 12.0 %
835	55.2	0.97	9.68	9.68	9.68	0.66	0.69	± 12.0 %
900	55.0	1.05	9.43	9.43	9.43	0.35	0.99	± 12.0 %
1450	54.0	1.30	8.11	8.11	8.11	0.74	0.62	± 12.0 %
1640	53.8	1.40	8.25	8.25	8.25	0.60	0.71	± 12.0 %
1750	53.4	1.49	7.77	7.77	7.77	0.65	0.69	± 12.0 %
1810	53.3	1.52	7.64	7.64	7.64	0.52	0.77	± 12.0 %
1900	53.3	1.52	7.51	7.51	7.51	0.63	0.70	± 12.0 %
2000	53.3	1.52	7.61	7.61	7.61	0.45	0.79	± 12.0 %
2300	52.9	1.81	7.30	7.30	7.30	0.67	0.64	± 12.0 %
2450	52.7	1.95	7.08	7.08	7.08	0.80	0.61	± 12.0 %
2600	52.5	2.16	6.81	6.81	6.81	0.80	0.50	± 12.0 %
3500	51.3	3.31	6.40	6.40	6.40	0.57	0.85	± 13.1 %
5200	49.0	5.30	4.60	4.60	4.60	0.40	1.90	± 13.1 %
5300	48.9	5.42	4.42	4.42	4.42	0.40	1.90	± 13.1 %
5500	48.6	5.65	4.04	4.04	4.04	0.45	1.90	± 13.1 %
5600	48.5	5.77	4.01	4.01	4.01	0.45	1.90	± 13.1 %
5800	48.2	6.00	4.18	4.18	4.18	0.50	1.90	± 13.1 %


^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\vartheta = 0^\circ$

f=600 MHz,TEM




f=1800 MHz,R22





Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell , $f_{\text{eval}} = 1900 \text{ MHz}$)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, ϑ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: EX3DV4 - SN:3979

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-46.1
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm