

**47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091
Maximum Permissible Exposure Calculations**

FCC ID: MZR-YRHCPZB3FM

EUT Device Category = General Population/Uncontrolled Exposure

EUT consists of one ISM band radio transmitting operating at frequencies from:
2405 MHz to 2480 MHz

MPE Summary:

According subpart 1.1307 (b)(1) and 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure							
Frequency (MHz)	Range	Electric Strength (V/m)	Field	Magnetic Strength (A/m)	Field	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614		1.63		*(100)	30	
1.34-30		824/f	2.19/f		*(180/f ²)	30	
30-300	27.5		0.073		0.2	30	
300-1500	/		/		f/1500	30	
1500-100,000	/		/		1.0	30	

f = frequency in MHz;

* = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

PG = EIRP

MPE and Limit for 20 cm distance are calculated as follows:

f (MHz)	Field Strength (dBuV/m)	EIRP (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Δ
2405	116.07	121.3	0.02413	1.0	0.97587
2440	116.52	134.6	0.02678	1.0	0.97322
2480	116.43	131.8	0.02622	1.0	0.97378

Result: The device meets FCC MPE limit at 20 cm for General Population/Uncontrolled Exposure as specified in 47 CRF §1.1310 and §2.1091.