




*Figure 1 Galtronics 02102140-08076-2 Wi-Fi
Dual Band PCB Antenna*

Dual-Band Wi-Fi Antenna 02102140-08076-2

Engineering Data Sheets

Galtronics Embedded Antenna

8930 S. Beck Avenue Suite #103
Tempe, Arizona 85284-2891 USA
Tel: 1-480-496-5100
Fax: 1-480-598-2766

WE'RE MAKING WAVES

Revision History (Required)

Revisions	Date	Note
S1	Jun 28, 2024	Initial draft

Disclaimers

The document is proprietary, which may be changed without notice. Please communicate with Galtronics sale team to verify before finalizing your product design.

Contents

1. Galtronics Dual Band Wi-Fi Antenna 4

2. Features 4

3. Specifications and Interface..... 4

4. Return Loss..... 5

5. Gain, Directivity and Efficiency..... 5

6. Radiation Pattern..... 6

Figures

Figure 1 Galtronics Wi-Fi Dual Band PCB Antenna 1

Figure 2 Return Loss 5

Figure 3 Measurement Coordinate System..... 6

Figure 4 Radiation Patterns 9

1. Galtronics Dual Band Wi-Fi Antenna

The Galtronics 02102140-08076-2 antenna is a Dual Band Wi-Fi Antenna that operates in 2400-2500 MHz and 5150-5850 MHz bands. It provides high efficient radiation with good cost benefit. The antenna can be mounted on a customer device by double sided adhesive foam tape and connected to the radio through a U.FL connector.

2. Features

- Operates in 2400-2500 MHz and 5150-5850 MHz bands
- Peak gain: 2.03 dBi in 2.4GHz band and 3.22 dBi in 5GHz band.
- High efficiency
- U.FL connector interface
- Mounted by double sided adhesive foam tape

3. Specifications and Interface

Standard	Wi-Fi Dual Band
Frequency Range	2400-2500 MHz and 5150-5850 MHz
Peak Gain	2.03 dBi in 2.4GHz band and 3.22 dBi in 5GHz band
VSWR	2:1
Feed Impedance	50 Ω
Power Handling	30 dBm
Interface	U.FL
Antenna Dimensions	24 mm x 17.8 mm x 1.04 mm (L x W x T)
Temperature range	Operating: -20° C to +60° C (-4° F to +140° F) Storage: -20° C to +60° C (-4° F to +140° F)
Humidity Range	Operating: 10% to 85% non-condensing Storage: 5% to 90% non-condensing

4. Return Loss

The antenna was tested with antenna mounted on a 100 x 100 x 2.3mm ABS evaluation board with 1.6mm thickness double-sided tape and a 27 mm length cable from edge. (Cable Total Length is 40mm).




Figure 2 Return Loss

5. Gain, Directivity and Efficiency

Table 1Peak Gain, Directivity & Efficiency

Dual Band	Frequency (MHz)	Peak Gain (dBi)	Antenna Directivity (dBi)	Terminal Efficiency (%)
Wi-Fi Antenna	2400	2.03	3.66	68.78
	2450	1.94	3.67	67.08
	2500	2.00	3.79	66.26
	Average			67.37

Dual Band	Frequency (MHz)	Peak Gain (dBi)	Antenna Directivity (dBi)	Terminal Efficiency (%)
Wi-Fi Antenna	5150	2.91	4.30	72.54
	5350	3.22	4.47	74.98
	5550	3.19	4.48	74.38
	5750	2.84	4.39	69.92
	5850	2.85	4.39	70.19
	Average			72.40

6. Radiation Pattern

Figure 3 shows the antenna measurement coordinate system in anechoic chamber. Azimuth plane is XY plane ($\Theta=90^\circ$), Elevation 1 plane is XZ plane ($\Phi=0^\circ$) and Elevation 2 plane is YZ plane ($\Phi=90^\circ$).





Figure 3 Measurement Orientation


WE'RE MAKING WAVES

Figure 3 (A), (B) and (C) show the radiation pattern in three major planes.




(A). Azimuth plane (XY plane) radiation pattern

WE'RE MAKING WAVES



(B). Elevation 1 plane (XZ plane) radiation pattern

WE'RE MAKING WAVES



(C). Elevation 2 plane (YZ plane) radiation pattern

Figure 4 Radiation Patterns in Wi-Fi Dual Band.