

FCC RADIO TEST REPORT

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : 150N Wireless LAN Broadband Router
Model No. : BR-6228GNL / GR-228GNL /
3G-6208GNL / 3G-208GNL
Brand Name : EDIMAX
Filing Type : New Application
Applicant : EDIMAX TECHNOLOGY CO., LTD.
Manufacturer : No.3, Wu Chuan 3rd Road, Wu-Ku Industrial Park.
Taipei Hsien, Taiwan
FCC ID : NDD9562281102
Received Date : Mar. 16, 2011
Final Test Date : Aug. 08, 2011
Multiple Listing : Please refer to section 2.2

Statement

Test result included is only for the 802.11n of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



SPORTON International Inc.

No. 52 Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

Table of Contents

1 SUMMARY OF THE TEST RESULT 2

2 GENERAL INFORMATION..... 3

2.1 Product Details..... 3

2.2 Table for Multiple Listing 3

2.3 Accessories..... 3

2.4 Table for Filed Antenna..... 4

2.5 Table for Carrier Frequencies 4

2.6 Test Manner 錯誤! 尚未定義書籤。 5

2.7 Table for Test Modes 5

2.8 Table for Testing Locations..... 5

2.9 Table for Supporting Units 5

2.10 Table for Parameters of Test Software Setting..... 6

2.11 EUT Operation during Test 6

2.12 Test Configuration..... 7

3 TEST RESULT 8

3.1 AC Power Line Conducted Emissions Measurement 8

3.2 Maximum Peak Output Power Measurement 16

3.3 Power Spectral Density Measurement..... 18

3.4 6dB Spectrum Bandwidth Measurement 24

3.5 Radiated Emissions Measurement 30

3.6 Band Edge and Fundamental Emissions Measurement..... 52

3.7 Antenna Requirements 57

4 LIST OF MEASURING EQUIPMENTS 58

5 TEST LOCATION..... 60

6 TAF CERTIFICATE OF ACCREDITATION..... 61

APPENDIX A. MAXIMUM PERMISSIBLE EXPOSURE A1 ~ A3

APPENDIX B. TEST PHOTOS B1 ~ B6

APPENDIX C. PHOTOGRAPHS OF EUT C1 ~ C12

History of This Test Report

Original Issue Date: Aug. 10, 2011

Report No.: FR130931AI

No additional attachment.

Additional attachment were issued as following record:

Attachment No.	Issue Date	Description

CERTIFICATE OF COMPLIANCE

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : 150N Wireless LAN Broadband Router
Model No. : BR-6228GNL / GR-228GNL /
3G-6208GNL / 3G-208GNL
Brand Name : EDIMAX
Applicant : EDIMAX TECHNOLOGY CO., LTD.
No.3, Wu Chuan 3rd Road, Wu-Ku Industrial Park.
Taipei Hsien, Taiwan

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Mar. 16, 2011 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Wayne Hsu / Vice Manager

SPORTON International Inc.

No. 52 Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

1 SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
3.1	15.207	AC Power Line Conducted Emissions	Complies	1.70 dB
3.2	15.247(b)(3)	Maximum Peak Output Power	Complies	15.05 dB
3.3	15.247(e)	Power Spectral Density	Complies	31.34 dB
3.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
3.5	15.247(d)	Radiated Emissions	Complies	1.01 dB
3.6	15.247(d)	Band Edge and Fundamental Emissions	Complies	1.06 dB
3.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

2 GENERAL INFORMATION

2.1 Product Details

The only difference between model 3G-6208GNL / 3G-208GNL and BR-6228GNL / GR-228GNL is 3G function. There is a 3G function in model 3G-6208GNL / 3G-208GNL, the other isn't. Only the radio detail of IEEE 802.11n is shown in this report. For more detailed features description, please refer to the specifications or user's manual.

Items	Description
Power Type	Power from Adapter
Modulation	See the below table for IEEE 802.11n
Data Rate (Mbps)	
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	MCS 0 (20MHz) : 17.68 MHz ; MCS 0 (40MHz) : 36.00 MHz
Conducted Output Power	MCS 0 (20MHz) : 14.43 dBm ; MCS 0 (40MHz) : 14.95 dBm

2.2 Table for Multiple Listing

The models are exactly same in both physical and electrical. The different in model number for marketing purpose.

No.	Brand Name	Model Name
1	Edimax	BR-6228GNL, GR-228GNL, 3G-6208GNL, 3G-208GNL
2	Edge-core, SMC	SMCWBR-11S3GN2

2.3 Accessories

Power	Brand	Model	Rating
Switching Adapter	DVE	DSA -6PFA-05 FUS 050100	INPUT : 100-240V~50/60Hz 0.2A OUTPUT : +5V 1A
Switching power supply	PHIHONG	PSAA10R-050	INPUT : 100-240V~21-29VA 50-60Hz 300mA OUTPUT : +5V 2A MAX.
Switching Adapter	DVE	DSA-12PFA-05 FUS 050200	INPUT : 100-240V~50/60Hz 0.5A OUTPUT : +5V 2A

2.4 Table for Filed Antenna

Antenna & Bandwidth

Antenna	Single (TX)	
Bandwidth Mode	20 MHz	40 MHz
802.11b	V	X
802.11g	V	X
802.11n (2.4GHz)	V	V

Ant.	Antenna Type	Connector	Gain (dBi)	Remark
A	Dipole Antenna (For long)	Reversed-SMA	5.00	TX / RX

Ant.	Antenna Type	Connector	Gain (dBi)	Remark
B	Dipole Antenna (For medium)	Reversed-SMA	3.00	TX / RX

Ant.	Antenna Type	Connector	Gain (dBi)	Remark
C	Dipole Antenna (For short)	Reversed-SMA	2.00	TX / RX

EUT may match the three antennas use. Performed the worst configuration for higher gain was test in final test report.

IEEE 802.11n Modulation Scheme

MCS Index	Nss	Modulation	R	NBPS	NCBPS		NDBPS		Data rate(Mbps)	
					20MHz	40MHz	20MHz	40MHz	800nsGI	
									20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPS	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

2.5 Table for Carrier Frequencies

IEEE 802.11n 20MHz bandwidth systems use channel 1~11.

IEEE 802.11n 40MHz bandwidth systems use channel 3~9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

2.6 Test Manner

- a. The following test modes were performed for EMI test:
 - Mode 1. Switching Adapter DVD DSA -6PFA-05 FUS 050100 with EUT (without USB Port)
 - Mode 2. Switching power supply PHIHONG PSAA10R-050 with EUT (USB Port (3G function))
 - Mode 3. Switching Adapter DVE DSA-12PFA-05 FUS 050200 with EUT (USB Port (3G function))
- b. The test mode 2 was the worst case in the Radiated Emissions (Above 1GHz) test.

2.7 Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on the entire possible configuration for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
AC Power Line Conducted Emissions Radiated Emissions 9kHz~1GHz	Mode 1 / Mode 2 / Mode 3	Auto	-
Maximum Peak Output Power Power Spectral Density 6dB Spectrum Bandwidth Radiated Emissions Above 1GHz Fundamental Emissions	MCS 0 (20MHz)	6.5 Mbps	1/6/11
	MCS 0 (40MHz)	13.5 Mbps	3/6/9
Band Edge Emissions	MCS 0 (20MHz)	6.5 Mbps	1/11
	MCS 0 (40MHz)	13.5 Mbps	3/9

2.8 Table for Testing Locations

Test Site No.	Site Category	Location
CO04-HY	Conduction	Hwa Ya
TH01-HY	OVEN Room	Hwa Ya
03CH02-HY	SAC	Hwa Ya

Semi Anechoic Chamber (SAC).

2.9 Table for Supporting Units

Support Unit	Brand	Model	FCC ID	Remark
(USB) Mouse	Microsoft	1004	DoC	Conducted Emissions
Notebook	DELL	E5500	DoC	
Modem	ACEEX	DM-1414	IFAXDM1414	
3G Dongle	ZTE	MF626	N/A	
3G Station (Remote workstation)	R&S	CMU200	N/A	
Person computer (Remote workstation)	HP	DC579AV	N/A	
LCD Monitor (Remote workstation)	DELL	2408WFPb	N/A	
(PS/2) Mouse (Remote workstation)	HP	M-S69	N/A	
(PS/2) Keyboard (Remote workstation)	HP	KB-0133	N/A	
Notebook	DELL	E5500	DoC	Radiated Emissions

2.10 Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11n

Test Software Version	MP N Test		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n (20MHz)	27	27	27
Frequency	2422 MHz	2437 MHz	2452 MHz
IEEE 802.11n (40MHz)	28	28	28

2.11 EUT Operation during Test

An executive program, "EMCTEST.EXE" under Win XP, which generates a complete line of continuously repeating "H" pattern was used as the test software.

Turn on the power of all equipment.


- a. The NB reads the test program from the hard disk drive and runs it.
- b. The NB sends "H" messages to the monitor, and the monitor displays " H " patterns on the screen.
- c. The NB sends "H" messages to the modem.
- d. Repeat the step b to d.

At the same time, the following programs were executed:


- Executed "WiFi" to link with the remote workstation to receive and transmit data.
- Executed "ping" to link with the remote workstation to receive and transmit data by LAN.
- Executed "MP N Test" to keep transmitting signals at fixed frequency. (Only for radio tested.)

2.12 Test Configuration

**Radiation Emissions Test Configuration
For radiated emissions 9kHz~1GHz**



For radiated emissions above 1GHz



3 TEST RESULT

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Class B

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

3.1.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

3.1.3 Test Procedures

1. The EUT warm up about 15 minutes then start test.
2. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
5. The frequency range from 150 KHz to 30 MHz was searched.
6. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
7. The measurement has to be done between each power line and ground at the power terminal.

3.1.4 Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω. LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

3.1.5 Test Deviation

There is no deviation with the original standard.


3.1.6 EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.

3.1.7 Results of AC Power Line Conducted Emissions Measurement

Final Test Date	Aug. 02, 2011	Test Site No.	CO04-HY
Temperature	24.1°C	Humidity	57.1%
Test Engineer	Jason	Configuration	Mode 1


Line



Measurement Data

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.4214950	42.56	-14.86	57.42	42.16	0.09	0.31	QP
2	0.4214950	33.46	-13.96	47.42	33.06	0.09	0.31	Average
3	12.748	52.61	-7.39	60.00	51.75	0.30	0.56	QP
4	12.748	47.69	-2.31	50.00	46.83	0.30	0.56	Average
5	13.420	45.41	-4.59	50.00	44.53	0.31	0.57	Average
6	13.420	49.92	-10.08	60.00	49.04	0.31	0.57	QP
7	17.693	46.83	-13.17	60.00	45.86	0.37	0.60	QP
8	17.693	43.69	-6.31	50.00	42.72	0.37	0.60	Average
9	21.663	48.30	-1.70	50.00	47.27	0.43	0.60	Average
10	21.663	48.70	-11.30	60.00	47.67	0.43	0.60	QP
11	27.160	38.00	-12.00	50.00	36.94	0.51	0.55	Average
12	27.160	42.60	-17.40	60.00	41.54	0.51	0.55	QP

Neutral




MEASUREMENT DATA

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.4189980	38.19	-19.28	57.47	37.80	0.08	0.31	QP
2	0.4189980	32.79	-14.68	47.47	32.40	0.08	0.31	Average
3	12.806	50.39	-9.61	60.00	49.53	0.30	0.56	QP
4	12.806	41.76	-8.24	50.00	40.90	0.30	0.56	Average
5	13.360	50.28	-9.72	60.00	49.40	0.31	0.57	QP
6	13.360	45.28	-4.72	50.00	44.40	0.31	0.57	Average
7	16.168	41.48	-8.52	50.00	40.53	0.35	0.60	Average
8	16.168	47.90	-12.10	60.00	46.95	0.35	0.60	QP
9	19.710	31.97	-18.03	50.00	30.97	0.40	0.60	Average
10	19.710	44.74	-15.26	60.00	43.74	0.40	0.60	QP
11	23.130	38.04	-11.96	50.00	36.98	0.46	0.60	Average
12	23.130	47.05	-12.95	60.00	45.99	0.46	0.60	QP

Note:
Level = Read Level + LISN Factor + Cable Loss.

Final Test Date	Aug. 02, 2011	Test Site No.	CO04-HY
Temperature	24.1°C	Humidity	57.1%
Test Engineer	Jason	Configuration	Mode 2

Line



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.4420810	51.65	-5.37	57.02	51.24	0.09	0.32	QP
2	0.4420810	38.04	-8.98	47.02	37.63	0.09	0.32	Average
3	0.4761190	52.83	-3.58	56.41	52.40	0.09	0.34	QP
4	0.4761190	35.94	-10.47	46.41	35.51	0.09	0.34	Average
5	0.7169240	32.97	-13.03	46.00	32.44	0.10	0.43	Average
6	0.7169240	44.91	-11.09	56.00	44.38	0.10	0.43	QP
7	2.110	41.67	-4.33	46.00	41.04	0.13	0.50	Average
8	2.110	51.94	-4.06	56.00	51.31	0.13	0.50	QP
9	18.600	32.90	-17.10	50.00	31.92	0.38	0.60	Average
10	18.600	39.69	-20.31	60.00	38.71	0.38	0.60	QP
11	28.686	45.60	-14.40	60.00	44.54	0.53	0.53	QP
12	28.686	41.80	-8.20	50.00	40.74	0.53	0.53	Average

Neutral





Figure 1: Neutral Spectrum

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.4811910	41.55	-4.77	46.32	41.13	0.08	0.34	Average
2	0.4811910	52.76	-3.56	56.32	52.34	0.08	0.34	QP
3	0.5731280	29.81	-16.19	46.00	29.34	0.09	0.38	Average
4	0.5731280	44.85	-11.15	56.00	44.38	0.09	0.38	QP
5	0.7084240	32.31	-13.69	46.00	31.80	0.09	0.42	Average
6	0.7084240	45.31	-10.69	56.00	44.80	0.09	0.42	QP
7	1.960	37.63	-8.37	46.00	37.02	0.11	0.50	Average
8	1.960	50.26	-5.74	56.00	49.65	0.11	0.50	QP
9	12.747	44.75	-15.25	60.00	43.89	0.30	0.56	QP
10	12.747	40.37	-9.63	50.00	39.51	0.30	0.56	Average
11	19.210	39.56	-20.44	60.00	38.57	0.39	0.60	QP
12	19.210	33.44	-16.56	50.00	32.45	0.39	0.60	Average

Note:
Level = Read Level + LISN Factor + Cable Loss.


Final Test Date	Aug. 02, 2011	Test Site No.	CO04-HY
Temperature	24.1°C	Humidity	57.1%
Test Engineer	Jason	Configuration	Mode 3

Line



	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.1712450	48.49	-16.41	64.90	48.33	0.08	0.08	QP
2	0.1712450	32.52	-22.38	54.90	32.36	0.08	0.08	Average
3	0.2561510	45.57	-15.99	61.56	45.32	0.08	0.17	QP
4	0.2561510	37.91	-13.65	51.56	37.66	0.08	0.17	Average
5	12.746	40.89	-19.11	60.00	40.03	0.30	0.56	QP
6	12.746	36.92	-13.08	50.00	36.06	0.30	0.56	Average
7	14.151	39.61	-20.39	60.00	38.72	0.31	0.58	QP
8	14.151	34.96	-15.04	50.00	34.07	0.31	0.58	Average
9	16.228	46.24	-13.76	60.00	45.30	0.34	0.60	QP
10	16.228	42.47	-7.53	50.00	41.53	0.34	0.60	Average
11	28.685	39.63	-20.37	60.00	38.57	0.53	0.53	QP
12	28.685	34.55	-15.45	50.00	33.49	0.53	0.53	Average

Neutral



0.15 0.2 0.5 1 2 5 10 20 30

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.1632450	48.28	-17.02	65.30	48.13	0.08	0.07	QP
2	0.1632450	30.75	-24.55	55.30	30.60	0.08	0.07	Average
3	0.1873850	45.82	-18.33	64.15	45.65	0.08	0.09	QP
4	0.1873850	29.36	-24.79	54.15	29.19	0.08	0.09	Average
5	0.2495360	44.45	-17.32	61.77	44.20	0.08	0.17	QP
6	0.2495360	30.21	-21.56	51.77	29.96	0.08	0.17	Average
7	2.460	26.18	-19.82	46.00	25.56	0.12	0.50	Average
8	2.460	37.36	-18.64	56.00	36.74	0.12	0.50	QP
9	12.809	33.41	-16.59	50.00	32.55	0.30	0.56	Average
10	12.809	40.92	-19.08	60.00	40.06	0.30	0.56	QP
11	13.358	40.78	-19.22	60.00	39.90	0.31	0.57	QP
12	13.358	34.13	-15.87	50.00	33.25	0.31	0.57	Average

Note:
Level = Read Level + LISN Factor + Cable Loss.

3.2 Maximum Peak Output Power Measurement

3.2.1 Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-multipoint antenna reduction operation, the limit has to be reduced by 1dB for every dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

3.2.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	MA2411B

3.2.3 Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

3.2.4 Test Setup Layout



3.2.5 Test Deviation

There is no deviation with the original standard.

3.2.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.2.7 Test Result of Maximum Peak Output Power

Final Test Date	Mar. 25, 2011	Test Site No.	TH01-HY
Temperature	27°C	Humidity	62%
Test Engineer	Ian	Configurations	802.11n

Configuration of IEEE 802.11n (20MHz)

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	14.32	30.00	Complies
6	2437 MHz	14.39	30.00	Complies
11	2462 MHz	14.43	30.00	Complies

Configuration of IEEE 802.11n (40MHz)

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	14.83	30.00	Complies
6	2437 MHz	14.91	30.00	Complies
9	2452 MHz	14.95	30.00	Complies

3.3 Power Spectral Density Measurement

3.3.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

3.3.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

3.3.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 3 kHz and VBW to 30 kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

3.3.4 Test Setup Layout



3.3.5 Test Deviation

There is no deviation with the original standard.

3.3.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.3.7 Test Result of Power Spectral Density

Final Test Date	Mar. 25, 2011	Test Site No.	TH01-HY
Temperature	27°C	Humidity	62%
Test Engineer	Ian	Configurations	802.11n


Configuration of IEEE 802.11n (20MHz)

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-23.59	8.00	Complies
6	2437 MHz	-23.34	8.00	Complies
11	2462 MHz	-23.34	8.00	Complies

Configuration of IEEE 802.11n (40MHz)


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	-24.41	8.00	Complies
6	2437 MHz	-23.73	8.00	Complies
9	2452 MHz	-25.37	8.00	Complies

Power Density Plot on Configuration of IEEE 802.11n (20MHz) / 2412 MHz




Date: 25.MAR.2011 16:54:13

Power Density Plot on Configuration of IEEE 802.11n (20MHz) / 2437 MHz




Date: 25.MAR.2011 16:56:50

Power Density Plot on Configuration of IEEE 802.11n (20MHz) / 2462 MHz




Date: 25.MAR.2011 17:01:32

Power Density Plot on Configuration of IEEE 802.11n (40MHz) / 2422 MHz




Date: 25.MAR.2011 17:05:04

Power Density Plot on Configuration of IEEE 802.11n (40MHz) / 2437 MHz



Date: 25.MAR.2011 17:07:05

Power Density Plot on Configuration of IEEE 802.11n (40MHz) / 2452 MHz



Date: 25.MAR.2011 17:10:42

3.4 6dB Spectrum Bandwidth Measurement

3.4.1 Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

3.4.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

3.4.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

3.4.4 Test Setup Layout



3.4.5 Test Deviation

There is no deviation with the original standard.

3.4.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.4.7 Test Result of 6dB Spectrum Bandwidth

Final Test Date	Mar. 25, 2011	Test Site No.	TH01-HY
Temperature	27°C	Humidity	62%
Test Engineer	Ian	Configurations	802.11n


Configuration of IEEE 802.11n (20MHz)

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.80	17.68	500	Complies
6	2437 MHz	17.80	17.68	500	Complies
11	2462 MHz	17.80	17.68	500	Complies

Configuration of IEEE 802.11n (40MHz)


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	36.64	36.00	500	Complies
6	2437 MHz	36.64	36.00	500	Complies
9	2452 MHz	36.64	36.00	500	Complies

6 dB Bandwidth Plot on Configuration of IEEE 802.11n (20MHz) / 2412 MHz




Date: 25.MAR.2011 16:53:15

6 dB Bandwidth Plot on Configuration of IEEE 802.11n (20MHz) / 2437 MHz




Date: 25.MAR.2011 16:55:41

6 dB Bandwidth Plot on Configuration of IEEE 802.11n (20MHz) / 2462 MHz




Date: 25.MAR.2011 17:00:12

6 dB Bandwidth Plot on Configuration of IEEE 802.11n (40MHz) / 2422 MHz




Date: 25.MAR.2011 17:03:52

6 dB Bandwidth Plot on Configuration of IEEE 802.11n (40MHz) / 2437 MHz



Date: 25.MAR.2011 17:06:09

6 dB Bandwidth Plot on Configuration of IEEE 802.11n (40MHz) / 2452 MHz



Date: 25.MAR.2011 17:09:26

3.5 Radiated Emissions Measurement

3.5.1 Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.5.3 Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

3.5.4 Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

3.5.5 Test Deviation

There is no deviation with the original standard.

3.5.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.5.7 Results of Radiated Emissions (9kHz~30MHz)

Final Test Date	Aug. 08, 2011	Test Site No.	03CH02-HY
Temperature	24.2°C	Humidity	50.5%
Test Engineer	Daniel		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.5.8 Results of Radiated Emissions (30MHz~1GHz)

Final Test Date	Aug. 08, 2011	Test Site No.	03CH02-HY
Temperature	24.2°C	Humidity	50.5%
Test Engineer	Daniel	Configuration	Mode 1


Horizontal



03CH02-HY

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	156.100	30.38	-13.12	43.50	45.06	10.64	2.07	27.39	Peak	---	---
2	249.220	29.29	-16.71	46.00	40.46	12.97	2.68	26.82	Peak	---	---
3	311.300	35.93	-10.07	46.00	46.00	13.88	2.93	26.88	Peak	---	---
4	498.510	38.40	-7.60	46.00	45.54	17.26	3.78	28.18	Peak	---	---
5	676.990	31.75	-14.25	46.00	36.32	19.15	4.32	28.04	Peak	---	---
6	781.750	33.32	-12.68	46.00	36.39	20.01	4.70	27.78	Peak	---	---

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	51.340	34.91	-5.09	40.00	52.41	9.16	1.14	27.80	QP	---	---
2	156.100	38.95	-4.55	43.50	53.63	10.64	2.07	27.39	Peak	---	---
3	249.220	32.64	-13.36	46.00	43.81	12.97	2.68	26.82	Peak	---	---
4	311.300	31.99	-14.01	46.00	42.06	13.88	2.93	26.88	Peak	---	---
5	498.510	37.25	-8.75	46.00	44.39	17.26	3.78	28.18	Peak	---	---
6	723.550	35.25	-10.75	46.00	39.54	19.18	4.47	27.94	Peak	---	---

Note:
 The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
 Emission level (dBuV/m) = 20 log Emission level (uV/m).
 Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


Final Test Date	Aug. 08, 2011	Test Site No.	03CH02-HY
Temperature	24.2°C	Humidity	50.5%
Test Engineer	Daniel	Configuration	Mode 2

Horizontal



	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
			dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	40.670	28.20	-11.80	40.00	41.97	13.01	1.01	27.79	Peak	---	---
2	102.750	29.93	-13.57	43.50	44.35	11.53	1.64	27.59	Peak	---	---
3	207.510	38.66	-4.84	43.50	51.71	11.60	2.37	27.02	Peak	---	---
4	362.710	40.94	-5.06	46.00	50.47	14.68	3.09	27.30	Peak	---	---
5	467.470	41.86	-4.14	46.00	49.65	16.63	3.60	28.02	Peak	---	---
6	625.580	40.13	-5.87	46.00	44.28	19.84	4.14	28.13	Peak	---	---

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	51.340	36.40	-3.60	40.00	53.90	9.16	1.14	27.80	QP	---	---
2	156.100	35.50	-8.00	43.50	50.18	10.64	2.07	27.39	Peak	---	---
3	311.300	42.45	-3.55	46.00	52.52	13.88	2.93	26.88	Peak	---	---
4	467.470	44.99	-1.01	46.00	52.78	16.63	3.60	28.02	QP	---	---
5	520.820	44.85	-1.15	46.00	51.34	17.90	3.79	28.18	QP	---	---
6	572.230	39.20	-6.80	46.00	44.12	19.36	3.88	28.16	Peak	---	---

Note:


The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


Final Test Date	Aug. 08, 2011	Test Site No.	03CH02-HY
Temperature	24.2°C	Humidity	50.5%
Test Engineer	Daniel	Configuration	Mode 3

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	207.510	39.89	-3.61	43.50	52.94	11.60	2.37	27.02	Peak	---	---
2	260.860	42.21	-3.79	46.00	53.13	13.15	2.74	26.81	Peak	---	---
3	311.300	41.04	-4.96	46.00	51.11	13.88	2.93	26.88	Peak	---	---
4	362.710	44.64	-1.36	46.00	54.17	14.68	3.09	27.30	QP	---	---
5	498.510	37.58	-8.42	46.00	44.72	17.26	3.78	28.18	Peak	---	---
6	781.750	34.24	-11.76	46.00	37.31	20.01	4.70	27.78	Peak	---	---

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	51.340	36.84	-3.16	40.00	54.34	9.16	1.14	27.80	QP	---	---
2	102.750	35.46	-8.04	43.50	49.88	11.53	1.64	27.59	Peak	---	---
3	207.510	40.27	-3.23	43.50	53.32	11.60	2.37	27.02	Peak	---	---
4	311.300	43.72	-2.28	46.00	53.79	13.88	2.93	26.88	QP	---	---
5	498.510	41.56	-4.44	46.00	48.70	17.26	3.78	28.18	Peak	---	---
6	520.820	44.85	-1.15	46.00	51.34	17.90	3.79	28.18	QP	---	---

Note:
 The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
 Emission level (dBuV/m) = 20 log Emission level (uV/m).
 Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.5.9 Results for Radiated Emissions (1GHz~10th Harmonic)

Final Test Date	Mar. 16, 2011	Test Site No.	03CH02-HY
Temperature	24.2°C	Humidity	50.5%
Test Engineer	Daniel	Configuration	802.11n Ch. 1 (20MHz)


Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Preamp	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	4824.000	51.61	-22.39	74.00	45.78	35.76	4.58	34.51 Peak	---	---
2	4824.000	38.51	-15.49	54.00	32.68	35.76	4.58	34.51 Average	---	---
3	7236.000	54.81			45.62	37.85	5.63	34.29 Peak	---	---
4	9648.000	55.73			44.63	39.39	6.34	34.63 Peak	---	---

Note: The items 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4824.000	53.03	-20.97	74.00	47.83	35.13	4.58	34.51	Peak	---	---
2	4824.000	39.96	-14.04	54.00	34.76	35.13	4.58	34.51	Average	---	---
3	7236.000	57.01			48.77	36.90	5.63	34.29	Peak	---	---
4	9648.000	56.01			45.71	38.59	6.34	34.63	Peak	---	---

Note: The items 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Final Test Date	Mar. 16, 2011	Test Site No.	03CH02-HY
Temperature	24.2°C	Humidity	50.5%
Test Engineer	Daniel	Configuration	802.11n Ch. 6 (20MHz)


Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Preamp	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	4874.000	53.56	-20.44	74.00	47.57	35.83	4.61	34.45	Peak	---
2	4874.000	39.25	-14.75	54.00	33.26	35.83	4.61	34.45	Average	---
3	7311.000	39.39	-14.61	54.00	30.18	37.86	5.64	34.29	Average	---
4	7311.000	53.27	-20.73	74.00	44.06	37.86	5.64	34.29	Peak	---
5	9748.000	55.14			43.85	39.51	6.36	34.58	Peak	---

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical



Date: 2011-03-16


TABLE 2

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4874.000	40.57	-13.43	54.00	35.23	35.18	4.61	34.45	Average	---	---
2	4874.000	55.22	-18.78	74.00	49.88	35.18	4.61	34.45	Peak	---	---
3	7311.000	39.77	-14.23	54.00	31.50	36.92	5.64	34.29	Average	---	---
4	7311.000	55.90	-18.10	74.00	47.63	36.92	5.64	34.29	Peak	---	---
5	9748.000	55.10			44.61	38.71	6.36	34.58	Peak	---	---

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Final Test Date	Mar. 16, 2011	Test Site No.	03CH02-HY
Temperature	24.2°C	Humidity	50.5%
Test Engineer	Daniel	Configuration	802.11n Ch. 11 (20MHz)


Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Preamp	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	4924.000	54.78	-19.22	74.00	48.58	35.90	4.68	34.38	Peak	---
2	4924.000	40.42	-13.58	54.00	34.22	35.90	4.68	34.38	Average	---
3	7386.000	38.94	-15.06	54.00	29.70	37.88	5.65	34.29	Average	---
4	7386.000	53.13	-20.87	74.00	43.89	37.88	5.65	34.29	Peak	---
5	9848.000	56.26			44.81	39.61	6.38	34.54	Peak	---

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4924.000	53.47	-20.53	74.00	47.94	35.23	4.68	34.38	Peak	---	---
2	4924.000	40.02	-13.98	54.00	34.49	35.23	4.68	34.38	Average	---	---
3	7386.000	38.18	-15.82	54.00	29.86	36.96	5.65	34.29	Average	---	---
4	7386.000	51.73	-22.27	74.00	43.41	36.96	5.65	34.29	Peak	---	---
5	9848.000	54.91			44.26	38.81	6.38	34.54	Peak	---	---

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Final Test Date	Mar. 16, 2011	Test Site No.	03CH02-HY
Temperature	24.2°C	Humidity	50.5%
Test Engineer	Daniel	Configuration	802.11n Ch. 3 (40MHz)


Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4844.000	38.00	-16.00	54.00	32.09	35.78	4.61	34.48	Average	---	---
2	4844.000	51.38	-22.62	74.00	45.47	35.78	4.61	34.48	Peak	---	---
3	7266.000	40.19	-13.81	54.00	30.99	37.86	5.63	34.29	Average	---	---
4	7266.000	54.15	-19.85	74.00	44.95	37.86	5.63	34.29	Peak	---	---
5	9688.000	56.16			44.98	39.43	6.35	34.60	Peak	---	---

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4844.000	41.09	-12.91	54.00	35.82	35.14	4.61	34.48	Average	---	---
2	4844.000	53.73	-20.27	74.00	48.46	35.14	4.61	34.48	Peak	---	---
3	7266.000	39.56	-14.44	54.00	31.31	36.91	5.63	34.29	Average	---	---
4	7266.000	52.93	-21.07	74.00	44.68	36.91	5.63	34.29	Peak	---	---
5	9688.000	55.74			45.36	38.63	6.35	34.60	Peak	---	---

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Final Test Date	Mar. 16, 2011	Test Site No.	03CH02-HY
Temperature	24.2°C	Humidity	50.5%
Test Engineer	Daniel	Configuration	802.11n Ch. 6 (40MHz)


Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	deg
1	4874.000	38.33	-15.67	54.00	32.34	35.83	4.61	34.45	Average	---	---
2	4874.000	51.66	-22.34	74.00	45.67	35.83	4.61	34.45	Peak	---	---
3	7311.000	40.25	-13.75	54.00	31.04	37.86	5.64	34.29	Average	---	---
4	7311.000	55.03	-18.97	74.00	45.82	37.86	5.64	34.29	Peak	---	---
5	9748.000	56.78			45.49	39.51	6.36	34.58	Peak	---	---

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	4874.000	41.31	-12.69	54.00	35.97	35.18	4.61	34.45	Average	---	---
2	4874.000	53.14	-20.86	74.00	47.80	35.18	4.61	34.45	Peak	---	---
3	7311.000	39.65	-14.35	54.00	31.38	36.92	5.64	34.29	Average	---	---
4	7311.000	53.47	-20.53	74.00	45.20	36.92	5.64	34.29	Peak	---	---
5	9748.000	56.62			46.13	38.71	6.36	34.58	Peak	---	---

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Final Test Date	Mar. 16, 2011	Test Site No.	03CH02-HY
Temperature	24.2°C	Humidity	50.5%
Test Engineer	Daniel	Configuration	802.11n Ch. 9 (40MHz)


Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Preamp	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	4904.000	39.12	-14.88	54.00	33.02	35.88	4.64	34.42	Average	---
2	4904.000	52.02	-21.98	74.00	45.92	35.88	4.64	34.42	Peak	---
3	7356.000	40.34	-13.66	54.00	31.12	37.87	5.64	34.29	Average	---
4	7356.000	54.58	-19.42	74.00	45.36	37.87	5.64	34.29	Peak	---
5	9808.000	57.34			45.96	39.57	6.37	34.56	Peak	---

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4904.000	40.92	-13.08	54.00	35.49	35.21	4.64	34.42	Average	---	---
2	4904.000	52.40	-21.60	74.00	46.97	35.21	4.64	34.42	Peak	---	---
3	7356.000	39.43	-14.57	54.00	31.14	36.94	5.64	34.29	Average	---	---
4	7356.000	53.34	-20.66	74.00	45.05	36.94	5.64	34.29	Peak	---	---
5	9808.000	56.66			46.08	38.77	6.37	34.56	Peak	---	---

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

3.6 Band Edge and Fundamental Emissions Measurement

3.6.1 Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.6.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak

3.6.3 Test Procedures

1. The test procedure is the same as section 3.5.3; only the frequency range investigated is limited to 100MHz around band edges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

3.6.4 Test Setup Layout

This test setup layout is the same as that shown in section 3.5.4.

3.6.5 Test Deviation

There is no deviation with the original standard.

3.6.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.6.7 Test Result of Band Edge and Fundamental Emissions

Final Test Date	Mar. 15, 2011	Test Site No.	03CH02-HY
Temperature	24.2°C	Humidity	50.5%
Test Engineer	Daniel	Configuration	802.11n Ch. 1, 6, 11 (20MHz)

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2390.000	51.14	-2.86	54.00	16.09	32.03	3.02	0.00	Average	---	---
2 @	2416.970	104.98			69.87	32.09	3.02	0.00	Average	---	---
1 @	2390.000	72.42	-1.58	74.00	37.37	32.03	3.02	0.00	Peak	---	---
2 @	2418.300	116.79			81.68	32.09	3.02	0.00	Peak	---	---

The item 2 is Fundamental Emissions.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2431.410	104.29			69.09	32.15	3.05	0.00	Average	---	---
1 @	2430.650	115.63			80.43	32.15	3.05	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2456.490	102.61			67.28	32.28	3.05	0.00	Average	---	---
2 @	2483.500	52.71	-1.29	54.00	17.29	32.34	3.08	0.00	Average	---	---
1 @	2455.730	113.97			78.64	32.28	3.05	0.00	Peak	---	---
2 @	2483.500	72.33	-1.67	74.00	36.91	32.34	3.08	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Final Test Date	Mar. 15, 2011	Test Site No.	03CH02-HY
Temperature	24.2°C	Humidity	50.5%
Test Engineer	Daniel	Configuration	802.11n Ch. 3, 6, 9 (40MHz)

Channel 3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2390.000	52.94	-1.06	54.00	17.89	32.03	3.02	0.00	Average	---	---
2 @	2425.140	101.74			66.54	32.15	3.05	0.00	Average	---	---
1 @	2390.000	71.51	-2.49	74.00	36.46	32.03	3.02	0.00	Peak	---	---
2 @	2426.660	112.97			77.77	32.15	3.05	0.00	Peak	---	---

The item 2 is Fundamental Emissions.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2427.610	101.59			66.39	32.15	3.05	0.00	Average	---	---
1 @	2428.940	112.66			77.46	32.15	3.05	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

Channel 9

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2440.530	99.17			63.91	32.21	3.05	0.00	Average	---	---
2 @	2483.500	51.94	-2.06	54.00	16.52	32.34	3.08	0.00	Average	---	---
1 @	2444.140	110.03			74.77	32.21	3.05	0.00	Peak	---	---
2 @	2484.420	69.44	-4.56	74.00	34.02	32.34	3.08	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Emission not in Restricted Band


Final Test Date	Mar. 25, 2011	Test Site No.	TH01-HY
Temperature	27°C	Humidity	62%
Test Engineer	Ian	Configurations	802.11n

Low Band Edge Plot on Configuration of IEEE 802.11n (20MHz) / 2412 MHz




Date: 25.MAR.2011 16:52:01

High Band Edge Plot on Configuration of IEEE 802.11n (20MHz) / 2462 MHz




Date: 25.MAR.2011 16:58:35

Low Band Edge Plot on Configuration of IEEE 802.11n (40MHz) / 2422 MHz



Date: 25.MAR.2011 17:02:53

High Band Edge Plot on Configuration of IEEE 802.11n (40MHz) / 2452 MHz



Date: 25.MAR.2011 17:08:22

3.7 Antenna Requirements

3.7.1 Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

3.7.2 Antenna Connector Construction

Please refer to section 2.3 in this test report; antenna connector complied with the requirements.

4 LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz ~ 2.75GHz	Apr. 20, 2011	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99041	9kHz ~ 30MHz	Mar. 10, 2011	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz ~ 30MHz	May 04, 2011	Conduction (CO04-HY)
RF Cable-CON	HUBER+SUHNER	RG213/U	CB049	9kHz ~ 30MHz	Apr. 21, 2011	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSU26.5	100015	20Hz ~ 26.5GHz	Jan. 06, 2011	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	N/A	Oct. 22, 2010	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 02, 2010	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 02, 2010	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 30, 2010	Conducted (TH01-HY)
Power Sensor	Anritsu	MA2411B	0917017	300MHz ~ 40GHz	Jan. 06, 2011	Conducted (TH01-HY)
Power Meter	Anritsu	ML2495A	0949003	300MHz ~ 40GHz	Jan. 06, 2011	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Jul. 26, 2010*	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.

For radiated emissions 9kHz~1GHz tested.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP40	100305/040	9kHz ~ 40GHz	Feb. 11, 2011	Radiation (03CH02-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	30MHz ~ 1GHz 3m	May 11, 2011	Radiation (03CH02-HY)
Amplifier	Agilent	8447D	2944A11146	100kHz ~ 1.3GHz	Jul. 25, 2011	Radiation (03CH02-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz ~ 1GHz	Mar. 07, 2011	Radiation (03CH02-HY)
Bilog Antenna	SCHAFFNER	CBL61128	2723	30MHz ~ 2GHz	Oct. 16, 2010	Radiation (03CH02-HY)
Turn Table	HD	DS 420	420/649/00	0 - 360 degree	N/A	Radiation (03CH02-HY)
Antenna Mast	HD	MA 240	240/559/00	1 m ~ 4 m	N/A	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	R&S	HFH2-Z2	860004/001	9kHz ~ 30MHz	Jul. 29, 2010*	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is two year.

For radiated emissions above 1GHz and fundamental emissions tested.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP40	100305/040	9kHz ~ 40GHz	Feb. 11, 2011	Radiation (03CH02-HY)
Amplifier	Agilent	8449B	3008A02373	1GHz ~ 26.5GHz	Jul. 23, 2010	Radiation (03CH02-HY)
Horn Antenna	ETS-LINDGREN	3117	00091920	1GHz ~ 18GHz	Nov. 11, 2010	Radiation (03CH02-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX106	03CH02-HY	1GHz ~ 40GHz	Mar. 07, 2011	Radiation (03CH02-HY)
Bilog Antenna	SCHAFFNER	CBL61128	2723	30MHz ~ 2GHz	Oct. 16, 2010	Radiation (03CH02-HY)
Turn Table	HD	DS 420	420/649/00	0 - 360 degree	N/A	Radiation (03CH02-HY)
Antenna Mast	HD	MA 240	240/559/00	1 m ~ 4 m	N/A	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is one year.

5 TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

6 TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-110111

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.

EMC & Wireless Communications Laboratory

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

- Accreditation Criteria** : ISO/IEC 17025:2005
- Accreditation Number** : 1190
- Originally Accredited** : December 15, 2003
- Effective Period** : January 10, 2010 to January 09, 2013
- Accredited Scope** : Testing Field, see described in the Appendix
- Specific Accreditation Program** : Accreditation Program for Designated Testing Laboratory for Commodities Inspection
Accreditation Program for Telecommunication Equipment Testing Laboratory
Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities

Jay-San Chen
President, Taiwan Accreditation Foundation
Date : January 11, 2011

PI, total 24 pages