

FCC RADIO TEST REPORT

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : 150N Wireless LAN Broadband Router
Model No. : BR-6258GN / GR-528GN / BR-6258n
Brand Name : EDIMAX
Filing Type : New Application
Applicant : EDIMAX TECHNOLOGY CO., LTD.
No.3, Wu Chuan 3rd Road, Wu-Ku
Industrial Park, Taipei Hsien, Taiwan
FCC ID : NDD9562581023
Manufacturer : EDIMAX TECHNOLOGY CO., LTD.
No.3, Wu Chuan 3rd Road, Wu-Ku
Industrial Park, Taipei Hsien, Taiwan
Received Date : Jun. 17, 2010
Final Test Date : Nov. 27, 2010
Multiple Listing : Please refer to section 2.5

Statement

Test result included is only for the 802.11b/g part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



SPORTON International Inc.

No. 52 Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

Table of Contents

1 SUMMARY OF THE TEST RESULT	2
2 GENERAL INFORMATION.....	3
2.1 Product Details	3
2.2 Accessories	3
2.3 Table for Filed Antenna	3
2.4 Table for Carrier Frequencies	3
2.5 Table for Multiple Listing	3
2.6 Table for Test Modes	4
2.7 Table for Testing Locations	4
2.8 Table for Supporting Units.....	4
2.9 Table for Parameters of Test Software Setting	5
2.10 EUT Operation during Test	5
2.11 Test Configuration	6
3 TEST RESULT	8
3.1 AC Power Line Conducted Emissions Measurement.....	8
3.2 Peak Output Power Measurement	14
3.3 Test Procedures	14
3.4 Power Spectral Density Measurement.....	16
3.5 6dB Spectrum Bandwidth Measurement.....	22
3.6 Radiated Emissions Measurement.....	28
3.7 Band Edge and Fundamental Emissions Measurement	48
3.8 Antenna Requirements.....	53
4 LIST OF MEASURING EQUIPMENTS	54
5 TEST LOCATION.....	56
6 TAF CERTIFICATE OF ACCREDITATION	57
APPENDIX A. MAXIMUM PERMISSIBLE EXPOSURE.....	A1 ~ A3
APPENDIX B. TEST PHOTOS	B1 ~ B6
APPENDIX C. PHOTOGRAPHS OF EUT	C1 ~ C13

History of This Test Report

Original Issue Date: Nov. 29, 2010

Report No.: FR001209AC

■ No additional attachment.

□ Additional attachment were issued as following record:

Attachment No.	Issue Date	Description


CERTIFICATE OF COMPLIANCE

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : 150N Wireless LAN Broadband Router
Model No. : BR-6258GN / GR-528GN / BR-6258n
Brand Name : EDIMAX
Applicant : EDIMAX TECHNOLOGY CO., LTD.
No.3, Wu Chuan 3rd Road, Wu-Ku Industrial
Park, Taipei Hsien, Taiwan

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jun. 17, 2010 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Wayne Hsu / Vice Manager

SPORTON International Inc.

No. 52 Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

1 SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
3.1	15.207	AC Power Line Conducted Emissions	Complies	7.96 dB
3.2	15.247(b)(3)	Peak Output Power	Complies	12.69 dB
3.3	15.247(e)	Power Spectral Density	Complies	23.75 dB
3.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
3.5	15.247(d)	Radiated Emissions	Complies	1.19 dB
3.6	15.247(d)	Band Edge Emissions	Complies	1.13 dB
3.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Peak Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

2 GENERAL INFORMATION

2.1 Product Details

Only the radio detail of IEEE 802.11b/g is shown in this report. For more detailed features description, please refer to the manufacturer's specifications or user's manual.

Items	Description
Power Type	+5Vdc from adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (DBPSK / DQPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11b/g: 11
Channel Band Width (99%)	11b: 14.96 MHz ; 11g: 16.48 MHz
Conducted Output Power	11b: 17.31 dBm ; 11g: 15.75 dBm

2.2 Accessories

Power	Brand	Model	Rating
AC Adaptor	PHIHONG	PSA05F-050Q	INPUT : 100-240V ~ 50/60Hz 0.15A OUTPUT : +5V 1A
Other			
USB cable			

2.3 Table for Filed Antenna

Ant.	Antenna Type	Connector	Gain (dBi)	Remark
A	Chip Antenna	Fixed on Board	0.50	TX / RX

2.4 Table for Carrier Frequencies

Frequency Allocation for 802.11b/g

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

2.5 Table for Multiple Listing

No.	Brand Name	Model Name
1	Edimax	BR-6258GN,GR-528GN,BR-6258n
2	PCI	MZK-RP150N

2.6 Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on the entire possible configuration for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
AC Power Line Conducted Emissions	Adapter Mode / USB Mode	Auto	-
Peak Output Power Power Spectral Density 6dB Spectrum Bandwidth Radiated Emissions Above 1GHz	11b/CCK	11 Mbps	1/6/11
	11g/BPSK	6 Mbps	1/6/11
Radiated Emissions 9kHz~1GHz	Normal Mode	Auto	-
Fundamental Emissions	11b/CCK	11 Mbps	1/6/11
	11g/BPSK	6 Mbps	1/6/11
Band Edge Emissions	11b/CCK	11 Mbps	1/11
	11g/BPSK	6 Mbps	1/11

2.7 Table for Testing Locations

Test Site No.	Site Category	Location
CO01-HY	Conduction	Hwa Ya
TH01-HY	OVEN Room	Hwa Ya
03CH03-HY	SAC	Hwa Ya

Semi Anechoic Chamber (SAC).

2.8 Table for Supporting Units

Support Unit	Brand	Model	FCC ID	Remark
Notebook	DELL	6400	DoC	Conducted
LCD Monitor	DELL	2408WFPb	DoC	
(USB) Mouse	Microsoft	1004	DoC	
iPod Nano	Apple	A1199	DoC	
Personal Computer (Remote workstation)	HP	DC7700	DoC	
(PS2) Keyboard (Remote workstation)	HP	KB-0133	DoC	
(PS2) Mouse (Remote workstation)	HP	M-S69	DoC	
Notebook	DELL	E5500	DoC	Radiated
Notebook (Remote workstation)	DELL	D400	DoC	

2.9 Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11b/g

Test Software Version	MP Test		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	43	44	45
IEEE 802.11g	32	33	34

2.10 EUT Operation during Test

Conducted Emissions:

An executive program, "EMCTEST.EXE" under WIN XP, which generates a complete line of continuously repeating "H" pattern was used as the test software.

The program was executed as follows :

- Turn on the power of all equipment.
- The NB reads the test program from the hard disk drive and runs it.
- The NB sends "H" messages to the panel and displays "H" patterns on the screen.

At the same time, the following programs were executed:

- Executed "ping.exe" to link with the remote workstation to receive and transmit data via RJ45 cable.


Radiated Emissions:


- Executed "MP Test" to keep transmitting signals at fixed frequency.

2.11 Test Configuration

2.11.1 Radiation Emissions Test Configuration

For radiated emissions 9kHz~1GHz



For radiated emissions above 1GHz

3 TEST RESULT

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Class B

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

3.1.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

3.1.3 Test Procedures

1. The EUT warm up about 15 minutes then start test.
2. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
5. The frequency range from 150 KHz to 30 MHz was searched.
6. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
7. The measurement has to be done between each power line and ground at the power terminal.

3.1.4 Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

3.1.5 Test Deviation

There is no deviation with the original standard.


3.1.6 EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.

3.1.7 Results of AC Power Line Conducted Emissions Measurement


Final Test Date	Nov. 27, 2010	Test Site No.	CO01-HY
Temperature	24.8	Humidity	52.1%
Test Engineer	David	Configuration	Adapter Mode

Line



	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.480	43.83	-12.52	56.35	43.46	0.09	0.28	QP
2	0.480	35.04	-11.31	46.35	34.67	0.09	0.28	Average
3	0.627	45.67	-10.33	56.00	45.04	0.10	0.53	QP
4	0.627	35.65	-10.35	46.00	35.02	0.10	0.53	Average
5	0.702	44.87	-11.13	56.00	44.13	0.10	0.64	QP
6	0.702	35.29	-10.71	46.00	34.55	0.10	0.64	Average
7	0.853	33.84	-12.16	46.00	32.90	0.11	0.83	Average
8	0.853	43.43	-12.57	56.00	42.49	0.11	0.83	QP
9	0.963	44.17	-11.83	56.00	43.12	0.11	0.94	QP
10	0.963	34.72	-11.28	46.00	33.67	0.11	0.94	Average
11	6.917	44.28	-15.72	60.00	43.89	0.23	0.16	QP
12	6.917	34.79	-15.21	50.00	34.40	0.23	0.16	Average

Neutral




	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.232	39.19	-23.19	62.38	39.03	0.06	0.10	QP
2	0.232	28.76	-23.62	52.38	28.60	0.06	0.10	Average
3	0.312	24.49	-25.43	49.92	24.31	0.07	0.11	Average
4	0.312	38.06	-21.86	59.92	37.88	0.07	0.11	QP
5	0.391	25.69	-22.36	48.05	25.51	0.07	0.11	Average
6	0.391	38.25	-19.80	58.05	38.07	0.07	0.11	QP
7	0.557	42.21	-13.79	56.00	41.71	0.08	0.42	QP
8	0.557	31.18	-14.82	46.00	30.68	0.08	0.42	Average
9	0.861	25.28	-20.72	46.00	24.35	0.09	0.84	Average
10	0.861	38.43	-17.57	56.00	37.50	0.09	0.84	QP
11	7.588	41.47	-18.53	60.00	41.08	0.22	0.17	QP
12	7.590	32.28	-17.72	50.00	31.89	0.22	0.17	Average

Note:

Level = Read Level + LISN Factor + Cable Loss.


Final Test Date	Nov. 27, 2010	Test Site No.	CO01-HY
Temperature	24.8	Humidity	52.1%
Test Engineer	David	Configuration	USB Mode

Line



	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.172	48.97	-15.89	64.86	48.79	0.08	0.10	QP
2	0.172	43.42	-11.44	54.86	43.24	0.08	0.10	Average
3	0.234	41.82	-20.49	62.31	41.64	0.08	0.10	QP
4	0.234	36.16	-16.15	52.31	35.98	0.08	0.10	Average
5	0.292	37.98	-22.49	60.47	37.78	0.09	0.11	QP
6	0.292	32.77	-17.70	50.47	32.57	0.09	0.11	Average
7	0.871	34.94	-21.06	56.00	33.98	0.11	0.85	QP
8	0.871	29.55	-16.45	46.00	28.59	0.11	0.85	Average
9	1.570	34.41	-11.59	46.00	33.87	0.12	0.42	Average
10	1.570	36.84	-19.16	56.00	36.30	0.12	0.42	QP
11	3.370	39.94	-16.06	56.00	39.66	0.16	0.12	QP
12	3.370	35.54	-10.46	46.00	35.26	0.16	0.12	Average

Neutral



	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.176	46.99	-17.68	64.67	46.83	0.06	0.10	QP
2	0.176	42.70	-11.97	54.67	42.54	0.06	0.10	Average
3	0.232	43.95	-18.43	62.38	43.79	0.06	0.10	QP
4	0.232	36.00	-16.38	52.38	35.84	0.06	0.10	Average
5	0.291	37.68	-22.82	60.50	37.50	0.07	0.11	QP
6	0.291	35.45	-15.05	50.50	35.27	0.07	0.11	Average
7	0.989	35.99	-20.01	56.00	34.93	0.09	0.97	QP
8	0.989	32.42	-13.58	46.00	31.36	0.09	0.97	Average
9	1.804	38.04	-7.96	46.00	37.68	0.11	0.25	Average
10	1.804	40.97	-15.03	56.00	40.61	0.11	0.25	QP
11	4.017	43.68	-12.32	56.00	43.42	0.14	0.12	QP
12	4.020	35.45	-10.55	46.00	35.19	0.14	0.12	Average

Note:

Level = Read Level + LISN Factor + Cable Loss.

3.2 Peak Output Power Measurement

3.2.1 Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-multipoint antenna reduction operation, the limit has to be reduced by 1dB for every dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

3.2.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	MA2411B

3.3 Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

3.3.1 Test Setup Layout



3.3.2 Test Deviation

There is no deviation with the original standard.

3.3.3 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.3.4 Test Result of Peak Output Power

Final Test Date	Nov. 24, 2010	Test Site No.	TH01-HY
Temperature	20	Humidity	65%
Test Engineer	Cain	Configuration	802.11b/g

Configuration IEEE 802.11b

Channel	Frequency	Conducted Peak Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	17.31	30.00	Complies
6	2437 MHz	17.25	30.00	Complies
11	2462 MHz	17.10	30.00	Complies

Configuration IEEE 802.11g

Channel	Frequency	Conducted Peak Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	15.75	30.00	Complies
6	2437 MHz	15.48	30.00	Complies
11	2462 MHz	15.24	30.00	Complies

3.4 Power Spectral Density Measurement

3.4.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

3.4.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

3.4.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 3 kHz and VBW to 30 kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

3.4.4 Test Setup Layout



3.4.5 Test Deviation

There is no deviation with the original standard.

3.4.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.4.7 Test Result of Power Spectral Density

Final Test Date	Nov. 24, 2010	Test Site No.	TH01-HY
Temperature	20	Humidity	65%
Test Engineer	Cain	Configuration	802.11b/g


Configuration IEEE 802.11b

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-15.75	8.00	Complies
6	2437 MHz	-15.96	8.00	Complies
11	2462 MHz	-16.34	8.00	Complies

Configuration IEEE 802.11g


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-23.24	8.00	Complies
6	2437 MHz	-23.65	8.00	Complies
11	2462 MHz	-24.04	8.00	Complies

Power Density Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 24.NOV.2010 19:06:30

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 24.NOV.2010 19:11:43

Power Density Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 24.NOV.2010 19:18:19

Power Density Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 24.NOV.2010 19:36:03

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 24.NOV.2010 19:42:24

Power Density Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 24.NOV.2010 19:48:46

3.5 6dB Spectrum Bandwidth Measurement

3.5.1 Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

3.5.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

3.5.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

3.5.4 Test Setup Layout



3.5.5 Test Deviation

There is no deviation with the original standard.

3.5.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.5.7 Test Result of 6dB Spectrum Bandwidth

Final Test Date	Nov. 24, 2010	Test Site No.	TH01-HY
Temperature	20	Humidity	65%
Test Engineer	Cain	Configuration	802.11b/g


Configuration IEEE 802.11b

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	10.16	14.96	500	Complies
6	2437 MHz	10.16	14.92	500	Complies
11	2462 MHz	10.16	14.88	500	Complies

Configuration IEEE 802.11g


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.60	16.48	500	Complies
6	2437 MHz	16.60	16.48	500	Complies
11	2462 MHz	16.64	16.48	500	Complies

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 24.NOV.2010 19:05:07

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 24.NOV.2010 19:10:27

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 24.NOV.2010 19:17:10

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2412 MHz



Date: 24.NOV.2010 19:34:19

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 24.NOV.2010 19:40:40

3.6 Radiated Emissions Measurement

3.6.1 Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.6.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.6.3 Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

3.6.4 Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

3.6.5 Test Deviation

There is no deviation with the original standard.

3.6.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.6.7 Results of Radiated Emissions (9kHz~30MHz)

Final Test Date	Nov. 16, 2010	Test Site No.	03CH02-HY
Temperature	25.6	Humidity	57%
Test Engineer	Daniel		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.6.8 Results of Radiated Emissions (30MHz~1GHz)


Final Test Date	Nov. 16, 2010	Test Site No.	03CH02-HY
Temperature	25.6	Humidity	57%
Test Engineer	Daniel	Configuration	Adapter Mode

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	32.910	28.67	-11.33	40.00	40.61	15.11	0.81	27.86	Peak
2	156.100	34.45	-9.05	43.50	49.13	10.64	2.07	27.39	Peak
3	311.300	40.29	-5.71	46.00	50.36	13.88	2.93	26.88	Peak
4	467.470	35.29	-10.71	46.00	43.08	16.63	3.60	28.02	Peak
5	676.990	34.23	-11.77	46.00	38.80	19.15	4.32	28.04	Peak
6	781.750	36.37	-9.63	46.00	39.44	20.01	4.70	27.78	Peak

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	51.340	37.30	-2.70	40.00	54.80	9.16	1.14	27.80	QP
2	156.100	42.31	-1.19	43.50	56.99	10.64	2.07	27.39	QP
3	311.300	42.73	-3.27	46.00	52.80	13.88	2.93	26.88	QP
4	467.470	36.97	-9.03	46.00	44.76	16.63	3.60	28.02	Peak
5	781.750	36.73	-9.27	46.00	39.80	20.01	4.70	27.78	Peak
6	905.910	40.10	-5.90	46.00	42.25	20.17	5.02	27.34	Peak


Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Final Test Date	Nov. 22, 2010	Test Site No.	03CH02-HY
Temperature	25.6	Humidity	57%
Test Engineer	Daniel	Configuration	USB Mode

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	156.100	34.99	-8.51	43.50	49.67	10.64	2.07	27.39	Peak
2	238.550	39.73	-6.27	46.00	51.38	12.62	2.60	26.87	Peak
3	304.510	42.49	-3.51	46.00	52.62	13.78	2.92	26.83	Peak
4	424.790	40.20	-5.80	46.00	48.82	15.76	3.41	27.79	QP
5	443.220	39.21	-6.79	46.00	47.49	16.14	3.47	27.89	QP
6	458.740	40.06	-5.94	46.00	48.04	16.45	3.54	27.97	QP

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	66.860	27.35	-12.65	40.00	46.92	6.85	1.30	27.72	Peak
2	156.100	41.93	-1.57	43.50	56.61	10.64	2.07	27.39	QP
3	238.550	32.53	-13.47	46.00	44.18	12.62	2.60	26.87	Peak
4	338.460	37.70	-8.30	46.00	47.51	14.29	2.99	27.09	QP
5	458.740	37.84	-8.16	46.00	45.82	16.45	3.54	27.97	QP
6	932.100	42.96	-3.04	46.00	44.24	20.82	5.16	27.26	Peak

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamplifier Factor = Level.

3.6.9 Results for Radiated Emissions (1GHz~10th Harmonic)

Final Test Date	Jun. 17, 2010	Test Site No.	03CH02-HY
Temperature	25.6	Humidity	57%
Test Engineer	Daniel	Configuration	802.11b Ch. 1


Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4824.000	53.89	-20.11	74.00	48.06	35.76	4.58	34.51	Peak
2	4824.000	49.88	-4.12	54.00	44.05	35.76	4.58	34.51	Average
3	7236.000	52.79			43.60	37.85	5.63	34.29	Peak
4	9648.000	55.44			44.34	39.39	6.34	34.63	Peak

Note: The items 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4824.000	56.34	-17.66	74.00	51.14	35.13	4.58	34.51	Peak
2	4824.000	52.67	-1.33	54.00	47.47	35.13	4.58	34.51	Average
3	7236.000	53.17			44.93	36.90	5.63	34.29	Peak
4	9648.000	56.16			45.86	38.59	6.34	34.63	Peak

Note: The items 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	Nov. 09, 2010	Test Site No.	03CH02-HY
Temperature	25.6	Humidity	57%
Test Engineer	Daniel	Configuration	802.11b Ch. 6

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4874.000	52.54	-1.46	54.00	46.55	35.83	4.61	34.45	Average
2	4874.000	56.61	-17.39	74.00	50.62	35.83	4.61	34.45	Peak
3	7311.000	52.22	-21.78	74.00	43.01	37.86	5.64	34.29	Peak
4	7311.000	38.53	-15.47	54.00	29.32	37.86	5.64	34.29	Average
5	9748.000	54.37			43.08	39.51	6.36	34.58	Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4874.000	52.80	-1.20	54.00	47.46	35.18	4.61	34.45	Average
2	4874.000	56.36	-17.64	74.00	51.02	35.18	4.61	34.45	Peak
3	7311.000	51.93	-22.07	74.00	43.66	36.92	5.64	34.29	Peak
4	7311.000	37.47	-16.53	54.00	29.20	36.92	5.64	34.29	Average
5	9748.000	53.67			43.18	38.71	6.36	34.58	Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	Nov. 08, 2010	Test Site No.	03CH02-HY
Temperature	25.6	Humidity	57%
Test Engineer	Daniel	Configuration	802.11b Ch. 11

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4924.000	49.48	-4.52	54.00	43.28	35.90	4.68	34.38	Average
2	4924.000	55.04	-18.96	74.00	48.84	35.90	4.68	34.38	Peak
3	7386.000	38.37	-15.63	54.00	29.13	37.88	5.65	34.29	Average
4	7386.000	52.98	-21.02	74.00	43.74	37.88	5.65	34.29	Peak
5	9848.000	55.54			44.09	39.61	6.38	34.54	Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4924.000	52.70	-1.30	54.00	47.17	35.23	4.68	34.38	Average
2	4924.000	56.76	-17.24	74.00	51.23	35.23	4.68	34.38	Peak
3	7386.000	37.85	-16.15	54.00	29.53	36.96	5.65	34.29	Average
4	7386.000	52.25	-21.75	74.00	43.93	36.96	5.65	34.29	Peak
5	9848.000	55.58			44.93	38.81	6.38	34.54	Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	Nov. 08, 2010	Test Site No.	03CH02-HY
Temperature	25.6	Humidity	57%
Test Engineer	Daniel	Configuration	802.11g Ch. 1

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4824.000	38.91	-15.09	54.00	33.08	35.76	4.58	34.51	Average
2	4824.000	53.13	-20.87	74.00	47.30	35.76	4.58	34.51	Peak
3	7236.000	52.50			43.31	37.85	5.63	34.29	Peak
4	9648.000	54.63			43.53	39.39	6.34	34.63	Peak

Note: The items 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	4824.000	40.95	-13.05	54.00	35.75	35.13	4.58	34.51 Average
2	4824.000	53.76	-20.24	74.00	48.56	35.13	4.58	34.51 Peak
3	7236.000	54.77			46.53	36.90	5.63	34.29 Peak
4	9648.000	54.30			44.00	38.59	6.34	34.63 Peak

Note: The items 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	Nov. 09, 2010	Test Site No.	03CH02-HY
Temperature	25.6	Humidity	57%
Test Engineer	Daniel	Configuration	802.11g Ch. 6

Horizontal

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	4874.000	39.52	-14.48	54.00	33.53	35.83	4.61	34.45 Average
2	4874.000	52.28	-21.72	74.00	46.29	35.83	4.61	34.45 Peak
3	7311.000	53.02	-20.98	74.00	43.81	37.86	5.64	34.29 Peak
4	7311.000	38.49	-15.51	54.00	29.28	37.86	5.64	34.29 Average
5	9748.000	54.69			43.40	39.51	6.36	34.58 Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	4874.000	54.39	-19.61	74.00	49.05	35.18	4.61	34.45 Peak
2	4874.000	40.17	-13.83	54.00	34.83	35.18	4.61	34.45 Average
3	7311.000	37.58	-16.42	54.00	29.31	36.92	5.64	34.29 Average
4	7311.000	52.28	-21.72	74.00	44.01	36.92	5.64	34.29 Peak
5	9748.000	54.00			43.51	38.71	6.36	34.58 Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).


Final Test Date	Nov. 08, 2010	Test Site No.	03CH02-HY
Temperature	25.6	Humidity	57%
Test Engineer	Daniel	Configuration	802.11g Ch. 11

Horizontal

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Remark
			dB	dBuV/m	dBuV	dB/m	dB	dB
1	4924.000	38.76	-15.24	54.00	32.56	35.90	4.68	34.38 Average
2	4924.000	52.34	-21.66	74.00	46.14	35.90	4.68	34.38 Peak
3	7386.000	39.48	-14.52	54.00	30.24	37.88	5.65	34.29 Average
4	7386.000	52.67	-21.33	74.00	43.43	37.88	5.65	34.29 Peak
5	9848.000	56.14			44.69	39.61	6.38	34.54 Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	4924.000	40.40	-13.60	54.00	34.87	35.23	4.68	34.38	Average
2	4924.000	53.97	-20.03	74.00	48.44	35.23	4.68	34.38	Peak
3	7386.000	38.41	-15.59	54.00	30.09	36.96	5.65	34.29	Average
4	7386.000	52.07	-21.93	74.00	43.75	36.96	5.65	34.29	Peak
5	9848.000	55.61			44.96	38.81	6.38	34.54	Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.7 Band Edge and Fundamental Emissions Measurement

3.7.1 Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.7.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	11MHz / 1MHz for Peak

3.7.3 Test Procedures

1. The test procedure is the same as section 3.5.3; only the frequency range investigated is limited to 100MHz around band edges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

3.7.4 Test Setup Layout

This test setup layout is the same as that shown in section 3.5.4.

3.7.5 Test Deviation

There is no deviation with the original standard.

3.7.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.7.7 Test Result of Band Edge and Fundamental Emissions

Final Test Date	Jun. 17, 2010	Test Site No.	03CH02-HY
Temperature	25	Humidity	55%
Test Engineer	Daniel	Configuration	802.11b Ch. 1, 6, 11

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	2386.570	60.83	-13.17	74.00	25.78	32.03	3.02	0.00	Peak
2 X	2410.890	112.72			77.61	32.09	3.02	0.00	Peak
1	2386.570	48.42	-5.58	54.00	13.37	32.03	3.02	0.00	Average
2 @	2410.890	108.02			72.91	32.09	3.02	0.00	Average

The item 2 is Fundamental Emissions.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 X	2412.980	113.67			78.56	32.09	3.02	0.00	Peak
1 @	2410.890	109.18			74.07	32.09	3.02	0.00	Average

The item 1 is Fundamental Emissions.

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 X	2460.860	113.25			77.92	32.28	3.05	0.00	Peak
2	2483.500	63.17	-10.83	74.00	27.75	32.34	3.08	0.00	Peak
1 @	2461.050	108.62			73.29	32.28	3.05	0.00	Average
2	2483.500	52.82	-1.18	54.00	17.40	32.34	3.08	0.00	Average

The item 1 is Fundamental Emissions.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamplifier Factor = Level.

Final Test Date	Jun. 17, 2010	Test Site No.	03CH02-HY
Temperature	25.6	Humidity	57%
Test Engineer	Daniel	Configuration	802.11g Ch. 1, 6, 11

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	2390.000	71.51	-2.49	74.00	36.46	32.03	3.02	0.00	Peak
2 X	2418.300	113.29			78.18	32.09	3.02	0.00	Peak
1	2390.000	52.87	-1.13	54.00	17.82	32.03	3.02	0.00	Average
2 X	2417.540	102.62			67.51	32.09	3.02	0.00	Average

The item 2 is Fundamental Emissions.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 X	2438.820	112.87			77.61	32.21	3.05	0.00	Peak
1 X	2439.010	102.56			67.30	32.21	3.05	0.00	Average

The item 1 is Fundamental Emissions.

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1 X	2468.460	109.24			73.88	32.28	3.08	0.00	Peak
2	2483.500	68.29	-5.71	74.00	32.87	32.34	3.08	0.00	Peak
1 X	2465.420	97.67			62.31	32.28	3.08	0.00	Average
2	2483.500	52.84	-1.16	54.00	17.42	32.34	3.08	0.00	Average

The item 1 is Fundamental Emissions.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Emission not in Restricted Band


Final Test Date	Nov. 24, 2010	Test Site No.	TH01-HY
Temperature	20	Humidity	65%
Test Engineer	Cain	Configuration	802.11b/g

Low Band Edge Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 24.NOV.2010 19:03:30

High Band Edge Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 24.NOV.2010 19:15:10

Low Band Edge Plot on Configuration IEEE 802.11g / 2412 MHz



Date: 24.NOV.2010 19:31:41

High Band Edge Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 24.NOV.2010 19:45:27

3.8 Antenna Requirements

3.8.1 Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

3.8.2 Antenna Connector Construction

Please refer FCC 15.247 section 15.203. The antenna specification is not subject to the requirement of FCC 15.247 section 2.2.

4 LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100132	9kHz – 2.75GHz	Sep. 14, 2010	Conduction (CO01-HY)
LISN	MessTec	NNB-2/16Z	2001/004	9kHz – 30MHz	Jan. 19, 2010	Conduction (CO01-HY)
LISN (Support Unit)	MessTec	NNB-2/16Z	2001/009	9kHz – 30MHz	Mar. 01, 2010	Conduction (CO01-HY)
EMI Filter	LINDGREN	LRE-2060	1004	< 450Hz	N/A	Conduction (CO01-HY)
EMI Filter	LINDGREN	N6006	201052	0 – 60Hz	N/A	Conduction (CO01-HY)
RF Cable-CON	HUBER+SUHNER	RG213/U	07611832010001	9kHz – 30MHz	May 05, 2010	Conduction (CO01-HY)
Isolation Transformer	Erika Fiedler OHG	D-65396 Walluf	58	45MHz-2.15GHz	N/A	Conduction (CO01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSU26.5	100015	20Hz ~ 26.5GHz	Nov. 18, 2010	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Apr. 16, 2010	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	N/A	Oct. 22, 2010	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 02, 2009	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 02, 2009	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 30, 2010	Conducted (TH01-HY)
Power Sensor	Anritsu	MA2411B	0917017	300MHz~40GHz	Dec. 03, 2009	Conducted (TH01-HY)
Power Meter	Anritsu	ML2495A	0949003	300MHz~40GHz	Dec. 03, 2009	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Jul. 26, 2010*	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP40	100305/040	9 kHz - 40GHz	Feb. 02, 2010	Radiation (03CH02-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	30 MHz - 1 GHz 3m	May. 01, 2010	Radiation (03CH02-HY)
Amplifier	Agilent	8447D	2944A11146	100 kHz – 1.3 GHz	Jul. 24, 2009 Jul. 23, 2010	Radiation (03CH02-HY)
Amplifier	Agilent	8449B	3008A02373	1GHz – 26.5 GHz	Jul. 24, 2009 Jul. 23, 2010	Radiation (03CH02-HY)
Horn Antenna	ETS-LINDGREN	3117	00091920	1GHz~18GHz	Oct. 22, 2009 Oct. 20, 2010	Radiation (03CH02-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz ~ 1GHz	Feb. 26, 2010	Radiation (03CH02-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX106	03CH02-HY	1GHz~40GHz	Feb. 26, 2010	Radiation (03CH02-HY)
Bilog Antenna	SCHAFFNER	CBL61128	2723	30 MHz - 2 GHz	Nov. 30, 2009	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul. 29, 2010*	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is two year.

5 TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

6 TAF CERTIFICATE OF ACCREDITATION


財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate No. : L1190-100529

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2010 to January 09, 2013
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities


Jay-San Chen
President, Taiwan Accreditation Foundation
Date : May 29, 2010

PI, total 23 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix