



RADIO EXPOSURE TEST REPORT

FCC ID : NKR-ATTGW450

Equipment : 5G Residential Gateway

Brand Name : WNC

Model Name : CGW450-400


Applicant : Wistron NeWeb Corp.
20 Park Avenue II, Hsinchu Science Park, Hsinchu 308,
Taiwan, R.O.C

Manufacturer : NEWEB VIET NAM CO., LTD.
Land Lot CN01, Dong Van III Industrial zone, Dong Van
Ward, Duy Tien Town, Ha Nam Province, VietNam

Standard : 47 CFR Part 2.1091

The product was received on Aug. 01, 2022, and testing was started from Aug. 03, 2022 and completed on Aug. 15, 2022. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.



Approved by: Sam Chen

Sporton International Inc. Hsinchu Laboratory

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 EUT General Information	5
1.2 Accessories	8
1.3 Table for Certified WWAN Module Information	8
1.4 Testing Location	8
2 Maximum Permissible Exposure	9
2.1 Limit of Maximum Permissible Exposure	9
2.2 MPE Calculation Method	9
2.3 MPE Exemption	10
2.4 Calculated Result and Limit	11
Photographs of EUT v02	



TEL : 886-3-656-9065
FAX : 886-3-656-9085
Report Template No.: CB-A1_1 Ver1.1



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

1. The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results.
2. The measurement uncertainty please refer to report "Measurement Uncertainty".

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Sam Chen

Report Producer: Sandy Chuang

1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5725-5850	5180-5240 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)

Evaluation Mode		Uplink Frequency Range (MHz)	Downlink Frequency Range (MHz)	Modulation Type
4G Band (LTE)	Band 2	1850~1910	1930~1990	QPSK, 16QAM, 64QAM, 256QAM
	Band 5	824~849	869~894	
	Band 12	698~716	729~746	
	Band 14	788~798	758~768	
	Band 30	2305~2315	2350~2360	
	Band 66	1710~1780	2110~2200	
Evaluation Mode		Uplink Frequency Range (MHz)	Downlink Frequency Range (MHz)	DFT-s-OFDM (PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM)
5G Band (NR)	n2	1850~1910	1930~1990	
	n5	824~849	869~894	
	n12	698~716	729~746	
	n30	2305~2315	2350~2360	
	n66	1710~1780	2110~2200	
	n77	3450~3550	3450~3550	
		3700~3980	3700~3980	

**1.1.1 Antenna Information**

Ant.	Port		Brand	Model Name	Antenna Type	Connector	Modes of Operation
	WLAN 2.4GHz	WLAN 5GHz					
1	1	1	WNC	48XKAC42	Dipole	I-PEX	WLAN 2.4GHz, 5GHz UNII 1, 3
2	2	2	WNC	48XKAC3F	Dipole	I-PEX	
3	3	3	WNC	48XKAC45	Dipole	I-PEX	
4	4	4	WNC	48XKAC46	Dipole	I-PEX	
5	-	-	WNC	48XKAC3G	Dipole	I-PEX	WLAN 6GHz
6	-	-	WNC	48XKAC3G	Dipole	I-PEX	
7	-	-	WNC	48XKAC3G	Dipole	I-PEX	
8	-	-	WNC	48XKAC3N	Dipole	I-PEX	
9	5	-	WNC	48XKAC3H	Dipole	I-PEX	WLAN 5GHz UNII 2C
10	-	-	WNC	48XKAC3L	Dipole	I-PEX	WWAN full band
11	-	-	WNC	48XKAC3P	Dipole	I-PEX	
12	-	-	WNC	48XKAC3R	Dipole	I-PEX	WWAN dual band
13	-	-	WNC	48XKAC3X	Dipole	I-PEX	
14	-	-	WNC	48XKAC3J	Dipole	I-PEX	
15	-	-	WNC	48XKAC3K	Dipole	I-PEX	WWAN single band
16	-	-	WNC	48XKAC3Y	Dipole	I-PEX	
17	-	-	WNC	48XKAC3Z	Dipole	I-PEX	



Ant.	Antenna Gain (dBi)									
	WLAN 2.4GHz			WLAN 5GHz UNII 1			WLAN 5GHz UNII 3			
1	6.15			4.38			5.49			
2	5.22			3.21			5.48			
3	4.46			4.16			4.07			
4	4.87			4.01			5.91			
Freq.	700 MHz	780 MHz	850 MHz	1800 MHz	2100 MHz	2300 MHz	3300 MHz	4200 MHz		
10	1.7	2.1	3.8	2.8	2.6	5.6	5.0	2.2		
11	2.2	2.8	0.9	3.9	2.4	3.9	4.5	3.4		
Freq.	1800 MHz		2100 MHz		2300 MHz		3300 MHz		4200 MHz	
12	4.1		3.2		3.3		2.8		3.1	
13	3.3		4.1		4.2		3.6		3.5	
14	2.8		3.6		2.7		5.2		4.5	
Freq.	3300 MHz					4200 MHz				
15	4.2					3.6				
16	4.2					3.7				
17	3.0					3.0				

Note1: The above information was declared by manufacturer.

Note2: The antenna 5~9 don't function in this application.

Note3: **For WLAN 2.4GHz function:**

For IEEE 802.11 b/g/n/VHT/ax (4TX/4RX):

Port 1, Port 2, Port 3 and Port 4 can be used as transmitting/receiving antenna.

Port 1, Port 2, Port 3 and Port 4 could transmit/receive simultaneously.

For WLAN 5GHz function:

For IEEE 802.11a/n/ac/ax (4TX/5RX that it includes 1RX for UNII 2A):

Port 1, Port 2, Port 3 and Port 4 can be used as transmitting/receiving antenna.

Port 1, Port 2, Port 3, Port 4 and Port 5 could transmit/receive simultaneously.

Note4: The EUT doesn't enable the DFS band at this time.



1.2 Accessories

Accessories			
Equipment Name	Brand Name	Model Name	Rating
AC Adapter	AT&T	EPS72R0-16	INPUT: 120V~1.8A, 60Hz OUTPUT: 12V, 6A, 72W

1.3 Table for Certified WWAN Module Information

Brand Name	Model Name	FCC ID	Bands
WNC	IMQC	NKRIMQC	4G Band (LTE): B2/B5/B12/B14/B30/B66 5G Band (NR): n2/n5/n12/n30/n66/n77(3450~3550MHz)/n77(3700~3980MHz)

Note: The above information was declared by manufacturer.

1.4 Testing Location

Testing Location Information	
Test Lab. : Sporton International Inc. Hsinchu Laboratory	
Hsinchu	ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)
(TAF: 3787)	TEL: 886-3-656-9065 FAX: 886-3-656-9085
	Test site Designation No. TW3787 with FCC.
	Conformity Assessment Body Identifier (CABID) TW3787 with ISED.



2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	*(100)	<6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500	-	-	f/300	<6
1500-100,000	-	-	5	<6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500	-	-	f/1500	<30
1500-100,000	-	-	1.0	<30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 89 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 MPE Exemption

Option (A): 1.1307(b)(3)(i)(A): Available maximum time-averaged power is < 1 mW

Option (B): 1.1307(b)(3)(i)(B): Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, <= P_{th}.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option (C): 1.1307(b)(3)(i)(C): ERP is below a threshold calculated based on the distance

R between the person and the antenna / radiating structure, where $R > \lambda / 2 \pi$.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.
Note: R is in meters, f is in MHz.	



2.4 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;G1D	6.15	29.77	35.92	0.07	35.99	3.97192	89	0.03990	1.00000
5.2G;D1D	4.38	29.19	33.57	0.50	34.07	2.55270	89	0.02564	1.00000
5.8G;D1D	5.91	29.93	35.84	0.15	35.99	3.97192	89	0.03990	1.00000
LTE Band 5	3.80	35.30	39.10	0.50	39.60	9.12011	89	0.09162	0.54980

MPE Exemption Option C							
Frequency (MHz)	$\lambda/2\pi$ (m)	R (m)	Tune-up EIRP (dBm)	Tune-up ERP (dBm)	Tune-up ERP (W)	ERP Threshold (W)	MPE Exemption
824.7	0.0579	0.89	39.60	37.45	5.559	8.362	Complies
2412	0.0198		35.99	33.84	2.421	15.208	Complies
5745	0.0083		35.99	33.84	2.421	15.208	Complies

Simultaneous Transmission Analysis Mode:

Simultaneous Transmissions Option C							
Frequency (MHz)	R (m)	Tune-up EIRP (dBm)	Tune-up ERP (dBm)	Tune-up ERP (W)	ERP Threshold (W)	Simultaneous Transmissions	Simultaneous Transmissions Limit
824.7	0.89	39.60	37.45	5.559	8.362	0.98	<= 1
2412		35.99	33.84	2.421	15.208		
5745		35.99	33.84	2.421	15.208		

Note: The above antenna gain was declared by manufacturer.

————THE END————