

## RF Exposure Report

**Report No.:** SA180223C02 R1

**FCC ID:** NKR-DHUME997

**Test Model:** Catapult ERM997-1

**Received Date:** Feb. 23, 2018

**Test Date:** Mar. 23 ~ May 07, 2018

**Issued Date:** Jul. 04, 2018

**Applicant:** Wistron NeWeb Corp.

**Address:** 20 Park Avenue II, Hsinchu Science Park, Hsinchu 308, Taiwan, R.O.C.

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record .....</b>	<b>3</b>
<b>1      Certificate of Conformity.....</b>	<b>4</b>
<b>2      RF Exposure.....</b>	<b>5</b>
2.1    Limits for Maximum Permissible Exposure (MPE).....	5
2.2    MPE Calculation Formula .....	5
2.3    Classification .....	5
<b>3      Calculation Result of Maximum Conducted Power.....</b>	<b>6</b>

### Release Control Record

Issue No.	Description	Date Issued
SA180223C02	Original release	May 14, 2018
SA180223C02 R1	Revising Test Model Name.	Jul. 04, 2018

## 1 Certificate of Conformity

**Product:** Marvell 88W8997 11ac 2x2 and BT Combo module

**Brand:** WNC

**Test Model:** Catapult ERM997-1

**Sample Status:** Engineering sample

**Applicant:** Wistron NeWeb Corp.

**Test Date:** Mar. 23 ~ May 07, 2018

**Standards:** FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :**  , **Date:** Jul. 04, 2018  
Polly Chien / Specialist

**Approved by :**  , **Date:** Jul. 04, 2018  
Bruce Chen / Project Engineer

## 2 RF Exposure

### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

### 3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
WLAN: 2412-2462	19.39	6.52	20	<b>0.078</b>	1
WLAN: 5180-5240	17.24	9.26	20	0.089	1
WLAN: 5260-5320	17.29	9.26	20	0.090	1
WLAN: 5500-5700	17.74	9.26	20	0.100	1
WLAN: 5745-5825	17.88	9.26	20	<b>0.103</b>	1
BT EDR: 2402-2480	9.58	3.79	20	0.004	1
BT LE: 2402-2480	9.97	3.79	20	<b>0.005</b>	1

Note:

WLAN

2.4GHz Band: Directional gain =  $G_{ANT\ MAX} + 10 \log(N_{ANT}/N_{SS}) = 3.51\ dBi + 10 \log(2/1) = 6.52\ dBi$

5GHz Band: Directional gain =  $G_{ANT\ MAX} + 10 \log(N_{ANT}/N_{SS}) = 6.25\ dBi + 10 \log(2/1) = 9.26\ dBi$

BT: antenna gain: 3.79dB

Frequency Band	Max Power (dBm)			Total Power (dBm)	Power Limit (dBm)
	WLAN	BT EDR	BT LE		
2.4GHz	19.39	9.58	-	19.82	30
2.4GHz	19.39	-	9.97	19.86	30

Conclusion:

\*The BT could transmit simultaneously either with WLAN 2.4GHz or 5GHz at the same time.

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 + .....etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + BT = 0.078 + 0.005 = 0.083

WLAN 5GHz + BT = 0.103 + 0.005 = 0.108

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---