



FCC RADIO TEST REPORT

Applicant's company	Wistron NeWeb Corporation
Applicant Address	20 Park Avenue II, Hsinchu Science Park, Hsinchu 308,Taiwan,R.O.C.
FCC ID	NKR-DNURW7601
Manufacturer's company	Wistron NeWeb Corporation
Manufacturer Address	20 Park Avenue II, Hsinchu Science Park, Hsinchu 308,Taiwan,R.O.C.

Product Name	802.11 bgn WiFi Module
Brand Name	WNC
Model Name	DNUR-W7601
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Feb. 02, 2013
Final Test Date	Feb. 26, 2013
Submission Type	Original Equipment



Statement

Test result included in this report is for the IEEE 802.11n and IEEE 802.11b/g part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures

and found in compliance with the limit given in **ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart C, KDB**

558074 D01 v02 and KDB 662911 D01 v01r02.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details	3
3.2. Accessories	4
3.3. Table for Filed Antenna	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes	6
3.6. Table for Supporting Units	7
3.7. Table for Parameters of Test Software Setting	8
3.8. Test Configurations	9
4. TEST RESULT	11
4.1. AC Power Line Conducted Emissions Measurement	11
4.2. Maximum Conducted Output Power Measurement	15
4.3. Power Spectral Density Measurement	18
4.4. 6dB Spectrum Bandwidth Measurement	24
4.5. Radiated Emissions Measurement	29
4.6. Emissions Measurement	47
4.7. Antenna Requirements	61
5. LIST OF MEASURING EQUIPMENTS	62
6. TEST LOCATION	64
APPENDIX A. TEST PHOTOS	A1 ~ A8
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE	B1 ~ B3



History of This Test Report



Report No.: FR320203

Certificate No.: CB10202074

1. CERTIFICATE OF COMPLIANCE

Product Name : 802.11 bgn WiFi Module
Brand Name : WNC
Model Name : DNUR-W7601
Applicant : Wistron NeWeb Corporation
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sportun International as requested by the applicant to evaluate the EMC performance of the product sample received on Feb. 02, 2013 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Sam Chen'.

Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	11.61 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	4.30 dB
4.3	15.247(e)	Power Spectral Density	Complies	8.61 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.39 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.15 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n

Items	Description
Product Type	WLAN (1TX, 1RX)
Radio Type	Intentional Transceiver
Power Type	From Host System
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	MCS0 (20MHz): 27.76 MHz ; MCS0 (40MHz): 35.84 MHz
Maximum Conducted Output Power	MCS0 (20MHz): 24.53 dBm ; MCS0 (40MHz): 18.94 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

IEEE 802.11b/g

Items	Description
Product Type	802.11b : WLAN (1TX, 1RX) 802.11g : WLAN (1TX, 1RX)
Radio Type	Intentional Transceiver
Power Type	From Host System
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	11b: 18.96 MHz ; 11g: 29.92MHz
Maximum Conducted Output Power	11b: 25.70 dBm ; 11g: 25.00 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna & Band width

Antenna	Single (TX)	
Band width Mode	20 MHz	40 MHz
IEEE 802.11b	V	X
IEEE 802.11g	V	X
IEEE 802.11n	V	V

IEEE 802.11n spec

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Datarate(Mbps)			
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
					800nsGI		400nsGI					
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5	7.200	15
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0	14.400	30
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5	21.700	45
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0	28.900	60
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0	43.300	90
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0	57.800	120
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5	65.000	135
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0	72.200	150

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

3.2. Accessories

N/A

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Remark
1	WNC	-	PCB Antenna	N/A	3.48	TX / RX
2	WNC	-	PCB Antenna	N/A	1.67	RX


Note: The EUT has two antennas.

For IEEE 802.11b/g/n Mode: (1TX, 1RX)

Only Ant. 1 can be used as transmit antenna.

Either Ant. 1 and Ant. 2 can be used as receiving antenna.

The EUT supports the antenna with RX diversity function.



3.4. Table for Carrier Frequencies

For IEEE 802.11b/g, use Channel 1~Channel 11.

There are two bandwidth systems for IEEE 802.11n.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	MCS0/20MHz	6.5 Mbps	1/6/11	1
	MCS0/40MHz	13.5 Mbps	3/6/9	1
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Power Spectral Density	MCS0/20MHz	6.5 Mbps	1/6/11	1
	MCS0/40MHz	13.5 Mbps	3/6/9	1
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
6dB Spectrum Bandwidth	MCS0/20MHz	6.5 Mbps	1/6/11	1
	MCS0/40MHz	13.5 Mbps	3/6/9	1
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Radiated Emissions 9kHz~1GHz	Normal Link	-	-	-
Radiated Emissions 1GHz~10 th Harmonic	MCS0/20MHz	6.5 Mbps	1/6/11	1
	MCS0/40MHz	13.5 Mbps	3/6/9	1
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1

Band Edge Emissions	MCS0/20MHz	6.5 Mbps	1/6/11	1
	MCS0/40MHz	13.5 Mbps	3/6/9	1
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1

The following test modes were performed for the test:

Mode 1: Place EUT in X axis

Mode 2: Place EUT in Y axis

Mode 3: Place EUT in Z axis

Mode 2 generated the worst case, so it was selected to perform test and its test result was written in the report.

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC). Please refer section 6 for Test Site Address.

3.6. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Wireless AP	Planex	GW-AP54SGX	N/A
Earphone	i-Acom	HOH-323-BK	N/A
Mouse	DELL	MOC5UO	DoC
Notebook	DELL	M1330	E2K4965AGNM

3.7. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11n

Test Software Version	Ralink Wireless Utility 0.0.0.8		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 20MHz	06(Default 0E)	1A(Default 0F)	06(Default 10)
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0 40MHz	01(Default 0E)	09(Default 0F)	03(Default 0F)

Power Parameters of IEEE 802.11b/g


Test Software Version	Ralink Wireless Utility 0.0.0.8		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	0F(Default 0E)	1F(Default 0F)	13(Default 10)
IEEE 802.11g	05(Default 0E)	1C(Default 0F)	08(Default 10)

During the test, "Ralink Wireless Utility 0.0.0.8" under WIN XP was executed the test program to control the EUT continuously transmit RF signal.

3.8. Test Configurations


3.8.1. AC Power Line Conduction Emissions and Radiation Emissions Test Configuration

Test Configuration: AC Power Line Conduction and Radiation Emissions: 30MHz~1GHz



Item	Connection	Shield	Length
1	Power Cable	No	2.6m
2	USB Cable	No	1.8m
3	Audio Cable	No	1.1m
4	USB Cable	No	0.1m

Test Configuration: above 1GHz



Item	Connection	Shield	Length
1	Power Cable	No	2.6m
2	USB Cable	No	0.1m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23°C	Humidity	57%
Test Engineer	Kane Liu	Phase	Line
Configuration	Normal Link		



Freq	Level	Over	Limit	Read	LISN	Cable	Remark
		MHz	dBuV	dB	Line	Level	
1	0.15403	51.11	-14.67	65.78	50.77	0.16	0.18 QP
2	0.15403	35.72	-20.06	55.78	35.38	0.16	0.18 AVERAGE
3 @	0.18838	52.50	-11.61	64.11	52.15	0.15	0.20 QP
4	0.18838	33.59	-20.52	54.11	33.24	0.15	0.20 AVERAGE
5	0.19654	35.52	-18.24	53.76	35.17	0.15	0.20 AVERAGE
6 @	0.19654	51.99	-11.77	63.76	51.64	0.15	0.20 QP
7	0.20833	50.24	-13.03	63.27	49.89	0.15	0.20 QP
8	0.20833	34.31	-18.96	53.27	33.96	0.15	0.20 AVERAGE
9	3.623	33.21	-12.79	46.00	32.71	0.21	0.28 AVERAGE
10	3.623	43.93	-12.07	56.00	43.43	0.21	0.28 QP
11	3.799	33.69	-12.31	46.00	33.18	0.22	0.29 AVERAGE
12	3.799	42.26	-13.74	56.00	41.75	0.22	0.29 QP

Temperature	23°C	Humidity	57%
Test Engineer	Kane Liu	Phase	Neutral
Configuration	Normal Link		



Freq	Level	Over	Limit	Read	LISN	Cable	Remark
		Limit	Line	Level	Factor	Loss	
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15080	34.70	-21.26	55.96	34.44	0.08	0.18 AVERAGE
2	0.15080	50.63	-15.33	65.96	50.37	0.08	0.18 QP
3	0.16155	48.04	-17.34	65.38	47.78	0.08	0.18 QP
4	0.16155	33.58	-21.80	55.38	33.32	0.08	0.18 AVERAGE
5	0.18838	51.78	-12.33	64.11	51.50	0.08	0.20 QP
6	0.18838	33.21	-20.90	54.11	32.93	0.08	0.20 AVERAGE
7	0.19447	35.50	-18.35	53.84	35.22	0.08	0.20 AVERAGE
8	0.19447	51.50	-12.35	63.84	51.22	0.08	0.20 QP
9	0.20396	50.15	-13.30	63.45	49.87	0.08	0.20 QP
10	0.20396	34.56	-18.89	53.45	34.28	0.08	0.20 AVERAGE
11 @	3.759	44.16	-11.84	56.00	43.74	0.13	0.29 QP
12	3.759	34.05	-11.95	46.00	33.63	0.13	0.29 AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limit has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB558074 v01 r02 section 8.2.3 option 3.
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	25°C	Humidity	58%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n
Test Date	Feb. 26, 2013		

Configuration IEEE 802.11n MCS0 20MHz / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	18.00	30.00	Complies
6	2437 MHz	24.53	30.00	Complies
11	2462 MHz	17.40	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	15.35	30.00	Complies
6	2437 MHz	18.94	30.00	Complies
9	2452 MHz	16.02	30.00	Complies

Temperature	25°C	Humidity	58%
Test Engineer	Benson Peng	Configurations	IEEE 802.11b/g
Test Date	Feb. 26, 2013		

Configuration IEEE 802.11b / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	21.90	30.00	Complies
6	2437 MHz	25.70	30.00	Complies
11	2462 MHz	22.80	30.00	Complies

Configuration IEEE 802.11g / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	17.70	30.00	Complies
6	2437 MHz	25.00	30.00	Complies
11	2462 MHz	18.30	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RB	100 kHz
VB	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test procedures refer KDB558074 v01 r02 section 9.1 option 1
2. Spectrum analyzer must be capable of utilizing a number of measurement points in each sweep that is greater than or equal to twice the span/RBW in order to ensure bin-to-bin spacing of \leq RBW/2 so that narrowband signals are not lost between frequency bins.
3. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
4. Ensure that the number of measurement points in the sweep $\geq 2 \times$ span/RBW (use of a greater number of measurement points than this minimum requirement is recommended).
5. Use the peak marker function to determine the maximum level in any 100 kHz band segment within the fundamental EBW.
6. Scale the observed power level to an equivalent level in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where: $BWCF = 10\log(3 \text{ kHz}/100 \text{ kHz}) = -15.2 \text{ dB}$.
7. The resulting PSD level must be $\leq 8 \text{ dBm}$.
8. When measuring power spectral density with multiple antenna systems, add every result of the values by mathematic formula.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	25°C	Humidity	58%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n

Configuration IEEE 802.11n MCS0 20MHz / Ant. 1

Channel	Frequency	Power Density (dBm/100kHz)	BWCF factor (100kHz to 3kHz)	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	7.25	-15.23	-7.98	8.00	Complies
6	2437 MHz	13.48	-15.23	-1.75	8.00	Complies
11	2462 MHz	6.59	-15.23	-8.64	8.00	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1

Channel	Frequency	Power Density (dBm/100kHz)	BWCF factor (100kHz to 3kHz)	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
3	2422 MHz	1.16	-15.23	-14.07	8.00	Complies
6	2437 MHz	4.65	-15.23	-10.58	8.00	Complies
9	2452 MHz	1.86	-15.23	-13.37	8.00	Complies

Temperature	25°C	Humidity	58%
Test Engineer	Benson Peng	Configurations	IEEE 802.11b/g

Configuration IEEE 802.11b / Ant. 1


Channel	Frequency	Power Density (dBm/100kHz)	BWCF factor (100kHz to 3kHz)	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	11.20	-15.23	-4.03	8.00	Complies
6	2437 MHz	14.62	-15.23	-0.61	8.00	Complies
11	2462 MHz	12.29	-15.23	-2.94	8.00	Complies

Configuration IEEE 802.11g / Ant. 1


Channel	Frequency	Power Density (dBm/100kHz)	BWCF factor (100kHz to 3kHz)	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	6.42	-15.23	-8.81	8.00	Complies
6	2437 MHz	13.91	-15.23	-1.32	8.00	Complies
11	2462 MHz	7.64	-15.23	-7.59	8.00	Complies

Note: All the test values were listed in the report.

For plots, only the channel with maximum results was shown.

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 / 2437 MHz


Date: 26.FEB.2013 06:55:01

Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 / 2437 MHz



Date: 26.FEB.2013 06:56:52

Power Density Plot on Configuration IEEE 802.11b / Ant. 1 / 2437 MHz



Date: 26.FEB.2013 06:50:04

Power Density Plot on Configuration IEEE 802.11g / Ant. 1 / 2437 MHz



Date: 26.FEB.2013 06:52:48

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	1-5 % or DTS BW, not exceed 100KHz
VB	$\geq 3 \times$ RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 5.1.1 EBW Measurement Procedure
3. Multiple antenna system was performed in accordance with KDB 662911 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	25°C	Humidity	58%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n

Configuration IEEE 802.11n MCS0 20MHz / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.12	17.60	500	Complies
6	2437 MHz	17.12	27.76	500	Complies
11	2462 MHz	17.04	17.60	500	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	35.20	35.84	500	Complies
6	2437 MHz	35.20	35.84	500	Complies
9	2452 MHz	35.20	35.84	500	Complies

Temperature	25°C	Humidity	58%
Test Engineer	Benson Peng	Configurations	IEEE 802.11b/g

Configuration IEEE 802.11b / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	10.08	12.64	500	Complies
6	2437 MHz	10.08	18.96	500	Complies
11	2462 MHz	10.08	12.96	500	Complies


Configuration IEEE 802.11g / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.40	16.56	500	Complies
6	2437 MHz	16.40	29.92	500	Complies
11	2462 MHz	16.40	16.56	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 / 2462 MHz




Date: 26.FEB.2013 07:22:42

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 / 2437 MHz




Date: 26.FEB.2013 07:23:54

6 dB Bandwidth Plot on Configuration IEEE 802.11b / Ant. 1 / 2437 MHz



Date: 26.FEB.2013 07:17:28

6 dB Bandwidth Plot on Configuration IEEE 802.11g / Ant. 1 / 2437 MHz



Date: 26.FEB.2013 07:19:44

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For Radiated Emissions below 1GHz



For Radiated Emissions above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	25°C	Humidity	60%
Test Engineer	Kenneth Huang	Configurations	Normal Link
Test Date	Feb. 22, 2013		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);


Limit line = specific limits (dBuV) + distance extrapolation factor.




4.5.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	25°C	Humidity	60%
Test Engineer	Kenneth Huang	Configurations	Normal Link

Horizontal



Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Pol/Phase	
		Line	Limit	Level	Loss	Factor	Factor				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	295.78	33.21	46.00	-12.79	43.74	2.51	26.84	13.80	Peak	0	400 HORIZONTAL
2	406.36	34.64	46.00	-11.36	42.58	3.02	27.53	16.57	Peak	0	400 HORIZONTAL
3	455.83	37.62	46.00	-8.38	45.09	3.26	27.82	17.09	Peak	0	400 HORIZONTAL
4	480.00	45.60	46.00	-0.40	52.69	3.33	27.90	17.48	QP	333	100 HORIZONTAL
5	721.61	40.24	46.00	-5.76	43.07	4.18	27.10	20.09	Peak	0	400 HORIZONTAL
6	960.23	36.21	54.00	-17.79	35.84	4.86	26.45	21.96	Peak	0	400 HORIZONTAL

Vertical


Freq	Level	Limit	Over	Read	Cable			Preamp	Antenna	T/Pos	A/Pos	Pol/Phase
					Line	Limit	dB	dBuV	dB	dB	dB/m	
1	36.79	30.18	40.00	-9.82	41.61	0.95	28.00	15.62	Peak	0	100	VERTICAL
2	84.32	29.09	40.00	-10.91	47.39	1.37	27.89	8.22	Peak	0	100	VERTICAL
3 P	479.11	40.83	46.00	-5.17	47.95	3.32	27.90	17.46	Peak	0	100	VERTICAL
4	720.64	37.52	46.00	-8.48	40.36	4.18	27.10	20.08	Peak	0	100	VERTICAL
5	746.83	37.58	46.00	-8.42	40.30	4.21	27.12	20.19	Peak	0	100	VERTICAL
6	830.25	36.65	46.00	-9.35	38.11	4.40	26.90	21.04	Peak	0	100	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11n MCS0 20MHz Ch 1 / Ant. 1
Test Date	Feb. 21, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m						
MHz	dBuV/m	dBuV/m	dB									cm	deg	
1	4824.00	29.95	54.00	-24.05	28.61	3.31	33.06	35.03	Average			100	214	HORIZONTAL
2	4824.00	40.17	74.00	-33.83	38.83	3.31	33.06	35.03	Peak			100	214	HORIZONTAL

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m						
MHz	dBuV/m	dBuV/m	dB									cm	deg	
1	4824.00	33.07	54.00	-20.93	31.73	3.31	33.06	35.03	Average			100	269	VERTICAL
2	4824.00	42.85	74.00	-31.15	41.51	3.31	33.06	35.03	Peak			100	269	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11n MCS0 20MHz Ch 6 / Ant. 1
Test Date	Feb. 21, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB						
MHz														
1	4873.97	33.30	54.00	-20.70	31.84	3.33	33.16	35.03	Average			100	214	HORIZONTAL
2	4873.97	44.28	74.00	-29.72	42.82	3.33	33.16	35.03	Peak			100	214	HORIZONTAL
3	7311.03	32.21	54.00	-21.79	27.59	4.06	35.96	35.40	Average			100	260	HORIZONTAL
4	7311.03	43.60	74.00	-30.40	38.98	4.06	35.96	35.40	Peak			100	260	HORIZONTAL

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB						
MHz														
1	4873.94	39.35	54.00	-14.65	37.89	3.33	33.16	35.03	Average			100	141	VERTICAL
2	4873.94	50.01	74.00	-23.99	48.55	3.33	33.16	35.03	Peak			100	141	VERTICAL
3	7311.03	32.43	54.00	-21.57	27.81	4.06	35.96	35.40	Average			100	199	VERTICAL
4	7311.03	42.85	74.00	-31.15	38.23	4.06	35.96	35.40	Peak			100	199	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11n MCS0 20MHz Ch11 / Ant. 1
Test Date	Feb. 21, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			Loss	Factor	Factor			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4924.00	29.44	54.00	-24.56	27.84	3.35	33.26	35.01	Average	100	161 HORIZONTAL
2	4924.00	40.10	74.00	-33.90	38.50	3.35	33.26	35.01	Peak	100	161 HORIZONTAL
3	7386.00	32.48	54.00	-21.52	27.73	4.06	36.09	35.40	Average	100	86 HORIZONTAL
4	7386.00	43.14	74.00	-30.86	38.39	4.06	36.09	35.40	Peak	100	86 HORIZONTAL

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			Loss	Factor	Factor			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4924.00	29.86	54.00	-24.14	28.26	3.35	33.26	35.01	Average	100	110 VERTICAL
2	4924.00	40.47	74.00	-33.53	38.87	3.35	33.26	35.01	Peak	100	110 VERTICAL
3	7386.00	32.66	54.00	-21.34	27.91	4.06	36.09	35.40	Average	100	39 VERTICAL
4	7386.00	42.81	74.00	-31.19	38.06	4.06	36.09	35.40	Peak	100	39 VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11n MCS0 40MHz Ch 3 / Ant. 1
Test Date	Feb. 21, 2013		

Horizontal

Freq	Level	Limit		Over Line	Read Limit	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m						
1	4844.00	29.86	54.00	-24.14	28.48	3.32	33.09	35.03	Average			100	285	HORIZONTAL
2	4844.00	40.85	74.00	-33.15	39.47	3.32	33.09	35.03	Peak			100	285	HORIZONTAL

Vertical

Freq	Level	Limit		Over Line	Read Limit	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m						
1	4844.00	30.32	54.00	-23.68	28.94	3.32	33.09	35.03	Average			100	234	VERTICAL
2	4844.00	40.01	74.00	-33.99	38.63	3.32	33.09	35.03	Peak			100	234	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11n MCS0 40MHz Ch 6 / Ant. 1
Test Date	Feb. 21, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB						
MHz													cm	deg
1	4874.06	29.33	54.00	-24.67	27.87	3.33	33.16	35.03	Average			100	252	HORIZONTAL
2	4874.06	40.09	74.00	-33.91	38.63	3.33	33.16	35.03	Peak			100	252	HORIZONTAL
3	7311.00	32.60	54.00	-21.40	27.98	4.06	35.96	35.40	Average			100	173	HORIZONTAL
4	7311.00	43.31	74.00	-30.69	38.69	4.06	35.96	35.40	Peak			100	173	HORIZONTAL

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB						
MHz													cm	deg
1	4874.00	29.51	54.00	-24.49	28.05	3.33	33.16	35.03	Average			100	35	VERTICAL
2	4874.00	39.38	74.00	-34.62	37.92	3.33	33.16	35.03	Peak			100	35	VERTICAL
3	7311.00	32.88	54.00	-21.12	28.26	4.06	35.96	35.40	Average			100	105	VERTICAL
4	7311.00	43.10	74.00	-30.90	38.48	4.06	35.96	35.40	Peak			100	105	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11n MCS0 40MHz Ch 9 / Ant. 1
Test Date	Feb. 21, 2013		

Horizontal

Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos
		Line	Limit	Level	Loss	Factor	Factor		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg
1	4904.00	29.45	54.00	-24.55	27.94	3.34	33.19	35.02	Average
2	4904.00	40.59	74.00	-33.41	39.08	3.34	33.19	35.02	Peak
3	7356.00	32.58	54.00	-21.42	27.90	4.06	36.02	35.40	Average
4	7356.00	43.00	74.00	-31.00	38.32	4.06	36.02	35.40	Peak

Vertical

Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos
		Line	Limit	Level	Loss	Factor	Factor		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg
1	4904.00	29.38	54.00	-24.62	27.87	3.34	33.19	35.02	Average
2	4904.00	40.38	74.00	-33.62	38.87	3.34	33.19	35.02	Peak
3	7356.00	32.65	54.00	-21.35	27.97	4.06	36.02	35.40	Average
4	7356.00	44.01	74.00	-29.99	39.33	4.06	36.02	35.40	Peak

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11b CH 1 / Ant. 1
Test Date	Feb. 21, 2013		

Horizontal

Freq	Level	Limit		Over Line	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg
1	4823.95	47.47	54.00	-6.53	46.13	3.31	33.06	35.03	Average	102	301 HORIZONTAL
2	4823.95	50.43	74.00	-23.57	49.09	3.31	33.06	35.03	Peak	102	301 HORIZONTAL

Vertical

Freq	Level	Limit		Over Line	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg
1	4823.89	53.12	74.00	-20.88	51.78	3.31	33.06	35.03	Peak	100	141 VERTICAL
2	4824.00	50.15	54.00	-3.85	48.81	3.31	33.06	35.03	Average	100	141 VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11b CH 6 / Ant. 1
Test Date	Feb. 21, 2013		

Horizontal

Freq	Level	Limit		Over	Read	Cable			Antenna	Preamp	A/Pos	T/Pos	Pol/Phase
		Line	Limit			Loss	Factor	Factor					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg				
1	4874.01	47.29	54.00	-6.71	45.83	3.33	33.16	35.03	Average		100	301	HORIZONTAL
2	4874.01	49.95	74.00	-24.05	48.49	3.33	33.16	35.03	Peak		100	301	HORIZONTAL
3	7311.00	32.77	54.00	-21.23	28.15	4.06	35.96	35.40	Average		100	296	HORIZONTAL
4	7311.00	43.87	74.00	-30.13	39.25	4.06	35.96	35.40	Peak		100	296	HORIZONTAL

Vertical

Freq	Level	Limit		Over	Read	Cable			Antenna	Preamp	A/Pos	T/Pos	Pol/Phase
		Line	Limit			Loss	Factor	Factor					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg				
1	4874.00	53.61	54.00	-0.39	52.15	3.33	33.16	35.03	Average		103	337	VERTICAL
2	4874.00	55.66	74.00	-18.34	54.20	3.33	33.16	35.03	Peak		103	337	VERTICAL
3	7311.00	32.78	54.00	-21.22	28.16	4.06	35.96	35.40	Average		100	220	VERTICAL
4	7311.00	44.81	74.00	-29.19	40.19	4.06	35.96	35.40	Peak		100	220	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11b CH 11 / Ant. 1
Test Date	Feb. 21, 2013		

Horizontal

Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
		Line	Limit	Level	Loss	Factor	Factor		cm	deg	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB			
1	4923.94	43.43	54.00	-10.57	41.83	3.35	33.26	35.01	Average	100	300 HORIZONTAL
2	4923.94	47.92	74.00	-26.08	46.32	3.35	33.26	35.01	Peak	100	300 HORIZONTAL
3	7386.00	43.11	54.00	-10.89	38.36	4.06	36.09	35.40	Average	100	113 HORIZONTAL
4	7386.00	32.71	74.00	-41.29	27.96	4.06	36.09	35.40	Peak	100	113 HORIZONTAL

Vertical

Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
		Line	Limit	Level	Loss	Factor	Factor		cm	deg	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB			
1	4923.97	49.02	54.00	-4.98	47.42	3.35	33.26	35.01	Average	102	344 VERTICAL
2	4923.97	51.55	74.00	-22.45	49.95	3.35	33.26	35.01	Peak	102	344 VERTICAL
3	7386.00	32.34	54.00	-21.66	27.59	4.06	36.09	35.40	Average	100	269 VERTICAL
4	7386.00	42.84	74.00	-31.16	38.09	4.06	36.09	35.40	Peak	100	269 VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11g CH 1 / Ant. 1
Test Date	Feb. 21, 2013		

Horizontal

Freq	Level	Limit		Over Line	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		dB	dB			Loss	Factor	Factor			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4824.00	30.10	54.00	-23.90	28.76	3.31	33.06	35.03	Average	100	252 HORIZONTAL
2	4824.00	39.50	74.00	-34.50	38.16	3.31	33.06	35.03	Peak	100	252 HORIZONTAL

Vertical

Freq	Level	Limit		Over Line	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		dB	dB			Loss	Factor	Factor			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4824.00	33.20	54.00	-20.80	31.86	3.31	33.06	35.03	Average	100	141 VERTICAL
2	4824.00	45.01	74.00	-28.99	43.67	3.31	33.06	35.03	Peak	100	141 VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11g CH 6 / Ant. 1
Test Date	Feb. 21, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			Loss	Factor	Factor			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4874.06	34.71	54.00	-19.29	33.25	3.33	33.16	35.03	Average	100	307 HORIZONTAL
2	4874.06	44.49	74.00	-29.51	43.03	3.33	33.16	35.03	Peak	100	307 HORIZONTAL
3	7311.03	32.20	54.00	-21.80	27.58	4.06	35.96	35.40	Average	100	233 HORIZONTAL
4	7311.03	42.86	74.00	-31.14	38.24	4.06	35.96	35.40	Peak	100	233 HORIZONTAL

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			Loss	Factor	Factor			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4874.03	37.04	54.00	-16.96	35.58	3.33	33.16	35.03	Average	100	147 VERTICAL
2	4874.03	48.05	74.00	-25.95	46.59	3.33	33.16	35.03	Peak	100	147 VERTICAL
3	7311.03	32.26	54.00	-21.74	27.64	4.06	35.96	35.40	Average	100	274 VERTICAL
4	7311.03	42.17	74.00	-31.83	37.55	4.06	35.96	35.40	Peak	100	274 VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11g CH 11 / Ant. 1
Test Date	Feb. 21, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	CableAntenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			Loss	Factor	Factor			
1	4924.00	30.08	54.00	-23.92	28.48	3.35	33.26	35.01	Average	100	300 HORIZONTAL
2	4924.00	40.58	74.00	-33.42	38.98	3.35	33.26	35.01	Peak	100	300 HORIZONTAL
3	7386.00	32.43	54.00	-21.57	27.68	4.06	36.09	35.40	Average	100	225 HORIZONTAL
4	7386.00	43.16	74.00	-30.84	38.41	4.06	36.09	35.40	Peak	100	225 HORIZONTAL

Vertical

Freq	Level	Limit		Over Limit	Read Level	CableAntenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			Loss	Factor	Factor			
1	4924.00	30.28	54.00	-23.72	28.68	3.35	33.26	35.01	Average	100	73 VERTICAL
2	4924.00	39.01	74.00	-34.99	37.41	3.35	33.26	35.01	Peak	100	73 VERTICAL
3	7386.00	33.39	54.00	-20.61	28.64	4.06	36.09	35.40	Average	100	161 VERTICAL
4	7386.00	42.82	74.00	-31.18	38.07	4.06	36.09	35.40	Peak	100	161 VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 kHz / 300 kHz for Peak

4.6.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around band edges.

For Conducted Out of Band Emission Measurement:

1. Test was performed in accordance with KDB 558074 v02 Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure
2. The conducted emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit. Only worst data of each operating mode is presented.

4.6.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Conducted Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.4.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11n MCS0 20MHz Ch 1, 6, 11 / Ant. 1
Test Date	Feb. 21, 2013		

Channel 1

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m					
MHz		dBuV/m	dBuV/m									cm	deg
1	2390.00	53.85	54.00	-0.15	23.46	2.22	28.17	0.00	Average		100	185	VERTICAL
2	2390.00	73.16	74.00	-0.84	42.77	2.22	28.17	0.00	Peak		100	185	VERTICAL
3	2405.11	98.59			68.16	2.22	28.21	0.00	Average		100	185	VERTICAL
4	2419.05	109.07			78.59	2.23	28.25	0.00	Peak		100	185	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m					
MHz		dBuV/m	dBuV/m									cm	deg
1	2387.76	72.41	74.00	-1.59	42.03	2.21	28.17	0.00	Peak		100	9	VERTICAL
2	2390.00	53.18	54.00	-0.82	22.79	2.22	28.17	0.00	Average		100	9	VERTICAL
3	2444.05	104.61	54.00			2.24	28.29	0.00	Average		100	9	VERTICAL
4	2444.69	115.44	74.00			2.24	28.29	0.00	Peak		100	9	VERTICAL
5	2483.50	51.36	54.00	-2.64	20.73	2.26	28.37	0.00	Average		100	9	VERTICAL
6	2483.50	66.02	74.00	-7.98	35.39	2.26	28.37	0.00	Peak		100	9	VERTICAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 11

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase	
		Line	dB			dBuV	dB	dB/m						
MHz		dBuV/m	dBuV/m									cm	deg	
1	2469.05	97.68	54.00				2.26	28.37	0.00	Average		100	185	VERTICAL
2	2469.69	107.88	74.00				2.26	28.37	0.00	Peak		100	185	VERTICAL
3	2483.50	53.69	54.00	-0.31	23.06	2.26	28.37	0.00	Average		100	185	VERTICAL	
4	2483.50	73.02	74.00	-0.98	42.39	2.26	28.37	0.00	Peak		100	185	VERTICAL	

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11n MCS0 40MHz Ch 3, 6, 9 / Ant. 1
Test Date	Feb. 21, 2013		

Channel 3

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB/m					
1	2390.00	53.39	54.00	-0.61	23.00	2.22	28.17	0.00	Average	100	211	HORIZONTAL	
2	2390.00	69.06	74.00	-4.94	38.67	2.22	28.17	0.00	Peak	100	211	HORIZONTAL	
3	2406.62	90.92	54.00			2.22	28.21	0.00	Average	100	211	HORIZONTAL	
4	2410.14	102.15	74.00			2.22	28.21	0.00	Peak	100	211	HORIZONTAL	

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB/m						
1	2389.04	53.49	54.00	-0.51	23.11	2.21	28.17	0.00	Average	100	212	HORIZONTAL		
2	2390.00	69.16	74.00	-4.84	38.77	2.22	28.17	0.00	Peak	100	212	HORIZONTAL		
3	2421.94	93.30	54.00			2.23	28.25	0.00	Average	100	212	HORIZONTAL		
4	2424.82	104.63	74.00			2.23	28.25	0.00	Peak	100	212	HORIZONTAL		
5	2483.50	51.64	54.00	-2.36	21.00	2.26	28.38	0.00	Average	100	212	HORIZONTAL		
6	2483.50	68.01	74.00	-5.99	37.37	2.26	28.38	0.00	Peak	100	212	HORIZONTAL		

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 9

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB/m						
1	2436.30	105.05	74.00			2.23	28.29	0.00	Peak	101	329	VERTICAL		
2	2436.62	93.74	54.00			2.23	28.29	0.00	Average	101	329	VERTICAL		
3	2483.50	53.39	54.00	-0.61	22.76	2.26	28.37	0.00	Average	101	329	VERTICAL		
4	2483.50	70.25	74.00	-3.75	39.62	2.26	28.37	0.00	Peak	101	329	VERTICAL		

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11b CH 1, 6, 11 / Ant. 1
Test Date	Feb. 21, 2013		

Channel 1

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB	dB/m				
1	2389.04	53.23	54.00	-0.77	22.85	2.21	28.17	0.00	Average	101	322	VERTICAL	
2	2389.04	61.33	74.00	-12.67	30.95	2.21	28.17	0.00	Peak	101	322	VERTICAL	
3	2410.24	106.96	54.00			2.22	28.21	0.00	Average	101	322	VERTICAL	
4	2411.04	110.46	74.00			2.22	28.21	0.00	Peak	101	322	VERTICAL	

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB	dB/m					
1	2390.00	51.72	54.00	-2.28	21.33	2.22	28.17	0.00	Average	101	319	VERTICAL		
2	2390.00	60.64	74.00	-13.36	30.25	2.22	28.17	0.00	Peak	101	319	VERTICAL		
3	2435.40	111.55	54.00			2.23	28.29	0.00	Average	101	319	VERTICAL		
4	2435.72	114.98	74.00			2.23	28.29	0.00	Peak	101	319	VERTICAL		
5	2483.50	50.68	54.00	-3.32	20.05	2.26	28.37	0.00	Average	101	319	VERTICAL		
6	2483.50	61.14	74.00	-12.86	30.51	2.26	28.37	0.00	Peak	101	319	VERTICAL		

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 11

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB	dB/m					
1	2462.96	111.18	74.00			2.24	28.33	0.00	Peak	100	202	VERTICAL		
2	2463.76	107.61	54.00			2.24	28.33	0.00	Average	100	202	VERTICAL		
3	2483.50	53.64	54.00	-0.36	23.01	2.26	28.37	0.00	Average	100	202	VERTICAL		
4	2483.50	61.41	74.00	-12.59	30.78	2.26	28.37	0.00	Peak	100	202	VERTICAL		

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Tak	Configurations	IEEE 802.11g CH 1, 6, 11 / Ant. 1
Test Date	Feb. 21, 2013		

Channel 1

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB						
1	2389.52	70.19	74.00	-3.81	39.81	2.21	28.17	0.00	Peak	100	212	HORIZONTAL		
2	2390.00	53.70	54.00	-0.30	23.31	2.22	28.17	0.00	Average	100	212	HORIZONTAL		
3	2404.79	97.94	54.00			2.22	28.21	0.00	Average	100	212	HORIZONTAL		
4	2405.27	107.49	74.00			2.22	28.21	0.00	Peak	100	212	HORIZONTAL		

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB						
1	2390.00	53.60	54.00	-0.40	23.21	2.22	28.17	0.00	Average	100	9	VERTICAL		
2	2390.00	69.26	74.00	-4.74	38.87	2.22	28.17	0.00	Peak	100	9	VERTICAL		
3	2444.05	104.90	54.00			2.24	28.29	0.00	Average	100	9	VERTICAL		
4	2444.37	115.68	74.00			2.24	28.29	0.00	Peak	100	9	VERTICAL		
5	2483.50	52.10	54.00	-1.90	21.47	2.26	28.37	0.00	Average	100	9	VERTICAL		
6	2483.50	65.15	74.00	-8.85	34.52	2.26	28.37	0.00	Peak	100	9	VERTICAL		

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB						
1	2454.79	99.95	54.00			2.24	28.33	0.00	Average	100	31	VERTICAL		
2	2457.03	110.72	74.00			2.24	28.33	0.00	Peak	100	31	VERTICAL		
3	2483.50	53.75	54.00	-0.25	23.12	2.26	28.37	0.00	Average	100	31	VERTICAL		
4	2483.98	72.31	74.00	-1.69	41.68	2.26	28.37	0.00	Peak	100	31	VERTICAL		

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Plot on Configuration IEEE 802.11n MCS0 20MHz / Reference Level




Date: 26.FEB.2013 06:55:01

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 1 (down 30dBc)




Date: 26.FEB.2013 07:08:57

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 6 (down 30dBc)




Date: 26.FEB.2013 07:09:26

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 11 (down 30dBc)




Date: 26.FEB.2013 07:09:51

Plot on Configuration IEEE 802.11n MCS0 40MHz / Reference Level




Date: 26.FEB.2013 06:56:52

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 3 (down 30dBc)




Date: 26.FEB.2013 07:11:07

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 6 (down 30dBc)



Date: 26.FEB.2013 07:11:29

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 9 (down 30dBc)




Date: 26.FEB.2013 07:11:52

Plot on Configuration IEEE 802.11b / Reference Level




Date: 26.FEB.2013 06:50:04

Plot on Configuration IEEE 802.11b / CH 1 (down 30dBc)




Date: 26.FEB.2013 07:00:51

Plot on Configuration IEEE 802.11b / CH 6 (down 30dBc)




Date: 26.FEB.2013 07:04:08

Plot on Configuration IEEE 802.11b / CH 11 (down 30dBc)




Date: 26.FEB.2013 07:04:35

Plot on Configuration IEEE 802.11g / Reference Level




Date: 26.FEB.2013 06:52:48

Plot on Configuration IEEE 802.11g / CH 1 (down 30dBc)




Date: 26.FEB.2013 07:06:25

Plot on Configuration IEEE 802.11g / CH 6 (down 30dBc)



Date: 26.FEB.2013 07:06:54

Plot on Configuration IEEE 802.11g / CH 11 (down 30dBc)



Date: 26.FEB.2013 07:07:32

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Oct. 23, 2012	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov.26, 2012	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9kHz ~ 30MHz	Jun. 22, 2012	Conduction (CO01-CB)
Impulsbegrenzer Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz~30MHz	Feb. 21, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz~30MHz	Dec. 4, 2012	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	-	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Jan. 11, 2012	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
forHorn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 16, 2012	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 20, 2012	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz – 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz – 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 05, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 28, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 27, 2012	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

** Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085