

FCC RADIO TEST REPORT

Applicant's company	Wistron NeWeb Corporation
Applicant Address	20 Park Avenue II, Hsinchu Science Park, Hsinchu 308,Taiwan,R.O.C.
FCC ID	NKR-DTVDCCK
Manufacturer's company	Wistron NeWeb Corporation
Manufacturer Address	20 Park Avenue II, Hsinchu Science Park, Hsinchu 308,Taiwan,R.O.C.

Product Name	DirecTV Cinema Connection Kit
Brand Name	DirecTV
Model Name	DCAW1R0-01
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Received Date	Oct. 29, 2010
Final Test Date	Jan. 12, 2011
Submission Type	Original Equipment



Statement

Test result included is only for the 802.11n, 802.11b/g part and 802.11a (5725 ~ 5850MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	6
3.4. Table for Carrier Frequencies	7
3.5. Table for Test Modes	8
3.6. Table for Testing Locations.....	9
3.7. Table for Supporting Units	10
3.8. Table for Parameters of Test Software Setting	10
3.9. Test Configurations	12
4. TEST RESULT	15
4.1. AC Power Line Conducted Emissions Measurement.....	15
4.2. Maximum Conducted Output Power Measurement.....	19
4.3. Power Spectral Density Measurement	24
4.4. 6dB Spectrum Bandwidth Measurement	31
4.5. Radiated Emissions Measurement	39
4.6. Band Edge Emissions Measurement	62
4.7. Antenna Requirements	72
5. LIST OF MEASURING EQUIPMENTS	73
6. TEST LOCATION.....	75
7. TAF CERTIFICATE OF ACCREDITATION	76
APPENDIX A. PHOTOGRAPHS OF EUT.....	A1 ~ A25
APPENDIX B. TEST PHOTOS.....	B1 ~ B5
APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....	C1 ~C3

History of This Test Report

Original Issue Date: Jan. 24, 2011

Report No.: FR002833AB


- ☒ No additional attachment.
- ☐ Additional attachment were issued as following record:

Attachment No.	Issue Date	Description

1. CERTIFICATE OF COMPLIANCE

Product Name : DirectTV Cinema Connection Kit
Brand Name : DirectTV
Model Name : DCAW1R0-01
Applicant : Wistron NeWeb Corporation
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Oct. 29, 2010 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Jordan Hsiao

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	9.94 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	1.24 dB
4.3	15.247(e)	Power Spectral Density	Complies	6.53 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	1.96 dB
4.6	15.247(d)	Band Edge Emissions	Complies	1.36 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n

Items	Description
Product Type	IEEE 802.11n: WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	<For 2.4GHz Band>: 11 for 20MHz bandwidth <For 5GHz Band>: 5 for 20MHz bandwidth ; 2 for 40MHz bandwidth
Channel Band Width (99%)	<For 2.4GHz Band>: MCS0 (20MHz): 17.40 MHz <For 5GHz Band>: MCS0 (20MHz): 17.48 MHz ; MCS0 (40MHz): 35.28MHz
Conducted Output Power	<For 2.4GHz Band>: MCS0 (20MHz): 28.76 dBm <For 5GHz Band>: MCS0 (20MHz): 28.30 dBm ; MCS0 (40MHz): 28.12 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

IEEE 802.11a/b/g

Items	Description
Product Type	IEEE 802.11a: WLAN (1TX, 3RX) IEEE 802.11b: WLAN (1TX, 1RX) IEEE 802.11g: WLAN (1TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11b/g: 11 ; 11a: 5
Channel Band Width (99%)	11b: 16.48 MHz ; 11g: 16.40 MHz ; 11a: 16.40 MHz
Conducted Output Power	11b: 23.17 dBm ; 11g: 26.22 dBm ; 11a: 24.83 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna & Band width

<For 2.4GHz Band>:

Antenna	Single (TX)		Three (TX)	
Band width Mode	20 MHz	40 MHz	20 MHz	40 MHz
IEEE 802.11b	V	X	X	X
IEEE 802.11g	V	X	X	X
IEEE 802.11n	X	X	V	X

<For 5GHz Band>:

Antenna	Single (TX)		Three (TX)	
Band width Mode	20 MHz	40 MHz	20 MHz	40 MHz
IEEE 802.11a	V	X	X	X
IEEE 802.11n	X	X	V	V

IEEE 802.11n spec

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Datarate(Mbps)			
									800nsGI		400nsGI	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5	7.200	15
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0	14.400	30
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5	21.700	45
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0	28.900	60
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0	43.300	90
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0	57.800	120
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5	65.000	135
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0	72.200	150
8	2	BPSK	1/2	1	104	216	52	108	13.0	27.0	14.444	30
9	2	QPSK	1/2	2	208	432	104	216	26.0	54.0	28.889	60
10	2	QPSK	3/4	2	208	432	156	324	39.0	81.0	43.333	90
11	2	16-QAM	1/2	4	416	864	208	432	52.0	108.0	57.778	120
12	2	16-QAM	3/4	4	416	864	312	648	78.0	162.0	86.667	180
13	2	64-QAM	2/3	6	624	1296	416	864	104.0	216.0	115.556	240
14	2	64-QAM	3/4	6	624	1296	468	972	117.0	243.0	130.000	270
15	2	64-QAM	5/6	6	624	1296	520	1080	130.0	270.0	144.444	300

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

3.2. Accessories

Power	Brand	Model	Rating
Adapter	DIRECTV	MT18-E120150-A1	Input: 120VAC, 60Hz, 0.8A Output: 12VDC, 1.5A
Others			
Coaxial Cable*2, Shielded, 150cm			
Cradle			

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)		Remark
					2.4GHz Band	5GHz Band	
A(J2)	Airgain	M2450DLCM	Embedded Antenna	U.FL	3.80	2.30	TX/RX
B(J3)	Airgain	M2450DLCM	Embedded Antenna	U.FL	3.80	2.30	TX/RX
C(J4)	Airgain	M2450DLCM	Embedded Antenna	U.FL	3.80	2.30	TX/RX

Note: The EUT has three antennas {Ant. A (J2), Ant. B (J3), Ant. C (J4)}.

For IEEE 802.11n mode (3TX/3RX):

Ant. A & Ant. B & Ant. C could both transmit/receive simultaneously.

For IEEE 802.11a mode (1TX/3RX):

The EUT supports the antenna with TX diversity function for IEEE 802.11a mode.

Ant. A and Ant. B and Ant. C can be used as transmitting or receiving antenna.

Due to Ant. A & Ant. B & Ant. C are identical and the Ant. A generated the worst test result, all the tests were base on this setting and recorded in this report.

For IEEE 802.11b mode (1TX/1RX):


Only Ant. A can be used as transmitting/receiving antenna.

For IEEE 802.11g mode (1TX/3RX):

The EUT supports the antenna with TX diversity function for IEEE 802.11g mode.

Ant. A and Ant. B and Ant. C can be used as transmitting or receiving antenna.

Due to Ant. A & Ant. B & Ant. C are identical and the Ant. C generated the worst test result, all the tests were base on this setting and recorded in this report.



3.4. Table for Carrier Frequencies

<For 2.4GHz Band>

Frequency Allocation for 802.11b/g

There are two bandwidth systems for IEEE 802.11n.

For both 20MHz bandwidth systems, use Channel 1 ~Channel 11.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

<For 5GHz Band>

Frequency Allocation for 802.11a

There are two bandwidth systems for IEEE 802.11n.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz	149	5745 MHz	159	5795 MHz
	151	5755 MHz	161	5805 MHz
	153	5765 MHz	165	5825 MHz
	157	5785 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

<For 2.4GHz Band>

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	A+B+C
Max. Peak Conducted Output Power	MCS0/20MHz	6.5Mbps	1/6/11	A, B, C A+B+C
	11b/CCK	1 Mbps	1/6/11	A
	11g/BPSK	6 Mbps	1/6/11	C
Power Spectral Density 6dB Spectrum Bandwidth	MCS0/20MHz	6.5Mbps	1/6/11	A+B+C
	11b/CCK	1 Mbps	1/6/11	A
	11g/BPSK	6 Mbps	1/6/11	C
Radiated Emissions Below 1GHz	Normal Link	Auto	-	A+B+C
Radiated Emissions Above 1GHz	MCS0/20MHz	6.5Mbps	1/6/11	A+B+C
	11b/CCK	1 Mbps	1/6/11	A
	11g/BPSK	6 Mbps	1/6/11	C
Band Edge Emissions	MCS0/20MHz	6.5Mbps	1/11	A+B+C
	11b/CCK	1 Mbps	1/11	A
	11g/BPSK	6 Mbps	1/11	C

<For 5GHz Band>

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	A+B+C
Max. Peak Conducted Output Power	MCS0/20MHz	6.5Mbps	149/157/165	A, B, C A+B+C
	MCS0/40MHz	13.5Mbps	151/159	A, B, C A+B+C
	11a/BPSK	6 Mbps	149/157/165	A
Power Spectral Density 6dB Spectrum Bandwidth	MCS0/20MHz	6.5Mbps	149/157/165	A+B+C
	MCS0/40MHz	13.5Mbps	151/159	A+B+C
	11a/BPSK	6 Mbps	149/157/165	A
Radiated Emissions Below 1GHz	Normal Link	Auto	-	A+B+C
Radiated Emissions Above 1GHz	MCS0/20MHz	6.5Mbps	149/157/165	A+B+C
	MCS0/40MHz	13.5Mbps	151/159	A+B+C
	11a/BPSK	6 Mbps	149/157/165	A
Band Edge Emissions	MCS0/20MHz	6.5Mbps	-	-
	MCS0/40MHz	13.5Mbps	-	-
	11a/BPSK	6 Mbps	-	-

NOTE: All the test modes were listed as below.

Test Mode 1: EUT put vertically on the table + Cradle

Test Mode 2: EUT put horizontally on the table

Due to Mode 1 generated the worst test result, so it was recorded in this report.

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	187376	IC 4086D	-
CO01-CB	Conduction	Hsin Chu	187376	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D505	E2K24GBRL
Notebook	DELL	D505	E2K24GBRL
Notebook	DELL	D400	E2K24GBRL
Notebook	DELL	PP25L	E2K4965AGNM
DIRECT TV	WNEWB	J713	N/A
DIRECT TV	WNEWB	J713	N/A
DIRECT TV AP	WNEWB	J715	N/A

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

<For 2.4GHz Band>

Power Parameters of IEEE 802.11n MCS0 20MHz Ant. A / Ant. B / Ant. C

Test Software Version	DUT GUI		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n 20MHz	25/22/24	23/20/22	24/22/24

Power Parameters of IEEE 802.11b Ant. A,

Test Software Version	DUT GUI		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	20	23	19

Power Parameters of IEEE 802.11g Ant. C

Test Software Version	DUT GUI		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11g	20	17	21

<For 5GHz Band>

Power Parameters of IEEE 802.11n MCS0 20MHz Ant. A / Ant. B / Ant. C

Test Software Version	DUT GUI		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11n 20MHz	6/5/5	6/5/5	6/5/5

Power Parameters of IEEE 802.11n MCS0 40MHz Ant. A / Ant. B / Ant. C

Test Software Version	DUT GUI	
Frequency	5755 MHz	5795 MHz
IEEE 802.11n 40MHz	6/5/5	6/5/5

Power Parameters of IEEE 802.11a Ant. A

Test Software Version	DUT GUI		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	25	25	25


During the test, "DUT GUI" under WIN XP was executed the test program to control the EUT continuously transmit RF signal.

3.9. Test Configurations


3.9.1. Radiation Emissions Test Configuration

Test Configuration: 9kHz~1GHz

Test Mode: Mode 1




Test Configuration: Above 1GHz



3.9.2. AC Power Line Conduction Emissions Test Configuration

Test Mode: Mode 1



4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25.6°C	Humidity	56%
Test Engineer	Sin Chang	Phase	Line
Configuration	Normal Link / Mode 1		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.17034	50.05	-14.89	64.94	49.79	0.06	0.20	QP
2	0.17034	30.15	-24.79	54.94	29.89	0.06	0.20	AVERAGE
3	0.22918	43.62	-18.86	62.48	43.37	0.05	0.20	QP
4	0.22918	31.08	-21.40	52.48	30.83	0.05	0.20	AVERAGE
5	0.53498	46.06	-9.94	56.00	45.83	0.03	0.20	QP
6	0.53498	34.69	-11.31	46.00	34.46	0.03	0.20	AVERAGE
7	0.61726	46.03	-9.97	56.00	45.80	0.03	0.20	QP
8	0.61726	22.99	-23.01	46.00	22.76	0.03	0.20	AVERAGE
9	3.025	43.30	-12.70	56.00	43.01	0.08	0.21	QP
10	3.025	32.04	-13.96	46.00	31.75	0.08	0.21	AVERAGE
11	3.399	30.36	-15.64	46.00	29.99	0.09	0.28	AVERAGE
12	3.399	43.94	-12.06	56.00	43.57	0.09	0.28	QP
13	3.584	45.70	-10.30	56.00	45.31	0.09	0.30	QP
14	3.584	30.89	-15.11	46.00	30.50	0.09	0.30	AVERAGE

Temperature	25.6°C	Humidity	56%
Test Engineer	Sin Chang	Phase	Neutral
Configuration	Normal Link / Mode 1		



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.17866	39.13	-15.42	54.55	38.84	0.09	0.20	AVERAGE
2	0.17866	51.60	-12.95	64.55	51.31	0.09	0.20	QP
3	0.53498	34.07	-11.93	46.00	33.80	0.07	0.20	AVERAGE
4	0.53498	44.15	-11.85	56.00	43.88	0.07	0.20	QP
5	0.61075	35.32	-10.68	46.00	35.05	0.07	0.20	AVERAGE
6	0.61075	45.99	-10.01	56.00	45.72	0.07	0.20	QP
7	2.931	28.51	-17.49	46.00	28.19	0.12	0.20	AVERAGE
8	2.931	42.11	-13.89	56.00	41.79	0.12	0.20	QP
9	3.364	32.60	-13.40	46.00	32.20	0.13	0.27	AVERAGE
10	3.364	44.81	-11.19	56.00	44.41	0.13	0.27	QP
11	3.565	44.71	-11.29	56.00	44.28	0.13	0.30	QP
12	3.565	30.05	-15.95	46.00	29.62	0.13	0.30	AVERAGE
13	14.750	29.23	-20.77	50.00	28.27	0.56	0.40	AVERAGE
14	14.750	36.38	-23.62	60.00	35.42	0.56	0.40	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the peak power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Peak

4.2.3. Test Procedures

Spectrum Parameter	Setting
RF Output Power Method	☒ ANSI C63.10 clause 6.10.2.1 (a) power meter method
RF Output Power Method	☐ ANSI C63.10 clause 6.10.2.1 (b) channel integration method
RF Output Power Method	☐ ANSI C63.10 clause 6.10.3.1 Method 1 - spectral trace averaging
RF Output Power Method	☐ ANSI C63.10 clause 6.10.3.2 Method 2 - zero-span mode with trace averaging
Note: When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.	

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	26°C	Humidity	60%
Test Engineer	Sean Ku	Configurations	IEEE 802.11n
Test Date	Nov. 18, 2010		

<For 2.4GHz Band>

Configuration IEEE 802.11n MCS0 20MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	21.55	30.00	Complies
6	2437 MHz	23.70	30.00	Complies
11	2462 MHz	22.44	30.00	Complies

Configuration IEEE 802.11n MCS0 20MHz Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	22.86	30.00	Complies
6	2437 MHz	24.12	30.00	Complies
11	2462 MHz	22.12	30.00	Complies

Configuration IEEE 802.11n MCS0 20MHz Ant. C

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	22.25	30.00	Complies
6	2437 MHz	24.12	30.00	Complies
11	2462 MHz	22.16	30.00	Complies

Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B + Ant. C

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	27.02	30.00	Complies
6	2437 MHz	28.76	30.00	Complies
11	2462 MHz	27.01	30.00	Complies

<For 5GHz Band>

Configuration IEEE 802.11n MCS0 20MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	24.03	30.00	Complies
157	5785 MHz	24.05	30.00	Complies
165	5825 MHz	23.96	30.00	Complies

Configuration IEEE 802.11n MCS0 20MHz Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	22.64	30.00	Complies
157	5785 MHz	22.99	30.00	Complies
165	5825 MHz	23.46	30.00	Complies

Configuration IEEE 802.11n MCS0 20MHz Ant. C

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	22.29	30.00	Complies
157	5785 MHz	22.70	30.00	Complies
165	5825 MHz	23.11	30.00	Complies

Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B + Ant. C

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	27.82	30.00	Complies
157	5785 MHz	28.06	30.00	Complies
165	5825 MHz	28.30	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	24.00	30.00	Complies
159	5795 MHz	24.14	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	22.55	30.00	Complies
159	5795 MHz	23.03	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. C

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	22.30	30.00	Complies
159	5795 MHz	22.74	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B + Ant. C

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	27.79	30.00	Complies
159	5795 MHz	28.12	30.00	Complies

Temperature	26°C	Humidity	60%
Test Engineer	Sean Ku	Configurations	IEEE 802.11a/b/g
Test Date	Nov. 18, 2010		

Configuration IEEE 802.11b Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	21.73	30.00	Complies
6	2437 MHz	23.17	30.00	Complies
11	2462 MHz	20.84	30.00	Complies

Configuration IEEE 802.11g Ant. C

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	24.89	30.00	Complies
6	2437 MHz	26.22	30.00	Complies
11	2462 MHz	25.50	30.00	Complies

Configuration IEEE 802.11a Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	24.55	29.94	Complies
157	5785 MHz	24.70	29.94	Complies
165	5825 MHz	24.83	29.94	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	30 kHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	10s

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 30kHz and the sweep time to 10s and record the maximum peak value.
5. Measuring multiple antennas, the connector is required to link with spectrum analyser through a combiner.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	26°C	Humidity	60%
Test Engineer	Sean Ku	Configurations	IEEE 802.11n

<For 2.4GHz Band>

Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B + Ant. C

Channel	Frequency	Power Density (dBm / 3kHz)	Max. Limit (dBm/ 3kHz)	Result
1	2412 MHz	-3.43	8.00	Complies
6	2437 MHz	-2.42	8.00	Complies
11	2462 MHz	-6.17	8.00	Complies

<For 5GHz Band>

Configuration 11a IEEE 802.11n MCS0 20MHz Ant. A + Ant. B + Ant. C

Channel	Frequency	Power Density (dBm / 3kHz)	Max. Limit (dBm / 3kHz)	Result
149	5745 MHz	1.00	8.00	Complies
157	5785 MHz	0.24	8.00	Complies
165	5825 MHz	0.97	8.00	Complies

Configuration 11a IEEE 802.11n MCS0 40MHz Ant. A + Ant. B + Ant. C

Channel	Frequency	Power Density (dBm / 3kHz)	Max. Limit (dBm / 3kHz)	Result
151	5755 MHz	1.47	8.00	Complies
159	5795 MHz	0.76	8.00	Complies

Temperature	26°C	Humidity	60%
Test Engineer	Sean Ku	Configurations	IEEE 802.11a/b/g

Configuration IEEE 802.11b Ant. A

Channel	Frequency	Power Density (dBm / 3kHz)	Max. Limit (dBm / 3kHz)	Result
1	2412 MHz	-6.17	8.00	Complies
6	2437 MHz	-6.26	8.00	Complies
11	2462 MHz	-6.31	8.00	Complies

Configuration IEEE 802.11g Ant. C

Channel	Frequency	Power Density (dBm / 3kHz)	Max. Limit (dBm / 3kHz)	Result
1	2412 MHz	-13.43	8.00	Complies
6	2437 MHz	-14.15	8.00	Complies
11	2462 MHz	-12.89	8.00	Complies


Configuration IEEE 802.11a Ant. A

Channel	Frequency	Power Density (dBm / 3kHz)	Max. Limit (dBm / 3kHz)	Result
149	5745 MHz	-4.93	8.00	Complies
157	5785 MHz	-4.96	8.00	Complies
165	5825 MHz	-5.90	8.00	Complies

Note: All the test values were listed in the report.


For plots, only the worse case of DSSS and OFDM modulation were listed in the report.

Power Density Plot on Configuration 11a IEEE 802.11n MCS0 40MHz Ant. A + Ant. B + Ant. C / 5755 MHz




Date: 18.NOV.2010 16:39:12

Power Density Plot on Configuration 11a IEEE 802.11n MCS0 40MHz Ant. A + Ant. B + Ant. C / 5795 MHz




Date: 18.NOV.2010 16:42:36

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B + Ant. C / 2412 MHz




Date: 18.NOV.2010 14:41:44

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B + Ant. C / 2437 MHz




Date: 18.NOV.2010 17:12:15

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B + Ant. C / 2462 MHz




Date: 18.NOV.2010 14:55:51

Power Density Plot on Configuration IEEE 802.11b Ant. A / 2412 MHz




Date: 18.NOV.2010 13:24:48

Power Density Plot on Configuration IEEE 802.11b Ant. A / 2437 MHz



Date: 18.NOV.2010 13:34:40

Power Density Plot on Configuration IEEE 802.11b Ant. A / 2462 MHz



Date: 18.NOV.2010 13:38:55

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.
4. Measuring multiple antennas, the connector is required to link with spectrum analyzer through a combiner.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	26°C	Humidity	60%
Test Engineer	Sean Ku	Configurations	IEEE 802.11n

<For 2.4GHz Band>

Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B + Ant. C

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.56	17.40	500	Complies
6	2437 MHz	17.16	17.40	500	Complies
11	2462 MHz	17.56	17.40	500	Complies

<For 5GHz Band>

Configuration 11a IEEE 802.11n MCS0 20MHz Ant. A + Ant. B + Ant. C

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	17.56	17.48	500	Complies
157	5785 MHz	17.32	17.48	500	Complies
165	5825 MHz	17.32	17.40	500	Complies

Configuration 11a IEEE 802.11n MCS0 40MHz Ant. A + Ant. B + Ant. C

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	35.12	35.20	500	Complies
159	5795 MHz	35.04	35.28	500	Complies

Temperature	26°C	Humidity	60%
Test Engineer	Sean Ku	Configurations	IEEE 802.11a/b/g

Configuration IEEE 802.11b Ant. A

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	12.56	16.40	500	Complies
6	2437 MHz	12.08	16.48	500	Complies
11	2462 MHz	12.60	16.44	500	Complies

Configuration IEEE 802.11g Ant. C

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.48	16.40	500	Complies
6	2437 MHz	16.48	16.40	500	Complies
11	2462 MHz	16.48	16.40	500	Complies


Configuration IEEE 802.11a Ant. A

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.48	16.40	500	Complies
157	5785 MHz	16.52	16.40	500	Complies
165	5825 MHz	16.52	16.40	500	Complies

Note: All the test values were listed in the report.


For plots, only the worse case of DSSS and OFDM modulation were listed in the report.

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. A / 2412 MHz




Date: 18.NOV.2010 13:23:19

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. A / 2437 MHz




Date: 18.NOV.2010 13:33:10

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. A / 2462 MHz




Date: 18.NOV.2010 13:37:25

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. C / 2412 MHz




Date: 18.NOV.2010 15:15:22

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. C / 2437 MHz




Date: 18.NOV.2010 15:23:43

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. C / 2462 MHz




Date: 18.NOV.2010 15:30:17

6 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A / 5745 MHz




Date: 18.NOV.2010 15:53:05

6 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A / 5785MHz



Date: 18.NOV.2010 15:57:45

6 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A / 5825 MHz



Date: 18.NOV.2010 16:00:53

4.5. Radiated Emissions Measurement

4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	Normal Link
Evaluating Date	Nov. 23, 2010		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	Normal Link / Mode 1

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	77.53	30.17	40.00	-9.83	49.83	1.00	27.69	7.03	0	400	Peak	HORIZONTAL
2	249.22	36.66	46.00	-9.34	49.06	1.90	27.00	12.70	0	400	Peak	HORIZONTAL
3	399.57	39.12	46.00	-6.88	48.36	2.30	27.60	16.06	0	400	Peak	HORIZONTAL
4	506.27	39.61	46.00	-6.39	47.30	2.71	28.10	17.70	0	400	Peak	HORIZONTAL
5	583.87	41.34	46.00	-4.66	47.99	2.87	28.10	18.58	0	400	Peak	HORIZONTAL
6	600.36	42.26	46.00	-3.74	48.69	2.90	28.10	18.77	0	400	Peak	HORIZONTAL
7	874.87	35.36	46.00	-10.64	38.97	3.50	27.45	20.34	0	400	Peak	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	45.52	36.52	40.00	-3.48	53.60	0.70	27.80	10.02	0	400	Peak	VERTICAL
2 !	156.10	39.67	43.50	-3.83	53.55	1.48	27.32	11.96	0	400	Peak	VERTICAL
3 !	163.86	39.18	43.50	-4.32	52.62	1.52	27.28	12.32	0	400	Peak	VERTICAL
4	399.57	38.94	46.00	-7.06	48.18	2.30	27.60	16.06	0	400	Peak	VERTICAL
5	499.48	39.82	46.00	-6.18	47.60	2.70	28.09	17.61	0	400	Peak	VERTICAL
6 !	578.05	40.73	46.00	-5.27	47.45	2.86	28.10	18.52	0	400	Peak	VERTICAL
7	749.74	39.78	46.00	-6.22	44.65	3.50	27.80	19.43	0	400	Peak	VERTICAL
8	900.09	39.63	46.00	-6.37	42.90	3.60	27.40	20.53	0	400	Peak	VERTICAL
9	1000.00	39.96	54.00	-14.04	41.97	3.70	27.00	21.29	0	400	Peak	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11n MCS0 20MHz Ch 1 / Ant. A + Ant. B + Ant. C
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4823.57	54.42	74.00	-19.58	53.08	3.31	33.06	35.03	231	112	Peak	HORIZONTAL
2	4824.03	39.94	54.00	-14.06	38.60	3.31	33.06	35.03	231	112	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4823.55	52.50	74.00	-21.50	51.16	3.31	33.06	35.03	300	108	Peak	VERTICAL
2	4823.90	37.89	54.00	-16.11	36.55	3.31	33.06	35.03	300	108	Average	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11n MCS0 20MHz Ch 6 / Ant. A + Ant. B + Ant. C
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4873.44	64.06	74.00	-9.94	62.60	3.33	33.16	35.03	236	110 Peak	HORIZONTAL
2	4873.47	51.47	54.00	-2.53	50.01	3.33	33.16	35.03	236	110 Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4871.63	64.33	74.00	-9.67	62.87	3.33	33.16	35.03	282	113 Peak	VERTICAL
2	4871.93	52.04	54.00	-1.96	50.58	3.33	33.16	35.03	282	113 Average	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11n MCS0 20MHz Ch11 / Ant. A + Ant. B + Ant. C
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	deg	cm	
1	4923.94	36.05	54.00	-17.95	34.45	3.35	33.26	35.01	218	100 Average	HORIZONTAL
2	4924.00	46.56	74.00	-27.44	44.96	3.35	33.26	35.01	218	100 Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	deg	cm	
1	4923.94	36.34	54.00	-17.66	34.74	3.35	33.26	35.01	292	100 Average	VERTICAL
2	4924.09	46.33	74.00	-27.67	44.73	3.35	33.26	35.01	292	100 Peak	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	11a IEEE 802.11n MCS0 20MHz CH 149 / Ant. A + Ant. B + Ant. C
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	11488.91	46.36	60.00	-13.64	37.75	5.11	38.78	35.28	287	100 Average	HORIZONTAL
2	11489.33	59.43	80.00	-20.57	50.82	5.11	38.78	35.28	287	100 Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	11488.97	50.32	60.00	-9.68	41.71	5.11	38.78	35.28	351	100 Average	VERTICAL
2	11489.25	62.68	80.00	-17.32	54.07	5.11	38.78	35.28	351	100 Peak	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	11a IEEE 802.11n MCS0 20MHz CH 157 / Ant. A + Ant. B + Ant. C
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	11569.91	47.00	60.00	-13.00	38.33	5.14	38.83	35.30	327	100 Average	HORIZONTAL
2	11570.09	59.09	80.00	-20.91	50.42	5.14	38.83	35.30	327	100 Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	11570.42	61.48	80.00	-18.52	52.81	5.14	38.83	35.30	100	100 Peak	VERTICAL
2	11570.48	49.59	60.00	-10.41	40.92	5.14	38.83	35.30	100	100 Average	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	11a IEEE 802.11n MCS0 20MHz CH 165 / Ant. A + Ant. B + Ant. C
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	deg	cm		
1	11649.52	58.41	80.00	-21.59	49.69	5.16	38.86	35.30	284	100	Peak	HORIZONTAL
2	11650.50	45.98	60.00	-14.02	37.26	5.16	38.86	35.30	284	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	deg	cm		
1	11650.11	61.57	80.00	-18.43	52.85	5.16	38.86	35.30	346	100	Peak	VERTICAL
2	11650.38	50.59	60.00	-9.41	41.87	5.16	38.86	35.30	346	100	Average	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	11a IEEE 802.11n MCS0 40MHz CH 151 / Ant. A + Ant. B + Ant. C
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor			
						dB	dB/m	dB	deg	cm	
1	11509.87	53.52	80.00	-26.48	44.89	5.12	38.79	35.28	284	100 Peak	HORIZONTAL
2	11509.89	45.01	60.00	-14.99	36.38	5.12	38.79	35.28	284	100 Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor			
						dB	dB/m	dB	deg	cm	
1	11509.89	51.04	60.00	-8.96	42.41	5.12	38.79	35.28	350	100 Average	VERTICAL
2	11510.08	57.41	80.00	-22.59	48.78	5.12	38.79	35.28	350	100 Peak	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	11a IEEE 802.11n MCS0 40MHz CH 159 / Ant. A + Ant. B + Ant. C
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	11589.89	45.86	60.00	-14.14	37.19	5.14	38.83	35.30	285	100 Average	HORIZONTAL
2	11590.08	53.46	80.00	-26.54	44.79	5.14	38.83	35.30	285	100 Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	11589.88	49.96	60.00	-10.04	41.29	5.14	38.83	35.30	350	100 Average	VERTICAL
2	11589.91	56.32	80.00	-23.68	47.65	5.14	38.83	35.30	350	100 Peak	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11b CH 1 / Ant. A
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg		
1 p	4823.82	48.20	74.00	-25.80	48.00	3.00	35.26	32.46	123	158	Peak	HORIZONTAL
2 a	4823.90	44.73	54.00	-9.27	44.53	3.00	35.26	32.46	123	158	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg		
1 a	4823.91	44.87	54.00	-9.13	44.67	3.00	35.26	32.46	115	42	Average	VERTICAL
2 p	4823.96	48.58	74.00	-25.42	48.38	3.00	35.26	32.46	115	42	Peak	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11b CH 6 / Ant. A
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg		
1 a	4873.86	50.60	54.00	-3.40	50.18	3.01	35.15	32.56	133	156	Average	HORIZONTAL
2 p	4874.02	52.61	74.00	-21.39	52.19	3.01	35.15	32.56	133	156	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg		
1 a	4873.89	50.71	54.00	-3.29	50.29	3.01	35.15	32.56	100	88	Average	VERTICAL
2 p	4874.05	52.74	74.00	-21.26	52.32	3.01	35.15	32.56	100	88	Peak	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11b CH 11 / Ant. A
Test Date	Jan. 12, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase	Au Facto
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm			d
1 a	4923.93	47.51	54.00	-6.49	44.74	4.39	35.20	33.58	148	121	Average	HORIZONTAL	0.0
2 p	4923.93	51.31	74.00	-22.69	48.54	4.39	35.20	33.58	148	121	Peak	HORIZONTAL	0.0

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg		
1 a	4823.91	44.87	54.00	-9.13	44.67	3.00	35.26	32.46	115	42	Average	VERTICAL
2 p	4823.96	48.58	74.00	-25.42	48.38	3.00	35.26	32.46	115	42	Peak	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11g CH 1 / Ant. C
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4823.92	35.93	54.00	-18.07	34.59	3.31	33.06	35.03	155	124	Average	HORIZONTAL
2	4824.12	44.01	74.00	-29.99	42.67	3.31	33.06	35.03	155	124	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4823.96	36.47	54.00	-17.53	35.13	3.31	33.06	35.03	107	100	Average	VERTICAL
2	4826.24	50.50	74.00	-23.50	49.16	3.31	33.06	35.03	107	100	Peak	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11g CH 6 / Ant. C
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg		
1 a	4875.80	39.44	54.00	-14.56	39.02	3.01	35.15	32.56	102	70	Average	HORIZONTAL
2 p	4876.28	52.56	74.00	-21.44	52.14	3.01	35.15	32.56	102	70	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg		
1 p	4873.53	52.34	74.00	-21.66	51.92	3.01	35.15	32.56	112	104	Peak	VERTICAL
2 a	4873.94	39.84	54.00	-14.16	39.42	3.01	35.15	32.56	112	104	Average	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11g CH 11 / Ant. C
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4924.00	39.51	54.00	-14.49	37.91	3.35	33.26	35.01	39	100	Average	HORIZONTAL
2	4926.60	51.30	74.00	-22.70	49.70	3.35	33.26	35.01	39	100	Peak	HORIZONTAL
3	7385.20	38.59	54.00	-15.41	33.84	4.06	36.09	35.40	107	141	Average	HORIZONTAL
4	7390.00	53.04	74.00	-20.96	48.29	4.06	36.09	35.40	107	141	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4924.00	40.76	54.00	-13.24	39.16	3.35	33.26	35.01	114	101	Average	VERTICAL
2	4926.30	53.65	74.00	-20.35	52.05	3.35	33.26	35.01	114	101	Peak	VERTICAL
3	7385.10	39.15	54.00	-14.85	34.40	4.06	36.09	35.40	90	100	Average	VERTICAL
4	7386.40	52.94	74.00	-21.06	48.19	4.06	36.09	35.40	90	100	Peak	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11a CH 149 / Ant. A
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg		
1 a	11490.00	51.08	60.00	-8.92	42.57	4.76	34.75	38.50	103	33	Average	HORIZONTAL
2 p	11495.00	63.22	80.00	-16.78	54.69	4.78	34.75	38.50	103	33	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg		
1 p	11490.00	64.09	80.00	-15.91	55.58	4.76	34.75	38.50	101	106	Peak	VERTICAL
2 a	11490.10	52.70	60.00	-7.30	44.19	4.76	34.75	38.50	101	106	Average	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11a CH 157 / Ant. A
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg		
1 p	11568.40	63.17	80.00	-16.83	54.60	4.86	34.80	38.51	104	32	Peak	HORIZONTAL
2 a	11570.00	52.07	60.00	-7.93	43.47	4.91	34.82	38.51	104	32	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg		
1 a	11570.10	51.80	60.00	-8.20	43.20	4.91	34.82	38.51	104	104	Average	VERTICAL
2 p	11574.90	62.95	80.00	-17.05	54.35	4.91	34.82	38.51	104	104	Peak	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11a CH 165 / Ant. A
Test Date	Nov. 17, 2010		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg		
1 p	11649.90	62.92	80.00	-17.08	54.26	5.03	34.90	38.53	103	28	Peak	HORIZONTAL
2 a	11650.20	50.98	60.00	-9.02	42.32	5.03	34.90	38.53	103	28	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg		
1 p	11649.80	62.67	80.00	-17.33	54.01	5.03	34.90	38.53	100	106	Peak	VERTICAL
2 a	11650.20	51.09	60.00	-8.91	42.43	5.03	34.90	38.53	100	106	Average	VERTICAL

4.6. Band Edge Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz / 100 KHz for Peak

4.6.3. Test Procedures

- The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
- In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11n MCS0 20MHz Ch 1, 6, 11 / Ant. A + Ant. B + Ant. C
Test Date	Jan. 12, 2011		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase	Au Facto
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm			d
1	2389.00	65.71	74.00	-8.29	34.80	2.86	0.00	28.05	74	153	Peak	HORIZONTAL	0.0
2	2390.00	52.36	54.00	-1.64	21.43	2.88	0.00	28.05	74	153	Average	HORIZONTAL	0.0
3	2409.00	112.62	74.00			2.88	0.00	28.09	74	153	Peak	HORIZONTAL	0.0
4	2417.40	103.22	54.00			2.89	0.00	28.13	74	153	Average	HORIZONTAL	0.0

Item 3, 4 are the fundamental frequency at 2412 MHz

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase	Au Facto
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm			d
1	2389.20	51.32	54.00	-2.68	20.41	2.86	0.00	28.05	61	156	Average	HORIZONTAL	0.0
2	2390.00	64.53	74.00	-9.47	33.60	2.88	0.00	28.05	61	156	Peak	HORIZONTAL	0.0
3	2430.60	101.91	54.00			2.89	0.00	28.13	61	156	Average	HORIZONTAL	0.0
4	2431.00	112.35	74.00			2.89	0.00	28.13	61	156	Peak	HORIZONTAL	0.0
5	2483.50	48.80	54.00	-5.20	17.61	2.93	0.00	28.26	61	156	Average	HORIZONTAL	0.0
6	2489.10	61.60	74.00	-12.40	30.37	2.93	0.00	28.30	61	156	Peak	HORIZONTAL	0.0

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase	Au Facto
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm			d
1	2467.20	102.06	54.00			2.93	0.00	28.22	70	176	Average	HORIZONTAL	0.0
2	2468.00	111.38	74.00			2.93	0.00	28.22	70	176	Peak	HORIZONTAL	0.0
3	2483.50	52.64	54.00	-1.36	21.45	2.93	0.00	28.26	70	176	Average	HORIZONTAL	0.0
4	2484.70	65.45	74.00	-8.55	34.26	2.93	0.00	28.26	70	176	Peak	HORIZONTAL	0.0

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11b CH 1, 6, 11 / Ant. A
Test Date	Jan. 12, 2011		

Channel 1

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase	Au
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm			d
1 !	2386.20	52.61	54.00	-1.39	21.70	2.86	0.00	28.05	57	154	Average	HORIZONTAL	0.0
2	2386.40	62.34	74.00	-11.66	31.43	2.86	0.00	28.05	57	154	Peak	HORIZONTAL	0.0
3 p	2411.00	108.68	74.00			2.88	0.00	28.09	57	154	Peak	HORIZONTAL	0.0
4 a	2411.20	103.85	54.00			2.88	0.00	28.09	57	154	Average	HORIZONTAL	0.0

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase	Au
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm			d
1	2388.80	60.23	74.00	-13.77	29.32	2.86	0.00	28.05	58	157	Peak	HORIZONTAL	0.0
2 !	2389.60	48.42	54.00	-5.58	17.51	2.86	0.00	28.05	58	157	Average	HORIZONTAL	0.0
3 p	2436.20	105.72	74.00			2.89	0.00	28.18	58	157	Peak	HORIZONTAL	0.0
4 a	2436.20	101.78	54.00			2.89	0.00	28.18	58	157	Average	HORIZONTAL	0.0
5	2498.70	44.68	54.00	-9.32	13.44	2.94	0.00	28.30	58	157	Average	HORIZONTAL	0.0

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg		
1 p	2461.71	112.18	74.00			2.08	0.00	27.76	102	128	Peak	VERTICAL
2 a	2462.58	104.55	54.00			2.08	0.00	27.76	102	128	Average	VERTICAL
3 !	2487.43	52.50	54.00	-1.50	22.67	2.10	0.00	27.73	102	128	Average	VERTICAL
4	2487.70	63.31	74.00	-10.69	33.51	2.10	0.00	27.70	102	128	Peak	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	25.6°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11g CH 1, 6, 11 / Ant. C
Test Date	Jan. 12, 2011		

Channel 1

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase	Au
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	deg	cm			d
1 !	2389.20	68.91	74.00	-5.09	38.00	2.86	0.00	28.05	64	151	Peak	HORIZONTAL	0.0
2 !	2390.00	52.60	54.00	-1.40	21.67	2.88	0.00	28.05	64	151	Average	HORIZONTAL	0.0
3 a	2405.60	101.22	54.00			2.88	0.00	28.09	64	151	Average	HORIZONTAL	0.0
4 p	2407.60	110.84	74.00			2.88	0.00	28.09	64	151	Peak	HORIZONTAL	0.0

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase	Au
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	deg	cm			d
1	2388.60	65.77	74.00	-8.23	34.86	2.86	0.00	28.05	73	155	Peak	HORIZONTAL	0.0
2 !	2390.00	52.46	54.00	-1.54	21.53	2.88	0.00	28.05	72	155	Average	HORIZONTAL	0.0
3 a	2430.00	105.78	54.00			2.89	0.00	28.13	73	155	Average	HORIZONTAL	0.0
4 p	2430.20	115.36	74.00			2.89	0.00	28.13	73	155	Peak	HORIZONTAL	0.0
5	2483.50	60.30	74.00	-13.70	29.11	2.93	0.00	28.26	73	155	Peak	HORIZONTAL	0.0
6 !	2483.50	49.56	54.00	-4.44	18.37	2.93	0.00	28.26	73	155	Average	HORIZONTAL	0.0

Item 3, 4 are the fundamental frequency at 2437 MHz.


Channel 11

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase	Au
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	deg	cm			d
1 a	2455.00	101.35	54.00			2.91	0.00	28.22	74	154	Average	HORIZONTAL	0.0
2 p	2455.20	110.56	74.00			2.91	0.00	28.22	74	154	Peak	HORIZONTAL	0.0
3 !	2483.50	52.32	54.00	-1.68	21.13	2.93	0.00	28.26	74	154	Average	HORIZONTAL	0.0
4	2483.90	66.35	74.00	-7.65	35.16	2.93	0.00	28.26	74	154	Peak	HORIZONTAL	0.0

Item 1, 2 are the fundamental frequency at 2462 MHz.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B + Ant. C / 2412 MHz




Date: 18.NOV.2010 14:41:54

High Band Edge Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B + Ant. C / 2462 MHz




Date: 18.NOV.2010 14:56:01

Low Band Edge Plot on Configuration 11a IEEE 802.11n MCS0 20MHz Ant. A + Ant. B + Ant. C/ 5745 MHz




Date: 18.NOV.2010 16:25:56

High Band Edge Plot on Configuration 11a IEEE 802.11n MCS0 20MHz Ant. A + Ant. B + Ant. C/ 5825 MHz




Date: 18.NOV.2010 16:32:47

Low Band Edge Plot on Configuration 11a IEEE 802.11n MCS0 40MHz Ant. A + Ant. B + Ant. C/ 5755 MHz




Date: 18.NOV.2010 16:39:22

High Band Edge Plot on Configuration 11a IEEE 802.11n MCS0 40MHz Ant. A + Ant. B + Ant. C/ 5795 MHz




Date: 18.NOV.2010 16:42:46

Low Band Edge Plot on Configuration IEEE 802.11b Ant. A / 2412 MHz




Date: 18.NOV.2010 13:24:58

High Band Edge Plot on Configuration IEEE 802.11b Ant. A / 2462 MHz




Date: 18.NOV.2010 13:39:05

Low Band Edge Plot on Configuration IEEE 802.11g Ant. C / 2412 MHz




Date: 18.NOV.2010 15:17:01

High Band Edge Plot on Configuration IEEE 802.11g Ant. C / 2462 MHz




Date: 18.NOV.2010 15:31:56

Low Band Edge Plot on Configuration IEEE 802.11a Ant. A / 5745 MHz



Date: 18.NOV.2010 15:54:44

High Band Edge Plot on Configuration IEEE 802.11a Ant. A / 5825 MHz



Date: 18.NOV.2010 16:02:32

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Sep. 01, 2010	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Apr. 24, 2010	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9K ~ 30MHz	Oct. 30, 2010	Conduction (CO01-CB)
PULSE LIMITER	R&S	ESH3-Z2	100430	9K~30MHz	Jan. 04, 2010	Conduction (CO01-CB)
COND Cable	-	Cable	-	0.15MHz~30MHz	Dec. 01, 2010	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Oct. 17, 2010	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 13, 2010	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Oct. 08, 2010	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 17, 2010	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 06, 2010	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Nov. 17, 2010	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP	100304	9kHz ~ 40GHz	Nov. 06, 2010	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 06, 2010	Radiation (03CH01-CB)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Sep. 09, 2010*	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N/A	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N/A	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	-	30 MHz - 1 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	-	1 GHz - 40 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	-	1 GHz - 40 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP30	100023	9KHz~30GHz	Mar. 05, 2010	Conducted (TH01-CB)
Temp. and Humidity Chamber	TEN BILLION	TTH-D3SP	TBN-931011	-30~100°C	May. 21, 2010	Conducted (TH01-CB)
Signal Generator	R&S	SMR40	100302	10MHz-40GHz	Mar. 09, 2010	Conducted (TH01-CB)
RF Power Divider	HP	11636A	00306	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	44100	1839	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Power Splitter	Anaren	42100	17930	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
Signal generator	R&S	SMU200A	102782	10MHz-40GHz	Mar. 09, 2010	Conducted (TH01-CB)
Horn Antenna	COM-POWER	AH-118	071187	1GHz – 18GHz	Apr. 16, 2010	Conducted (TH01-CB)
Horn Antenna	COM-POWER	AH-118	071042	1GHz – 18GHz	Oct. 14, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-12	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-13	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Sep. 13, 2010	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Sep. 08, 2010	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

Note: For “*” Calibration Interval of instruments listed above is two years.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 728, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-091230

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2010 to January 09, 2013
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities



Jay-San Chen
President, Taiwan Accreditation Foundation
Date : December 30, 2009

P1, total 22 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix