




# FCC RF Exposure Report

**FCC ID** : NKR-MB20  
**Product Description** : WLAN/BLE module  
**Model No.** : DHSK-MB20  
**Brand Name** : Wistron NeWeb Corporation  
**Applicant** : Wistron NeWeb Corporation  
**Address** : 20 Park Avenue II, Hsinchu Science Park,  
Hsinchu 308, Taiwan, R.O.C.  
**Standard** : 47 CFR FCC Part 2.1091  
**Received Date** : Apr. 02, 2024  
**Tested Date** : Jul. 15 ~ Jul. 18, 2024

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:



Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager

## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>4</b>
1.1	INFORMATION .....	4
<b>2</b>	<b>RF EXPOSURE TEST EXEMPTIONS.....</b>	<b>5</b>
2.1	1-mW TEST EXEMPTION .....	5
2.2	SAR-BASED EXEMPTION .....	5
2.3	MPE-BASED EXEMPTION.....	5
2.4	REFERENCE GUIDANCE .....	6
2.5	DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE .....	6
2.6	MEASUREMENT UNCERTAINTY.....	6
2.7	EXEMPTION CALCULATION .....	6
<b>3</b>	<b>TEST LABORATORY INFORMATION .....</b>	<b>7</b>

## Release Record

Report No.	Version	Description	Issued Date
FA380701-02	Rev. 01	Initial issue	Aug. 16, 2024

## 1 General Description

### 1.1 INFORMATION

#### 1.1.1 Product Details

The following models are provided to this EUT.

Brand Name	Model Name	Product Name	Product Description	Description
Wistron NeWeb Corporation	DHSK-MB20	81DHSK08.G01	WLAN/BLE module	LED *0, Button*0, level shifter*4, connector*2
		81DHSK08.G02		LED *0, Button*0, level shifter*1, connector*1
		81DHSK08.G03		LED *2, Button*1, level shifter*4, connector*2

◆ Remark: RF PCB layout and RF components of all the above listed models are the same, no change.

## 2 RF Exposure Test Exemptions

### 2.1 1-mW TEST EXEMPTION

Available maximum time-averaged power is no more than 1 mW.

### 2.2 SAR-BASED EXEMPTION

This exemption is applicable to the frequency range between 300 MHz and 6 GHz, with test separation distances between 0.5 cm and 40 cm, and for all RF sources in fixed, mobile, and portable device exposure conditions.

The maximum time-averaged power or effective radiated power (ERP), whichever is greater,  $\leq P_{th}$

$$P_{th} (\text{mW}) = \text{ERP}_{20\text{cm}}(d/20)^x \quad d \leq 20\text{cm}$$

$$P_{th} (\text{mW}) = \text{ERP}_{20\text{cm}} \quad 20 \text{ cm} < d \leq 40\text{cm}$$

Where  $x = -\log_{10}\left(\frac{60}{\text{ERP}_{20\text{cm}}\sqrt{f}}\right)$

$$P_{th} (\text{mW}) = \text{ERP}_{20\text{cm}}(\text{mW}) = 2040f \quad 0.3\text{GHz} \leq f < 1.5 \text{ GHz}$$

$$P_{th} (\text{mW}) = \text{ERP}_{20\text{cm}}(\text{mW}) = 3060 \quad 1.5\text{GHz} \leq f < 6 \text{ GHz}$$

Frequency (MHz)	Power Thresholds	
	mW	dBm
663	1353	31.31
699	1426	31.54
704	1436	31.57
777	1585	32.00
824	1681	32.26
902	1840	32.65
1500 ~ 6000	3060	34.86

### 2.3 MPE-BASED EXEMPTION

For a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters.

Radio Source Frequency		Minimum Distance			Threshold ERP	
$F_L$ MHz	$F_H$ MHz	$\lambda_L / 2\pi$	$\lambda_H / 2\pi$	W		
0.3	-	1.34	159 m	-	35.6 m	$1920 R^2$
1.34	-	30	35.6 m	-	1.6 m	$3450 R^2/f^2$
30	-	300	1.6 m	-	159 mm	$3.83 R^2$
300	-	1500	159 mm	-	31.8 mm	$0.0128 R^2f$
1500	-	100000	31.8 mm	-	0.5 mm	$19.2 R^2$

Note: R is the antenna-person separation distance.

## 2.4 REFERENCE GUIDANCE

447498 D04 Interim General RF Exposure Guidance v01.

## 2.5 DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE

None

## 2.6 MEASUREMENT UNCERTAINTY

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Parameters	Uncertainty
Conducted power	±0.808 dB

### Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

### Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

## 2.7 EXEMPTION CALCULATION

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Maximum Tune Up Limit (dBm)	Antenna Gain (dBi)	EIRP (dBm)	ERP (dBm)	ERP (mW)	SAR-Based Exemption Thresholds (mW)	Ratio	Pass/ Fail
2412-2462 WLAN	22.76	23.0	1.13	24.13	21.98	157.76	3060	0.052	Pass
2402-2480 BLE	8.59	9.0	1.13	10.13	7.98	6.28	3060	0.0021	Pass

Note:

Minimum separation distance = 20 cm.

### 3 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

**Linkou**

Tel: 886-2-2601-1640  
No.30-2, Ding Fwu Tsuen, Lin Kou  
District, New Taipei City, Taiwan  
(R.O.C.)

**Kwei Shan**

Tel: 886-3-271-8666  
No.3-1, Lane 6, Wen San 3rd  
St., Kwei Shan Dist., Tao Yuan  
City 33381, Taiwan (R.O.C.)  
No.2-1, Lane 6, Wen San 3rd  
St., Kwei Shan Dist., Tao Yuan  
City 33381, Taiwan (R.O.C.)

**Kwei Shan Site II**

Tel: 886-3-271-8640  
No.14-1, Lane 19, Wen San 3rd  
St., Kwei Shan Dist., Tao Yuan  
City 33381, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666  
Fax: 886-3-318-0345  
Email: ICC\_Service@icertifi.com.tw

—END—