


FCC Test Report

FCC ID : NKR-MB43
Equipment : Wireless module
Model No. : DHSC-MB43
Brand Name : WNC
Applicant : Wistron NeWeb Corporation
Address : 20 Park Avenue II, Hsinchu Science Park,
Hsinchu 308,Taiwan,R.O.C.
Standard : 47 CFR FCC Part 15.247
Received Date : Jul. 13, 2022
Tested Date : Jul. 26 ~ Aug. 01, 2022

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:


Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	8
1.5	Test Standards	9
1.6	Reference Guidance	9
1.7	Deviation from Test Standard and Measurement Procedure.....	9
1.8	Measurement Uncertainty	9
2	TEST CONFIGURATION.....	10
2.1	Testing Facility	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS	11
3.1	6dB and Occupied Bandwidth.....	11
3.2	Conducted Output Power	12
3.3	Power Spectral Density	13
3.4	Unwanted Emissions into Restricted Frequency Bands	14
3.5	Emissions in Non-Restricted Frequency Bands.....	16
3.6	AC Power Line Conducted Emissions	17
4	TEST LABORATORY INFORMATION	18

Appendix A. 6dB and Occupied Bandwidth

Appendix B. Conducted Output Power

Appendix C. Power Spectral Density

Appendix D. Unwanted Emissions into Restricted Frequency Bands

Appendix E. Emissions in Non-Restricted Frequency Bands

Appendix F. AC Power Line Conducted Emissions

Release Record

Report No.	Version	Description	Issued Date
FR271305AC	Rev. 01	Initial issue	Nov. 25, 2022

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emission	[dBuV]: 0.555MHz 34.68 (Margin -11.32dB) - AV	Pass
15.247(d) 15.209	Unwanted Emissions	[dBuV/m at 3m]: 2483.50MHz 53.00 (Margin -1.00dB) - AV	Pass
15.247(b)(3)	Conducted Output Power	Max Power [dBm]: 25.24	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	Data Rate / MCS
2400-2483.5	b	2412-2462	1-11 [11]	1	1-11 Mbps
2400-2483.5	g	2412-2462	1-11 [11]	1	6-54 Mbps
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	1	MCS 0-7
Note 1: RF output power specifies that Maximum Conducted (Average) Output Power. Note 2: DSSS-DBPSK, DQPSK, CCK modulation OFDM- BPSK, QPSK, 16QAM and 64QAM modulation.					

1.1.2 Antenna Details

Ant. No.	Type	Connector	Gain (dBi)
1	PIFA	No	2.6

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	12.7Vdc from host
-------------------	-------------------

1.1.4 Accessories

N/A

1.1.5 Channel List

Channel	Frequency(MHz)
1	2412
2	2417
3	2422
4	2427
5	2432
6	2437
7	2442
8	2447
9	2452
10	2457
11	2462

1.1.6 Test Tool and Duty Cycle

Test Tool	Tera Term, V 4.66		
Duty Cycle and Duty Factor	Mode	Duty Cycle (%)	Duty Factor (dB)
	11b	99.59%	0.02
	11g	94.31%	0.25
	HT20	93.94%	0.27


1.1.7 Power Index of Test Tool

Modulation Mode	Test Frequency (MHz)	Power Index
11b	2412	70
11b	2437	70
11b	2462	68
11g	2412	66
11g	2437	78
11g	2462	66
HT20	2412	62
HT20	2437	78
HT20	2462	62

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	Notebook	DELL	Latitude E5400	DoC	---
2	Fixture	---	---	---	Provided by applicant.

1.3 Test Setup Chart

Test Setup Diagram	
 The diagram shows a large rectangular area representing the test setup. Inside, there is a green box labeled 'Fixture' and a white box labeled 'Notebook'. A cable labeled '1' connects the 'Fixture' to the 'Notebook'. Below the 'Fixture' is a purple box labeled 'EUT', connected to the 'Fixture' by a cable labeled 'fixture cable'.	
No.	Signal cable / Length (m)
1	USB, 1m shielded.

1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Tested Date	Jul. 29, 2022				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101658	Feb. 16, 2022	Feb. 15, 2023
LISN	R&S	ENV216	101579	Apr. 21, 2022	Apr. 20, 2023
LISN (Support Unit)	SCHWARZBECK	NSLK 8127	8127667	Jan. 07, 2022	Jan. 06, 2023
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 19, 2021	Oct. 18, 2022
50 ohm terminal (Support Unit)	NA	50	04	May 10, 2022	May 09, 2023
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Tested Date	Jul. 26 ~ Jul. 27, 2022				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Mar. 15, 2022	Mar. 14, 2023
Spectrum Analyzer	R&S	FSV40	101498	Nov. 29, 2021	Nov. 28, 2022
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 08, 2021	Nov. 07, 2022
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Jun. 28, 2022	Jun. 27, 2023
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 03, 2021	Dec. 02, 2022
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170508	Jan. 11, 2022	Jan. 10, 2023
Preamplifier	EMC	EMC02325	980225	Jun. 28, 2022	Jun. 27, 2023
Preamplifier	Agilent	83017A	MY39501308	Sep. 28, 2021	Sep. 27, 2022
Preamplifier	EMC	EMC184045B	980192	Jul. 08, 2022	Jul. 07, 2023
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 05, 2021	Oct. 04, 2022
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 05, 2021	Oct. 04, 2022
LF cable 11M	EMC	EMCCFD400-NW-N W-11000	200801	Oct. 05, 2021	Oct. 04, 2022
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	160502	Oct. 05, 2021	Oct. 04, 2022
RF Cable	EMC	EMC104-35M-35M-8000	210920	Oct. 05, 2021	Oct. 04, 2022
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 05, 2021	Oct. 04, 2022
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Aug. 01, 2022				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101910	Apr. 18, 2022	Apr. 17, 2023
Power Meter	Anritsu	ML2495A	1241002	Nov. 07, 2021	Nov. 06, 2022
Power Sensor	Anritsu	MA2411B	1207366	Nov. 07, 2021	Nov. 06, 2022
Measurement Software	Sporton	SENSE-15247_DTS	V5.10	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

47 CFR FCC Part 15.247
ANSI C63.10-2013

1.6 Reference Guidance

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

1.7 Deviation from Test Standard and Measurement Procedure

None

1.8 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$)).

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.130 Hz
Conducted power	± 0.808 dB
Power density	± 0.583 dB
Conducted emission	± 2.715 dB
AC conducted emission	± 2.92 dB
Unwanted Emission ≤ 1 GHz	± 3.41 dB
Unwanted Emission > 1 GHz	± 4.59 dB

2 Test Configuration

2.1 Testing Facility

Test Laboratory	International Certification Corporation
Test Site	CO01-WS, 03CH01-WS, TH01-WS
Address of Test Site	No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 33381, Taiwan (R.O.C.)

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- ISED#: 10807A
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate	Test Configuration
AC Power Line Conducted Emission	11g	2437	6 Mbps	---
Unwanted Emissions ≤ 1GHz	11g	2437	6 Mbps	---
Unwanted Emissions >1GHz				
Conducted Output Power	11b	2412 / 2437 / 2462	1 Mbps	---
6dB bandwidth	11g	2412 / 2437 / 2462	6 Mbps	
Power spectral density	HT20	2412 / 2437 / 2462	MCS 0	
NOTE:				
1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.				

3 Transmitter Test Results

3.1 6dB and Occupied Bandwidth

3.1.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.1.2 Test Procedures


6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

1. Set resolution bandwidth (RBW) = 1% ~ 5 % of OBW, Video bandwidth = 3 x RBW
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.1.3 Test Setup



3.1.4 Test Results

Ambient Condition	25°C / 61%	Tested By	Roger Lu
-------------------	------------	-----------	----------

Refer to Appendix A.

3.2 Conducted Output Power

3.2.1 Limit of Conducted Output Power

Conducted power shall not exceed 1Watt.

Antenna gain $\leq 6\text{dBi}$, no any corresponding reduction is in output power limit.

Antenna gain $> 6\text{dBi}$

Non Fixed, point to point operations.

The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB


Fixed, point to point operations

Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Test Procedures

A broadband RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.2.3 Test Setup



3.2.4 Test Results

Ambient Condition	25°C / 61%	Tested By	Roger Lu
-------------------	------------	-----------	----------

Refer to Appendix B.

3.3 Power Spectral Density

3.3.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.3.2 Test Procedures

Peak PSD

1. Set the RBW = 3 kHz, VBW = 10 kHz.
2. Detector = Peak, Sweep time = auto couple.
3. Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.


Average PSD, duty cycle $\geq 98\%$

1. Set the RBW = 30 kHz, VBW = 100 kHz.
2. Detector = RMS, Sweep time = auto couple.
3. Sweep time = auto couple.
4. Employ trace averaging (RMS) mode over a minimum of 100 traces.
5. Use the peak marker function to determine the maximum amplitude level.

Average PSD, duty cycle $< 98\%$

1. Set the RBW = 30 kHz, VBW = 100 kHz. Detector = RMS.
2. Set the sweep time to: ≥ 10 (number of measurement points in sweep) $\times$ (total on/off period of the transmitted signal).
3. Perform the measurement over a single sweep.
4. Use the peak marker function to determine the maximum amplitude level.
5. Add $10 \log (1/x)$, where x is the duty cycle.

3.3.3 Test Setup



3.3.4 Test Results

Ambient Condition	25°C / 61%	Tested By	Roger Lu
-------------------	------------	-----------	----------

Refer to Appendix C.

3.4 Unwanted Emissions into Restricted Frequency Bands

3.4.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.4.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.4.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



3.4.4 Test Results

Refer to Appendix D.

3.5 Emissions in Non-Restricted Frequency Bands

3.5.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.5.2 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.5.3 Test Setup



3.5.4 Test Results

Ambient Condition	25°C / 61%	Tested By	Roger Lu
-------------------	------------	-----------	----------

Refer to Appendix E.

3.6 AC Power Line Conducted Emissions

3.6.1 Limit of AC Power Line Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.6.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V / 60Hz.

3.6.3 Test Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.6.4 Test Results

Refer to Appendix F.

4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No.30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan
(R.O.C.)

Kwei Shan

Tel: 886-3-271-8666

No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)
No.2-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Kwei Shan Site II

Tel: 886-3-271-8640

No.14-1, Lane 19, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 333, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0345

Email: ICC_Service@icertifi.com.tw

==END==

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
802.11b_Nss1,(1Mbps)_1TX	9.025M	14.068M	14M1G1D	8.025M	14.018M
802.11g_Nss1,(6Mbps)_1TX	15.075M	17.341M	17M3D1D	15.025M	16.367M
802.11n HT20_Nss1,(MCS0)_1TX	15.125M	18.216M	18M2D1D	13.15M	17.466M

Max-N dB = Maximum 6dB down bandwidth; Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth; Min-OBW = Minimum 99% occupied bandwidth

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.11b_Nss1,(1Mbps)_1TX	-	-	-	-
2412MHz	Pass	500k	8.025M	14.018M
2437MHz	Pass	500k	9.025M	14.068M
2462MHz	Pass	500k	8.55M	14.068M
802.11g_Nss1,(6Mbps)_1TX	-	-	-	-
2412MHz	Pass	500k	15.075M	16.367M
2437MHz	Pass	500k	15.05M	17.341M
2462MHz	Pass	500k	15.025M	16.392M
802.11n HT20_Nss1,(MCS0)_1TX	-	-	-	-
2412MHz	Pass	500k	13.15M	17.516M
2437MHz	Pass	500k	15.05M	18.216M
2462MHz	Pass	500k	15.125M	17.466M

Port X-N dB = Port X 6dB down bandwidth;
Port X-OBW = Port X 99% occupied bandwidth

802.11b_Nss1,(1Mbps)_1TX

EBW


2412MHz



802.11b_Nss1,(1Mbps)_1TX

EBW


2437MHz



802.11b_Nss1,(1Mbps)_1TX

EBW


2462MHz



802.11g_Nss1,(6Mbps)_1TX

EBW


2412MHz



802.11g_Nss1,(6Mbps)_1TX

EBW


2437MHz



802.11g_Nss1,(6Mbps)_1TX

EBW


2462MHz



802.11n HT20_Nss1,(MCS0)_1TX

EBW


2412MHz



802.11n HT20_Nss1,(MCS0)_1TX

EBW


2437MHz



802.11n HT20_Nss1,(MCS0)_1TX

EBW

2462MHz





Conducted Output Power(Peak)

Appendix B.1

Summary

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
802.11b_Nss1,(1Mbps)_1TX	19.73	0.09397
802.11g_Nss1,(6Mbps)_1TX	25.24	0.33420
802.11n HT20_Nss1,(MCS0)_1TX	25.19	0.33037

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Total Power (dBm)	Power Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.11b_Nss1,(1Mbps)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	2.60	19.62	19.62	30.00	22.22	36.00
2437MHz	Pass	2.60	19.73	19.73	30.00	22.33	36.00
2462MHz	Pass	2.60	19.23	19.23	30.00	21.83	36.00
802.11g_Nss1,(6Mbps)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	2.60	23.37	23.37	30.00	25.97	36.00
2437MHz	Pass	2.60	25.24	25.24	30.00	27.84	36.00
2462MHz	Pass	2.60	23.84	23.84	30.00	26.44	36.00
802.11n HT20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	2.60	22.88	22.88	30.00	25.48	36.00
2437MHz	Pass	2.60	25.19	25.19	30.00	27.79	36.00
2462MHz	Pass	2.60	23.03	23.03	30.00	25.63	36.00

DG = Directional Gain; Port X = Port X output power



Conducted Output Power(Average)

Appendix B.2

Summary

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
802.11b_Nss1,(1Mbps)_1TX	17.53	0.05662
802.11g_Nss1,(6Mbps)_1TX	20.60	0.11482
802.11n HT20_Nss1,(MCS0)_1TX	20.56	0.11376

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Total Power (dBm)	Power Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.11b_Nss1,(1Mbps)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	2.60	17.46	17.46	-	20.06	-
2437MHz	Pass	2.60	17.53	17.53	-	20.13	-
2462MHz	Pass	2.60	17.02	17.02	-	19.62	-
802.11g_Nss1,(6Mbps)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	2.60	16.12	16.12	-	18.72	-
2437MHz	Pass	2.60	20.6	20.60	-	23.20	-
2462MHz	Pass	2.60	16.53	16.53	-	19.13	-
802.11n HT20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	2.60	15.02	15.02	-	17.62	-
2437MHz	Pass	2.60	20.56	20.56	-	23.16	-
2462MHz	Pass	2.60	15.21	15.21	-	17.81	-

DG = Directional Gain; Port X = Port X output power

Note : Conducted average output power is for reference only

**Summary**

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
802.11b_Nss1,(1Mbps)_1TX	-4.19
802.11g_Nss1,(6Mbps)_1TX	-3.77
802.11n HT20_Nss1,(MCS0)_1TX	-3.38

RBW = 3kHz;

Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)
802.11b_Nss1,(1Mbps)_1TX	-	-	-	-	-
2412MHz	Pass	2.60	-5.37	-5.37	8.00
2437MHz	Pass	2.60	-4.19	-4.19	8.00
2462MHz	Pass	2.60	-5.28	-5.28	8.00
802.11g_Nss1,(6Mbps)_1TX	-	-	-	-	-
2412MHz	Pass	2.60	-7.85	-7.85	8.00
2437MHz	Pass	2.60	-3.77	-3.77	8.00
2462MHz	Pass	2.60	-9.18	-9.18	8.00
802.11n HT20_Nss1,(MCS0)_1TX	-	-	-	-	-
2412MHz	Pass	2.60	-9.95	-9.95	8.00
2437MHz	Pass	2.60	-3.38	-3.38	8.00
2462MHz	Pass	2.60	-9.87	-9.87	8.00


DG = Directional Gain; RBW = 3kHz;

PD = Power density; Port X = Port X Power Density;

802.11b_Nss1,(1Mbps)_1TX

PSD


2412MHz



802.11b_Nss1,(1Mbps)_1TX

PSD


2437MHz



802.11b_Nss1,(1Mbps)_1TX

PSD


2462MHz



802.11g_Nss1,(6Mbps)_1TX

PSD


2412MHz



802.11g_Nss1,(6Mbps)_1TX

PSD


2437MHz



802.11g_Nss1,(6Mbps)_1TX

PSD


2462MHz



802.11n HT20_Nss1,(MCS0)_1TX

PSD


2412MHz



802.11n HT20_Nss1,(MCS0)_1TX

PSD

2437MHz






802.11n HT20_Nss1,(MCS0)_1TX

PSD

2462MHz





Unwanted Emissions (Below 1GHz)

Modulation	11g	Test Freq. (MHz)	2437																																																																						
Polarization	Horizontal																																																																								
Test By :Roger Lu- Temperature(°C):26 Humidity(%):23																																																																									
Level (dBuV/m) CLASS-B <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>71.71</td><td>32.87</td><td>40.00</td><td>-7.13</td><td>44.26</td><td>-11.39</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>2</td><td>173.56</td><td>35.37</td><td>43.50</td><td>-8.13</td><td>45.11</td><td>-9.74</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>263.77</td><td>29.16</td><td>46.00</td><td>-16.84</td><td>38.78</td><td>-9.62</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>4</td><td>360.77</td><td>26.46</td><td>46.00</td><td>-19.54</td><td>33.86</td><td>-7.40</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>408.30</td><td>31.37</td><td>46.00</td><td>-14.63</td><td>37.09</td><td>-5.72</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>6</td><td>551.86</td><td>32.04</td><td>46.00</td><td>-13.96</td><td>34.87</td><td>-2.83</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table> Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m). Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	71.71	32.87	40.00	-7.13	44.26	-11.39	Peak	---	---	2	173.56	35.37	43.50	-8.13	45.11	-9.74	Peak	---	---	3	263.77	29.16	46.00	-16.84	38.78	-9.62	Peak	---	---	4	360.77	26.46	46.00	-19.54	33.86	-7.40	Peak	---	---	5	408.30	31.37	46.00	-14.63	37.09	-5.72	Peak	---	---	6	551.86	32.04	46.00	-13.96	34.87	-2.83	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																																																
1	71.71	32.87	40.00	-7.13	44.26	-11.39	Peak	---	---																																																																
2	173.56	35.37	43.50	-8.13	45.11	-9.74	Peak	---	---																																																																
3	263.77	29.16	46.00	-16.84	38.78	-9.62	Peak	---	---																																																																
4	360.77	26.46	46.00	-19.54	33.86	-7.40	Peak	---	---																																																																
5	408.30	31.37	46.00	-14.63	37.09	-5.72	Peak	---	---																																																																
6	551.86	32.04	46.00	-13.96	34.87	-2.83	Peak	---	---																																																																



Modulation	11g	Test Freq. (MHz)	2437
Polarization	Vertical		
Test By :Roger Lu- Temperature(°C):26 Humidity(%):23			
Level (dBUV/m) </			



Unwanted Emission (Above 1GHz) for 11b

Modulation	11b	Test Freq. (MHz)	2412
Polarization	Horizontal		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBUV/m)			



Modulation	11b	Test Freq. (MHz)	2412
Polarization	Vertical		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBuV/m) </			



Modulation	11b	Test Freq. (MHz)	2437
Polarization	Horizontal		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBuV/m) <			



Modulation	11b	Test Freq. (MHz)	2437
Polarization	Vertical		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBuV/m) </			



Modulation	11b	Test Freq. (MHz)	2462
Polarization	Horizontal		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBuV/m)			



Modulation	11b	Test Freq. (MHz)	2462
Polarization	Vertical		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBuV/m) </			



Unwanted Emissions (Above 1GHz) for 11g

Modulation	11g	Test Freq. (MHz)	2412
Polarization	Horizontal		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBuV/m)			



Modulation	11g	Test Freq. (MHz)	2412																																																																						
Polarization	Vertical																																																																								
Test By :Akun Chung Temperature(°C):26 Humidity(%):62																																																																									
<table><tr><th></th><th>Freq. MHz</th><th>Emission level dBUV/m</th><th>Limit dBUV/m</th><th>Margin dB</th><th>SA reading dBUV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>2390.00</td><td>48.91</td><td>54.00</td><td>-5.09</td><td>51.66</td><td>-2.75</td><td>Average</td><td>323</td><td>312</td></tr><tr><td>2</td><td>2390.00</td><td>63.80</td><td>74.00</td><td>-10.20</td><td>66.55</td><td>-2.75</td><td>Peak</td><td>323</td><td>312</td></tr><tr><td>3</td><td>4824.00</td><td>35.80</td><td>54.00</td><td>-18.20</td><td>31.66</td><td>4.14</td><td>Average</td><td>100</td><td>330</td></tr><tr><td>4</td><td>4824.00</td><td>47.02</td><td>74.00</td><td>-26.98</td><td>42.88</td><td>4.14</td><td>Peak</td><td>100</td><td>330</td></tr><tr><td>5</td><td>12060.00</td><td>44.22</td><td>54.00</td><td>-9.78</td><td>30.43</td><td>13.79</td><td>Average</td><td>100</td><td>50</td></tr><tr><td>6</td><td>12060.00</td><td>56.32</td><td>74.00</td><td>-17.68</td><td>42.53</td><td>13.79</td><td>Peak</td><td>100</td><td>50</td></tr></table>					Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	2390.00	48.91	54.00	-5.09	51.66	-2.75	Average	323	312	2	2390.00	63.80	74.00	-10.20	66.55	-2.75	Peak	323	312	3	4824.00	35.80	54.00	-18.20	31.66	4.14	Average	100	330	4	4824.00	47.02	74.00	-26.98	42.88	4.14	Peak	100	330	5	12060.00	44.22	54.00	-9.78	30.43	13.79	Average	100	50	6	12060.00	56.32	74.00	-17.68	42.53	13.79	Peak	100	50
	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																																																
1	2390.00	48.91	54.00	-5.09	51.66	-2.75	Average	323	312																																																																
2	2390.00	63.80	74.00	-10.20	66.55	-2.75	Peak	323	312																																																																
3	4824.00	35.80	54.00	-18.20	31.66	4.14	Average	100	330																																																																
4	4824.00	47.02	74.00	-26.98	42.88	4.14	Peak	100	330																																																																
5	12060.00	44.22	54.00	-9.78	30.43	13.79	Average	100	50																																																																
6	12060.00	56.32	74.00	-17.68	42.53	13.79	Peak	100	50																																																																
Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).																																																																									



Modulation	11g	Test Freq. (MHz)	2437
Polarization	Horizontal		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBUV/m)			



Modulation	11g	Test Freq. (MHz)	2437
Polarization	Vertical		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBuV/m) </			



Modulation	11g	Test Freq. (MHz)	2462
Polarization	Horizontal		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBuV/m)			



Modulation	11g	Test Freq. (MHz)	2462
Polarization	Vertical		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBuV/m) </			



Unwanted Emissions (Above 1GHz) for HT20

Modulation	HT20		Test Freq. (MHz)		2412	
Polarization	Horizontal					
Test By :Akun Chung Temperature(°C):26 Humidity(%):62						
Level (dBUV/m) <						



Modulation	HT20	Test Freq. (MHz)	2412
Polarization	Vertical		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBUV/m) </			



Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Horizontal		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBuV/m) <			



Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Vertical		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBuV/m) <			



Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Horizontal		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBuV/m) </			




Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Vertical		
Test By :Akun Chung Temperature(°C):26 Humidity(%):62			
Level (dBUV/m)			



802.11b_Nss1,(1Mbps)_1TX

CSEndB


2412MHz



802.11b_Nss1,(1Mbps)_1TX

CSEndB


2437MHz



802.11b_Nss1,(1Mbps)_1TX

CSEndB


2462MHz



802.11g_Nss1,(6Mbps)_1TX

CSEndB


2412MHz



802.11g_Nss1,(6Mbps)_1TX

2437MHz


CSEndB



802.11g_Nss1,(6Mbps)_1TX

2462MHz


CSEndB



802.11n HT20_Nss1,(MCS0)_1TX

CSENdB


2412MHz



802.11n HT20_Nss1,(MCS0)_1TX

CSENdB

2437MHz






802.11n HT20_Nss1,(MCS0)_1TX

CSEndB

2462MHz






Modulation Mode	11g	Test Freq. (MHz)	2437
Power Phase	Line		

Test by : Joe Liao

Temperature: 24°C

Humidity: 65%



	Freq MHz	Level dBUV	Limit Line dBUV	Over Limit dB	Read Level dBUV	Factor dB	Cable loss dB	Aux dB	Remark
1	0.195	32.51	53.80	-21.29	22.75	9.68	0.08	0.00	Average
2	0.195	42.40	63.80	-21.40	32.64	9.68	0.08	0.00	QP
3	0.222	30.18	52.74	-22.56	20.42	9.68	0.08	0.00	Average
4	0.222	39.77	62.74	-22.97	30.01	9.68	0.08	0.00	QP
5*	0.555	34.68	46.00	-11.32	24.90	9.67	0.11	0.00	Average
6	0.555	41.87	56.00	-14.13	32.09	9.67	0.11	0.00	QP
7	1.464	27.49	46.00	-18.51	17.62	9.69	0.18	0.00	Average
8	1.464	33.81	56.00	-22.19	23.94	9.69	0.18	0.00	QP
9	3.417	20.31	46.00	-25.69	10.40	9.70	0.21	0.00	Average
10	3.417	30.19	56.00	-25.81	20.28	9.70	0.21	0.00	QP
11	14.907	26.59	50.00	-23.41	16.30	9.73	0.56	0.00	Average
12	14.907	31.75	60.00	-28.25	21.46	9.73	0.56	0.00	QP

Note 1: Level (dBUV) = Read Level (dBUV) + LISN Factor (dB) + Cable Loss (dB) + Aux (dB).

2: Over Limit (dB) = Level (dBUV) - Limit Line (dBUV).




Modulation Mode	11g	Test Freq. (MHz)	2437
Power Phase	Neutral		

Test by : Joe Liao

Temperature: 24°C

Humidity: 65%



	Freq MHz	Level dBUV	Limit Line dBUV	Over Limit dB	Read Level dBUV	Factor dB	Cable loss dB	Aux dB	Remark
1	0.150	28.98	56.00	-27.02	19.29	9.61	0.08	0.00	Average
2	0.150	46.43	66.00	-19.57	36.74	9.61	0.08	0.00	QP
3	0.186	23.32	54.20	-30.88	13.63	9.61	0.08	0.00	Average
4	0.186	40.99	64.20	-23.21	31.30	9.61	0.08	0.00	QP
5*	0.555	32.35	46.00	-13.65	22.63	9.61	0.11	0.00	Average
6	0.555	38.03	56.00	-17.97	28.31	9.61	0.11	0.00	QP
7	1.418	24.97	46.00	-21.03	15.17	9.62	0.18	0.00	Average
8	1.418	30.20	56.00	-25.80	20.40	9.62	0.18	0.00	QP
9	1.810	25.44	46.00	-20.56	15.63	9.62	0.19	0.00	Average
10	1.810	30.20	56.00	-25.80	20.39	9.62	0.19	0.00	QP
11	14.750	24.92	50.00	-25.08	14.62	9.75	0.55	0.00	Average
12	14.750	30.87	60.00	-29.13	20.57	9.75	0.55	0.00	QP

Note 1: Level (dBUV) = Read Level (dBUV) + LISN Factor (dB) + Cable Loss (dB) + Aux (dB).

2: Over Limit (dB) = Level (dBUV) - Limit Line (dBUV).