


FCC Test Report

FCC ID : NKR-SP69
Equipment : 11abgn/ac WLAN/Bluetooth Combo Module
Model No. : DHUB-SP69
Brand Name : SHARP Corporation
Applicant : Wistron NeWeb Corp.
Address : 20 Park Avenue II, Hsinchu Science Park,
Hsinchu 308, Taiwan, R.O.C.
Standard : 47 CFR FCC Part 15.247
Received Date : Oct. 03, 2014
Tested Date : Oct. 29 ~ Nov. 12 , 2014

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:



Gary Chang / Manager ✓



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	Test Equipment List and Calibration Data.....	8
1.5	Test Standards	9
1.6	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS.....	11
3.1	Conducted Emissions.....	11
3.2	6dB and Occupied Bandwidth	14
3.3	RF Output Power	17
3.4	Power Spectral Density	19
3.5	Emissions in Restricted Frequency Bands.....	21
3.6	Emissions in non-restricted Frequency Bands	33
4	TEST LABORATORY INFORMATION	35

Release Record

Report No.	Version	Description	Issued Date
FR4O1301AE	Rev. 01	Initial issue	Dec. 04, 2014

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emissions	[dBuV]: 0.497MHz 32.26 (Margin -13.79dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 719.67MHz 44.74 (Margin -1.26dB) - QP	Pass
15.247(b)(3)	Maximum Output Power	Power [dBm]: 8.61	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Freq. (MHz)	Channel Number	Data Rate
2400-2483.5	LE	2402-2480	0-39 [40]	1 Mbps
Note 1: Bluetooth LE (Low energy) uses GFSK modulation.				

1.1.2 Antenna Details

Ant. No.	Type	Gain (dBi)	Connector	Remark
1	PIFA	4.2	U.FL	---

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	5Vdc from host
-------------------	----------------

1.1.4 Accessories

NA

1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
37	2402	9	2422	18	2442	28	2462
0	2404	10	2424	19	2444	29	2464
1	2406	38	2426	20	2446	30	2466
2	2408	11	2428	21	2448	31	2468
3	2410	12	2430	22	2450	32	2470
4	2412	13	2432	23	2452	33	2472
5	2414	14	2434	24	2454	34	2474
6	2416	15	2436	25	2456	35	2476
7	2418	16	2438	26	2458	36	2478
8	2420	17	2440	27	2460	39	2480

1.1.6 Test Tool and Duty Cycle

Test tool	Blue Tool, Version: 1.8.8.6
Duty cycle of test signal (%)	68.08%
Duty Factor (dB)	1.67


1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)		
	2402	2440	2480
GFSK/1Mbps	Default	Default	Default

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Signal cable / Length (m)
1	Notebook	DELL	E6430	Doc	Fixture cable 0.12m non-shielded cable w/o core

1.3 Test Setup Chart



1.4 Test Equipment List and Calibration Data

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
EMC Receiver	R&S	ESCS 30	100174	Apr. 14, 2014	Apr. 13, 2015
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 23, 2013	Nov. 22, 2014
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Dec. 04, 2013	Dec. 03, 2014
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Apr. 23, 2014	Apr. 22, 2015
50 ohm terminal (Support Unit)	NA	50	04	Apr. 18, 2014	Apr. 17, 2015
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber 3 / (03CH03-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	Agilent	N9010A	MY53400091	Sep. 16, 2014	Sep. 15, 2015
Receiver	R&S	ESR3	101657	Jan. 18, 2014	Jan. 17, 2015
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-562	Feb. 07, 2014	Feb. 06, 2015
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 20, 2014	Feb. 19, 2015
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA9170154	Jan. 10, 2014	Jan. 09, 2015
Preamplifier	EMC	EMC02325	980187	Nov. 22, 2013	Nov. 21, 2014
Preamplifier	Agilent	83017A	MY53270014	Sep. 17, 2014	Sep. 16, 2015
Preamplifier	EMC	EMC184045B	980192	Aug. 26, 2014	Aug. 25, 2015
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Feb. 19, 2014	Feb. 18, 2015
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY22601/4	Feb. 19, 2014	Feb. 18, 2015
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Feb. 19, 2014	Feb. 18, 2015
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-001	Feb. 17, 2014	Feb. 16, 2015
LF cable-3M	EMC	EMC8D-NM-NM-3000	131103	Feb. 17, 2014	Feb. 16, 2015
LF cable-13M	EMC	EMC8D-NM-NM-13000	131104	Feb. 17, 2014	Feb. 16, 2015
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014
Note: Calibration Interval of instruments listed above is two year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 17, 2014	Feb. 16, 2015
Power Meter	Anritsu	ML2495A	1241002	Sep. 29, 2014	Sep. 28, 2015
Power Sensor	Anritsu	MA2411B	1207366	Sep. 29, 2014	Sep. 28, 2015
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2009

FCC KDB 558074 D01 DTS Meas Guidance v03r02

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.134 Hz
Conducted power	± 0.808 dB
Frequency error	± 34.134 Hz
Temperature	± 0.6 °C
Conducted emission	± 2.670 dB
AC conducted emission	± 2.92 dB
Radiated emission ≤ 1 GHz	± 3.26 dB
Radiated emission > 1 GHz	± 4.94 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	22°C / 69%	Peter Lin
Radiated Emissions	03CH03-WS	21-22°C / 61-63%	Aska Huang
RF Conducted	TH01-WS	23°C / 62%	Brad Wu

➤ FCC site registration No.: 390588

➤ IC site registration No.: 10807C-1

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate (Mbps)	Test Configuration
AC Power Line Conducted Emissions	BT LE	2440	1Mbps	1
Radiated Emissions ≤ 1GHz	BT LE	2440	1Mbps	1, 2
Radiated Emissions > 1GHz	BT LE	2402, 2440, 2480	1Mbps	1
Maximum Output Power	BT LE	2402, 2440, 2480	1Mbps	1
6dB bandwidth				
Power spectral density				

NOTE:

1. The EUT and its antenna were pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case for EUT, and the **X-plane** results were found as the worst case for antenna and shown in this report.

2. 4 different length of BT antenna cable were provided for this device: 400mm / 500mm / 550mm / 600mm. 400mm and 600mm were selected for final testing as below test configurations.

1) Configuration 1: 400mm

2) Configuration 2: 600mm

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz


3.1.3 Test Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions

Modulation Mode	GFSK	Test Freq. (MHz)	2440
Power Phase	Line		



	Freq MHz	Level dBUV	Limit Line dBUV	Over Limit dB	Read Level dBUV	LISN factor dB	cable loss dB	Remark
1	0.159	37.35	55.52	-18.17	36.93	0.40	0.02	Average
2*	0.159	50.03	65.52	-15.49	49.61	0.40	0.02	QP
3	0.200	31.22	53.62	-22.40	30.82	0.39	0.01	Average
4	0.200	40.69	63.62	-22.93	40.29	0.39	0.01	QP
5	0.497	25.48	46.05	-20.57	25.07	0.39	0.02	Average
6	0.497	35.02	56.05	-21.03	34.61	0.39	0.02	QP
7	1.680	21.38	46.00	-24.62	20.93	0.43	0.02	Average
8	1.680	26.78	56.00	-29.22	26.33	0.43	0.02	QP
9	9.302	24.09	50.00	-25.91	23.32	0.53	0.24	Average
10	9.302	32.35	60.00	-27.65	31.58	0.53	0.24	QP
11	21.147	12.63	50.00	-37.37	11.67	0.55	0.41	Average
12	21.147	20.15	60.00	-39.85	19.19	0.55	0.41	QP

Note 1: Level (dBUV) = Read Level (dBUV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBUV) – Limit Line (dBUV).

Modulation Mode	GFSK	Test Freq. (MHz)	2440																																																																																																																																							
Power Phase	Neutral																																																																																																																																									
Level (dBUV) Frequency (MHz) <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Over</th><th>Read</th><th>LISN</th><th>cable</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV</th><th>Line</th><th>Limit</th><th>Level</th><th>factor</th><th>loss</th><th>Remark</th></tr><tr><th></th><th></th><th></th><th>dBuV</th><th>dB</th><th>dBuV</th><th>dB</th><th>dB</th><th></th></tr></thead><tbody><tr><td>1</td><td>0.159</td><td>38.79</td><td>55.52</td><td>-16.73</td><td>38.29</td><td>0.48</td><td>0.02</td><td>Average</td></tr><tr><td>2</td><td>0.159</td><td>46.96</td><td>65.52</td><td>-18.56</td><td>46.46</td><td>0.48</td><td>0.02</td><td>QP</td></tr><tr><td>3</td><td>0.200</td><td>32.23</td><td>53.62</td><td>-21.39</td><td>31.74</td><td>0.48</td><td>0.01</td><td>Average</td></tr><tr><td>4</td><td>0.200</td><td>41.32</td><td>63.62</td><td>-22.30</td><td>40.83</td><td>0.48</td><td>0.01</td><td>QP</td></tr><tr><td>5*</td><td>0.497</td><td>32.26</td><td>46.05</td><td>-13.79</td><td>31.77</td><td>0.47</td><td>0.02</td><td>Average</td></tr><tr><td>6</td><td>0.497</td><td>38.72</td><td>56.05</td><td>-17.33</td><td>38.23</td><td>0.47</td><td>0.02</td><td>QP</td></tr><tr><td>7</td><td>1.716</td><td>23.25</td><td>46.00</td><td>-22.75</td><td>22.73</td><td>0.50</td><td>0.02</td><td>Average</td></tr><tr><td>8</td><td>1.716</td><td>28.11</td><td>56.00</td><td>-27.89</td><td>27.59</td><td>0.50</td><td>0.02</td><td>QP</td></tr><tr><td>9</td><td>3.922</td><td>15.50</td><td>46.00</td><td>-30.50</td><td>14.83</td><td>0.52</td><td>0.15</td><td>Average</td></tr><tr><td>10</td><td>3.922</td><td>21.71</td><td>56.00</td><td>-34.29</td><td>21.04</td><td>0.52</td><td>0.15</td><td>QP</td></tr><tr><td>11</td><td>9.302</td><td>17.75</td><td>50.00</td><td>-32.25</td><td>16.95</td><td>0.56</td><td>0.24</td><td>Average</td></tr><tr><td>12</td><td>9.302</td><td>24.64</td><td>60.00</td><td>-35.36</td><td>23.84</td><td>0.56</td><td>0.24</td><td>QP</td></tr></tbody></table>					Freq	Level	Limit	Over	Read	LISN	cable			MHz	dBuV	Line	Limit	Level	factor	loss	Remark				dBuV	dB	dBuV	dB	dB		1	0.159	38.79	55.52	-16.73	38.29	0.48	0.02	Average	2	0.159	46.96	65.52	-18.56	46.46	0.48	0.02	QP	3	0.200	32.23	53.62	-21.39	31.74	0.48	0.01	Average	4	0.200	41.32	63.62	-22.30	40.83	0.48	0.01	QP	5*	0.497	32.26	46.05	-13.79	31.77	0.47	0.02	Average	6	0.497	38.72	56.05	-17.33	38.23	0.47	0.02	QP	7	1.716	23.25	46.00	-22.75	22.73	0.50	0.02	Average	8	1.716	28.11	56.00	-27.89	27.59	0.50	0.02	QP	9	3.922	15.50	46.00	-30.50	14.83	0.52	0.15	Average	10	3.922	21.71	56.00	-34.29	21.04	0.52	0.15	QP	11	9.302	17.75	50.00	-32.25	16.95	0.56	0.24	Average	12	9.302	24.64	60.00	-35.36	23.84	0.56	0.24	QP
	Freq	Level	Limit	Over	Read	LISN	cable																																																																																																																																			
	MHz	dBuV	Line	Limit	Level	factor	loss	Remark																																																																																																																																		
			dBuV	dB	dBuV	dB	dB																																																																																																																																			
1	0.159	38.79	55.52	-16.73	38.29	0.48	0.02	Average																																																																																																																																		
2	0.159	46.96	65.52	-18.56	46.46	0.48	0.02	QP																																																																																																																																		
3	0.200	32.23	53.62	-21.39	31.74	0.48	0.01	Average																																																																																																																																		
4	0.200	41.32	63.62	-22.30	40.83	0.48	0.01	QP																																																																																																																																		
5*	0.497	32.26	46.05	-13.79	31.77	0.47	0.02	Average																																																																																																																																		
6	0.497	38.72	56.05	-17.33	38.23	0.47	0.02	QP																																																																																																																																		
7	1.716	23.25	46.00	-22.75	22.73	0.50	0.02	Average																																																																																																																																		
8	1.716	28.11	56.00	-27.89	27.59	0.50	0.02	QP																																																																																																																																		
9	3.922	15.50	46.00	-30.50	14.83	0.52	0.15	Average																																																																																																																																		
10	3.922	21.71	56.00	-34.29	21.04	0.52	0.15	QP																																																																																																																																		
11	9.302	17.75	50.00	-32.25	16.95	0.56	0.24	Average																																																																																																																																		
12	9.302	24.64	60.00	-35.36	23.84	0.56	0.24	QP																																																																																																																																		
Note 1: Level (dBUV) = Read Level (dBUV) + LISN Factor (dB) + Cable Loss (dB). 2: Over Limit (dB) = Level (dBUV) – Limit Line (dBUV).																																																																																																																																										

3.2 6dB and Occupied Bandwidth


3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures


1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

3.2.3 Test Setup




3.2.4 Test Result of 6dB and Occupied Bandwidth

Freq. (MHz)	6dB Bandwidth (kHz)	Limit (kHz)
2402	708.7	500
2440	708.7	500
2480	704.35	500



Freq. (MHz)	99% Occupied Bandwidth (MHz)
2402	1.05
2440	1.05
2480	1.05



3.3 RF Output Power

3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.


- ☒ Antenna gain $\leq 6\text{dBi}$, no any corresponding reduction is in output power limit.
- ☐ Antenna gain $> 6\text{dBi}$
 - ☐ Non Fixed, point to point operations.
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB
 - ☐ Fixed, point to point operations
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

3.3.2 Test Procedures

- ☒ Maximum Peak Conducted Output Power
 - ☐ **Spectrum analyzer**
 1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
 2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
 3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.
 - ☒ **Power meter**
 1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- ☒ Maximum Conducted Average Output Power (For reference only)
 - ☒ **Power meter**
 1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.3.3 Test Setup



3.3.4 Test Result of Maximum Output Power

Freq. (MHz)	Peak Conducted Power (dBm)	Limit (dBm)
2402	7.74	30
2440	8.61	30
2480	7.92	30

Freq. (MHz)	Average Conducted Power (dBm)	Limit (dBm)
2402	7.52	30
2440	8.41	30
2480	7.73	30

Note: Average power is for reference only.

3.4 Power Spectral Density


3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures


- ☒ Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
 1. Set the RBW = 3kHz, VBW = 10kHz.
 2. Detector = Peak, Sweep time = auto couple.
 3. Trace mode = max hold, allow trace to fully stabilize.
 4. Use the peak marker function to determine the maximum amplitude level.
- ☐ Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
 1. Set the RBW = 100kHz, VBW = 300 kHz.
 2. Detector = RMS, Sweep time = auto couple.
 3. Set the sweep time to: $\geq 10 \times (\text{number of measurement points in sweep}) \times (\text{maximum data rate per stream})$.
 4. Perform the measurement over a single sweep.
 5. Use the peak marker function to determine the maximum amplitude level.\

3.4.3 Test Setup



3.4.4 Test Result of Power Spectral Density

Freq. (MHz)	Power Spectral Density (dBm / 3kHz)	Limit (dBm)
2402	-4.90	8
2440	-4.31	8
2480	-5.07	8



3.5 Emissions in Restricted Frequency Bands

3.5.1 Limit of Emissions in Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.5.3 Test Setup

Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Horizontal	Test Configuration	1




The graph displays the radiated unwanted emissions of a transmitter below 1 GHz. The y-axis represents the emission level in dBuV/m, ranging from 0 to 90. The x-axis represents the frequency in MHz, ranging from 30 to 1000. A red line indicates the FCC CLASS-B limit, which is 40 dBuV/m from 30 MHz to 100 MHz, 45 dBuV/m from 100 MHz to 200 MHz, and 50 dBuV/m from 200 MHz to 1000 MHz. Six emission peaks are identified and labeled with numbers 1 through 6. The data for these peaks is provided in the table below.

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	74.62	31.13	40.00	-8.87	47.55	-16.42	Peak	---	---
2	131.85	38.98	43.50	-4.52	53.41	-14.43	Peak	---	---
3	240.49	38.07	46.00	-7.93	52.76	-14.69	Peak	---	---
4	480.08	38.18	46.00	-7.82	46.42	-8.24	Peak	---	---
5	719.67	35.13	46.00	-10.87	38.87	-3.74	Peak	---	---
6	951.50	37.92	46.00	-8.08	37.68	0.24	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	144.46	30.01	43.50	-13.49	43.48	-13.47	Peak	---	---
2	240.49	28.39	46.00	-17.61	43.08	-14.69	Peak	---	---
3	275.41	30.67	46.00	-15.33	44.00	-13.33	Peak	---	---
4	480.08	33.69	46.00	-12.31	41.93	-8.24	Peak	---	---
5	798.24	38.40	46.00	-7.60	40.81	-2.41	Peak	---	---
6	952.47	42.21	46.00	-3.79	41.96	0.25	Peak	---	---


Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Horizontal	Test Configuration	2



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	101.78	31.52	43.50	-11.98	49.42	-17.90	Peak	---	---
2	242.43	42.09	46.00	-3.91	56.74	-14.65	Peak	---	---
3	267.65	39.34	46.00	-6.66	53.05	-13.71	Peak	---	---
4	482.02	40.70	46.00	-5.30	48.92	-8.22	Peak	---	---
5	722.58	43.01	46.00	-2.99	46.70	-3.69	QP	---	---
6	939.86	36.43	46.00	-9.57	36.39	0.04	Peak	---	---


Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Vertical	Test Configuration	2



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	69.64	36.21	40.00	-3.79	51.51	-15.30	Peak	---	---
2	131.46	30.99	43.50	-12.51	45.47	-14.48	Peak	---	---
3	294.75	35.55	46.00	-10.45	48.29	-12.74	Peak	---	---
4	480.13	40.05	46.00	-5.95	48.29	-8.24	Peak	---	---
5	719.67	44.74	46.00	-1.26	48.48	-3.74	QP	---	---
6	975.83	37.66	54.00	-16.34	37.16	0.50	Peak	---	---

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)


Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	34.08	54.00	-19.92	39.07	-4.99	Average	---	---
2	1500.00	47.44	74.00	-26.56	52.43	-4.99	Peak	---	---
3	2390.00	37.75	54.00	-16.25	39.43	-1.68	Average	---	---
4	2390.00	50.28	74.00	-23.72	51.96	-1.68	Peak	---	---
5	4804.00	34.66	54.00	-19.34	29.32	5.34	Average	---	---
6	4804.00	45.68	74.00	-28.32	40.34	5.34	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	34.35	54.00	-19.65	39.34	-4.99	Average	---	---
2	1500.00	47.80	74.00	-26.20	52.79	-4.99	Peak	---	---
3	2390.00	37.75	54.00	-16.25	39.43	-1.68	Average	---	---
4	2390.00	50.50	74.00	-23.50	52.18	-1.68	Peak	---	---
5	4804.00	37.64	54.00	-16.36	32.30	5.34	Average	---	---
6	4804.00	46.57	74.00	-27.43	41.23	5.34	Peak	---	---

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Horizontal	Test Configuration	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	34.44	54.00	-19.56	39.43	-4.99	Average	---	---
2	1500.00	47.80	74.00	-26.20	52.79	-4.99	Peak	---	---
3	4880.00	38.60	54.00	-15.40	33.06	5.54	Average	---	---
4	4880.00	47.44	74.00	-26.56	41.90	5.54	Peak	---	---
5	7320.00	38.50	54.00	-15.50	27.21	11.29	Average	---	---
6	7320.00	50.36	74.00	-23.64	39.07	11.29	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Vertical	Test Configuration	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	34.44	54.00	-19.56	39.43	-4.99	Average	---	---
2	1500.00	48.30	74.00	-25.70	53.29	-4.99	Peak	---	---
3	4880.00	42.41	54.00	-11.59	36.87	5.54	Average	---	---
4	4880.00	49.35	74.00	-24.65	43.81	5.54	Peak	---	---
5	7320.00	38.48	54.00	-15.52	27.19	11.29	Average	---	---
6	7320.00	50.08	74.00	-23.92	38.79	11.29	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal	Test Configuration	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	34.62	54.00	-19.38	39.61	-4.99	Average	---	---
2	1500.00	47.76	74.00	-26.24	52.75	-4.99	Peak	---	---
3	2483.50	38.42	54.00	-15.58	39.76	-1.34	Average	---	---
4	2483.50	52.46	74.00	-21.54	53.80	-1.34	Peak	---	---
5	4960.00	36.22	54.00	-17.78	30.48	5.74	Average	---	---
6	4960.00	46.08	74.00	-27.92	40.34	5.74	Peak	---	---
7	7440.00	38.68	54.00	-15.32	27.42	11.26	Average	---	---
8	7440.00	50.94	74.00	-23.06	39.68	11.26	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	34.49	54.00	-19.51	39.48	-4.99	Average	---	---
2	1500.00	47.28	74.00	-26.72	52.27	-4.99	Peak	---	---
3	2483.50	37.92	54.00	-16.08	39.26	-1.34	Average	---	---
4	2483.50	50.38	74.00	-23.62	51.72	-1.34	Peak	---	---
5	4960.00	41.96	54.00	-12.04	36.22	5.74	Average	---	---
6	4960.00	48.96	74.00	-25.04	43.22	5.74	Peak	---	---
7	7440.00	37.94	54.00	-16.06	26.68	11.26	Average	---	---
8	7440.00	50.39	74.00	-23.61	39.13	11.26	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.6 Emissions in non-restricted Frequency Bands

3.6.1 Emissions in non-restricted frequency bands limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz

3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level


Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.6.4 Test Setup



3.6.5 Test Result of Emissions in non-restricted Frequency Bands



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan,
R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd
St., Kwei Shan Hsiang, Tao Yuan
Hsien 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan Hsiang, Tao Yuan
Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==