


7.6.3 NR n7

RF Mode	NR n7 Channel Bandwidth: 20MHz	Channel	CH 507000 : 2535 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	63.95	-45.54	-25.00	-20.54	2.00 H	205	63.58	-109.12
2	172.59	-47.10	-25.00	-22.10	1.00 H	74	61.54	-108.64
3	279.29	-45.11	-25.00	-20.11	1.50 H	185	62.80	-107.91
4	480.08	-52.17	-25.00	-27.17	1.00 H	289	50.60	-102.77
5	662.44	-56.03	-25.00	-31.03	2.00 H	170	43.16	-99.19
6	877.78	-54.10	-25.00	-29.10	2.00 H	276	41.99	-96.09

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n7 Channel Bandwidth: 20MHz	Channel	CH 507000 : 2535 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	41.64	-41.91	-25.00	-16.91	1.00 V	2	65.93	-107.84
2	207.51	-48.59	-25.00	-23.59	1.50 V	169	62.54	-111.13
3	268.62	-48.36	-25.00	-23.36	1.00 V	200	59.98	-108.34
4	483.96	-50.10	-25.00	-25.10	1.00 V	77	52.57	-102.67
5	655.65	-57.05	-25.00	-32.05	2.00 V	174	42.19	-99.24
6	874.87	-54.12	-25.00	-29.12	1.50 V	278	41.94	-96.06

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




7.6.4 NR n41

RF Mode	NR n41 Channel Bandwidth: 100MHz	Channel	CH 518598 : 2592.99 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	63.95	-45.51	-25.00	-20.51	2.00 H	224	63.61	-109.12
2	172.59	-47.15	-25.00	-22.15	1.00 H	78	61.49	-108.64
3	279.29	-44.95	-25.00	-19.95	1.00 H	186	62.96	-107.91
4	478.14	-52.29	-25.00	-27.29	1.50 H	298	50.51	-102.80
5	692.51	-56.26	-25.00	-31.26	2.00 H	122	42.42	-98.68
6	874.87	-53.88	-25.00	-28.88	2.00 H	173	42.18	-96.06

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n41 Channel Bandwidth: 100MHz	Channel	CH 518598 : 2592.99 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	41.64	-41.50	-25.00	-16.50	1.00 V	169	66.34	-107.84
2	207.51	-48.53	-25.00	-23.53	1.50 V	165	62.60	-111.13
3	265.71	-48.15	-25.00	-23.15	2.00 V	236	60.35	-108.50
4	474.26	-50.06	-25.00	-25.06	1.00 V	83	52.79	-102.85
5	691.54	-56.32	-25.00	-31.32	1.50 V	2	42.39	-98.71
6	830.25	-53.93	-25.00	-28.93	2.00 V	291	42.24	-96.17

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




7.6.5 NR n66

RF Mode	NR n66 Channel Bandwidth: 40MHz	Channel	CH 349000 : 1745 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	63.95	-45.52	-13.00	-32.52	2.00 H	206	63.60	-109.12
2	172.59	-47.14	-13.00	-34.14	1.00 H	74	61.50	-108.64
3	278.32	-44.78	-13.00	-31.78	1.00 H	179	63.16	-107.94
4	477.17	-51.87	-13.00	-38.87	1.50 H	291	50.94	-102.81
5	659.53	-56.10	-13.00	-43.10	1.00 H	186	43.13	-99.23
6	843.83	-54.12	-13.00	-41.12	2.00 H	218	42.15	-96.27

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n66 Channel Bandwidth: 40MHz	Channel	CH 349000 : 1745 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	41.64	-41.74	-13.00	-28.74	1.00 V	2	66.10	-107.84
2	207.51	-48.62	-13.00	-35.62	1.00 V	167	62.51	-111.13
3	266.68	-48.26	-13.00	-35.26	1.50 V	243	60.19	-108.45
4	483.96	-49.91	-13.00	-36.91	1.00 V	87	52.76	-102.67
5	668.26	-56.85	-13.00	-43.85	2.00 V	161	42.25	-99.10
6	826.37	-54.40	-13.00	-41.40	1.50 V	299	41.76	-96.16

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




7.6.6 NR n71

RF Mode	NR n71 Channel Bandwidth: 20MHz	Channel	CH 136100 : 680.5 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	63.95	-47.58	-13.00	-34.58	2.00 H	208	63.69	-111.27
2	172.59	-49.23	-13.00	-36.23	1.00 H	78	61.56	-110.79
3	277.35	-47.52	-13.00	-34.52	1.00 H	172	62.60	-110.12
4	480.08	-54.03	-13.00	-41.03	1.50 H	302	50.89	-104.92
5	653.71	-58.24	-13.00	-45.24	1.00 H	188	43.17	-101.41
6	836.07	-56.00	-13.00	-43.00	2.00 H	235	42.30	-98.30

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
- The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n71 Channel Bandwidth: 20MHz	Channel	CH 136100 : 680.5 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	41.64	-44.19	-13.00	-31.19	1.00 V	2	65.80	-109.99
2	207.51	-50.89	-13.00	-37.89	1.50 V	173	62.39	-113.28
3	267.65	-50.62	-13.00	-37.62	1.00 V	241	59.94	-110.56
4	481.05	-51.65	-13.00	-38.65	2.00 V	82	53.23	-104.88
5	655.65	-59.22	-13.00	-46.22	2.00 V	209	42.17	-101.39
6	897.18	-54.97	-13.00	-41.97	1.00 V	30	43.21	-98.18

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. $Margin\ value = ERP - Limit\ value$
4. The other ERP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




7.6.7 NR n77 (PC2)

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	63.95	-45.85	-13.00	-32.85	2.00 H	46	63.27	-109.12
2	172.59	-47.14	-13.00	-34.14	1.00 H	79	61.50	-108.64
3	279.29	-45.57	-13.00	-32.57	1.50 H	174	62.34	-107.91
4	480.08	-52.28	-13.00	-39.28	2.00 H	294	50.49	-102.77
5	651.77	-56.24	-13.00	-43.24	1.00 H	191	43.03	-99.27
6	850.62	-53.59	-13.00	-40.59	2.00 H	3	42.68	-96.27

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	40.67	-41.83	-13.00	-28.83	1.50 V	17	66.15	-107.98
2	208.48	-48.82	-13.00	-35.82	2.00 V	172	62.30	-111.12
3	266.68	-48.83	-13.00	-35.83	1.00 V	239	59.62	-108.45
4	484.93	-50.09	-13.00	-37.09	2.00 V	85	52.54	-102.63
5	599.39	-55.46	-13.00	-42.46	1.50 V	169	44.95	-100.41
6	834.13	-54.21	-13.00	-41.21	1.00 V	49	41.94	-96.15

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 636666 : 3954.99 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	62.98	-46.01	-13.00	-33.01	1.50 H	49	62.66	-108.67
2	172.59	-47.21	-13.00	-34.21	1.00 H	72	61.43	-108.64
3	278.32	-45.48	-13.00	-32.48	2.00 H	184	62.46	-107.94
4	475.23	-52.18	-13.00	-39.18	1.00 H	300	50.65	-102.83
5	624.61	-56.32	-13.00	-43.32	1.00 H	12	43.38	-99.70
6	868.08	-53.93	-13.00	-40.93	1.50 H	119	42.21	-96.14

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 636666 : 3954.99 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	41.64	-41.58	-13.00	-28.58	1.00 V	15	66.26	-107.84
2	208.48	-48.52	-13.00	-35.52	1.50 V	171	62.60	-111.12
3	482.02	-50.12	-13.00	-37.12	1.00 V	80	52.60	-102.72
4	663.41	-57.09	-13.00	-44.09	2.00 V	161	42.08	-99.17
5	828.31	-54.13	-13.00	-41.13	1.00 V	117	42.04	-96.17
6	976.72	-53.54	-13.00	-40.54	1.50 V	18	41.67	-95.21

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




7.6.8 NR n77 (PC3)

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 67 % RH
Tested By	Tim Chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	77.53	-49.55	-13.00	-36.55	1.00 H	20	61.90	-111.45
2	129.91	-59.75	-13.00	-46.75	1.00 H	354	48.92	-108.67
3	283.17	-63.99	-13.00	-50.99	1.50 H	350	43.42	-107.41
4	416.06	-59.85	-13.00	-46.85	2.00 H	2	44.53	-104.38
5	653.71	-58.41	-13.00	-45.41	2.00 H	233	41.19	-99.60
6	884.57	-55.05	-13.00	-42.05	1.50 H	2	41.42	-96.47

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	22 °C, 67 % RH
Tested By	Tim Chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	53.28	-44.14	-13.00	-31.14	1.00 V	2	63.51	-107.65
2	129.91	-56.79	-13.00	-43.79	1.00 V	17	51.88	-108.67
3	220.12	-57.64	-13.00	-44.64	1.50 V	304	53.46	-111.10
4	288.02	-59.65	-13.00	-46.65	2.00 V	184	47.64	-107.29
5	627.52	-58.80	-13.00	-45.80	1.50 V	203	41.15	-99.95
6	864.20	-56.11	-13.00	-43.11	1.00 V	293	40.69	-96.80

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	22°C, 67% RH
Tested By	Tim Chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	77.53	-48.19	-13.00	-35.19	1.50 H	186	63.26	-111.45
2	128.94	-58.09	-13.00	-45.09	1.00 H	2	50.73	-108.82
3	286.08	-63.10	-13.00	-50.10	1.50 H	207	44.23	-107.33
4	425.76	-60.24	-13.00	-47.24	1.50 H	201	43.77	-104.01
5	630.43	-58.44	-13.00	-45.44	2.00 H	169	41.47	-99.91
6	939.86	-54.87	-13.00	-41.87	1.00 H	355	40.98	-95.85

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	22°C, 67% RH
Tested By	Tim Chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	53.28	-43.99	-13.00	-30.99	1.00 V	34	63.66	-107.65
2	219.15	-58.05	-13.00	-45.05	1.00 V	2	53.03	-111.08
3	453.89	-61.79	-13.00	-48.79	1.50 V	45	41.41	-103.20
4	629.46	-57.69	-13.00	-44.69	2.00 V	150	42.24	-99.93
5	781.75	-54.72	-13.00	-41.72	1.00 V	303	42.10	-96.82
6	925.31	-55.01	-13.00	-42.01	1.50 V	131	40.99	-96.00

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



Without shielding case


7.6.9 NR n2

RF Mode	NR n2 Channel Bandwidth: 20MHz	Channel	CH 376000 : 1880 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	63.95	-45.49	-13.00	-32.49	2.00 H	213	63.63	-109.12
2	172.59	-46.97	-13.00	-33.97	1.00 H	67	61.67	-108.64
3	278.32	-45.00	-13.00	-32.00	1.50 H	175	62.94	-107.94
4	475.23	-51.96	-13.00	-38.96	1.00 H	292	50.87	-102.83
5	624.61	-55.70	-13.00	-42.70	2.00 H	182	44.00	-99.70
6	808.91	-53.01	-13.00	-40.01	1.50 H	152	43.28	-96.29

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n2 Channel Bandwidth: 20MHz	Channel	CH 376000 : 1880 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	40.67	-40.59	-13.00	-27.59	1.00 V	156	67.39	-107.98
2	208.48	-48.42	-13.00	-35.42	1.00 V	173	62.70	-111.12
3	266.68	-49.32	-13.00	-36.32	2.00 V	235	59.13	-108.45
4	483.96	-50.03	-13.00	-37.03	1.00 V	89	52.64	-102.67
5	658.56	-55.88	-13.00	-42.88	1.50 V	165	43.35	-99.23
6	866.14	-52.76	-13.00	-39.76	1.50 V	2	43.42	-96.18

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




7.6.10 NR n5

RF Mode	NR n5 Channel Bandwidth: 20MHz	Channel	CH 167300 : 836.5 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	62.98	-46.92	-13.00	-33.92	2.00 H	46	63.90	-110.82
2	172.59	-49.25	-13.00	-36.25	1.00 H	78	61.54	-110.79
3	277.35	-47.54	-13.00	-34.54	1.00 H	178	62.58	-110.12
4	478.14	-54.59	-13.00	-41.59	1.50 H	293	50.36	-104.95
5	645.95	-58.00	-13.00	-45.00	1.00 H	180	43.43	-101.43
6	878.75	-56.36	-13.00	-43.36	2.00 H	238	41.90	-98.26

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + $20\log(D) - 104.8 - 2.15$
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
- The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n5 Channel Bandwidth: 20MHz	Channel	CH 167300 : 836.5 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	32.91	-42.42	-13.00	-29.42	1.00 V	91	68.38	-110.80
2	207.51	-50.76	-13.00	-37.76	1.50 V	173	62.52	-113.28
3	267.65	-50.51	-13.00	-37.51	1.00 V	198	60.05	-110.56
4	484.93	-52.02	-13.00	-39.02	2.00 V	83	52.76	-104.78
5	774.96	-57.06	-13.00	-44.06	1.00 V	319	41.41	-98.47
6	943.74	-54.77	-13.00	-41.77	1.50 V	267	42.90	-97.67

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. $Margin\ value = ERP - Limit\ value$
4. The other ERP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




7.6.11 NR n7

RF Mode	NR n7 Channel Bandwidth: 20MHz	Channel	CH 507000 : 2535 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	62.98	-45.74	-25.00	-20.74	2.00 H	58	62.93	-108.67
2	172.59	-47.25	-25.00	-22.25	1.00 H	75	61.39	-108.64
3	276.38	-45.47	-25.00	-20.47	1.50 H	16	62.55	-108.02
4	478.14	-52.40	-25.00	-27.40	1.00 H	294	50.40	-102.80
5	674.08	-55.33	-25.00	-30.33	2.00 H	184	43.64	-98.97
6	940.83	-53.20	-25.00	-28.20	1.50 H	301	42.31	-95.51

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n7 Channel Bandwidth: 20MHz	Channel	CH 507000 : 2535 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	41.64	-41.89	-25.00	-16.89	1.00 V	15	65.95	-107.84
2	207.51	-48.56	-25.00	-23.56	1.50 V	168	62.57	-111.13
3	263.77	-48.46	-25.00	-23.46	2.00 V	234	60.14	-108.60
4	482.02	-49.76	-25.00	-24.76	2.00 V	81	52.96	-102.72
5	658.56	-55.97	-25.00	-30.97	1.00 V	185	43.26	-99.23
6	839.95	-54.26	-25.00	-29.26	1.50 V	13	41.94	-96.20

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




7.6.12 NR n41

RF Mode	NR n41 Channel Bandwidth: 100MHz	Channel	CH 518598 : 2592.99 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	62.98	-45.72	-25.00	-20.72	2.00 H	37	62.95	-108.67
2	172.59	-46.95	-25.00	-21.95	1.00 H	69	61.69	-108.64
3	281.23	-45.45	-25.00	-20.45	1.50 H	190	62.39	-107.84
4	480.08	-52.20	-25.00	-27.20	1.00 H	297	50.57	-102.77
5	654.68	-55.92	-25.00	-30.92	2.00 H	175	43.33	-99.25
6	825.40	-53.90	-25.00	-28.90	1.50 H	2	42.26	-96.16

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n41 Channel Bandwidth: 100MHz	Channel	CH 518598 : 2592.99 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	40.67	-40.96	-25.00	-15.96	1.00 V	1	67.02	-107.98
2	207.51	-48.67	-25.00	-23.67	1.50 V	178	62.46	-111.13
3	266.68	-48.41	-25.00	-23.41	1.00 V	239	60.04	-108.45
4	487.84	-49.64	-25.00	-24.64	2.00 V	83	52.90	-102.54
5	613.94	-56.24	-25.00	-31.24	1.00 V	166	43.74	-99.98
6	903.97	-53.51	-25.00	-28.51	1.50 V	166	42.44	-95.95

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




7.6.13 NR n66

RF Mode	NR n66 Channel Bandwidth: 40MHz	Channel	CH 349000 : 1745 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	63.95	-44.57	-13.00	-31.57	2.00 H	53	64.55	-109.12
2	172.59	-47.11	-13.00	-34.11	1.00 H	64	61.53	-108.64
3	278.32	-45.49	-13.00	-32.49	1.00 H	184	62.45	-107.94
4	481.05	-52.10	-13.00	-39.10	1.50 H	302	50.63	-102.73
5	647.89	-56.36	-13.00	-43.36	2.00 H	171	42.92	-99.28
6	870.02	-53.48	-13.00	-40.48	2.00 H	87	42.60	-96.08

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n66 Channel Bandwidth: 40MHz	Channel	CH 349000 : 1745 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	41.64	-41.63	-13.00	-28.63	1.50 V	19	66.21	-107.84
2	207.51	-48.58	-13.00	-35.58	1.00 V	172	62.55	-111.13
3	260.86	-48.58	-13.00	-35.58	1.00 V	224	60.14	-108.72
4	484.93	-50.05	-13.00	-37.05	2.00 V	86	52.58	-102.63
5	646.92	-56.62	-13.00	-43.62	1.50 V	263	42.66	-99.28
6	898.15	-52.41	-13.00	-39.41	2.00 V	54	43.64	-96.05

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




7.6.14 NR n71

RF Mode	NR n71 Channel Bandwidth: 20MHz	Channel	CH 136100 : 680.5 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	63.95	-47.68	-13.00	-34.68	2.00 H	215	63.59	-111.27
2	173.56	-49.25	-13.00	-36.25	1.00 H	66	61.62	-110.87
3	277.35	-46.65	-13.00	-33.65	1.50 H	180	63.47	-110.12
4	483.96	-54.09	-13.00	-41.09	2.00 H	292	50.73	-104.82
5	655.65	-58.20	-13.00	-45.20	1.00 H	184	43.19	-101.39
6	940.83	-54.83	-13.00	-41.83	1.50 H	288	42.83	-97.66

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
- The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n71 Channel Bandwidth: 20MHz	Channel	CH 136100 : 680.5 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	41.64	-43.91	-13.00	-30.91	1.50 V	2	66.08	-109.99
2	207.51	-50.80	-13.00	-37.80	1.00 V	172	62.48	-113.28
3	269.59	-50.69	-13.00	-37.69	1.00 V	241	59.76	-110.45
4	488.81	-52.36	-13.00	-39.36	2.00 V	84	52.32	-104.68
5	644.01	-58.74	-13.00	-45.74	1.00 V	283	42.70	-101.44
6	942.77	-54.66	-13.00	-41.66	1.50 V	306	43.01	-97.67

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. $Margin\ value = ERP - Limit\ value$
4. The other ERP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




7.6.15 NR n77 (PC2)

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	63.95	-45.78	-13.00	-32.78	2.00 H	217	63.34	-109.12
2	172.59	-46.99	-13.00	-33.99	1.00 H	73	61.65	-108.64
3	275.41	-45.50	-13.00	-32.50	1.50 H	13	62.55	-108.05
4	480.08	-52.41	-13.00	-39.41	1.00 H	296	50.36	-102.77
5	656.62	-56.32	-13.00	-43.32	1.50 H	185	42.92	-99.24
6	824.43	-54.15	-13.00	-41.15	1.00 H	231	42.00	-96.15

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	40.67	-41.86	-13.00	-28.86	1.00 V	2	66.12	-107.98
2	208.48	-48.55	-13.00	-35.55	1.50 V	172	62.57	-111.12
3	265.71	-48.65	-13.00	-35.65	1.00 V	233	59.85	-108.50
4	485.90	-49.89	-13.00	-36.89	2.00 V	87	52.71	-102.60
5	693.48	-56.03	-13.00	-43.03	1.00 V	45	42.62	-98.65
6	840.92	-53.84	-13.00	-40.84	1.50 V	280	42.38	-96.22

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 663666 : 3954.99 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	63.95	-45.74	-13.00	-32.74	2.00 H	224	63.38	-109.12
2	172.59	-47.30	-13.00	-34.30	1.00 H	65	61.34	-108.64
3	277.35	-45.36	-13.00	-32.36	1.50 H	174	62.61	-107.97
4	447.10	-52.98	-13.00	-39.98	1.00 H	280	50.48	-103.46
5	624.61	-56.24	-13.00	-43.24	2.00 H	10	43.46	-99.70
6	901.06	-49.98	-13.00	-36.98	1.00 H	317	46.04	-96.02

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 663666 : 3954.99 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 65 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	40.67	-41.41	-13.00	-28.41	1.00 V	2	66.57	-107.98
2	207.51	-48.77	-13.00	-35.77	1.50 V	165	62.36	-111.13
3	267.65	-48.59	-13.00	-35.59	1.00 V	245	59.82	-108.41
4	482.02	-50.47	-13.00	-37.47	1.00 V	92	52.25	-102.72
5	695.42	-56.91	-13.00	-43.91	2.00 V	300	41.69	-98.60
6	875.84	-54.22	-13.00	-41.22	1.50 V	248	41.86	-96.08

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




7.6.16 NR n77 (PC3)

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	22°C, 67% RH
Tested By	Tim Chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	49.40	-47.15	-13.00	-34.15	2.00 H	144	60.36	-107.51
2	130.88	-47.53	-13.00	-34.53	1.00 H	164	61.13	-108.66
3	294.81	-45.21	-13.00	-32.21	1.50 H	104	61.95	-107.16
4	358.83	-47.67	-13.00	-34.67	1.00 H	118	58.11	-105.78
5	617.82	-59.35	-13.00	-46.35	2.00 H	243	40.77	-100.12
6	829.28	-55.52	-13.00	-42.52	1.00 H	258	41.26	-96.78

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	22°C, 67% RH
Tested By	Tim Chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	51.34	-46.17	-13.00	-33.17	1.00 V	335	61.40	-107.57
2	116.33	-49.24	-13.00	-36.24	1.50 V	317	60.61	-109.85
3	295.78	-46.79	-13.00	-33.79	1.00 V	196	60.35	-107.14
4	543.13	-50.22	-13.00	-37.22	2.00 V	167	51.34	-101.56
5	629.46	-53.85	-13.00	-40.85	1.00 V	3	46.08	-99.93
6	903.97	-55.90	-13.00	-42.90	1.50 V	198	40.36	-96.26

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	22°C, 67% RH
Tested By	Tim Chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	46.49	-46.80	-13.00	-33.80	2.00 H	87	60.69	-107.49
2	149.31	-47.36	-13.00	-34.36	1.50 H	245	60.33	-107.69
3	294.81	-46.61	-13.00	-33.61	1.00 H	93	60.55	-107.16
4	355.92	-48.09	-13.00	-35.09	1.50 H	117	57.76	-105.85
5	624.61	-59.24	-13.00	-46.24	1.00 H	235	40.76	-100.00
6	889.42	-55.06	-13.00	-42.06	2.00 H	263	41.33	-96.39

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	22°C, 67% RH
Tested By	Tim Chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	46.49	-46.74	-13.00	-33.74	1.00 V	17	60.75	-107.49
2	72.68	-46.72	-13.00	-33.72	1.50 V	102	63.44	-110.16
3	149.31	-46.80	-13.00	-33.80	1.00 V	249	60.89	-107.69
4	294.81	-46.86	-13.00	-33.86	2.00 V	194	60.30	-107.16
5	639.16	-57.44	-13.00	-44.44	1.50 V	29	42.25	-99.69
6	858.38	-56.31	-13.00	-43.31	1.00 V	82	40.48	-96.79

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



7.7 Radiated Spurious Emissions above 1GHz

With shielding case

7.7.1 NR n2

RF Mode	NR n2 Channel Bandwidth: 5MHz	Channel	CH 370500 : 1852.5 MHz
Frequency Range	1 GHz ~ 20 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3705.00	-50.14	-13.00	-37.14	3.15 H	257	43.12	-93.26
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3705.00	-47.94	-13.00	-34.94	2.06 V	175	45.32	-93.26

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n2 Channel Bandwidth: 5MHz	Channel	CH 376000 : 1880 MHz
Frequency Range	1 GHz ~ 20 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-50.00	-13.00	-37.00	3.34 H	46	43.06	-93.06
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-47.81	-13.00	-34.81	2.24 V	287	45.25	-93.06

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n2 Channel Bandwidth: 5MHz	Channel	CH 381500 : 1907.5 MHz
Frequency Range	1 GHz ~ 20 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3815.00	-49.86	-13.00	-36.86	2.16 H	285	43.12	-92.98
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3815.00	-47.71	-13.00	-34.71	1.86 V	301	45.27	-92.98

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n2 Channel Bandwidth: 20MHz	Channel	CH 381500 : 1907.5 MHz
Frequency Range	1 GHz ~ 20 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3720.00	-50.03	-13.00	-37.03	2.15 H	143	43.17	-93.20
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3720.00	-47.88	-13.00	-34.88	3.54 V	46	45.32	-93.20

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n2 Channel Bandwidth: 20MHz	Channel	CH 376000 : 1880 MHz
Frequency Range	1 GHz ~ 20 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-49.39	-13.00	-36.39	1.68 H	235	43.67	-93.06
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-47.22	-13.00	-34.22	3.81 V	135	45.84	-93.06

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n2 Channel Bandwidth: 20MHz	Channel	CH 380000 : 1900 MHz
Frequency Range	1 GHz ~ 20 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3800.00	-49.98	-13.00	-36.98	3.57 H	145	43.05	-93.03
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3800.00	-47.66	-13.00	-34.66	2.15 V	36	45.37	-93.03

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

7.7.2 NR n5

RF Mode	NR n5 Channel Bandwidth: 5MHz	Channel	CH 165300 : 826.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1653.00	-58.37	-13.00	-45.37	2.86 H	256	43.24	-101.61
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1653.00	-56.20	-13.00	-43.20	2.53 V	78	45.41	-101.61

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n5 Channel Bandwidth: 5MHz	Channel	CH 167300 : 836.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1673.00	-58.35	-13.00	-45.35	2.75 H	35	43.26	-101.61
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1673.00	-56.13	-13.00	-43.13	1.23 V	324	45.48	-101.61

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n5 Channel Bandwidth: 5MHz	Channel	CH 169300 : 846.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1693.00	-58.27	-13.00	-45.27	2.35 H	45	43.34	-101.61
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1693.00	-56.22	-13.00	-43.22	1.16 V	317	45.39	-101.61

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n5 Channel Bandwidth: 20MHz	Channel	CH 166800 : 834 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1668.00	-58.32	-13.00	-45.32	2.76 H	215	43.29	-101.61
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1668.00	-56.25	-13.00	-43.25	1.68 V	73	45.36	-101.61

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. Margin value = ERP – Limit value
4. The other ERP levels were very low against the limit.

RF Mode	NR n5 Channel Bandwidth: 20MHz	Channel	CH 167300 : 836.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1673.00	-57.83	-13.00	-44.83	3.15 H	217	43.78	-101.61
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1673.00	-55.66	-13.00	-42.66	2.13 V	254	45.95	-101.61

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. Margin value = ERP – Limit value
4. The other ERP levels were very low against the limit.

RF Mode	NR n5 Channel Bandwidth: 20MHz	Channel	CH 167800 : 839 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1678.00	-58.26	-13.00	-45.26	3.84 H	183	43.35	-101.61
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1678.00	-56.33	-13.00	-43.33	2.16 V	137	45.28	-101.61

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

7.7.3 NR n7

RF Mode	NR n7 Channel Bandwidth: 5MHz	Channel	CH 500500 : 2502.5 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5005.00	-36.63	-25.00	-11.63	1.56 H	315	53.87	-90.50
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5005.00	-35.29	-25.00	-10.29	2.14 V	265	55.21	-90.50

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n7 Channel Bandwidth: 5MHz	Channel	CH 507000 : 2535 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5070.00	-36.24	-25.00	-11.24	2.14 H	246	53.75	-89.99
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5070.00	-34.73	-25.00	-9.73	1.53 V	243	55.26	-89.99

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n7 Channel Bandwidth: 5MHz	Channel	CH 513500 : 2567.5 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5135.00	-36.15	-25.00	-11.15	3.42 H	257	53.67	-89.82
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5135.00	-34.48	-25.00	-9.48	1.65 V	183	55.34	-89.82

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n7 Channel Bandwidth: 20MHz	Channel	CH 502000 : 2510 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5020.00	-36.89	-25.00	-11.89	3.75 H	186	53.48	-90.37
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5020.00	-35.13	-25.00	-10.13	1.65 V	59	55.24	-90.37

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n7 Channel Bandwidth: 20MHz	Channel	CH 507000 : 2535 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5070.00	-35.81	-25.00	-10.81	3.45 H	125	54.18	-89.99
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5070.00	-34.22	-25.00	-9.22	1.14 V	216	55.77	-89.99

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n7 Channel Bandwidth: 20MHz	Channel	CH 512000 : 2560 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5120.00	-36.12	-25.00	-11.12	1.86 H	146	53.69	-89.81
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5120.00	-34.54	-25.00	-9.54	1.96 V	76	55.27	-89.81

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

7.7.4 NR n41

RF Mode	NR n41 Channel Bandwidth: 10MHz	Channel	CH 502002 : 2510.01 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5002.02	-35.50	-25.00	-10.50	1.26 H	38	55.02	-90.52
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5002.02	-32.50	-25.00	-7.50	1.97 V	153	58.02	-90.52

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 10MHz	Channel	CH 518598 : 2592.99 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5185.98	-35.04	-25.00	-10.04	1.14 H	36	55.07	-90.11
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5185.98	-32.14	-25.00	-7.14	1.65 V	183	57.97	-90.11

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 10MHz	Channel	CH 537000 : 2685 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5370.00	-35.43	-25.00	-10.43	1.25 H	46	55.08	-90.51
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5370.00	-32.45	-25.00	-7.45	1.87 V	176	58.06	-90.51

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 50MHz	Channel	CH 504204 : 2521.02 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5042.04	-35.16	-25.00	-10.16	1.35 H	19	55.03	-90.19
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5042.04	-32.26	-25.00	-7.26	1.86 V	191	57.93	-90.19

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 50MHz	Channel	CH 518598 : 2592.99 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5185.98	-35.05	-25.00	-10.05	1.35 H	39	55.06	-90.11
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5185.98	-32.07	-25.00	-7.07	1.45 V	32	58.04	-90.11

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 50MHz	Channel	CH 532998 : 2664.99 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5329.98	-35.52	-25.00	-10.52	1.32 H	39	55.04	-90.56
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5329.98	-32.50	-25.00	-7.50	1.83 V	205	58.06	-90.56

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 100MHz	Channel	CH 509202 : 2546.01 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5092.02	-34.72	-25.00	-9.72	1.36 H	45	55.12	-89.84
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5092.02	-31.91	-25.00	-6.91	1.85 V	183	57.93	-89.84

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 100MHz	Channel	CH 518598 : 2592.99 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5185.98	-34.54	-25.00	-9.54	1.46 H	46	55.57	-90.11
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5185.98	-31.63	-25.00	-6.63	2.01 V	176	58.48	-90.11

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 100MHz	Channel	CH 528000 : 2640 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5280.00	-35.41	-25.00	-10.41	1.75 H	176	55.13	-90.54
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5280.00	-32.39	-25.00	-7.39	1.75 V	176	58.15	-90.54

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

7.7.5 NR n66

RF Mode	NR n66 Channel Bandwidth: 5MHz	Channel	CH 342500 : 1712.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3425.00	-49.41	-13.00	-36.41	1.23 H	258	44.69	-94.10
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3425.00	-47.18	-13.00	-34.18	2.35 V	98	46.92	-94.10

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 5MHz	Channel	CH 349000 : 1745 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.00	-48.80	-13.00	-35.80	1.28 H	246	44.71	-93.51
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.00	-46.62	-13.00	-33.62	2.24 V	129	46.89	-93.51

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 5MHz	Channel	CH 355500 : 1777.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3555.00	-48.59	-13.00	-35.59	1.21 H	243	44.72	-93.31
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3555.00	-46.48	-13.00	-33.48	2.34 V	138	46.83	-93.31

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 20MHz	Channel	CH 344000 : 1720 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3440.00	-49.26	-13.00	-36.26	2.43 H	156	44.73	-93.99
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3440.00	-47.12	-13.00	-34.12	2.72 V	126	46.87	-93.99

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 20MHz	Channel	CH 349000 : 1745 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.00	-48.79	-13.00	-35.79	2.21 H	146	44.72	-93.51
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.00	-46.56	-13.00	-33.56	2.46 V	123	46.95	-93.51

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 20MHz	Channel	CH 354000 : 1770 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3540.00	-48.60	-13.00	-35.60	2.41 H	135	44.73	-93.33
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3540.00	-46.49	-13.00	-33.49	2.64 V	129	46.84	-93.33

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 40MHz	Channel	CH 346000 : 1730 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3460.00	-48.07	-13.00	-35.07	1.21 H	224	45.74	-93.81
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3460.00	-46.83	-13.00	-33.83	2.14 V	84	46.98	-93.81

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 40MHz	Channel	CH 349000 : 1745 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.00	-48.25	-13.00	-35.25	1.28 H	215	45.26	-93.51
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.00	-46.08	-13.00	-33.08	2.34 V	125	47.43	-93.51

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 40MHz	Channel	CH 352000 : 1760 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3520.00	-48.40	-13.00	-35.40	1.28 H	210	44.96	-93.36
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3520.00	-46.24	-13.00	-33.24	2.14 V	119	47.12	-93.36

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

7.7.6 NR n71

RF Mode	NR n71 Channel Bandwidth: 5MHz	Channel	CH 133100 : 665.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1331.00	-53.30	-13.00	-40.30	1.07 H	245	47.76	-101.06
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1331.00	-51.20	-13.00	-38.20	2.37 V	125	49.86	-101.06

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n71 Channel Bandwidth: 5MHz	Channel	CH 136100 : 680.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1361.00	-53.28	-13.00	-40.28	1.58 H	243	47.73	-101.01
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1361.00	-51.15	-13.00	-38.15	2.15 V	173	49.86	-101.01

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. Margin value = ERP – Limit value
4. The other ERP levels were very low against the limit.

RF Mode	NR n71 Channel Bandwidth: 5MHz	Channel	CH 139100 : 695.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1391.00	-52.98	-13.00	-39.98	1.25 H	241	47.88	-100.86
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1391.00	-50.91	-13.00	-37.91	2.24 V	148	49.95	-100.86

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n71 Channel Bandwidth: 20MHz	Channel	CH 134600 : 673 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1346.00	-53.16	-13.00	-40.16	1.24 H	223	47.91	-101.07
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1346.00	-51.69	-13.00	-38.69	2.15 V	159	49.38	-101.07

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n71 Channel Bandwidth: 20MHz	Channel	CH 136100 : 680.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1361.00	-52.64	-13.00	-39.64	1.09 H	243	48.37	-101.01
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1361.00	-50.39	-13.00	-37.39	2.13 V	146	50.62	-101.01

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n71 Channel Bandwidth: 20MHz	Channel	CH 137600 : 688 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1376.00	-53.01	-13.00	-40.01	1.21 H	248	47.93	-100.94
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1376.00	-50.96	-13.00	-37.96	2.13 V	157	49.98	-100.94

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

7.7.7 NR n77 (PC2)

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 630334 : 3455.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6910.02	-53.17	-13.00	-40.17	1.24 H	138	33.52	-86.69
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6910.02	-52.71	-13.00	-39.71	1.53 V	204	33.98	-86.69

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-52.56	-13.00	-39.56	1.05 H	27	33.46	-86.02
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-52.05	-13.00	-39.05	1.43 V	185	33.97	-86.02

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 636332 : 3544.98 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7089.96	-52.19	-13.00	-39.19	1.08 H	165	33.46	-85.65
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7089.96	-51.84	-13.00	-38.84	1.53 V	178	33.81	-85.65

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 631668 : 3475.021 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6950.04	-52.93	-13.00	-39.93	1.15 H	212	33.56	-86.49
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6950.04	-52.50	-13.00	-39.50	1.65 V	208	33.99	-86.49

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-52.66	-13.00	-39.66	1.20 H	98	33.36	-86.02
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-52.05	-13.00	-39.05	1.25 V	241	33.97	-86.02

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 635000 : 3525 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7050.00	-52.14	-13.00	-39.14	1.15 H	165	33.52	-85.66
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7050.00	-51.79	-13.00	-38.79	1.58 V	177	33.87	-85.66

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-52.20	-13.00	-39.20	1.24 H	165	33.82	-86.02
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-51.59	-13.00	-38.59	1.56 V	182	34.43	-86.02

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 647000 : 3705 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7410.00	-52.14	-13.00	-39.14	1.42 H	149	33.26	-85.40
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7410.00	-51.45	-13.00	-38.45	1.56 V	210	33.95	-85.40

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-52.33	-13.00	-39.33	1.26 H	105	33.31	-85.64
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-51.69	-13.00	-38.69	1.51 V	193	33.95	-85.64

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 665000 : 3975 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7950.00	-51.44	-13.00	-38.44	1.08 H	142	33.47	-84.91
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7950.00	-50.92	-13.00	-37.92	1.63 V	189	33.99	-84.91

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 648334 : 3725.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7450.02	-51.95	-13.00	-38.95	1.25 H	141	33.32	-85.27
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7450.02	-51.25	-13.00	-38.25	1.56 V	198	34.02	-85.27

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-52.17	-13.00	-39.17	1.24 H	141	33.47	-85.64
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-51.71	-13.00	-38.71	1.65 V	217	33.93	-85.64

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 663666 : 3954.99 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7909.98	-51.25	-13.00	-38.25	1.25 H	193	33.45	-84.70
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7909.98	-50.72	-13.00	-37.72	1.51 V	227	33.98	-84.70

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 650000 : 3750 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7500.00	-52.07	-13.00	-39.07	1.04 H	29	33.38	-85.45
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7500.00	-51.51	-13.00	-38.51	1.72 V	218	33.94	-85.45

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-51.79	-13.00	-38.79	1.12 H	96	33.85	-85.64
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-51.22	-13.00	-38.22	1.52 V	186	34.42	-85.64

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 662000 : 3930 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7860.00	-51.57	-13.00	-38.57	1.42 H	216	33.42	-84.99
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7860.00	-51.13	-13.00	-38.13	1.58 V	196	33.86	-84.99

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

7.7.8 NR n77 (PC3)

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 630334 : 3455.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6910.02	-53.96	-13.00	-40.96	1.26 H	140	45.82	-99.78
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6910.02	-52.53	-13.00	-39.53	1.63 V	208	47.25	-99.78

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-52.99	-13.00	-39.99	1.03 H	21	46.21	-99.20
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-51.99	-13.00	-38.99	1.49 V	193	47.21	-99.20

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 636332 : 3544.98 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7089.96	-52.16	-13.00	-39.16	1.05 H	178	46.15	-98.31
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7089.96	-51.80	-13.00	-38.80	1.58 V	183	46.51	-98.31

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 631668 : 3475.02 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6950.04	-53.77	-13.00	-40.77	1.14 H	216	45.78	-99.55
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6950.04	-52.57	-13.00	-39.57	1.66 V	207	46.98	-99.55

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-53.64	-13.00	-40.64	1.32 H	104	45.56	-99.20
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-51.77	-13.00	-38.77	1.26 V	247	47.43	-99.20

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 635000 : 3525 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7050.00	-53.02	-13.00	-40.02	1.17 H	177	45.53	-98.55
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7050.00	-51.52	-13.00	-38.52	1.67 V	187	47.03	-98.55

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-53.17	-13.00	-40.17	1.27 H	187	46.03	-99.20
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-51.64	-13.00	-38.64	1.55 V	189	47.56	-99.20

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 647000 : 3705 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7410.00	-51.15	-13.00	-38.15	1.43 H	142	46.51	-97.66
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7410.00	-50.61	-13.00	-37.61	1.56 V	211	47.05	-97.66

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-51.69	-13.00	-38.69	1.21 H	111	46.05	-97.74
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-50.69	-13.00	-37.69	1.54 V	196	47.05	-97.74

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 665000 : 3975 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7950.00	-50.55	-13.00	-37.55	1.04 H	144	45.89	-96.44
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7950.00	-49.61	-13.00	-36.61	1.67 V	201	46.83	-96.44

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 648334 : 3725.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7450.02	-51.66	-13.00	-38.66	1.23 H	147	45.65	-97.31
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7450.02	-50.64	-13.00	-37.64	1.51 V	203	46.67	-97.31

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-52.21	-13.00	-39.21	1.24 H	144	45.53	-97.74
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-50.90	-13.00	-37.90	1.63 V	211	46.84	-97.74

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 663666 : 3954.99 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7909.98	-50.60	-13.00	-37.60	1.18 H	207	46.04	-96.64
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7909.98	-49.87	-13.00	-36.87	1.57 V	219	46.77	-96.64

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 650000 : 3750 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7500.00	-51.63	-13.00	-38.63	1.06 H	24	45.84	-97.47
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7500.00	-50.50	-13.00	-37.50	1.68 V	207	46.97	-97.47

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-52.27	-13.00	-39.27	1.18 H	104	45.47	-97.74
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-50.50	-13.00	-37.50	1.54 V	194	47.24	-97.74

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 662000 : 3930 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7860.00	-50.84	-13.00	-37.84	1.52 H	332	46.07	-96.91
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7860.00	-49.92	-13.00	-36.92	1.43 V	202	46.99	-96.91

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

Without shielding case

7.7.9 NR n2

RF Mode	NR n2 Channel Bandwidth: 5MHz	Channel	CH 370500 : 1852.5 MHz
Frequency Range	1 GHz ~ 20 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3705.00	-50.02	-13.00	-37.02	3.04 H	245	43.24	-93.26
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3705.00	-47.80	-13.00	-34.80	2.16 V	157	45.46	-93.26

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

RF Mode	NR n2 Channel Bandwidth: 5MHz	Channel	CH 376000 : 1880 MHz
Frequency Range	1 GHz ~ 20 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-49.94	-13.00	-36.94	3.14 H	58	43.12	-93.06
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-47.70	-13.00	-34.70	2.15 V	276	45.36	-93.06

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n2 Channel Bandwidth: 5MHz	Channel	CH 381500 : 1907.5 MHz
Frequency Range	1 GHz ~ 20 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3815.00	-49.72	-13.00	-36.72	2.15 H	287	43.26	-92.98
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3815.00	-47.62	-13.00	-34.62	1.82 V	314	45.36	-92.98

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n2 Channel Bandwidth: 20MHz	Channel	CH 381500 : 1907.5 MHz
Frequency Range	1 GHz ~ 20 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3720.00	-49.94	-13.00	-36.94	2.14 H	149	43.26	-93.20
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3720.00	-49.96	-13.00	-36.96	2.10 V	159	43.24	-93.20

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n2 Channel Bandwidth: 20MHz	Channel	CH 376000 : 1880 MHz
Frequency Range	1 GHz ~ 20 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-49.34	-13.00	-36.34	1.72 H	243	43.72	-93.06
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-47.10	-13.00	-34.10	3.57 V	145	45.96	-93.06

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n2 Channel Bandwidth: 20MHz	Channel	CH 380000 : 1900 MHz
Frequency Range	1 GHz ~ 20 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3800.00	-49.87	-13.00	-36.87	3.24 H	135	43.16	-93.03
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3800.00	-47.57	-13.00	-34.57	2.12 V	46	45.46	-93.03

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

7.7.10 NR n5

RF Mode	NR n5 Channel Bandwidth: 5MHz	Channel	CH 165300 : 826.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1653.00	-58.26	-13.00	-45.26	2.76 H	245	43.35	-101.61
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1653.00	-56.09	-13.00	-43.09	2.42 V	68	45.52	-101.61

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n5 Channel Bandwidth: 5MHz	Channel	CH 167300 : 836.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1673.00	-58.23	-13.00	-45.23	2.67 H	45	43.38	-101.61
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1673.00	-56.05	-13.00	-43.05	1.25 V	314	45.56	-101.61

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n5 Channel Bandwidth: 5MHz	Channel	CH 169300 : 846.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1693.00	-58.14	-13.00	-45.14	2.24 H	13	43.47	-101.61
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1693.00	-56.15	-13.00	-43.15	1.28 V	305	45.46	-101.61

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n5 Channel Bandwidth: 20MHz	Channel	CH 166800 : 834 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1668.00	-58.26	-13.00	-45.26	2.67 H	224	43.35	-101.61
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1668.00	-56.14	-13.00	-43.14	1.76 V	86	45.47	-101.61

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n5 Channel Bandwidth: 20MHz	Channel	CH 167300 : 836.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1673.00	-57.72	-13.00	-44.72	3.24 H	224	43.89	-101.61
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1673.00	-55.58	-13.00	-42.58	2.16 V	242	46.03	-101.61

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. Margin value = ERP – Limit value
4. The other ERP levels were very low against the limit.

RF Mode	NR n5 Channel Bandwidth: 20MHz	Channel	CH 167800 : 839 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1678.00	-58.19	-13.00	-45.19	3.75 H	165	43.42	-101.61
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1678.00	-56.25	-13.00	-43.25	2.06 V	142	45.36	-101.61

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. Margin value = ERP – Limit value
4. The other ERP levels were very low against the limit.

7.7.11 NR n7

RF Mode	NR n7 Channel Bandwidth: 5MHz	Channel	CH 500500 : 2502.5 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5005.00	-36.56	-25.00	-11.56	1.42 H	310	53.94	-90.50
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5005.00	-35.16	-25.00	-10.16	2.17 V	253	55.34	-90.50

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n7 Channel Bandwidth: 5MHz	Channel	CH 507000 : 2535 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5070.00	-36.12	-25.00	-11.12	2.16 H	265	53.87	-89.99
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5070.00	-34.63	-25.00	-9.63	1.67 V	254	55.36	-89.99

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n7 Channel Bandwidth: 5MHz	Channel	CH 513500 : 2567.5 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5135.00	-36.10	-25.00	-11.10	3.14 H	243	53.72	-89.82
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5135.00	-34.40	-25.00	-9.40	1.42 V	156	55.42	-89.82

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n7 Channel Bandwidth: 20MHz	Channel	CH 502000 : 2510 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5020.00	-36.78	-25.00	-11.78	3.67 H	174	53.59	-90.37
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5020.00	-34.99	-25.00	-9.99	1.62 V	64	55.38	-90.37

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n7 Channel Bandwidth: 20MHz	Channel	CH 507000 : 2535 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5070.00	-35.73	-25.00	-10.73	3.32 H	128	54.26	-89.99
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5070.00	-34.16	-25.00	-9.16	1.23 V	227	55.83	-89.99

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n7 Channel Bandwidth: 20MHz	Channel	CH 512000 : 2560 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5120.00	-36.07	-25.00	-11.07	1.74 H	152	53.74	-89.81
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5120.00	-34.45	-25.00	-9.45	1.86 V	67	55.36	-89.81

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

7.7.12 NR n41

RF Mode	NR n41 Channel Bandwidth: 10MHz	Channel	CH 502002 : 2510.01 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5002.02	-35.40	-25.00	-10.40	1.35 H	46	55.12	-90.52
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5002.02	-32.36	-25.00	-7.36	1.92 V	147	58.16	-90.52

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 10MHz	Channel	CH 518598 : 2592.99 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5185.98	-34.95	-25.00	-9.95	1.24 H	46	55.16	-90.11
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5185.98	-32.07	-25.00	-7.07	1.76 V	174	58.04	-90.11

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 10MHz	Channel	CH 537000 : 2685 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5370.00	-35.37	-25.00	-10.37	1.35 H	57	55.14	-90.51
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5370.00	-32.39	-25.00	-7.39	1.88 V	177	58.12	-90.51

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 50MHz	Channel	CH 504204 : 2521.02 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5042.04	-35.03	-25.00	-10.03	1.39 H	25	55.16	-90.19
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5042.04	-32.14	-25.00	-7.14	1.94 V	186	58.05	-90.19

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 50MHz	Channel	CH 518598 : 2592.99 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5185.98	-34.96	-25.00	-9.96	1.36 H	47	55.15	-90.11
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5185.98	-31.97	-25.00	-6.97	1.56 V	36	58.14	-90.11

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 50MHz	Channel	CH 532998 : 2664.99 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5329.98	-35.44	-25.00	-10.44	1.45 H	46	55.12	-90.56
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5329.98	-32.42	-25.00	-7.42	1.82 V	215	58.14	-90.56

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 100MHz	Channel	CH 509202 : 2546.01 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5092.02	-34.60	-25.00	-9.60	1.45 H	59	55.24	-89.84
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5092.02	-31.81	-25.00	-6.81	1.76 V	182	58.03	-89.84

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 100MHz	Channel	CH 518598 : 2592.99 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5185.98	-34.48	-25.00	-9.48	1.43 H	56	55.63	-90.11
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5185.98	-31.55	-25.00	-6.55	2.03 V	185	58.56	-90.11

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n41 Channel Bandwidth: 100MHz	Channel	CH 528000 : 2640 MHz
Frequency Range	1 GHz ~ 27 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5280.00	-35.30	-25.00	-10.30	1.62 H	169	55.24	-90.54
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5280.00	-32.30	-25.00	-7.30	1.69 V	224	58.24	-90.54

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

7.7.13 NR n66

RF Mode	NR n66 Channel Bandwidth: 5MHz	Channel	CH 342500 : 1712.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3425.00	-49.34	-13.00	-36.34	1.25 H	243	44.76	-94.10
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3425.00	-47.04	-13.00	-34.04	2.14 V	78	47.06	-94.10

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 5MHz	Channel	CH 349000 : 1745 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.00	-48.68	-13.00	-35.68	1.24 H	241	44.83	-93.51
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.00	-46.56	-13.00	-33.56	2.16 V	143	46.95	-93.51

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 5MHz	Channel	CH 355500 : 1777.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3555.00	-48.49	-13.00	-35.49	1.34 H	256	44.82	-93.31
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3555.00	-46.36	-13.00	-33.36	2.14 V	146	46.95	-93.31

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 20MHz	Channel	CH 344000 : 1720 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3440.00	-49.13	-13.00	-36.13	2.51 H	176	44.86	-93.99
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3440.00	-47.06	-13.00	-34.06	2.45 V	136	46.93	-93.99

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 20MHz	Channel	CH 349000 : 1745 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.00	-48.67	-13.00	-35.67	2.14 H	152	44.84	-93.51
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.00	-46.46	-13.00	-33.46	2.31 V	142	47.05	-93.51

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 20MHz	Channel	CH 354000 : 1770 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3540.00	-48.48	-13.00	-35.48	2.32 H	141	44.85	-93.33
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3540.00	-46.42	-13.00	-33.42	2.51 V	136	46.91	-93.33

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 40MHz	Channel	CH 346000 : 1730 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3460.00	-47.97	-13.00	-34.97	1.35 H	217	45.84	-93.81
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3460.00	-46.78	-13.00	-33.78	2.11 V	75	47.03	-93.81

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 40MHz	Channel	CH 349000 : 1745 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.00	-48.15	-13.00	-35.15	1.20 H	187	45.36	-93.51
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.00	-45.95	-13.00	-32.95	2.38 V	128	47.56	-93.51

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n66 Channel Bandwidth: 40MHz	Channel	CH 352000 : 1760 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3520.00	-48.30	-13.00	-35.30	1.35 H	204	45.06	-93.36
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3520.00	-46.10	-13.00	-33.10	2.16 V	125	47.26	-93.36

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

7.7.14 NR n71

RF Mode	NR n71 Channel Bandwidth: 5MHz	Channel	CH 133100 : 665.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1331.00	-53.20	-13.00	-40.20	1.14 H	236	47.86	-101.06
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1331.00	-51.11	-13.00	-38.11	2.46 V	137	49.95	-101.06

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n71 Channel Bandwidth: 5MHz	Channel	CH 136100 : 680.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1361.00	-53.14	-13.00	-40.14	1.52 H	235	47.87	-101.01
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1361.00	-50.96	-13.00	-37.96	2.14 V	152	50.05	-101.01

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n71 Channel Bandwidth: 5MHz	Channel	CH 139100 : 695.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1391.00	-52.90	-13.00	-39.90	1.34 H	235	47.96	-100.86
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1391.00	-50.79	-13.00	-37.79	2.14 V	159	50.07	-100.86

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n71 Channel Bandwidth: 20MHz	Channel	CH 134600 : 673 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1346.00	-53.03	-13.00	-40.03	1.34 H	227	48.04	-101.07
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1346.00	-51.60	-13.00	-38.60	2.19 V	165	49.47	-101.07

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n71 Channel Bandwidth: 20MHz	Channel	CH 136100 : 680.5 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1361.00	-52.58	-13.00	-39.58	1.14 H	257	48.43	-101.01
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1361.00	-50.25	-13.00	-37.25	2.35 V	154	50.76	-101.01

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

RF Mode	NR n71 Channel Bandwidth: 20MHz	Channel	CH 137600 : 688 MHz
Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1376.00	-52.88	-13.00	-39.88	1.28 H	241	48.06	-100.94
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1376.00	-50.92	-13.00	-37.92	2.14 V	169	50.02	-100.94

Remarks:

- ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
+ 20log(D) – 104.8 – 2.15
- Margin value = ERP – Limit value
- The other ERP levels were very low against the limit.

7.7.15 NR n77 (PC2)

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 630334 : 3455.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6910.02	-53.06	-13.00	-40.06	1.26 H	134	33.63	-86.69
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6910.02	-52.58	-13.00	-39.58	1.42 V	196	34.11	-86.69

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-52.45	-13.00	-39.45	1.06 H	33	33.57	-86.02
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-51.97	-13.00	-38.97	1.42 V	176	34.05	-86.02

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 636332 : 3544.98 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7089.96	-52.08	-13.00	-39.08	1.16 H	175	33.57	-85.65
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7089.96	-51.71	-13.00	-38.71	1.59 V	184	33.94	-85.65

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 631668 : 3475.021 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6950.04	-52.87	-13.00	-39.87	1.24 H	214	33.62	-86.49
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6950.04	-52.43	-13.00	-39.43	1.57 V	189	34.06	-86.49

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-52.60	-13.00	-39.60	1.24 H	105	33.42	-86.02
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-52.00	-13.00	-39.00	1.21 V	245	34.02	-86.02

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 635000 : 3525 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7050.00	-52.01	-13.00	-39.01	1.24 H	159	33.65	-85.66
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7050.00	-51.74	-13.00	-38.74	1.52 V	165	33.92	-85.66

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-52.05	-13.00	-39.05	1.26 H	174	33.97	-86.02
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-51.45	-13.00	-38.45	1.51 V	184	34.57	-86.02

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 647000 : 3705 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7410.00	-52.03	-13.00	-39.03	1.26 H	169	33.37	-85.40
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7410.00	-51.31	-13.00	-38.31	1.43 V	215	34.09	-85.40

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-52.19	-13.00	-39.19	1.24 H	106	33.45	-85.64
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-51.57	-13.00	-38.57	1.57 V	186	34.07	-85.64

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 665000 : 3975 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7950.00	-51.32	-13.00	-38.32	1.14 H	157	33.59	-84.91
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7950.00	-50.80	-13.00	-37.80	1.57 V	176	34.11	-84.91

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 648334 : 3725.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7450.02	-51.81	-13.00	-38.81	1.27 H	156	33.46	-85.27
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7450.02	-51.13	-13.00	-38.13	1.43 V	208	34.14	-85.27

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-52.07	-13.00	-39.07	1.25 H	148	33.57	-85.64
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-51.59	-13.00	-38.59	1.62 V	224	34.05	-85.64

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 663666 : 3954.99 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7909.98	-51.14	-13.00	-38.14	1.24 H	185	33.56	-84.70
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7909.98	-50.63	-13.00	-37.63	1.58 V	225	34.07	-84.70

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 650000 : 3750 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7500.00	-52.00	-13.00	-39.00	1.07 H	35	33.45	-85.45
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7500.00	-51.37	-13.00	-38.37	1.65 V	224	34.08	-85.45

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-51.67	-13.00	-38.67	1.15 H	93	33.97	-85.64
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-51.07	-13.00	-38.07	1.56 V	178	34.57	-85.64

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 662000 : 3930 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	24 °C, 78 % RH
Tested By	vincent chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7860.00	-51.42	-13.00	-38.42	1.43 H	215	33.57	-84.99
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7860.00	-51.05	-13.00	-38.05	1.52 V	193	33.94	-84.99

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

7.7.16 NR n77 (PC3)

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 630334 : 3455.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6910.02	-52.66	-13.00	-39.66	1.42 H	165	47.12	-99.78
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6910.02	-51.27	-13.00	-38.27	2.41 V	106	48.51	-99.78

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-52.15	-13.00	-39.15	1.25 H	198	47.05	-99.20
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-50.77	-13.00	-37.77	2.43 V	99	48.43	-99.20

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 636332 : 3544.98 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7089.96	-51.26	-13.00	-38.26	1.25 H	197	47.05	-98.31
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7089.96	-49.86	-13.00	-36.86	2.34 V	122	48.45	-98.31

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 631668 : 3475.02 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6950.04	-52.50	-13.00	-39.50	1.45 H	193	47.05	-99.55
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	6950.04	-51.12	-13.00	-38.12	2.46 V	114	48.43	-99.55

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-52.11	-13.00	-39.11	1.32 H	221	47.09	-99.20
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-50.47	-13.00	-37.47	2.41 V	112	48.73	-99.20

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 635000 : 3525 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7050.00	-51.47	-13.00	-38.47	1.26 H	165	47.08	-98.55
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7050.00	-50.09	-13.00	-37.09	2.46 V	117	48.46	-98.55

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 633334 : 3500.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-52.04	-13.00	-39.04	1.35 H	204	47.16	-99.20
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7000.02	-50.63	-13.00	-37.63	2.54 V	103	48.57	-99.20

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 647000 : 3705 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7410.00	-51.23	-13.00	-38.23	2.34 H	147	46.43	-97.66
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7410.00	-49.41	-13.00	-36.41	1.25 V	181	48.25	-97.66

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-51.27	-13.00	-38.27	2.32 H	142	46.47	-97.74
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-49.42	-13.00	-36.42	1.27 V	220	48.32	-97.74

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 10MHz	Channel	CH 665000 : 3975 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7950.00	-49.95	-13.00	-36.95	2.35 H	127	46.49	-96.44
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7950.00	-48.15	-13.00	-35.15	1.17 V	165	48.29	-96.44

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 648334 : 3725.01 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7450.02	-50.83	-13.00	-37.83	2.35 H	122	46.48	-97.31
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7450.02	-49.04	-13.00	-36.04	1.14 V	165	48.27	-97.31

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-51.27	-13.00	-38.27	2.39 H	145	46.47	-97.74
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-49.50	-13.00	-36.50	1.06 V	205	48.24	-97.74

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 50MHz	Channel	CH 663666 : 3954.99 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7909.98	-50.22	-13.00	-37.22	2.56 H	144	46.42	-96.64
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7909.98	-48.39	-13.00	-35.39	1.35 V	161	48.25	-96.64

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 650000 : 3750 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7500.00	-50.99	-13.00	-37.99	2.25 H	147	46.48	-97.47
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7500.00	-49.18	-13.00	-36.18	1.14 V	165	48.29	-97.47

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 656000 : 3840 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-51.16	-13.00	-38.16	2.46 H	135	46.58	-97.74
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7680.00	-49.38	-13.00	-36.38	1.23 V	187	48.36	-97.74

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	NR n77 Channel Bandwidth: 100MHz	Channel	CH 662000 : 3930 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 73% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7860.00	-50.45	-13.00	-37.45	2.35 H	124	46.46	-96.91
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7860.00	-48.68	-13.00	-35.68	1.16 V	198	48.23	-96.91

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

7.8 Frequency Stability

Environmental Conditions:	25°C, 60% RH	Tested By:	James Yang
---------------------------	--------------	------------	------------

7.8.1 NR n2 SCS 15 kHz

NR n2 SCS 15 kHz, Channel Bandwidth: 5 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 370500 (1852.5 MHz)		CH 381500 (1907.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	1852.500009	0.0049	1907.500005	0.0026
4.7	1852.499999	-0.0054	1907.499993	-0.0037
4.5	1852.500003	0.0016	1907.500007	0.0037

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 370500 (1852.5 MHz)		CH 381500 (1907.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	1852.499993	-0.0038	1907.499996	-0.0021
-30	1852.500006	0.0032	1907.500006	0.0031
-20	1852.499996	-0.0022	1907.499999	-0.0005
-10	1852.499995	-0.0027	1907.499995	-0.0026
0	1852.500005	0.0027	1907.500004	0.0021
10	1852.500005	0.0027	1907.500005	0.0026
20	1852.500001	0.0005	1907.499996	-0.0021
30	1852.500006	0.0032	1907.500009	0.0047
40	1852.500003	0.0016	1907.500008	0.0042
50	1852.500009	0.0049	1907.500008	0.0042
60	1852.500006	0.0032	1907.500004	0.0021
70	1852.499998	-0.0011	1907.499996	-0.0021
80	1852.500001	0.0005	1907.500002	0.001
85	1852.500008	0.0043	1907.500006	0.0031

NR n2 SCS 15 kHz, Channel Bandwidth: 10 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 371000 (1855 MHz)		CH 381000 (1905 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	1854.999996	-0.0022	1904.999996	-0.0021
4.7	1855.000004	0.0022	1905.000005	0.0026
4.5	1854.999993	-0.0038	1904.999993	-0.0037

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 371000 (1855 MHz)		CH 381000 (1905 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	1855.000006	0.0032	1905.000003	0.0016
-30	1855.000001	0.0005	1905.000001	0.0005
-20	1854.999992	-0.0043	1904.999994	-0.0031
-10	1855.000008	0.0043	1905.000008	0.0042
0	1855.000001	0.0054	1905.000007	0.0037
10	1855.000004	0.0022	1905.000002	0.001
20	1855	0	1905	0
30	1855.000006	0.0032	1905.000001	0.0052
40	1855.000009	0.0049	1905.000005	0.0026
50	1855.000001	0.0005	1905	0
60	1854.999992	-0.0043	1904.999995	-0.0026
70	1855.000006	0.0032	1905.000003	0.0016
80	1855.000005	0.0027	1905.000008	0.0042
85	1854.999992	-0.0043	1904.99999	-0.0052

NR n2 SCS 15 kHz, Channel Bandwidth: 15 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 371500 (1857.5 MHz)		CH 380500 (1902.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	1857.500004	0.0022	1902.500009	0.0047
4.7	1857.500004	0.0022	1902.500004	0.0021
4.5	1857.500001	0.0054	1902.500009	0.0047

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 371500 (1857.5 MHz)		CH 380500 (1902.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	1857.499998	-0.0011	1902.500002	0.0011
-30	1857.500001	0.0005	1902.500005	0.0026
-20	1857.500003	0.0016	1902.500005	0.0026
-10	1857.499994	-0.0032	1902.499996	-0.0021
0	1857.500009	0.0048	1902.500004	0.0021
10	1857.500001	0.0005	1902.500006	0.0032
20	1857.499999	-0.0005	1902.499997	-0.0016
30	1857.499994	-0.0032	1902.499993	-0.0037
40	1857.500005	0.0027	1902.500001	0.0005
50	1857.499999	-0.0005	1902.499996	-0.0021
60	1857.499998	-0.0011	1902.500002	0.0011
70	1857.500005	0.0027	1902.500003	0.0016
80	1857.499997	-0.0016	1902.500002	0.0011
85	1857.499998	-0.0011	1902.499998	-0.0011

NR n2 SCS 15 kHz, Channel Bandwidth: 20 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 372000 (1860 MHz)		CH 380000 (1900 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	1860.000003	0.0016	1900.000002	0.0011
4.7	1859.999991	-0.0048	1899.999994	-0.0032
4.5	1859.999994	-0.0032	1899.999992	-0.0042

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 372000 (1860 MHz)		CH 380000 (1900 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	1860.000005	0.0027	1900.000009	0.0047
-30	1860.000005	0.0027	1900.000003	0.0016
-20	1860.000002	0.0011	1900.000003	0.0016
-10	1860.000007	0.0038	1900.000007	0.0037
0	1860.000007	0.0038	1900.000005	0.0026
10	1860.000002	0.0011	1900.000002	0.0011
20	1859.999993	-0.0038	1899.999996	-0.0021
30	1860.000007	0.0038	1900.000005	0.0026
40	1860.000006	0.0032	1900.000001	0.0053
50	1859.999993	-0.0038	1899.999992	-0.0042
60	1860	0	1900	0
70	1859.999991	-0.0048	1899.999994	-0.0032
80	1860.000001	0.0054	1900.000009	0.0047
85	1860.000009	0.0048	1900.000008	0.0042

7.8.2 NR n5 SCS 15 kHz

NR n5 SCS 15 kHz, Channel Bandwidth: 5 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 165300 (826.5 MHz)		CH 169300 (846.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	826.500005	0.006	846.500003	0.0035
4.7	826.500005	0.006	846.50001	0.0118
4.5	826.500007	0.0085	846.500004	0.0047

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 165300 (826.5 MHz)		CH 169300 (846.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	826.500008	0.0097	846.500006	0.0071
-30	826.49999	-0.0121	846.49999	-0.0118
-20	826.5	0	846.500003	0.0035
-10	826.499992	-0.0097	846.499997	-0.0035
0	826.500006	0.0073	846.500005	0.0059
10	826.499998	-0.0024	846.499993	-0.0083
20	826.499993	-0.0085	846.499993	-0.0083
30	826.500004	0.0048	846.500004	0.0047
40	826.499992	-0.0097	846.499993	-0.0083
50	826.499992	-0.0097	846.499995	-0.0059
60	826.500008	0.0097	846.500004	0.0047
70	826.499998	-0.0024	846.500002	0.0024
80	826.500008	0.0097	846.500005	0.0059
85	826.50001	0.0121	846.500005	0.0059

NR n5 SCS 15 kHz, Channel Bandwidth: 10 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 165800 (829 MHz)		CH 168800 (844 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	829.000008	0.0097	844.000007	0.0083
4.7	829.000008	0.0097	844.000008	0.0095
4.5	829	0	843.999996	-0.0047

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 165800 (829 MHz)		CH 168800 (844 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	829.000008	0.0097	844.000006	0.0071
-30	829.000007	0.0084	844.000009	0.0107
-20	829.000009	0.0109	844.000005	0.0059
-10	829.000006	0.0072	844.000009	0.0107
0	829.000001	0.0012	844.000002	0.0024
10	828.999992	-0.0097	843.999992	-0.0095
20	828.999991	-0.0109	843.99999	-0.0118
30	828.99999	-0.0121	843.99999	-0.0118
40	829.000006	0.0072	844.000001	0.0012
50	829.000006	0.0072	844.000009	0.0107
60	829.000003	0.0036	843.999998	-0.0024
70	829.000009	0.0109	844.000008	0.0095
80	828.999991	-0.0109	843.999994	-0.0071
85	829.000001	0.0012	844.000005	0.0059

NR n5 SCS 15 kHz, Channel Bandwidth: 15 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 166300 (831.5 MHz)		CH 168300 (841.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	831.500008	0.0096	841.500006	0.0071
4.7	831.499997	-0.0036	841.499997	-0.0036
4.5	831.500009	0.0108	841.500001	0.0119

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 166300 (831.5 MHz)		CH 168300 (841.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	831.499993	-0.0084	841.499993	-0.0083
-30	831.499992	-0.0096	841.499996	-0.0048
-20	831.500005	0.006	841.500005	0.0059
-10	831.499993	-0.0084	841.499996	-0.0048
0	831.499991	-0.0108	841.499995	-0.0059
10	831.500004	0.0048	841.500007	0.0083
20	831.499999	-0.0012	841.500003	0.0036
30	831.500003	0.0036	841.500008	0.0095
40	831.499991	-0.0108	841.499999	-0.0119
50	831.500009	0.0108	841.500001	0.0119
60	831.499995	-0.006	841.499992	-0.0095
70	831.500009	0.0108	841.500008	0.0095
80	831.499993	-0.0084	841.499998	-0.0024
85	831.499995	-0.006	841.499995	-0.0059

NR n5 SCS 15 kHz, Channel Bandwidth: 20 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 166800 (834 MHz)		CH 167800 (839 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	833.999992	-0.0096	838.999997	-0.0036
4.7	834.000002	0.0024	838.999998	-0.0024
4.5	834.000001	0.0012	839.000004	0.0048

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 166800 (834 MHz)		CH 167800 (839 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	833.999992	-0.0096	838.999994	-0.0072
-30	833.999991	-0.0108	838.999994	-0.0072
-20	834.000007	0.0084	839.000006	0.0072
-10	833.999993	-0.0084	838.999992	-0.0095
0	833.999996	-0.0048	838.999994	-0.0072
10	834.000004	0.0048	839	0
20	834.000002	0.0024	839.000001	0.0012
30	833.999997	-0.0036	838.999998	-0.0024
40	834.000003	0.0036	839.000007	0.0083
50	833.999997	-0.0036	838.999996	-0.0048
60	834.000001	0.0012	839.000003	0.0036
70	834.000003	0.0036	839	0
80	834	0	839.000004	0.0048
85	833.999995	-0.006	838.999996	-0.0048

7.8.3 NR n7 SCS 15 kHz

NR n7 SCS 15 kHz, Channel Bandwidth: 5 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 500500 (2502.5 MHz)		CH 513500 (2567.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	2502.5	0	2567.499998	-0.0008
4.7	2502.500009	0.0036	2567.500005	0.0019
4.5	2502.499992	-0.0032	2567.499994	-0.0023

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 500500 (2502.5 MHz)		CH 513500 (2567.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	2502.500008	0.0032	2567.500001	0.0039
-30	2502.5	0	2567.500002	0.0008
-20	2502.500004	0.0016	2567.499999	-0.0004
-10	2502.499992	-0.0032	2567.499996	-0.0016
0	2502.499999	-0.0004	2567.500002	0.0008
10	2502.500002	0.0008	2567.5	0
20	2502.500009	0.0036	2567.500004	0.0016
30	2502.499998	-0.0008	2567.500003	0.0012
40	2502.499991	-0.0036	2567.499991	-0.0035
50	2502.499993	-0.0028	2567.499997	-0.0012
60	2502.500003	0.0012	2567.5	0
70	2502.500002	0.0008	2567.500003	0.0012
80	2502.499993	-0.0028	2567.499996	-0.0016
85	2502.499992	-0.0032	2567.499995	-0.0019

NR n7 SCS 15 kHz, Channel Bandwidth: 10 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 501000 (2505 MHz)		CH 513000 (2565 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	2505.000008	0.0032	2565.000007	0.0027
4.7	2505.000008	0.0032	2565.000004	0.0016
4.5	2504.99999	-0.004	2564.999991	-0.0035

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 501000 (2505 MHz)		CH 513000 (2565 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	2504.999993	-0.0028	2564.999994	-0.0023
-30	2505	0	2564.999999	-0.0004
-20	2505.000003	0.0012	2565.000008	0.0031
-10	2504.999992	-0.0032	2564.999992	-0.0031
0	2504.999996	-0.0016	2564.999996	-0.0016
10	2505.000008	0.0032	2565.000008	0.0031
20	2504.999991	-0.0036	2564.99999	-0.0039
30	2505.000001	0.0004	2565.000003	0.0012
40	2505	0	2564.999996	-0.0016
50	2504.999996	-0.0016	2564.999994	-0.0023
60	2504.999995	-0.002	2564.999994	-0.0023
70	2505.000006	0.0024	2565.000001	0.0039
80	2504.999991	-0.0036	2564.999993	-0.0027
85	2505.000008	0.0032	2565.000005	0.0019

NR n7 SCS 15 kHz, Channel Bandwidth: 15 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 501500 (2507.5 MHz)		CH 512500 (2562.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	2507.499995	-0.002	2562.499993	-0.0027
4.7	2507.499993	-0.0028	2562.499994	-0.0023
4.5	2507.500009	0.0036	2562.500007	0.0027

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 501500 (2507.5 MHz)		CH 512500 (2562.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	2507.499993	-0.0028	2562.49999	-0.0039
-30	2507.500002	0.0008	2562.499998	-0.0008
-20	2507.499994	-0.0024	2562.499994	-0.0023
-10	2507.499998	-0.0008	2562.499994	-0.0023
0	2507.499997	-0.0012	2562.5	0
10	2507.500007	0.0028	2562.500006	0.0023
20	2507.5	0	2562.500003	0.0012
30	2507.499996	-0.0016	2562.499998	-0.0008
40	2507.499996	-0.0016	2562.499998	-0.0008
50	2507.499992	-0.0032	2562.499993	-0.0027
60	2507.499992	-0.0032	2562.49999	-0.0039
70	2507.499994	-0.0024	2562.499994	-0.0023
80	2507.499994	-0.0024	2562.499996	-0.0016
85	2507.499997	-0.0012	2562.499998	-0.0008

NR n7 SCS 15 kHz, Channel Bandwidth: 20 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 502000 (2510 MHz)		CH 512000 (2560 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	2510.000003	0.0012	2560.000004	0.0016
4.7	2510.000006	0.0024	2560.000002	0.0008
4.5	2509.999999	-0.0004	2560	0

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 502000 (2510 MHz)		CH 512000 (2560 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	2510.000002	0.0008	2560.000005	0.002
-30	2509.999995	-0.002	2559.999999	-0.0004
-20	2509.999999	-0.0004	2559.999999	-0.0004
-10	2509.999992	-0.0032	2559.999995	-0.002
0	2510.000005	0.002	2560.000005	0.002
10	2509.999993	-0.0028	2559.999995	-0.002
20	2509.999991	-0.0036	2559.999994	-0.0023
30	2510.000001	0.004	2560.000006	0.0023
40	2509.999999	-0.0004	2560.000004	0.0016
50	2510.000009	0.0036	2560.000006	0.0023
60	2509.999991	-0.0036	2559.999993	-0.0027
70	2510.000001	0.004	2560.000006	0.0023
80	2510.000009	0.0036	2560.000008	0.0031
85	2509.999994	-0.0024	2559.999993	-0.0027

7.8.4 NR n41 SCS 30 kHz

NR n41 SCS 30 kHz, Channel Bandwidth: 10 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 500202 (2501.01 MHz)		CH 537000 (2685 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	2501.009999	-0.0004	2684.999995	-0.0019
4.7	2501.009993	-0.0028	2684.999997	-0.0011
4.5	2501.010008	0.0032	2685.000007	0.0026

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 500202 (2501.01 MHz)		CH 537000 (2685 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	2501.010001	0.0004	2685.000004	0.0015
-30	2501.009997	-0.0012	2684.999999	-0.0004
-20	2501.009997	-0.0012	2685	0
-10	2501.009993	-0.0028	2684.999992	-0.0003
0	2501.009993	-0.0028	2684.999991	-0.0034
10	2501.009997	-0.0012	2684.999995	-0.0019
20	2501.010004	0.0016	2685.000003	0.0011
30	2501.010002	0.0008	2685.000004	0.0015
40	2501.010003	0.0012	2685.000007	0.0026
50	2501.009994	-0.0024	2684.999991	-0.0034
60	2501.010003	0.0012	2685.000005	0.0019
70	2501.010007	0.0028	2685.000005	0.0019
80	2501.010009	0.0036	2685.000009	0.0034
85	2501.010006	0.0024	2685.000005	0.0019

NR n41 SCS 30 kHz, Channel Bandwidth: 15 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 500700 (2503.5 MHz)		CH 536496 (2682.48 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	2503.500001	0.0004	2682.480005	0.0019
4.7	2503.499991	-0.0036	2682.479995	-0.0019
4.5	2503.499999	-0.0004	2682.479998	-0.0007

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 500700 (2503.5 MHz)		CH 536496 (2682.48 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	2503.499998	-0.0008	2682.479997	-0.0011
-30	2503.499999	-0.0004	2682.479996	-0.0015
-20	2503.499991	-0.0036	2682.47999	-0.0037
-10	2503.499995	-0.002	2682.48	0
0	2503.499996	-0.0016	2682.479995	-0.0019
10	2503.499998	-0.0008	2682.479996	-0.0015
20	2503.500005	0.002	2682.480003	0.0011
30	2503.500003	0.0012	2682.480001	0.0004
40	2503.499995	-0.002	2682.47999	-0.0037
50	2503.499998	-0.0008	2682.479995	-0.0019
60	2503.499991	-0.0036	2682.479996	-0.0015
70	2503.499994	-0.0024	2682.479991	-0.0034
80	2503.500009	0.0036	2682.480008	0.003
85	2503.499993	-0.0028	2682.479996	-0.0015

NR n41 SCS 30 kHz, Channel Bandwidth: 20 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 501204 (2506.02 MHz)		CH 535998 (2679.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	2506.019992	-0.0032	2679.989995	-0.0019
4.7	2506.020009	0.0036	2679.990008	0.003
4.5	2506.019994	-0.0024	2679.98999	-0.0037

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 501204 (2506.02 MHz)		CH 535998 (2679.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	2506.019991	-0.0036	2679.98999	-0.0037
-30	2506.019997	-0.0012	2679.99	0
-20	2506.019994	-0.0024	2679.989996	-0.0015
-10	2506.020005	0.002	2679.990007	0.0026
0	2506.020008	0.0032	2679.990004	0.0015
10	2506.020004	0.0016	2679.990006	0.0022
20	2506.020008	0.0032	2679.990004	0.0015
30	2506.02001	0.004	2679.99001	0.0037
40	2506.020007	0.0028	2679.990004	0.0015
50	2506.020002	0.0008	2679.990007	0.0026
60	2506.020007	0.0028	2679.990008	0.003
70	2506.019995	-0.002	2679.989994	-0.0022
80	2506.019999	-0.0004	2679.989998	-0.0007
85	2506.02	0	2679.989997	-0.0011

NR n41 SCS 30 kHz, Channel Bandwidth: 40 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 503202 (2516.01 MHz)		CH 534000 (2670 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	2516.009995	-0.002	2669.999997	-0.0011
4.7	2516.010001	0.0004	2670.000001	0.0004
4.5	2516.010004	0.0016	2669.999999	-0.0004

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 503202 (2516.01 MHz)		CH 534000 (2670 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	2516.009996	-0.0016	2669.999998	-0.0007
-30	2516.01	0	2670.000002	0.0007
-20	2516.009993	-0.0028	2669.999995	-0.0019
-10	2516.010003	0.0012	2670.000001	0.0004
0	2516.010003	0.0012	2670.000005	0.0019
10	2516.010008	0.0032	2670.00001	0.0037
20	2516.009996	-0.0016	2669.999996	-0.0015
30	2516.01	0	2670	0
40	2516.010001	0.0004	2669.999996	-0.0015
50	2516.009993	-0.0028	2669.999991	-0.0034
60	2516.010007	0.0028	2670.000003	0.0011
70	2516.009992	-0.0032	2669.999991	-0.0034
80	2516.009999	-0.0004	2669.999999	-0.0004
85	2516.009997	-0.0012	2670	0

NR n41 SCS 30 kHz, Channel Bandwidth: 50 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 504204 (2521.02 MHz)		CH 532998 (2664.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	2521.019993	-0.0028	2664.989998	-0.0008
4.7	2521.020004	0.0016	2664.990002	0.0008
4.5	2521.019998	-0.0008	2664.990001	0.0004

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 504204 (2521.02 MHz)		CH 532998 (2664.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	2521.019997	-0.0012	2664.989996	-0.0015
-30	2521.020004	0.0016	2664.990005	0.0019
-20	2521.019996	-0.0016	2664.989996	-0.0015
-10	2521.019991	-0.0036	2664.989992	-0.003
0	2521.020005	0.002	2664.99001	0.0038
10	2521.02	0	2664.990004	0.0015
20	2521.02	0	2664.990005	0.0019
30	2521.019996	-0.0016	2664.989999	-0.0004
40	2521.019996	-0.0016	2664.989996	-0.0015
50	2521.019998	-0.0008	2664.990001	0.0004
60	2521.019999	-0.0004	2664.990003	0.0011
70	2521.020001	0.0004	2664.990004	0.0015
80	2521.020007	0.0028	2664.990009	0.0034
85	2521.020008	0.0032	2664.990005	0.0019

NR n41 SCS 30 kHz, Channel Bandwidth: 60 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 505200 (2526 MHz)		CH 531996 (2659.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	2526	0	2659.980001	0.0004
4.7	2526.000003	0.0012	2659.980007	0.0026
4.5	2525.999996	-0.0016	2659.979993	-0.0026

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 505200 (2526 MHz)		CH 531996 (2659.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	2526.000005	0.002	2659.980008	0.003
-30	2525.999999	-0.0004	2659.98	0
-20	2526.000009	0.0036	2659.980005	0.0019
-10	2526.000008	0.0032	2659.980008	0.003
0	2525.999998	-0.0008	2659.979997	-0.0011
10	2525.999997	-0.0012	2659.979997	-0.0011
20	2525.999994	-0.0024	2659.979992	-0.003
30	2525.999999	-0.0004	2659.980002	0.0008
40	2525.999996	-0.0016	2659.979994	-0.0023
50	2526.000002	0.0008	2659.980001	0.0004
60	2525.999999	-0.0004	2659.979997	-0.0011
70	2526.000005	0.002	2659.980003	0.0011
80	2526.000008	0.0032	2659.980008	0.003
85	2526.000004	0.0016	2659.980004	0.0015

NR n41 SCS 30 kHz, Channel Bandwidth: 70 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 506202 (2531.01 MHz)		CH 531000 (2655 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	2531.009997	-0.0012	2654.999998	-0.0008
4.7	2531.010006	0.0024	2655.000006	0.0023
4.5	2531.009999	-0.0004	2654.999996	-0.0015

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 506202 (2531.01 MHz)		CH 531000 (2655 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	2531.009994	-0.0024	2654.999996	-0.0015
-30	2531.010008	0.0032	2655.000004	0.0015
-20	2531.010004	0.0016	2655	0
-10	2531.010003	0.0012	2654.999999	-0.0004
0	2531.009999	-0.0004	2655.000001	0.0004
10	2531.01	0	2654.999999	-0.0004
20	2531.009996	-0.0016	2654.999998	-0.0008
30	2531.010002	0.0008	2654.999997	-0.0011
40	2531.010005	0.002	2655.000009	0.0034
50	2531.009991	-0.0036	2654.999996	-0.0015
60	2531.009994	-0.0024	2654.999994	-0.0023
70	2531.010001	0.0004	2655.000006	0.0023
80	2531.01001	0.004	2655.000007	0.0026
85	2531.010002	0.0008	2655	0

NR n41 SCS 30 kHz, Channel Bandwidth: 80 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 507204 (2536.02 MHz)		CH 529998 (2649.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	2536.020006	0.0024	2649.990002	0.0008
4.7	2536.020005	0.002	2649.990009	0.0034
4.5	2536.019995	-0.002	2649.989994	-0.0023

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 507204 (2536.02 MHz)		CH 529998 (2649.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	2536.019994	-0.0024	2649.989997	-0.0011
-30	2536.020004	0.0016	2649.990006	0.0023
-20	2536.020004	0.0016	2649.990007	0.0026
-10	2536.02	0	2649.989999	-0.0004
0	2536.019995	-0.002	2649.989998	-0.0008
10	2536.019997	-0.0012	2649.989993	-0.0026
20	2536.019997	-0.0012	2649.989996	-0.0015
30	2536.02	0	2649.989998	-0.0008
40	2536.020006	0.0024	2649.990005	0.0019
50	2536.020009	0.0035	2649.990005	0.0019
60	2536.019997	-0.0012	2649.989999	-0.0004
70	2536.020001	0.0004	2649.99	0
80	2536.020003	0.0012	2649.990006	0.0023
85	2536.02	0	2649.99	0

NR n41 SCS 30 kHz, Channel Bandwidth: 90 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 508200 (2541 MHz)		CH 528996 (2644.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	2540.999995	-0.002	2644.97999	-0.0038
4.7	2541.000001	0.0004	2644.980006	0.0023
4.5	2540.999994	-0.0024	2644.979994	-0.0023

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 508200 (2541 MHz)		CH 528996 (2644.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	2540.999992	-0.0031	2644.979992	-0.003
-30	2540.999994	-0.0024	2644.979992	-0.003
-20	2541.000005	0.002	2644.980005	0.0019
-10	2541	0	2644.979999	-0.0004
0	2541.000004	0.0016	2644.980006	0.0023
10	2540.999992	-0.0031	2644.979992	-0.003
20	2541.000001	0.0039	2644.980006	0.0023
30	2540.999991	-0.0035	2644.979992	-0.003
40	2541.000002	0.0008	2644.979997	-0.0011
50	2540.999991	-0.0035	2644.979996	-0.0015
60	2540.999996	-0.0016	2644.98	0
70	2540.999994	-0.0024	2644.979994	-0.0023
80	2541.000008	0.0031	2644.980006	0.0023
85	2540.999994	-0.0024	2644.979999	-0.0004

NR n41 SCS 30 kHz, Channel Bandwidth: 100 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 509202 (2546.01 MHz)		CH 528000 (2640 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	2546.010002	0.0008	2640.000005	0.0019
4.7	2546.010005	0.002	2640.000007	0.0027
4.5	2546.010007	0.0027	2640.000007	0.0027

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 509202 (2546.01 MHz)		CH 528000 (2640 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	2546.009998	-0.0008	2639.999999	-0.0004
-30	2546.009993	-0.0027	2639.999992	-0.003
-20	2546.009997	-0.0012	2639.999999	-0.0004
-10	2546.010005	0.002	2640.000008	0.003
0	2546.010003	0.0012	2639.999999	-0.0004
10	2546.009998	-0.0008	2639.999996	-0.0015
20	2546.010009	0.0035	2640.00001	0.0038
30	2546.010003	0.0012	2639.999999	-0.0004
40	2546.010002	0.0008	2640.000004	0.0015
50	2546.010009	0.0035	2640.000006	0.0023
60	2546.009996	-0.0016	2639.999997	-0.0011
70	2546.009996	-0.0016	2639.999992	-0.003
80	2546.010002	0.0008	2639.999997	-0.0011
85	2546.01001	0.0039	2640.00001	0.0038

7.8.5 NR n66 SCS 15 kHz

NR n66 SCS 15 kHz, Channel Bandwidth: 5 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 342500 (1712.5 MHz)		CH 355500 (1777.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	1712.499993	-0.0041	1777.499993	-0.0039
4.7	1712.499995	-0.0029	1777.499993	-0.0039
4.5	1712.500006	0.0035	1777.500004	0.0023

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 342500 (1712.5 MHz)		CH 355500 (1777.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	1712.500001	0.0006	1777.5	0
-30	1712.500005	0.0029	1777.500007	0.0039
-20	1712.499993	-0.0041	1777.499994	-0.0034
-10	1712.499991	-0.0053	1777.499995	-0.0028
0	1712.500006	0.0035	1777.500001	0.0006
10	1712.499997	-0.0018	1777.499998	-0.0011
20	1712.499991	-0.0053	1777.499994	-0.0034
30	1712.49999	-0.0058	1777.49999	-0.0056
40	1712.499997	-0.0018	1777.500001	0.0006
50	1712.500009	0.0053	1777.50001	0.0056
60	1712.500009	0.0053	1777.500005	0.0028
70	1712.499995	-0.0029	1777.49999	-0.0056
80	1712.500003	0.0018	1777.500006	0.0034
85	1712.500006	0.0035	1777.500009	0.0051

NR n66 SCS 15 kHz, Channel Bandwidth: 10 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 343000 (1715 MHz)		CH 355000 (1775 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	1715.000008	0.0047	1775.000006	0.0034
4.7	1714.999999	-0.0006	1775	0
4.5	1714.999994	-0.0035	1774.999993	-0.0039

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 343000 (1715 MHz)		CH 355000 (1775 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	1714.999998	-0.0012	1775	0
-30	1715.000006	0.0035	1775.000001	0.0056
-20	1715.000004	0.0023	1775.000001	0.0006
-10	1714.999999	-0.0006	1774.999997	-0.0017
0	1714.999999	-0.0058	1774.999992	-0.0045
10	1715.000004	0.0023	1775	0
20	1715.000003	0.0017	1775.000005	0.0028
30	1714.999999	-0.0058	1774.999995	-0.0028
40	1715.000002	0.0012	1775.000006	0.0034
50	1714.999997	-0.0017	1774.999996	-0.0023
60	1715.000008	0.0047	1775.000004	0.0023
70	1714.999996	-0.0023	1774.999999	-0.0006
80	1714.999994	-0.0035	1774.999997	-0.0017
85	1714.999996	-0.0023	1774.999997	-0.0017

NR n66 SCS 15 kHz, Channel Bandwidth: 15 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 343500 (1717.5 MHz)		CH 354500 (1772.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	1717.499992	-0.0047	1772.499993	-0.0039
4.7	1717.500007	0.0041	1772.500009	0.0051
4.5	1717.499992	-0.0047	1772.499995	-0.0028

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 343500 (1717.5 MHz)		CH 354500 (1772.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	1717.499994	-0.0035	1772.499998	-0.0011
-30	1717.499992	-0.0047	1772.499994	-0.0034
-20	1717.499997	-0.0017	1772.499999	-0.0006
-10	1717.500009	0.0052	1772.500005	0.0028
0	1717.499993	-0.0041	1772.499991	-0.0051
10	1717.500006	0.0035	1772.500008	0.0045
20	1717.500001	0.0058	1772.500005	0.0028
30	1717.500003	0.0017	1772.500006	0.0034
40	1717.499993	-0.0041	1772.499991	-0.0051
50	1717.499992	-0.0047	1772.499994	-0.0034
60	1717.500002	0.0012	1772.500003	0.0017
70	1717.500002	0.0012	1772.500004	0.0023
80	1717.499998	-0.0012	1772.499998	-0.0011
85	1717.500003	0.0017	1772.500008	0.0045

NR n66 SCS 15 kHz, Channel Bandwidth: 20 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 344000 (1720 MHz)		CH 354000 (1770 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	1720	0	1770	0
4.7	1720.000006	0.0035	1770.000007	0.004
4.5	1720.000003	0.0017	1770.000003	0.0017

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 344000 (1720 MHz)		CH 354000 (1770 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	1720.000009	0.0052	1770.000009	0.0051
-30	1719.999992	-0.0047	1769.999993	-0.004
-20	1720	0	1770.000004	0.0023
-10	1720.000004	0.0023	1770.000004	0.0023
0	1720.000006	0.0035	1770.000001	0.0006
10	1720.000003	0.0017	1770.000005	0.0028
20	1719.999998	-0.0012	1769.999997	-0.0017
30	1720.000009	0.0052	1770.000005	0.0028
40	1719.999997	-0.0017	1770.000001	0.0006
50	1719.999995	-0.0029	1769.999999	-0.0006
60	1719.999997	-0.0017	1769.999999	-0.0006
70	1720.000008	0.0047	1770.000001	0.0056
80	1720.000003	0.0017	1770.000003	0.0017
85	1720.000007	0.0041	1770.000001	0.0056

NR n66 SCS 15 kHz, Channel Bandwidth: 40 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 346000 (1730 MHz)		CH 352000 (1760 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	1729.999995	-0.0029	1759.999999	-0.0006
4.7	1729.999993	-0.004	1759.999991	-0.0051
4.5	1729.999994	-0.0035	1759.999993	-0.004

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 346000 (1730 MHz)		CH 352000 (1760 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	1730.000005	0.0029	1760.000007	0.004
-30	1729.999993	-0.004	1759.99999	-0.0057
-20	1729.999997	-0.0017	1760	0
-10	1729.999999	-0.0006	1759.999994	-0.0034
0	1729.999997	-0.0017	1760.000002	0.0011
10	1729.999992	-0.0046	1759.999991	-0.0051
20	1730.000002	0.0012	1760.000001	0.0006
30	1729.99999	-0.0058	1759.999994	-0.0034
40	1730.000009	0.0052	1760.000009	0.0051
50	1730.000001	0.0006	1760.000003	0.0017
60	1729.999996	-0.0023	1759.999999	-0.0006
70	1730	0	1760.000003	0.0017
80	1730.000008	0.0046	1760.000004	0.0023
85	1729.999996	-0.0023	1759.999999	-0.0006

7.8.6 NR n71 SCS 15 kHz

NR n71 SCS 15 kHz, Channel Bandwidth: 5 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 133100 (665.5 MHz)		CH 139100 (695.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	665.499999	-0.0015	695.499995	-0.0072
4.7	665.499991	-0.0135	695.499994	-0.0086
4.5	665.499994	-0.009	695.49999	-0.0144

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 133100 (665.5 MHz)		CH 139100 (695.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	665.499992	-0.012	695.49999	-0.0144
-30	665.50001	0.015	695.500008	0.0115
-20	665.50001	0.015	695.500009	0.0129
-10	665.500003	0.0045	695.500007	0.0101
0	665.500002	0.003	695.500006	0.0086
10	665.5	0	695.500001	0.0014
20	665.499992	-0.012	695.499996	-0.0058
30	665.500006	0.009	695.500008	0.0115
40	665.499991	-0.0135	695.499996	-0.0058
50	665.499998	-0.003	695.500001	0.0014
60	665.499996	-0.006	695.499995	-0.0072
70	665.499997	-0.0045	695.499998	-0.0029
80	665.500003	0.0045	695.500007	0.0101
85	665.499997	-0.0045	695.499996	-0.0058

NR n71 SCS 15 kHz, Channel Bandwidth: 10 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 133600 (668 MHz)		CH 138600 (693 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	668.000001	0.0015	693.000003	0.0043
4.7	668.000003	0.0045	693	0
4.5	668	0	693.000004	0.0058

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 133600 (668 MHz)		CH 138600 (693 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	667.999995	-0.0075	692.999996	-0.0058
-30	668	0	692.999998	-0.0029
-20	668.000008	0.012	693.000004	0.0058
-10	667.999992	-0.012	692.999995	-0.0072
0	668.000008	0.012	693.000001	0.0144
10	668.000008	0.012	693.000008	0.0115
20	668.000004	0.006	693.000006	0.0087
30	667.999999	-0.015	692.999992	-0.0115
40	668.000009	0.0135	693.000009	0.013
50	668.000005	0.0075	693.000006	0.0087
60	667.999996	-0.006	693	0
70	668.000001	0.015	693.000009	0.013
80	668.000009	0.0135	693.000004	0.0058
85	667.999996	-0.006	692.999996	-0.0058

NR n71 SCS 15 kHz, Channel Bandwidth: 15 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 134100 (670.5 MHz)		CH 138100 (690.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	670.500008	0.0119	690.500005	0.0072
4.7	670.500008	0.0119	690.500009	0.013
4.5	670.499993	-0.0104	690.499994	-0.0087

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 134100 (670.5 MHz)		CH 138100 (690.5 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	670.500002	0.003	690.499998	-0.0029
-30	670.500005	0.0075	690.500001	0.0014
-20	670.500006	0.0089	690.500001	0.0145
-10	670.499998	-0.003	690.500002	0.0029
0	670.499992	-0.0119	690.499992	-0.0116
10	670.499996	-0.006	690.499998	-0.0029
20	670.499993	-0.0104	690.499994	-0.0087
30	670.5	0	690.499999	-0.0014
40	670.500003	0.0045	690.500008	0.0116
50	670.499995	-0.0075	690.499997	-0.0043
60	670.499998	-0.003	690.499999	-0.0014
70	670.499991	-0.0134	690.499996	-0.0058
80	670.5	0	690.500001	0.0014
85	670.499994	-0.0089	690.499995	-0.0072

NR n71 SCS 15 kHz, Channel Bandwidth: 20 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 134600 (673 MHz)		CH 137600 (688 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	673.000003	0.0045	688.000006	0.0087
4.7	673.000003	0.0045	688	0
4.5	672.999998	-0.003	687.999997	-0.0044

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 134600 (673 MHz)		CH 137600 (688 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	672.999998	-0.003	687.999998	-0.0029
-30	673.000009	0.0134	688.000005	0.0073
-20	672.999994	-0.0089	687.999997	-0.0044
-10	672.999991	-0.0134	687.999999	-0.0145
0	672.999998	-0.003	687.999998	-0.0029
10	672.999996	-0.0059	687.999999	-0.0015
20	672.999991	-0.0134	687.999995	-0.0073
30	673.000002	0.003	688	0
40	672.999991	-0.0134	687.999999	-0.0145
50	673.000001	0.0149	688.000006	0.0087
60	672.999997	-0.0045	687.999995	-0.0073
70	673.000009	0.0134	688.000006	0.0087
80	673.000004	0.0059	688.000006	0.0087
85	672.999994	-0.0089	687.999993	-0.0102

7.8.7 NR n77 SCS 30 kHz (3.45 GHz ~ 3.55 GHz)

NR n77 SCS 30 kHz (3.45 GHz ~ 3.55 GHz), Channel Bandwidth: 10 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 630334 (3455.01 MHz)		CH 636332 (3544.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3455.010003	0.0009	3544.98	0
4.7	3455.010001	0.0003	3544.979997	-0.0008
4.5	3455.010002	0.0006	3544.980007	0.002

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 630334 (3455.01 MHz)		CH 636332 (3544.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3455.009999	-0.0003	3544.980004	0.0011
-30	3455.009993	-0.002	3544.97999	-0.0028
-20	3455.009992	-0.0023	3544.979992	-0.0023
-10	3455.009994	-0.0017	3544.979993	-0.002
0	3455.010001	0.0003	3544.980001	0.0003
10	3455.010004	0.0012	3544.979999	-0.0003
20	3455.009996	-0.0012	3544.979995	-0.0014
30	3455.009999	-0.0003	3544.98	0
40	3455.009992	-0.0023	3544.979996	-0.0011
50	3455.010002	0.0006	3544.979999	-0.0003
60	3455.009997	-0.0009	3544.979999	-0.0003
70	3455.010008	0.0023	3544.98001	0.0028
80	3455.009996	-0.0012	3544.979993	-0.002
85	3455.009994	-0.0017	3544.979991	-0.0025

NR n77 SCS 30 kHz (3.45 GHz ~ 3.55 GHz), Channel Bandwidth: 15 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 630500 (3457.5 MHz)		CH 636166 (3542.49 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3457.499995	-0.0014	3542.49	0
4.7	3457.499992	-0.0023	3542.489997	-0.0008
4.5	3457.499992	-0.0023	3542.48999	-0.0028

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 630500 (3457.5 MHz)		CH 636166 (3542.49 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3457.499995	-0.0014	3542.489991	-0.0025
-30	3457.500001	0.0003	3542.489997	-0.0008
-20	3457.500004	0.0012	3542.490006	0.0017
-10	3457.499996	-0.0012	3542.489992	-0.0023
0	3457.5	0	3542.489998	-0.0006
10	3457.499993	-0.002	3542.489992	-0.0023
20	3457.500002	0.0006	3542.49	0
30	3457.499995	-0.0014	3542.48999	-0.0028
40	3457.49999	-0.0029	3542.48999	-0.0028
50	3457.500004	0.0012	3542.490008	0.0023
60	3457.5	0	3542.490004	0.0011
70	3457.499999	-0.0003	3542.490003	0.0008
80	3457.499995	-0.0014	3542.489995	-0.0014
85	3457.499995	-0.0014	3542.489992	-0.0023

NR n77 SCS 30 kHz (3.45 GHz ~ 3.55 GHz), Channel Bandwidth: 20 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 630668 (3460.02 MHz)		CH 636000 (3540 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3460.019992	-0.0023	3539.999992	-0.0023
4.7	3460.019998	-0.0006	3540.000001	0.0003
4.5	3460.020001	0.0003	3540.000003	0.0008

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 630668 (3460.02 MHz)		CH 636000 (3540 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3460.020007	0.002	3540.00001	0.0028
-30	3460.02001	0.0029	3540.000008	0.0023
-20	3460.019997	-0.0009	3540	0
-10	3460.020006	0.0017	3540.000006	0.0017
0	3460.019991	-0.0026	3539.999992	-0.0023
10	3460.020008	0.0023	3540.000008	0.0023
20	3460.019998	-0.0006	3540.000001	0.0003
30	3460.020009	0.0026	3540.00001	0.0028
40	3460.019995	-0.0014	3539.999993	-0.002
50	3460.019994	-0.0017	3539.999992	-0.0023
60	3460.019991	-0.0026	3539.999995	-0.0014
70	3460.019991	-0.0026	3539.999992	-0.0023
80	3460.019993	-0.002	3539.999997	-0.0008
85	3460.019993	-0.002	3539.99999	-0.0028

NR n77 SCS 30 kHz (3.45 GHz ~ 3.55 GHz), Channel Bandwidth: 30 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 631000 (3465 MHz)		CH 635666 (3534.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3464.999996	-0.0012	3534.989992	-0.0023
4.7	3465.000002	0.0006	3534.989999	-0.0003
4.5	3465.000005	0.0014	3534.990005	0.0014

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 631000 (3465 MHz)		CH 635666 (3534.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3464.999997	-0.0009	3534.989993	-0.002
-30	3465.000001	0.0003	3534.99	0
-20	3464.999994	-0.0017	3534.989993	-0.002
-10	3465.000003	0.0009	3534.990001	0.0003
0	3464.999996	-0.0012	3534.989992	-0.0023
10	3465.000006	0.0017	3534.990004	0.0011
20	3465.000005	0.0014	3534.99001	0.0028
30	3464.999995	-0.0014	3534.989999	-0.0003
40	3464.999995	-0.0014	3534.99	0
50	3464.999991	-0.0026	3534.989992	-0.0023
60	3464.999996	-0.0012	3534.989994	-0.0017
70	3464.999993	-0.002	3534.989993	-0.002
80	3464.999999	-0.0003	3534.990003	0.0008
85	3464.999996	-0.0012	3534.989999	-0.0003

NR n77 SCS 30 kHz (3.45 GHz ~ 3.55 GHz), Channel Bandwidth: 40 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 631334 (3470.01 MHz)		CH 635332 (3529.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3470.010008	0.0023	3529.980008	0.0023
4.7	3470.009992	-0.0023	3529.979991	-0.0025
4.5	3470.010006	0.0017	3529.980009	0.0025

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 631334 (3470.01 MHz)		CH 635332 (3529.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3470.00999	-0.0029	3529.979991	-0.0025
-30	3470.010009	0.0026	3529.980007	0.002
-20	3470.010004	0.0012	3529.98	0
-10	3470.01001	0.0029	3529.980008	0.0023
0	3470.010001	0.0003	3529.980002	0.0006
10	3470.010001	0.0003	3529.980002	0.0006
20	3470.009997	-0.0009	3529.979994	-0.0017
30	3470.009997	-0.0009	3529.980001	0.0003
40	3470.009994	-0.0017	3529.979991	-0.0025
50	3470.01	0	3529.98	0
60	3470.010002	0.0006	3529.980001	0.0003
70	3470.010008	0.0023	3529.980005	0.0014
80	3470.009991	-0.0026	3529.979994	-0.0017
85	3470.009998	-0.0006	3529.979998	-0.0006

NR n77 SCS 30 kHz (3.45 GHz ~ 3.55 GHz), Channel Bandwidth: 50 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 631668 (3475.02 MHz)		CH 635000 (3525 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3475.020007	0.002	3525.000006	0.0017
4.7	3475.02	0	3525.000003	0.0009
4.5	3475.020009	0.0026	3525.000008	0.0023

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 631668 (3475.02 MHz)		CH 635000 (3525 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3475.020002	0.0006	3525.000001	0.0003
-30	3475.019992	-0.0023	3524.999993	-0.002
-20	3475.019991	-0.0026	3524.999995	-0.0014
-10	3475.020001	0.0003	3524.999999	-0.0003
0	3475.019997	-0.0009	3525.000001	0.0003
10	3475.019998	-0.0006	3524.999999	-0.0003
20	3475.019999	-0.0003	3525.000002	0.0006
30	3475.020005	0.0014	3525.000002	0.0006
40	3475.020003	0.0009	3524.999999	-0.0003
50	3475.020009	0.0026	3525.000006	0.0017
60	3475.019999	-0.0003	3525.000001	0.0003
70	3475.019992	-0.0023	3524.999996	-0.0011
80	3475.019991	-0.0026	3524.999991	-0.0026
85	3475.019998	-0.0006	3525.000003	0.0009

NR n77 SCS 30 kHz (3.45 GHz ~ 3.55 GHz), Channel Bandwidth: 60 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 632000 (3480 MHz)		CH 634666 (3519.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3480.000005	0.0014	3519.990004	0.0011
4.7	3480.000005	0.0014	3519.990009	0.0026
4.5	3479.999991	-0.0026	3519.989994	-0.0017

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 632000 (3480 MHz)		CH 634666 (3519.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3479.999999	-0.0003	3519.99	0
-30	3480.000002	0.0006	3519.990003	0.0009
-20	3480.000004	0.0011	3519.99	0
-10	3479.999995	-0.0014	3519.989994	-0.0017
0	3480.000001	0.0029	3519.990007	0.002
10	3479.999994	-0.0017	3519.989994	-0.0017
20	3480.000002	0.0006	3519.990004	0.0011
30	3480	0	3519.990005	0.0014
40	3479.999995	-0.0014	3519.989991	-0.0026
50	3480.000006	0.0017	3519.990006	0.0017
60	3480	0	3519.990004	0.0011
70	3479.999999	-0.0003	3519.989999	-0.0003
80	3480.000006	0.0017	3519.990008	0.0023
85	3479.999998	-0.0006	3519.99	0

NR n77 SCS 30 kHz (3.45 GHz ~ 3.55 GHz), Channel Bandwidth: 70 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 632334 (3485.01 MHz)		CH 634332 (3514.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3485.009993	-0.002	3514.97999	-0.0028
4.7	3485.010004	0.0011	3514.980008	0.0023
4.5	3485.009992	-0.0023	3514.979993	-0.002

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 632334 (3485.01 MHz)		CH 634332 (3514.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3485.00999	-0.0029	3514.979991	-0.0026
-30	3485.009992	-0.0023	3514.979991	-0.0026
-20	3485.010008	0.0023	3514.980007	0.002
-10	3485.010003	0.0009	3514.980003	0.0009
0	3485.010008	0.0023	3514.980009	0.0026
10	3485.01001	0.0029	3514.980005	0.0014
20	3485.010008	0.0023	3514.980004	0.0011
30	3485.01	0	3514.980003	0.0009
40	3485.010008	0.0023	3514.98001	0.0028
50	3485.010001	0.0003	3514.980001	0.0003
60	3485.009991	-0.0026	3514.979991	-0.0026
70	3485.009994	-0.0017	3514.979992	-0.0023
80	3485.009993	-0.002	3514.979996	-0.0011
85	3485.010003	0.0009	3514.980005	0.0014

NR n77 SCS 30 kHz (3.45 GHz ~ 3.55 GHz), Channel Bandwidth: 80 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 632668 (3490.02 MHz)		CH 634000 (3510 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3490.020003	0.0009	3510.000005	0.0014
4.7	3490.019999	-0.0003	3510	0
4.5	3490.020004	0.0011	3509.999999	-0.0003

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 632668 (3490.02 MHz)		CH 634000 (3510 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3490.020001	0.0003	3510.000001	0.0003
-30	3490.020007	0.002	3510.000009	0.0026
-20	3490.020004	0.0011	3510.000004	0.0011
-10	3490.01999	-0.0029	3509.999991	-0.0026
0	3490.019993	-0.002	3509.99999	-0.0028
10	3490.020001	0.0003	3510.000006	0.0017
20	3490.020005	0.0014	3510.000006	0.0017
30	3490.020007	0.002	3510.000003	0.0009
40	3490.020005	0.0014	3510.000007	0.002
50	3490.02	0	3510	0
60	3490.01999	-0.0029	3509.999994	-0.0017
70	3490.020009	0.0026	3510.000007	0.002
80	3490.020009	0.0026	3510.000008	0.0023
85	3490.020005	0.0014	3510.00001	0.0028

NR n77 SCS 30 kHz (3.45 GHz ~ 3.55 GHz), Channel Bandwidth: 90 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 633000 (3495 MHz)		CH 633666 (3504.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3495.000005	0.0014	3504.990007	0.002
4.7	3495.000002	0.0006	3504.990006	0.0017
4.5	3495.000007	0.002	3504.990005	0.0014

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 633000 (3495 MHz)		CH 633666 (3504.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3495.00001	0.0029	3504.990007	0.002
-30	3494.999996	-0.0011	3504.989993	-0.002
-20	3494.999999	-0.0003	3504.990002	0.0006
-10	3495.000006	0.0017	3504.990003	0.0009
0	3494.999995	-0.0014	3504.989994	-0.0017
10	3495.000008	0.0023	3504.990008	0.0023
20	3494.999992	-0.0023	3504.989991	-0.0026
30	3495.000008	0.0023	3504.990005	0.0014
40	3495	0	3504.989998	-0.0006
50	3495.000009	0.0026	3504.990005	0.0014
60	3495.000006	0.0017	3504.990001	0.0029
70	3495.000002	0.0006	3504.990002	0.0006
80	3495.000003	0.0009	3504.99	0
85	3495.000005	0.0014	3504.990004	0.0011

NR n77 SCS 30 kHz (3.45 GHz ~ 3.55 GHz), Channel Bandwidth: 100 MHz

Frequency Stability Versus Voltage		
Voltage (Vdc)	CH 633334 (3500.01 MHz)	
	Frequency (MHz)	Frequency Error (ppm)
4.9	3500.010005	0.0014
4.7	3500.010007	0.002
4.5	3500.010008	0.0023

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature		
Temperature (°C)	CH 633334 (3500.01 MHz)	
	Frequency (MHz)	Frequency Error (ppm)
-40	3500.010004	0.0011
-30	3500.009994	-0.0017
-20	3500.010005	0.0014
-10	3500.009997	-0.0009
0	3500.009991	-0.0026
10	3500.010009	0.0026
20	3500.010005	0.0014
30	3500.009993	-0.002
40	3500.010009	0.0026
50	3500.010005	0.0014
60	3500.009991	-0.0026
70	3500.009995	-0.0014
80	3500.010008	0.0023
85	3500.010008	0.0023

7.8.8 NR n77 SCS 30 kHz (3.7 GHz ~ 3.98 GHz)

NR n77 SCS 30 kHz (3.7 GHz ~ 3.98 GHz), Channel Bandwidth: 10 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 647000 (3705 MHz)		CH 665000 (3975 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3705.000003	0.0008	3975.000002	0.0005
4.7	3705.000008	0.0022	3975.000006	0.0015
4.5	3705.000002	0.0005	3975.000006	0.0015

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 647000 (3705 MHz)		CH 665000 (3975 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3705	0	3975.000003	0.0008
-30	3705.000001	0.0003	3975.000002	0.0005
-20	3704.999993	-0.0019	3974.999997	-0.0008
-10	3705.000007	0.0019	3975.000001	0.0025
0	3704.999992	-0.0022	3974.999991	-0.0023
10	3705.000008	0.0022	3975.000007	0.0018
20	3705	0	3974.999999	-0.0003
30	3705.000003	0.0008	3975.000005	0.0013
40	3705.000001	0.0027	3975.000009	0.0023
50	3704.999999	-0.0003	3975	0
60	3705.000006	0.0016	3975.000008	0.002
70	3704.999995	-0.0013	3974.999996	-0.001
80	3705.000009	0.0024	3975.000007	0.0018
85	3705.000004	0.0011	3975.000005	0.0013

NR n77 SCS 30 kHz (3.7 GHz ~ 3.98 GHz), Channel Bandwidth: 15 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 647168 (3707.52 MHz)		CH 664832 (3972.48 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3707.519997	-0.0008	3972.480002	0.0005
4.7	3707.519993	-0.0019	3972.47999	-0.0025
4.5	3707.519993	-0.0019	3972.47999	-0.0025

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 647168 (3707.52 MHz)		CH 664832 (3972.48 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3707.520009	0.0024	3972.480008	0.002
-30	3707.520001	0.0003	3972.480004	0.001
-20	3707.520005	0.0013	3972.480001	0.0003
-10	3707.519993	-0.0019	3972.47999	-0.0025
0	3707.519991	-0.0024	3972.479991	-0.0023
10	3707.520006	0.0016	3972.480008	0.002
20	3707.519997	-0.0008	3972.479992	-0.002
30	3707.519991	-0.0024	3972.479991	-0.0023
40	3707.51999	-0.0027	3972.479994	-0.0015
50	3707.520001	0.0003	3972.480006	0.0015
60	3707.519994	-0.0016	3972.479999	-0.0003
70	3707.520004	0.0011	3972.480001	0.0003
80	3707.520003	0.0008	3972.480004	0.001
85	3707.519994	-0.0016	3972.479997	-0.0008

NR n77 SCS 30 kHz (3.7 GHz ~ 3.98 GHz), Channel Bandwidth: 20 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 647334 (3710.01 MHz)		CH 664666 (3969.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3710.009993	-0.0019	3969.989997	-0.0008
4.7	3710.010009	0.0024	3969.990009	0.0023
4.5	3710.010009	0.0024	3969.990006	0.0015

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 647334 (3710.01 MHz)		CH 664666 (3969.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3710.009991	-0.0024	3969.98999	-0.0025
-30	3710.009997	-0.0008	3969.99	0
-20	3710.009994	-0.0016	3969.989996	-0.001
-10	3710.010001	0.0003	3969.990001	0.0003
0	3710.010004	0.0011	3969.989999	-0.0003
10	3710.009996	-0.0011	3969.989998	-0.0005
20	3710.01	0	3969.990002	0.0005
30	3710.009992	-0.0022	3969.989995	-0.0013
40	3710.010002	0.0005	3969.989999	-0.0003
50	3710.009997	-0.0008	3969.989997	-0.0008
60	3710.010002	0.0005	3969.990001	0.0003
70	3710.009991	-0.0024	3969.989995	-0.0013
80	3710.009994	-0.0016	3969.989992	-0.002
85	3710.010004	0.0011	3969.990008	0.002

NR n77 SCS 30 kHz (3.7 GHz ~ 3.98 GHz), Channel Bandwidth: 30 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 647668 (3715.02 MHz)		CH 664332 (3964.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3715.02001	0.0027	3964.980009	0.0023
4.7	3715.020006	0.0016	3964.980002	0.0005
4.5	3715.019994	-0.0016	3964.979991	-0.0023

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 647668 (3715.02 MHz)		CH 664332 (3964.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3715.019992	-0.0022	3964.979993	-0.0018
-30	3715.020007	0.0019	3964.980009	0.0023
-20	3715.019998	-0.0005	3964.979994	-0.0015
-10	3715.019992	-0.0022	3964.979992	-0.002
0	3715.019991	-0.0024	3964.979992	-0.002
10	3715.019997	-0.0008	3964.979992	-0.002
20	3715.019995	-0.0013	3964.979998	-0.0005
30	3715.020005	0.0013	3964.980003	0.0008
40	3715.019999	-0.0003	3964.980001	0.0003
50	3715.019995	-0.0013	3964.979996	-0.001
60	3715.019994	-0.0016	3964.979996	-0.001
70	3715.01999	-0.0027	3964.97999	-0.0025
80	3715.01999	-0.0027	3964.97999	-0.0025
85	3715.019999	-0.0003	3964.979995	-0.0013

NR n77 SCS 30 kHz (3.7 GHz ~ 3.98 GHz), Channel Bandwidth: 40 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 648000 (3720 MHz)		CH 664000 (3960 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3720.000002	0.0005	3960	0
4.7	3720	0	3960.000001	0.0003
4.5	3720	0	3960.000002	0.0005

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 648000 (3720 MHz)		CH 664000 (3960 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3719.999991	-0.0024	3959.99999	-0.0025
-30	3720	0	3960	0
-20	3720.000004	0.0011	3960.000001	0.0003
-10	3719.999991	-0.0024	3959.999992	-0.002
0	3720.000003	0.0008	3960.000001	0.0003
10	3719.999998	-0.0005	3960.000001	0.0003
20	3720.000009	0.0024	3960.000009	0.0023
30	3719.999995	-0.0013	3959.999993	-0.0018
40	3719.999995	-0.0013	3959.999993	-0.0018
50	3719.999991	-0.0024	3959.99999	-0.0025
60	3719.999993	-0.0019	3959.999995	-0.0013
70	3719.999995	-0.0013	3959.999993	-0.0018
80	3719.999993	-0.0019	3959.999994	-0.0015
85	3719.999994	-0.0016	3959.999997	-0.0008

NR n77 SCS 30 kHz (3.7 GHz ~ 3.98 GHz), Channel Bandwidth: 50 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 648334 (3725.01 MHz)		CH 663666 (3954.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3725.010005	0.0013	3954.990004	0.001
4.7	3725.009993	-0.0019	3954.989994	-0.0015
4.5	3725.009997	-0.0008	3954.989994	-0.0015

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 648334 (3725.01 MHz)		CH 663666 (3954.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3725.009999	-0.0003	3954.990001	0.0003
-30	3725.009997	-0.0008	3954.989995	-0.0013
-20	3725.009991	-0.0024	3954.98999	-0.0025
-10	3725.010005	0.0013	3954.99	0
0	3725.010001	0.0003	3954.990005	0.0013
10	3725.01	0	3954.990005	0.0013
20	3725.009997	-0.0008	3954.989998	-0.0005
30	3725.009997	-0.0008	3954.989995	-0.0013
40	3725.009993	-0.0019	3954.989993	-0.0018
50	3725.009999	-0.0003	3954.990003	0.0008
60	3725.010002	0.0005	3954.990005	0.0013
70	3725.010008	0.0021	3954.990007	0.0018
80	3725.009998	-0.0005	3954.989997	-0.0008
85	3725.010006	0.0016	3954.990009	0.0023

NR n77 SCS 30 kHz (3.7 GHz ~ 3.98 GHz), Channel Bandwidth: 60 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 648668 (3730.02 MHz)		CH 663332 (3949.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3730.019991	-0.0024	3949.979991	-0.0023
4.7	3730.019992	-0.0021	3949.979994	-0.0015
4.5	3730.02001	0.0027	3949.980005	0.0013

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 648668 (3730.02 MHz)		CH 663332 (3949.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3730.019992	-0.0021	3949.97999	-0.0025
-30	3730.019991	-0.0024	3949.979993	-0.0018
-20	3730.020001	0.0003	3949.980002	0.0005
-10	3730.020001	0.0003	3949.980002	0.0005
0	3730.019997	-0.0008	3949.979994	-0.0015
10	3730.019997	-0.0008	3949.980001	0.0003
20	3730.019999	-0.0003	3949.979996	-0.001
30	3730.019994	-0.0016	3949.979992	-0.002
40	3730.019997	-0.0008	3949.979994	-0.0015
50	3730.020003	0.0008	3949.98	0
60	3730.020006	0.0016	3949.980006	0.0015
70	3730.019999	-0.0003	3949.979996	-0.001
80	3730.020002	0.0005	3949.980001	0.0003
85	3730.019995	-0.0013	3949.979995	-0.0013

NR n77 SCS 30 kHz (3.7 GHz ~ 3.98 GHz), Channel Bandwidth: 70 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 649000 (3735 MHz)		CH 663000 (3945 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3735.000004	0.0011	3945.000003	0.0008
4.7	3734.999997	-0.0008	3944.999993	-0.0018
4.5	3735.000007	0.0019	3945.000006	0.0015

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 649000 (3735 MHz)		CH 663000 (3945 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3735.000006	0.0016	3945.000002	0.0005
-30	3734.999997	-0.0008	3945.000002	0.0005
-20	3734.999996	-0.0011	3944.999991	-0.0023
-10	3734.999992	-0.0021	3944.999993	-0.0018
0	3734.999998	-0.0005	3944.999996	-0.001
10	3734.999994	-0.0016	3944.999995	-0.0013
20	3735	0	3945.000005	0.0013
30	3734.999997	-0.0008	3945	0
40	3735.000009	0.0024	3945.000005	0.0013
50	3734.999993	-0.0019	3944.999993	-0.0018
60	3735.000007	0.0019	3945.000006	0.0015
70	3734.999993	-0.0019	3944.999995	-0.0013
80	3734.999991	-0.0024	3944.99999	-0.0025
85	3735.000006	0.0016	3945.000003	0.0008

NR n77 SCS 30 kHz (3.7 GHz ~ 3.98 GHz), Channel Bandwidth: 80 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 649334 (3740.01 MHz)		CH 662666 (3939.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3740.009991	-0.0024	3939.989994	-0.0015
4.7	3740.009999	-0.0003	3939.99	0
4.5	3740.010003	0.0008	3939.990004	0.001

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 649334 (3740.01 MHz)		CH 662666 (3939.99 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3740.010004	0.0011	3939.990003	0.0008
-30	3740.009995	-0.0013	3939.989994	-0.0015
-20	3740.01001	0.0027	3939.990007	0.0018
-10	3740.009995	-0.0013	3939.989995	-0.0013
0	3740.010002	0.0005	3939.990004	0.001
10	3740.01	0	3939.990005	0.0013
20	3740.009996	-0.0011	3939.989992	-0.002
30	3740.010007	0.0019	3939.990007	0.0018
40	3740.010001	0.0003	3939.990005	0.0013
50	3740.009999	-0.0003	3939.99	0
60	3740.010007	0.0019	3939.990002	0.0005
70	3740.009999	-0.0003	3939.990001	0.0003
80	3740.009999	-0.0003	3939.989996	-0.001
85	3740.010004	0.0011	3939.99	0

NR n77 SCS 30 kHz (3.7 GHz ~ 3.98 GHz), Channel Bandwidth: 90 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 649668 (3745.02 MHz)		CH 662332 (3934.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3745.019992	-0.0021	3934.979993	-0.0018
4.7	3745.019996	-0.0011	3934.979997	-0.0008
4.5	3745.019997	-0.0008	3934.979996	-0.001

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 649668 (3745.02 MHz)		CH 662332 (3934.98 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3745.020009	0.0024	3934.980008	0.002
-30	3745.020003	0.0008	3934.980003	0.0008
-20	3745.020008	0.0021	3934.98001	0.0025
-10	3745.020004	0.0011	3934.980001	0.0003
0	3745.01999	-0.0027	3934.979994	-0.0015
10	3745.019993	-0.0019	3934.979993	-0.0018
20	3745.020005	0.0013	3934.980002	0.0005
30	3745.020009	0.0024	3934.980005	0.0013
40	3745.020002	0.0005	3934.980002	0.0005
50	3745.019991	-0.0024	3934.979994	-0.0015
60	3745.019994	-0.0016	3934.979993	-0.0018
70	3745.019993	-0.0019	3934.979996	-0.001
80	3745.020009	0.0024	3934.980007	0.0018
85	3745.01999	-0.0027	3934.97999	-0.0025

NR n77 SCS 30 kHz (3.7 GHz ~ 3.98 GHz), Channel Bandwidth: 100 MHz

Frequency Stability Versus Voltage				
Voltage (Vdc)	CH 650000 (3750 MHz)		CH 662000 (3930 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.9	3750.000002	0.0005	3930.000004	0.001
4.7	3749.999996	-0.0011	3929.999997	-0.0008
4.5	3750.000001	0.0003	3930.000005	0.0013

Note: The applicant defined the normal working voltage is from 4.9 to 4.5 Vdc.

Frequency Stability Versus Temperature				
Temperature (°C)	CH 650000 (3750 MHz)		CH 662000 (3930 MHz)	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	3750.000009	0.0024	3930.000006	0.0015
-30	3750.000002	0.0005	3930.000002	0.0005
-20	3749.999993	-0.0019	3929.999996	-0.001
-10	3750.000007	0.0019	3930.000004	0.001
0	3750.000006	0.0016	3930.000001	0.0025
10	3749.999993	-0.0019	3929.999998	-0.0005
20	3750	0	3930	0
30	3749.99999	-0.0027	3929.999994	-0.0015
40	3750.000009	0.0024	3930.000007	0.0018
50	3750.000009	0.0024	3930.000008	0.002
60	3750.000005	0.0013	3930.000002	0.0005
70	3750.000005	0.0013	3930.000001	0.0025
80	3750.000007	0.0019	3930.000004	0.001
85	3750.000008	0.0021	3930.000006	0.0015

8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---