



American Telecommunications Certification Body Inc.  
6731 Whittier Ave, McLean, VA 22101

May 4, 2004

RE: Wistron Neweb Corporation  
FCC ID: NKRCRP-1

I have a few comments on this Application.

- 1.) Block Diagram must have all oscillator frequencies listed, please revise.
- 2.) MPE Report needs low, mid and high frequencies listed for each of the frequency ranges in the application. Report also needs to show results for Turbo Mode please revise.

|                 |     |     |     |      |
|-----------------|-----|-----|-----|------|
| 2412.0 – 2462.0 | 11b | Low | Mid | High |
| 2412.0 – 2462.0 | 11g | Low | Mid | High |
| 5150.0 – 5350.0 | ?   | Low | Mid | High |
| 5725.0 – 5825.0 | 11a | Low | Mid | High |

- 3.) Page 2 of Test Report states under Test Results Summary, Radiation Exposure "SAR Report Attached". There is no SAR Report with this application please revise test report.
- 4.) On page 11, 33, 49 of Test Report please describe how peak power was measured. Instruments used, if using power meter list bandwidth of the meter head. Complying with Part 15.407(a)(4). Add description to the appendix.
- 5.) On the 731 Form there is no power listed for the 5150.0 – 5350.0 frequency band, please revise.

Thank you,

Douglas E. Noble  
Examining Engineer

[mailto: dnoble@americanTCB.com](mailto:dnoble@americanTCB.com)

The items indicated above must be submitted before processing can continue on the above referenced application. Failure to provide the requested information may result in application termination. Correspondence should be considered part of the permanent submission and may be viewed from the Internet after a Grant of Equipment Authorization is issued.

Please do not respond to this correspondence using the email reply button. In order for your response to be processed expeditiously, you must submit your documents through the AmericanTCB.com website. Also, please note that partial responses increase processing time and should not be submitted.

Any questions about the content of this correspondence should be directed to the sender.