



FCC ID: NKRUPAUS002
Issued on Mar. 10, 2005

Report No.: FR520501

FCC TEST REPORT

CATEGORY : Fixed

PRODUCT NAME : Satellite Radio Receiver

FCC ID. : NKRUPAUS002

FILING TYPE : Certification

BRAND NAME : Xact

MODEL NAME : UPA-BK

APPLICANT : **Wistron NeWeb Corporation**

No. 10-1, Li-hsin Road I, Science-baded Industrial Park,
Hsinchu 300, Taiwan, R.O.C.

MANUFACTURER : Same as applicant

ISSUED BY : **SPORTON INTERNATIONAL INC.**

6F, No. 106, Sec. 1, Hsin Tai Wu Rd., His Chih, Taipei Hsien,
Taiwan, R.O.C.

Statements:

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

Certificate or Test Report could not be used by the applicant to claim the product endorsement by CNLA and any agency of U.S. government.

The test equipments used to perform the test are calibrated and traceable to NML/ROC or NIST/USA.



1190

ILAC MRA



Table of Contents

| | |
|---|-----------------|
| HISTORY OF THIS TEST REPORT | II |
| CERTIFICATE OF COMPLIANCE..... | III |
| 1. GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST..... | 1 |
| 1.1. Applicant | 1 |
| 1.2. Manufacturer..... | 1 |
| 1.3. Basic Description of Equipment under Test..... | 1 |
| 1.4. Features of Equipment under Test | 1 |
| 1.5. Table for Carrier Frequencies | 2 |
| 2. TEST CONFIGURATION OF THE EQUIPMENT UNDER TEST..... | 3 |
| 2.1. Connection Diagram of Test System | 3 |
| 2.2. The Test Mode Description..... | 3 |
| 2.3. Description of Test Supporting Units | 3 |
| 3. GENERAL INFORMATION OF TEST | 4 |
| 3.1. Test Facility..... | 4 |
| 3.2. Standards for Methods of Measurement..... | 4 |
| 3.3. DoC Statement | 4 |
| 3.4. Frequency Range Investigated | 4 |
| 3.5. Test Distance | 4 |
| 3.6. Test Software | 4 |
| 4. LIST OF MEASUREMENTS | 5 |
| 4.1. Summary of the Test Results..... | 5 |
| 5. TEST RESULT | 6 |
| 5.1. Test of Maximum Field Strength of Fundamental..... | 6 |
| 5.2. Test of Emission Bandwidth..... | 8 |
| 5.3. Test of AC Power Line Conducted Emission..... | 11 |
| 5.4. Test of Spurious Radiated Emission..... | 17 |
| 5.5. Antenna Requirements | 23 |
| 6. LIST OF MEASURING EQUIPMENTS USED..... | 24 |
| 7. COMPANY PROFILE..... | 25 |
| 7.1. Certificate of Accreditation | 25 |
| 7.2. Test Location | 25 |
| 8. CNLA CERTIFICATE OF ACCREDITATION..... | 26 |
| APPENDIX A. PHOTOGRAPHS OF EUT | A1 ~ A30 |



FCC ID: NKRUPAUS002
Issued on Mar. 10, 2005

Report No.: FR520501

HISTORY OF THIS TEST REPORT

Received Date: Feb. 05, 2005

Test Date: Feb. 28, 2005

Original Report Issue Date: Mar. 10, 2005

Report No.: FR520501

■ No additional attachment.

Additional attachment were issued as following record:



FCC ID: NKRUPAUS002
Issued on Mar. 10, 2005

Report No.: FR520501

CERTIFICATE OF COMPLIANCE

with

47 CFR FCC Part 15 Subpart C

PRODUCT NAME : Satellite Radio Receiver

BRAND NAME : Xact

MODEL NAME : UPA-BK

APPLICANT : **Wistron NeWeb Corporation**

No. 10-1, Li-hsin Road I, Science-baded Industrial Park,
Hsinchu 300, Taiwan, R.O.C.

MANUFACTURER : Same as applicant

I HEREBY CERTIFY THAT:

The measurements shown in this test report were made in accordance with the procedures given in ANSI C63.4-2003 and all test are performed according to 47 CFR FCC Part 15 Subpart C. Testing was carried out on Feb. 28, 2005 at SPORTON International Inc. LAB.



Dr. Alan Lane
Vice General Manager
Sporton International Inc.



FCC ID: NKRUPAUS002

Issued on Mar. 10, 2005

Report No.: FR520501

1. General Description of Equipment under Test

1.1. Applicant

Wistron NeWeb Corporation

No. 10-1, Li-hsin Road I, Science-baded Industrial Park, Hsinchu 300, Taiwan, R.O.C.

1.2. Manufacturer

Same as applicant

1.3. Basic Description of Equipment under Test

This product is a FM Transmitter with GPS receiver. The technical data has been listed on section "Features of Equipment under Test".

1.4. Features of Equipment under Test

| Items | Description |
|-------------------------------|--------------------------------|
| Type of Modulation | FM |
| Number of Channels | 3 |
| Frequency Band | 88.10 MHz ~ 107.90 MHz |
| Carrier Frequency | See section 1.5 for details |
| Channel Bandwidth | 150kHz |
| Antenna Type | Inverted-F Antenna |
| Testing Duty Cycle | 100.00% |
| Test Power Source | 110VAC to 6.5VDC power adapter |
| Temperature Range (Operating) | -10 ~ 55 °C |



FCC ID: NKRUPAUS002
Issued on Mar. 10, 2005

Report No.: FR520501


1.5. Table for Carrier Frequencies

| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|------------|---------|-----------|---------|-----------|---------|-----------|
| 01 | 88.10 MHz | - | - | - | - | - | - |
| 02 | 97.01 MHz | - | - | - | - | - | - |
| 03 | 107.90 MHz | - | - | - | - | - | - |
| - | - | - | - | - | - | - | - |



2. Test Configuration of the Equipment under Test

2.1. Connection Diagram of Test System



2.2. The Test Mode Description

1. According to ANSI C63.4-2003: Frequency range of EUT is more than 10 MHz, we have to test the lowest, middle and highest channels of EUT.
2. AC conduction emission is independent of channel selection, there will be no effect on test results so only channel 03 with FM modulation was tested.

2.3. Description of Test Supporting Units

| Support unit | Brand | Model No. | Serial No. | FCC ID | Data cable (m) |
|--------------|---------|-----------|------------|--------|----------------|
| Speaker | HYUNDAI | KY-480 | - | DoC | - |



3. General Information of Test

3.1. Test Facility

Test Site Location : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiag, Tao Yuan Hsien, Taiwan, R.O.C.
: TEL 886-3-327-3456
: FAX 886-3-318-0055
Test Site No : 03CH03-HY / CO01-HY

3.2. Standards for Methods of Measurement

Here is the list of the standards followed in this test report.

ANSI C63.4-2003

47 CFR FCC Part 15 Subpart C

3.3. DoC Statement

This EUT is also classified as a device of computer peripheral Class B which DoC has to be followed. It has been verified according to the rule of 47 CFR part 15 Subpart B, and found that all the requirements has been fulfilled.

3.4. Frequency Range Investigated

Radiated emission test: from 30 MHz to 10th carrier harmonic

3.5. Test Distance

The test distance of radiated emission (30MHz~1GHz) test from antenna to EUT is 3 M.

The test distance of radiated emission (1GHz~10th carrier harmonic) test from antenna to EUT is 3 M.

3.6. Test Software

There is no test software for the test.



4. List of Measurements

4.1. Summary of the Test Results

| Applied Standard: 47 CFR FCC Part 15 Subpart C | | | |
|--|-----------|---------------------------------------|--------|
| Paragraph | FCC Rule | Description of Test | Result |
| 5.1 | 15.239(b) | Maximum Field Strength of Fundamental | Pass |
| 5.2 | 15.207 | AC Power Line Conducted Emission | Pass |
| 5.4 | 15.239(c) | Spurious Radiated Emission | Pass |
| 5.5 | 15.203 | Antenna Requirement | Pass |

5. Test Result

5.1. Test of Maximum Field Strength of Fundamental

5.1.1. Applicable Standard

Section 15.239(b): The field strength of fundamental emissions shall not exceed 250 microvolts/meter at 3 meters (measurement instrumentation employing an average detector).

5.1.2. Measuring Instruments

Item 6~17 of the table is on section 6.


5.1.3. Description of Major Test Instruments Setting

- Test Receiver : R&S ESCS 30
- Attenuation : 10 dB
- Start Frequency : 0.15 MHz
- Stop Frequency : 30 MHz
- IF Bandwidth : 9 KHz

5.1.4. Test Procedures

1. Configure the EUT according to ANSI C63.4.
2. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization.
4. For carrier field strength emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. For carrier field strength emission, use 9kHz RBW of Receiver for reading under average and peak detector.

5.1.5. Test Setup Layout





FCC ID: NKRUPAUS002

Issued on Mar. 10, 2005

Report No.: FR520501

5.1.6. Test Criteria

All test results complied with the requirements of 15.239(b). Measurement Uncertainty is 2.26dB.

5.1.7. Test Result

- Temperature: 26°C
- Relative Humidity: 64%
- Duty Cycle of the Equipment During the Test: 100.00%
- Test Engineer: Ming Da, Kou

| Channel No. | Frequency (MHz) | Level (dBuV/m) | Over Limit (dB) | Limit Line (dBuV/m) | Read Level (dBuV) | Detector |
|-------------|-----------------|----------------|-----------------|---------------------|-------------------|----------|
| 01 | 88.10 MHz | 27.41 | -12.59 | 40.00 | 48.50 | Average |
| 01 | 88.10 MHz | 40.05 | 0.05 | 40.00 | 61.14 | Peak |
| 02 | 97.01 MHz | 21.67 | -18.33 | 40.00 | 40.63 | Average |
| 02 | 97.01 MHz | 30.93 | -12.57 | 43.50 | 50.51 | Peak |
| 03 | 107.90 MHz | 39.79 | -3.71 | 43.50 | 57.75 | Average |
| 03 | 107.90 MHz | 39.82 | -3.68 | 43.50 | 57.78 | Peak |

Note:

Correct Factor = Antenna Factor + Cable Loss - Preamp Factor.

Read Level = Level of Receiver or Spectrum.

Level = Read Level + Correct Factor.



5.2. Test of Emission Bandwidth

5.2.1. Applicable Standard

Section **錯誤! 找不到參照來源。** : Emissions from the intentional radiator shall be confined within a band 200 kHz wide centered on the operating frequency.

5.2.2. Measuring Instruments

Item 7 of the table is on section 6.


5.2.3. Description of Major Test Instruments Setting

- Spectrum Analyzer : R&S FSP40
- Attenuation : Auto
- Center Frequency : Carrier frequency
- Span Frequency : Suitable for observe
- RB : 10 kHz
- VB : 10 kHz

5.2.4. Test Procedures

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Set RBW of spectrum analyzer to 1% of occupied bandwidth
3. Set the 99% occupied bandwidth function to measure the bandwidth of EUT.

5.2.5. Test Setup Layout



5.2.6. Test Criteria

All test results complied with the requirements of **錯誤! 找不到參照來源。**. Measurement Uncertainty is 1×10^{-5} .

5.2.7. Test Result

- Temperature: 26°C
- Relative Humidity: 64%
- Duty Cycle of the Equipment During the Test: 100.00%
- Test Engineer: Bunny Yao

| Channel | Frequency (MHz) | Bandwidth (kHz) | Max. Limit (kHz) |
|---------|-----------------|-----------------|------------------|
| 01 | 88.10 MHz | | 200 |
| 02 | 97.01 MHz | | 200 |




FCC ID: NKRUPAUS002
Issued on Mar. 10, 2005

Report No.: FR520501

| | | | |
|----|------------|--|-----|
| 03 | 107.90 MHz | | 200 |
|----|------------|--|-----|

Modulation Type: FM (Channel 01) :




Date: 15.MAR.2005 04:03:17

Modulation Type: FM (Channel 02) :




FCC ID: NKRUPAUS002
Issued on Mar. 10, 2005

Report No.: FR520501



Date: 15.MAR.2005 04:05:05

Modulation Type: FM (Channel 03) :



Date: 15.MAR.2005 03:56:25



FCC ID: NKRUPAUS002

Issued on Mar. 10, 2005

Report No.: FR520501

5.3. Test of AC Power Line Conducted Emission

5.3.1. Applicable Standard

Section 15.207: For a Low-power Radio-frequency Device is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

| Frequency (MHz) | QP Limit (dBuV) | AV Limit (dBuV) |
|-----------------|-----------------|-----------------|
| 0.15~0.5 | 66~56 | 56~46 |
| 0.5~5 | 56 | 46 |
| 5~30 | 60 | 50 |

5.3.2. Measuring Instruments

Please reference item 1~5 in chapter 6 for the instruments used for testing.

5.3.3. Description of Major Test Instruments Setting

- Test Receiver : R&S ESCS 30
- Attenuation : 10 dB
- Start Frequency : 0.15 MHz
- Stop Frequency : 30 MHz
- IF Bandwidth : 9 KHz

5.3.4. Test Procedures



FCC ID: NKRUPAUS002


Issued on Mar. 10, 2005

Report No.: FR520501

1. Configure the EUT according to ANSI C63.4.
2. The EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN)
4. All the support units are connected to the other LISNs. The LISN should provides 50uH/50ohms coupling impedance.
5. The frequency range from 150 KHz to 30 MHz was searched.
6. Use the Channel & Power Controlling software to make the EUT working on selected channel and expected output power, then use the "H" Patter Generator software to make the supporting equipments stay on working condition.
7. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
8. The measurement has to be done between each power line and ground at the power terminal for each RF channel. Only one RF channel has to be investigated since this test is independent with the RF channel selection.



5.3.5. Test Setup Layout



5.3.6. Test Criteria


All test results complied with the requirements of 15.207. Measurement Uncertainty is 2.54dB.



5.3.7. Test Result of Conducted Emission for CH 03 / 107.90 MHz

- Temperature: 26°C
- Relative Humidity: 64%
- Test Engineer: Sky Wu

Line to Ground



| Freq | Level | Over | Limit | Read | LISN | Cable | Remark |
|-------------|-------|--------|-------|-------|--------|-------|---------|
| | | Line | Limit | Line | Factor | Loss | |
| MHz | dBuV | dB | dBuV | dBuV | dB | dB | |
| 1 0.2365680 | 48.75 | -13.47 | 62.22 | 48.44 | 0.06 | 0.25 | QP |
| 2 0.2365680 | 30.79 | -21.43 | 52.22 | 30.48 | 0.06 | 0.25 | Average |
| 3 0.4736030 | 47.26 | -9.19 | 56.45 | 46.98 | 0.06 | 0.22 | QP |
| 4 0.4736030 | 30.42 | -16.03 | 46.45 | 30.14 | 0.06 | 0.22 | Average |
| 5 0.7059500 | 47.01 | -8.99 | 56.00 | 46.17 | 0.11 | 0.73 | QP |
| 6 0.7059500 | 30.24 | -15.76 | 46.00 | 29.40 | 0.11 | 0.73 | Average |
| 7 0.8969640 | 22.28 | -23.72 | 46.00 | 21.50 | 0.11 | 0.67 | Average |
| 8 0.8969640 | 42.42 | -13.58 | 56.00 | 41.64 | 0.11 | 0.67 | QP |
| 9 1.754 | 36.89 | -19.11 | 56.00 | 36.48 | 0.11 | 0.30 | QP |
| 10 1.754 | 18.92 | -27.08 | 46.00 | 18.51 | 0.11 | 0.30 | Average |
| 11 27.129 | 33.60 | -26.40 | 60.00 | 32.74 | 0.40 | 0.46 | QP |
| 12 27.129 | 20.11 | -29.89 | 50.00 | 19.25 | 0.40 | 0.46 | Average |




FCC ID: NKRUPAUS002

Issued on Mar. 10, 2005

Report No.: FR520501

Neutral to Ground



| Freq | Level | Over Limit | Limit Line | Read Level | | LISN Factor | Cable Loss | Cable Remark |
|------|-----------|------------|------------|------------|-------|-------------|------------|--------------|
| | | | | MHz | dBuV | | | |
| 1 | 0.3359100 | 46.74 | -12.56 | 59.30 | 46.33 | 0.11 | 0.30 | QP |
| 2 | 0.3359100 | 36.69 | -12.61 | 49.30 | 36.28 | 0.11 | 0.30 | Average |
| 3 | 0.4502700 | 49.69 | -7.18 | 56.87 | 49.34 | 0.11 | 0.24 | QP |
| 4 | 0.4502700 | 37.82 | -9.05 | 46.87 | 37.47 | 0.11 | 0.24 | Average |
| 5 | 0.6763850 | 37.00 | -9.00 | 46.00 | 36.10 | 0.23 | 0.67 | Average |
| 6 | 0.6763850 | 50.85 | -5.15 | 56.00 | 49.95 | 0.23 | 0.67 | QP |
| 7 | 0.7945250 | 47.77 | -8.23 | 56.00 | 46.84 | 0.23 | 0.70 | QP |
| 8 | 0.7945250 | 30.18 | -15.82 | 46.00 | 29.25 | 0.23 | 0.70 | Average |
| 9 | 0.9061940 | 48.79 | -7.21 | 56.00 | 47.89 | 0.23 | 0.67 | QP |
| 10 | 0.9061940 | 31.24 | -14.76 | 46.00 | 30.34 | 0.23 | 0.67 | Average |
| 11 | 1.013 | 46.61 | -9.39 | 56.00 | 45.75 | 0.23 | 0.63 | QP |
| 12 | 1.013 | 30.44 | -15.56 | 46.00 | 29.58 | 0.23 | 0.63 | Average |

Note:

Corrected Reading: Probe (LISN / ISN) Factor + Cable Loss + Read Level = Level.



FCC ID: NKRUPAUS002
Issued on Mar. 10, 2005

Report No.: FR520501

5.3.8. Photographs of Conducted Emission Test Configuration

FRONT VIEW



REAR VIEW





FCC ID: NKRUPAUS002

Issued on Mar. 10, 2005

Report No.: FR520501

5.4. Test of Spurious Radiated Emission

5.4.1. Applicable Standard

Section 15.239(c): The field strength of any emissions radiated on any frequency outside of the specified 200 kHz band shall not exceed the general radiated emission limits in Section 15.209.

5.4.2. Measuring Instruments

Please reference item 1~17 in chapter 6 for the instruments used for testing.

5.4.3. Description of Major Test Instruments Setting


- Spectrum Analyzer : R&S FSP40
 - Attenuation : Auto
 - Start Frequency : 1000 MHz
 - Stop Frequency : 10th carrier harmonic
 - RB / VB : 1 MHz / 1MHz for Peak
 - RB / VB : 1 MHz / 10Hz for Average
- Test Receiver : R&S ESCS 30
 - Attenuation : Auto
 - Start Frequency : 30 MHz
 - Stop Frequency : 1000 MHz
 - RB : 120 KHz for QP or PK

5.4.4. Test Procedures

1. Configure the EUT according to ANSI C63.4.
2. The EUT was placed on the top of the turntable 0.8 meter above ground.
3. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
4. Power on the EUT and all the supporting units.
5. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
6. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization.
7. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
8. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
9. For emission above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
10. If the emission level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz and average method for above the 1GHz. the reported.

11. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB higher than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

5.4.5. Test Setup Layout



5.4.6. Test Criteria

All test results complied with the requirements of 15.239(c). Measurement Uncertainty is 2.26dB.



FCC ID: NKRUPAUS002

Issued on Mar. 10, 2005

Report No.: FR520501

5.4.7. Test Results for CH 01 / 88.10 MHz

- Temperature: 26°C
- Relative Humidity: 64%
- Duty Cycle of the Equipment During the Test: 100.00%
- Test Engineer: Ming Da, Kou

(A) **Polarization: Horizontal**

| Freq | Level | Over Limit | Antenna Line Factor | Cable Preamp | | Read Level | | Remark |
|---------|-------|------------|---------------------|--------------|------|------------|-------|------------|
| | | | | dB | dB/m | dB | dB | |
| 43.580 | 14.23 | -25.77 | 40.00 | 10.30 | 0.56 | 29.83 | 33.19 | HORIZONTAL |
| 87.230 | 27.41 | -12.59 | 40.00 | 8.20 | 0.75 | 30.04 | 48.50 | HORIZONTAL |
| 299.660 | 18.06 | -27.94 | 46.00 | 13.00 | 1.37 | 30.16 | 33.85 | HORIZONTAL |
| 351.070 | 19.54 | -26.46 | 46.00 | 14.44 | 1.48 | 30.58 | 34.24 | HORIZONTAL |
| 418.970 | 20.45 | -25.55 | 46.00 | 16.58 | 1.61 | 30.36 | 32.62 | HORIZONTAL |
| 552.830 | 22.01 | -23.99 | 46.00 | 18.42 | 1.87 | 30.64 | 32.36 | HORIZONTAL |
| 735.190 | 23.00 | -23.00 | 46.00 | 19.86 | 2.15 | 30.17 | 31.16 | HORIZONTAL |
| 850.620 | 24.15 | -21.85 | 46.00 | 20.27 | 2.36 | 29.93 | 31.44 | HORIZONTAL |

(B) **Polarization: Vertical**

| Freq | Level | Over Limit | Antenna Line Factor | Cable Preamp | | Read Level | | Remark |
|---------|-------|------------|---------------------|--------------|------|------------|-------|----------|
| | | | | dB | dB/m | dB | dB | |
| 87.230 | 40.05 | 0.05 | 40.00 | 8.20 | 0.75 | 30.04 | 61.14 | VERTICAL |
| 118.270 | 24.48 | -19.02 | 43.50 | 11.62 | 0.88 | 30.04 | 42.02 | VERTICAL |
| 160.950 | 20.12 | -23.38 | 43.50 | 9.55 | 1.01 | 30.17 | 39.72 | VERTICAL |
| 191.020 | 17.89 | -25.61 | 43.50 | 8.47 | 1.09 | 29.96 | 38.29 | VERTICAL |
| 552.830 | 22.02 | -23.98 | 46.00 | 18.42 | 1.87 | 30.64 | 32.37 | VERTICAL |
| 621.700 | 22.32 | -23.68 | 46.00 | 18.72 | 1.96 | 30.64 | 32.27 | VERTICAL |
| 882.630 | 25.53 | -20.47 | 46.00 | 20.33 | 2.39 | 29.15 | 31.96 | VERTICAL |

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Probe Factor + Cable Loss + Read Level - Preamp Factor = Level



FCC ID: NKRUPAUS002

Issued on Mar. 10, 2005

Report No.: FR520501

5.4.8. Test Results for CH 02 / 97.01 MHz

- Temperature: 26°C
- Relative Humidity: 64%
- Duty Cycle of the Equipment During the Test: 100.00%
- Test Engineer: Ming Da, Kou

(A) Polarization: Horizontal

| Freq MHz | Level dBuV/m | Over Limit | Antenna Line Factor | Cable Loss | Preamp Factor | Read Level dBuV | Pol/Phase | Remark |
|-------------|-----------------|---------------|------------------------|---------------|------------------|-----------------------|-----------|------------|
| | | dB | dBuV/m | dB/m | dB | dB | | |
| 94.990 | 30.93 | -12.57 | 43.50 | 9.75 | 0.79 | 30.12 | 50.51 | HORIZONTAL |
| 109.540 | 18.80 | -24.70 | 43.50 | 11.50 | 0.84 | 30.07 | 36.53 | HORIZONTAL |
| 272.500 | 15.72 | -30.28 | 46.00 | 12.50 | 1.31 | 30.04 | 31.95 | HORIZONTAL |
| 299.660 | 18.23 | -27.77 | 46.00 | 13.00 | 1.37 | 30.16 | 34.02 | HORIZONTAL |
| 419.940 | 19.18 | -26.82 | 46.00 | 16.60 | 1.61 | 30.36 | 31.33 | HORIZONTAL |
| 660.500 | 22.48 | -23.52 | 46.00 | 18.90 | 2.05 | 30.34 | 31.88 | HORIZONTAL |
| 780.780 | 24.01 | -21.99 | 46.00 | 19.80 | 2.22 | 30.10 | 32.10 | HORIZONTAL |

(B) Polarization: Vertical

| Freq MHz | Level dBuV/m | Over Limit | Antenna Line Factor | Cable Loss | Preamp Factor | Read Level dBuV | Pol/Phase | Remark |
|-------------|-----------------|---------------|------------------------|---------------|------------------|-----------------------|-----------|----------|
| | | dB | dBuV/m | dB/m | dB | dB | | |
| 43.580 | 21.67 | -18.33 | 40.00 | 10.30 | 0.56 | 29.83 | 40.63 | VERTICAL |
| 94.990 | 36.08 | -7.42 | 43.50 | 9.75 | 0.79 | 30.12 | 55.65 | VERTICAL |
| 118.270 | 24.43 | -19.07 | 43.50 | 11.62 | 0.88 | 30.04 | 41.97 | VERTICAL |
| 160.950 | 19.80 | -23.70 | 43.50 | 9.55 | 1.01 | 30.17 | 39.40 | VERTICAL |
| 191.020 | 17.19 | -26.31 | 43.50 | 8.47 | 1.09 | 29.96 | 37.59 | VERTICAL |
| 400.540 | 18.58 | -27.42 | 46.00 | 15.94 | 1.59 | 30.35 | 31.40 | VERTICAL |
| 455.830 | 19.83 | -26.17 | 46.00 | 16.52 | 1.69 | 30.47 | 32.09 | VERTICAL |
| 859.350 | 24.64 | -21.36 | 46.00 | 20.21 | 2.37 | 29.72 | 31.78 | VERTICAL |

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Probe Factor + Cable Loss + Read Level - Preamp Factor = Level



FCC ID: NKRUPAUS002

Issued on Mar. 10, 2005

Report No.: FR520501

5.4.9. Test Results for CH 03 / 107.90 MHz

- Temperature: 26°C
- Relative Humidity: 64%
- Duty Cycle of the Equipment During the Test: 100.00%
- Test Engineer: Ming Da, Kou

(A) Polarization: Horizontal

| Freq | Level | Over | Limit | Antenna | Cable | Preamp | Read | Remark |
|---------|--------|--------|--------|---------|-------|--------|-------|------------|
| | | Line | Factor | dB/m | dB | Loss | Level | |
| MHz | dBuV/m | dB | dBuV/m | dB/m | dB | dB | dBuV | |
| 30.000 | 33.80 | -6.20 | 40.00 | 18.10 | 0.47 | 29.80 | 45.03 | HORIZONTAL |
| 43.580 | 22.41 | -17.59 | 40.00 | 10.30 | 0.56 | 29.83 | 41.37 | HORIZONTAL |
| 106.630 | 39.79 | -3.71 | 43.50 | 11.29 | 0.83 | 30.08 | 57.75 | HORIZONTAL |
| 125.060 | 23.00 | -20.50 | 43.50 | 11.85 | 0.89 | 30.03 | 40.28 | HORIZONTAL |
| 143.490 | 19.42 | -24.08 | 43.50 | 10.70 | 0.94 | 30.06 | 37.83 | HORIZONTAL |
| 160.950 | 19.34 | -24.16 | 43.50 | 9.55 | 1.01 | 30.17 | 38.94 | HORIZONTAL |
| 188.110 | 16.51 | -26.99 | 43.50 | 8.36 | 1.08 | 29.98 | 37.04 | HORIZONTAL |
| 417.030 | 18.51 | -27.49 | 46.00 | 16.53 | 1.61 | 30.36 | 30.73 | HORIZONTAL |
| 528.580 | 20.76 | -25.24 | 46.00 | 17.70 | 1.83 | 30.58 | 31.81 | HORIZONTAL |
| 722.580 | 23.01 | -22.99 | 46.00 | 19.50 | 2.14 | 30.26 | 31.63 | HORIZONTAL |
| 800.180 | 23.47 | -22.53 | 46.00 | 20.00 | 2.26 | 30.13 | 31.34 | HORIZONTAL |

(B) Polarization: Vertical

| Freq | Level | Over | Limit | Antenna | Cable | Preamp | Read | Remark |
|---------|--------|--------|--------|---------|-------|--------|-------|----------|
| | | Line | Factor | dB/m | dB | Loss | Level | |
| MHz | dBuV/m | dB | dBuV/m | dB/m | dB | dB | dBuV | |
| 30.000 | 33.42 | -6.58 | 40.00 | 18.10 | 0.47 | 29.80 | 44.65 | VERTICAL |
| 83.350 | 20.73 | -19.27 | 40.00 | 7.40 | 0.73 | 29.97 | 42.57 | VERTICAL |
| 106.630 | 39.82 | -3.68 | 43.50 | 11.29 | 0.83 | 30.08 | 57.78 | VERTICAL |
| 160.950 | 19.20 | -24.30 | 43.50 | 9.55 | 1.01 | 30.17 | 38.80 | VERTICAL |
| 191.020 | 17.95 | -25.55 | 43.50 | 8.47 | 1.09 | 29.96 | 38.35 | VERTICAL |
| 206.540 | 14.85 | -28.65 | 43.50 | 8.80 | 1.13 | 29.99 | 34.90 | VERTICAL |
| 292.870 | 15.68 | -30.32 | 46.00 | 12.86 | 1.36 | 30.08 | 31.54 | VERTICAL |
| 361.740 | 17.17 | -28.83 | 46.00 | 14.81 | 1.50 | 30.56 | 31.42 | VERTICAL |
| 463.590 | 20.03 | -25.97 | 46.00 | 16.73 | 1.71 | 30.50 | 32.10 | VERTICAL |
| 579.990 | 21.60 | -24.40 | 46.00 | 18.70 | 1.90 | 30.78 | 31.78 | VERTICAL |
| 649.830 | 21.70 | -24.30 | 46.00 | 18.89 | 2.02 | 30.32 | 31.11 | VERTICAL |
| 754.590 | 23.60 | -22.40 | 46.00 | 19.91 | 2.16 | 30.07 | 31.60 | VERTICAL |
| 827.340 | 23.66 | -22.34 | 46.00 | 20.27 | 2.31 | 30.03 | 31.11 | VERTICAL |
| 908.820 | 26.28 | -19.72 | 46.00 | 20.59 | 2.43 | 28.79 | 32.06 | VERTICAL |

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Probe Factor + Cable Loss + Read Level - Preamp Factor = Level



FCC ID: NKRUPAUS002
Issued on Mar. 10, 2005


Report No.: FR520501

5.4.10. Photographs of Radiated Emission Test Configuration

FRONT VIEW



REAR VIEW





5.5. Antenna Requirements

5.5.1. Standard Applicable

Section 15.203: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

5.5.2. Antenna Connected Construction

There is no antenna connector for Inverted-F antenna.

5.5.3. Test Criteria

All test results complied with the requirements of 15.203.



FCC ID: NKRUPAUS002

Issued on Mar. 10, 2005

Report No.: FR520501

6. List of Measuring Equipments Used

| Items | Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Remark |
|-------|--------------------------|--------------------|------------|------------|------------------|------------------|-----------------------|
| 1 | EMC Receiver | R&S | ESCS 30 | 100132 | 9 KHz – 2.75 GHz | Jun. 23, 2004 | Conduction (CO01-HY) |
| 2 | LISN | MessTec | NNB-2/16Z | 2001/008 | 9 KHz – 30 MHz | May 03, 2004 | Conduction (CO01-HY) |
| 3 | LISN (Support Unit) | MessTec | NNB-2/16Z | 2001/009 | 9 KHz – 30 MHz | Apr. 19, 2004 | Conduction (CO01-HY) |
| 4 | EMI Filter | LINDGREN | LRE-2060 | 1004 | < 450 Hz | N/A | Conduction (CO01-HY) |
| 5 | EMI Filter | LINDGREN | N6006 | 201052 | 0 ~ 60 Hz | N/A | Conduction (CO01-HY) |
| 6 | RF Cable-CON | Suhner Switzerland | RG223/U | CB029 | 9KHz~30MHz | Dec. 23, 2004 | Conduction (CO01-HY) |
| 7 | 3m Semi Anechoic Chamber | SIDT FRANKONIA | SAC-3M | 03CH03-HY | 30MHz~1GHz 3m | Jun. 21, 2004 | Radiation (03CH03-HY) |
| 8 | Spectrum analyzer | R&S | FSP40 | 100004 | 9KHZ~40GHz | Aug. 31, 2004 | Radiation (03CH03-HY) |
| 9 | Amplifier | SCHAFFNER | CPA9231A | 18667 | 9KHz – 2GHz | Jan. 10, 2005 | Radiation (03CH03-HY) |
| 10 | Biconical Antenna | SCHWARZBECK | VHBB 9124 | 301 | 30MHz –200MHz | Jul. 28, 2004 | Radiation (03CH03-HY) |
| 11 | Log Antenna | SCHWARZBECK | VUSLP 9111 | 221 | 200MHz -1GHz | Jul. 28, 2004 | Radiation (03CH03-HY) |
| 12 | RF Cable-R03m | Jye Bao | RG142 | CB021 | 30MHz~1GHz | Dec. 02, 2004 | Radiation (03CH03-HY) |
| 13 | Amplifier | MITEQ | AFS44 | 849984 | 100MHz~26.5GHz | Mar. 26, 2004 | Radiation (03CH03-HY) |
| 14 | Horn Antenna | EMCO | 3115 | 6741 | 1GHz – 18GHz | Apr. 07, 2004 | Radiation (03CH03-HY) |
| 15 | Turn Table | HD | DS 420 | 420/650/00 | 0 ~ 360 degree | N/A | Radiation (03CH03-HY) |
| 16 | Antenna Mast | HD | MA 240 | 240/560/00 | 1 m - 4 m | N/A | Radiation (03CH03-HY) |
| 17 | Horn Antenna | Schwarzbeck | BBHA9170 | 154 | 18GHz~40GHz | Jun. 09, 2004 | Radiation (03CH03-HY) |
| 18 | RF Cable-HIGH | Jye Bao | RG142 | CB030-HIGH | 1GHz~29.5GHz | Dec. 04, 2004 | Radiation (03CH03-HY) |

※ Calibration Interval of instruments listed above is one year.



7. Company Profile

SPORTON Lab. was established in 1986 with one shielded room: the first private EMI test facility, offering local manufacturers an alternative EMI test familial apart from ERSO. In 1988, one 3M and 10M/3M open area test site were setup and also obtained official accreditation from FCC, VCCI and NEMKO. In 1993, a Safety laboratory was founded and obtained accreditation from UL of USA, CSA of Canada and TUV (Rhineland & PS) of Germany. In 1995, one EMC lab, including EMI and EMS test facilities was setup. In 1997, SPORTON Group has provided financial expense to relocate the headquarter to Orient Scientific Park in Taipei Hsien to offer more comprehensive, more qualified and better service to local suppliers and manufactures. In 1999, Safety Group and Component Group were setup. In 2001, SPORTON has established 3M/10M chamber in Hwa Ya Technology Park.

7.1. Certificate of Accreditation

| | |
|--------|-----------------|
| Taiwan | BSMI, CNLA, DGT |
| USA | FCC, NVLAP, UL |
| EU | Nemko, TUV |
| Japan | VCCI |
| Canada | Industry Canada |

7.2. Test Location

| | |
|--------|--|
| SHIJR | ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 02-2696-2468 FAX : 02-2696-2255 |
| HWA YA | ADD : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 03-327-3456 FAX : 03-318-0055 |
| LINKOU | ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 02-2601-1640 FAX : 02-2601-1695 |
| DUNGHU | ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 02-2631-4739 FAX : 02-2631-9740 |
| JUNGHE | ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 02-8227-2020 FAX : 02-8227-2626 |
| NEIHU | ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 02-2794-8886 FAX : 02-2794-9777 |



FCC ID: NKRUPAUS002
Issued on Mar. 10, 2005

Report No.: FR520501


8. CNLA Certificate of Accreditation

Test Lab. : Sporton International Inc.
Accreditation Number : 1190
Originally Accredited : 2003/12/15
Effective Period : 2003/12/15~2006/12/14
Accredited Scope : 47 CFR FCC Part 15 Subpart C (9kHz~40GHz)



Taiwan Accreditation Foundation
Chinese National Laboratory Accreditation
Certificate of Accreditation

Accreditation Criteria: ISO 17025
Accreditation Number: 1190
Organization/Laboratory: EMC & Wireless Communications Laboratory, Sporton International Inc.
Originally Accredited: December 15, 2003
Effective Period: December 15, 2003 To December 14, 2006
Accredited Scope: Electrical Testing Field, 7 items, details shown in the following pages.
Specific Accreditation Program: Recognition and Approval of Designated Laboratory for Commodities Inspection


President, Taiwan Accreditation Foundation
Date: July 19, 2004

(This document is invalid unless accompanied by all 4 pages)

CNLA-ZL03191E Page 1 of 4