



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	Wistron NeWeb Corporation
Applicant Address	No. 10-1, Li-hsin Road I, Science-baded Industrial Park, Hsinchu 300, Taiwan, R.O.C.
FCC ID	NKRUWASLV5
Manufacturer's company	Wistron NeWeb Corporation
Manufacturer Address	No. 10-1, Li-hsin Road I, Science-baded Industrial Park, Hsinchu 300, Taiwan, R.O.C.

Product Name	Satellite Radio receiver Car Dock
Brand Name	Sirius
Model Name	SLV1
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.239
Test Freq. Range	88 ~ 108MHz
Receive Date	Jul. 4, 2006
Final Test Date	Sep. 18, 2006
Submission Type	Original Equipment



Statement

The device is only possible within the range 88.1-107.9MHz.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	3
3.3. Table for Filed Antenna.....	3
3.4. Table for Carrier Frequencies	4
3.5. Table for Test Modes.....	4
3.6. Table for Testing Locations.....	4
3.7. Table for Supporting Units	5
3.8. Test Configurations	5
4. TEST RESULT	9
4.1. Field Strength of Fundamental Emissions Measurement.....	9
4.2. 20dB Spectrum Bandwidth Measurement	35
4.3. Radiated Emissions Measurement	38
4.4. Band Edge Emissions Measurement	65
4.5. Antenna Requirements	75
5. LIST OF MEASURING EQUIPMENTS	76
6. SPORTON COMPANY PROFILE	77
6.1. Test Location.....	77
APPENDIX A. PHOTOGRAPHS OF EUT.....	A1 ~ A14
APPENDIX B. TEST PHOTOS.....	B1 ~ B10



History of This Test Report

Original Issue Date: Sep. 29, 2006

Report No.: FR671326-01

■ No additional attachment.

Additional attachment were issued as following record:



1. CERTIFICATE OF COMPLIANCE

Product Name : Satellite Radio receiver Car Dock
Brand Name : Sirius
Model Name : SLV1
Applicant : Wistron NeWeb Corporation
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.239

Sportun International as requested by the applicant to evaluate the EMC performance of the product sample received on Jul. 4, 2006 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

Sharon Jiang 29.9.06

Prepared By:

Sharon Jiang / Specialist

Steven Lu 29.9.06

Tested By:

Steven Lu / Engineer

Wayne Hsu 29.9.06

Reviewed By:

Wayne Hsu

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
-	15.207	AC Power Line Conducted Emissions	-	-
4.1	15.239(b)	Field Strength of Fundamental Emissions	Complies	0.25 dB
4.2	15.239(a)	20dB Spectrum Bandwidth	Complies	-
4.3	15.239(c)	Radiated Emissions	Complies	3.12 dB
4.4	15.239(c)	Band Edge Emissions	Complies	8.52 dB
4.5	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.26dB	Confidence levels of 95%
Field Strength of Fundamental Emissions	±3.72dB	Confidence levels of 95%
20dB Spectrum Bandwidth	±6.25×10-7	Confidence levels of 95%
Radiated Emissions/ Band Edge Emissions	±3.72dB	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Product Type	Low Power Communication Device (FM Transmitter)
Radio Type	Intentional Transmitter
Power Type	Car charger
Interface Type	DC IN / Line OUT / Antenna connect / FM
Modulation	FM
Frequency Range	88 ~ 108MHz
Channel Number	100
Channel Band Width (99%)	74.00 kHz
Max. Field Strength	47.75 dBuV/m at 3m (Average)
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

3.2. Accessories

Power	Brand	Model	Rating
Car charger	DVE	DDA-10W-05	Input: 9-16VDC, 1.35A Output: +5VDC, 2A
Others			
Car dock / SL100 / Remote control			

3.3. Table for Filed Antenna

Ant.	Description
1	Integrated (for FM transmitter)
2	External (for FM transmitter) – connector: Audio Jack (2.5mm)

3.4. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency
88 ~ 108MHz	1	88.1 MHz
	2	88.3 MHz
	:	:
	50	97.9 MHz
	51	98.1 MHz
	52	98.3 MHz
	:	:
	99	107.7 MHz
	100	107.9 MHz

3.5. Table for Test Modes

Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Channel	Ant.
Field Strength of Fundamental Emissions 20dB Spectrum Bandwidth	CTX1(Antenna without bundle of cable / Antenna with bundle of cable)	1/51/100	1/1+2
Radiated Emissions 9kHz~30MHz	CTX1 (Antenna without bundle of cable / Antenna with bundle of cable)	51	1/1+2
Radiated Emissions 30MHz~10 th Harmonic	CTX1 (Antenna without bundle of cable / Antenna with bundle of cable)	1/51/100	1/1+2
Band Edge Emissions	CTX1(Antenna without bundle of cable / Antenna with bundle of cable)	1/100	1/1+2

Note:

CTX1=Continuously transmitting and audio modulating content a range of 100 to 5000 Hz.

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units


Support Unit	Brand	Model	FCC ID
Speaker	Dell	A125	DoC
Main receiver	SIRIUS	SL100	NKRUWASLDKSP
Car battery	YUASA	YTX&A-BS	DOC

3.8. Test Configurations


3.8.1. Radiation Emissions Test Configuration

Mode 1: Antenna without bundle of cable / Ant.1

9kHz~1GHz




88~108MHz




Mode 2: Antenna with bundle of cable / Ant.1

9kHz~1GHz




88~108MHz




Mode 3: Antenna without bundle of cable / Ant. 1 + Ant.2

9kHz~1GHz




88~108MHz




Mode 4: Antenna with bundle of cable / Ant. 1 + Ant.2

9kHz~1GHz



88~108MHz



4. TEST RESULT

4.1. Field Strength of Fundamental Emissions Measurement

4.1.1. Limit

The field strength of fundamental emissions shall comply with the following table.

Frequency Band (MHz)	Fundamental Emissions Limit (dBuV/m) at 3m
88~108	48 (Average)
88~108	68 (Peak)

4.1.2. Measuring Instruments and Setting


Please refer to section 5 in this report. The following table is the setting of the receiver.

Receiver Parameter	Setting
Attenuation	Auto
Center Frequency	Fundamental Frequency
RB	120 KHz
Detector	Peak / Average

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. For Fundamental emissions, use the receiver to measure peak and average reading.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

4.1.4. Test Setup Layout



4.1.5. Test Deviation

There is no deviation with the original standard.


4.1.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.1.7. Test Result of Field Strength of Fundamental Emissions


Temperature	24°C	Humidity	64%
Test Engineer	Beck Wu	Configurations	Channel 1 / Antenna without bundle of cable / Ant. 1

Vertical



Freq	Level	Over Limit	Limit Line	Read		Ant Pos	Table Pos
				Antenna	Cable		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
2 @ 88.096	41.68	-6.32	48.00	58.27	8.98	0.55	26.12 AVERAGE
3 @ 88.096	42.56	-25.44	68.00	59.15	8.98	0.55	26.12 PEAK

Item 2, 3 are fundamental frequency at 88.1 MHz.

Horizontal


Freq	Level	Over Limit	Limit	Read	Antenna	Cable	Preamp	Table	
								Pos	Pos
MHz	dBuV/m	dB	dBuV/m	Line	Level Factor	Loss Factor	Remark	cm	deg
2 @	88.107	40.03	-7.97	48.00	56.62	8.98	0.55	26.12	AVERAGE
3	88.107	41.46	-26.54	68.00	58.05	8.98	0.55	26.12	PEAK

Item 2, 3 are fundamental frequency at 88.1 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Temperature	24°C	Humidity	64%
Test Engineer	Beck Wu	Configurations	Channel 51 / Antenna without bundle of cable / Ant. 1

Vertical



Freq	Level	Over Limit	Limit	Read	Antenna	Cable	Preamp			Ant Pos	Table Pos
								Line	Factor		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB			cm	deg
1 @	98.096	41.85	-6.15	48.00	56.60	10.82	0.42	26.00	AVERAGE	247	360
2	98.096	42.29	-25.71	68.00	57.05	10.82	0.42	26.00	PEAK	247	360

Item 1, 2 are fundamental frequency at 98.1 MHz.

Horizontal


Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
		Limit	Line	Level	Factor	Cable	Preamp			
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	98.107	45.50	-22.50	68.00	60.25	10.82	0.42	26.00 PEAK	176	291
2 @	98.107	44.02	-3.98	48.00	58.78	10.82	0.42	26.00 AVERAGE	176	291

Item 1, 2 are fundamental frequency at 98.1 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Temperature	24°C	Humidity	64%
Test Engineer	Beck Wu	Configurations	Channel 100 / Antenna without bundle of cable /Ant. 1

Vertical



Freq	Level	Over Limit	Limit	Read	Antenna	Cable	Preamp	Ant	Table	
									Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 @	107.897	44.50	-3.50	48.00	57.68	12.24	0.53	25.95	AVERAGE	301 103
2	107.897	44.87	-23.13	68.00	58.05	12.24	0.53	25.95	PEAK	301 103

Item 1, 2 are fundamental frequency at 107.9 MHz.

Horizontal


Freq	Level	Over Limit	Line	Read		Ant	Table		
				Antenna Factor	Cable Loss Factor			Pos	Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 @	107.914	45.48	-2.52	48.00	58.66	12.24	0.53	25.95	AVERAGE
2	107.914	46.40	-21.60	68.00	59.58	12.24	0.53	25.95	PEAK

Item 1, 2 are fundamental frequency at 107.9 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Temperature	24°C	Humidity	64%
Test Engineer	Beck Wu	Configurations	Channel 1 / Antenna with bundle of cable / Ant. 1


Vertical



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant Pos	Table Pos
		Limit	Line	Level	Factor	Loss	Factor		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
2	88.106	39.82	-8.18	48.00	56.41	8.98	0.55	26.12	AVERAGE
3	88.106	41.17	-26.83	68.00	57.76	8.98	0.55	26.12	PEAK

Item 2, 3 are fundamental frequency at 88.1 MHz.

Horizontal



Freq	Level	Over Limit	Limit Line	Read		Ant	Table		
				Antenna Factor	Cable Loss Factor			Pos	Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
2	88.106	36.19	-11.81	48.00	52.78	8.98	0.55	26.12	AVERAGE
3	88.106	37.26	-30.74	68.00	53.85	8.98	0.55	26.12	PEAK

Item 2, 3 are fundamental frequency at 88.1 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Temperature	24°C	Humidity	64%
Test Engineer	Beck Wu	Configurations	Channel 51 / Antenna with bundle of cable / Ant. 1

Vertical



Freq	Level	Over Limit	Line	Read		Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
				Antenna	Level Factor					
1	98.105	40.26	-7.74	48.00	55.01	10.82	0.42	26.00 AVERAGE	100	0
2	98.105	40.82	-27.18	68.00	55.58	10.82	0.42	26.00 PEAK	100	0

Item 1, 2 are fundamental frequency at 98.1 MHz.

Horizontal


Freq	Level	Over Limit	Limit	Read	Antenna	Cable	Preamp			Ant Pos	Table Pos
								Line	Factor		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB			cm	deg
1 !	98.113	45.12	-2.88	48.00	59.88	10.82	0.42	26.00	AVERAGE	190	310
2	98.113	46.51	-21.49	68.00	61.27	10.82	0.42	26.00	PEAK	190	310

Item 1, 2 are fundamental frequency at 98.1 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Temperature	24°C	Humidity	64%
Test Engineer	Beck Wu	Configurations	Channel 100 / Antenna with bundle of cable / Ant. 1

Vertical



Freq	Level	Over Limit	Limit Line	Read		Ant	Table		
				Antenna	Cable	Preamp			
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 @	107.911	45.84	-2.16	48.00	59.02	12.24	0.53	25.95	AVERAGE
2	107.911	46.46	-21.54	68.00	59.64	12.24	0.53	25.95	PEAK

Item 1, 2 are fundamental frequency at 107.9 MHz.

Horizontal


Freq	Level	Over Limit	Limit Line	Read		Ant	Table		
				Antenna Factor	Cable Loss Factor			Pos	Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 @	107.911	46.52	-1.48	48.00	59.70	12.24	0.53	25.95	AVERAGE
2	107.911	47.37	-20.63	68.00	60.55	12.24	0.53	25.95	PEAK

Item 1, 2 are fundamental frequency at 107.9 MHz.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level




Temperature	24°C	Humidity	64%
Test Engineer	Beck Wu	Configurations	Channel 1 / Antenna without bundle of cable / Ant. 1+Ant. 2

Vertical



Freq	Over Limit		ReadAntenna		Cable Preamp		Remark	Ant Pos	Table Pos	
	Level	Limit	Line	Level Factor	dB	dB				
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
88.106	39.18	-8.82	48.00	55.77	8.98	0.55	26.12	AVERAGE	217	250
88.106	40.03	-27.97	68.00	56.62	8.98	0.55	26.12	PEAK	217	250

Item 2, 3 are fundamental frequency at 88.1 MHz.

Horizontal


Freq	Level	Over Limit	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table	
									Pos	Pos	
MHz	dBuV/m	dB	dBuV/m	Line	Level Factor	dBuV	dB/m	dB	dB	cm	deg
2 !	88.106	43.80	-4.20	48.00	60.39	8.98	0.55	26.12	AVERAGE	182	141
3	88.106	44.31	-23.69	68.00	60.90	8.98	0.55	26.12	PEAK	182	141

Item 2, 3 are fundamental frequency at 88.1 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Temperature	24°C	Humidity	64%
Test Engineer	Beck Wu	Configurations	Channel 51 / Antenna without bundle of cable / Ant. 1+Ant. 2

Vertical



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table
		Limit	Line	Level	Factor	Loss	Factor		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	98.096	43.28	-4.72	48.00	58.03	10.82	0.42	26.00	AVERAGE
2	98.096	43.82	-24.18	68.00	58.58	10.82	0.42	26.00	PEAK

Item 1, 2 are fundamental frequency at 98.1 MHz.

Horizontal


Freq	Level	Over Limit	Limit Line	Read Antenna		Cable Preamp		Ant Pos	Table Pos		
				MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1 @	98.100	47.50	-0.50	48.00	62.25	10.82	0.42	26.00	AVERAGE	398	116
2	98.100	47.79	-20.21	68.00	62.54	10.82	0.42	26.00	PEAK	398	116

Item 1, 2 are fundamental frequency at 98.1 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Temperature	24°C	Humidity	64%
Test Engineer	Beck Wu	Configurations	Channel 100 / Antenna without bundle of cable / Ant. 1+Ant. 2

Vertical



Freq	Level	Over Limit	Limit Line	Read		Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	
				Antenna	Level Factor						
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	107.901	40.66	-7.34	48.00	53.85	12.24	0.53	25.95	AVERAGE	324	114
2	107.901	41.26	-26.74	68.00	54.44	12.24	0.53	25.95	PEAK	324	114

Item 1, 2 are fundamental frequency at 107.9 MHz.

Horizontal


Freq	Level	Over Limit	Limit Line	Read		Ant	Table			
				Antenna Factor	Cable Loss Factor			Pos	Pos	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
107.900	48.03	-19.97	68.00	61.22	12.24	0.53	25.95	PEAK	275	55
107.900	47.30	-0.70	48.00	60.48	12.24	0.53	25.95	AVERAGE	275	55

Item 1, 2 are fundamental frequency at 107.9 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Temperature	24°C	Humidity	64%
Test Engineer	Beck Wu	Configurations	Channel 1 / Antenna with bundle of cable / Ant. 1+Ant. 2


Vertical



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table
		Limit	Line	Level	Factor	Loss	Factor		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
2	88.110	39.65	-8.35	48.00	56.24	8.98	0.55	26.12	AVERAGE
3	88.110	40.47	-27.53	68.00	57.06	8.98	0.55	26.12	PEAK

Item 2, 3 are fundamental frequency at 88.1 MHz.

Horizontal



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
		Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
2 !	88.110	43.24	-4.76	48.00	59.83	8.98	0.55	26.12 AVERAGE	400	360
3	88.110	43.63	-24.37	68.00	60.22	8.98	0.55	26.12 PEAK	400	360

Item 2, 3 are fundamental frequency at 88.1 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Temperature	24°C	Humidity	64%
Test Engineer	Beck Wu	Configurations	Channel 51 / Antenna with bundle of cable / Ant. 1 + Ant. 2

Vertical



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table
		Limit	Line	Level	Factor	Loss	Factor		
		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	98.102	45.49	-2.51	48.00	60.24	10.82	0.42	26.00	AVERAGE
2	98.102	46.07	-21.93	68.00	60.83	10.82	0.42	26.00	PEAK

Item 1, 2 are fundamental frequency at 98.1 MHz.

Horizontal


Freq	Level	Over Limit	Line	Read		Cable	Preamp	Ant	Table
				Antenna	Level Factor				
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 @	98.093	47.75	-0.25	48.00	62.50	10.82	0.42	26.00	AVERAGE
2	98.095	49.17	-18.83	68.00	63.93	10.82	0.42	26.00	PEAK

Item 1, 2 are fundamental frequency at 98.1 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Temperature	24°C	Humidity	64%
Test Engineer	Beck Wu	Configurations	Channel 100 / Antenna with bundle of cable / Ant. 1+Ant. 2


Vertical



Freq	Level	Over Limit	Limit Line	Read		Ant	Table		
				Antenna	Cable			Pos	Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	107.894	41.96	-6.04	48.00	55.14	12.24	0.53	25.95	AVERAGE
2	107.894	42.13	-25.87	68.00	55.31	12.24	0.53	25.95	PEAK

Item 1, 2 are fundamental frequency at 107.9 MHz.

Horizontal



Freq	Level	Over Limit	Line	Read		Ant	Table		
				Antenna	Cable			Pos	Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 @	107.901	47.52	-0.48	48.00	60.70	12.24	0.53	25.95	AVERAGE
2	107.901	48.98	-19.02	68.00	62.16	12.24	0.53	25.95	PEAK

Item 1, 2 are fundamental frequency at 107.9 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

4.2. 20dB Spectrum Bandwidth Measurement

4.2.1. Limit

Emissions from the intentional radiator shall be confined within a band 200 kHz wide centered on the operating frequency.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 20dB Bandwidth
RB	10 kHz
VB	10 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 10 kHz and the video bandwidth of 10 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.
4. Maximum internal modulation was used since the radio does not have an external audio input. The modulator audio input level control was set to maximum to perform this test. All OBW measurements are made at maximum audio input levels.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of 20dB Spectrum Bandwidth

Temperature	24°C	Humidity	64%
Test Engineer	Leo Hung	Configurations	Channel 1/51/100


Frequency	20dB BW (kHz)	99% OBW (kHz)	Frequency range (MHz) $f_L > 88\text{MHz}$	Frequency range (MHz) $f_H < 108\text{MHz}$	Test Result
88.1 MHz	57.00	53.00	88.0740	-	Complies
98.1 MHz	58.00	57.00	-	-	Complies
107.9 MHz	77.00	74.00	-	107.9400	Complies

20 dB/99% Bandwidth Plot on 88.1 MHz




Date: 18.JUL.2006 16:18:00

20 dB/99% Bandwidth Plot on 98.1 MHz



Date: 18.JUL.2006 16:20:35

20 dB/99% Bandwidth Plot on 107.9 MHz



Date: 18.JUL.2006 16:21:36