

## Appendix 5

### RF Exposure Information

**FCC ID: NLB24023TX****Maximum transmitter power:**

Frequency (GHz)	Maximum peak output power (dBuV/m)	Output power (mW)
2.405	81.61	0.0435
2.440	82.81	0.0573
2.475	83.25	0.0634

**For FCC**

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq$  50 mm are determined by:[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot$  [ $\sqrt{f(\text{GHz})}$ ]  $\leq$  3.0 for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2

**Result:**

$$(0.0435/5) * \sqrt{2.405} = 0.0135 < 3.0$$

$$(0.0573/5) * \sqrt{2.440} = 0.0179 < 3.0$$

$$(0.0634/5) * \sqrt{2.475} = 0.0199 < 3.0$$

**Conclusion:**

No SAR is required.