



**Produkte**  
*Products*

<b>Prüfbericht-Nr.:</b> <i>Test Report No.:</i>	CN21QT36 001	<b>Auftrags-Nr.:</b> <i>Order No.:</i>	158229677	<b>Seite 1 von 12</b> <i>Page 1 of 12</i>
<b>Kunden-Referenz-Nr.:</b> <i>Client Reference No.:</i>	N/A	<b>Auftragsdatum:</b> <i>Order date:</i>	13.04.2021	
<b>Auftraggeber:</b> <i>Client:</i>	Dickie Spielzeug GmbH & Co. KG Werkstrasse 1, D-90765 Fuerth, Germany			
<b>Prüfgegenstand:</b> <i>Test Item:</i>	Low Power Transmitter (27.145MHz)			
<b>Bezeichnung / Typ-Nr.:</b> <i>Identification / Type No.:</i>	27221			
<b>Auftrags-Inhalt:</b> <i>Order content:</i>	Radio equipment testing			
<b>Prüfgrundlage:</b> <i>Test specification:</i>	FCC Part 15 Subpart C			
<b>Wareneingangsdatum:</b> <i>Date of receipt:</i>	13.04.2021			
<b>Prüfmuster-Nr.:</b> <i>Test sample No.:</i>	A003023348-005			
<b>Prüfzeitraum:</b> <i>Testing period:</i>	21.04.2021 - 21.04.2021			
<b>Ort der Prüfung:</b> <i>Place of testing:</i>	Hong Kong			
<b>Prüflaboratorium:</b> <i>Testing laboratory:</i>	TÜV Rheinland Hong Kong Ltd.			
<b>Prüfergebnis*:</b> <i>Test result*:</i>	Pass			
<b>geprüft von / tested by:</b>		<b>kontrolliert von / reviewed by:</b>		
				
05.07.2021	Felicia Chan / Assistant Engineer	05.07.2021	Sharon Li / Unit Senior Manager	
<b>Datum</b> <i>Date</i>	<b>Name / Stellung</b> <i>Name / Position</i>	<b>Unterschrift</b> <i>Signature</i>	<b>Datum</b> <i>Date</i>	<b>Name / Stellung</b> <i>Name / Position</i>
<b>Sonstiges / Other:</b> FCC ID: NLB27221TX				
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt Test item complete and undamaged		
<p>* Legende: 1 = sehr gut      2 = gut      3 = befriedigend      4 = ausreichend      5 = mangelhaft  P(ass) = entspricht o.g. Prüfgrundlage(n)      F(ail) = entspricht nicht o.g. Prüfgrundlage(n)      N/A = nicht anwendbar      N/T = nicht getestet</p> <p>Legend: 1 = very good      2 = good      3 = satisfactory      4 = sufficient      5 = poor  P(ass) = passed a.m test specification(s)      F(ail) = failed a.m test specification(s)      N/A = not applicable      N/T = not tested</p>				
<p>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</p> <p><i>This test report relates to the a. m test sample. Without permission of the test center this test report is not permitted to be duplicate in extracts. This test report does not entitle to carry any test mark.</i></p>				

## Test Summary

### **Radiated Emission of Carrier Frequency**

*Result: Pass*

### **Spurious Radiated Emissions**

*Result: Pass*

### **Bandwidth Measurement**

*Result: Pass*

## Contents

<b>List of Test and Measurement Instruments.....</b>	<b>4</b>
<b>General Product Information .....</b>	<b>5</b>
Product Function and Intended Use .....	5
Ratings and System Details.....	5
Independent Operation Modes.....	6
Submitted Documents.....	6
Related Submittal(s) Grants .....	6
<b>Test Set-up and Operation Mode .....</b>	<b>7</b>
Principle of Configuration Selection .....	7
Test Operation and Test Software.....	7
Special Accessories and Auxiliary Equipment.....	7
Countermeasures to achieve EMC Compliance .....	7
<b>Test Methodology .....</b>	<b>8</b>
Radiated Emission .....	8
Field Strength Calculation .....	8
<b>Test Results.....</b>	<b>9</b>
Radiated Emission of Carrier Frequency Subclause 15.227(a).....	9
Spurious Radiated Emissions Subclause 15.227(b).....	10
Bandwidth Measurement .....	12
<b>Appendix 1 Test Protocol</b>	
<b>Appendix 2 Test Setup</b>	
<b>Appendix 3 EUT External Photo</b>	
<b>Appendix 4 EUT Internal Photo</b>	
<b>Appendix 5 FCCID Label, Block Diagram, Schematics and User manual</b>	

## List of Test and Measurement Instruments

### Radiated Emission

Equipment	Manufacturer	Type	Cal. Date	Due Date
Semi-anechoic Chamber	Frankonia	Nil	5-Mar-21	5-Mar-22
Multi-functional Anechoic Chamber	Albatross	Nil	4-Jan-21	4-Jan-22
Test Receiver	R & S	ESU40	7-Oct-20	7-Oct-21
Active Loop Antenna	EMCO	6502	3-Nov-20	3-Nov-22
Bi-conical Antenna	R & S	HK116	15-Sep-20	15-Sep-22
Log Periodic Antenna	R & S	HL223	15-Sep-20	15-Sep-22
Coaxial cable	Harbour	SF118/11n/11n/1 2000.0	3-Aug-20	3-Aug-22

### Radio Test

Equipment	Manufacturer	Type	Cal. Date	Due Date
Signal and Spectrum Analyzer	R & S	FSV40	3-Nov-20	3-Nov-21

## General Product Information

### Product Function and Intended Use

The equipment under test (EUT) is a transmitter for a RC toy car operating at 27.145 MHz. The EUT has two control rods for commanding the forward, backward, left and right movement of the associated receiver.

#### FCC ID: NLB27221TX

Model	Product description
27221	Radio Control Toy Transmitter

### Ratings and System Details

	Transmitter
Frequency range	: 27.145MHz
Number of channels	: 1
Type of antenna	: Permanent wired antenna
Power supply	: Battery operated 3V
Ports	: none
Protection Class	: III

[www.tuv.com](http://www.tuv.com)

## **Independent Operation Modes**

The basic operation modes are:

- Remote Control: On and Off

For further information refer to User Manual

## **Submitted Documents**

The submitted documents are listed as follow:

- Circuit diagram
- Block diagram
- User manual
- Label artwork

## **Related Submittal(s) Grants**

This is a single application for certification of the transmitter.

## Test Set-up and Operation Mode

### Principle of Configuration Selection

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### Test Operation and Test Software

Test operation should refer to test methodology.

- There was no special software to exercise the device.

### Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

### Countermeasures to achieve EMC Compliance

- none

## Test Methodology

### Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360 °, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

### Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.  
R = Reading of Spectrum Analyzer in dBuV.  
AF = Antenna Factor in dB.  
CF = Cable Attenuation Factor in dB.  
FA = Filter Attenuation Factor in dB.  
PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.



## Test Results

### Radiated Emission of Carrier Frequency

### Subclause 15.227(a)

**RESULT:**
**Pass**

Test Specification : FCC Part 15 Subclause 15.227(a)  
 Test Method : ANSI 63.10-2013  
 Measurement Location : Semi Anechoic Chamber  
 Measurement Distance : 3m  
 :  
 Detector Function : Peak and Average  
 Measurement BW : 120 kHz  
 Supply Voltage : DC 3V

**Polarization: Vertical**

Detector function	Frequency (MHz)	Measured Field strength at 3m (dB $\mu$ V/m)	Delta to Limit (dB)
Peak	27.145	69.7	-30.3
Average	27.145	64.2	-15.8

**Polarization: Horizontal**

Detector function	Frequency (MHz)	Measured Field strength at 3m (dB $\mu$ V/m)	Delta to Limit (dB)
Peak	27.145	45.0	-55.0
Average	27.145	39.1	-40.9

**Limit**
**Subclause 15.227(a)**

Frequency within the band	Peak Emission		Average Emission	
	( $\mu$ V/m)	dB $\mu$ V/m	( $\mu$ V/m)	dB $\mu$ V/m
26.96-27.28 MHz	100,000	100.0	10,000	80.0

According to section 15.35(b), when average radiated emission measurements are specified in this part, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. Unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

## Spurious Radiated Emissions

## Subclause 15.227(b)

### RESULT:

Pass

Test Specification : FCC Part 15 Subclause 15.209  
 Test Method : ANSI 63.10-2013  
 Measurement Location : Semi Anechoic Chamber  
 Measurement Distance : 3m  
 Detector Function : Quasi Peak  
 Measurement BW : 120 kHz  
 Supply Voltage : DC 3V  
 Measuring Frequency Range : 30-1000MHz

#### Polarization: Vertical

Frequency (MHz)	Field strength at 3m (dBuV/m)	Limit at 3m (dBuV/m)	Delta to Limit (dB)
54.290	25.8	40.0	-14.2
81.435	14.6	43.5	-28.9
*108.580	9.4	43.5	-34.1
*135.726	9.6	43.5	-33.9
*162.871	11.6	43.5	-31.9
190.017	12.2	43.5	-31.3
217.162	9.3	46.0	-36.7
*244.308	9.8	46.0	-36.2
*271.453	10.9	46.0	-35.1
298.598	11.6	46.0	-34.4

#### Polarization: Horizontal

Frequency (MHz)	Field strength at 3m (dBuV/m)	Limit at 3m (dBuV/m)	Delta to Limit (dB)
54.290	6.5	40.0	-33.5
81.435	6.6	43.5	-36.9
*108.580	8.5	43.5	-35.0
*135.726	9.5	43.5	-34.0
*162.871	11.5	43.5	-32.0
190.017	12.1	43.5	-31.4
217.162	9.2	46.0	-36.8
*244.308	9.7	46.0	-36.3
*271.453	10.7	46.0	-35.3
298.598	11.6	46.0	-34.4

Remark: (1) ' \* ' indicates the frequency of the emissions fall into the restricted band as defined in Section 15.205(a). They comply with the radiated emission limits specified in Section 15.209.  
 (2) There is no spurious emission found between lowest oscillating frequency to 30 MHz.

**Limit****Subclause 15.209**

Radiated emissions, which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209.

Limit for Radiated Emission under Section 15.209:

<b>Frequency (MHz)</b>	<b>Field strength (<math>\mu\text{V/m}</math>)</b>	<b>Field strength (dB<math>\mu\text{V/m}</math>)</b>	<b>Measurement distance (m)</b>
30-88	100	$20 \cdot \log(100) = 40.0$	3
88-216	150	$20 \cdot \log(150) = 43.5$	3
216-960	200	$20 \cdot \log(200) = 46.0$	3
960-2500	500	$20 \cdot \log(500) = 54.0$	3

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector and above 1000 MHz are based on the measurements employing an average detector.

[www.tuv.com](http://www.tuv.com)

## Bandwidth Measurement

Port of Testing	:	Antenna port
Detector Function	:	Peak
Supply Voltage	:	DC 9V

The field strength of any emissions appearing at the lower edge 26.96 MHz and upper edge 27.28 MHz are 36.83 dB and 34.87 dB below the carrier respectively.

For test results refer to Appendix 1.