



47 CFR PART 15 SUBPART B

TEST REPORT

of

Portable GNSS receiver

Model Name: Portable GNSS receiver

Trade Name: MobileMapper 10

Brand Name: ASHTECH


Report No.: SH11030016E01

FCC ID: NZI802140

prepared for

ASHTECH S.A.S

ZAC LA FLEURIAYE BP 60433 RUE THOMAS EDISON
44474 CARQUEFOU CEDEX FRANCE



prepared by

Shenzhen Electronic Product Quality Testing Center

Morlab Laboratory

3/F, Electronic Testing Building, Shahe Road, Xili,
Nanshan District, Shenzhen, 518055 P. R. China

Tel: +86 755 86130398

Fax: +86 755 86130218



CTIA Authorized Test Lab.
LAB CODE 20081223-00

NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. Any objections should be raised to us within thirty workdays since the date of issue.

TABLE OF CONTENTS

1. TEST CERTIFICATION.....	3
2. GENERAL INFORMATION	4
2.1 EUT Description	4
2.2 Test Standards and Results	5
2.3 Facilities and Accreditations.....	5
2.3.1 Facilities	5
2.3.2 Test Environment Conditions.....	5
3. TEST CONDITIONS SETTING	6
3.1 Test Mode	6
3.2 Description Of Support Units.....	6
3.3 Test Setup and Equipments List.....	7
3.3.1 Conducted Emission	7
3.3.2 Radiated Emission.....	8
4. 47 CFR PART 15B REQUIREMENTS	9
4.1 Conducted Emission.....	9
4.1.1 Requirement.....	9
4.1.2 Test Description	9
4.1.3 Test Result.....	9
4.2 Radiated Emission	12
4.2.1 Requirement.....	12
4.2.2 Test Description	12
4.2.3 Test Result.....	12

1. TEST CERTIFICATION

Equipment under Test: Portable GNSS receiver

Trade Name: MobileMapper 10

Brand Name: ASHTECH

Model Name: Portable GNSS receiver

FCC ID: NZI802140

Applicant: ASHTECH S.A.S

Applicant Address: ZAC LA FLEURIAYE BP 60433 RUE THOMAS EDISON 44474
CARQUEFOU CEDEX FRANCE

Manufacturer: Beijing UniStrong Science & Technology Co., Ltd

Manufacturer Address: 6F East, A2 Building, #9 Jiuxianqiao East Road, Chaoyang
District, Beijing 100015, China

Test Standards: 47 CFR Part 15 Subpart B

ANSI C63.4-2003

ICES-003 Issue 4

Test Date(s): 2011-3-20~2011-3-25

Test Result: PASS

* We Hereby Certify That:

The equipment under test was tested by Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the requirement of related FCC rules.

The test results of this report only apply for the tested sample equipment identified above. The test report shall be invalid without all the signatures of the test engineer, the reviewer and the approver.

Tested by:

Zhang Wenjie
Zhang Wenjie

Dated: 2011.4.1

Reviewed by:



Dated: 2011.4.1

Approved by:

Wei Bei
Wei Bei

Dated: 2011.4.1

2. GENERAL INFORMATION

2.1 EUT Description

EUT Type.....: Portable GNSS receiver
Model Name: Portable GNSS receiver
Hardware Version: v2.0
Software Version: 01.001.1chs
Frequency: GSM850/900/1800/1900 MHz ,ISM 2.4GHz
Modulation Type.....: GSM/GPRS : GMSK
EDGE:8PSK
Bluetooth (1Mbps) : GFSK
Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK
Bluetooth EDR (3Mbps) : 8-DPSK
802.11b : DSSS (BPSK / QPSK / CCK)
802.11g : OFDM (BPSK / QPSK / 16QAM / 64QAM)
Power Supply.....: Battery
Brand name: DBK
Mode Name.: MG-4LH
Capacitance: 3000mAh
Rated voltage: 3.7V
Charge limited: 4.2V
Manufacturer: SHENZHEN DBK ELECTRONICS CO., LTD
AC Adapter (Charger for Battery)
Brand name: PHIHONG
Mode Name.: PSAI05R-050Q
Rated Input: AC 100-240V,300mA,50/60Hz
Rated Output: DC 5V,1000mA
Manufacturer: PHIHONG TECHNOLOGY CO.,LTD

Note 1: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2.2 Test Standards and Results

EMISSION			
Standard	Item	Result	Remarks
FCC 47 CFR Part 15 Subpart B ICES-003 Issue 4 ANSI C63.4-2003	Conducted (Main Port)	PASS	Meet Class B limit
	Radiated	PASS	Meet Class B limit

2.3 Facilities and Accreditations

2.3.1 Facilities

Shenzhen Electronic Product Quality Testing Center Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Laboratories (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659.

All measurement facilities used to collect the measurement data are located at Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen 518055 CHINA. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

2.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	20 – 25
Relative Humidity (%):	40 – 60
Atmospheric Pressure (kPa):	106

3. TEST CONDITIONS SETTING

3.1 Test Mode

The test modes of the EUT are showed as below:

Mode 1. EUT+PC Mode

The EUT configuration of the emission test is EUT + Micro SD card + Battery + +PC.

In this test mode, a connection was established between the EUT and a PC; date was transmitted between EUT and the PC, and maintained during the measurement.

3.2 Description Of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


No.	Equipment	Model No.	Serial No.	Trade Name
1	Notebook	HP520	CDP7450MTI	HP
2	Micro SD card	1#	1#	N/A

Note: Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

3.3 Test Setup and Equipments List

3.3.1 Conducted Emission

A. Test Setup:




The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides $50\Omega/50\mu\text{H}$ of coupling impedance for the measuring instrument. The Common Antenna is used for the call between the EUT and the System Simulator (SS). A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Rohde&Schwarz	ESCI3	100666	2010.09	1year
LISN	Rohde&Schwarz	ENV216	812744	2010.09	1year
System Simulator	Rohde&Schwarz	CMU200	105571	2010.09	1year
Personal Computer	Lenovo	(n.a.)	(n.a.)	(n.a.)	(n.a.)

3.3.2 Radiated Emission

A. Test Setup:



The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower. The Common Antenna is used for the call between the EUT and the System Simulator (SS).

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Rohde&Schwarz	ESCI3	100666	2010.09	1year
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2010.09	1year
Test Antenna - Bi-Log	Rohde&Schwarz	HL562	100385	2010.09	1year
System Simulator	Rohde&Schwarz	CMU200	105571	2010.09	1year
Personal Computer	Lenovo	(n.a.)	(n.a.)	(n.a.)	(n.a.)

4. 47 CFR PART 15B REQUIREMENTS

4.1 Conducted Emission

4.1.1 Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5- 30	60	50

NOTE:

- a) The limit subjects to the Class B digital device.
- b) The lower limit shall apply at the band edges.
- c) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

4.1.2 Test Description

See section 3.3.1 of this report.


4.1.3 Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.


**A. Test Verdict Recorded for Suspicious Points:**

Frequency (MHz)	QuasiPeak (dB μ V)	Meas. Time (ms)	Band width (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.351488	50.5	150.000	9.000	N	9.7	8.3	58.8	PASS
0.452231	45.9	150.000	9.000	N	9.7	10.9	56.8	PASS
0.474619	45.3	150.000	9.000	N	9.6	11.1	56.4	PASS
0.515662	45.9	150.000	9.000	N	9.7	10.1	56.0	PASS
0.571631	52.4	150.000	9.000	N	9.7	3.6	56.0	PASS
0.631331	49.6	150.000	9.000	N	9.7	6.4	56.0	PASS
0.351488	49.3	150.000	9.000	L	9.7	9.5	58.8	PASS
0.500738	52.5	150.000	9.000	L	9.7	3.5	56.0	PASS
0.549244	46.0	150.000	9.000	L	9.7	10.0	56.0	PASS
0.567900	47.8	150.000	9.000	L	9.7	8.2	56.0	PASS
0.702225	44.9	150.000	9.000	L	9.7	11.1	56.0	PASS
2.385019	45.3	150.000	9.000	L	9.8	10.7	56.0	PASS

Frequency (MHz)	Average (dB μ V)	Meas. Time (ms)	Band width (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.198506	40.1	150.000	9.000	N	9.6	13.4	53.5	PASS
0.351488	41.1	150.000	9.000	N	9.7	7.6	48.7	PASS
0.452231	37.0	150.000	9.000	N	9.7	9.8	46.8	PASS
0.474619	37.1	150.000	9.000	N	9.6	9.3	46.4	PASS
0.571631	44.5	150.000	9.000	N	9.7	1.5	46.0	PASS
0.631331	40.2	150.000	9.000	N	9.7	5.8	46.0	PASS
0.247012	40.9	150.000	9.000	L	9.6	10.7	51.6	PASS
0.500738	45.6	150.000	9.000	L	9.7	0.4	46.0	PASS
0.567900	43.4	150.000	9.000	L	9.7	2.6	46.0	PASS
0.627600	44.5	150.000	9.000	L	9.7	1.5	46.0	PASS
1.556681	42.6	150.000	9.000	L	9.8	3.4	46.0	PASS
2.385019	41.0	150.000	9.000	L	9.8	5.0	46.0	PASS

B. Test Plot:

(Plot: L Phase)



(Plot: N Phase)

4.2 Radiated Emission

4.2.1 Requirement

According to FCC section 15.109, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength	
	µV/m	dB µV/m
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

NOTE:


- Field Strength (dB µV/m) = $20 \cdot \log[\text{Field Strength } (\mu\text{V/m})]$.
- In the emission tables above, the tighter limit applies at the band edges.

4.2.2 Test Description


See section 3.2.2 of this report.

4.2.3 Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

A. Test Plot:

(Plot: Test Antenna Vertical)



(Plot: Test Antenna Horizontal)

**** END OF REPORT ****