Programming the HomeLink® buttons

& DANGERDangerto life from toxic exhaust gasin enclosedspaces

Combustion engines emit toxic exhaust gases suchas carbon monoxide. Inhaling these exhaust gases is hazardous to health and leads to poisoning.

- Never leave the engine or, if present, the stationary heater running in an enclosed spacewithout sufficient ventilation.
- WARNINGRiskof injury by becoming trapped when opening and closing a garagedoor

Whenyou operate or program a garagedoor with an integrated garagedoor opener, persons can become trapped or struck by the garagedoor if they standwithin its range of movement.


Always make sure that nobody is within the range of the garagedoor's movement. Only operate the following doors using the garage door opener:

- R Doors with a safety stop and reversing feature
- R Doorsthat complywith the applicable safety standards

Before programming the garage door opener, park the vehicle outside the garage. Ensure that the vehicle is switched on but not started.

Requirements:

- R Thevehicle has been parked outside the garageor outside the range of movement of the door.
- R Thevehicle is switched on.
- R Thevehicle has not been started.
- R Theoriginal remote control for the garage door is used.
- % Thegaragedoor opener function is always available when the vehicle is switched on.



Programming procedure: press the button to be programmed (outlined in 1, 1st, 2nd, or 3rd button) and then release it.

If the selected button is not programmed, the indicator lamp 2 flashes oranges lowly.

- Moreover Toreprograma button that has already been programmed, press the corresponding button until the indicator lamp 2 starts to flash oranges lowly. This may take up to 20 seconds.
- Point the remote control 3 from a distance of between 5 cm and 30 cm underneath the mirror towards the first, second or third button.
- Press and hold the button on the remote control 3 until one of the following signals appears:
 - R Theindicator lamp 2 lights up greencontinuously. Programming is complete.
 - R The indicator lamp 2 flashes green. Programmingwas successful.

Theselected HomeLink® button is now programmed.

- # Test the programming: press and hold the HomeLink® button for two seconds.
- Releasethe HomeLink® button and, after three seconds, press and hold it again for two seconds.

- # Repeatthis process once more (three times in total).
- % If youhavea garagedoor system with fixed code or QuickTrain technology, pressing the programmed HomeLink® button opens or closes the garagedoor.
 If the garagedoor is not working and the indicator lamp 2 is flashing quickly, you must perform rolling code synchronisation (/ page 3).

<u>Performing rolling code synchronisation (if required)</u>

If the garagedoor is not working and the indicator lampin the inside mirror is flashing quickly, your garagedoor systemoperates with rolling code. In this case, you must perform rolling code synchronisation.

Information on rolling code synchronisation: In the following steps, you must pressthe "Learn" "Program" or "Smart" button on the garagedoor openerin yourgarage. Please note that the names of the buttons may vary depending on the

manufacturer. For more information, refer to the owner's manual for the garagedoor opener.

- R Have someone help you so that the steps can be carried out faster and more easily.
- R You may need a ladder or something of similar stability to help you reach the buttons. Do not stand on yourvehicleto carry out these steps!
- R Certain timings must be observed for the following steps. It maybe necessary to try carrying out the steps several times.
- Find the "Learn", "Program" or "Smart" button on the garage door opener in the garage. The shape and colour of the buttons vary depending on the manufacturer.
- # Press the "Learn", "Program" or "Smart" button.
 - Depending on the manufacturer of the garage door opener, an indicator lamp may start to flash.
- Within 30 seconds, press and hold the Home-Link® button in the vehiclefor three seconds.
- Pressthe HomeLink® button again and hold it for three seconds.

4 Garagedoor opener (HomeLink®)

- Repeatthis process once more (three times in total).
 - Rolling code synchronisation is now complete. HomeLink® should now activate your garage door equippedwith a rolling code.
- Pleasenote that somegaragedoor openers mayrequire the HomeLink® button to be pressed for different lengths of time during the synchronisation process. Observe the owner's manual for the garage door manufacturer.
 - More information can be found on the https://www.homelink.com

Resolving problems when programming Home-Link®

- Ensure that the remote control used for programming is approved by the manufacturer of the garage door opener and activates the door.
- Replace the batteries in the remote control 5.

- Hold the remote control 5 at various angles in front of the inside mirror from a distance of between5 cmand 30 cm.
 - Hold each position for at least 25 seconds before trying another position.
- Hold the remotecontrol 5 at the same angles at various distances in front of the inside mirror. You should test every position for at least 25 seconds before trying another position.
- Onremotecontrols that only transmit for a limited period, press the button 6 on the remotecontrol 5 againbefore transmission ends.
- Support and additional programming information:
 - R United States (U.S.): call the free Home-Link® hotline on 1-800-355-3515
 - R Visit the https://www.homelink.com

Deleting the HomeLink® buttons

- Pressand hold buttons 1 and 3.Theindicator lamp 4 lights up orange.
- # If the indicator lamp4 flashes green, release buttons 1 and 3.
 Thismaytake up to 10 seconds.
 - Theentire memoryhas been deleted.

<u>Special programmingmodes(if required</u>

D-mode: A special programming mode is required for some devices available on the market. Only usethis if this is expressly stated in the programming instructions in the owner's manual for the deviceor on the https://www.homelink.com.

Country-specific information for regulatory radio components

Information regarding modifications to radio components Modifications to radio components may invalidate the general operating permit for the radio component in question. The radio component manufacturer shall accept no responsibility for such modi-fications.

Information regarding crossing national borders You must observe the radio regulatory provisions for the country in which you are currently driving when operating the vehicle.

Wireless vehicle components



FCC

This device complies with FCC rules part 15 and Innovation, Science, and Economic Development Canada RSS-210. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference that may be received including interference that may cause undesired operation. WARNING: The transmitter has been tested and complies with FCC and ISED rules. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the device.

This equipment complies with FCC and ISED radiation exposure limits set forth for an uncontrolled environment. End Users must follow the specific operating instructions for satisfying RF exposure compliance. This transmitter must be at least 20 cm from the user and must not be co-located or operating in conjunction with any other antenna or transmitter.

IC

Cet appareil est conforme aux règlements de la FCC, section 15, et au CNR-210 d'Innovation, Sciences et Développement économique Canada. Le fonctionnement est assujetti aux deux conditions suivantes : (1) cet appareil ne doit pas causer d'interférences nuisibles et (2) cet appareil doit accepter toute interférence reçue, y compris celle qui pourrait entraîner un dysfonctionnement. MISE EN GARDE : L'émetteur a subi des tests et est conforme aux règlements de la FCC et d'ISDE. Les changements ou modifications non approuvés explicitement par la partie responsable de la conformité pourraient rendre caduque l'autorisation de l'utilisateur de se servir du dispositif.

Cet appareil est conforme aux limites d'exposition aux radiations de la FCC et d'ISDE établies pour un environnement non contrôlé. Les utilisateurs finaux doivent respecter les instructions d'utilisation spécifiques pour satisfaire aux exigences de conformité aux expositions de RF. L'émetteur doit se trouver à 20 cm au minimum de l'utilisateur et ne doit pas être situé au même endroit que tout autre émetteur ou antenne ni fonctionner avec un autre émetteur ou antenne.

Country-specific information for regulatory radio components

Information regarding modifications to radio components

Modifications to radio components mayinvalidate the general operating permit for the radio component in question. The radio component manufacturer shall accept no responsibility for such modifications.

Information regarding crossing national borders You must observe the radio regulatory provisions for the country in which you are currently driving when operating the vehicle.

Wireless vehicle components For Mexico only:





The following information applies to all wireless components of the vehicle and of the information systems and communication devices integrated in the vehicle:

Operation of this device is subject to the following two conditions: (1) this devicemust not cause harmful interference, and (2) this devicemust accept any interference received, including interference that may cause undesired operation.