

Output Power by Radio Configuration

		RC1	RC2	RC3		RC4		RC5	
Spreading Rate		1	1	1		1		3	
Rate Set, bps (R-FCH)									
Code Rate		$\frac{1}{3}$	$\frac{1}{2}$	$\frac{1}{4}$	$\frac{1}{2}$	$\frac{1}{4}$		$\frac{1}{4}$	$\frac{1}{3}$
Modulation		64-ray orthogonal	64-ray orthogonal	BPSK + pilot		BPSK + pilot		BPSK + pilot	
Service Option	Type	Power (dBm)	Power (dBm)	Power (dBm)		Power (dBm)		Power (dBm)	
1	Voice	N/S	---	N/S		N/S		---	
2	Loop Back	25.03	---	25.00		24.99		---	
3	Voice	25.10	---	25.10		25.06		---	
9	Loop Back	---	25.15	---		---		---	
17	Voice	---	N/S	---		---		---	
32	+F-SCH	---	---	N/S		N/S		---	
32	+SCH	---	---	N/S		N/S		---	
33	---	---	---	---		---		---	
33	+F-SCH	---	---	---		---		---	
55	Loop Back	25.08	25.13	24.94		25.00		---	
032768	Voice	---	N/S	---		---		---	