

FCC PART 15 Subpart C
EMI MEASUREMENT AND TEST REPORT
For
Shenzhen Baoan Hantong Electronics Factory

Block 11 & 12, Jinbi Industrial Area,
Hwangtain, Baoan, Shenzhen, China

FCC ID: OK8ATC2488HT03

2003-06-09

This Report Concerns: <input checked="" type="checkbox"/> Original Report	Equipment Type: 2.4GHz Cordless Caller ID Telephone System
Test Engineer: Ming Jing / 	
Report Number: R0304234	
Test Date: 2003-05-11	
Reviewed By: Ling Zhang / 	
Prepared By: Bay Area Compliance Laboratory Corporation 230 Commercial Street Sunnyvale, CA 94085 Tel: (408) 732-9162 Fax: (408) 732 9164	

Note: This test report is specially limited to the above client company and the product model only. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

TABLE OF CONTENTS

1 - GENERAL INFORMATION.....	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 OBJECTIVE	4
1.3 RELATED SUBMITTAL(S)/GRANT(S).....	4
1.4 TEST METHODOLOGY	4
1.5 TEST FACILITY	4
1.6 TEST EQUIPMENT LIST	5
1.7 LOCAL SUPPORT EQUIPMENT.....	5
1.8 EXTERNAL I/O CABLING LIST AND DETAILS	6
2 - SYSTEM TEST CONFIGURATION.....	7
2.1 DESCRIPTION OF TEST CONFIGURATION	7
2.2 EQUIPMENT MODIFICATIONS	7
2.3 CONFIGURATION OF TEST SYSTEM.....	8
2.4 TEST SETUP BLOCK DIAGRAM	8
3 - SUMMARY OF TEST RESULTS.....	9
4 - CONDUCTED OUTPUT POWER MEASUREMENT.....	10
4.1 STANDARD APPLICABLE	10
4.2 MEASUREMENT PROCEDURE.....	10
4.3 MEASUREMENT RESULT	10
5 - 6 DB BANDWIDTH.....	14
5.1 STANDARD APPLICABLE	14
5.2 MEASUREMENT PROCEDURE.....	14
5.3 MEASUREMENT DATA.....	14
6 - SPURIOUS EMISSION.....	18
6.1 STANDARD APPLICABLE	18
6.2 MEASUREMENT PROCEDURE.....	18
6.3 MEASUREMENT DATA.....	18
7 - 100 KHZ BANDWIDTH OF BAND EDGES MEASUREMENT.....	22
7.1 STANDARD APPLICABLE	22
7.2 MEASUREMENT PROCEDURE.....	22
7.3 TEST RESULTS	22
8 - POWER SPECTRAL DENSITY.....	27
8.1 STANDARD APPLICABLE	27
8.2 MEASUREMENT PROCEDURE.....	27
8.3 TEST RESULTS	27
9 - ANTENNA REQUIREMENT.....	31
9.1 STANDARD APPLICABLE	31
9.2 ANTENNA CONNECTED CONSTRUCTION	31
10 - RF SAFETY REQUIREMENTS TO 2.1091	32
11 - SPURIOUS RADIATED EMISSION DATA	33
11.1 MEASUREMENT UNCERTAINTY	33
11.2 EUT SETUP	33
11.3 SPECTRUM ANALYZER SETUP	33
11.4 TEST PROCEDURE	34
11.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	34
11.6 SUMMARY OF TEST RESULTS	34
12 – CONDUCTED EMISSIONS	39

12.1 MEASUREMENT UNCERTAINTY	39
12.2 EUT SETUP	39
12.3 SPECTRUM ANALYZER SETUP	39
12.4 TEST PROCEDURE	39
12.5 SUMMARY OF TEST RESULTS	40
12.6 CONDUCTED EMISSIONS TEST DATA	40
12.7 PLOT OF CONDUCTED EMISSIONS TEST DATA	40

1 - GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Shenzhen Baoan Hantong Electronics Factory's product, FCC ID: OK8ATC2488HT03, Model No.: ATC2488 or the "EUT" as referred to in this report is a 2.4GHz Digital Spread Spectrum Technology Cordless Caller ID Telephone. The EUT was composed of two parts, one is the base which measures approximately 4.75" L x 1.75" W x 5.5" H, and the other is the handset which measures 2.0" L x 1.25" W x 5.5" H.

The base unit of the EUT was fed by the Shenzhen Baoan AC/DC Adapter, M/N: U090030D.

1.2 Objective

This type approval report is prepared on behalf of *Shenzhen Baoan Hantong Electronics Factory* in accordance with Part 2, Subpart J, Part 15, Subparts A, B, and C of the Federal Communication Commissions rules.

The objective of the manufacturer is to demonstrate compliance with FCC rules for Output Power, Antenna Requirements, 6 dB Bandwidth, power density, 100 kHz Bandwidth of Band Edges Measurement, and Conducted and Spurious Radiated Emission.

1.3 Related Submittal(s)/Grant(s)

No Related Submittals.

1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4 –1992, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory, Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

1.5 Test Facility

The Open Area Test site used by Bay Area Compliance Laboratory Corporation to collect radiated and conducted emission measurement data is located in the back parking lot of the building at 230 Commercial Street, Sunnyvale, California, USA.

Test site at Bay Area Compliance Laboratory Corporation has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-1992.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-1298 and R-1234. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratory Corporation is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (NVLAP). The scope of the accreditation covers the FCC Method - 47 CFR Part 15 - Digital Devices, CISPR 22: 1997, and AS/NZS 3548: Electromagnetic Interference - Limits and Methods of Measurement of Information Technology Equipment test methods under NVLAP Lab Code 200167-0.

1.6 Test Equipment List

Manufacturer	Description	Model	Serial Number	Cal. Due Date
HP	Spectrum Analyzer	8568B	2517A01610	2003-10-30
HP	Spectrum Analyzer	8593A	29190A00242	2004-05-01
HP	Amplifier	8447E	1937A01054	2004-05-01
HP	Quasi-Peak Adapter	85650A	2521A00718	2004-05-01
Com-Power	Biconical Antenna	AB-100	14012	2004-05-01
Com-Power	LISN	LI-200	12005	2004-03-28
Com-Power	LISN	LI-200	12008	2004-03-28
Com-Power	Log Periodic Antenna	AL-100	16091	2004-05-01
Com-Power	Log Periodic Antenna	AB-900	15049	2004-05-01
Rohde & Schwarz	EMI Test Receiver	ESPI	1147 8007 07	2003-12-03
Agilent	Spectrum Analyzer (9KHz – 40GHz)	8564E	08303	2003-08-01
Agilent	Spectrum Analyzer (9KHz – 50GHz)	8565EC	06042	2004-05-03
HP	Amplifier (1-26.5GHz)	8449B	3147A00400	2004-03-14
A.H.System	Horn Antenna (700MHz-18GHz)	SAS-200/571	261	2003-05-31

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. certifies that all calibration has been performed using suitable standards traceable to the NIST.

1.7 Local Support Equipment

Manufacturer	Description	Model	Serial Number	FCC ID
TELTON CORP.	SIMULATOR	TLS-3B-01	80071	DOC
Panasonic	Telephone	KX-T3175	6IBTB142741	ACJMLA-75986-MT-E

1.8 External I/O Cabling List and Details

Cable Description	Length (M)	From	To
None-Shielded Telephone Cable	2.0	RJ45 Port/EUT	Telephone Simulator RJ45 Port
None-Shielded Telephone Cable	2.0	RJ45 Port/Simulator	Telephone RJ45 Port/Panasonic

2 - SYSTEM TEST CONFIGURATION

2.1 Description of Test Configuration

The EUT was configured for testing in a typical fashion (as normally used by a typical user).

Handset being tested: The Cordless Telephone - Handset, Model ATC2488 was placed on the wooden table and tested in three orthogonal axis. The Low, middle, and high channels were tested. The handset was transmitting to and receiving from the base unit. The EUT was investigated for emissions while off hook. The radiated data was taken in this mode of operation. All initial and final investigations were performed with the EMI receiver in manual mode scanning the frequency range continuously.


Base being tested: The Cordless Telephone – Base, Model ATC2488 was placed on the wooden table. The Low, middle, and high channels were tested. The base was connected to the line simulator and an AC adapter via its Tel Line and power ports, respectively. The base was transmitting and receiving from the handset. The conducted as well as radiated data were taken in this mode of operation. All initial and final investigations were performed with the EMI receiver in manual mode scanning the frequency range continuously. The cables were bundled and routed as shown in the 2.3.

2.2 Equipment Modifications

No modification(s) was made by BACL Corp. to ensure the EUT complies with the applicable limits and standards.

2.3 Configuration of Test System


Radiated Setup for Base




Radiated Setup for Handset

2.4 Test Setup Block Diagram

Radiated Setup for Base



Radiated Setup for Handset



3 - SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT	Section Reference
§ 15.205	Restricted Bands	Compliant	Section 12
§15.203	Antenna Requirement	Compliant	Section 9
§15.207 (a)	Conducted Emission	Compliant	Section 12
§15.209 (a)	Radiated Emission	Compliant	Section 11
§15.209 (f)	Spurious Emission	Compliant	Section 6
§15.247 (a) (2)	6 dB Bandwidth	Compliant	Section 5
§15.247 (b) (3)	Peak Output Power	Compliant	Section 4
§15.247 (b) (5)	RF Exposure	Compliant	Section 10
§ 15.247 (c)	100 kHz Bandwidth of Frequency Band Edges	Compliant	Section 7
§15.247 (d)	Peak Power Spectral Density	Compliant	Section 8

4 - CONDUCTED OUTPUT POWER MEASUREMENT

4.1 Standard Applicable

According to §15.247(b) (3), for systems using digital modulation, the maximum peak output power of the intentional radiator shall not exceed 1 Watt.



4.2 Measurement Procedure



1. Place the EUT on the turntable and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.


4.3 Measurement Result

Please refer to the attached pictures for more information.

Unit	Channel	Output Power (dBm)	Output Power (W)	Standard (W)	Result
Base	Low	1.00	0.0013	≤ 1W	Compliant
Base	Mid	2.50	0.0018	≤ 1W	Compliant
Base	High	2.67	0.0018	≤ 1W	Compliant
Handset	Low	0.00	0.0010	≤ 1W	Compliant
Handset	Mid	1.83	0.0015	≤ 1W	Compliant
Handset	High	2.33	0.0017	≤ 1W	Compliant







5 - 6 DB BANDWIDTH

5.1 Standard Applicable

According to §15.247(a)(2), for digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.



5.2 Measurement Procedure



1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



5.3 Measurement Data

Please refer to the following pages.

Unit	Channel	6 DB Bandwidth (MHz)	6 DB Bandwidth (kHz)	Standard (kHz)	Result
Base	Low	1.00	1000	≥ 500	Compliant
Base	Mid	0.97	970	≥ 500	Compliant
Base	High	1.27	1270	≥ 500	Compliant
Handset	Low	1.00	1000	≥ 500	Compliant
Handset	Mid	1.03	1030	≥ 500	Compliant
Handset	High	1.03	1030	≥ 500	Compliant







6 - SPURIOUS EMISSION

6.1 Standard Applicable

According to §15.209 (a), except as provided elsewhere in the subpart of 15.209, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Measurement	Field strength (microvolts/meter)	distance (meters)
0.009-0.490.....	2400/F(kHz)	300	
0.490-1.705.....	24000/F(kHz)	30	
1.705-30.0.....	30	30	
30-88.....	100 **	3	
88-216.....	150 **	3	
216-960.....	200 **	3	
Above 960.....	500	3	

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.



6.2 Measurement Procedure



1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the SA on Max-Hold Mode, and then keep the EUT in transmitting mode. Record all the signals from each channel until each one has been recorded.
4. Set the SA on View mode and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.



6.3 Measurement Data

Please refer to the following pages.

Spurious Emission	Test Result (base and handset)
Low Channel	Compliant
Middle Channel	Compliant
High Channel	Compliant







7 - 100 KHZ BANDWIDTH OF BAND EDGES MEASUREMENT

7.1 Standard Applicable

According to §15.247(c), if *any* 100 kHz bandwidth outside these frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in § 15.209(a).



7.2 Measurement Procedure



1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



7.3 Test Results



Please refer to the following pages.

Band Edge Bandwidth	Test Result (base and handset)
Low Channel	Compliant
Middle Channel	Compliant
High Channel	Compliant









8 - POWER SPECTRAL DENSITY

8.1 Standard Applicable

According to §15.247 (d), for digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.



8.2 Measurement Procedure



1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of SA on any frequency be measured and set SA to 1MHz span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
4. Repeat above procedures until all frequencies measured were complete.



8.3 Test Results

Please refer to the following plot(s).

Power Density	Test Result (Base and Handset)
Low Channel	Compliant
Middle Channel	Compliant
High Channel	Compliant







9 - ANTENNA REQUIREMENT

9.1 Standard Applicable

For intentional device, according to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to § 15.247 (1), if transmitting antennas of directional gain greater than 6 dBi are used the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

9.2 Antenna Connected Construction

The directional gain of antenna used for transmitting is 0 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Please see EUT photo for details.

10 - RF SAFETY REQUIREMENTS TO 2.1091

According to section 3 of Supplement C to OET Bulleting 65, Part 15 Transmitters are categorically excluded from Routine Environmental Evaluation by measurement or precise computations unless otherwise required by the Commissions.

According to §15.247(b)(5) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1093 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-15000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

MPE Prediction

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

For handset of the EUT:

Maximum peak output power at antenna input terminal: 2.67 (dBm)

Maximum peak output power at antenna input terminal: 1.85 (mW)

Antenna Gain (typical): 0 (dBi)

Maximum antenna gain: 1 (numeric)

Prediction distance: 3 (cm)

Predication frequency: 2400 (MHz)

MPE limit for uncontrolled exposure at prediction frequency: 1 (mW/cm²)

Power density at predication frequency: 0.016 (mW/cm²)

Test Result

The predicted power density level at 3 cm is 0.016 mW/cm². This is below the uncontrolled exposure limit of 1mW/cm² at 2400 MHz.

11 - SPURIOUS RADIATED EMISSION DATA

11.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at BACL is ± 4.0 dB.

11.2 EUT Setup

The radiated emission tests were performed in the open area 3-meter test site, using the setup in accordance with the ANSI C63.4 - 1992. The specification used was the FCC 15 Subpart C limits.

The base of the EUT was connected to a 120 VAC / 60 Hz power source.

The spacing between the peripherals was 10 centimeters.

Input / Output cables were draped along the edge of the test table and bundle when necessary.

11.3 Spectrum Analyzer Setup

According to FCC Rules, 47 CFR §15.33 (a) (1), the system was tested to 25000 MHz.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

<u>Frequency Range</u>	<u>RBW</u>	<u>Video B/W</u>
Below 30MHz	10kHz	10KHz
30 – 1000MHz	100kHz	100kHz
Above 1000MHz	1MHz	1MHz

11.4 Test Procedure

For the radiated emissions test, both the EUT and all support equipment power cords were connected to the AC floor outlet since the power supply used in the EUT did not provide an accessory power outlet.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB μ V of specification limits), and are distinguished with a "Qp" in the data table.

11.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB μ V means the emission is 7dB μ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Class B Limit}$$

11.6 Summary of Test Results

According to the data in section 11.7, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.207, and 15.247, and had the worst margin of:

Base, 30MHz to 25000MHz, 3 meters

-8.9 dB μ V at 7206.90 MHz in the Horizontal polarization, Low Channel
-8.3 dB μ V at 7325.25 MHz in the Vertical polarization, Middle Channel
-9.1 dB μ V at 7441.74 MHz in the Vertical polarization, High Channel
-5.3 dB μ V at 959.20 MHz in the Vertical polarization, Unintentional Emission

Handset, 30MHz to 25000MHz, 3 meters

-6.3 dB μ V at 7206.90 MHz in the Horizontal polarization, Low Channel
-4.3 dB μ V at 7322.34 MHz in the Horizontal polarization, Middle Channel
-7.6 dB μ V at 4961.14 MHz in the Horizontal polarization, High Channel
-5.6 dB μ V at 82.12 MHz in the Vertical polarization, Unintentional Emission

11.6.1 Radiated Emission Test Data for Base, 30MHz to 25000MHz, 3 meters

INDICATED			TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 SUBPART C	
Frequency MHz	Ampl. dB μ V/m	Comments		Angle Degree	Height Meter	Polar H/V	Antenna dB μ V/m	Cable DB		Corr. Ampl. dB μ V/m	Limit dB μ V/m
Low Channel											
2402.30	98.2	PEAK	15	1.2	V	28.1	3.4	30.0	99.7		
2402.30	67.7	AVE	15	1.2	V	28.1	3.4	30.0	69.2		
2402.30	102.3	PEAK	110	1.5	H	28.1	3.4	30.0	103.8		
2402.30	71.4	AVE	110	1.5	H	28.1	3.4	30.0	72.9		
7206.90	34.4	AVE	230	1.5	H	35.1	5.6	30.0	45.1	54.0	-8.9
9609.20	33.2	AVE	180	1.8	H	35.1	5.6	30.0	43.9	54.0	-10.1
4804.60	35.8	AVE	60	1.8	H	32.5	4.9	30.0	43.2	54.0	-10.8
7206.90	31.9	AVE	90	1.3	H	35.1	5.6	30.0	42.6	54.0	-11.4
4804.60	34.7	AVE	45	1.5	H	32.5	4.9	30.0	42.1	54.0	-11.9
9609.20	30.8	AVE	150	1.5	H	35.1	5.6	30.0	41.5	54.0	-12.5
4804.60	42.3	PEAK	60	1.8	V	32.5	4.9	30.0	49.7	74.0	-24.3
4804.60	41.1	PEAK	45	1.5	V	32.5	4.9	30.0	48.5	74.0	-25.5
7206.90	37.2	PEAK	230	1.5	V	35.1	5.6	30.0	47.9	74.0	-26.1
9609.20	36.3	PEAK	180	1.8	V	35.1	5.6	30.0	47.0	74.0	-27.0
7206.90	36.1	PEAK	90	1.3	V	35.1	5.6	30.0	46.8	74.0	-27.2
9609.20	32.4	PEAK	150	1.5	V	35.1	5.6	30.0	43.1	74.0	-30.9
Middle Channel											
2441.75	97.8	PEAK	45	1.0	V	28.1	3.4	30.0	99.3		
2441.75	67.1	AVE	45	1.0	V	28.1	3.4	30.0	68.6		
2441.75	101.9	PEAK	90	1.5	H	28.1	3.4	30.0	103.4		
2441.75	70.8	AVE	90	1.5	H	28.1	3.4	30.0	72.3		
7325.25	35.0	AVE	270	1.5	V	35.1	5.6	30.0	45.7	54.0	-8.3
9767.00	34.0	AVE	180	1.8	V	35.1	5.6	30.0	44.7	54.0	-9.3
4883.50	36.0	AVE	30	1.8	V	32.5	4.9	30.0	43.4	54.0	-10.6
7325.25	32.0	AVE	90	1.3	H	35.1	5.6	30.0	42.7	54.0	-11.3
4883.50	35.0	AVE	45	1.1	H	32.5	4.9	30.0	42.4	54.0	-11.6
9767.00	31.0	AVE	125	1.1	H	35.1	5.6	30.0	41.7	54.0	-12.3
4883.50	42.5	PEAK	30	1.8	V	32.5	4.9	30.0	49.9	74.0	-24.1
4883.50	41.0	PEAK	45	1.1	H	32.5	4.9	30.0	48.4	74.0	-25.6
7325.25	37.0	PEAK	270	1.5	V	35.1	5.6	30.0	47.7	74.0	-26.3
7325.25	36.0	PEAK	90	1.3	H	35.1	5.6	30.0	46.7	74.0	-27.3
9767.00	36.0	PEAK	180	1.8	V	35.1	5.6	30.0	46.7	74.0	-27.3
9767.00	32.0	PEAK	125	1.1	H	35.1	5.6	30.0	42.7	74.0	-31.3

Radiated Emission Test Data for Base, 30MHz to 25000MHz, 3 meters (Continued)

INDICATED			TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 SUBPART C	
Frequency MHz	Ampl. dB μ V/m	Comments		Angle Degree	Height Meter	Polar H/V	Antenna dB μ V/m	Cable DB		Corr. Ampl. dB μ V/m	Limit dB μ V/m
High Channel											
2480.58	97.7	PEAK	15	1.2	H	28.1	3.4	30.0	99.2		
2480.58	67.0	AVE	15	1.2	H	28.1	3.4	30.0	68.5		
2480.58	101.6	PEAK	110	1.2	V	28.1	3.4	30.0	103.1		
2480.58	70.5	AVE	110	1.2	V	28.1	3.4	30.0	72.0		
7441.74	34.2	AVE	210	1.8	V	35.1	5.6	30.0	44.9	54.0	-9.1
9922.32	33.1	AVE	160	1.2	V	35.1	5.6	30.0	43.8	54.0	-10.2
4961.16	35.4	AVE	60	1.5	V	32.5	4.9	30.0	42.8	54.0	-11.2
7441.74	31.7	AVE	70	1.5	H	35.1	5.6	30.0	42.4	54.0	-11.6
4961.16	34.6	AVE	30	1.2	H	32.5	4.9	30.0	42.0	54.0	-12.0
9922.32	30.9	AVE	150	1.2	H	35.1	5.6	30.0	41.6	54.0	-12.4
4961.16	42.2	PEAK	60	1.5	V	32.5	4.9	30.0	49.6	74.0	-24.4
4961.16	41.3	PEAK	30	1.2	H	32.5	4.9	30.0	48.7	74.0	-25.3
7441.74	37.4	PEAK	210	1.8	V	35.1	5.6	30.0	48.1	74.0	-25.9
7441.74	36.2	PEAK	70	1.5	H	35.1	5.6	30.0	46.9	74.0	-27.1
9922.32	36.1	PEAK	160	1.2	V	35.1	5.6	30.0	46.8	74.0	-27.2
9922.32	32.5	PEAK	150	1.2	H	35.1	5.6	30.0	43.2	74.0	-30.8
Unintentional Emission, 30MHz to 1000MHz											
959.20	38.1		110	1.5	V	23.3	4.3	25.0	40.7	46.0	-5.3
550.00	41.9		120	1.8	H	19.3	2.8	25.0	39.0	46.0	-7.0
124.19	46.5		180	1.2	V	11.7	1.6	25.0	34.8	43.5	-8.7
111.90	45.3		60	2.0	H	11.3	1.5	25.0	33.1	43.5	-10.4
120.08	40.2		15	2.0	H	11.7	1.6	25.0	28.5	43.5	-15.0
140.40	38.6		90	1.2	V	12.4	1.6	25.0	27.6	43.5	-15.9

Note:

AVE.: Average

11.6.2 Radiated Emission Test Data for Handset, 30MHz to 25000MHz, 3 meters

INDICATED			TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 SUBPART C	
Frequency MHz	Ampl. dB μ V/m	Comments		Angle Degree	Height Meter	Polar H/V	Antenna dB μ V/m	Cable DB		Corr. Ampl. dB μ V/m	Limit dB μ V/m
Low Channel											
2402.30	104.8	PEAK	120	1.0	H	28.1	3.4	30.0	106.3		
2402.30	71.2	AVE	120	1.0	H	28.1	3.4	30.0	72.6		
2402.30	103.8	PEAK	100	1.3	V	28.1	3.4	30.0	105.3		
2402.30	70.0	AVE	100	1.3	V	28.1	3.4	30.0	71.5		
7206.90	37.0	AVE	90	1.5	H	35.1	5.6	30.0	47.7	54.0	-6.3
7206.90	36.0	AVE	180	1.1	V	35.1	5.6	30.0	46.7	54.0	-7.3
9609.20	36.0	AVE	270	1.3	V	35.1	5.6	30.0	46.7	54.0	-7.3
9609.20	35.0	AVE	270	1.2	H	35.1	5.6	30.0	45.7	54.0	-8.3
4804.60	37.8	AVE	270	1.5	H	32.5	4.9	30.0	45.2	54.0	-8.8
4804.60	34.0	AVE	250	1.0	V	32.5	4.9	30.0	41.4	54.0	-12.6
4804.60	47.3	PEAK	270	1.5	H	32.5	4.9	30.0	54.7	74.0	-19.3
7206.90	43.0	PEAK	90	1.5	H	35.1	5.6	30.0	53.7	74.0	-20.3
4804.60	46.0	PEAK	250	1.0	V	32.5	4.9	30.0	53.4	74.0	-20.6
7206.90	42.0	PEAK	180	1.1	V	35.1	5.6	30.0	52.7	74.0	-21.3
9609.20	41.0	PEAK	270	1.2	H	35.1	5.6	30.0	51.7	74.0	-22.3
9609.20	39.0	PEAK	270	1.3	V	35.1	5.6	30.0	49.7	74.0	-24.3
Middle Channel											
2440.79	104.0	PEAK	100	1.0	H	28.1	3.4	30.0	105.5		
2440.79	69.3	AVE	100	1.0	H	28.1	3.4	30.0	70.8		
2440.79	103.8	PEAK	120	1.5	V	28.1	3.4	30.0	105.3		
2440.79	70.5	AVE	120	1.5	V	28.1	3.4	30.0	72.0		
7322.34	39.0	AVE	45	2.5	H	35.1	5.6	30.0	49.7	54.0	-4.3
4881.56	41.0	AVE	0	1.8	V	32.5	4.9	30.0	48.4	54.0	-5.6
12203.90	36.0	AVE	80	1.0	H	35.1	5.6	30.0	46.7	54.0	-7.3
4881.56	38.9	AVE	270	1.0	H	32.5	4.9	30.0	46.3	54.0	-7.7
7322.34	34.0	AVE	90	1.0	V	35.1	5.6	30.0	44.7	54.0	-9.3
12203.90	34.0	AVE	45	1.0	V	35.1	5.6	30.0	44.7	54.0	-9.3
7322.34	43.8	PEAK	45	2.5	H	35.1	5.6	30.0	54.5	74.0	-19.5
4881.56	46.0	PEAK	270	1.0	H	32.5	4.9	30.0	53.4	74.0	-20.6
7322.34	42.0	PEAK	90	1.0	V	35.1	5.6	30.0	52.7	74.0	-21.3
4881.56	44.0	PEAK	0	1.8	V	32.5	4.9	30.0	51.4	74.0	-22.6
12203.90	38.0	PEAK	80	1.0	H	35.1	5.6	30.0	48.7	74.0	-25.3
12203.90	37.0	PEAK	45	1.0	V	35.1	5.6	30.0	47.7	74.0	-26.3

Radiated Emission Test Data for Handset, 30MHz to 25000MHz, 3 meters (Continued)

INDICATED			TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 SUBPART C	
Frequency MHz	Ampl. dB μ V/m	Comments		Angle Degree	Height Meter	Polar H/V	Antenna dB μ V/m	Cable DB		Corr. Ampl. dB μ V/m	Limit dB μ V/m
High Channel											
2480.58	104.6	PEAK	90	1.0	H	28.1	3.4	30.0	106.1		
2480.58	70.5	AVE	90	1.0	H	28.1	3.4	30.0	72.0		
2480.58	105.1	PEAK	90	1.0	V	28.1	3.4	30.0	106.6		
2480.58	71.5	AVE	90	1.0	V	28.1	3.4	30.0	73.0		
4961.14	39.0	AVE	330	1.2	H	32.5	4.9	30.0	46.4	54.0	-7.6
4961.14	38.0	AVE	120	1.2	V	32.5	4.9	30.0	45.4	54.0	-8.6
7441.71	34.5	AVE	0	1.8	H	35.1	5.6	30.0	45.2	54.0	-8.8
12402.85	33.0	AVE	180	1.4	V	35.1	5.6	30.0	43.7	54.0	-10.3
12402.85	32.1	AVE	90	1.5	H	35.1	5.6	30.0	42.8	54.0	-11.2
7441.71	32.0	AVE	0	1.8	V	35.1	5.6	30.0	42.7	54.0	-11.3
4961.14	46.0	PEAK	330	1.2	H	32.5	4.9	30.0	53.4	74.0	-20.6
4961.14	45.0	PEAK	120	1.2	V	32.5	4.9	30.0	52.4	74.0	-21.6
7441.71	40.0	PEAK	0	1.8	H	35.1	5.6	30.0	50.7	74.0	-23.3
7441.71	38.0	PEAK	0	1.8	V	35.1	5.6	30.0	48.7	74.0	-25.3
12402.85	37.8	PEAK	90	1.5	H	35.1	5.6	30.0	48.6	74.0	-25.4
12402.85	36.0	PEAK	180	1.4	V	35.1	5.6	30.0	46.7	74.0	-27.3
Unintentional Emission, 30MHz to 1000MHz											
82.12	48.7		0	1.2	V	9.5	1.2	25.0	34.4	40.0	-5.6
66.78	48.1		30	1.2	V	9.3	1.2	25.0	33.6	40.0	-6.4
550.00	42.3		120	2.0	H	19.3	2.8	25.0	39.4	46.0	-6.6
124.19	47.2		180	1.2	V	11.7	1.6	25.0	35.5	43.5	-8.0
111.90	45.2		90	2.0	H	11.3	1.5	25.0	33.0	43.5	-10.5
420.90	40.8		270	2.5	H	16.5	2.7	25.0	35.0	46.0	-11.0
150.00	40.9		90	2.0	V	12.7	1.7	25.0	30.3	43.5	-13.2
120.08	40.6		0	2.5	H	11.7	1.6	25.0	28.9	43.5	-14.6
257.08	40.6		90	1.2	V	13.3	2.2	25.0	31.1	46.0	-14.9
140.40	38.7		200	1.2	V	12.4	1.6	25.0	27.7	43.5	-15.8

Note:

AVE.: Average

12 – CONDUCTED EMISSIONS

12.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at BACL is ± 2.4 dB.

12.2 EUT Setup

The measurement was performed at shield room, using the same setup per ANSI C63.4 – 1992 measurement procedure. The specification used was FCC Class B limits.

The base of the EUT was connected to a 120 VAC / 60 Hz power source.

The spacing between the peripherals was 10 centimeters.

Input / Output cables were draped along the edge of the test table and bundle when necessary.

12.3 Spectrum Analyzer Setup

The spectrum analyzer was set with the following configurations during the conduction test:

Start Frequency.....	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10 kHz
Video Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode.....	Normal

12.4 Test Procedure

During the conducted emission test, the power cord of the host system was connected to the auxiliary outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of each modes tested to ensure EUT is compliant with all installation combination.

All data was recorded in the peak detection mode. Quasi-peak readings were only performed when an emission was found to be marginal (within -4 dB μ V of specification limits). Quasi-peak readings are distinguished with a “Qp”.

12.5 Summary of Test Results

According to the data in section 12.6, the EUT complied with the FCC Conducted margin for a Class B device and these test results is deemed satisfactory evidence of compliance with ICES-003 of the Canadian Interference-Causing Equipment Regulations, with the *worst* margin reading of:

-22.8 dB μ V at 13.5 MHz in the Neutral mode, 150kHz – 30 MHz

12.6 Conducted Emissions Test Data

LINE CONDUCTED EMISSIONS				FCC CLASS B	
Frequency MHz	Amplitude dB μ V	Detector Qp/Ave/Peak	Phase Line/Neutral	Limit dB μ V	Margin dB
13.500	33.2	Ave	Neutral	56	-22.8
0.800	33.0	Ave	Line	56	-23.0
0.150	37.0	QP	Neutral	66	-29.0
29.805	36.7	QP	Line	66	-29.3
0.150	36.5	QP	Line	66	-29.5
29.805	34.6	QP	Neutral	66	-31.4
13.500	33.8	QP	Neutral	66	-32.2
0.800	33.1	QP	Line	66	-32.9
29.805	23.1	Ave	Line	56	-32.9
29.805	18.5	Ave	Neutral	56	-37.5
0.150	8.6	Ave	Line	56	-47.4
0.150	8.5	Ave	Neutral	56	-47.5

12.7 Plot of Conducted Emissions Test Data

Plot(s) of Conducted Emissions Test Data is presented in the following page as reference.

Bay Area Compliance Laboratory Corp.
CISPR CLASS B

14. May 03 17:11


EUT: AT2488
Manuf: Shenzhen Baoan
Op Condi: Normal
Operator: Jerry
Comment: L

Scan Settings (1 Range)

Frequencies				Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	
150k	30M	5k	9k	QP+AV	20ms	10dBBLN	OFF	

Final Measurement: x QP / + AV

Meas Time: 1 s
Subranges: 25
Acc Margin: 6dB



Bay Area Compliance Corporation
CISPR CLASS B

14. May 03 15:55

BUT: AT2488
Manuf: Shenzhen Baoan
Op Cnd: Normal
Operator: Jerry
Comment: N

Scan Settings (1 Range)
| ----- Frequencies ----- | ----- Receiver Settings ----- |
Start Stop Step IF BW Detector M-Time Atten Preamp
150k 30M 5k 9k QP+AV 20ms 10dBLN OFF
Final Measurement: x QP / + AV
Meas. Time: 1 s
Subranges: 25
Acc Margin: 6dB

