

December 17, 2013

TUV SUD BABT
Octagon House,
Concorde Way
Segensworth Rd N,
Fareham
PO15 5RL

Subject: SAR Evaluation Exemption Compliance information

FCC KDB 447498 D01v05 Clause 4.3.1.1 SAR test exemption criteria

FCC ID: OOO-M350

Portable Exposure SAR Exemption

Per FCC KDB 447498 D01 RF Exposure v05r01

Maximum e.r.p. power = 14.53 mW

$f_{\text{(GHz)}} = 0.0001251$

A test separation distance of 5 mm has been applied to the SAR test exclusion calculation.

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [f_{\text{(GHz)}}] \leq 3.0$$

$f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷


The result is rounded to one decimal place for comparison

[Ref: Clause 4.3.1.1]

$$[(14.53\text{mW})/(5, \text{mm})] \cdot [0.0001251_{\text{(GHz)}}] \leq 3.0$$
$$0.033 \leq 3.0$$

Therefore, the device meets the FCC SAR exemption requirements.

Sincerely,



Name: Joel Schneider

Title: Senior EMC Engineer