

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
TESTED TO FCC PART 15 REQUIREMENTS**

For

INTENTIONAL RADIATOR

**FM WIRELESS HANDS FREE KIT
TO BE USED WITH CELL PHONE INSIDE A VEHICLE**

**MODEL NO: HFK-DDB-MT00STARBK
HFK-SSB-NK006190BK, HFK-DDB-ER000788BK**

FCC ID: OSHPTI88M7KNKMTER

REPORT NO: 00U0186-1

ISSUE DATE: MAY 03, 2000

Prepared for
**PRIORITY TECH, INC.
46771 GREMONT BLVD.
FREMONT, CA 94538 USA**

Prepared by
**COMPLIANCE ENGINEERING SERVICES, INC.
d.b.a.
COMPLIANCE CERTIFICATION SERVICES
1366 BORDEAUX DRIVE
SUNNYVALE, CA 94089, USA
TEL: (408) 752-8166
FAX: (408) 752-8168**

TABLE OF CONTENTS	PAGE
1. VERIFICATION OF COMPLIANCE.....	1
2. PRODUCT DESCRIPTION.....	2
3. TEST FACILITY.....	2
4. MEASUREMENT STANDARDS.....	2
5. TEST METHODOLOGY.....	2
6. MEASUREMENT EQUIPMENT USED.....	2
7. RADIATED EMISSION LIMITS.....	3
8. SYSTEM TEST CONFIGURATION.....	3
9. TEST PROCEDURE.....	4
10. SETUP PHOTOS.....	6
11. TEST RESULT.....	7
TEST DATA	

1. VERIFICATION OF COMPLIANCE

COMPANY NAME : PRIORITY TECH, INC.
46771 FREMONT BLVD.
FREMONT, CA 94538 USA

CONTACT PERSON : C. H. PAN/ PRESIDENT

TELEPHONE NO. : (510) 226-7800

EUT DESCRIPTION : FM WIRELESS HANDS FREE KIT TO BE USED
WITH CELL PHONE INSIDE A VEHICLE

MODEL NAME/NUMBER : HFK-DDB-MT00STARBK, HFK-DDB-NK006190BK
HFK-DDB-ER000788BK

DATE TESTED : MAY 03, 2000

REPORT NUMBER : 00U0186

TYPE OF EQUIPMENT	FM WIRELESS HANDS FREE KIT TO BE USED WITH CELL PHONE INSIDE A VEHICLE
EQUIPMENT TYPE	88.7MHz RECEIVER
MEASUREMENT PROCEDURE	ANSI C63.4 / 1992
LIMIT TYPE	CERTIFICATION
FCC RULE	CFR 47, PART 15

The above equipment was tested by Compliance Engineering Services, Inc. for compliance with the requirements set forth in CFR 47, PART 15. This said equipment in the configuration described in this report shows that maximum emission levels emanating from equipment are within the compliance requirements. **Warning** : This document reports conditions under which testing was conducted and results of tests performed. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification will constitute fraud and shall nullify the document.

T. N. COKENIAS / ENGINEERING DIRECTOR
COMPLIANCE CERTIFICATION SERVICES

2. PRODUCT DESCRIPTION

Fundamental Frequency	88.7 MHz
Power Source	FROM VEHICLE DC
Usage	VEHICLE HANDS-FREE KIT
Power Requirement	12 VDC
Antenna Requirement	Permanently attached

3. TEST FACILITY

The 3/10/30 meter open area test site and conducted measurement facility used to collect the radiated data is located at 561F Monterey Road, Morgan Hill, California, U.S.A. A detailed description of the test facility was submitted to the Commission on May 27, 1994.

4. MEASUREMENT STANDARDS

The site is constructed and calibrated in conformance with the requirements of ANSI C63.4/1992.

5. TEST METHODOLOGY

For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 KHz, up to at least the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower. (CFR 47 Section 15.33)

6. MEASUREMENT EQUIPMENT USED

Manufacturer	Model Number	Description	Cal Due Date
H.P.	8593EM	EMC RECEIVER 9K-26.5GHz	09/2000
SCHAFFUER-CHASE	CBL6112B	Antenna	02/2001
H.P.	8447D	Preamplifier (0.1 - 1300 MHz)	09/2000


7. RADIATED EMISSION LIMITS

GENERAL REQUIREMENTS	SECTION 15.209, 15.239
----------------------	------------------------

8. SYSTEM TEST CONFIGURATION

Used 12Vdc to activate the EUT.

Radiated Open Site Test Set-up



9. TEST PROCEDURE

Radiated Emissions, 15.209





Fig. 1

1. The EUT was placed on a wooden table on the outdoor ground plane. The search antenna was placed 3-meters from the EUT.
2. The turntable was slowly rotated to locate the direction of maximum emission. The EUT was moved throughout the.
3. Once maximum direction was determined, the search antenna was raised and lowered. The maximum readings so obtained are recorded in the data listed below.

Radiated Emissions, 15.239 (a) & 15.239(b), (c)**Test Set-up**

According to FCC 15.239(a), the EUT and accessories shall be placed on the 1 meter site in above configuration.

First, connect 12Vdc + and - pins of battery to the power inputs of EUT by using the wires to activate the continuous emissions.


Using a probe to detect the emission signal from the EUT and measure 88.7MHz EUT signal level on the screen of spectrum analyzer (HP 8593EM) with RES BW=VID BW=1Khz and Span Size = 200kHz.

Apply a low frequency signal of signal generator to #5 and #7 pin of HEADER connector of EUT using 2 wires.

Turn on the signal generator. Set up 2.5 kHz as a modulation frequency and adjust the output amplitude value to get the modulated FM signal with about 200kHz deviation. (See attached plots).

Measure the band width of FM modulated signal on the level 20dB down below the original CW signal.

A plot of such combined signal pattern was made. (See attached)

10. SETUP PHOTOS

11. TEST RESULT

All emissions were measured at 3 meters by using the following limits. Attached data sheet and plots show the passing radiation results to testing to 15.209 and 15.239.

The limit of any emissions in 80-108MHz shall not exceed 250uV (Or 48 dBuV/m) at 3 meters.

The test is based on measurement instrumentation employing average detector, not Q-P detection.

The test block diagram is without FM modulation signal input (CW EUT emission signal test only) at 3 meters.

The radiation limit of any frequency outside of band follows 15.209