

198 Kezhu Road, Scientech Park, Guangzhou Economic & Technological

Development District, Guangzhou, China 510663

Telephone: +86 (0) 20 82155555 Report No.: GZEM181100232702

Fax: +86 (0) 20 82075059 Page: 1 of 12 Email: ee.guangzhou@sgs.com

TEST REPORT

Application No.: GZEM1811002327CR

Applicant: FOCAL JMLab

Address of Applicant: 108 Avenue de l'Avenir ZI Molina La Chazotte 42350 La Talaudière FRANCE

Manufacturer:The same as ApplicantAddress of Manufacturer:The same as ApplicantFactory:Minami Acoustics Limited

Address of Factory: Shangou Industrial Park GongJiang Town, Yudu County Ganzhou City

Jiangxi 342300 China

Equipment Under Test (EUT):

EUT Name: Bluetooth Headphones

Model No.: Focal Sphear Wireless, Focal Sphear Wireless/Black, Focal Sphear

Wireless/Blue, Focal Sphear Wireless/Olive, Focal Sphear Wireless/Purple,

Focal Sphear Wireless/XX, [XX=AA to ZZ (for different color)]. ¤

Please refer to section 2 of this report which indicates which model was

actually tested and which were electrically identical.

Trade Mark: FOCAL

Standard(s): 47 CFR Part 1.1307, Part 1.1310

Date of Receipt: 2018-11-02

Date of Test: 2018-11-02 to 2018-11-20

Date of Issue: 2018-12-12

Test Result: Pass*



Kobe Jian Lab Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: GZEM181100232702

Page: 2 of 12

	Revision Record						
Version	Version Chapter Date Modifier Remark						
01		2018-12-12		Original			

Authorized for issue by:		
Tested By	Jackson Wan	2018-11-02 to 2018-11-20
	Jackson_Yuan /Project Engineer	Date
Checked By	Riday Liu	2018-12-12
	Ricky Liu /Reviewer	Date



Report No.: GZEM181100232702

Page: 3 of 12

2 Test Summary

Radio Spectrum Technical Requirement						
Item Standard Method Requirement Resul						
RF Exposure	47 CFR Part 1.1307, Part 1.1310	CFR 47 Part 1.1310	CFR 47 Part 1.1310	Pass		

¤ Declaration of EUT Family Grouping:

Model No.: Focal Sphear Wireless, Focal Sphear Wireless/Blue, Focal Sphear Wireless/Olive, Focal Sphear Wireless/Purple, Focal Sphear Wireless/XX, [XX=AA to ZZ (for different color)].

According to the declaration from the applicant, the electrical circuit design, layout, components used and internal wiring were identical for all models, with only differences on the item's no and outer color.

Therefore only one model Focal Sphear Wireless/Black was tested in this report.



Report No.: GZEM181100232702

Page: 4 of 12

3 Contents

			Page
1	Cov	ver Page	1
2	Test	t Summary	3
3		ntents	
4		neral Information	
	4.1 4.2 4.3 4.4 4.5 4.6 4.7	Details of E.U.T. Description of Support Units Measurement Uncertainty Test Location Test Facility Deviation from Standards Abnormalities from Standard Conditions	
5	Equ	ipment List	9
6	Rad	lio Spectrum Technical Requirement	10
	6.1 6.1.2		10
7	Pho	otographs	12
	7.1	EUT Constructional Details	12



Report No.: GZEM181100232702

Page: 5 of 12

4 General Information

4.1 Details of E.U.T.

Power Supply: DC 5 V for charging by AC/DC adapter

Powered by Built-in battery as below:

Model No.: 401230

Rated: 3.7V, 120mAh, 0.44Wh

Test Voltage: AC 120V, 60Hz with AC/DC adapter referred to section 4.2 for charging

DC 3.7V for earphone working

Cable: Micro USB charging ports (unshielded, <3m)

Antenna Gain 0.8 dBi

Antenna Type Integrated Antenna

Channel Spacing 1MHz

Modulation Type GFSK, π/4DQPSK, 8DPSK

Number of Channels 79

Operation Frequency 2402MHz to 2480MHz

Software CSR

Spectrum Spread

Technology

Frequency Hopping Spread Spectrum(FHSS)

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
AC/DC Adapter	SGS	DC 5V	REF. No.SEA0500
Laptop	Lenovo	T430u	REF. No.SEA1800

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty	
1	Radio Frequency	±5.5 x 10 ⁻⁸	
2	Duty cycle	±0.57%	
3	Occupied Bandwidth	±3%	
4	RF Conducted power	±0.68dB	
5	RF Power Density	±1.50dB	
6	Conducted Spurious Emissions	±1.04dB	
7	RF Radiated Power	±4.5dB (below 1GHz)	
1	nr naulateu rowei	±4.8dB (above 1GHz)	
8	Radiated Spurious Emission Test	±4.5dB (30MHz-1GHz)	
0	nadiated Spullous Ellission Test	±4.8dB (1GHz-18GHz)	
9	Temperature	±0.4℃	
10	Humidity	±1.3%	
11	Supply Voltages	±1.5%	
12	Time	±3%	



Report No.: GZEM181100232702

Page: 6 of 12

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory, 198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.



Report No.: GZEM181100232702

Page: 7 of 12

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● NVLAP (Lab Code: 200611-0)

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

ACMA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

● SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

● CNAS (Lab Code: L0167)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to

ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

● FCC Recognized 2.948 Listed Test Firm(Registration No.: 282399)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

FCC Recognized Accredited Test Firm(Registration No.: 486818)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818, Jul 13, 2017.

● Industry Canada (Registration No.: 4620B-1)

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

● VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

● CBTL (Lab Code: TL129)

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.



Report No.: GZEM181100232702

Page: 8 of 12

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Report No.: GZEM181100232702

Page: 9 of 12

5 Equipment List

Conducted Peak Output Power						
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date	
EXA Signal Analzer	AgilentTechnologies	N9010A	EMC2138	2018-11-19	2019-11-18	
6dB Attenuator	HP	8491A	EMC2062	2018-04-04	2020-04-03	
Test Software JS1120-3	HangTianXing	V2.6	GZE100-69	N/A	N/A	

General used equipment						
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date	
DMM	Fluke	73	EMC0006	2018-07-20	2019-07-19	
DMM	Fluke	73	EMC0007	2018-07-19	2019-07-18	



Report No.: GZEM181100232702

Page: 10 of 12

6 Radio Spectrum Technical Requirement

6.1 RF Exposure

6.1.1 Test Requirement:

CFR 47 Part 1.1310

Limit:

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in Part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)				
(A) Limits for Occupational/Controlled Exposure								
0.3-3.0	614	1.63	*100	6				
3.0-30	1842/f	4.89/f	*900/f ²	6				
30-300	61.4	0.163	1.0	6				
300-1,500			f/300	6				
1,500-100,000			5	6				
	(B) Limits for General Population/Uncontrolled Exposure							
0.3-1.34	614	1.63	*100	30				
1.34-30	824/f	2.19/f	*180/f ²	30				
30-300	27.5	0.073	0.2	30				
300-1,500			f/1500	30				
1,500-100,000			1.0	30				
f - frequency in MHz		•	•	•				

f = frequency in MHz

According to IEEE C95.3:2002 section 5.5.1.1, The power density S at a point on the axis at a distance d from a transmitting antenna is given by the Friis free-space transmission formula

$$S = \frac{PG}{4\pi d^2}$$

$$S = power density (mW/cm^2)$$

$$P = the net power delivered to the antenna (mW)$$

$$G = gain of the antenna in linear scale$$

 $S = power density (mW/cm^2)$

d = distance between observation point and center of the radiator (cm)

⁼ Plane-wave equivalent power density



Report No.: GZEM181100232702

Page: 11 of 12

6.1.2 Conclusion

The Max conducted output power is 4.793 dBm in Lowest channel (2.441 GHz);

4.793 dBm logarithmic terms convert to numeric result is nearly 3.02 mW

According to the formula. calculate the test result:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}]$

General RF Exposure = $(3.02 \text{ mW} / 5 \text{ mm}) \times \sqrt{2.441 \text{ GHz}} = 0.942 \text{ }\bigcirc$

SAR requirement:

S = 3.0

2;

(1) < (2).

So the SAR report is not required.



Report No.: GZEM181100232702

Page: 12 of 12

7 Photographs

7.1 EUT Constructional Details

Please refer to Appendix A - Photographs of EUT Constructional Details for GZEM1811002327CR.

--End of Report-