Software Security Description – KDB 594280 D02v01r02 Section II

General Description

1. Describe how any software/firmware update will be	There is no downloadable software provided by the
obtained, downloaded, and installed. Software that is	manufacturer that can modify critical radio transmitter
accessed through manufacturer's website or device's	parameters. All critical parameters are programmed in
management system, must describe the different levels	OTP memory at the factory and cannot be modified or
of security.	overridden by third parties.
2. Describe all the radio frequency parameters that are	There are no rf parameters that can be modified. All rf
modified by any software/firmware without any	parameters are programmed in OTP memory at the
hardware changes. Are these parameters in some way	factory and cannot be modified or overridden by third
limited, such that, it will not exceed the authorized	parties.
parameters?	
3. Describe in detail the authentication protocols that	The firmware is programmed at the factory and cannot
are in place to ensure that the source of the	be modified by third parties.
software/firmware is legitimate. Describe in detail how	
the software is protected against modification.	
Describe in detail the verification protocols in place	The firmware is programmed at the factory and cannot
to ensure that installed software/firmware is legitimate.	be modified by third parties.
	, ,
5. Describe in detail any encryption methods used to	The firmware is programmed at the factory and cannot
support the use of legitimate software/firmware.	be modified by third parties therefore no encryption is
	necessary.
6. For a device that can be configured as a master and	This is a client module only.
	This is a chefit inodule only.
client (with active or passive scanning), explain how the	
device ensures compliance for each mode? In particular	
if the device acts as master in some band of operation	
and client in another; how is compliance ensured in	
each band of operation?	

Third-Party Access Control

1. Explain if any third parties have the capability to	Third parties do not the capability to operate in any
operate a US sold device on any other regulatory	manner that is violation of the certification in the U.S.
domain, frequencies, or in any manner that is in	
violation of the certification.	
2. What prevents third parties from loading non-US	RF parameters are programmed into OTP memory at the
versions of the software/firmware on the device?	factory and cannot be reprogrammed or re-flashed by
Describe in detail how the device is protected from	third parties.
"flashing" and the installation of third-party firmware	
such as DD-WRT. (See, for example, http://www.dd-	

wrt.com/)	
3. For Certified Transmitter modular devices, describe how the module grantee ensures that hosts manufactures fully comply with these software security	There are no rf parameters that can be modified. All rf parameters are programmed in OTP memory at the factory and cannot be modified or overridden by third
requirements for U-NII devices. If the module is controlled through driver software loaded in the host, describe how the drivers are controlled and managed such that the modular transmitter parameters are not modified outside the grant of authorization.	parties. The module is not controlled by driver software on the host and cannot override critical rf parameters stored in module OTP memory.

SOFTWARE CONFIGURATION DESCRIPTION - KDB 594280 D02v01r02 Section III

USER CONFIGURATION GUIDE

1. To whom is the UI accessible? (Professional installer,	No UI provided.
end user, other.)	
a) What parameters are viewable to the professional	None
installer/end-user?	
b) What parameters are accessible or modifiable to	None
the professional installer?	
i) Are the parameters in some way limited, so that	The module micro-code reads the parameters from the
the installers will not enter parameters that exceed	module OTP memory. These parameters cannot be
those authorized?	modified or overridden by sw drivers.
ii) What controls exist that the user cannot operate	Default mode is always FCC compliant. Other country
the device outside its authorization in the U.S.?	modes cannot be activated without receiving three
	independent country codes from different APs, otherwise
	remains in FCC default mode (always FCC compliant)
c) What configuration options are available to the	None
end-user?	
i) Are the parameters in some way limited, so that	The module micro-code reads the parameters from the
the installers will not enter parameters that exceed	module OTP memory. These parameters cannot be
those authorized?	modified or overridden by sw drivers.
ii) What controls exist that the user cannot operate	Default mode is always FCC compliant. Other country
the device outside its authorization in the U.S.?	modes cannot be activated without receiving three
	independent country codes from different APs, otherwise
	remains in FCC default mode (always FCC compliant)
d) Is the country code factory set? Can it be changed	Default country code is set in the factory and no UI is
in the UI?	provided for modification.
i) If so, what controls exist to ensure that the	Programmed for default mode which is always FCC
device can only operate within its authorization in the	compliant. Always set for default for all start-ups, resets,
	timeouts or other host or network events.
	1

FCC ID: PD98265D2_IC: 1000M-8265D2

U.S.?	
e) What are the default parameters when the device	Always FCC compliant
is restarted?	
2. Can the radio be configured in bridge or mesh mode?	No
If yes, an attestation may be required. Further	
information is available in KDB Publication 905462 D02.	
3. For a device that can be configured as a master and client (with active or passive scanning), if this is user configurable, describe what controls exist, within the UI, to ensure compliance for each mode. If the device acts as a master in some bands and client in others, how is this configured to ensure compliance?	This is a client device.
4. For a device that can be configured as different types of access points, such as point-to-point or point-to-multipoint, and use different types of antennas, describe what controls exist to ensure compliance with applicable limits and the proper antenna is used for each mode of operation. (See Section 15.407(a))	This device is not an access point.

Name and surname of applicant (or <u>authorized</u> representative):

Date: May 11, 2016 Signature: