

TEST REPORT

EUT Description	Notebook Computer
Brand Name	HP
Model Name	TPN-C162
FCC ID	PD9AX211D2
ISED ID	1000M-AX211D2
Date of Test Start/End	2023-07-07 / 2023-07-07
Features	IEEE 802.11a/b/g/n/ac/ax

Applicant	Intel Corporation SAS
Address	425 Rue de Goa – Le Cargo B6 – 06600 Antibes, FRANCE
Contact Person	Benjamin Lavenant
Telephone/Fax/ Email	Benjamin.lavenant@intel.com

Test Report identification	230606-01.TR01
Revision Control	Rev. 03 This test report replaces any previous versions of this test report (see Section 7)

The test results relate only to the samples tested.

Reviewed by _____

Intel Corporation S.A.S – WRF Lab
425 rue de Goa – Le Cargo B6 - 06600, Antibes, France
Tel. +33493001400 / Fax +33493001401

Table of Contents

1. Standards, reference documents and applicable test methods	3
2. General conditions, competences and guarantees	3
3. Environmental Conditions	3
4. Test Sample	3
5. EUT Features	4
6. Remarks and comments	4
7. Test Results summary	4
7.1. WLAN TX POWER TABLE SUMMARY	4
8. Document Revision History	5
Annex A. Test & System description	6
A.1 TEST SETUP	6
A.2 PROCEDURE	6
A.3 TEST EQUIPMENT LIST	7
Annex B. Test Results	8
B.1 TRIGGER LID ANGLE DETECTION AND POWER VERIFICATION 2.4GHZ	8
B.1.1 LCD DIRECTION 0°	8
B.1.2 LCD DIRECTION 90/270°	10
B.2 TRIGGER LID ANGLE DETECTION AND POWER VERIFICATION 5GHZ	12
B.2.1 LCD DIRECTION 0°	12
B.2.2 LCD DIRECTION 90/270°	14

1. Standards, reference documents and applicable test methods

- a. KDB 388624 D02 Pre-Approval Guidance List v18, PRE-APPROVAL GUIDANCE LIST
- b. FCC Presentations TCB Workshop November 2019, RF exposure procedures.

2. General conditions, competences and guarantees

- ✓ Intel WRF Lab only provides testing services and is committed to providing reliable, unbiased test results and interpretations.
- ✓ Intel WRF Lab is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.
- ✓ Intel WRF Lab has developed calibration and proficiency programs for its measurement equipment to ensure correlated and reliable results to its customers.
- ✓ This report is only referred to the item that has undergone the test.
- ✓ This report does not imply an approval of the product by the Certification Bodies or competent Authorities.

3. Environmental Conditions

- ✓ At the site where the measurements were performed the following limits were not exceeded during the tests:

Temperature	23.4°C ± 1°C
Humidity	57.5% ± 5%

4. Test Sample

Sample	ID #	Description	Model	Serial #	Note
#1	230606-01.S01	Notebook Computer	TPN-C162	CND3070C86	-

5. EUT Features

The herein information is provided by the customer.

Intel WRF Lab declines any responsibility for the accuracy of the stated customer provided information, especially if it has any impact on the correctness of test results presented in this report.

Brand Name	HP
Model Name	TPN-C162
Prototype / Production	Production
Host Identification	Notebook Computer

6. Remarks and comments

1. The test report is validation of the G sensor functionality

7. Test Results summary

7.1. WLAN Tx Power Table Summary

Device Mode	Lid Angle range	LCD Direction	2.4GHz-CH6 802.11b				5GHz-CH120 802.11a			
			Target Power (dBm)		Measured Power (dBm)		Target Power (dBm)		Measured Power (dBm)	
			Antenna AUX	Antenna MAIN	Antenna AUX	Antenna MAIN	Antenna AUX	Antenna MAIN	Antenna AUX	Antenna MAIN
Lid Close	0° ≤ - <35°	-	Standby	Standby	Standby	Standby	Standby	Standby	Standby	Standby
Laptop	35° ≤ - <160°	0°	20.5	20.5	19.82	19.56	20.5	20.5	19.98	19.65
Flat	161° ≤ - <180°	0°	15.5	15.5	14.91	14.62	12.5	12.5	11.87	11.73
Book	120° ≤ - ≤170°	90°; 270°	15.5	15.5	14.88	14.53	12.5	12.5	11.91	11.61
AIO	161° ≤ - <180 (with kickstand)	90°	20.5	20.5	19.78	19.49	20.5	20.5	19.86	19.63

8. Document Revision History

Revision #	Modified by	Revision Details
Rev.00	Cheiel I	Initial release
Rev 01	Cheiel I	Correction of table summary per operation description document upon customer request
Rev 02	Cheiel I	Correction of lid angle range on table summary per operation description document and modification of the applicant upon customer request
Rev 03	Cheiel I	Correction of AIO table results


Annex A. Test & System description

A.1 Test setup

The conducted power measurement test setup is described in the following and illustrated in Figure 1.

- The DUT is Notebook Computer from *HP* model *TPN-C162*. An *AX211D2W* connectivity module is installed inside
- A control PC is used to configure the call box as an access point to manage the uplink and downlink data traffic.
- Uplink signal power is measured with the Call Box.
- Path loss in the power measurement setup from the wireless module antenna port to the Call Box.

Figure.1 – Power measurement test setup.



A.2 Procedure

The following additional guidance applies only to convertible laptops whose screen rotates around one axis, from 0 degrees to 180 degrees, in a clamshell style, i.e., from closed mode to open mode, to “tent” mode, and finally, to tablet mode. This process must be followed to determine the lid angle where a power reduction occurs, by taking power measurements at each step, as indicated in the step listed here below:

1. From the lid in closed mode (0 degrees), open the screen in 10-degree steps until laptop mode is obtained
2. Lower the screen by 5 degrees increments to verify that the “closed mode” is triggered
3. From the position of the previous step, open the screen in 1-degree increments until laptop mode is triggered again
4. Continue opening the screen in 1-degree increments until at least 5 degrees past where “laptop mode” was obtained, then continue opening the screen in 10-degree steps until the device switches to tablet mode
5. Reverse the previous procedure to go from tablet mode back down to closed mode

A.3 Test Equipment List

Equipment and accessories used for the conducted power measurement test setup are listed below. The Test Platform (DUT), test setup and associated equipment are shown in A.1.

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
125-000	Communication Tester	CMW500	129337	Rohde & Schwartz	2023-04-20	2025-04-20
022-003 022-004	RF path (RF cable + Adapters)	-	-	-	RF path loss was verified before usage	

Annex B. Test Results

B.1 Trigger lid angle detection and power verification 2.4GHz

B.1.1 LCD direction 0°

The lid is rotating from 0 to 180. The screen is vertical, LCD direction is 0 degree.

Mode	Angle	Measured power	
	(degree)	2.4GHz-Ch6(dBm)	
		AUX	MAIN
Lid close	0	Standby	Standby
	10	Standby	Standby
	20	Standby	Standby
	30	Standby	Standby
Laptop	40	19.82	19.56
Lid close	35	Standby	Standby
	36	Standby	Standby
	37	Standby	Standby
	38	Standby	Standby
	39	Standby	Standby
Laptop	40	19.82	19.56
	41	19.82	19.56
	42	19.82	19.56
	43	19.82	19.56
	44	19.82	19.56
	45	19.82	19.56
	50	19.82	19.56
	60	19.82	19.56
	70	19.82	19.56
	80	19.82	19.56
	90	19.82	19.56
	100	19.82	19.56
	110	19.82	19.56
	120	19.82	19.56
	130	19.82	19.56
	140	19.82	19.56
	150	19.82	19.56
	160	19.82	19.56
Flat	170	14.91	14.62
	165	14.91	14.62
Laptop	160	19.82	19.56
Flat	161	14.91	14.62
	162	14.91	14.62
	163	14.91	14.62
	164	14.91	14.62
	165	14.91	14.62
	170	14.91	14.62
	180	14.91	14.62

Test Report No: 230606-01.TR01

The lid is rotating from 180 degrees to 0 degree. The screen is vertical, LCD direction to 0 degree.

Mode	Angle	Measured power	
	(degree)	2.4GHz-Ch6(dBm)	
		AUX	MAIN
Flat	180	14.91	14.62
	170	14.91	14.62
Laptop	160	19.82	19.56
Flat	165	14.91	14.62
	164	14.91	14.62
	163	14.91	14.62
	162	14.91	14.62
	161	14.91	14.62
Laptop	160	19.82	19.56
	159	19.82	19.56
	158	19.82	19.56
	157	19.82	19.56
	156	19.82	19.56
	155	19.82	19.56
	150	19.82	19.56
	140	19.82	19.56
	130	19.82	19.56
	120	19.82	19.56
	110	19.82	19.56
	100	19.82	19.56
	90	19.82	19.56
	80	19.82	19.56
	70	19.82	19.56
	60	19.82	19.56
	50	19.82	19.56
	40	19.82	19.56
Lid Close	30	Standby	Standby
Laptop	35	19.82	19.56
Lid Close	34	Standby	Standby
	33	Standby	Standby
	32	Standby	Standby
	31	Standby	Standby
	30	Standby	Standby
	20	Standby	Standby
	10	Standby	Standby
	0	Standby	Standby

B.1.2 LCD direction 90/270°

The lid is rotating from 0 to 180 degrees. The screen is vertical, LCD direction to 90 or 270 degrees for book mode. AIO mode is performed in flat with kickstand. The angle is 120 degrees.

Mode	Angle	Measured power	
	(degree)	2.4GHz-Ch6 (dBm)	
		AUX	MAIN
Lid close	0	Standby	Standby
	10	Standby	Standby
	20	Standby	Standby
	30	Standby	Standby
Book	40	14.88	14.53
Lid close	35	Standby	Standby
	36	Standby	Standby
	37	Standby	Standby
	38	Standby	Standby
	39	Standby	Standby
Book	40	14.88	14.53
	41	14.88	14.53
	42	14.88	14.53
	43	14.88	14.53
	44	14.88	14.53
	45	14.88	14.53
	50	14.88	14.53
	60	14.88	14.53
	70	14.88	14.53
	80	14.88	14.53
	90	14.88	14.53
	100	14.88	14.53
	110	14.88	14.53
	120	14.88	14.53
	130	14.88	14.53
	140	14.88	14.53
	150	14.88	14.53
	160	14.88	14.53
AIO with kickstand at 120°	170	19.78	19.49
	165	19.78	19.49
Book	160	14.88	14.53
AIO with kickstand at 120°	161	19.78	19.49
	162	19.78	19.49
	163	19.78	19.49
	164	19.78	19.49
	165	19.78	19.49
	170	19.78	19.49
	180	19.78	19.49

Test Report No: 230606-01.TR01

The lid is rotating from 180 to 0 degrees. The screen is vertical, LCD direction to 90 or 270 degrees for book mode. AIO mode is performed in flat with kickstand. The angle is 120 degrees.

Mode	Angle	Measured power	
	(degree)	2.4GHz-Ch6(dBm)	
		AUX	MAIN
AIO with kickstand at 120°	180	19.78	19.49
	170	19.78	19.49
Book	160	14.88	14.53
AIO with kickstand at 120°	165	19.78	19.49
	164	19.78	19.49
	163	19.78	19.49
	162	19.78	19.49
	161	19.78	19.49
Book	160	14.88	14.53
	159	14.88	14.53
	158	14.88	14.53
	157	14.88	14.53
	156	14.88	14.53
	150	14.88	14.53
	140	14.88	14.53
	130	14.88	14.53
	120	14.88	14.53
	110	14.88	14.53
	100	14.88	14.53
	90	14.88	14.53
	80	14.88	14.53
	70	14.88	14.53
	60	14.88	14.53
	50	14.88	14.53
	40	14.88	14.53
Lid Close	30	Standby	Standby
Book	35	14.88	14.53
Lid Close	34	Standby	Standby
	33	Standby	Standby
	32	Standby	Standby
	31	Standby	Standby
	30	Standby	Standby
	20	Standby	Standby
	10	Standby	Standby
	0	Standby	Standby

B.2 Trigger lid angle detection and power verification 5GHz

B.2.1 LCD direction 0°

The lid is rotating from 0 to 180. The screen is vertical, LCD direction is 0 degree.

Mode	Angle	Measured power	
	(degree)	5GHz-Ch120(dBm)	
		AUX	MAIN
Lid close	0	Standby	Standby
	10	Standby	Standby
	20	Standby	Standby
	30	Standby	Standby
Laptop	40	19.98	19.65
Lid close	35	Standby	Standby
	36	Standby	Standby
	37	Standby	Standby
	38	Standby	Standby
	39	Standby	Standby
Laptop	40	19.98	19.65
	41	19.98	19.65
	42	19.98	19.65
	43	19.98	19.65
	44	19.98	19.65
	45	19.98	19.65
	50	19.98	19.65
	60	19.98	19.65
	70	19.98	19.65
	80	19.98	19.65
	90	19.98	19.65
	100	19.98	19.65
	110	19.98	19.65
	120	19.98	19.65
	130	19.98	19.65
	140	19.98	19.65
	150	19.98	19.65
	160	19.98	19.65
Flat	170	11.87	11.73
	165	11.87	11.73
Laptop	160	19.98	19.65
Flat	161	11.87	11.73
	162	11.87	11.73
	163	11.87	11.73
	164	11.87	11.73
	165	11.87	11.73
	170	11.87	11.73
	180	11.87	11.73

Test Report No: 230606-01.TR01

The lid is rotating from 180 degrees to 0 degree. The screen is vertical, LCD direction to 0 degree.

Mode	Angle	Measured power	
	(degree)	5GHz-Ch120(dBm)	
		AUX	MAIN
Flat	180	11.87	11.73
	170	11.87	11.73
Laptop	160	19.98	19.65
Flat	165	11.87	11.73
	164	11.87	11.73
	163	11.87	11.73
	162	11.87	11.73
Laptop	161	11.87	11.73
	160	19.98	19.65
	159	19.98	19.65
	158	19.98	19.65
	157	19.98	19.65
	156	19.98	19.65
	155	19.98	19.65
	150	19.98	19.65
	140	19.98	19.65
	130	19.98	19.65
	120	19.98	19.65
	110	19.98	19.65
	100	19.98	19.65
	90	19.98	19.65
	80	19.98	19.65
	70	19.98	19.65
	60	19.98	19.65
	50	19.98	19.65
	40	19.98	19.65
Lid Close	30	Standby	Standby
Laptop	35	19.98	19.65
Lid Close	34	Standby	Standby
	33	Standby	Standby
	32	Standby	Standby
	31	Standby	Standby
	30	Standby	Standby
	20	Standby	Standby
	10	Standby	Standby
	0	Standby	Standby

B.2.2 LCD direction 90/270°

The lid is rotating from 0 to 180 degrees. The screen is vertical, LCD direction to 90 or 270 degrees for book mode. AIO mode is performed in flat with kickstand. The angle is 120 degrees.

Mode	Angle	Measured power	
	(degree)	5GHz-Ch120(dBm)	
		AUX	MAIN
Lid close	0	Standby	Standby
	10	Standby	Standby
	20	Standby	Standby
	30	Standby	Standby
Book	40	11.91	11.61
Lid close	35	Standby	Standby
	36	Standby	Standby
	37	Standby	Standby
	38	Standby	Standby
	39	Standby	Standby
Book	40	11.91	11.61
	41	11.91	11.61
	42	11.91	11.61
	43	11.91	11.61
	44	11.91	11.61
	45	11.91	11.61
	50	11.91	11.61
	60	11.91	11.61
	70	11.91	11.61
	80	11.91	11.61
	90	11.91	11.61
	100	11.91	11.61
	110	11.91	11.61
	120	11.91	11.61
	130	11.91	11.61
	140	11.91	11.61
	150	11.91	11.61
	160	11.91	11.61
AIO with kickstand at 120°	170	19.86	19.63
	165	19.86	19.63
Book	160	11.91	11.61
AIO with kickstand at 120°	161	19.86	19.63
	162	19.86	19.63
	163	19.86	19.63
	164	19.86	19.63
	165	19.86	19.63
	170	19.86	19.63
	180	19.86	19.63

Test Report No: 230606-01.TR01

The lid is rotating from 180 to 0 degrees. The screen is vertical, LCD direction to 90 or 270 degrees for book mode. AIO mode is performed in flat with kickstand. The angle is 120 degrees.

Mode	Angle	Measured power	
	(degree)	5GHz-Ch120(dBm)	
		AUX	MAIN
AIO with kickstand at 120°	180	19.86	19.63
	170	19.86	19.63
Book	160	11.91	11.61
AIO with kickstand at 120°	165	19.86	19.63
	164	19.86	19.63
	163	19.86	19.63
	162	19.86	19.63
	161	19.86	19.63
Book	160	11.91	11.61
	159	11.91	11.61
	158	11.91	11.61
	157	11.91	11.61
	156	11.91	11.61
	150	11.91	11.61
	140	11.91	11.61
	130	11.91	11.61
	120	11.91	11.61
	110	11.91	11.61
	100	11.91	11.61
	90	11.91	11.61
	80	11.91	11.61
	70	11.91	11.61
	60	11.91	11.61
	50	11.91	11.61
	40	11.91	11.61
Lid Close	30	Standby	Standby
Book	35	11.91	11.61
Lid Close	34	Standby	Standby
	33	Standby	Standby
	32	Standby	Standby
	31	Standby	Standby
	30	Standby	Standby
	20	Standby	Standby
	10	Standby	Standby
	0	Standby	Standby